



**Electromagnetic compatibility
and Radio spectrum Matters (ERM);**

Short Range Devices;

Road Transport and Traffic Telematics (RTTT);

Short range radar equipment operating in the 24 GHz range;

Part 1: Technical requirements and

methods of measurement

Reference

REN/ERM-TGSRR-056-1

Keywords

radar, radio, RTTT, SRD, testing

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2012.
All rights reserved.

DECTTM, PLUGTESTSTM, UMTSTM and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPPTM and LTETM are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	6
Foreword.....	6
1 Scope	7
2 References	7
2.1 Normative references	7
2.2 Informative references.....	8
3 Definitions, symbols and abbreviations	9
3.1 Definitions.....	9
3.2 Symbols.....	10
3.3 Abbreviations	11
4 Technical requirements specifications	12
4.1 Presentation of equipment for testing purposes.....	12
4.1.1 Choice of model for testing	12
4.2 Mechanical and electrical design.....	12
4.3 Auxiliary test equipment	12
4.4 Interpretation of the measurement results	12
5 Test conditions, power sources and ambient temperatures	13
5.1 Normal and extreme test conditions	13
5.2 External test power source.....	13
5.3 Normal test conditions.....	13
5.3.1 Normal temperature and humidity	13
5.3.2 Normal test power source	13
5.3.2.1 Mains voltage	13
5.3.2.2 Other power sources	13
5.4 Extreme test conditions	14
5.4.1 Extreme temperatures	14
5.4.1.1 Procedure for tests at extreme temperatures.....	14
5.4.1.2 Extreme temperature ranges.....	14
5.4.2 Extreme test source voltages.....	14
5.4.2.1 Mains voltage	14
5.4.2.2 Other power sources.....	14
6 General conditions.....	14
6.1 Test fixture	14
6.1.1 Requirements	14
6.1.2 Calibration	15
6.1.3 General requirements for RF cables.....	17
6.1.4 Shielded anechoic chamber.....	18
7 Methods of measurement and limits for transmitter parameters	19
7.1 Methods of measurement and limits for transmitters in the 22,000 GHz to 26,65 GHz band for type A and B	19
7.1.1 Permitted range of operating frequencies	19
7.1.1.1 Definition	19
7.1.1.2 Method of measurement.....	19
7.1.1.3 Limits	20
7.1.1.3.1 Limits for type A	20
7.1.1.3.2 Limits for type B	20
7.1.2 Maximum radiated average power density (e.i.r.p.)	20
7.1.2.1 Definition	20
7.1.2.2 Method of measurement.....	20
7.1.2.3 Limits for UWB maximum radiated average power density (e.i.r.p.) for type A.....	22
7.1.2.4 Limits for UWB maximum radiated average power density (e.i.r.p.) for type B.....	22
7.1.3 Maximum radiated peak power density (e.i.r.p.)	23

7.1.3.1	Definition	23
7.1.3.2	Method of measurement	23
7.1.3.3	Standard procedure and setup extensions	24
7.1.3.4	Limits for UWB maximum radiated peak power density (e.i.r.p.) for type A	24
7.1.3.5	Limits for UWB maximum radiated peak power density (e.i.r.p.) for type B	25
7.1.4	Methods of measurement and limits for emissions in the 24,05 GHz to 24,25 GHz band	26
7.1.4.1	Equivalent isotropically radiated power (e.i.r.p.)	26
7.1.4.1.1	Definition	26
7.1.4.1.2	Method of measurement	26
7.1.4.1.3	Limits	28
7.1.4.2	Permitted range of operating frequencies	28
7.1.4.2.1	Definition	28
7.1.4.2.2	Method of measurement for equipment not using FH modulation	28
7.1.4.2.3	Method of measurement for equipment using pulsed FH modulation	29
7.1.4.2.4	Limit	30
7.1.5	Vertical plane transmitter emissions in the 23,6 GHz to 24 GHz band	30
7.1.5.1	Definition	30
7.1.5.2	Measurement procedure	30
7.1.5.3	Vertical emission limits in the 23,6 GHz to 24,0 GHz band for type A	30
7.1.5.4	Emission limits for Type B	30
7.2	Radiated emissions in the non-operating-frequency range	31
7.2.1	Definition	31
7.2.2	Measuring receiver	31
7.2.3	Method of measurement for emissions in the non-operating frequency range	31
7.2.4	Limits	32
8	Methods of measurement and limits for receiver parameters	32
8.1	Receiver spurious emissions	32
8.1.1	Definition	32
8.1.2	Method of measurement - radiated spurious emissions	32
8.1.3	Limit	33
9	Measurement uncertainty	33
Annex A (normative):	Radiated measurements	35
A.1	Test sites and general arrangements for measurements involving the use of radiated fields	35
A.2	Guidance on the use of radiation test sites	35
A.2.1	Substitution antenna	35
A.3	Indoor test site using a fully anechoic RF chamber	35
A.3.1	Example of the construction of a shielded anechoic chamber	35
A.3.2	Influence of parasitic reflections in anechoic chambers	37
A.3.3	Calibration of the shielded RF anechoic chamber	37
Annex B (normative):	General description of measurement methods	38
B.1	Radiated measurements	38
B.2	Performance requirements for preamplifier and horn antenna	39
B.3	Measurement of the residual carrier	39
Annex C (informative):	Example of modulation schemes	40
C.1	Pseudo Noise Pulse Position Modulation (PN PPM)	40
C.1.1	Definition	40
C.1.2	Typical operation parameters	41
C.2	Pulsed FH (Pulsed Frequency Hopping)	41
C.2.1	Definition	41
C.2.2	Typical operation parameters	42
C.2.3	Additional requirements for pulsed FH equipment measurement	42
C.2.3.1	Pulsed FH modulation	42
C.2.3.2	Measurement requirements	42

C.3	PN-2-PSK (Pseudo noise binary coded phase shift keying).....	43
C.3.1	Definition	43
C.3.2	Typical operation parameters	44
Annex D (normative):	General description of Type A: Short range radar equipment operating in the range from 22,000 GHz to 26,65 GHz	45
Annex E (normative):	General description of Type B: Short range radar equipment operating in the range from 24,25 GHz to 26,65 GHz	46
Annex F (informative):	Typical antenna elevation pattern for a 26 GHz SRR in the passive band and the averaged elevation pattern above 30°	47
Annex G (normative):	Installation requirements of 24 GHz Short Range Radar (SRR) systems	48
G.1	Installation requirements for type A.....	48
G.2	Installation requirements for Type B.....	49
Annex H (informative):	Conversion of power density to e.i.r.p.....	50
H.1	Assumptions	50
H.2	Example.....	50
Annex I (informative):	Bibliography.....	51
History		52

iTech Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI EN 302 288-1 V1.6.1 \(2012-03\)](https://standards.iteh.ai/catalog/standards/etsi/c139f8a9-8810-49b1-b289-da5eba4e96be/etsi-en-302-288-1-v1-6-1-2012-03)

<https://standards.iteh.ai/catalog/standards/etsi/c139f8a9-8810-49b1-b289-da5eba4e96be/etsi-en-302-288-1-v1-6-1-2012-03>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This final draft European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the Vote phase of the ETSI standards Two-step Approval Procedure.

For non EU countries the present document may be used for regulatory (Type Approval) purposes.

Equipment compliant with the present document is intended for fitment into road vehicles, therefore it is subject to automotive EMC type approval and has to comply with Directive 95/54/EC [4]. For use on vehicles outside the scope of Directive 95/54/EC [4] compliance with an EMC directive/standard appropriate for that use is required.

The present document is part 1 of a multi-part deliverable covering Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices, Road Transport and Traffic Telematics (RTTT); Short range radar equipment operating in the 24 GHz range, as identified below:

Part 1: "Technical requirements and methods of measurement";

Part 2: "Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive".

ETSI EN 302 288-1 V1.6.1 (2012-03)

Proposed national transposition dates

Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa

1 Scope

The present document specifies the technical requirements and methods of measurement for Short Range Devices (SRD) working as UWB devices with at least 500 MHz bandwidth in the 22,000 GHz to 26,65 GHz frequency range intended for Road Transport and Traffic Telematics (RTTT) applications, such as automotive 24 GHz Short Range Radar (SRR) for e.g. obstacle detection, stop and go, blind spot detection, parking aid, backup aid, precrash and other automotive applications.

The present document covers transmitters intended to operate in a temporary frequency designation under the 24 GHz ECC decision CEPT/ECC/DEC/(04)10 [i.7], the EU Commission decision on 24 GHz SRR 2005/50/EC [i.1] and the amendment as presented in RSCOM11-07 21 [i.8].

The operating frequency range for intentional UWB emissions with at least 500 MHz bandwidth in the 22,000 GHz to 26,65 GHz range until 30th June 2013 as given in annex D and from 24,25 GHz to 26,65 GHz until 1st January 2018 as given in annex E. However, the date of 1 January 2018 will be extended by 4 years for automotive short-range radar equipment mounted on motor vehicles for which a type approval application has been submitted pursuant to Article 6(6) of Directive 2007/46/EC [6] and has been granted before 1 January 2018.

The present document applies to:

- a) Transmitters in the range from 22,000 GHz to 26,65 GHz operating as UWB devices over the specific bandwidth defined for the individual devices.
- b) Receivers operating in the range from 22,000 GHz to 26,65 GHz.
- c) Integrated transceivers.

The present document contains the technical characteristics and test methods for short range radar equipment fitted with integral antennas.

The present document does not necessarily include all the characteristics which may be required by a user, nor does it necessarily represent the optimum performance achievable.

The present document covers short range radar mobile applications. The present document covers only SRR equipment for road vehicles.

The present document complies with field limits for human exposure to electromagnetic fields as provided by the EC Recommendation 1999/519/EC [i.2] and the methods for compliance demonstration in EN 50371 [i.3].

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] CISPR 16 (parts 1-1, 1-4 and 1-5): "Specification for radio disturbance and immunity measuring apparatus and methods; Part 1: Radio disturbance and immunity measuring apparatus".
- [2] CEPT/ERC/REC 01-06: "Procedure for mutual recognition of type testing and type approval for radio equipment".