



**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
Short Range Devices;
Road Transport and Traffic Telematics (RTTT);
Short range radar equipment operating in the 24 GHz range;
Part 2: Harmonized EN covering the essential requirements of
article 3.2 of the R&TTE Directive**

Reference

REN/ERM-TGSRR-056-2

Keywords

radar, radio, regulation, RTTT, SRD, testing

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2012.
All rights reserved.

DECTTM, PLUGTESTSTM, UMTSTM and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPPTM and LTETM are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	5
Foreword.....	5
Introduction	5
1 Scope	6
2 References	6
2.1 Normative references	6
2.2 Informative references	7
3 Definitions, symbols and abbreviations	7
3.1 Definitions	7
3.2 Symbols	7
3.3 Abbreviations	7
4 Technical requirements specifications	8
4.1 Environmental conditions.....	8
4.1.1 Environmental profile	8
4.2 Conformance requirements	8
4.2.1 Transmitter requirements.....	8
4.2.1.1 Limits for transmitters in the range from 22 GHz to 26,65 GHz for type A and B.....	8
4.2.1.1.1 Permitted range of operating frequencies for type A.....	8
4.2.1.1.2 Permitted range of operating frequencies for type B.....	8
4.2.1.1.3 Maximum radiated average power density (e.i.r.p.) for type A.....	8
4.2.1.1.4 Maximum radiated average power density (e.i.r.p.) for type B.....	8
4.2.1.1.5 Maximum radiated peak power density (e.i.r.p.) for type A.....	8
4.2.1.1.6 Maximum radiated peak power density (e.i.r.p.) for type B.....	8
4.2.1.2 Limits for transmitters in the range from 24,05 GHz to 24,25 GHz	8
4.2.1.2.1 Permitted range of operating frequencies	8
4.2.1.2.2 Limit for transmitted peak power (e.i.r.p.) in the 24,05 GHz to 24,25 GHz SRD band	9
4.2.1.3 Vertical plane emission limits in the range from 23,6 GHz to 24,0 GHz.....	9
4.2.1.4 Emission limits in the range from 24,05 GHz to 26,65 GHz	9
4.2.1.5 Transmitter emissions in the non-operating-frequency range	9
4.2.2 Receiver requirements	9
4.2.2.1 Receiver spurious emissions	9
4.2.3 Installation requirements.....	9
5 Testing for compliance with technical requirements.....	9
5.1 Environmental conditions for testing	9
5.2 Essential radio test suites.....	9
5.2.1 Transmitter test suites	9
5.2.1.1 Transmitters operating in the 22 GHz to 26,65 GHz band.....	9
5.2.1.1.1 Permitted range of operating frequencies	9
5.2.1.1.2 Maximum radiated average power density (e.i.r.p.)	9
5.2.1.1.3 Maximum radiated peak power density (e.i.r.p.).....	10
5.2.1.2 Transmitters operating in the 24,050 GHz to 24,250 GHz band.....	10
5.2.1.2.1 Permitted range of operating frequencies	10
5.2.1.2.2 Equivalent isotropically radiated power (e.i.r.p.)	10
5.2.1.3 Vertical plane transmitter emissions	10
5.2.1.4 Transmitter emissions in the Radiated emissions in the non-operating-frequency range	10
5.2.2 Receiver test suites.....	10
5.2.2.1 Receiver spurious emissions	10
5.2.3 Installation requirements.....	10
5.3 Interpretation of results and measurement uncertainty.....	10
Annex A (normative): HS Requirements and conformance Test specifications Table (HS-RTT).....	12