

**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
Short Range Devices (SRD);
Level Probing Radar (LPR) equipment operating in the
frequency ranges 6 GHz to 8,5 GHz, 24,05 GHz to 26,5 GHz,
57 GHz to 64 GHz, 75 GHz to 85 GHz;
Part 1: Technical characteristics and test methods**

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI EN 302 729-1 V1.1.2 \(2011-03\)](https://standards.iteh.ai/catalog/standards/etsi/4ebadd63-3f43-4b11-9c65-eb01ff099ac2/etsi-en-302-729-1-v1-1-2-2011-03)

<https://standards.iteh.ai/catalog/standards/etsi/4ebadd63-3f43-4b11-9c65-eb01ff099ac2/etsi-en-302-729-1-v1-1-2-2011-03>



Reference

DEN/ERM-TGTLPR-0114-1

Keywords

EHF, radar, regulation, SHF, short range, SRD,
testing, UWB

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2011.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTE™ is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	6
Foreword.....	6
Introduction	6
1 Scope	8
2 References	8
2.1 Normative references	9
2.2 Informative references	9
3 Definitions, symbols and abbreviations	10
3.1 Definitions	10
3.2 Symbols.....	10
3.3 Abbreviations	11
4 General requirements specifications	11
4.1 Presentation of equipment for testing purposes.....	11
4.2 Choice of model for testing	12
4.3 Mechanical and electrical design.....	12
4.3.1 Marking (equipment identification).....	12
4.3.1.1 Equipment identification	12
4.4 Auxiliary test equipment and product information.....	12
4.5 General requirements for RF cables	13
4.6 RF waveguides	13
4.6.1 Wave Guide Attenuators.....	14
4.7 External harmonic mixers	14
4.7.1 Introduction.....	14
4.7.2 Signal identification.....	15
4.7.3 Measurement hints	15
4.8 Preamplifier	16
4.9 Interpretation of the measurement results	16
4.9.1 Conversion loss data and measurement uncertainty	17
4.10 Other emissions from device circuitry.....	18
5 Test conditions, power sources and ambient temperatures	18
5.1 Normal test conditions.....	18
5.2 External test power source.....	18
5.3 Normal test conditions.....	19
5.3.1 Normal temperature and humidity	19
5.3.2 Normal test power source	19
5.3.2.1 Mains voltage	19
5.3.2.2 Regulated lead-acid battery power source.....	19
5.3.2.3 Other power sources.....	19
6 General conditions.....	19
6.1 Radiated measurement arrangements	19
6.2 Conducted measurement arrangements	20
6.3 Shielded anechoic chamber	20
6.4 Measuring receiver	21
7 LPR methods of measurement and limits.....	21
7.1 Frequency band of operation	21
7.1.1 Definition.....	21
7.1.2 Method of measurement	22
7.1.3 Limits.....	24
7.2 Maximum value of mean power spectral density (within main beam).....	24
7.2.1 Definition.....	24
7.2.2 Method of measurement	24

7.2.3	Limits.....	26
7.3	Maximum value of peak power	27
7.3.1	Definition.....	27
7.3.2	Method of measurement	27
7.3.3	Limits.....	29
7.4	LPR antenna characteristics	29
7.4.1	Definition.....	29
7.4.2	Method of measurement	29
7.4.3	Limits.....	31
7.5	Range of modulation parameters.....	31
7.6	Other Emissions (OE)	31
7.6.1	Definition.....	31
7.6.2	Method of measurement	31
7.6.3	Limits.....	32
7.7	Mitigation techniques.....	33
7.7.1	Shielding effects	33
7.7.2	Frequency domain mitigation	33
7.7.3	Activity Factor (AF)	34
7.7.4	Thermal radiation.....	34
7.7.5	Adaptive Power Control (APC).....	34
7.7.5.1	Definition and description of the APC	34
7.7.5.2	Method of measurement for APC	34
7.7.5.3	APC Range Limits	36
7.7.6	Equivalent mitigation techniques.....	36
8	Methods of measurement and limits for receiver parameters.....	36
8.1	Receiver spurious emissions.....	36
Annex A (normative):	Radiated measurement.....	37
A.1	Test sites and general arrangements for measurements involving the use of radiated fields.....	37
A.1.1	Anechoic Chamber	37
A.1.2	Anechoic Chamber with a conductive ground plane.....	38
A.1.3	Open Area Test Site (OATS)	39
A.1.4	Minimum requirements for test sites for measurements above 18 GHz.....	40
A.1.5	Test antenna.....	42
A.1.6	Substitution antenna	42
A.1.7	Measuring antenna	42
A.2	Guidance on the use of radiation test sites	42
A.2.1	Verification of the test site	42
A.2.2	Preparation of the EUT.....	43
A.2.3	Power supplies to the EUT	43
A.2.4	Range length.....	43
A.2.5	Site preparation	44
A.3	Coupling of signals.....	44
A.3.1	General	44
A.4	Standard test methods.....	44
A.4.1	Calibrated setup.....	44
A.4.2	Substitution method.....	45
Annex B (normative):	Conducted measurements	47
Annex C (informative):	Installation of Level Probing Radar (LPR) Equipment in the proximity of Radio Astronomy sites.....	48
Annex D (informative):	Measurement antenna and preamplifier specifications	49
Annex E (informative):	Practical test distances for accurate measurements	50
E.1	Introduction	50
E.2	Conventional near-field measurements distance limit	50

Annex F (normative):	Range of modulation parameters	51
F.1	Pulse modulation	51
F.1.1	Definition	51
F.1.2	Operating parameters	52
F.2	Frequency modulated continuous wave	52
F.2.1	Definition	52
F.2.2	Operating parameters	53
Annex G (informative):	Atmospheric absorptions and material dependent attenuations.....	54
G.1	Atmospheric absorptions.....	54
G.2	Material dependent attenuations.....	56
History		58

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ETSI EN 302 729-1 V1.1.2 (2011-03)

<https://standards.iteh.ai/catalog/standards/etsi/4ebadd63-3f43-4b11-9c65-eb01ff099ac2/etsi-en-302-729-1-v1-1-2-2011-03>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This final draft European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the Vote phase of the ETSI standards Two-step Approval Procedure.

For non-EU countries, the present document may be used for regulatory (Type Approval) purposes.

The present document is part 1 of a multi-part deliverable covering Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD); Level Probing Radar (LPR) equipment operating in the frequency ranges 6 GHz to 8,5 GHz, 24,05 GHz to 26,5 GHz, 57 GHz to 64 GHz, 75 GHz to 85 GHz, as identified below:

Part 1: "Technical characteristics and test methods";

Part 2: "Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive".

Proposed national transposition dates

Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa

Introduction

Clauses 1 and 3 provide a general description on the types of equipment covered by the present document and the definitions and abbreviations used.

Clause 2 provides the information on normative and informative reference documentation.

Clause 4 provides a guide as to the number of samples required in order that tests may be carried out, and any markings on the equipment which the provider should provide. It also includes the general testing requirements and gives the maximum measurement uncertainty values.

Clauses 5 and 6 give guidance on the test and general conditions for testing of the LPR device.

Clause 7 specifies the LPR spectrum utilization parameters which are required to be measured. The clauses provide details on how the equipment should be tested and the conditions which should be applied. It also includes information on applicable interference mitigation techniques for LPR.

- Annex A (normative) provides specifications concerning radiated measurements.
- Annex B (normative) provides specifications concerning conducted measurements.
- Annex C (informative) provides specifications concerning the installation requirements for LPR.
- Annex D (informative) covers information on recommended Measurement antenna and preamplifier specifications.
- Annex E (informative) contains information on the practical test distances for accurate measurements.
- Annex F (normative) provides the range of modulation schemes for LPR.
- Annex G (informative) contains information on atmospheric absorptions and material dependent attenuations In the frequency range between 40 GHz and 246 GHz.
- Annex H (informative) Bibliography covers other supplementary information.

Test and measurement limitations

The ERA report 2006-0713 [i.7] has shown that there are practical limitations on measurements of RF radiated emissions. The minimum radiated levels that can be practically measured in the lower GHz frequency range by using a radiated measurement setup with a horn antenna and pre-amplifier are typically in the range of about -70 dBm/MHz to -75 dBm/MHz (e.i.r.p.) to have sufficient confidence in the measured result (i.e. EUT signal should be at least 6 dB above the noise floor of the spectrum analyser and the measurement is performed under far-field conditions at a onemetre distance).

The present document therefore recognizes these difficulties and provides a series of radiated test methods suitable for the different LPR technologies.

ETSI EN 302 729-1 V1.1.2 (2011-03)

<https://standards.iteh.ai/catalog/standards/etsi/4ebadd63-3f43-4b11-9c65-eb01ff099ac2/etsi-en-302-729-1-v1-1-2-2011-03>