

ETSI EN 302 769 V1.2.1 (2011-04)

European Standard

Digital Video Broadcasting (DVB); Frame structure channel coding and modulation for a second generation digital transmission system for cable systems (DVB-C2)



EBU-UER

iTeh Standards
(<https://standards.itih.ai>)
Document Preview

[ETSI EN 302 769 V1.2.1 \(2011-04\)](https://standards.itih.ai/catalog/standards/etsi/7f26a2fd-8e64-4f18-a5f0-fdf5d493b136/etsi-en-302-769-v1-2-1-2011-04)

<https://standards.itih.ai/catalog/standards/etsi/7f26a2fd-8e64-4f18-a5f0-fdf5d493b136/etsi-en-302-769-v1-2-1-2011-04>

DVB
Digital Video
Broadcasting



Reference

REN/JTC-DVB-288

Keywordsaudio, broadcasting, cable, data, digital, DVB,
MPEG, TV, video**ETSI**650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iteh Standards
(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2011.

© European Broadcasting Union 2011.

All rights reserved.

DECTTM, **PLUGTESTS**TM, **UMTS**TM, **TIPHON**TM, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPPTM is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTETM is a Trade Mark of ETSI currently being registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	6
Foreword.....	6
1 Scope	7
2 References	8
2.1 Normative references	8
2.2 Informative references.....	8
3 Definitions, symbols and abbreviations	9
3.1 Definitions.....	9
3.2 Symbols.....	11
3.3 Abbreviations	14
4 DVB-C2 System architecture	16
4.1 System overview	16
4.2 System architecture	16
4.3 Target performance	19
5 Input processing	19
5.1 Mode adaptation.....	19
5.1.1 Input Formats.....	20
5.1.2 Input Interface.....	20
5.1.3 Input Stream Synchronization (Optional).....	21
5.1.4 Null Packet Deletion (optional, for TS only, NM and HEM).....	21
5.1.5 CRC-8 encoding (for GFPS and TS, NM only).....	22
5.1.6 Baseband Header (BBHeader) insertion.....	22
5.1.7 Mode adaptation sub-system output stream formats.....	24
5.2 Stream adaptation.....	27
5.2.1 Scheduler	27
5.2.2 Padding	27
5.2.3 BB scrambling	27
6 Bit-interleaved coding and modulation	28
6.1 FEC encoding.....	28
6.1.1 Outer encoding (BCH).....	29
6.1.2 Inner encoding (LDPC)	30
6.1.2.1 Inner coding for normal FECFrame	30
6.1.2.2 Inner coding for short FECFrame	32
6.1.3 Bit Interleaver	32
6.2 Mapping bits onto constellations.....	34
6.2.1 Bit to cell word demultiplexer	35
6.2.2 Cell word mapping into I/Q constellations	38
7 Data Slice Packet Generation.....	45
7.1 Data Slice Packets for Data Slice Type 1	45
7.2 Data Slice Packets for Data Slice Type 2	45
7.2.1 FECFrame header signalling data.....	46
7.2.2 Coding of the FECFrame header	47
7.2.2.1 Error Coding	48
7.2.2.2 Cyclic Delay.....	48
7.2.2.3 Scrambling of the lower branch	48
7.2.3 Mapping onto QAM constellations.....	49
7.2.3.1 Robust FECFrame header	49
7.2.3.2 High efficiency FECFrame header.....	49
7.2.4 Mapping of the XFECFrame cells	49
7.2.5 Length of the Data Slice Packet for Data Slice Type 2.....	49
7.2.6 Stuffing Data Slice Packets.....	50

8	Generation, coding and modulation of Layer 1 part 2 signalling.....	51
8.1	Overview	51
8.2	Preamble Header	51
8.3	L1 signalling part 2 data.....	53
8.3.1	L1 block padding	58
8.3.2	CRC for the L1 signalling part 2.....	58
8.3.3	L1 padding	58
8.4	Modulation and error correction coding of the L1 part 2 data.....	58
8.4.1	Overview	58
8.4.2	Parameters for FEC encoding of L1 part 2 data.....	60
8.4.3	FEC Encoding.....	62
8.4.3.1	Zero padding of BCH information bits	62
8.4.3.2	BCH encoding.....	64
8.4.3.3	LDPC encoding.....	64
8.4.3.4	Puncturing of LDPC parity bits.....	64
8.4.3.5	Removal of zero padding bits.....	65
8.4.3.6	Bit interleaving for L1 signalling part 2.....	65
8.4.4	Mapping bits onto constellations	66
8.4.4.1	Demultiplexing of L1 signalling part 2	66
8.4.4.2	Mapping onto QAM constellations	66
8.5	Time interleaving of L1 signalling part 2 data	67
9	Frame Builder.....	69
9.1	C2 Frame structure	69
9.1.1	Duration of the C2 Frame	69
9.2	Pilot Reference Sequence	70
9.2.1	Data Scrambling Sequence	70
9.2.2	Pilot Scrambling Sequence	70
9.2.3	Pilot Reference Sequence	71
9.3	Preamble Symbol	71
9.3.1	Preamble Symbol overview	71
9.3.2	Frequency Interleaving	71
9.3.3	Pilot insertion.....	72
9.3.3.1	Locations of the preamble pilots	72
9.3.3.2	Amplitude and modulation of the preamble pilots	72
9.3.4	Mapping and scrambling of the signalling data	73
9.3.5	Notches within Preamble Symbols	73
9.3.5.1	Narrowband Notches.....	73
9.3.5.2	Broadband Notches	74
9.4	Data Slice generation.....	74
9.4.1	Location of Data Slices.....	74
9.4.1.1	Start and end OFDM carrier of Data Slices	74
9.4.1.2	Maximum width of Data Slices.....	74
9.4.1.3	Minimum width of Data Slices	75
9.4.1.4	Notches within Data Slices	75
9.4.2	Number of payload cells in Data Slice.....	75
9.4.3	Mapping of the Data Slice Packets	75
9.4.4	Time Interleaving.....	76
9.4.5	Frequency Interleaving	80
9.5	Stuffing Data Slices	81
9.6	Pilot Insertion	81
9.6.1	Introduction.....	81
9.6.2	Scattered pilot insertion	82
9.6.2.1	Locations of the scattered pilots	82
9.6.2.2	Amplitudes of the scattered pilots	82
9.6.2.3	Modulation of the scattered pilots	82
9.6.3	Continual pilot insertion	82
9.6.3.1	Locations of the continual pilots	83
9.6.3.2	Amplitudes of the Continual Pilots	83
9.6.3.3	Modulation of the Continual Pilots	83
9.6.4	Edge pilot insertion	83
9.6.4.1	Locations of the edge pilots	83

9.6.4.2	Amplitudes of the Edge Pilots.....	84
9.6.4.3	Modulation of the Edge Pilots.....	84
9.7	Dummy carrier reservation.....	85
10	OFDM generation	85
10.1	IFFT - OFDM Modulation	85
10.2	Guard interval insertion.....	87
10.3	Spectrum characteristics.....	87
Annex A (normative):	Addresses of parity bit accumulators for Nldpc = 64 800	89
Annex B (normative):	Addresses of parity bit accumulators for Nldpc = 16 200	95
Annex C (normative):	Input stream synchronizer	97
Annex D (normative):	Input Remultiplexing Subsystem: Splitting of input MPEG-2 Transport Streams into Data PLPs, generation of a Common PLP of a group of PLPs and insertion of Null Packets into Transport Streams	99
D.1	Overview	99
D.2	Splitting of a group of input TSs into TSPSS streams and a TSPSC stream	100
D.2.1	General	100
D.2.2	Extraction of the Common PLP from a group of TS.....	100
D.2.3	Insertion of additional Null Packets into TSPSS.....	101
D.3	Receiver Implementation Considerations.....	102
D.3.1	Recombination of TSPSS and TSPSC in a receiver	102
Annex E (normative):	Calculation of the CRC word	104
Annex F (normative):	Bundling of PLPs	105
Annex G (informative):	Transport Stream regeneration and clock recovery using ISCR.....	106
Annex H (informative):	Pilot patterns	107
Annex I (informative):	Bibliography.....	110
History	111

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (EN) has been produced by Joint Technical Committee (JTC) Broadcast of the European Broadcasting Union (EBU), Comité Européen de Normalisation ELECTrotechnique (CENELEC) and the European Telecommunications Standards Institute (ETSI).

NOTE: The EBU/ETSI JTC Broadcast was established in 1990 to co-ordinate the drafting of standards in the specific field of broadcasting and related fields. Since 1995 the JTC Broadcast became a tripartite body by including in the Memorandum of Understanding also CENELEC, which is responsible for the standardization of radio and television receivers. The EBU is a professional association of broadcasting organizations whose work includes the co-ordination of its members' activities in the technical, legal, programme-making and programme-exchange domains. The EBU has active members in about 60 countries in the European broadcasting area; its headquarters is in Geneva.

European Broadcasting Union
CH-1218 GRAND SACONNEX (Geneva)
Switzerland
Tel: +41 22 717 21 11
Fax: +41 22 717 24 81

The Digital Video Broadcasting Project (DVB) is an industry-led consortium of broadcasters, manufacturers, network operators, software developers, regulatory bodies, content owners and others committed to designing global standards for the delivery of digital television and data services. DVB fosters market driven solutions that meet the needs and economic circumstances of broadcast industry stakeholders and consumers. DVB standards cover all aspects of digital television from transmission through interfacing, conditional access and interactivity for digital video, audio and data. The consortium came together in 1993 to provide global standardisation, interoperability and future proof specifications.

National transposition dates

Date of adoption of this EN:	18 April 2011
Date of latest announcement of this EN (doa):	31 July 2011
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 January 2012
Date of withdrawal of any conflicting National Standard (dow):	31 January 2012

1 Scope

The present document describes a second generation baseline transmission system for digital television broadcasting via Hybrid Fibre Coax (HFC) cable networks and Master Antenna Television (MATV) installations. It specifies the channel coding, modulation and lower layer signalling protocol system intended for the provision of digital television services and generic data streams.

The scope is as follows:

- it gives a general description of the Baseline System for digital cable TV;
- it specifies the digital signal processing in order to establish compatibility between pieces of equipment developed by different manufacturers. This is achieved by describing in detail the signal processing at the transmitting side, while the processing at the receiving side is left open to individual implementations. However, for the purpose of securing interoperability it is necessary in this text to refer to certain implementation aspects of the receiving end.

DVB-C [i.4] was introduced as a European Norm in 1994. It specifies single carrier QAM modulation and Reed-Solomon channel coding and is used today by many cable operators worldwide for television and data broadcasting as well as for forward channel transmission of the Data Over Cable System defined in [i.7].

Since 1994 enhanced digital transmission technologies have evolved somewhat:

- New channel coding schemes, combined with higher order modulation, promise more powerful alternatives to the DVB-C coding and modulation schemes. The result is a capacity gain in the order of 30 % at a given cable channel bandwidth and CATV network performance.
- Variable Coding and Modulation (VCM) may be applied to provide different levels of error protection to different services (e.g. SDTV and HDTV, audio, multimedia).
- In the case of interactive and point-to-point applications, the VCM functionality may be combined with the use of return channels, to achieve Adaptive Coding and Modulation (ACM). This technique provides more exact channel protection and dynamic link adaptation to propagation conditions, targeting each individual receiving terminal.
- DVB-C is strictly focused on a unique data format, the MPEG Transport Stream (ISO/IEC 13818-1 [i.1] or a reference to it). Extended flexibility to cope with other input data formats (such as multiple Transport Streams, or generic data formats) is now possible without significant complexity increase.

The present document defines a "second generation" modulation and channel coding system (denoted the "C2 System" or "DVB-C2" for the purposes of the present document) to make use of the improvements listed above. DVB-C2 is a single, very flexible standard, covering a variety of applications by cable, as described below. It is characterized by:

- a flexible input stream adapter, suitable for operation with single and multiple input streams of various formats (packetized or continuous);
- a powerful FEC system based on LDPC (Low-Density Parity Check) codes concatenated with BCH (Bose Chaudhuri Hocquenghem) codes, allowing Quasi Error Free operation close to the Shannon limit, depending on the transmission mode (AWGN channel, modulation constrained Shannon limit);
- a wide range of code rates (from 2/3 up to 9/10); 5 constellations, ranging in spectrum efficiency from 1 to 10,8 bit/s/Hz, optimized for operation in cable networks;
- Adaptive Coding and Modulation (ACM) functionality, optimizing channel coding and modulation on a frame-by-frame basis.