

**Broadband Wireless Access Systems (BWA) in the
3 400 MHz to 3 800 MHz frequency band;
Base Stations;
Harmonized EN covering the essential requirements
of article 3.2 of the R&TTE Directive**

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI EN 302 774 V1.1.1 \(2011-05\)](https://standards.iteh.ai/catalog/standards/etsi/5e75a9a9-c011-43e9-8db9-469beafeaebf/etsi-en-302-774-v1-1-1-2011-05)

<https://standards.iteh.ai/catalog/standards/etsi/5e75a9a9-c011-43e9-8db9-469beafeaebf/etsi-en-302-774-v1-1-1-2011-05>



ReferenceDEN/BRAN-0060004

Keywords

base station, radio

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iteh Standards
(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2010.
All rights reserved.

DECTTM, **PLUGTESTS**TM, **UMTS**TM, **TIPHON**TM, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPPTM is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTETM is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	5
Foreword.....	5
Introduction	5
1 Scope	6
2 References	6
2.1 Normative references	6
2.2 Informative references.....	6
3 Definitions, symbols and abbreviations	7
3.1 Definitions.....	7
3.2 Symbols.....	7
3.3 Abbreviations	7
4 Essential requirements specification	8
4.1 Environmental profile.....	8
4.2 Conformance requirements	8
4.2.1 Introduction.....	8
4.2.2 Transmitter out of band emissions	8
4.2.2.1 Definition	8
4.2.2.2 Limits	8
4.2.3 Transmitter Adjacent Channel Leakage power Ratio (ACLR)	9
4.2.3.1 Definition	9
4.2.3.2 Limits	10
4.2.4 Transmitter spurious emissions.....	10
4.2.4.1 Definition	10
4.2.4.2 Limits	10
4.2.5 Maximum output power accuracy	10
4.2.5.1 Definition	10
4.2.5.2 Limits	11
4.2.6 Transmitter intermodulation attenuation.....	11
4.2.6.1 Definition	11
4.2.6.2 Limits	11
4.2.7 Receiver spurious emissions	11
4.2.7.1 Definition	11
4.2.7.2 Limits	11
4.2.8 Receiver adjacent channel rejection (ACR).....	11
4.2.8.1 Definition	11
4.2.8.2 Limits	11
4.2.9 Receiver blocking.....	12
4.2.9.1 Definition	12
4.2.9.2 Limits	12
4.2.10 Receiver intermodulation response rejection	12
4.2.10.1 Definition and applicability.....	12
4.2.10.2 Limits	12
5 Testing for compliance with technical requirements.....	13
5.1 Environmental conditions for testing	13
5.2 Product information.....	13
5.3 Interpretation of the measurement results	13
5.4 Essential radio test suites.....	14
5.4.1 Spectrum emission mask	14
5.4.1.1 Test Conditions	14
5.4.1.2 Test Setup.....	15
5.4.1.3 Test Procedure.....	15
5.4.2 Transmitter Adjacent Channel Leakage power Ratio (ACLR).....	15
5.4.2.1 Test Conditions	15

5.4.2.2	Test Setup.....	16
5.4.2.3	Test Procedure.....	16
5.4.3	Transmitter spurious emissions.....	17
5.4.3.1	Test Conditions	17
5.4.3.2	Test Setup.....	17
5.4.3.3	Test Procedure.....	17
5.4.4	Maximum output power accuracy	18
5.4.4.1	Test Conditions	18
5.4.4.2	Test Setup.....	18
5.4.4.3	Test Procedure.....	19
5.4.5	Transmitter Intermodulation attenuation	19
5.4.5.1	Test Conditions	19
5.4.5.2	Test Setup.....	20
5.4.5.3	Test Procedure.....	20
5.4.6	Receiver spurious emissions	20
5.4.6.1	Test Conditions	20
5.4.6.2	Test Setup.....	21
5.4.6.3	Test Procedure.....	21
5.4.7	Receiver adjacent channel rejection.....	22
5.4.7.1	Test Conditions	22
5.4.7.2	Test Setup.....	22
5.4.7.3	Test procedure.....	23
5.4.8	Receiver blocking	23
5.4.8.1	Test Conditions	23
5.4.8.2	Test Setup.....	24
5.4.8.3	Test Procedure.....	24
5.4.9	Receiver intermodulation response rejection	25
5.4.9.1	Test Conditions	25
5.4.9.2	Test Setup.....	25
5.4.9.3	Test Procedure.....	25
Annex A (normative):	HS Requirements and conformance Test specifications Table (HS-RTT).....	27
Annex B (informative):	The EN title in the official languages	29
History	30	30

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonized European Standard (Telecommunications series) has been produced by ETSI Technical Committee Broadband Radio Access Networks (BRAN), and is now submitted for the Public Enquiry phase of the ETSI standards Two-step Approval Procedure.

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Council Directive 98/34/EC (as amended) [i.2] laying down a procedure for the provision of information in the field of technical standards and regulations.

The present document is intended to become a Harmonized Standard, the reference of which will be published in the Official Journal of the European Communities referencing the Directive 1999/5/EC [i.1] of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity ("the R&TTE Directive").

The requirements relevant to Directive 1999/5/EC [i.1] are summarised in annex A.

Proposed national transposition dates

Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive [i.1]. The modular structure is shown in EG 201 399 [i.3].

The present document is intended to provide a smooth transition period for the introduction of BWA systems in this band, which shall end on 31 December 2013. Due to the fact that the sub-band 3 400 MHz to 3 600 MHz was also identified for IMT systems, it is expected that in version V1.2.1 of the present document the ACLR specification for this sub-band, because of its mobile use, will be aligned with the tighter ACLR value of -44,2 dB required for the mobile use, to be specified in EN 301 908 [i.9] for IMT Base Stations operating in the frequency range 3 400 MHz to 3 600 MHz. It is also expected that this first version will be withdrawn after 31 December 2013, being superseded by EN 302 774 (V1.2.1).