

**VHF air-ground and air-air Digital Link (VDL)
Mode 4 radio equipment;
Technical characteristics and methods of measurement
for aeronautical mobile (airborne) equipment;
Part 2: General description and data link layer**

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI EN 302 842-2 V1.3.1 \(2011-09\)](https://standards.iteh.ai/catalog/standards/etsi/2c263922-232b-4935-81a4-f8eb940b1ecf/etsi-en-302-842-2-v1-3-1-2011-09)

<https://standards.iteh.ai/catalog/standards/etsi/2c263922-232b-4935-81a4-f8eb940b1ecf/etsi-en-302-842-2-v1-3-1-2011-09>



Reference

REN/AERO-00007-2

Keywords

aeronautical, digital, radio, testing, VHF

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2011.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	8
Foreword.....	8
Introduction	9
1 Scope	10
2 References	12
2.1 Normative references	12
2.2 Informative references.....	13
3 Definitions and abbreviations.....	13
3.1 Definitions.....	13
3.1.1 Basic reference model definitions.....	13
3.1.2 Service conventions definitions	13
3.1.3 General definitions.....	13
3.1.4 Definition of bit order	17
3.2 Abbreviations	17
4 General description of VDL Mode 4 mobile station link layer	18
4.1 Overview of VDL Mode 4	18
4.1.1 Void	19
4.1.2 Relationship to OSI reference model	19
4.1.3 VDL Mode 4 services	21
4.1.4 ADS-B function	21
4.1.5 Operational scenarios.....	22
4.1.6 VDL Mode 4 fundamentals	22
4.1.7 Possible configuration of airborne equipment	23
4.1.8 Classes of equipment	25
4.1.9 Transceiver cross-links	25
4.1.10 Overall structure of specifications for VDL Mode 4	25
4.1.11 Equipment performance verification	27
5 Minimum performance specification under standard test conditions.....	28
5.1 MAC sublayer	28
5.1.1 Services.....	28
5.1.2 MAC sublayer services	28
5.1.3 MAC sublayer parameters	28
5.1.3.1 General	28
5.1.3.2 Parameter M1 (number of slots per superframe).....	29
5.1.3.3 Parameter M2_inc and M2_limit (MAC layer control parameters for network entry)	29
5.1.3.4 Inspection of m2 filter following transceiver failure.....	30
5.1.4 Time synchronization	30
5.1.4.1 Primary	30
5.1.4.2 Secondary.....	30
5.1.4.3 Alignment to UTC second	31
5.1.4.4 Data quality level	31
5.1.5 Slot idle/busy notification.....	31
5.1.5.1 Slot idle detection.....	31
5.1.5.2 Slot busy detection	31
5.1.5.3 Slot occupied detection	31
5.1.5.4 Signal level indication.....	31
5.1.6 Transmission processing.....	32
5.1.7 Received transmission processing	32
5.2 VSS sublayer	32
5.2.1 Services.....	33
5.2.1a Multiple access	33
5.2.1.1 Error detection.....	33
5.2.1.2 Channel congestion	33

5.2.2	Burst format	34
5.2.2.1	VSS burst structure	34
5.2.2.2	Version number	35
5.2.2.3	Source address	35
5.2.2.4	Message ID	35
5.2.2.5	Information field	36
5.2.2.6	Reservation fields	36
5.2.2.7	Autonomous/directed flag	36
5.2.3	VSS sublayer parameters	37
5.2.3.1	General	37
5.2.3.2	Parameter VS1 (number of ground quarantined slots)	37
5.2.3.3	Parameter VS2 (minimum CCI performance)	38
5.2.3.4	Parameter VS4 (quarantine slot re-use range)	38
5.2.3.5	Parameter VS5 (maximum burst length)	38
5.2.4	VSS quality of service parameters	39
5.2.4.1	General	39
5.2.4.2	Parameter Q1 (priority)	39
5.2.4.3	Parameters Q2a to Q2d (slot selection range constraint for level n)	40
5.2.4.4	Parameter Q3 (replace queued data)	40
5.2.4.5	Parameter Q4 (number of available slots)	41
5.2.5	Received transmission processing	41
5.2.6	Reserved access protocol specification	42
5.2.6.1	Reservation table	42
5.2.6.2	Selecting slots for transmission or reservation	43
5.2.6.3	Reserved transmissions	44
5.2.6.4	Reservation conflicts	45
5.2.6.5	Transmission conflicts for mobile stations	45
5.2.7	Random access protocol specification	46
5.2.7.1	General	46
5.2.7.2	Random access parameters	46
5.2.7.3	Random access procedures	48
5.2.8	Void	49
5.2.9	Null reservation protocol specification	49
5.2.9.1	Null reservation burst format	49
5.2.10	Periodic broadcast protocol specification	49
5.2.10.1	Periodic broadcast reservation burst format	49
5.2.10.2	Periodic broadcast timers	50
5.2.10.3	Periodic broadcast parameters	50
5.2.10.4	Periodic broadcast reception procedures	51
5.2.10.5	Periodic broadcast transmission procedures	52
5.2.11	Incremental broadcast protocol specification	55
5.2.11.1	Incremental broadcast reservation burst format	55
5.2.11.2	Incremental broadcast parameters	55
5.2.11.3	Incremental broadcast reception procedures	56
5.2.11.4	Incremental broadcast transmission procedures	56
5.2.12	Combined periodic broadcast and incremental broadcast protocol specification	57
5.2.12.1	Combined periodic broadcast and incremental broadcast reservation burst	57
5.2.13	Big negative dither (BND) broadcast protocol specifications	57
5.2.13.1	BND reservation burst format	57
5.2.13.2	BND broadcast parameters	58
5.2.13.3	BND broadcast reception procedures	58
5.2.13.4	BND broadcast transmission procedures	58
5.2.14	Unicast request protocol specification	58
5.2.14.1	Unicast request reservation burst format	58
5.2.14.1a	Unicast request parameters	59
5.2.14.2	Unicast request reception procedures	60
5.2.14.3	Unicast request transmission procedures	61
5.2.15	Information transfer request protocol specification	61
5.2.15.1	Information transfer request reservation burst format	61
5.2.15.2	Information transfer request reception procedures	63
5.2.16	Directed request protocol specification	63
5.2.16.1	Directed request reservation burst format	63

5.2.16.2	Directed request parameters	66
5.2.16.3	Directed request reception procedures	67
5.2.16.4	Directed request transmission procedures	68
5.2.16.5	Directed request response procedures	69
5.2.17	Block reservation protocols specification	70
5.2.17.1	Superframe block reservation burst format	70
5.2.17.2	Second frame block reservation burst format	71
5.2.17.3	Void	72
5.2.17.4	Superframe block reservation reception procedures	72
5.2.17.5	Second frame block reservation parameters	74
5.2.17.6	Second frame block reservation reception procedures	74
5.2.17.7	Void	74
5.2.17.7a	Procedures for responding to a rebroadcast request for superframe block reservation	74
5.2.18	Response protocol specification	75
5.2.18.1	Response burst format	75
5.2.19	General request protocol specification	75
5.2.19.1	General request burst format	75
5.2.19.2	General request procedures	76
5.2.20	General response protocol specification	76
5.2.20.1	General response burst format	76
5.2.20.2	General response procedures	78
5.2.21	Retransmission procedures	78
5.3	DLS sublayer	79
5.3.1	Services	79
5.3.1.1	General	79
5.3.1.2	Data transfer	79
5.3.1.3	Station address encoding	79
5.3.1.4	DLS burst formats	81
5.3.2	DLS system parameters	82
5.3.2.1	Parameter ND4 (maximum length of a UDATA burst)	82
5.3.3	DLS procedures	82
5.3.3.1	Broadcast	82
5.3.3.2	DLS not supported	82
5.3.3.3	User data packet reception	83
5.3.3.4	CTRL DLPDU	83
5.4	Link Management Entity (LME) sublayer	83
5.4.1	Services	83
5.4.2	Synchronization burst format	83
5.4.2.1	General	83
5.4.2.2	Fixed and variable data fields	83
5.4.2.3	Fixed data field format	84
5.4.2.4	Variable data field format	87
5.4.2.5	Synchronization burst request	87
5.4.2.6	Broadcast link management burst	87
5.4.3	Control (CTRL) parameter formats	88
5.4.3.1	Encoding	88
5.4.3.2	VDL Mode 4 parameter identification	88
5.4.3.3	Ground-initiated modification parameters	89
5.4.3.4	Ground-initiated information parameters	92
5.4.3a	LME timers and parameters	94
5.4.3a.1	General	94
5.4.3a.2	Counter L1 (maximum number of missed reservations) and Timer TL3 (inter miss timer)	95
5.4.4	LME procedures	95
5.4.4.1	Synchronization burst procedures	95
5.4.4.2	Peer Entity Contact Table (PECT)	98
5.4.4.3	Network entry protocol specifications	99
5.4.5	Additional material for ADS-B applications	105
5.4.5.1	Information field formats	105
5.4.5.2	ADS-B request format	106
5.5	Void	106
5.6	Definitions for Compact Position Reporting	106
5.6.1	Introduction	106

5.6.2	Parameter symbols, data types, constants and variables	107
5.6.2.1	Parameter symbols	107
5.6.2.2	Data types.....	107
5.6.2.3	Constants.....	107
5.6.2.4	Variables	107
5.6.2.5	Functions.....	107
5.6.2.6	Patch constants	107
5.6.3	Fixed data field position encoding.....	107
5.6.4	Fixed data field position local decoding	107
5.6.5	Fixed data field position global decoding	107
5.6.6	Position Report Processing	107
6	General design requirements	108
6.1	Controls and indicators.....	108
6.2	Warm up.....	108
6.3	Airworthiness	108
6.4	Intended function.....	108
6.5	International Telecommunications Union regulations.....	108
6.6	Fire protection	108
6.7	Operation of controls.....	108
6.8	Accessibility of controls	108
6.9	Effects of tests	108
6.10	Failure of the VDL Mode 4 equipment	108
6.11	Software management	108
6.12	Transceiver configuration.....	108
6.13	Provision for multiple redundant VDL4 transceivers.....	109
6.14	Reception capability	109
6.15	Transmission capability.....	109
6.16	Monitoring of proper operation.....	109
6.17	Power-up self test	109
7	Protocol test procedures	109
7.1	General	109
7.1.1	Input voltage	109
7.1.2	Power input frequency	109
7.1.3	Adjustment of equipment.....	109
7.1.4	Equipment configuration	109
7.1.5	Test equipment precautions	110
7.1.6	Ambient conditions.....	110
7.1.7	Connected loads.....	110
7.2	Required test rig	110
7.3	Protocol test-suite description methodology	112
7.4	Detailed protocol test procedures	112
7.4.1	Test-suite overview.....	113
7.4.2	Declarations	119
7.4.3	Constraints	119
7.4.3.1	Abbreviations	119
7.4.3.1.1	Subfield mnemonics	119
7.4.3.1.2	Special characters used in the subfield definitions	120
7.4.3.1.3	Station addresses and positions	120
7.4.3.1.4	Tables of values for use in CPR test cases	121
7.4.3.1.5	Tables of values for use in content checking test cases	133
7.4.3.1.6	VDL4 burst formats.....	135
7.4.3.2	Test cases	157
7.4.3.2.1	Test case macros.....	157
7.4.3.2.2	Test case descriptions	160
Annex A (informative): Cross reference matrix		384
Annex B (informative): Description of ISO/IEC 9646 test methodology.....		410
B.1	Overview of the structure of the ISO/IEC 9646 test suites	410

B.2	The test case description.....	410
B.3	The queue action	412
B.4	The repeat construct	412
B.5	Macro definitions	413
B.6	Test case naming	413
Annex C (informative): Bibliography		414
History		420

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI EN 302 842-2 V1.3.1 \(2011-09\)](https://standards.iteh.ai/catalog/standards/etsi/2c263922-232b-4935-81a4-f8eb940b1ecf/etsi-en-302-842-2-v1-3-1-2011-09)

<https://standards.iteh.ai/catalog/standards/etsi/2c263922-232b-4935-81a4-f8eb940b1ecf/etsi-en-302-842-2-v1-3-1-2011-09>