

**VHF air-ground and air-air Digital Link (VDL);
Mode 4 radio equipment;
Technical characteristics and methods of measurement
for aeronautical mobile (airborne) equipment;
Part 3: Additional broadcast aspects**

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI EN 302 842-3 V1.3.1 \(2011-09\)](https://standards.iteh.ai/catalog/standards/etsi/82000a03-5ce3-4d23-a3a3-75bd7176c1a1/etsi-en-302-842-3-v1-3-1-2011-09)

<https://standards.iteh.ai/catalog/standards/etsi/82000a03-5ce3-4d23-a3a3-75bd7176c1a1/etsi-en-302-842-3-v1-3-1-2011-09>



Reference

REN/AERO-00007-3

Keywords

aeronautical, digital, radio, testing, VHF

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2010.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTE™ is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	5
Foreword.....	5
Introduction	6
1 Scope	7
2 References	8
2.1 Normative references	8
2.2 Informative references.....	9
3 Definitions and abbreviations.....	9
3.1 Definitions.....	9
3.1.1 Basic reference model definitions.....	9
3.1.2 Service conventions definitions	9
3.1.3 General definitions.....	9
3.1.4 Definition of bit order	10
3.2 Abbreviations	10
4 General description of VDL Mode 4 broadcast services.....	11
4.1 General	11
4.2 Automatic Dependent Surveillance-Broadcast (ADS-B)	12
4.3 Traffic Information Service-Broadcast (TIS-B).....	13
4.4 Flight Information Service-Broadcast (FIS-B).....	13
4.5 GNSS Augmentation Service-Broadcast (GNS-B).....	14
5 Minimum performance specification under standard test conditions.....	15
5.1 Requirements for ADS-B	15
5.1.1 Information Field Formats	15
5.1.2 ADS-B Request	25
5.1.2.1 ADS-B request format.....	25
5.1.2.2 Sleep Mode	25
5.1.2.3 Automatic Selection of Variable Information Fields	26
5.1.3 Default ADS-B Reporting	28
5.1.4 ADS-B Procedures.....	28
5.1.5 CTRL Parameters	30
5.1.5.1 Directory of Service (DOS) message	30
5.1.5.2 Channel Management Parameter	31
5.1.6 Definitions for Compact Position Reporting	41
5.1.6.1 Information Field Offset Encoding	41
5.1.6.2 Information Field Offset Decoding.....	43
5.1.6.3 Patch ID Encoding	44
5.1.6.4 Patch Id Decoding.....	44
5.1.7 Encoding of UDATA (udid)	45
5.2 Requirements for TIS-B	45
5.2.1 Traffic Information Volume (TIV)	45
5.2.2 Void	45
5.2.3 Message format.....	46
5.2.4 Management message	47
5.2.5 Aircraft target messages (airborne TIV)	48
5.2.6 Aircraft target messages (ground TIV)	50
5.2.7 Ground vehicle target messages (ground TIV)	51
5.2.8 TIS-B offset encoding.....	52
5.3 Requirements for FIS-B	55
5.3.1 Message format for received FIS-B messages.....	55
5.3.2 Meteorological Aerodrome Report (METAR) message	56
5.3.3 Special Observations and Reports (SPECI) message.....	63
5.3.4 Automatic Terminal Information Service (ATIS) message	64
5.3.5 Runway Condition (RCN) message.....	66

5.3.6	SIGNificant METeorological Information (SIGMET) message.....	70
5.3.7	Temporary Segregated Areas (TSA) message	71
5.3.8	FIS-B report request message	74
5.3.9	Void	75
5.3.9a	Airborne system functions	75
5.3.9a.1	Transmission of requests	75
5.3.9a.2	Differentiation between reports.....	75
5.4	Requirements for GNSS Augmentation Service Broadcast (GNS-B) message	76
5.4.1	Message format.....	76
5.4.2	Message Type 1	77
5.4.3	Message Type 2	80
5.4.4	Message Type 4	83
5.4.5	CRC Calculation.....	89
5.4.5.1	GNS-B CRC.....	89
5.4.5.2	FAS CRC	89
5.4.5.3	Ephemeris CRC.....	90
6	General design requirements	90
7	Protocol test procedures	90
7.1	General	90
7.2	Required test rig	91
7.3	Protocol test-suite description methodology	91
7.4	Detailed protocol test procedures	91
7.4.1	Test-suite overview	91
7.4.2	Declarations	94
7.4.3	Constraints	95
7.4.3.1	Abbreviations	95
7.4.3.1.1	Subfield mnemonics	95
7.4.3.1.2	Station addresses and positions	98
7.4.3.1.3	Tables of values for use in CPR test cases	99
7.4.3.1.4	Tables of values for use in content checking test cases	109
7.4.3.1.5	VDL4 Burst formats	143
7.4.3.2	Test cases	178
7.4.3.2.1	Test case macros	179
7.4.3.2.2	Test case descriptions.....	180
Annex A (informative):	Cross reference matrix	259
Annex B (informative):	Bibliography	269
History		276

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Aeronautics (AERO), and is now submitted for the Public Enquiry phase of the ETSI standards Two-step Approval Procedure.

The present document is part 3 of a multi-part deliverable covering the VHF air-ground and air-air Digital Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for aeronautical mobile (airborne) equipment, as identified below:

Part 1: "Physical layer";

Part 2: "General description and data link layer";

Part 3: "Additional broadcast aspects";

Part 4: "Point-to-point functions";

The present document is accompanied by an equivalent ground-based standard, EN 301 842 parts 1 to 4 [4], covering the VHF air-ground Data Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for ground-based equipment.

NOTE: Minimum Operational Performance Specifications (MOPS) are also being developed for VDL Mode 4. EUROCAE have previously published Interim MOPS for VDL Mode 4 [i.6] which are a sub set of EN 302 842-1 [1], EN 302 842-2 [2], EN 302 842-3 (the present document) and EN 302 842-4 [3]. EN 302 842-1 [1], EN 302 842-2 [2], EN 302 842-3 (the present document) and EN 302 842-4 [3] comply with the requirements of CEC Mandate M/318.

Proposed national transposition dates

Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa

Introduction

The present document states the technical specifications for Very High Frequency (VHF) Digital Link (VDL) Mode 4 aeronautical mobile (airborne) radio transmitters, transceivers and receivers for air-ground and air-air communications operating in the VHF band, using Gaussian Filtered Frequency Shift Keying (GFSK) modulation with 25 kHz channel spacing and capable of tuning to any of the 25 kHz channels from 118,000 MHz to 136,975 MHz as defined in ICAO VDL SARPs [i.2].

The present document may be used to produce tests for the assessment of the performance of the equipment. The performance of the equipment submitted for type testing should be representative of the performance of the corresponding production model.

The present document has been written on the assumption that:

- the type test measurements will be performed only once, in an accredited test laboratory and the measurements accepted by the various authorities in order to grant type approval;
- if equipment available on the market is required to be checked it will be tested in accordance with the methods of measurement specified in the present document or a documented alternative approved by the certifying authority;
- equipment comply with EN 302 842-1 [1] and EN 302 842-2 [2].

NOTE: The present document has been produced with a view to maintaining consistency of numbering with the equivalent standard for ground equipment (EN 301 842 all parts [4]). Where requirements are the same, they have been given the same number. Some new airborne requirements have been inserted between requirements that were sequential in EN 301 842 [4]. This has led to a non-standard form of numbering for new requirements in some places.

(<https://standards.iteh.ai>)
Document Preview

ETSI EN 302 842-3 V1.3.1 (2011-09)

<https://standards.iteh.ai/catalog/standards/etsi/82000a03-5ce3-4d23-a3a3-75bd7176c1a1/etsi-en-302-842-3-v1-3-1-2011-09>

1 Scope

The present document applies to the following radio equipment types:

- Very High Frequency (VHF) Digital Link (VDL) Mode 4 aeronautical mobile (airborne) radio transmitters, transceivers and receivers for air-ground and air-air communications operating in the VHF band, using Gaussian Filtered Frequency Shift Keying (GFSK) modulation with 25 kHz channel spacing and capable of tuning to any of the 25 kHz channels from 118,000 MHz to 136,975 MHz as defined in ICAO VDL SARPs 130 [i.2].

The present technical document provides part 3 of the technical specifications.

The present document is designed to ensure that equipment certified to it will be compatible with the relevant ICAO VDL SARPs [i.2] and ICAO VDL4 Technical Manual [i.1].

Manufacturers should note that in future the tuning range for the transmitter may also cover any 25 kHz channel from 112,000 MHz to 117,975 MHz and the receiver(s) may cover any 25 kHz channel from 108,000 MHz to 117,975 MHz.

The present document applies to "aeronautical mobile (airborne and in some cases ground vehicles)" equipment which will hereinafter be referred to as "mobile" equipment.

The scope of the present document is limited to mobile stations. The equivalent specification for ground stations is EN 301 842 [4].

A description of the scope of the VDL Mode 4 system is provided in part 2 of these technical specifications (see EN 302 842-2 [2], clause 1).

EN 302 842-1 [1] deals with tests of the physical layer. EN 302 842-2 [2] deals with tests of the link layer sufficient to support broadcast functionality including requirements and tests sufficient to recognize and respond to transmissions associated with point-to-point communication. The present document provides technical specifications for a VDL Mode 4 mobile transceiver supporting a full Automatic Dependent Surveillance-Broadcast (ADS-B) capability and, optionally, the additional functionality of either, or a combination of, the following services:

- Traffic Information Service-Broadcast (TIS-B);
- Flight Information Service-Broadcast (FIS-B);
- GNSS Augmentation Service-Broadcast (GNS-B).

The TIS-B, FIS-B, or GNS-B reception processing functionality in the airborne equipment is expected to be provided by a TIS-B, FIS-B or GNS-B processor, which could be contained within the VDL Mode 4 transceiver, but could also be housed in a separate physical unit. Therefore to support TIS-B, FIS-B or GNS-B message reception, the minimum functionality demanded of a basic VDL Mode 4 airborne transceiver unit (i.e. one that does not have a TIS-B, FIS-B or GNS-B processor housed within it) is to pass to the TIS-B, FIS-B or GNS-B processor, all TIS-B, FIS-B or GNS-B messages received.

As the measured values of equipment performance may be a function of the method of measurement, standard test conditions and methods of test are recommended in the present document.

The present document is organized as follows:

- clause 2 provides references to relevant documents;
- clause 3 provides general definitions, abbreviations and symbols used;
- clause 4 describes the VDL Mode 4 mobile station functionality to support ADS-B, TIS-B, FIS-B and GNS-B;
- clause 5 provides performance specifications for the VDL Mode 4 mobile station supporting ADS-B, TIS-B, FIS-B and GNS-B Services;
- clause 6 provides general design requirements;