

# ETSI EN 302 878-2 V1.1.1 (2011-11)



## **Access, Terminals, Transmission and Multiplexing (ATTM); Third Generation Transmission Systems for Interactive Cable Television Services - IP Cable Modems; Part 2: Physical Layer; DOCSIS 3.0**

[ETSI EN 302 878-2 V1.1.1 \(2011-11\)](https://standards.iteh.ai/catalog/standards/etsi/c22008b7-7801-476b-91a6-4ced79becb5b5/etsi-en-302-878-2-v1-1-1-2011-11)

<https://standards.iteh.ai/catalog/standards/etsi/c22008b7-7801-476b-91a6-4ced79becb5b5/etsi-en-302-878-2-v1-1-1-2011-11>

---

Reference

DEN/ATTM-003006-2

---

Keywordsaccess, broadband, cable, data, IP, IPCable,  
modem**ETSI**650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

iteh Standards  
(<https://standards.iteh.ai>)  
Document Preview

---

**Important notice**

---

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

[http://portal.etsi.org/chaicor/ETSI\\_support.asp](http://portal.etsi.org/chaicor/ETSI_support.asp)

---

**Copyright Notification**

---

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2011.  
All rights reserved.

DECT<sup>TM</sup>, PLUGTESTS<sup>TM</sup>, UMTS<sup>TM</sup> and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.  
3GPP<sup>TM</sup> and LTE<sup>TM</sup> are Trade Marks of ETSI registered for the benefit of its Members and  
of the 3GPP Organizational Partners.  
GSM<sup>®</sup> and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Contents

|                                                                                                    |    |
|----------------------------------------------------------------------------------------------------|----|
| Intellectual Property Rights .....                                                                 | 9  |
| Foreword.....                                                                                      | 9  |
| 1 Scope .....                                                                                      | 10 |
| 1.1 Introduction and Purpose.....                                                                  | 10 |
| 1.2 Requirements.....                                                                              | 10 |
| 1.3 Conventions.....                                                                               | 10 |
| 2 References .....                                                                                 | 11 |
| 2.1 Normative references .....                                                                     | 11 |
| 2.2 Informative references.....                                                                    | 12 |
| 3 Definitions and abbreviations.....                                                               | 12 |
| 3.1 Definitions.....                                                                               | 12 |
| 3.2 Abbreviations .....                                                                            | 18 |
| 4 Void.....                                                                                        | 20 |
| 5 Functional Assumptions.....                                                                      | 20 |
| 5.1 Equipment Assumptions.....                                                                     | 20 |
| 5.1.1 Frequency Plan .....                                                                         | 20 |
| 5.1.2 Compatibility with Other Services.....                                                       | 20 |
| 5.1.3 Fault Isolation Impact on Other Users .....                                                  | 20 |
| 5.1.4 Cable System Terminal Devices .....                                                          | 21 |
| 5.2 RF Channel Assumptions .....                                                                   | 21 |
| 5.2.1 Transmission Downstream .....                                                                | 21 |
| 5.2.2 Transmission Upstream .....                                                                  | 21 |
| 5.2.2.1 Availability.....                                                                          | 22 |
| 5.3 Transmission Levels.....                                                                       | 22 |
| 5.4 Frequency Inversion .....                                                                      | 22 |
| 6 Physical Media Dependent Sublayer Specification.....                                             | 23 |
| 6.1 Scope .....                                                                                    | 23 |
| 6.2 Upstream .....                                                                                 | 23 |
| 6.2.1 Overview .....                                                                               | 23 |
| 6.2.2 Signal Processing Requirements.....                                                          | 24 |
| 6.2.3 Modulation Formats.....                                                                      | 26 |
| 6.2.4 R-S Encode .....                                                                             | 27 |
| 6.2.4.1 R-S Encode Modes.....                                                                      | 27 |
| 6.2.4.2 R-S Bit-to-Symbol Ordering .....                                                           | 27 |
| 6.2.5 Upstream R-S Frame Structure for DOCSIS 3.0 Multiple Transmit Channel mode Enabled .....     | 27 |
| 6.2.5.1 R-S Codeword Length.....                                                                   | 28 |
| 6.2.5.1.1 Burst Size .....                                                                         | 28 |
| 6.2.5.1.2 Fixed Codeword Length .....                                                              | 28 |
| 6.2.5.1.3 Shortened Last Codeword .....                                                            | 29 |
| 6.2.5.2 R-S FEC Disabled .....                                                                     | 29 |
| 6.2.6 Upstream R-S Frame Structure for DOCSIS 3.0 Multiple Transmit Channel mode Not Enabled ..... | 29 |
| 6.2.7 TDMA Byte Interleaver.....                                                                   | 29 |
| 6.2.7.1 Byte Interleaver Parameters .....                                                          | 29 |
| 6.2.7.2 Interleaver Operating Modes.....                                                           | 30 |
| 6.2.7.2.1 Fixed Mode.....                                                                          | 30 |
| 6.2.7.2.2 Dynamic Mode .....                                                                       | 31 |
| 6.2.8 Scrambler (Randomizer).....                                                                  | 32 |
| 6.2.9 TCM Encoder .....                                                                            | 33 |
| 6.2.9.1 Byte to TCM Symbol Mapping.....                                                            | 33 |
| 6.2.10 Preamble Prepend .....                                                                      | 35 |
| 6.2.11 Modulation Rates.....                                                                       | 36 |
| 6.2.11.1 DOCSIS 3.0 Modulation Rates .....                                                         | 36 |
| 6.2.11.2 Backward Compatibility Modulation Rates .....                                             | 36 |

|            |                                                                                     |    |
|------------|-------------------------------------------------------------------------------------|----|
| 6.2.12     | S-CDMA Framer and Interleaver .....                                                 | 36 |
| 6.2.12.1   | S-CDMA Framing Considerations.....                                                  | 36 |
| 6.2.12.2   | Mini-slot Numbering.....                                                            | 36 |
| 6.2.12.2.1 | Mini-slot Numbering Parameters in UCD .....                                         | 38 |
| 6.2.12.2.2 | Mini-slot Numbering Examples .....                                                  | 39 |
| 6.2.12.3   | Transmission Time.....                                                              | 40 |
| 6.2.12.4   | Latency Considerations.....                                                         | 40 |
| 6.2.12.5   | Spreader-off Bursts for Maintenance on S-CDMA channel .....                         | 40 |
| 6.2.12.6   | Limiting the Number of Codes Assigned to a CM.....                                  | 42 |
| 6.2.13     | S-CDMA Framer .....                                                                 | 42 |
| 6.2.13.1   | Subframe Definition.....                                                            | 42 |
| 6.2.13.2   | Framer Operation .....                                                              | 43 |
| 6.2.13.2.1 | Rules for Preamble and Coded TCM Symbols.....                                       | 43 |
| 6.2.13.2.2 | Rules for Uncoded Symbols and the Uncoded TCM Subsymbols .....                      | 44 |
| 6.2.13.2.3 | Subframe Example .....                                                              | 44 |
| 6.2.13.2.4 | Frame Transmission .....                                                            | 45 |
| 6.2.14     | Symbol Mapping .....                                                                | 45 |
| 6.2.15     | S-CDMA Spreader.....                                                                | 51 |
| 6.2.15.1   | Code Hopping .....                                                                  | 52 |
| 6.2.15.1.1 | Code Hopping Mode 1 .....                                                           | 53 |
| 6.2.15.1.2 | Code Hopping Mode 2 .....                                                           | 53 |
| 6.2.15.1.3 | Code hopping generator.....                                                         | 55 |
| 6.2.16     | Transmit Pre-Equalizer .....                                                        | 57 |
| 6.2.17     | Spectral Shaping .....                                                              | 59 |
| 6.2.17.1   | Upstream Frequency Agility and Range .....                                          | 59 |
| 6.2.17.2   | Spectrum Format.....                                                                | 59 |
| 6.2.18     | Relative Processing Delays.....                                                     | 59 |
| 6.2.19     | Transmit Power Requirements.....                                                    | 60 |
| 6.2.19.1   | TDMA Transmit Power Calculations.....                                               | 64 |
| 6.2.19.2   | S-CDMA Transmit Power Calculations.....                                             | 65 |
| 6.2.19.2.1 | S-CDMA Transmit Power Calculations when Maximum Scheduled Codes Is Not Enabled..... | 65 |
| 6.2.19.2.2 | S-CDMA Transmit Power Calculations When Maximum Scheduled Codes is Enabled .....    | 66 |
| 6.2.19.3   | Transmit Power Step Size .....                                                      | 69 |
| 6.2.19.4   | Transmit Power Requirements for Multiple Transmit Channel mode Not Enabled .....    | 69 |
| 6.2.20     | Burst Profiles .....                                                                | 70 |
| 6.2.20.1   | Ranging Offset .....                                                                | 71 |
| 6.2.20.2   | TDMA Reconfiguration Times .....                                                    | 72 |
| 6.2.20.3   | S-CDMA Reconfiguration Time .....                                                   | 73 |
| 6.2.20.4   | CM Timing Offsets When Changing Modulation Rate.....                                | 74 |
| 6.2.21     | Burst Timing Convention .....                                                       | 75 |
| 6.2.22     | Fidelity Requirements.....                                                          | 76 |
| 6.2.22.1   | Spurious Emissions .....                                                            | 76 |
| 6.2.22.1.1 | Adjacent Channel Spurious Emissions.....                                            | 79 |
| 6.2.22.1.2 | Spurious Emissions in the Upstream Frequency Range .....                            | 79 |
| 6.2.22.2   | Spurious Emissions During Burst On/Off Transients .....                             | 80 |
| 6.2.22.3   | Modulation Error Ratio (MER).....                                                   | 80 |
| 6.2.22.3.1 | Definitions .....                                                                   | 80 |
| 6.2.22.3.2 | Requirements .....                                                                  | 81 |
| 6.2.22.4   | Filter Distortion.....                                                              | 82 |
| 6.2.22.4.1 | Amplitude .....                                                                     | 82 |
| 6.2.22.5   | Carrier Phase Noise.....                                                            | 83 |
| 6.2.22.6   | Channel Frequency Accuracy .....                                                    | 83 |
| 6.2.22.7   | Modulation Rate Accuracy .....                                                      | 83 |
| 6.2.22.8   | Modulation Timing Jitter .....                                                      | 83 |
| 6.2.22.8.1 | Symbol Timing Jitter for TDMA Upstream Channels in Asynchronous Operation.....      | 83 |
| 6.2.22.8.2 | Modulation Timing Jitter for Synchronous Operation.....                             | 84 |
| 6.2.23     | Upstream Demodulator Input Power Characteristics.....                               | 84 |
| 6.2.24     | Upstream Electrical Output from the CM.....                                         | 85 |
| 6.2.25     | Upstream CM Transmitter Capabilities .....                                          | 86 |
| 6.2.25.1   | Description of CM Upstream Transmit Channel Set Capability.....                     | 86 |
| 6.3        | Downstream .....                                                                    | 87 |
| 6.3.1      | Downstream Protocol and Interleaving Support .....                                  | 87 |

|           |                                                    |    |
|-----------|----------------------------------------------------|----|
| 6.3.2     | Downstream Electrical Input to CM .....            | 87 |
| 6.3.3     | CM BER Performance .....                           | 87 |
| 6.3.3.1   | 64-QAM .....                                       | 88 |
| 6.3.3.1.1 | 64-QAM CM BER Performance .....                    | 88 |
| 6.3.3.1.2 | Image Rejection Performance .....                  | 88 |
| 6.3.3.1.3 | 64-QAM Adjacent Channel Performance.....           | 88 |
| 6.3.3.2   | 256-QAM .....                                      | 88 |
| 6.3.3.2.1 | 256-QAM CM BER Performance .....                   | 88 |
| 6.3.3.2.2 | 256-QAM Image Rejection Performance .....          | 88 |
| 6.3.3.2.3 | 256-QAM Adjacent Channel Performance.....          | 89 |
| 6.3.4     | Downstream Multiple Receiver Capabilities .....    | 89 |
| 6.3.4.1   | Receive Module Parameters.....                     | 89 |
| 6.3.4.2   | Receive Channel Parameters .....                   | 90 |
| 6.3.4.3   | Standard Receive Channel Profile.....              | 90 |
| 6.3.4.4   | Example Manufacturer Receive Channel Profile ..... | 91 |
| 6.3.4.5   | Reconfiguration of CM Receive Channels.....        | 92 |
| 6.3.5     | Non-Synchronous DS Channel Support .....           | 92 |

## **Annex A (normative): Timing Requirements for Supporting Business Services over DOCSIS .....93**

|     |           |    |
|-----|-----------|----|
| A.1 | CMTS..... | 93 |
| A.2 | CM.....   | 93 |

## **Annex B (normative): Additions and Modifications for European Specification.....94**

|           |                                                      |    |
|-----------|------------------------------------------------------|----|
| B.1       | Scope .....                                          | 94 |
| B.1.1     | Introduction and Purpose.....                        | 94 |
| B.1.2     | Background .....                                     | 94 |
| B.1.2.1   | Broadband Access Network.....                        | 94 |
| B.1.2.2   | Network and System Architecture .....                | 94 |
| B.1.2.2.1 | The DOCSIS Network .....                             | 94 |
| B.1.2.3   | Service Goals .....                                  | 95 |
| B.1.2.4   | Statement of Compatibility .....                     | 95 |
| B.1.2.5   | Reference Architecture .....                         | 95 |
| B.1.2.6   | Void .....                                           | 95 |
| B.1.3     | Requirements.....                                    | 95 |
| B.1.4     | Conventions.....                                     | 95 |
| B.1.5     | Void.....                                            | 95 |
| B.2       | References .....                                     | 95 |
| B.2.1     | Normative References .....                           | 95 |
| B.2.2     | Informative References .....                         | 95 |
| B.2.3     | Reference Acquisition .....                          | 95 |
| B.3       | Terms and Definitions .....                          | 95 |
| B.4       | Abbreviations and Acronyms .....                     | 96 |
| B.5       | Functional Assumptions.....                          | 96 |
| B.5.1     | Equipment Assumptions.....                           | 96 |
| B.5.1.1   | Frequency Plan .....                                 | 96 |
| B.5.1.2   | Compatibility with Other Services.....               | 96 |
| B.5.1.3   | Fault Isolation Impact on Other Users.....           | 96 |
| B.5.1.4   | Cable System Terminal Devices .....                  | 96 |
| B.5.2     | RF Channel Assumptions.....                          | 96 |
| B.5.2.1   | Transmission Downstream .....                        | 97 |
| B.5.2.2   | Transmission Upstream .....                          | 98 |
| B.5.2.2.1 | Availability.....                                    | 98 |
| B.5.3     | Transmission Levels.....                             | 98 |
| B.5.4     | Frequency Inversion.....                             | 98 |
| B.6       | Physical Media Dependent Sublayer Specification..... | 98 |
| B.6.1     | Scope .....                                          | 98 |

|              |                                                                                              |     |
|--------------|----------------------------------------------------------------------------------------------|-----|
| B.6.2        | Upstream .....                                                                               | 99  |
| B.6.2.1      | Overview .....                                                                               | 99  |
| B.6.2.2      | Signal Processing Requirements .....                                                         | 100 |
| B.6.2.3      | Modulation Formats .....                                                                     | 100 |
| B.6.2.4      | R-S Encode .....                                                                             | 100 |
| B.6.2.4.1    | R-S Encode Modes .....                                                                       | 100 |
| B.6.2.4.2    | R-S Bit-to-Symbol Ordering .....                                                             | 100 |
| B.6.2.5      | Upstream R-S Frame Structure for DOCSIS 3.0 Multiple Transmit Channel mode Enabled .....     | 100 |
| B.6.2.5.1    | R-S Codeword Length .....                                                                    | 100 |
| B.6.2.5.1.1  | Burst Size .....                                                                             | 100 |
| B.6.2.5.1.2  | Fixed Codeword Length .....                                                                  | 101 |
| B.6.2.5.1.3  | Shortened Last Codeword .....                                                                | 101 |
| B.6.2.5.2    | R-S FEC Disabled .....                                                                       | 101 |
| B.6.2.6      | Upstream R-S Frame Structure for DOCSIS 3.0 Multiple Transmit Channel mode Not Enabled ..... | 101 |
| B.6.2.7      | TDMA Byte Interleaver .....                                                                  | 101 |
| B.6.2.7.1    | Byte Interleaver Parameters .....                                                            | 101 |
| B.6.2.7.2    | Interleaver Operating Modes .....                                                            | 101 |
| B.6.2.7.2.1  | Fixed Mode .....                                                                             | 101 |
| B.6.2.7.2.2  | Dynamic Mode .....                                                                           | 101 |
| B.6.2.8      | Scrambler (Randomizer) .....                                                                 | 101 |
| B.6.2.9      | TCM Encoder .....                                                                            | 101 |
| B.6.2.9.1    | Byte to TCM Symbol Mapping .....                                                             | 101 |
| B.6.2.10     | Preamble Prepend .....                                                                       | 101 |
| B.6.2.11     | Modulation Rates .....                                                                       | 101 |
| B.6.2.11.1   | DOCSIS 3.0 Modulation Rates .....                                                            | 102 |
| B.6.2.11.2   | Backward Compatibility Modulation Rates .....                                                | 102 |
| B.6.2.12     | S-CDMA Framer and Interleaver .....                                                          | 102 |
| B.6.2.12.1   | S-CDMA Framing Considerations .....                                                          | 102 |
| B.6.2.12.2   | Mini-slot Numbering .....                                                                    | 102 |
| B.6.2.12.2.1 | Mini-slot Numbering Parameters in UCD .....                                                  | 102 |
| B.6.2.12.2.2 | Mini-slot Numbering Examples .....                                                           | 102 |
| B.6.2.12.3   | Transmission Time .....                                                                      | 102 |
| B.6.2.12.4   | Latency Considerations .....                                                                 | 102 |
| B.6.2.12.5   | Spreader-off Bursts for Maintenance on S-CDMA channel .....                                  | 102 |
| B.6.2.12.6   | Limiting the Number of Codes Assigned to a CM .....                                          | 102 |
| B.6.2.13     | S-CDMA Framer .....                                                                          | 102 |
| B.6.2.13.1   | Subframe Definition .....                                                                    | 102 |
| B.6.2.13.2   | Framer Operation .....                                                                       | 102 |
| B.6.2.13.2.1 | Rules for Preamble and Coded TCM Symbols .....                                               | 102 |
| B.6.2.13.2.2 | Rules for Uncoded Symbols and the Uncoded TCM Subsymbols .....                               | 103 |
| B.6.2.13.2.3 | Subframe Example .....                                                                       | 103 |
| B.6.2.13.2.4 | Frame Transmission .....                                                                     | 103 |
| B.6.2.14     | Symbol Mapping .....                                                                         | 103 |
| B.6.2.15     | S-CDMA Spreader .....                                                                        | 103 |
| B.6.2.15.1   | Code Hopping .....                                                                           | 103 |
| B.6.2.15.1.1 | Code Hopping Mode 1 .....                                                                    | 103 |
| B.6.2.15.1.2 | Code Hopping Mode 2 .....                                                                    | 103 |
| B.6.2.15.1.3 | Code Hopping Generator .....                                                                 | 103 |
| B.6.2.16     | Transmit Pre-Equalizer .....                                                                 | 103 |
| B.6.2.17     | Spectral Shaping .....                                                                       | 105 |
| B.6.2.17.1   | Upstream Frequency Agility and Range .....                                                   | 105 |
| B.6.2.17.2   | Spectrum Format .....                                                                        | 105 |
| B.6.2.18     | Relative Processing Delays .....                                                             | 105 |
| B.6.2.19     | Transmit Power Requirements .....                                                            | 106 |
| B.6.2.19.1   | TDMA Transmit Power Calculations .....                                                       | 109 |
| B.6.2.19.2   | S-CDMA Transmit Power Calculations .....                                                     | 110 |
| B.6.2.19.2.1 | S-CDMA Transmit power Calculations with Maximum Scheduled Codes Not Enabled .....            | 110 |
| B.6.2.19.2.2 | S-CDMA Transmit Power Calculations With Maximum Scheduled Codes Enabled .....                | 112 |
| B.6.2.19.3   | Transmit Power Step Size .....                                                               | 114 |
| B.6.2.19.4   | Transmit Power Requirements for Multiple Transmit Channel mode Not Enabled .....             | 114 |
| B.6.2.20     | Burst Profiles .....                                                                         | 115 |
| B.6.2.20.1   | Ranging Offset .....                                                                         | 116 |

|              |                                                                                |     |
|--------------|--------------------------------------------------------------------------------|-----|
| B.6.2.20.2   | TDMA Reconfiguration Times .....                                               | 116 |
| B.6.2.20.3   | S-CDMA Reconfiguration Times .....                                             | 118 |
| B.6.2.20.4   | CM Timing Offsets When Changing Modulation Rate.....                           | 118 |
| B.6.2.21     | Burst Timing Convention .....                                                  | 118 |
| B.6.2.22     | Fidelity Requirements.....                                                     | 118 |
| B.6.2.22.1   | Spurious Emissions .....                                                       | 118 |
| B.6.2.22.1.1 | Adjacent Channel Spurious Emissions.....                                       | 120 |
| B.6.2.22.1.2 | Spurious Emissions in the Upstream Frequency Range .....                       | 121 |
| B.6.2.22.2   | Spurious Emissions During Burst On/Off Transients .....                        | 121 |
| B.6.2.22.3   | Modulation Error Ratio (MER).....                                              | 121 |
| B.6.2.22.3.1 | Definitions.....                                                               | 122 |
| B.6.2.22.3.2 | Requirements.....                                                              | 122 |
| B.6.2.22.4   | Filter Distortion.....                                                         | 122 |
| B.6.2.22.4.1 | Amplitude.....                                                                 | 123 |
| B.6.2.22.5   | Carrier Phase Noise.....                                                       | 123 |
| B.6.2.22.6   | Channel Frequency Accuracy .....                                               | 123 |
| B.6.2.22.7   | Modulation Rate Accuracy .....                                                 | 123 |
| B.6.2.22.8   | Modulation Timing Jitter .....                                                 | 123 |
| B.6.2.22.8.1 | Symbol Timing Jitter for TDMA Upstream Channels in Asynchronous Operation..... | 123 |
| B.6.2.22.8.2 | Modulation Timing Jitter for Synchronous Operation.....                        | 123 |
| B.6.2.23     | Upstream Demodulator Input Power Characteristics.....                          | 123 |
| B.6.2.24     | Upstream Electrical Output from the CM.....                                    | 123 |
| B.6.2.25     | Upstream CM Transmitter Capabilities .....                                     | 124 |
| B.6.2.25.1   | Description of CM Upstream Transmit Channel Set Capabilities.....              | 124 |
| B.6.3        | Downstream .....                                                               | 124 |
| B.6.3.1      | Downstream Protocol and Interleaving Support.....                              | 124 |
| B.6.3.2      | Downstream Electrical Input to CM.....                                         | 125 |
| B.6.3.3      | CM BER Performance .....                                                       | 125 |
| B.6.3.3.1    | 64-QAM.....                                                                    | 125 |
| B.6.3.3.1.1  | 64-QAM CM BER Performance .....                                                | 125 |
| B.6.3.3.1.2  | 64-QAM Image Rejection Performance.....                                        | 126 |
| B.6.3.3.1.3  | 64-QAM Adjacent Channel Performance.....                                       | 126 |
| B.6.3.3.2    | 256-QAM.....                                                                   | 126 |
| B.6.3.3.2.1  | 256-QAM CM BER Performance .....                                               | 126 |
| B.6.3.3.2.2  | 256-QAM Image Rejection Performance .....                                      | 126 |
| B.6.3.3.2.3  | 256-QAM Adjacent Channel Performance.....                                      | 126 |
| B.6.3.4      | Downstream Multiple Receiver Capabilities .....                                | 126 |
| B.6.3.4.1    | Receive Module Parameters.....                                                 | 126 |
| B.6.3.4.2    | Receive Channel Parameters.....                                                | 127 |
| B.6.3.4.3    | Standard Receive Channel Profile.....                                          | 127 |
| B.6.3.4.4    | Example Manufacturer Receive Channel Profile .....                             | 127 |
| B.6.3.4.5    | Reconfiguration of CM Receive Channels.....                                    | 128 |
| B.6.3.5      | Non-Synchronous DS Channel Support .....                                       | 128 |

## **Annex C (normative): MPEG Header Synchronization and Recovery.....129**

C.1 MPEG Header Synchronization and Recovery in the North American Technology Option.....129

C.2 MPEG Header Synchronization and Recovery in the European Technology Option.....129

## **Annex D (informative): Example Preamble Sequence Introduction .....130**

D.1 Example Preamble Sequence .....

## **Annex E (informative): S-CDMA Framing.....132**

E.1 Coded Subsymbol Numbering .....

E.2 Uncoded Subsymbol Numbering .....

E.3 Framing Output Numbering .....

E.4 Comments.....

## **Annex F (informative): Ambient Temperature and Wind Loading Effects .....134**