

**Access, Terminals, Transmission and Multiplexing (ATTM);
Third Generation Transmission Systems for
Interactive Cable Television Services - IP Cable Modems;
Part 2: Physical Layer;
DOCSIS 3.0**

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI EN 302 878-2 V1.1.1 \(2011-11\)](https://standards.iteh.ai/catalog/standards/etsi/c22008b7-7801-476b-91a6-4ced79becb5b5/etsi-en-302-878-2-v1-1-1-2011-11)

<https://standards.iteh.ai/catalog/standards/etsi/c22008b7-7801-476b-91a6-4ced79becb5b5/etsi-en-302-878-2-v1-1-1-2011-11>



Reference

DEN/ATTM-003006-2

Keywordsaccess, broadband, cable, data, IP, IPCable,
modem**ETSI**650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iteh Standards
(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2011.
All rights reserved.

DECTTM, **PLUGTESTS**TM, **UMTS**TM, **TIPHON**TM, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPPTM is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTETM is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	9
Foreword.....	9
1 Scope	10
1.1 Introduction and Purpose.....	10
1.2 Requirements.....	10
1.3 Conventions.....	10
2 References	11
2.1 Normative references	11
2.2 Informative references.....	12
3 Definitions and abbreviations.....	12
3.1 Definitions	12
3.2 Abbreviations	18
4 Void.....	20
5 Functional Assumptions	20
5.1 Equipment Assumptions.....	20
5.1.1 Frequency Plan	20
5.1.2 Compatibility with Other Services.....	20
5.1.3 Fault Isolation Impact on Other Users	20
5.1.4 Cable System Terminal Devices	21
5.2 RF Channel Assumptions	21
5.2.1 Transmission Downstream	21
5.2.2 Transmission Upstream	21
5.2.2.1 Availability.....	22
5.3 Transmission Levels.....	22
5.4 Frequency Inversion	22
6 Physical Media Dependent Sublayer Specification.....	23
6.1 Scope	23
6.2 Upstream	23
6.2.1 Overview	23
6.2.2 Signal Processing Requirements	24
6.2.3 Modulation Formats.....	26
6.2.4 R-S Encode	27
6.2.4.1 R-S Encode Modes.....	27
6.2.4.2 R-S Bit-to-Symbol Ordering	27
6.2.5 Upstream R-S Frame Structure for DOCSIS 3.0 Multiple Transmit Channel mode Enabled	27
6.2.5.1 R-S Codeword Length.....	28
6.2.5.1.1 Burst Size	28
6.2.5.1.2 Fixed Codeword Length	28
6.2.5.1.3 Shortened Last Codeword	29
6.2.5.2 R-S FEC Disabled	29
6.2.6 Upstream R-S Frame Structure for DOCSIS 3.0 Multiple Transmit Channel mode Not Enabled	29
6.2.7 TDMA Byte Interleaver.....	29
6.2.7.1 Byte Interleaver Parameters	29
6.2.7.2 Interleaver Operating Modes.....	30
6.2.7.2.1 Fixed Mode.....	30
6.2.7.2.2 Dynamic Mode	31
6.2.8 Scrambler (Randomizer).....	32
6.2.9 TCM Encoder	33
6.2.9.1 Byte to TCM Symbol Mapping.....	33
6.2.10 Preamble Prepend	35
6.2.11 Modulation Rates.....	36
6.2.11.1 DOCSIS 3.0 Modulation Rates	36
6.2.11.2 Backward Compatibility Modulation Rates	36

6.2.12	S-CDMA Framer and Interleaver	36
6.2.12.1	S-CDMA Framing Considerations.....	36
6.2.12.2	Mini-slot Numbering.....	36
6.2.12.2.1	Mini-slot Numbering Parameters in UCD	38
6.2.12.2.2	Mini-slot Numbering Examples	39
6.2.12.3	Transmission Time.....	40
6.2.12.4	Latency Considerations.....	40
6.2.12.5	Spreader-off Bursts for Maintenance on S-CDMA channel	40
6.2.12.6	Limiting the Number of Codes Assigned to a CM.....	42
6.2.13	S-CDMA Framer	42
6.2.13.1	Subframe Definition.....	42
6.2.13.2	Framer Operation	43
6.2.13.2.1	Rules for Preamble and Coded TCM Symbols.....	43
6.2.13.2.2	Rules for Uncoded Symbols and the Uncoded TCM Subsymbols	44
6.2.13.2.3	Subframe Example	44
6.2.13.2.4	Frame Transmission	45
6.2.14	Symbol Mapping	45
6.2.15	S-CDMA Spreader.....	51
6.2.15.1	Code Hopping	52
6.2.15.1.1	Code Hopping Mode 1	53
6.2.15.1.2	Code Hopping Mode 2	53
6.2.15.1.3	Code hopping generator.....	55
6.2.16	Transmit Pre-Equalizer	57
6.2.17	Spectral Shaping	59
6.2.17.1	Upstream Frequency Agility and Range	59
6.2.17.2	Spectrum Format.....	59
6.2.18	Relative Processing Delays.....	59
6.2.19	Transmit Power Requirements.....	60
6.2.19.1	TDMA Transmit Power Calculations.....	64
6.2.19.2	S-CDMA Transmit Power Calculations.....	65
6.2.19.2.1	S-CDMA Transmit Power Calculations when Maximum Scheduled Codes Is Not Enabled.....	65
6.2.19.2.2	S-CDMA Transmit Power Calculations When Maximum Scheduled Codes is Enabled	66
6.2.19.3	Transmit Power Step Size	69
6.2.19.4	Transmit Power Requirements for Multiple Transmit Channel mode Not Enabled	69
6.2.20	Burst Profiles	70
6.2.20.1	Ranging Offset	71
6.2.20.2	TDMA Reconfiguration Times	72
6.2.20.3	S-CDMA Reconfiguration Time	73
6.2.20.4	CM Timing Offsets When Changing Modulation Rate.....	74
6.2.21	Burst Timing Convention	75
6.2.22	Fidelity Requirements.....	76
6.2.22.1	Spurious Emissions	76
6.2.22.1.1	Adjacent Channel Spurious Emissions.....	79
6.2.22.1.2	Spurious Emissions in the Upstream Frequency Range	79
6.2.22.2	Spurious Emissions During Burst On/Off Transients	80
6.2.22.3	Modulation Error Ratio (MER).....	80
6.2.22.3.1	Definitions	80
6.2.22.3.2	Requirements	81
6.2.22.4	Filter Distortion.....	82
6.2.22.4.1	Amplitude	82
6.2.22.5	Carrier Phase Noise.....	83
6.2.22.6	Channel Frequency Accuracy	83
6.2.22.7	Modulation Rate Accuracy	83
6.2.22.8	Modulation Timing Jitter	83
6.2.22.8.1	Symbol Timing Jitter for TDMA Upstream Channels in Asynchronous Operation.....	83
6.2.22.8.2	Modulation Timing Jitter for Synchronous Operation.....	84
6.2.23	Upstream Demodulator Input Power Characteristics.....	84
6.2.24	Upstream Electrical Output from the CM.....	85
6.2.25	Upstream CM Transmitter Capabilities	86
6.2.25.1	Description of CM Upstream Transmit Channel Set Capability.....	86
6.3	Downstream	87
6.3.1	Downstream Protocol and Interleaving Support	87

6.3.2	Downstream Electrical Input to CM	87
6.3.3	CM BER Performance	87
6.3.3.1	64-QAM	88
6.3.3.1.1	64-QAM CM BER Performance	88
6.3.3.1.2	Image Rejection Performance	88
6.3.3.1.3	64-QAM Adjacent Channel Performance.....	88
6.3.3.2	256-QAM.....	88
6.3.3.2.1	256-QAM CM BER Performance	88
6.3.3.2.2	256-QAM Image Rejection Performance	88
6.3.3.2.3	256-QAM Adjacent Channel Performance.....	89
6.3.4	Downstream Multiple Receiver Capabilities	89
6.3.4.1	Receive Module Parameters.....	89
6.3.4.2	Receive Channel Parameters	90
6.3.4.3	Standard Receive Channel Profile.....	90
6.3.4.4	Example Manufacturer Receive Channel Profile	91
6.3.4.5	Reconfiguration of CM Receive Channels.....	92
6.3.5	Non-Synchronous DS Channel Support	92

Annex A (normative): Timing Requirements for Supporting Business Services over DOCSIS93

A.1	CMTS.....	93
A.2	CM.....	93

Annex B (normative): Additions and Modifications for European Specification.....94

B.1	Scope	94
B.1.1	Introduction and Purpose.....	94
B.1.2	Background	94
B.1.2.1	Broadband Access Network.....	94
B.1.2.2	Network and System Architecture.....	94
B.1.2.2.1	The DOCSIS Network	94
B.1.2.3	Service Goals	95
B.1.2.4	Statement of Compatibility	95
B.1.2.5	Reference Architecture	95
B.1.2.6	Void	95
B.1.3	Requirements.....	95
B.1.4	Conventions.....	95
B.1.5	Organization of Document	95
B.2	References	95
B.2.1	Normative References	95
B.2.2	Informative References	95
B.2.3	Reference Acquisition	95
B.3	Terms and Definitions	95
B.4	Abbreviations and Acronyms	96
B.5	Functional Assumptions.....	96
B.5.1	Equipment Assumptions.....	96
B.5.1.1	Frequency Plan	96
B.5.1.2	Compatibility with Other Services.....	96
B.5.1.3	Fault Isolation Impact on Other Users	96
B.5.1.4	Cable System Terminal Devices	96
B.5.2	RF Channel Assumptions	96
B.5.2.1	Transmission Downstream	97
B.5.2.2	Transmission Upstream	98
B.5.2.2.1	Availability.....	98
B.5.3	Transmission Levels.....	98
B.5.4	Frequency Inversion	98
B.6	Physical Media Dependent Sublayer Specification.....	98
B.6.1	Scope	98
B.6.2	Upstream	99

B.6.2.1	Overview	99
B.6.2.2	Signal Processing Requirements	100
B.6.2.3	Modulation Formats	100
B.6.2.4	R-S Encode	100
B.6.2.4.1	R-S Encode Modes	100
B.6.2.4.2	R-S Bit-to-Symbol Ordering	100
B.6.2.5	Upstream R-S Frame Structure for DOCSIS 3.0 Multiple Transmit Channel mode Enabled	100
B.6.2.5.1	R-S Codeword Length	100
B.6.2.5.1.1	Burst Size	100
B.6.2.5.1.2	Fixed Codeword Length	101
B.6.2.5.1.3	Shortened Last Codeword	101
B.6.2.5.2	R-S FEC Disabled	101
B.6.2.6	Upstream R-S Frame Structure for DOCSIS 3.0 Multiple Transmit Channel mode Not Enabled	101
B.6.2.7	TDMA Byte Interleaver	101
B.6.2.7.1	Byte Interleaver Parameters	101
B.6.2.7.2	Interleaver Operating Modes	101
B.6.2.7.2.1	Fixed Mode	101
B.6.2.7.2.2	Dynamic Mode	101
B.6.2.8	Scrambler (Randomizer)	101
B.6.2.9	TCM Encoder	101
B.6.2.9.1	Byte to TCM Symbol Mapping	101
B.6.2.10	Preamble Prepend	101
B.6.2.11	Modulation Rates	101
B.6.2.11.1	DOCSIS 3.0 Modulation Rates	102
B.6.2.11.2	Backward Compatibility Modulation Rates	102
B.6.2.12	S-CDMA Framer and Interleaver	102
B.6.2.12.1	S-CDMA Framing Considerations	102
B.6.2.12.2	Mini-slot Numbering	102
B.6.2.12.2.1	Mini-slot Numbering Parameters in UCD	102
B.6.2.12.2.2	Mini-slot Numbering Examples	102
B.6.2.12.3	Transmission Time	102
B.6.2.12.4	Latency Considerations	102
B.6.2.12.5	Spreader-off Bursts for Maintenance on S-CDMA channel	102
B.6.2.12.6	Limiting the Number of Codes Assigned to a CM	102
B.6.2.13	S-CDMA Framer	102
B.6.2.13.1	Subframe Definition	102
B.6.2.13.2	Framer Operation	102
B.6.2.13.2.1	Rules for Preamble and Coded TCM Symbols	102
B.6.2.13.2.2	Rules for Uncoded Symbols and the Uncoded TCM Subsymbols	103
B.6.2.13.2.3	Subframe Example	103
B.6.2.13.2.4	Frame Transmission	103
B.6.2.14	Symbol Mapping	103
B.6.2.15	S-CDMA Spreader	103
B.6.2.15.1	Code Hopping	103
B.6.2.15.1.1	Code Hopping Mode 1	103
B.6.2.15.1.2	Code Hopping Mode 2	103
B.6.2.15.1.3	Code Hopping Generator	103
B.6.2.16	Transmit Pre-Equalizer	103
B.6.2.17	Spectral Shaping	105
B.6.2.17.1	Upstream Frequency Agility and Range	105
B.6.2.17.2	Spectrum Format	105
B.6.2.18	Relative Processing Delays	105
B.6.2.19	Transmit Power Requirements	106
B.6.2.19.1	TDMA Transmit Power Calculations	109
B.6.2.19.2	S-CDMA Transmit Power Calculations	110
B.6.2.19.2.1	S-CDMA Transmit power Calculations with Maximum Scheduled Codes Not Enabled	110
B.6.2.19.2.2	S-CDMA Transmit Power Calculations With Maximum Scheduled Codes Enabled	112
B.6.2.19.3	Transmit Power Step Size	114
B.6.2.19.4	Transmit Power Requirements for Multiple Transmit Channel mode Not Enabled	114
B.6.2.20	Burst Profiles	115
B.6.2.20.1	Ranging Offset	116
B.6.2.20.2	TDMA Reconfiguration Times	116

B.6.2.20.3	S-CDMA Reconfiguration Times	118
B.6.2.20.4	CM Timing Offsets When Changing Modulation Rate.....	118
B.6.2.21	Burst Timing Convention	118
B.6.2.22	Fidelity Requirements.....	118
B.6.2.22.1	Spurious Emissions	118
B.6.2.22.1.1	Adjacent Channel Spurious Emissions.....	120
B.6.2.22.1.2	Spurious Emissions in the Upstream Frequency Range	121
B.6.2.22.2	Spurious Emissions During Burst On/Off Transients	121
B.6.2.22.3	Modulation Error Ratio (MER).....	121
B.6.2.22.3.1	Definitions.....	122
B.6.2.22.3.2	Requirements.....	122
B.6.2.22.4	Filter Distortion.....	122
B.6.2.22.4.1	Amplitude	123
B.6.2.22.5	Carrier Phase Noise.....	123
B.6.2.22.6	Channel Frequency Accuracy	123
B.6.2.22.7	Modulation Rate Accuracy	123
B.6.2.22.8	Modulation Timing Jitter	123
B.6.2.22.8.1	Symbol Timing Jitter for TDMA Upstream Channels in Asynchronous Operation.....	123
B.6.2.22.8.2	Modulation Timing Jitter for Synchronous Operation.....	123
B.6.2.23	Upstream Demodulator Input Power Characteristics.....	123
B.6.2.24	Upstream Electrical Output from the CM.....	123
B.6.2.25	Upstream CM Transmitter Capabilities	124
B.6.2.25.1	Description of CM Upstream Transmit Channel Set Capabilities.....	124
B.6.3	Downstream	124
B.6.3.1	Downstream Protocol and Interleaving Support.....	124
B.6.3.2	Downstream Electrical Input to CM.....	125
B.6.3.3	CM BER Performance	125
B.6.3.3.1	64-QAM.....	125
B.6.3.3.1.1	64-QAM CM BER Performance	125
B.6.3.3.1.2	64-QAM Image Rejection Performance.....	126
B.6.3.3.1.3	64-QAM Adjacent Channel Performance.....	126
B.6.3.3.2	256-QAM.....	126
B.6.3.3.2.1	256-QAM CM BER Performance	126
B.6.3.3.2.2	256-QAM Image Rejection Performance	126
B.6.3.3.2.3	256-QAM Adjacent Channel Performance.....	126
B.6.3.4	Downstream Multiple Receiver Capabilities	126
B.6.3.4.1	Receive Module Parameters.....	126
B.6.3.4.2	Receive Channel Parameters.....	127
B.6.3.4.3	Standard Receive Channel Profile.....	127
B.6.3.4.4	Example Manufacturer Receive Channel Profile.....	127
B.6.3.4.5	Reconfiguration of CM Receive Channels.....	128
B.6.3.5	Non-Synchronous DS Channel Support	128

Annex C (normative): MPEG Header Synchronization and Recovery129

C.1 MPEG Header Synchronization and Recovery in the North American Technology Option.....129

C.2 MPEG Header Synchronization and Recovery in the European Technology Option.....129

Annex D (informative): Example Preamble Sequence Introduction130

D.1 Example Preamble Sequence

Annex E (informative): S-CDMA Framing.....132

E.1 Coded Subsymbol Numbering

E.2 Uncoded Subsymbol Numbering

E.3 Framing Output Numbering

E.4 Comments.....

Annex F (informative): Ambient Temperature and Wind Loading Effects134