



**Access, Terminals, Transmission and Multiplexing (ATTM);
Third Generation Transmission Systems for
Interactive Cable Television Services - IP Cable Modems;
Part 4: MAC and Upper Layer Protocols;
DOCSIS 3.0**

[ETSI EN 302 878-4 V1.1.1 \(2011-11\)](https://standards.iteh.ai/catalog/standards/etsi/783a65dc-acee-413e-b817-2562a27e8b04/etsi-en-302-878-4-v1-1-1-2011-11)

<https://standards.iteh.ai/catalog/standards/etsi/783a65dc-acee-413e-b817-2562a27e8b04/etsi-en-302-878-4-v1-1-1-2011-11>

Reference

DEN/ATTM-003006-4

Keywordsaccess, broadband, cable, data, IP, IPCable,
modem**ETSI**650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iteh Standards
(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2011.
All rights reserved.

DECTTM, PLUGTESTSTM, UMTSTM and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPPTM and LTETM are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	22
Foreword.....	22
1 Scope	23
1.1 Introduction and Purpose.....	23
1.2 Requirements.....	23
1.3 Conventions.....	23
2 References	23
2.1 Normative references	24
2.2 Informative references.....	27
3 Definitions and abbreviations.....	27
3.1 Definitions.....	27
3.2 Abbreviations	37
4 Void.....	41
5 Overview and Theory of Operations	41
5.1 DOCSIS 3.0 MULPI Key Features	41
5.2 Technical Overview	42
5.2.1 CMTS and CM Models.....	42
5.2.1.1 CMTS Model	42
5.2.1.1.1 Types of CMTS	42
5.2.1.1.2 CMTS Internal Forwarding Model.....	44
5.2.1.1.3 CMTS MAC Domain	45
5.2.1.2 CM Model	46
5.2.2 DOCSIS MAC Operation	46
5.2.2.1 QoS	46
5.2.2.1.1 Individual and Group Service Flows	47
5.2.2.2 Channel Bonding.....	48
5.2.2.2.1 Downstream Channel Bonding.....	48
5.2.2.2.2 Upstream Channel Bonding.....	49
5.2.2.3 Autonomous Load Balancing.....	51
5.2.3 Multicast Operation	51
5.2.4 Network and Higher Layer Protocols	52
5.2.5 CM and CPE Provisioning and Management	52
5.2.5.1 Initialization, Provisioning and Management of CMs	52
5.2.5.2 Initialization, Provisioning and Management of CPEs	53
5.2.6 Relationship to the Physical HFC Plant Topology	53
5.2.6.1 RF Topology Configuration.....	53
5.2.6.2 Frequency Assignment.....	55
5.2.7 Cable Service Group (CM-SG)	56
5.2.7.1 MAC Domain Channel Assignment.....	57
5.2.7.2 Multiple MAC Domains per Fibre Node	58
5.2.7.3 MAC Domain Downstream and Upstream Service Groups.....	59
5.2.7.4 Channel Bonding Topology Considerations	59
5.2.8 CMTS Downstream Service Model Example.....	60
6 Media Access Control Specification	61
6.1 Introduction	61
6.1.1 Overview	61
6.1.2 Definitions	61
6.1.2.1 MAC-Sublayer Domain	61
6.1.2.2 MAC Service Access Point.....	62
6.1.2.3 Service Flows	62
6.1.2.4 Upstream Intervals, Mini-Slots and 6,25-Microsecond Increments.....	62
6.1.2.4.1 TDMA mode	62
6.1.2.4.2 S-CDMA mode.....	63

6.1.2.5	MAC Frame	63
6.1.2.6	Logical Upstream Channels	63
6.1.2.6.1	Type 3 Logical Upstreams.....	64
6.1.2.6.2	Type 4 Logical Upstreams.....	64
6.1.3	Future Use.....	65
6.2	MAC Frame Formats.....	65
6.2.1	Generic MAC Frame Format	65
6.2.1.1	PMD Overhead	65
6.2.1.2	MAC Frame Transport.....	66
6.2.1.3	Ordering of Bits and Octets.....	66
6.2.1.3.1	Representing Negative Numbers	67
6.2.1.3.2	Type-Length-Value Fields.....	67
6.2.1.4	MAC Header Format.....	67
6.2.1.5	Data PDU	68
6.2.2	Packet-Based MAC Frames	69
6.2.2.1	Packet PDU and Isolation Packet PDU.....	69
6.2.3	ATM Cell MAC Frames	70
6.2.4	MAC-Specific Headers	70
6.2.4.1	Timing Header	70
6.2.4.2	MAC Management Header	71
6.2.4.3	Request Frame.....	71
6.2.4.4	Fragmentation Header.....	72
6.2.4.5	Queue-depth Based Request Frame	73
6.2.4.6	Concatenation Header	73
6.2.5	Extended MAC Headers	74
6.2.5.1	Piggyback Requests	76
6.2.5.2	Request Extended Header	76
6.2.5.3	Fragmentation Extended Header.....	76
6.2.5.4	Service Flow Extended Header.....	77
6.2.5.4.1	Payload Header Suppression Header.....	77
6.2.5.4.2	Unsolicited Grant Synchronization Header.....	78
6.2.5.5	BP_UP2 Extended Header.....	78
6.2.5.6	Downstream Service Extended Header.....	78
6.2.5.7	DPV Extended Header	80
6.3	Segment Header Format	80
6.4	MAC Management Messages.....	81
6.4.1	MAC Management Message Header	81
6.4.2	Time Synchronization (SYNC).....	84
6.4.3	Upstream Channel Descriptor (UCD).....	84
6.4.3.1	Example of UCD Encoded TLV Data.....	92
6.4.4	Upstream Bandwidth Allocation Map (MAP).....	93
6.4.5	Ranging Request Messages	95
6.4.5.1	Ranging Request (RNG-REQ)	97
6.4.5.2	Initial Ranging Request (INIT-RNG-REQ)	98
6.4.5.3	Bonded Initial Ranging Request (B-INIT-RNG-REQ).....	99
6.4.5.3.1	Capability Flags.....	99
6.4.6	Ranging Response (RNG-RSP)	100
6.4.6.1	Encodings.....	101
6.4.6.2	Example of TLV Data.....	102
6.4.6.3	Transmit Equalization Encodings	103
6.4.6.4	RNG-RSP Channel Overrides.....	103
6.4.6.5	Upstream Channel Adjustments.....	104
6.4.6.6	T4 Timeout Multiplier.....	104
6.4.7	Registration Request Messages.....	105
6.4.7.1	Registration Request (REG-REQ)	106
6.4.7.2	Multipart Registration Request (REG-REQ-MP)	106
6.4.8	Registration Response Messages	107
6.4.8.1	Registration Response (REG-RSP).....	109
6.4.8.2	Multipart Registration Response (REG-RSP-MP).....	110
6.4.8.3	Encodings.....	111
6.4.8.3.1	Modem Capabilities.....	111
6.4.8.3.2	DOCSIS 1.0 Service Class Data.....	111

6.4.9	Registration Acknowledge (REG-ACK)	112
6.4.10	Upstream Channel Change Request (UCC-REQ).....	113
6.4.11	Upstream Channel Change Response (UCC-RSP).....	114
6.4.12	Dynamic Service Addition - Request (DSA-REQ).....	114
6.4.12.1	CM-Initiated Dynamic Service Addition	115
6.4.12.2	CMTS-Initiated Dynamic Service Addition.....	115
6.4.13	Dynamic Service Addition - Response (DSA-RSP)	116
6.4.13.1	CM-Initiated Dynamic Service Addition	117
6.4.13.2	CMTS-Initiated Dynamic Service Addition.....	117
6.4.14	Dynamic Service Addition - Acknowledge (DSA-ACK)	117
6.4.15	Dynamic Service Change - Request (DSC-REQ).....	118
6.4.16	Dynamic Service Change - Response (DSC-RSP)	120
6.4.17	Dynamic Service Change - Acknowledge (DSC-ACK)	121
6.4.18	Dynamic Service Deletion - Request (DSD-REQ).....	122
6.4.19	Dynamic Service Deletion - Response (DSD-RSP).....	122
6.4.20	Dynamic Channel Change - Request (DCC-REQ)	123
6.4.20.1	Encodings.....	124
6.4.20.1.1	Upstream Channel ID	124
6.4.20.1.2	Downstream Parameters	124
6.4.20.1.3	Initialization Technique	125
6.4.20.1.4	UCD Substitution	126
6.4.20.1.5	Security Association Identifier (SAID) Substitution	127
6.4.20.1.6	Service Flow Substitutions	127
6.4.20.1.7	CMTS MAC Address	128
6.4.21	Dynamic Channel Change - Response (DCC-RSP).....	129
6.4.21.1	Encodings.....	129
6.4.21.1.1	CM Jump Time.....	130
6.4.22	Dynamic Channel Change - Acknowledge (DCC-ACK)	130
6.4.23	Device Class Identification Request (DCI-REQ)	131
6.4.24	Device Class Identification Response (DCI-RSP).....	132
6.4.25	Upstream Transmitter Disable (UP-DIS).....	132
6.4.26	Test Request (TST-REQ).....	134
6.4.27	Downstream Channel Descriptor (DCD).....	135
6.4.28	MAC Domain Descriptor (MDD).....	135
6.4.28.1	TLV Encodings	136
6.4.28.1.1	Downstream Active Channel List TLV	136
6.4.28.1.2	MAC Domain Downstream Service Group (MD-DS-SG) TLV	137
6.4.28.1.3	Downstream Ambiguity Resolution Frequency List TLV.....	138
6.4.28.1.4	Receive Channel Profile Reporting Control TLV	138
6.4.28.1.5	IP Initialization Parameters TLV	139
6.4.28.1.6	Early Authentication and Encryption (EAE) Enable/Disable TLV	139
6.4.28.1.7	Upstream Active Channel List TLV	140
6.4.28.1.8	Upstream Ambiguity Resolution Channel List TLV	140
6.4.28.1.9	Upstream Frequency Range TLV	141
6.4.28.1.10	Symbol Clock Locking Indicator	141
6.4.28.1.11	CM-STATUS Event Control	141
6.4.28.1.12	Upstream Transmit Power Reporting	142
6.4.28.1.13	DSG DA-to-DSID Association Entry	142
6.4.28.1.14	CM-STATUS Event Enable for Non-Channel-Specific Events	142
6.4.28.1.15	Extended Upstream Transmit Power Support	143
6.4.29	Dynamic Bonding Change Request (DBC-REQ)	143
6.4.30	Dynamic Bonding Change Response (DBC-RSP)	144
6.4.31	Dynamic Bonding Change Acknowledge (DBC-ACK)	146
6.4.32	DOCSIS Path Verify Request (DPV-REQ)	146
6.4.33	DOCSIS Path Verify Response (DPV-RSP)	148
6.4.34	Status Report (CM-STATUS).....	148
6.4.34.1	TLV Encodings	149
6.4.35	CM Control Request (CM-CTRL-REQ).....	149
6.4.35.1	TLV Encodings	150
6.4.36	CM Control Response (CM-CTRL-RSP).....	150
7	Media Access Control Protocol Operation.....	151

7.1	Timing and Synchronization	151
7.1.1	Global Timing Reference.....	151
7.1.2	CM Synchronization	152
7.1.3	Ranging.....	152
7.1.3.1	Broadcast Initial Ranging.....	152
7.1.3.2	Unicast Initial Ranging	153
7.1.4	Timing Units and Relationships.....	153
7.1.4.1	TDMA Timing Units and Relationships	153
7.1.4.1.1	Mini-Slot Capacity	153
7.1.4.1.2	Mini-Slot Numbering	154
7.1.4.2	S-CDMA Timing Units and Relationships	154
7.1.4.2.1	Mini-Slot Capacity	154
7.1.4.2.2	Mini-Slot Numbering	154
7.2	Upstream Data Transmission	155
7.2.1	Upstream Bandwidth Allocation.....	155
7.2.1.1	The Allocation MAP MAC Management Message	156
7.2.1.2	Information Elements.....	156
7.2.1.2.1	The Request IE	156
7.2.1.2.2	The Request/Data IE.....	157
7.2.1.2.3	The Initial Maintenance IE	157
7.2.1.2.4	The Station Maintenance IE	157
7.2.1.2.5	Short and Long Data Grant IEs	157
7.2.1.2.6	Data Acknowledge IE.....	158
7.2.1.2.7	Expansion IE	158
7.2.1.2.8	Null IE	158
7.2.1.2.9	Advanced PHY Short and Long Data Grant IEs	158
7.2.1.2.10	Advanced PHY Unsolicited Grant IE	159
7.2.1.3	Requesting with Multiple Transmit Channel Mode Disabled	159
7.2.1.4	Requesting with Multiple Transmit Channel Mode Enabled	160
7.2.1.4.1	Request Mechanisms for Segment Header OFF Service Flows	160
7.2.1.4.2	Request Mechanisms for Segment Header ON Service Flows	160
7.2.1.5	Information Element Feature Usage Summary	165
7.2.1.6	Map Transmission and Timing	165
7.2.1.7	Protocol Example	166
7.2.1.8	MAP Generation Example - Two Logical Upstreams.....	167
7.2.2	Upstream Transmission and Contention Resolution.....	168
7.2.2.1	Contention Resolution Overview	168
7.2.2.1.1	Contention Resolution with Multiple Transmit Channel Mode Disabled	168
7.2.2.1.2	Contention Resolution with Multiple Transmit Channel Mode Enabled.....	169
7.2.2.2	Transmit Opportunities	171
7.2.2.3	CM Bandwidth Utilization.....	172
7.2.3	Upstream Service Flow Scheduling Services	172
7.2.3.1	Unsolicited Grant Service	173
7.2.3.2	Real-Time Polling Service	173
7.2.3.3	Unsolicited Grant Service with Activity Detection.....	174
7.2.3.4	Non-Real-Time Polling Service	175
7.2.3.5	Best Effort Service	175
7.2.3.6	Other Services	175
7.2.3.6.1	Committed Information Rate (CIR).....	175
7.2.3.7	Parameter Applicability for Upstream Service Scheduling.....	175
7.2.3.8	CM Transmit Behavior	176
7.2.4	Continuous Concatenation and Fragmentation	176
7.2.5	Pre-3.0 DOCSIS Concatenation and Fragmentation.....	177
7.2.5.1	Concatenation.....	177
7.2.5.2	Fragmentation	178
7.2.5.2.1	CM Fragmentation Support.....	180
7.2.5.2.2	CMTS Fragmentation Support	182
7.2.5.2.3	Fragmentation Example.....	183
7.2.5.2.4	Pre-Registration Fragmentation.....	185
7.2.5.2.5	Considerations for Concatenated Packets and Fragmentation.....	186
7.3	Upstream - Downstream Channel Association within a MAC Domain.....	186
7.3.1	Primary Downstream Channels	186

7.3.2	MAP and UCD Messages	187
7.3.3	Multiple MAC Domains	187
7.4	DSID Definition	187
7.5	Quality of Service.....	188
7.5.1	Concepts	188
7.5.1.1	Service Flows	188
7.5.1.2	Classifiers.....	190
7.5.1.2.1	Upstream and Downstream QoS Classifiers.....	190
7.5.1.2.2	Upstream Drop Classifiers.....	192
7.5.2	Object Model	192
7.5.3	Service Classes	194
7.5.4	Authorization	195
7.5.5	States of Service Flows.....	195
7.5.5.1	Deferred Service Flows.....	195
7.5.5.1.1	Provisioned Service Flows	196
7.5.5.1.2	Authorized Service Flows	196
7.5.5.2	Admitted Service Flows	196
7.5.5.3	Active Service Flows	197
7.5.6	Service Flows and Classifiers	197
7.5.6.1	Policy-Based Classification and Service Classes	198
7.5.7	General Operation.....	198
7.5.7.1	Static Operation.....	198
7.5.7.2	Dynamic Service Flow Creation - CM Initiated.....	199
7.5.7.3	Dynamic Service Flow Creation - CMTS Initiated.....	200
7.5.7.4	Dynamic Service Flow Modification and Deletion.....	200
7.5.8	QoS Support for Joined IP Multicast Traffic	201
7.5.8.1	Overview.....	202
7.5.8.2	Group Configuration and Group QoS Configuration Tables	203
7.5.8.3	Instantiating Group Classifier Rules and Group Service Flows.....	204
7.5.8.3.1	Examples of GCR and GSF Instantiation.....	206
7.5.8.4	Default Group Service Flows	212
7.5.8.5	Service Class QoS Parameter Changes	212
7.5.8.6	Group QoS Configuration Changes	212
7.5.9	Other Multicast and Broadcast Traffic.....	213
7.6	Downstream Traffic Priority	213
7.6.1	Traffic Priority Ordering and Mapping to CM Output Queues.....	213
7.7	Payload Header Suppression	214
7.7.1	Overview	214
7.7.1.1	PHSI-indexed PHS.....	215
7.7.1.2	DSID-indexed PHS	215
7.7.2	Example Applications.....	216
7.7.3	Operation	216
7.7.4	Signalling.....	218
7.7.4.1	Signalling PHSI-Indexed Payload Header Suppression.....	218
7.7.4.2	Signalling DSID-Indexed Payload Header Suppression	219
7.7.5	Payload Header Suppression Examples.....	220
7.7.5.1	Upstream Example	220
7.7.5.2	Downstream Example	221
7.7.5.3	DSID-Indexed Multicast Example	222
7.8	Data Link Encryption Support.....	223
7.8.1	MAC Messages.....	223
7.8.2	Framing.....	223
7.8.3	Multiple Transmit Channel Mode Operation and Packet Encryption.....	223
8	Channel Bonding.....	223
8.1	Upstream and Downstream Common Aspects	224
8.1.1	Service Flow Assignment	224
8.1.2	CMTS Bonding and Topology Requirements	227
8.2	Downstream Channel Bonding.....	228
8.2.1	Multiple Downstream Channel Overview	228
8.2.2	CMTS Downstream Bonding Operation.....	229
8.2.3	Sequenced Downstream Packets.....	229