



**Intelligent Transport Systems (ITS);
Road Transport and Traffic Telematics (RTTT);
Dedicated Short Range Communications (DSRC);
Part 1: Technical characteristics and test methods for High
Data Rate (HDR) data transmission equipment operating in
the 5,8 GHz Industrial, Scientific and Medical (ISM) band**

<https://standards.iteh.ai/catalog/standards/etsi/bef6f81f-df28-48a4-afcd-5c7a737ba5aa/etsi-es-200-674-1-v2-4-1-2013-05>

<https://standards.iteh.ai/catalog/standards/etsi/bef6f81f-df28-48a4-afcd-5c7a737ba5aa/etsi-es-200-674-1-v2-4-1-2013-05>

Reference

RES/ITS-00261

Keywords

DSRC, ITS, protocol, testing

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2013.
All rights reserved.

DECTTM, PLUGTESTSTM, UMTSTM and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPPTM and LTETM are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	11
Foreword.....	11
Introduction	11
1 Scope	13
2 References	13
2.1 Normative references	13
2.2 Informative references	14
3 Definitions, symbols and abbreviations	14
3.1 Definitions	14
3.1.1 Layer 1 definitions	14
3.1.2 Layer 2 definitions	18
3.1.3 Layer 7 definitions	18
3.1.4 Security definitions	18
3.2 Definitions from other standards	19
3.2.1 Layer 2 related definitions	19
3.2.2 Layer 7 related definitions	19
3.3 Symbols	19
3.4 Abbreviations	20
4 General	21
4.1 Presentation of equipment for testing purposes	21
4.1.1 Choice of model for testing	21
4.1.2 Choice of operating frequencies	21
4.1.3 Testing of equipment with or without a permanent external RF port	21
4.1.4 Equipment with a permanent internal RF port	22
4.1.5 Equipment with a temporary RF port	22
4.1.6 Antennas	22
4.2 Mechanical and electrical design	22
4.2.1 General	22
4.2.2 Controls	22
4.2.3 Marking	22
4.2.3.1 Equipment identification	22
4.2.4 Receiver data squelch	22
4.3 Declarations by the applicant	23
4.4 Auxiliary test equipment	23
4.5 Interpretation of the measurement results	23
5 Test conditions, power sources and ambient temperatures	23
5.1 Normal and extreme test conditions	23
5.2 External test power source	23
5.3 Normal test conditions	24
5.3.1 Normal temperature and humidity	24
5.3.2 Normal test power source	24
5.3.2.1 Mains voltage	24
5.3.2.2 Regulated lead-acid battery power sources	24
5.3.2.3 Other power sources	24
5.4 Extreme test conditions	24
5.4.1 Extreme temperatures	24
5.4.1.1 Procedure for tests at extreme temperatures	24
5.4.1.1.1 Procedure for equipment designed for continuous transmit operation	24
5.4.1.1.2 Procedure for equipment designed for intermittent transmit operation	25
5.4.1.2 Extreme temperature ranges	25
5.4.2 Extreme test source voltages	25
5.4.2.1 Mains voltage	25
5.4.2.2 Lead-acid battery, regulated power sources	25

5.4.2.3	Power sources using other types of batteries.....	26
5.4.2.4	Other power sources.....	26
6	General conditions.....	26
6.1	Test signals and test modulation.....	26
6.1.1	Normal test signals (wanted and unwanted signals)	26
6.1.1.1	Signals for bit stream measurements.....	27
6.1.1.2	Signal for messages.....	27
6.2	Modes of operation of the transmitter	27
6.3	Encoder for receiver measurements	28
6.4	Facilities for access	28
6.4.1	Analogue access.....	28
6.4.2	Access points for data stream measurement	28
6.4.3	Coupling arrangements	29
6.4.3.1	Arrangements for measurements with continuous bit streams	29
6.4.3.2	Arrangement for measurements with messages	29
6.4.4	Message received indicator.....	29
6.5	Test sites and general arrangements for radiated measurements	29
6.6	Artificial antenna.....	29
6.7	Test fixture	29
6.7.1	Calibration	30
6.7.2	Mode of use	30
6.8	Specific RSU test conditions	30
6.8.1	Antenna characteristics	30
6.8.2	Signal modulation.....	31
6.8.3	Data coding.....	31
6.8.4	Bit rate	31
6.8.5	Angular E.I.R.P. mask	31
6.8.6	Wake-up trigger for OBU.....	31
6.9	Specific OBU test conditions	32
6.9.1	Antenna polarization.....	32
6.9.2	Modulation on carrier	32
6.9.3	Data coding.....	32
6.9.4	Use of sidebands	32
6.9.5	Responding bit rate and sub-carrier frequencies	32
6.9.6	Antenna characteristics	32
7	Layer 1: Methods of measurement and limits for road side unit transmitter parameters	33
7.1	Generalities.....	33
7.2	Equivalent isotropically radiated power (e.i.r.p.)	33
7.2.1	Definition.....	33
7.2.2	Method of measurement	33
7.2.3	Limits.....	34
7.3	Frequency error	34
7.3.1	Definition.....	34
7.3.2	Method of measurement	34
7.3.3	Limits.....	34
7.4	Transmitter spectrum mask	34
7.4.1	Definition.....	34
7.4.2	Method of measurement	35
7.4.3	Limits.....	35
7.5	Modulation depth	36
7.5.1	Definition.....	36
7.5.2	Method of measurement	36
7.5.3	Limits.....	36
7.6	Eye pattern.....	37
7.6.1	Definition.....	37
7.6.2	Method of measurement	37
7.6.3	Limits.....	38
7.7	Spurious emissions	38
7.7.1	Definition.....	38
7.7.2	Measuring receiver	38

7.7.3	Method of measurement conducted spurious emission.....	38
7.7.4	Method of measurement cabinet spurious radiation	39
7.7.5	Method of measurement radiated spurious emission	40
7.7.6	Limits.....	40
8	Layer 1: Methods of measurement and limits for road side unit receiver parameters	40
8.1	Maximum useable sensitivity	41
8.1.1	Definition.....	41
8.1.2	Method of measurements under normal and extreme test conditions	41
8.1.2.1	Test arrangement for equipment with integral antenna	41
8.1.2.2	Test arrangement for equipment with antenna connector	42
8.1.2.3	Test procedure for continuous bit streams	43
8.1.2.4	Test procedure for messages	43
8.1.3	Limits.....	43
8.2	Error behaviour at high wanted input signals	43
8.2.1	Definition.....	43
8.2.2	Method of measurement	43
8.2.3	Limits.....	44
8.3	Degradation measurements	44
8.3.1	Definition.....	44
8.3.2	General conditions	44
8.3.3	Co-channel rejection	45
8.3.3.1	Definition	45
8.3.3.2	Method of measurement.....	45
8.3.3.3	Limits	46
8.3.4	Adjacent channel selectivity	46
8.3.4.1	Definition	46
8.3.4.2	Method of measurement	46
8.3.4.3	Limits	47
8.3.5	Spurious response rejection and blocking/desensitization	47
8.3.5.1	Definition	47
8.3.5.2	Method of measurement.....	47
8.3.5.3	Limits	48
8.3.6	Intermodulation response rejection.....	48
8.3.6.1	Definition	48
8.3.6.2	Method of measurement	48
8.3.6.3	Limits	49
8.4	Spurious emissions	49
8.4.1	Definition.....	49
8.4.2	Method of measurement - conducted spurious emissions.....	49
8.4.3	Method of measurement - cabinet radiation	50
8.4.4	Method of measurement - radiated spurious components.....	50
8.4.5	Limits.....	51
9	Layer 1: Method of measurements and limits for on-board units	51
9.1	OBU sensitivity	51
9.1.1	Definition.....	51
9.1.2	Method of measurement	51
9.1.3	Limits.....	52
9.2	On board unit access.....	52
9.2.1	Definition.....	52
9.2.2	Method of measurement	52
9.2.3	Limits.....	54
9.3	Transponder conversion gain	54
9.3.1	Definition.....	54
9.3.2	Method of measurement	54
9.3.3	Limits.....	56
9.4	OBU maximum radiated subcarrier.....	56
9.4.1	Definition.....	56
9.4.2	Method of measurement	56
9.4.3	Limits.....	56
9.5	OBU frequency error.....	57

9.5.1	Definition	57
9.5.2	Method of measurement	57
9.5.3	Limits	58
9.6	OBU spurious radiation	58
9.6.1	Definition	58
9.6.2	Method of measurement	58
9.6.3	Limits	59
10	Layer 2 parameters and procedures	59
10.1	General conditions	59
10.2	Frame Structure	59
10.2.1	Definition	59
10.2.2	Limits	60
10.2.2.1	Validity of frames	60
10.2.2.2	Bit order	60
10.2.2.3	Transparency	60
10.2.2.4	Frame length	60
10.3	Opening and closing flags	60
10.3.1	Definition	60
10.3.2	Limits	61
10.4	LPDU	61
10.4.1	Definition	61
10.4.2	Limits	61
10.5	Frame check sequence	62
10.5.1	Definition	62
10.5.2	Limits	62
10.6	Frame transmission procedure	62
10.7	Frame reception procedure	62
10.8	Specific Road Side Unit parameters and procedures	62
10.8.1	Link ID allocation	62
10.8.2	Frame transmission	63
10.8.3	Frame reception	63
10.9	Specific On Board Units (OBUs) parameters and functions	63
10.9.1	Link ID allocation	63
10.9.2	Frame transmission	63
10.9.3	Frame reception	63
11	Layer 7 parameters and procedures	64
11.1	General conditions	64
11.2	General protocol rules	64
11.2.1	Protocol data unit formats	64
11.2.2	Concatenation	64
11.2.3	Sessions	64
11.3	Protocol messages and parameters: ASN.1 definitions	65
11.4	Encoding rules	69
11.4.1	Encoding of the primitive types	70
11.4.1.1	BIT STRING type	70
11.4.1.2	INTEGER type	70
11.4.2	Encoding of the structured types	70
11.4.2.1	SEQUENCE type	70
11.4.2.2	SEQUENCE OF type	70
11.4.2.3	CHOICE type	70
11.4.2.4	SET type	70
11.4.2.5	SET OF type	70
11.5	RSU specific parameters and procedures	71
11.5.1	Application protocol data unit formats	71
11.5.2	Open-Rq directive	71
11.5.2.1	Definition	71
11.5.2.2	Method of measurement	71
11.5.2.3	Limits	72
11.5.3	Close-Rq directive	72
11.5.3.1	Definition	72

11.5.3.2	Method of measurement.....	72
11.5.3.3	Limits	72
11.5.4	Select-TBA-Id-Rq directive.....	72
11.5.4.1	Definition	72
11.5.4.2	Method of measurement.....	72
11.5.4.3	Limits	72
11.5.5	Read-Display-Type-Rq directive	73
11.5.5.1	Definition	73
11.5.5.2	Method of measurement.....	73
11.5.5.3	Limits	73
11.5.6	Read-Master-Core-Rq directive.....	73
11.5.6.1	Definition	73
11.5.6.2	Method of measurement.....	73
11.5.6.3	Limits	73
11.5.7	Get-Master-Record-Rq directive	73
11.5.7.1	Definition	73
11.5.7.2	Method of measurement.....	73
11.5.7.3	Limits	74
11.5.8	Read-Appl-Core-Rq directive	74
11.5.8.1	Definition	74
11.5.8.2	Method of measurement.....	74
11.5.8.3	Limits	74
11.5.9	Write-Appl-Core-Rq directive	74
11.5.9.1	Definition	74
11.5.9.2	Method of measurement.....	74
11.5.9.3	Limits	74
11.5.10	Write-Appl-Core-Conf-Rq directive.....	75
11.5.10.1	Definition	75
11.5.10.2	Method of measurement.....	75
11.5.10.3	Limits	75
11.5.11	Write-Data-To-External-Rq directive	75
11.5.11.1	Definition	75
11.5.11.2	Method of measurement.....	76
11.5.11.3	Limits	76
11.5.12	Read-Data-From-External-Rq directive.....	76
11.5.12.1	Definition	76
11.5.12.2	Method of measurement.....	76
11.5.12.3	Limits	76
11.5.13	Read-Appl-Record-Rq directive	76
11.5.13.1	Definition	76
11.5.13.2	Method of measurement.....	77
11.5.13.3	Limits	77
11.5.14	Write-Appl-Record-Curr-Rq directive.....	77
11.5.14.1	Definition	77
11.5.14.2	Method of measurement.....	77
11.5.14.3	Limits	77
11.5.15	Write-Appl-Record-Curr-Conf-Rq directive	77
11.5.15.1	Definition	77
11.5.15.2	Method of measurement.....	77
11.5.15.3	Limits	78
11.5.16	Write-Appl-Record-Next-Rq directive	78
11.5.16.1	Definition	78
11.5.16.2	Method of measurement.....	78
11.5.16.3	Limits	78
11.5.17	Write-Appl-Record-Next-Conf-Rq directive	78
11.5.17.1	Definition	78
11.5.17.2	Method of measurement.....	78
11.5.17.3	Limits	79
11.5.18	Set-UIF-Rq directive.....	79
11.5.18.1	Definition	79
11.5.18.2	Method of measurement.....	79
11.5.18.3	Limits	79