

**Speech and multimedia Transmission Quality (STQ);  
Transmission Requirements for IP-based Narrowband and  
Wideband Home Gateways and Other Media Gateways from a  
QoS Perspective as Perceived by the User**

---

**iTeh Standards**  
**(<https://standards.iteh.ai>)**  
**Document Preview**

[ETSI ES 202 718 V1.1.1 \(2011-10\)](https://standards.iteh.ai/catalog/standards/etsi/d70843b0-dc3e-432d-a14f-1485dcca1ffe/etsi-es-202-718-v1-1-1-2011-10)

<https://standards.iteh.ai/catalog/standards/etsi/d70843b0-dc3e-432d-a14f-1485dcca1ffe/etsi-es-202-718-v1-1-1-2011-10>



---

Reference

DES/STQ-00145

---

Keywords

QoS, speech

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

(<https://standards.iteh.ai>)  
Document Preview

---

**Important notice**

---

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

[http://portal.etsi.org/chaicor/ETSI\\_support.asp](http://portal.etsi.org/chaicor/ETSI_support.asp)

---

**Copyright Notification**

---

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2011.  
All rights reserved.

DECT<sup>TM</sup>, PLUGTESTS<sup>TM</sup>, UMTS<sup>TM</sup> and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.  
3GPP<sup>TM</sup> and LTE<sup>TM</sup> are Trade Marks of ETSI registered for the benefit of its Members and  
of the 3GPP Organizational Partners.  
GSM<sup>®</sup> and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	5
Foreword.....	5
Introduction .....	5
1 Scope .....	6
2 References .....	6
2.1 Normative references .....	6
2.2 Informative references.....	8
3 Definitions and abbreviations.....	8
3.1 Definitions .....	8
3.2 Abbreviations .....	9
4 General considerations .....	9
4.1 Default Coding Algorithm.....	9
4.2 End-to-end considerations .....	9
4.3 Parameters to be investigated .....	10
4.3.1 Applicability of parameters to different MGWs .....	10
5 Test equipment .....	11
5.1 IP half channel measurement adaptor.....	11
5.2 Environmental conditions for tests.....	11
5.3 Accuracy of measurements and test signal generation .....	12
5.4 Network impairment simulation.....	12
6 Requirements and associated Measurement Methodologies .....	13
6.1 Test setup.....	13
6.1.1 Setup for Media Gateways with 4-wire interface .....	14
6.1.2 Setup for Media Gateways with 2-wire interface .....	14
6.1.3 Setup for Media Gateways with Wireless Access.....	15
6.1.4 Setup for IP-to-IP Media Gateways .....	15
6.1.5 Test Signal Levels.....	16
6.1.6 Background noise simulation.....	16
6.2 Coding independent parameters .....	16
6.2.1 Send Frequency response.....	16
6.2.2 Circuit Loudness Rating in Send .....	17
6.2.3 Linearity Range for CLR (SND).....	18
6.2.4 Send Distortion .....	19
6.2.5 Spurious Out-of-Band Signals in Send direction .....	20
6.2.6 Send Noise .....	20
6.2.7 Receive Frequency Response .....	20
6.2.8 Circuit Loudness Rating in Receive .....	21
6.2.9 Linearity Range for CLR (RCV) .....	22
6.2.10 Receive Distortion .....	23
6.2.11 Out-of-Band Signals Wideband to Narrowband Transcoding .....	24
6.2.12 Spurious Out-of-band Signals Narrowband to Wideband Transcoding.....	24
6.2.13 Minimum Activation Level and Sensitivity in Receive Direction .....	25
6.2.14 Receive Noise .....	25
6.2.15 Double Talk Performance .....	26
6.2.15.1 Attenuation Range in Send Direction during Double Talk $A_{H,S,dt}$ .....	26
6.2.15.2 Attenuation Range in Receive Direction during Double Talk $A_{H,R,dt}$ .....	28
6.2.15.3 Detection of Echo Components during Double Talk .....	29
6.2.15.4 Minimum Activation Level and Sensitivity of Double Talk Detection .....	31
6.2.16 Switching Characteristics .....	31
6.2.16.1 Activation in Send Direction.....	31
6.2.16.2 Activation in Receive Direction.....	32

6.2.16.3	Silence Suppression and Comfort Noise Generation .....	33
6.2.17	Background Noise Performance .....	33
6.2.17.1	Performance in Send Direction in the Presence of Background Noise .....	33
6.2.17.2	Quality of Speech with Background Noise .....	34
6.2.17.3	Quality of Background Noise Transmission (with Far End Speech) .....	35
6.2.17.4	Quality of Background Noise Transmission (with Near End Speech) .....	36
6.2.18	Quality of Echo Cancellation .....	36
6.2.18.1	Echo paths .....	36
6.2.18.2	Echo Performance According to ITU-T Recommendation G.168 .....	37
6.2.18.3	Terminal Coupling Loss (TCLw) .....	37
6.2.18.4	Temporal Echo Effects .....	38
6.2.18.5	Spectral Echo Attenuation .....	38
6.2.18.6	Occurrence of Artefacts .....	39
6.2.19	Variant Impairments; Network dependant .....	39
6.2.19.1	Clock Accuracy Send .....	39
6.2.19.2	Clock Accuracy Receive .....	39
6.2.19.3	Send Delay Variation .....	40
6.2.19.4	Delay versus Time Receive .....	40
6.2.19.5	Quality of Jitter buffer adjustment .....	40
6.2.20	Immunity to DTMF False Detection in Send Direction .....	40
6.3	Codec Specific Requirements .....	41
6.3.1	Send Delay .....	41
6.3.2	Receive delay .....	42
6.3.3	Delay for IP-to-IP MGW .....	44
6.3.4	Objective Listening Speech Quality MOS-LQO in Send direction .....	44
6.3.5	Objective Listening Quality MOS-LQO in Receive direction .....	45
6.3.5.1	Efficiency of Packet Loss Concealment (PLC) .....	47
6.3.5.2	Efficiency of Delay Variation Removal .....	47
<b>Annex A (informative):</b>	<b>Impulse Response of a Narrowband and Wideband DECT PP .....</b>	<b>48</b>
<b>Annex B (normative):</b>	<b>Test signal for immunity to DTMF false detection in send direction .....</b>	<b>50</b>
<b>Annex C (informative):</b>	<b>Bibliography .....</b>	<b>51</b>
History .....	ETSI ES 202 718 V1.1.1 (2011-10) .....	52

<https://standards.iteh.ai/catalog/standards/etsi/d70843b0-dc3e-432d-a14f-1485dcca1ffe/etsi-es-202-718-v1-1-1-2011-10>

---

# Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This final draft ETSI Standard (ES) has been produced by ETSI Technical Committee Speech and multimedia Transmission Quality (STQ), and is now submitted for the ETSI standards Membership Approval Procedure.

---

## Introduction

Traditionally, the analogue and digital telephones were interfacing switched-circuit 64 kbit/s PCM networks. With the fast growth of IP networks, packet-switched networks (VoIP) interfacing PSTN networks and mobile networks, as well as different types of IP-terminals, are being rapidly introduced. Different types of gateways are used to interconnect to such IP networks. Since the IP networks will be in many cases interworking with the traditional PSTN and private networks, many of the basic transmission requirements have to be harmonized between these different types of network from an end-to-end perspective, including specifications for the edge points.

The present document covers IP-based narrowband and wideband home gateways and other media gateways. It aims to enhance the interoperability and end-to-end quality.

In contrast to other standards which define minimum performance requirements, it is the intention of the present document to specify gateway equipment requirements which enable manufacturers and service providers to enable end-to-end speech performance as perceived by the user. These requirements are absolutely necessary to ensure a good quality, but they are not sufficient. They have to be combined with requirements (and associated relevant measurement methods) for other elements in the transmission chain (core IP network, PSTN, terminals), as well as for the whole mouth-to-ear transmission path.

---

# 1 Scope

The present document provides speech transmission performance requirements for narrowband and wideband media gateways from a QoS perspective as perceived by the user. Media gateways can be network or home based, they may include a transcoding function. The present document covers the following types of IP-based media gateways:

- ATA (Analogue Terminal Adapter), home gateway IP to POTS
- ITA (ISDN Terminal Adapter), home gateway IP to ISDN
- IAD (Integrated Access device), home router including ATA or ITA
- Network based ATA and ITA
- Carrier grade media gateway, network gateway IP to TDM
- IP-to-IP media gateway, network gateway with transcoding and/or other media processing

DECT interfaces of media gateways are excluded from the present document and should be measured according to the relevant DECT standards.

Interfaces of media gateways used together with terminals as a system (i.e. connected via Ethernet or with a proprietary interface) are excluded in the present document and should be measured according to the relevant terminal standard.

If a media gateway includes more than one interface type (e.g. POTS and ISDN), each interface has to be dealt with differently.

The requirements available in the present document will ensure a high compatibility with IP-and TDM-based fixed and wireless terminals and networks, including DECT and mobile terminals.

It is the aim to optimize interoperability, the listening and talking quality and the conversational performance. Related requirements and test methods are defined in the present document.

The present document does not apply to media gateways with 4-wire analogue interfaces.

---

## 2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

### 2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- |     |  |
|-----|--|
| [1] | ETSI EN 300 726: "Digital cellular telecommunications system (Phase 2+) (GSM); Enhanced Full Rate (EFR) speech transcoding (GSM 06.60)".   |
| [2] | ETSI TS 126 171: "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); AMR speech codec, wideband; General description (3GPP TS 26.171 version 6.0.0 Release 6)". |
| [3] | ITU-T Recommendation G.107: "The E-model, a computational model for use in transmission planning".   |

- [4] ITU-T Recommendation G.108: "Application of the E-model: A planning guide".
- [5] ITU-T Recommendation G.109: "Definition of categories of speech transmission quality".
- [6] ITU-T Recommendation G.100.1: "The use of the decibel and of relative levels in speechband telecommunications".
- [7] ITU-T Recommendation G.111: "Loudness Ratings (LRs) in an international connection".
- [8] ITU-T Recommendation G.122: "Influence of national systems on stability and talker echo in international connections".
- [9] ITU-T Recommendation G.711: "Pulse code modulation (PCM) of voice frequencies".
- [10] ITU-T Recommendation G.723.1: "Dual rate speech coder for multimedia communications transmitting at 5.3 and 6.3 kbit/s".
- [11] ITU-T Recommendation G.726: "40, 32, 24, 16 kbit/s Adaptive Differential Pulse Code Modulation (ADPCM)".
- [12] ITU-T Recommendation G.729: "Coding of speech at 8 kbit/s using conjugate-structure algebraic-code-excited linear prediction (CS-ACELP)".
- [13] ITU-T Recommendation G.729.1: "G.729-based embedded variable bit-rate coder: An 8-32 kbit/s scalable wideband coder bitstream interoperable with G.729".
- [14] ITU-T Recommendation G.1020: "Performance parameter definitions for quality of speech and other voiceband applications utilizing IP networks".
- [15] ITU-T Recommendation P.50: "Artificial voices".
- [16] ITU-T Recommendation P.340: "Transmission characteristics and speech quality parameters of hands-free terminals".
- [17] ITU-T Recommendation P.501: "Test signals for use in telephony".
- [18] ITU-T Recommendation P.502: "Objective test methods for speech communication systems using complex test signals".
- [19] ITU-T Recommendation P.862: "Perceptual evaluation of speech quality (PESQ): An objective method for end-to-end speech quality assessment of narrow-band telephone networks and speech codecs".
- [20] ISO 3 (1973): "Preferred numbers - Series of preferred numbers".
- [21] ITU-T Recommendation P.800.1: "Mean Opinion Score (MOS) terminology".
- [22] ETSI TS 102 971: "Access and Terminals (AT); Public Switched Telephone Network (PSTN); Harmonized specification of physical and electrical characteristics of a 2-wire analogue interface for short line interface".
- [23] ETSI ES 201 970: "Access and Terminals (AT); Public Switched Telephone Network (PSTN); Harmonized specification of physical and electrical characteristics at a 2-wire analogue presented Network Termination Point (NTP)".
- [24] ITU-T Recommendation G.168: "Digital network echo cancellers".
- [25] ITU-T Recommendation P.863: "Perceptual objective listening quality assessment".
- [26] ITU-T Recommendation G.722: "7 kHz audio-coding within 64 kbit/s".
- [27] ITU-T Recommendation G.722.1: "Low-complexity coding at 24 and 32 kbit/s for hands-free operation in systems with low frame loss".
- [28] ITU-T Recommendation G.722.2: "Wideband coding of speech at around 16 kbit/s using Adaptive Multi-Rate Wideband (AMR-WB)".