

ETSI ES 204 049 V1.1.1 (2026-01)



**Integrated broadband cable telecommunication networks
(CABLE);**

Standalone router specification

Document Preview

[ETSI ES 204 049 V1.1.1 \(2026-01\)](https://standards.iteh.ai/catalog/standards/etsi/00ad3f73-c1f5-47e5-aaa3-356e769ad3d3/etsi-es-204-049-v1-1-1-2026-01)

<https://standards.iteh.ai/catalog/standards/etsi/00ad3f73-c1f5-47e5-aaa3-356e769ad3d3/etsi-es-204-049-v1-1-1-2026-01>

Reference

DES/CABLE-0030

Keywords

CPE, IPCable, IPv4, IPv6, security

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed,
this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our
[Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2026.
All rights reserved.

Contents

Intellectual Property Rights	7
Foreword.....	7
Modal verbs terminology.....	7
1 Scope	8
2 References	8
2.1 Normative references	8
2.2 Informative references.....	11
3 Definition of terms, symbols and abbreviations.....	12
3.1 Terms.....	12
3.2 Symbols.....	14
3.3 Abbreviations	14
4 Theory of operation	16
4.1 General functions	16
4.2 Operational use cases	17
4.2.1 Introduction.....	17
4.2.2 sRouter as the Customer Edge Router (CER).....	17
4.3 TR-069 architecture.....	17
4.4 sRouter device management.....	18
4.5 Service discovery	18
4.5.1 Introduction.....	18
4.5.2 Multicast Domain Name System (mDNS).....	18
4.5.3 Universal Plug and Play (UPnP).....	19
4.6 Customer Edge Router Identification (CER-ID).....	20
4.7 IPv4 multicast NAPT	20
5 sRouter initialization	21
5.1 General requirements	21
5.2 Network Time Protocol (NTP).....	21
6 IPv4 provisioning	22
6.1 General requirements	22
6.2 DHCPv4 fields used by the sRouter	23
6.3 sRouter DHCPv4 server sub-element.....	24
6.3.1 Introduction.....	24
6.3.2 DHCPv4 server function goals	24
6.3.3 DHCPv4 server function system description	24
6.3.4 DHCPv4 server function requirements	24
6.4 Operator-facing IPv4 address release behavior	25
6.5 Customer-facing IPv4 address release behavior.....	26
7 Operator-facing IPv6 provisioning.....	26
7.1 General requirements	26
7.2 Obtain link-local address.....	27
7.3 Perform router discovery.....	27
7.4 Obtain IPv6 address and other configuration parameters.....	27
7.5 Use of T1 and T2 timers.....	30
7.6 Customer-facing IPv6 provisioning of CPE devices	30
7.6.1 Initial customer-facing IP interface provisioning	30
7.6.2 Additional customer-facing IP interfaces enabled after initial provisioning.....	32
7.6.3 SLAAC requirements for sRouter	32
7.6.3.1 General requirements	32
7.6.3.2 Local configuration of SLAAC options	33
7.6.4 DHCPv6 server requirements for sRouter	33
7.6.4.1 General requirements	33
7.6.4.2 Local configuration of DHCPv6 options.....	34

7.6.5	Prefix changes.....	34
7.7	Operator-facing IPv6 address release behavior	34
7.8	Customer-facing IPv6 address release behavior.....	35
7.9	CER-ID requirements.....	35
7.10	Router interface addressing using Link-ID.....	35
8	IPv4 data forwarding and NAT operation.....	36
8.1	Applicability.....	36
8.2	Introduction	36
8.2.1	Assumptions	36
8.2.2	Overview	36
8.3	System description	37
8.4	IPv4 Router sub-element.....	38
8.5	NAPT sub-element.....	39
8.5.1	General requirements.....	39
8.5.2	Dynamically triggered NAT translation	40
8.5.3	Application Layer Gateways (ALGs)	40
8.5.3.1	Introduction.....	40
8.5.3.2	ICMP error message ALG	40
8.5.3.3	FTP ALG	41
8.6	ARP sub-element.....	41
8.7	IPv4 multicast.....	41
8.7.1	Introduction.....	41
8.7.2	IGMP proxying.....	42
8.7.2.1	General requirements	42
8.7.2.2	IPv4 group membership database	42
8.7.2.3	IPv4 multicast forwarding.....	43
8.7.2.3.1	General requirements.....	43
8.7.2.3.2	IPv4 multicast forwarding example.....	43
8.8	IPv4/IPv6 coexistence technologies.....	45
8.8.1	Introduction.....	45
8.8.2	Dual-Stack Lite operation.....	45
8.8.3	Mapping of Address and Port (MAP).....	45
8.8.3.1	General requirements	45
8.8.3.2	MAP-E or MAP-T configuration via DHCP.....	46
8.8.4	Fragmentation	46
9	IPv6 data forwarding.....	47
9.1	Applicability and assumptions	47
9.2	Overview	47
9.3	System description	48
9.4	IPv6 multicast.....	49
9.4.1	General requirements.....	49
9.4.2	MLD proxying.....	50
9.4.3	IPv6 group membership database	50
9.4.4	IPv6 multicast forwarding	51
9.4.5	IPv6 multicast forwarding example.....	51
10	Quality of Service (QoS).....	53
10.1	General requirements	53
10.2	Downstream QoS operation	53
10.3	Upstream QoS operation	53
11	sRouter management	53
11.1	General requirements	53
11.2	sRouter TR-069 management interface requirements	54
11.3	sRouter SNMP management interface requirements.....	54
11.3.1	Introduction.....	54
11.3.2	ACS discovery	54
11.3.2.1	Introduction.....	54
11.3.2.2	TR-069 management server DHCP requirements.....	54
11.3.3	ACS selection	54
11.3.4	Dynamic ACS updates.....	54

11.3.5	TR-069 CWMP control and credentials.....	54
12	Security.....	54
12.1	Introduction	54
12.2	Traffic filtering.....	55
12.3	Management security on the operator-facing interface	55
12.3.1	General requirements.....	55
12.3.2	Management server authentication	56
12.3.3	sRouter authentication	56
12.4	Secure software update.....	57
12.4.1	Introduction.....	57
12.4.2	Secure software download	57
12.4.2.1	Introduction	57
12.4.2.2	TR-069 secure download	57
12.4.2.3	SNMP initiated secure software download	58
12.4.3	Secure boot	58
12.5	Physical protection of keys in the sRouter	58
12.6	Private data plane security on operator-facing interface	59
12.7	Community Wi-Fi® security.....	59
12.8	IPsec	59
13	Tunnel management and configuration	61
13.1	GRE requirements	61
Annex A (normative):	SNMP MIB objects supported by the sRouter	62
A.1	General requirements	62
A.2	sRouter interface numbering	62
A.3	sRouter ifTable requirements	63
A.4	sRouter ipNetToPhysicalTable requirements.....	65
A.5	CLAB-GRE-MIB	65
A.6	CLAB-GW-MIB	65
A.7	CLAB-WIFI-MIB	65
A.8	CLAB-ANI-DEV-MIB	65
Annex B (normative):	Provisioning and operational event messages	66
Annex C (normative):	TR-069 managed objects	68
C.1	General requirements	68
C.2	Profiles from TR-181	68
C.3	Extensions to TR-181 profiles.....	70
C.3.1	GRE tunnelling extensions	70
C.3.2	sRouter extensions.....	71
C.4	Management interface protocol requirements for GRE	71
Annex D (normative):	Simple security recommendations.....	73
D.1	Introduction	73
D.2	Summary of simple security recommendations	73
D.3	Critical recommendations.....	73
D.4	Important recommendations.....	75
D.5	BCP recommendations	76
D.6	Other recommendations	78

D.7	Recommendations in conflict with operator needs	78
Annex E (normative):	sRouter GRE tunnelling architecture	79
E.1	Introduction	79
E.2	Use case for data traffic flow for both private and public SSIDs.....	80
E.2.1	General requirements	80
E.2.2	Private network outbound from LAN.....	80
E.2.3	Private network inbound from WAN	81
E.2.4	Community Wi-Fi user outbound via public SSID	81
E.2.5	Community Wi-Fi user inbound via public SSID	81
Annex F (normative):	sRouter certificate public key infrastructure	82
F.1	General requirements	82
F.2	CableLabs Root CA certificate.....	83
F.3	CableLabs Device CA certificate.....	84
F.4	sRouter device certificate	84
F.5	CableLabs Service Provider CA certificate.....	85
F.6	Management/provisioning server certificate	86
F.7	CableLabs DOCSIS CVC CA certificate.....	86
F.8	Code Verification Certificate	87
F.9	Certificate Revocation List (CRL)	88
Annex G (informative):	Example routing with Link-ID	89
G.1	Scenario.....	89
G.2	IP MIB sRouter example.....	91
Annex I (informative):	Change history	92
History		93

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Foreword

This ETSI Standard (ES) has been produced by ETSI Technical Committee Integrated broadband cable telecommunication networks (CABLE).

Modal verbs terminology

In the present document **"shall"**, **"shall not"**, **"should"**, **"should not"**, **"may"**, **"need not"**, **"will"**, **"will not"**, **"can"** and **"cannot"** are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and **"must not"** are **NOT** allowed in ETSI deliverables except when used in direct citation.