



Environmental Engineering (EE); Guidance on simplified Life Cycle Assessments (LCA) of Information and Communication Technologies (ICT)

get full document from standards.iteh.ai

Reference

DES/EE-EEPS62

Keywords

energy consumption, environment, environmental
impact, green-house gas emission, ICT, LCA,
smartphone

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed,
this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our
[Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2026.
All rights reserved.

Contents

Intellectual Property Rights	6
Foreword.....	6
Modal verbs terminology.....	6
Executive summary	6
Introduction	6
1 Scope	8
2 References	8
2.1 Normative references	8
2.2 Informative references.....	8
3 Definition of terms, symbols and abbreviations.....	10
3.1 Terms.....	10
3.2 Symbols.....	16
3.3 Abbreviations	16
4 Introduction to simplified LCA approaches.....	16
4.1 General	16
4.2 Simplified approaches	17
4.3 Applicability of LCAs and simplified LCA	18
4.4 Decision tree for choosing approach	19
4.4.0 Determining possible approaches	19
4.4.1 Data availability.....	22
4.4.2 Reusing data for similar products	23
4.5 Overview of different approaches	24
5 Detailed guidance for simplified LCA approach.....	25
5.1 General	25
5.1.0 Introduction.....	25
5.1.1 Embodied environmental impacts in a simplified LCA.....	25
5.1.2 Use stage environmental impacts in a simplified LCA.....	25
5.1.3 Data quality.....	25
5.1.4 Energy mix.....	26
5.1.5 Cut-off	26
5.2 Product Parameter (PP) method	26
5.2.1 General introduction to PP method.....	26
5.2.2 Goal and Scope definition of PP method	28
5.2.3 Life Cycle Inventory (LCI) of PP method	28
5.2.3.0 Introduction to PP method inventory creation.....	28
5.2.3.1 Raw Materials stage	28
5.2.3.2 Production stage.....	29
5.2.3.2.0 Types of processes in production stage	29
5.2.3.2.1 Mechanics, Electro-Mechanics, cables and batteries processes	29
5.2.3.2.2 Electronics supply chain processes.....	30
5.2.3.2.3 Manufacturer activities.....	31
5.2.3.3 Use stage	32
5.2.3.3.0 Introduction	32
5.2.3.3.1 Additional impacts in use stage	32
5.2.3.4 EoLT	32
5.2.4 Life Cycle Impact Assessment (LCIA) of PP method.....	33
5.2.5 Life cycle interpretation of PP method	33
5.2.6 Reporting and review.....	35
5.2.7 Implementation examples of PP method	35
5.3 Life Cycle Stage Ratio Profiling (LCSRP).....	36
5.3.1 General introduction to LCSRP.....	36
5.3.2 General requirement for LCSRP.....	36

5.3.3	Goal and Scope definition of LCSRP	36
5.3.4	Life Cycle Inventory (LCI) of LCSRP	36
5.3.5	Life Cycle Impact Assessment (LCIA) of LCSRP	36
5.3.6	Life cycle interpretation of LCSRP	36
5.4	One Parameter LCA method (1PLCA)	37
5.4.1	General introduction to 1PLCA	37
5.4.2	General requirement of 1PLCA	37
5.4.3	Goal and scope definition of 1PLCA	37
5.4.4	Life Cycle Inventory (LCI) of 1PLCA	37
5.4.5	Life Cycle Impact Assessment (LCIA) of 1PLCA	37
5.4.6	Life cycle interpretation of 1PLCA	37
5.4.7	Considerations for different parameters using 1PLCA	38
5.5	Environmentally Extended Input Output (EEIO) analysis	38
5.5.1	General introduction to EEIO	38
5.5.2	General requirement for EEIO	39
5.5.3	Goal and Scope definition of EEIO	39
5.5.4	Life Cycle Inventory (LCI) of EEIO	39
5.5.5	Life Cycle Impact Assessment (LCIA) of EEIO	40
5.5.6	Life cycle interpretation of EEIO	40
6	Reporting	40
Annex A (informative):	Data availability - detailed view of applicability, purpose and limitations of LCA approaches	42
Annex B (informative):	Example of global GHG Emission Factors (EFs)	44
Annex C (informative):	Expanding the number of parameters in the PP method	45
Annex D (informative):	Example - Simplified LCA of a Smartphone	46
Annex E (informative):	Clarification of PP method and unit processes in Recommendation ITU-T L.1410 / ETSI ES 203 199	48
Annex F (informative):	Emission Factors (EF) template	52
Annex G (informative):	Parametrized Product Characteristics Approach (PPCA) - a Product Parameter method for simplified LCA	55
G.1	Characteristics of Parametrized Product Characteristics Approach (PPCA)	55
G.2	Studied product system and calculation framework for Parametrized Product Characteristic Approach	56
G.3	Method explained for a fictive ICT Network infrastructure product	63
G.3.1	GWP100 CO ₂ e	63
G.3.2	Resource depletion	66
G.3.3	Ecotoxicity	69
G.3.4	Water scarcity	72
G.4	Method explained for a fictive ICT consumer product	75
G.4.1	GWP100 CO ₂ e	75
G.4.2	Resource depletion	78
G.4.3	Ecotoxicity	81
G.4.4	Water scarcity	84
G.5	Sensitivity and uncertainty analysis	86
G.5.0	Background considerations	86
G.5.1	Sensitivity analysis	86
G.5.2	Uncertainty analysis	86
G.5.3	Example of code for implementation of clause G.3	87
G.5.3.0	Example code	87
G.5.3.1	Baseline and uncertainty range results	91
G.5.3.2	Selected graphs generated from script in clause G.5.3	92

Annex H (informative):	Example - Simplified LCA of a typical mobile network radio	94
Annex I (informative):	Example of approaches for input data and recycling.....	97
I.0	Primary and secondary raw materials	97
I.1	Taking recycling into account in the raw material stage	97
I.2	EoLT stage, metal recycling, and connecting it to the raw material stage	98
I.3	The 50/50 method.....	98
Annex J (informative):	Component Characterization	101
J.1	General about component characterization	101
J.2	Example case of using iNEMI's estimator tool: Printed wiring boards.....	101
Annex K (informative):	Example of GHG estimation using LCSR.....	103
Annex L (informative):	Additional information with examples regarding the similarity of products	104
Annex M (informative):	Example of GHG estimation for a display applying different parameters using the 1PLCA method.....	107
Annex N (informative):	Example of GWP calculation using EEIO.....	109
Annex O (informative):	Bibliography.....	110
Annex P (informative):	Change history	111
History		112

get full document from standards.iteh.ai

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Foreword

This ETSI Standard (ES) has been produced by ETSI Technical Committee Environmental Engineering (EE).

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Executive summary

The present document provides guidance on how to perform, use and report simplified LCAs.

Moreover, it gives guidance on when the use of simplified approaches is relevant and recommended.

Introduction

A Life Cycle Assessment (LCA) is a systematic methodology which gives an understanding of the relative importance of the different life cycle stages/activities. LCAs assist companies in determining where to put their efforts to improve life cycle environmental performance and also to monitor how this performance changes over time. However, it is important to keep in mind that the results of an LCA are always model-based representations of real environmental impact, and the absolute impact of a certain product, network, service or organization is beyond reach. This is true for all kinds of product systems, but especially so for the complex product systems of the ICT sector.

An LCA addresses potential environmental impact; an LCA does not predict absolute or precise environmental impact due to the relative expression of potential impacts to a reference unit, the integration of environmental data over space and time, the inherent uncertainty in modelling environmental impact, and the fact that some possible environmental impacts are clearly future impacts (ISO 14040 [3], clause 4.3).

In practice, it is virtually impossible to collect enough data for an assessment to give the absolute performance of a product system. Even then, the results would still have model and scenario uncertainty.

Consequently, any LCA result is only valid under the assumptions of the study and is still associated with substantial uncertainty, which needs to be considered so the outcome of the assessment is interpreted in a correct way. This goes for detailed LCA assessment approaches described in Recommendation ITU-T L.1410 [1] / ETSI ES 203 199 [2], and even more so if further simplifications are needed.

Yet, simplified approaches are needed in different situation to give an approximation of the environmental impacts of products. The present document will outline when such approaches are relevant and how they could be performed, used and reported.

Providing a LCA fully respecting Recommendation ITU-T L.1410 [1] / ETSI ES 203 199 [2] is a very complex and time-consuming task. Not all companies and organizations have the financial and human resources to meet the requirements demanded. Hence, to onboard a large community across the industry and monitor the achievements of environmental targets it seems useful to provide relevant parties (operators, OEMs, integrators, service providers and software developer) with simplified approaches to assess environmental impacts of ICT goods and services. This can be viewed as a "Minimal Viable" approach that encourage parties to deliver life cycle impact estimates with limited investment, time and costs.

As for detailed LCA in line with Recommendation ITU-T L.1410 [1] / ETSI ES 203 199 [2], techniques such as uncertainty analysis and sensitivity analysis are important to understand the results of a study and what conclusions can be made.

Quantitative results of detailed LCA's by different LCA practitioners cannot be compared without considerations of assumptions, limitations in data, differences in data sets and scenarios as described in Recommendation ITU-T L.1410 [1] / ETSI ES 203 199 [2]. This is even more true for simplified approaches which are to a larger extent based on generic data, simplifying assumptions etc. To allow for comparability of results, whether based on detailed or simplified approaches, product category rules would need to be developed at product category level that allows for developing common detailed scenarios and assumptions. Results based on such Product Category Rules would be comparable but at the expense of being less representative to the actual conditions of the individual product.

1 Scope

The present document provides guidance on how to perform, use and report simplified LCAs for ICT products and services.

Moreover, it gives guidance on when the use of simplified approaches is applicable and what are the limitations.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found in the [ETSI docbox](#).

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long-term validity.

The following referenced documents are necessary for the application of the present document.

- [1] [Recommendation ITU-T L.1410 \(11/24\)](#): "Methodology for environmental life cycle assessments of information and communication technology goods, networks and services".
- [2] [ETSI ES 203 199 \(V1.4.1\)](#): "Environmental Engineering (EE); Methodology for environmental Life Cycle Assessment (LCA) of Information and Communication Technology (ICT) goods, networks and services".

NOTE: References [1] and [2] are technically equivalent.

- [3] [ISO 14040:2006](#): "Environmental management — Life cycle assessment — Principles and framework".
- [4] [ISO 14044:2006](#): "Environmental management — Life cycle assessment — Requirements and guidelines".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long-term validity.

The following referenced documents may be useful in implementing an ETSI deliverable or add to the reader's understanding, but are not required for conformance to the present document.

- [i.1] Recommendation ITU-T L.1420 (2012): "Methodology for energy consumption and greenhouse gas emissions impact assessment of information and communication technologies in organizations".
- [i.2] Void.
- [i.3] Recommendation ITU-T L.1451 (2019): "Methodology for assessing the aggregated positive sector-level impacts of ICT in other sectors".
- [i.4] Void.

- [i.5] Recommendation ITU-T L.1450 (2018): "Methodologies for the assessment of the environmental impact of the information and communication technology sector".
- [i.6] Supplement ITU-T L. Suppl. 57 (2023) - Recommendation ITU-T L.1420: "Scope 3 guidance for telecommunication operators".
- [i.7] J. Malmodin, N. Lövehagen (2024): "A methodology for simplified LCAs of electronic products". In proceedings of Electronics Goes Green, Berlin, 18-20 June 2024. DOI: 10.23919/EGG62010.2024.10631258.
- [i.8] N. Lövehagen, J. Malmodin, P. Bergmark, S. Matinfar: "[Assessing embodied carbon emissions of communication user devices by combining approaches](#)". Renewable and Sustainable Energy Reviews. 2023 September 1;183:113422. DOI: 10.1016/j.rser.2023.113422.
- [i.9] Zhabura, Y. (2024): "[Environmental Impact Assessment Tool for Electronics](#)".
- [i.10] Abhishek Kumar Rajesh Jha, Anders S.G. Andrae, Brijesh Mainali: "[Comparison of Methods for Calculating Indirect Upstream Carbon Emissions from Information and Communication Technology Manufacturing](#)". WSEAS Trans. Env. Dev. 2023, 19, pp. 1045-1097. DOI: 10.37394/232015.2023.19.99.
- [i.11] GSMA™: "[Scope 3 Guidance for Telecommunication Operators](#)".
- [i.12] M. Ercan, J. Malmodin, P. Bergmark, E. Kimfalk, E. Nilsson: "Life cycle assessment of a smartphone". In: Proceedings of the ICT for sustainability (ICT4S), 2016. Amsterdam, The Netherlands.
- [i.13] ETSI TS 104 134 (V1.1.1): "Environmental Engineering (EE); Simplified Method for including Uncertainty and Sensitivity Aspects in Calculations of the Avoided Environmental Impact of Information and Communication Technology Solutions".
- [i.14] A.S.G. Andrae: "[Year 2025 global average midpoint proxy intensities for GWP100, ADP \(minerals\), Ecotoxicity \(CTUe\) and water scarcity \(m 3 \) for use in simplified LCA of ICT products](#)", 2025. DOI: 10.13140/RG.2.2.10765.45288.
- [i.15] Andrae A.S.G. and Vaija M. S. (2017): "[Precision of a Streamlined Life Cycle Assessment Approach Used in Eco-Rating of Mobile Phones](#)".
- [i.16] Yang Y., Guo Y. Q., Zhu W. S., & Huang, J. B. (2019): "[Environmental impact assessment of China's primary aluminium based on life cycle assessment](#)". Transactions of Nonferrous Metals Society of China, 29(8), pp. 1784-1792.
- [i.17] Ding N., Gao F., Wang Z., Gong X. & Nie Z. (2012): "[Environment impact analysis of primary aluminium and recycled aluminium](#)". Procedia Engineering, 27, pp. 465-474.
- [i.18] Backes J. G., Suer J., Pauliks N., Neugebauer S. & Traverso M. (2021): "[Life Cycle Assessment of an Integrated Steel Mill Using Primary Manufacturing Data: Actual Environmental Profile](#)". Sustainability, 13(6), 3443.
- [i.19] Suer J., Traverso M. & Jäger N. (2022): "[Review of Life Cycle Assessments for Steel and Environmental Analysis of Future Steel Production Scenarios](#)". Sustainability 2022, 14, 14131.
- [i.20] Andrae A. S. G. & Vaija M. S. (2014): "[To Which Degree Does Sector Specific Standardization Make Life Cycle Assessments Comparable?—The Case of Global Warming Potential of Smartphones](#)". Challenges, 5(2), pp. 409-429.
- [i.21] Abbate E., Rovelli D., Andreotti M., Brondi C. & Ballarino A. (2022): "[Plastic packaging substitution in industry: Variability of LCA due to manufacturing countries](#)". Procedia CIRP, 105, pp. 392-397.
- [i.22] Okrasinski T. A., & Benowitz M. S. (2020, February): "[Quantifying Environmental Life Cycle Impacts for ICT Products-A Simpler Approach](#)". In 2020 Pan Pacific Microelectronics Symposium (Pan Pacific) (pp. 1-4), IEEE™.
- [i.23] Andrae A. S. G. & Andersen, O. (2011): "[Life cycle assessment of integrated circuit packaging technologies](#)". The International Journal of Life Cycle Assessment, 16, pp. 258-267.

- [i.24] Grobe K. (2021, May): "[Generalization of Lifecycle Assessment in the case of Photonic Products](#)". In Photonic Networks; 22nd ITG Symposium (pp. 1-4). VDE.
- [i.25] Teehan P., & Kandlikar M. (2013): "[Comparing Embodied Greenhouse Gas Emissions of Modern Computing and Electronics Products](#)". Environmental science & technology, 47(9):3997-4003.
- [i.26] Grobe K. (2022, May): "[Energy Efficiency Limits to ICT Equipment Lifetime](#)". In Photonic Networks; 23rd ITG-Symposium (pp. 1-8). VDE.
- [i.27] Andrae, A. S. G., Itsubo N., Yamaguchi H., & Inaba A. (2008): "[Life Cycle Assessment of Japanese High-Temperature Conductive Adhesives](#)". Environmental science & technology, 42(8), pp. 3084-3089.
- [i.28] Andrae, A. S. G. (2020): "[Hypotheses for primary energy use, electricity use and CO₂ emissions of global computing and its shares of the total between 2020 and 2030](#)". WSEAS Transactions on Power Systems, 15(50-59), 4.
- [i.29] Kristanto G. A. & Koven W. (2019): "[Estimating greenhouse gas emissions from municipal solid waste management in Depok, Indonesia](#)". City and environment interactions, 4, 100027.
- [i.30] INEMI: "[Eco-Impact Estimator, Phase 3](#)".
- [i.31] Carbon Trust/GESI: "[ICT Sector Guidance built on the GHG Protocol Product Life Cycle Accounting and Reporting Standard](#)", July 2017.
- [i.32] Y. Yang, Y. Park, T. M. Smith, T. Kim, H.-S. Park: "[High-Resolution Environmentally Extended Input-Output Model to Assess the Greenhouse Gas Impact of Electronics in South Korea](#)".
- [i.33] Greenhouse Gas Protocol: "[Corporate Value Chain \(Scope 3\) Standard](#)".
- [i.34] Greenhouse Gas Protocol: "[Corporate Standard](#)".
- [i.35] ETSI EN 303 808: "Environmental Engineering (EE); Applicability of EN 45552 to EN 45559 methods for assessment of material efficiency aspects of ICT network infrastructure goods in the context of circular economy".
- [i.36] CLC/TR 45550:2020: "Definitions related to material efficiency", (produced by CEN).
- [i.37] ISO 14046:2014: "Environmental management — Water footprint — Principles, requirements and guidelines".
- [i.38] ETSI ES 202 336-1: "Environmental Engineering (EE); Monitoring and Control Interface for Infrastructure Equipment (Power, Cooling and Building Environment Systems used in Telecommunication Networks) Part 1: Generic Interface".
- [i.39] Greenhouse Gas Protocol: "[Product Life Cycle Accounting and Reporting Standard](#)".

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the following terms apply:

activity data: quantitative measure of a level of activity that results in GHG emissions

NOTE: See Corporate Value Chain (Scope 3) Standard [i.33], clause 7.2.

black box module: device, system or object which can be viewed solely in terms of its input, output and transfer characteristics without any knowledge of its internal workings

NOTE 1: In this context the black box module may consist of several part categories such as integrated circuits, mechanics, cables, etc., e.g. a power module on a PCBA.

NOTE 2: See ETSI ES 203 199 [2], clause 3.1.

CO₂ equivalent (CO₂ e): universal unit of measurement to indicate the Global Warming Potential (GWP) of each of the seven greenhouse gases, expressed in terms of the GWP of one unit of carbon dioxide

NOTE 1: It can be used to evaluate releasing (or avoiding releasing) different greenhouse gases against a common basis.

NOTE 2: See Corporate Standard [i.34], glossary.

commercial lifetime: length of time that a good is owned for before a new one is bought to replace it

NOTE 1: This term may be used to estimate the lifetime of consumer products.

NOTE 2: See ETSI ES 203 199 [2], clause 3.1.

comparative analysis: analysis aiming to compare two different product systems based on the same functional unit

NOTE: This definition comes from ETSI ES 203 199 [2].

cradle-to-gate: partial life cycle of ICT goods or parts, from material acquisition through to when they leave the factory gate (e.g. immediately following the production)

NOTE 1: See ETSI ES 203 199 [2], clause 3.1. This definition has been amended from GHG Protocol Product Standard [i.39].

NOTE 2: E.g. ICT goods ready to be put on the market/sales with no need for further processing.

cut-off: amount of energy or material flow, or the level of environmental significance associated with unit processes or product systems excluded from the study

NOTE: Unit processes excluded from the studied product system in an LCA.

data gap: LCI flows excluded from a unit process within the studied product system

NOTE: See ETSI ES 203 199 [2], clause 3.1.

depreciation time: time during which a (new) revenue-generating asset reaches its residual economic value

NOTE: The depreciation time is sometimes referred to as the legal lifetime.

Economic Input-Output approach (EIO): method using tables, called Input-Output (IO) tables, that describe financial transactions between economic sectors in a national economy, to approximate environmental impacts

embodied emissions: life cycle(s) emissions from the following life cycle stages:

- raw material acquisition;
- production; and
- end-of-life treatment.

EXAMPLE: All life cycle stages other than the use stage.

NOTE 1: See ETSI ES 203 199 [2], clause 3.1.

NOTE 2: Each life cycle includes transportation as generic process as described in ETSI ES 203 199 [2].

embodied environmental impact: life cycle(s) environmental impact from the following life cycle stages:

- raw material acquisition;
- production; and
- end-of-life treatment.

EXAMPLE: All life cycle stages other than the use stage.

NOTE 1: See ETSI ES 203 199 [2], clause 3.1.

NOTE 2: Each life cycle includes transportation as generic process as described in ETSI ES 203 199 [2].

emission factor: factor allowing GHG emissions to be estimated from a unit of available activity data (e.g. tonnes of fuel consumed, tonnes of product produced) and absolute GHG emissions

NOTE 1: See Corporate Standard [i.34], glossary and Recommendation ITU-T L.1451 [i.3].

NOTE 2: Another example is: $\text{kgCO}_2\text{e/kWh}$ electricity, $\text{kgCO}_2\text{e}/(\text{tonne} \times \text{km})$.

environmental impact: impact including positive and negative aspects on the environment

NOTE: See ETSI ES 203 199 [2], clause 3.1.

extended operating lifetime: aggregated duration of the actual use periods of the first user and consecutive use periods associated with reuse

NOTE 1: The user in different life cycles can be the same or different user.

NOTE 2: Reuse and refurbishment, enable several use periods and consecutive life cycles.

NOTE 3: ETSI EN 303 808 [i.35] definition is aligned with TR 45550:2020 [i.36].

NOTE 4: See ETSI ES 203 199 [2], clause 3.1.

functional unit: See ISO 14040 [3], clause 3.20.

GHG emission intensity: numerical value of Greenhouse Gas (GHG) emissions per unit

Global Warming Potential (GWP): ratio of the warming of the atmosphere caused by one greenhouse gas to that caused by a similar mass of carbon dioxide

NOTE 1: GWP is calculated over a specific time frame generally 100 years.

NOTE 2: See ETSI ES 203 199 [2], clause 3.1.

ICT goods: tangible goods deriving from or making use of technologies devoted to or concerned with:

- the acquisition, storage, manipulation (including transformation), management, movement, control, display, switching, interchange, transmission or reception of a diversity of data;
- the development and use of the hardware, software, and procedures associated with this delivery; and
- the representation, transfer, interpretation, and processing of data among persons, places, and machines, noting that the meaning assigned to the data is preserved during these operations.

NOTE: See ETSI ES 203 199 [2], clause 3.1.

ICT network: set of nodes and links that provide physical or over the air information and communication connections between two or more defined points

EXAMPLE: Wireless network, fixed network, Local Area Network (LAN), home network and server network, access networks, core networks, cloud computing networks.

NOTE: See ETSI ES 203 199 [2], clause 3.1.

ICT service (application): use of ICT goods and/or networks to provide value to one or more users

EXAMPLE: Teleconferencing, teleworking, e-ticketing, e-learning, e-healthcare, smart transport and logistics, procurement systems, supply chain management systems, music/film distribution over the Internet or voice over IP, machine-to-machine systems.

NOTE: See ETSI ES 203 199 [2], clause 3.1.

ICT-specific EoLT: any disassembly/dismantling/shredding/recycling process which needs special adaptation for handling of ICT goods

NOTE: See ETSI ES 203 199 [2], clause 3.1.

ICT-specific infrastructure: basic structures needed for the operation of the goods, network or service

EXAMPLE: Antenna towers, cabling systems.

infrastructure: basic structures needed for the operation of the society

EXAMPLE: Transportation systems, buildings and power plants.

NOTE: See ETSI ES 203 199 [2], clause 3.1.

LCA practitioner: person(s) or organization(s) performing an LCA

NOTE: See ETSI ES 203 199 [2], clause 3.1.

life cycle: See ISO 14040 [3], clause 3.1.

life cycle stage: one of several consecutive and interlinked stages of a product system

NOTE: See ETSI ES 203 199 [2], clause 3.1.

lifetime: duration which may correspond to commercial lifetime, operating lifetime, extended operating lifetime or depreciation lifetime

NOTE: See ETSI ES 203 199 [2], clause 3.1.

location-based data: average grid emission factor data for the given locality or region

NOTE: Description is from Recommendation ITU-T L.1410 [1] / ETSI ES 203 199 [2] main text.

market-based data: emissions from electricity that a company have purposefully chosen, e.g. derived from contractual instruments

NOTE: Description is from Recommendation ITU-T L.1410 [1] / ETSI ES 203 199 [2] main text.

modelled data: assumption-driven estimates, such as estimates resulting from scenarios, which are forward looking or scaled up from smaller pilot studies

NOTE: See ETSI ES 203 199 [2], clause 3.1.

natural resource: material source, such as wood, water, or a mineral deposit, that occurs in a natural state

NOTE: See ETSI ES 203 199 [2], clause 3.1.

node: point in a network topology at which lines intersect or branch

NOTE: See ETSI ES 203 199 [2], clause 3.1.

operating lifetime: duration of the actual use period (consisting of both active and non-active periods) for the first user

NOTE 1: Storage time is not included in operating lifetime.

NOTE 2: See ETSI ES 203 199 [2], clause 3.1.

operator: organization operating networks and services

NOTE: See ETSI ES 203 199 [2], clause 3.1.

other EoLT: any disassembly/dismantling/shredding/recycling process which does not need special adaptation for handling of ICT goods but could be used for any kind of good

NOTE: See ETSI ES 203 199 [2], clause 3.1.

part: constituent of ICT goods and support goods

EXAMPLE: Cable.

NOTE: See ETSI ES 203 199 [2], clause 3.1.

part category: classification of a part e.g. by its type

EXAMPLE: Fibre cable.

NOTE: See ETSI ES 203 199 [2], clause 3.1.

primary data: See ISO 14046 [i.37], clause 3.6.1.

primary energy: energy content of natural resources which can be used for energy production

NOTE: See ETSI ES 203 199 [2], clause 3.1.

primary raw material: material which originates from natural resources

NOTE: See ETSI ES 203 199 [2], clause 3.1.

process category: classification of a process type

EXAMPLE: Landfill, air, ship and train.

NOTE: See ETSI ES 203 199 [2], clause 3.1.

product system: See ISO 14040 [3], clause 3.28.

public data: data which is available to the public without access being restricted by requirements on membership, none-disclosure agreements, or similar restrictions

NOTE: See ETSI ES 203 199 [2], clause 3.1.

raw material: See ISO 14040 [3], clause 3.15.

raw material extraction: production of extracted raw materials used in raw material processing

NOTE: See ETSI ES 203 199 [2], clause 3.1.

raw material processing: production of processed raw materials used in in Part production

NOTE: See ETSI ES 203 199 [2], clause 3.1.

raw material recycling: production of raw materials from recycled products

NOTE: See ETSI ES 203 199 [2], clause 3.1.

recycling rate of disposed raw material: rate at which disposed goods end up in a recycling process is part of the scope of the LCA

NOTE: See ETSI ES 203 199 [2], clause 3.1.

reference product system: system (basically non-ICT but can also be ICT) which is replaced by ICT

EXAMPLE: Traditional service which is replaced by an ICT service.

NOTE: See ETSI ES 203 199 [2], clause 3.1.

re-use: process by which a product or its parts, having reached the end of their first use, are used for the same purpose for which they were conceived

NOTE 1: Reuse after second or subsequent usage is also considered as reuse, but normal, regular or sporadic use is not considered as reuse (TR 45550:2020 [i.36] and ETSI EN 303 808 [i.35]).

NOTE 2: ICT goods usage by a new user or in a new context is considered to be reuse.

NOTE 3: Definition amended from ETSI EN 303 808 [i.35] with additional note 2.

NOTE 4: See ETSI ES 203 199 [2], clause 3.1.

scope 3 emissions: scope 3 emissions are a consequence of the activities of the company, but occur from sources not owned or controlled by the company

NOTE 1: Some examples of scope 3 activities are extraction and production of purchased materials; transportation of purchased fuels; and use of sold products and services.

NOTE 2: Relevant Scope 3 categories for ICT companies are listed in Recommendation ITU-T L.1420 [i.1].

NOTE 3: See Corporate Standard [i.34].

secondary data: See ISO 14046 [i.37], clause 3.6.2.

secondary raw material: material which origins from recycled primary raw materials

NOTE: See ETSI ES 203 199 [2], clause 3.1.

service provider: organization operating a service (could be the same organization as the operator)

NOTE: See ETSI ES 203 199 [2], clause 3.1.

simplified Life Cycle Assessment: methodology to assess the environmental impact of a product or service with a more streamlined evaluation approach compared to a LCA following Recommendation ITU-T L.1410 [1] / ETSI ES 203 199 [2]

NOTE: It aims to provide a fast and cost-effective overview of the environmental performance of a product or service, enabling informed decision-making for product design and manufacturing.

storage time: length of time for which the goods are stored, including for both before and after its use stage

NOTE: See ETSI ES 203 199 [2], clause 3.1.

support activity: activities supporting unit processes associated with the function of the good, network or service

NOTE 1: Examples of support activities are activities directly associated with the product system, such as marketing, development and sales and also more general activities of the organization, such as data support, communication, and financial support.

NOTE 2: See ETSI ES 203 199 [2], clause 3.1.

support goods: device, system or object needed to realize the function of supporting the use of ICT goods

EXAMPLE: Goods for power supply and temperature regulation.

NOTE 1: See ETSI ES 202 336-1 [i.38] for an explanation which defines support goods for networks as infrastructure goods.

NOTE 2: See ETSI ES 203 199 [2], clause 3.1.

the 50/50 method: allocation method that allocates the credits equally to the life cycle using and the one supplying recycled material

NOTE 1: In reuse/refurbishment scenarios, the LCA practitioner needs to clearly declare how the allocation of raw materials has been handled in the assessment.

NOTE 2: See ETSI ES 203 199 [2], clause 3.1.

unit process: smallest element considered in the life cycle inventory analysis for which input and output data are quantified

NOTE 1: See also ISO 14040 [3] and ISO 14044 [4].

EXAMPLE: Part unit process such as IC Encapsulation and Display module assembly.

NOTE 2: See ETSI ES 203 199 [2], clause 3.1.

waste: See ISO 14040 [3], clause 3.35.