



**Terrestrial Trunked Radio (TETRA);
Voice plus Data (V+D) and Direct Mode Operation (DMO);
Part 18: Air interface optimized applications;
Sub-part 1: Location Information Protocol (LIP)**

[ETSI TS 100 392-18-1 V1.6.1 \(2012-08\)](https://standards.iteh.ai/catalog/standards/etsi/9ff31d2e-d6b5-4e7d-ad72-043b85823db1/etsi-ts-100-392-18-1-v1-6-1-2012-08)

<https://standards.iteh.ai/catalog/standards/etsi/9ff31d2e-d6b5-4e7d-ad72-043b85823db1/etsi-ts-100-392-18-1-v1-6-1-2012-08>

ReferenceRTS/TETRA-03221

Keywordsair interface, location, radio, TETRA, V+D

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2012.
All rights reserved.

DECTTM, PLUGTESTSTM, UMTSTM and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPPTM and LTETM are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	8
Foreword.....	8
1 Scope	9
2 References	9
2.1 Normative references	9
2.2 Informative references.....	9
3 Definitions, symbols and abbreviations	10
3.1 Definitions.....	10
3.2 Symbols.....	10
3.3 Abbreviations	10
4 Location information protocol.....	11
4.1 General	11
4.2 Location information protocol system architecture.....	12
4.3 Location information protocol service description.....	15
4.3.1 General on services.....	15
4.3.2 Services available at the LIP-SAP	15
4.3.3 Service primitives at the LIP-SAP	16
4.3.4 Service primitive parameters at the LIP-SAP	16
4.5.5 State description.....	16
5 Location information protocol description.....	17
5.1 Description of information elements	17
5.1.1 General on accuracies and uncertainties	17
5.1.2 Acknowledgement request.....	17
5.1.2a Backlog information elements.....	17
5.1.3 Basic parameters.....	17
5.1.4 Confidence level	17
5.1.5 Direction of travel and direction of travel accuracy.....	17
5.1.6 Horizontal position and horizontal position accuracy.....	18
5.1.7 Horizontal velocity and horizontal velocity accuracy.....	18
5.1.8 Location altitude and location altitude accuracy.....	18
5.1.9 Location information destination	18
5.1.10 Location message reference	18
5.1.11 Location shape	19
5.1.12 Maximum information age	19
5.1.13 Maximum reporting distance	19
5.1.14 Maximum reporting interval	19
5.1.15 Maximum response time.....	19
5.1.16 Minimum reporting interval.....	19
5.1.17 Reason for sending.....	19
5.1.18 Report type.....	19
5.1.19 Request priority	19
5.1.20 Requested/required	20
5.1.21 Start time.....	20
5.1.22 Stop time.....	20
5.1.23 Terminal or location identification	20
5.1.24 Trigger definition.....	21
5.1.25 Trigger type	21
5.1.26 Velocity type.....	21
5.1.27 Vertical velocity and vertical velocity accuracy	21
5.2 Information flows.....	21
5.2.1 General on information flows	21
5.2.2 Pre-programmed MS sending reports	22
5.2.3 Pre-programmed MS sending reports and receiving acknowledgement.....	22

5.2.4	MS receiving basic parameters	23
5.2.5	MS receiving basic parameters and sending response	23
5.2.6	MS reporting basic parameters	24
5.2.7	MS receiving immediate report request and sending response	24
5.2.8	MS receiving immediate report request and asking acknowledgement	25
5.2.9	MS receiving trigger definitions and sending reports	25
5.2.10	MS receiving trigger definitions and sending reports and asking acknowledgements.....	26
5.2.11	MS receiving trigger definitions and sending modification.....	26
5.2.12	MS receiving trigger definitions and rejecting triggers	27
5.2.13	MS receiving trigger definitions and sending reports to other location information destination	27
5.2.14	MS receiving trigger definitions via location server and sending reports to another location information destination	28
5.2.15	Trigger removal	29
5.2.16	Trigger reporting.....	29
5.2.17	Location reporting enabling.....	30
5.2.18	Location reporting disabling.....	30
5.2.19	Location reporting temporary control.....	31
5.2.20	Backlog information flows	32
5.2.21	Allocation of entities.....	32
5.3	Procedures	33
5.3.1	Relations to flow charts	33
5.3.2	General on control messages	33
5.3.3	Accuracy control in control messages	33
5.3.4	General on location report sending.....	34
5.3.5	General on location report reception.....	34
5.3.6	MS sending unsolicited reports	34
5.3.7	MS receiving basic parameters	35
5.3.8	MS reporting basic parameters	35
5.3.9	MS sending immediate reports	35
5.3.10	MS sending immediate report request	35
5.3.11	Triggered report request sending	35
5.3.12	MS receiving triggered reports requests	36
5.3.13	MS sending triggered reports.....	36
5.3.14	MS receiving triggered reports	37
5.3.15	Triggered report reception in location server	37
5.3.16	Trigger removal	37
5.3.17	Report trigger request	37
5.3.18	Location report enable/disable request	37
5.3.19	Trigger configuration request	38
5.3.20	Trigger and report type interactions.....	38
5.3.21	Location message reference usage.....	39
5.3.22	Triggers for Lost and Regained ability to determine location.....	39
5.3.23	Trigger for Ambience Listening call.....	39
5.3.24	Temporary control of location reporting.....	40
5.3.25	Track retrieval.....	40
5.3.25.1	General on track retrieval.....	40
5.3.25.2	Backlog requesting entity actions	41
5.3.25.3	MT or application actions	41
5.3.25.3.1	Backlog location reporting	41
5.3.25.3.2	Backlog location report recording enabling and disabling	42
5.3.25.3.3	Backlog location report triggers	42
5.3.25.3.4	Result code usage	43
5.3.26	Trigger for call setup.....	43
5.4	Management of time.....	43
6	Location information protocol coding requirements.....	44
6.1	General on coding requirements.....	44
6.2	Location information protocol PDU description tables.....	45
6.2.1	SHORT LOCATION REPORT PDU.....	45
6.2.2	LONG LOCATION REPORT PDU.....	45
6.2.3	LOCATION REPORT ACKNOWLEDGEMENT PDU.....	46
6.2.4	BASIC LOCATION PARAMETERS REQUEST PDU	46

6.2.5	BASIC LOCATION PARAMETERS RESPONSE PDU	47
6.2.6	REPORT BASIC LOCATION PARAMETERS REQUEST PDU	48
6.2.7	REPORT BASIC LOCATION PARAMETERS RESPONSE PDU	48
6.2.8	ADD/MODIFY TRIGGER REQUEST PDU	49
6.2.9	ADD/MODIFY TRIGGER RESPONSE PDU	50
6.2.10	REMOVE TRIGGER REQUEST PDU	51
6.2.11	REMOVE TRIGGER RESPONSE PDU	51
6.2.12	REPORT TRIGGERS REQUEST PDU	51
6.2.13	REPORT TRIGGER RESPONSE PDU	52
6.2.14	LOCATION REPORTING ENABLE/DISABLE REQUEST PDU	53
6.2.15	LOCATION REPORTING ENABLE/DISABLE RESPONSE PDU	53
6.2.16	IMMEDIATE LOCATION REPORT REQUEST PDU	54
6.2.17	LOCATION REPORTING TEMPORARY CONTROL REQUEST PDU	55
6.2.18	LOCATION REPORTING TEMPORARY CONTROL RESPONSE PDU	55
6.2.19	BACKLOG REQUEST PDU	56
6.2.20	BACKLOG RESPONSE PDU	56
6.2.21	Backlog PDUs	57
6.2.21.1	BACKLOG ADD/MODIFY TRIGGERS REQUEST PDU	57
6.2.21.2	BACKLOG ADD/MODIFY TRIGGERS RESPONSE PDU	58
6.2.21.3	BACKLOG CONFIGURATION REQUEST PDU	59
6.2.21.4	BACKLOG CONFIGURATION RESPONSE PDU	59
6.2.21.5	BACKLOG REMOVE TRIGGERS REQUEST PDU	59
6.2.21.6	BACKLOG REMOVE TRIGGERS RESPONSE PDU	59
6.2.21.7	BACKLOG REPORT TRIGGERS REQUEST PDU	60
6.2.21.8	BACKLOG REPORT TRIGGERS RESPONSE PDU	60
6.2.21.9	BACKLOG RETRIEVAL REQUEST PDU	60
6.2.21.10	BACKLOG RETRIEVAL RESPONSE PDU	61
6.3	Location information protocol PDU information elements	61
6.3.1	Acknowledgement request	61
6.3.2	Address or identification type	61
6.3.3	Angle	62
6.3.4	Backlog information elements	62
6.3.4.1	Backlog continuation state	62
6.3.4.2	Backlog denominator rule	62
6.3.4.3	Backlog distance interval rule	63
6.3.4.4	Backlog information available	63
6.3.4.5	Backlog retrieval action	63
6.3.4.6	Backlog retrieval rules	63
6.3.4.7	Backlog location reports present	64
6.3.4.8	Backlog location reports requested	64
6.3.4.9	Backlog order of processing	64
6.3.4.10	Backlog PDU Type	64
6.3.4.11	Backlog time frame rule	65
6.3.4.12	Backlog time interval rule	65
6.3.4a	Confidence level	65
6.3.4b	Default enable/disable lifetime	65
6.3.5	Direction of travel	65
6.3.6	Direction of travel extended	66
6.3.7	Direction of travel accuracy	66
6.3.8	Direction of travel and direction of travel accuracy	66
6.3.9	Direction of travel uncertainty	67
6.3.10	Extended user defined data	67
6.3.11	External subscriber number	67
6.3.12	Half of major axis	67
6.3.13	Half of minor axis	67
6.3.14	Horizontal position accuracy	67
6.3.15	Horizontal position and horizontal position accuracy	68
6.3.16	Horizontal position uncertainty	68
6.3.17	Horizontal velocity	68
6.3.18	Horizontal velocity accuracy	69
6.3.19	Horizontal velocity and horizontal velocity accuracy	70
6.3.20	Horizontal velocity and vertical velocity	70

6.3.21	Horizontal velocity and vertical velocity with uncertainty	70
6.3.22	Horizontal velocity and vertical velocity with direction of travel extended and uncertainty	70
6.3.23	Horizontal velocity uncertainty	71
6.3.24	Horizontal velocity with direction of travel extended	71
6.3.25	Horizontal velocity with direction of travel extended and uncertainty	71
6.3.26	Horizontal velocity with uncertainty	71
6.3.27	Inner radius	72
6.3.28	IPv4 address	72
6.3.29	IPv6 address	72
6.3.30	Latitude	72
6.3.31	Location altitude	72
6.3.32	Location altitude accuracy	73
6.3.33	Location altitude and location altitude accuracy	73
6.3.34	Location altitude uncertainty	73
6.3.35	Location arc	73
6.3.36	Location circle	74
6.3.37	Location circle with altitude	74
6.3.38	Location circle with altitude and uncertainty	74
6.3.39	Location data	74
6.3.40	Location ellipse	75
6.3.41	Location ellipse with altitude	75
6.3.42	Location ellipse with altitude and uncertainty	75
6.3.43	Location information destination	76
6.3.44	Location message reference	76
6.3.45	Location point	76
6.3.46	Location point and position error	76
6.3.47	Location point with altitude	77
6.3.48	Location reporting enable flags	77
6.3.49	Location shape	78
6.3.50	Longitude	78
6.3.51	Maximum information age	78
6.3.52	Maximum reporting distance	79
6.3.53	Maximum reporting interval	79
6.3.54	Maximum response time	79
6.3.54a	Minimum detection interval	80
6.3.55	Minimum reporting interval	80
6.3.56	MNI + SSI	80
6.3.57	MNI + SSI + external subscriber number	81
6.3.58	Name of location	81
6.3.59	Name server type	81
6.3.60	Outer radius	81
6.3.61	PDU type	82
6.3.62	PDU type extension	82
6.3.63	Position error	82
6.3.64	Reason for sending	83
6.3.65	Report type	84
6.3.66	Requested or required	84
6.3.67	Request priority	84
6.3.68	Result code	85
6.3.69	SDS type-1 value	86
6.3.70	SSI	86
6.3.71	SSI + external subscriber number	86
6.3.72	Start angle	86
6.3.73	Start time	87
6.3.74	Status value	87
6.3.75	Stop angle	87
6.3.76	Stop time	87
6.3.76a	Temporary control parameter definition	88
6.3.76b	Temporary control parameter type	88
6.3.76c	Temporary control validity	89
6.3.76d	Temporary maximum reporting distance - relative	89
6.3.76e	Temporary minimum reporting distance - absolute	89

6.3.76f	Temporary minimum reporting interval - absolute	90
6.3.76g	Temporary minimum reporting interval - relative	90
6.3.76h	Temporary report type	90
6.3.77	Terminal or location identification	90
6.3.78	Time elapsed	91
6.3.79	Time of position	91
6.3.80	Time data	92
6.3.81	Time type	92
6.3.82	Trigger definition (one-shot/recurring)	92
6.3.83	Trigger removal	93
6.3.84	Trigger type (one-shot/recurring)	94
6.3.85	Trigger type (recurring)	95
6.3.86	Type 5 element identifier	95
6.3.87	Type of additional data	96
6.3.88	User defined data	96
6.3.89	Velocity data	96
6.3.90	Velocity type	96
6.3.91	Vertical velocity	97
6.3.92	Vertical velocity accuracy	97
6.3.93	Vertical velocity and vertical velocity accuracy	98
6.3.94	Vertical velocity uncertainty	98
6.4	Type 5 information element description	98
6.4.1	Type 5 information element definition	98
6.4.2	Type 5 element length	98
6.4.3	Type 5 element length extension	99
6.4.4	Type 5 information element	99
6.5	Geographical shape descriptions	99
7	Implementation requirements	99
Annex A (informative):	Example of trigger priorities	100
A.1	Trigger priority setting	100
Annex B (informative):	Use of location message reference	102
B.1	Potential usage of location message reference	102
Annex C (informative):	Change Requests	103
History		105