

ETSI TS 100 392-2 V3.5.1 (2011-10)



Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 2: Air Interface (AI)

Document Preview

[ETSI TS 100 392-2 V3.5.1 \(2011-10\)](https://standards.iteh.ai/catalog/standards/etsi/8b290a89-8659-4a44-b4e4-2a7010d13e53/etsi-ts-100-392-2-v3-5-1-2011-10)

<https://standards.iteh.ai/catalog/standards/etsi/8b290a89-8659-4a44-b4e4-2a7010d13e53/etsi-ts-100-392-2-v3-5-1-2011-10>

Reference

RTS/TETRA-03206

Keywords

air interface, radio, TETRA, V+D

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2011.
All rights reserved.

DECTTM, PLUGTESTSTM, UMTSTM and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPPTM and LTETM are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	42
Foreword.....	42
Introduction	43
1 Scope	44
2 References	44
2.1 Normative references	45
2.2 Informative references	47
3 Definitions and abbreviations.....	48
3.1 Definitions	48
3.2 Abbreviations	54
4 Radio aspects.....	59
4.1 Introduction	59
4.2 Set of logical channels.....	59
4.3 Reference configuration	59
4.4 Error control schemes.....	60
4.5 Multiple access and timeslot structure.....	60
4.5.1 General.....	60
4.5.2 Hyperframes, multiframes and frames.....	61
4.5.3 Timeslots and bursts	61
4.5.4 Mapping of logical channels onto physical channels.....	62
4.6 Coding, interleaving and scrambling.....	62
4.7 Modulation	62
4.8 Transmission and reception.....	62
4.9 Other radio-related functions.....	62
4.10 Performance	63
4.11 TETRA modes of operation	63
4.11.1 Main control channel modes of operation.....	64
4.11.1.1 Conventional Access (CA) mode.....	64
4.11.1.2 Direct Access (DA) mode	64
4.11.2 Transmission modes	64
4.11.2.1 Downlink-Continuous Transmission (D-CT) mode.....	64
4.11.2.2 Downlink-Carrier Timesharing Transmission (D-CTT) mode.....	64
4.11.2.3 Downlink-Main Control Channel Timesharing Transmission (D-MCCTT) mode.....	64
4.11.2.4 Multiple Slot Transmission (MST) mode	64
4.11.3 Control modes.....	64
4.11.3.1 Normal Control Mode (NCM)	64
4.11.3.2 Minimum Control Mode (MCM).....	65
5 Modulation	66
5.1 Introduction	66
5.2 Modulation type	66
5.3 Modulation rate	66
5.4 Modulation symbol definition	66
5.5 Modulated signal definition.....	68
5.6 Modulation filter definition	68
5.7 Modulation block diagram	69
5.8 Introduction to QAM channels.....	69
5.9 Modulation type	69
5.10 Use of sub-carriers in QAM carriers	69
5.11 Modulation rate	69
5.12 Modulation symbol definition	70
5.13 Bit to symbol mapping	70
5.14 Data, synchronization and pilot symbol multiplexing.....	73
5.15 Sub-carrier frequency domain multiplexing.....	74

5.16	Modulated signal definition.....	74
5.17	Modulation filter definition	75
5.18	Modulation block diagram	76
6	Radio transmission and reception.....	77
6.1	Introduction	77
6.2	Frequency bands and channel arrangement.....	77
6.3	Reference test planes	77
6.4	Transmitter characteristics.....	78
6.4.1	Output power for phase modulation	78
6.4.1.1	Base Station (BS).....	78
6.4.1.2	Mobile Station (MS)	79
6.4.2	Unwanted conducted emissions for phase modulation	79
6.4.2.1	Definitions.....	79
6.4.2.2	Unwanted emissions close to the carrier	80
6.4.2.2.1	Emission during the useful part of the burst	80
6.4.2.2.2	Emission during the switching transients	80
6.4.2.3	Unwanted emissions far from the carrier	81
6.4.2.4	Unwanted emissions during the CLCH and BLCH	81
6.4.2.5	Unwanted emissions in the non-transmit state	82
6.4.3	Unwanted radiated emissions for phase modulation.....	82
6.4.4	RF tolerance for phase modulation.....	82
6.4.5	RF Output power time mask for phase modulation	82
6.4.5.1	BS.....	83
6.4.5.2	MS.....	83
6.4.6	Transmitter intermodulation attenuation for phase modulation.....	83
6.4.6.1	Definition	83
6.4.6.2	BS.....	83
6.4.6.3	MS.....	84
6.4.7	Intra-BS intermodulation requirements	84
6.4.8	Output power for QAM	84
6.4.8.1	BS.....	84
6.4.8.2	MS.....	85
6.4.9	Unwanted conducted emissions for QAM	85
6.4.9.1	Definitions.....	85
6.4.9.2	Unwanted emissions close to the carrier	85
6.4.9.2.1	Emission during the useful part of the burst	86
6.4.9.2.2	Emission during the switching transients	86
6.4.9.3	Unwanted emissions far from the carrier	87
6.4.9.4	Unwanted emissions during the CLCH-Q and BLCH-Q	88
6.4.9.5	Unwanted emissions in the non-transmit state	88
6.4.10	RF Output power time mask for QAM	88
6.4.10.1	BS.....	89
6.4.10.2	MS.....	90
6.4.11	Transmitter intermodulation attenuation.....	90
6.4.12	Intra-BS intermodulation requirements	90
6.5	Receiver characteristics	90
6.5.1	Blocking characteristics	90
6.5.1.1	Definition	90
6.5.1.2	Specification for Phase Modulation	90
6.5.1.3	Specification for QAM.....	91
6.5.2	Spurious response rejection	91
6.5.2.1	Definition	91
6.5.2.2	Specification for phase modulation.....	92
6.5.2.3	Specification for QAM.....	92
6.5.3	Intermodulation response rejection.....	93
6.5.3.1	Definition	93
6.5.3.2	Specification for Phase Modulation	93
6.5.3.3	Specification for QAM.....	93
6.5.4	Unwanted conducted emissions.....	93
6.5.4.1	Definition	93
6.5.4.2	Specification.....	93

6.5.5	Unwanted radiated emissions	94
6.6	Transmitter/receiver performance for phase modulation.....	94
6.6.1	Transmitter performance for phase modulation.....	94
6.6.1.1	Modulation accuracy for phase modulation	94
6.6.1.2	Vector error magnitude requirement at symbol time for phase modulation.....	94
6.6.2	Receiver performance for phase modulation	95
6.6.2.1	Nominal error rates for phase modulation.....	96
6.6.2.1.1	Nominal error rates for $\pi/4$ -DQPSK modulation	96
6.6.2.1.2	Nominal error rates for $\pi/8$ -D8PSK modulation	96
6.6.2.2	Dynamic reference sensitivity performance for phase modulation	96
6.6.2.2.1	BS receiver performance	97
6.6.2.2.2	MS receiver performance	98
6.6.2.3	Receiver performance at reference interference ratios for Phase Modulation.....	99
6.6.2.3.1	BS receiver performance	100
6.6.2.3.2	MS receiver performance	101
6.6.2.4	Static reference sensitivity performance for phase modulation.....	101
6.6.2.4.1	BS receiver performance	102
6.6.2.4.2	MS receiver performance	102
6.6.2.5	MS receiver performance for synchronization burst acquisition.....	103
6.7	Transmitter/receiver performance for QAM	103
6.7.1	Transmitter performance for QAM.....	103
6.7.1.1	Modulation accuracy for QAM.....	103
6.7.1.2	Vector error magnitude requirement at symbol time for QAM.....	104
6.7.2	Receiver performance for QAM	105
6.7.2.1	Nominal error rates for QAM.....	105
6.7.2.2	Dynamic reference sensitivity performance for QAM.....	105
6.7.2.3	Receiver performance at reference interference ratios for QAM	108
6.7.2.3.1	Adjacent channel interference	108
6.7.2.3.2	Co-channel interference	108
6.7.2.4	Static reference sensitivity performance for QAM	109
6.7.2.5	MS receiver performance for frequency correction burst acquisition on a DA cell.....	109
6.8	Propagation conditions	109
6.8.1	Propagation conditions - introduction.....	109
6.8.2	Tap-gain process types.....	110
6.8.3	Propagation models.....	111
7	Radio sub-system synchronization.....	112
7.1	Introduction	112
7.2	General description of synchronization system.....	112
7.3	Timebase counters for phase modulation	112
7.3.1	Timing counters for phase modulation	112
7.3.2	Values of the counters for phase modulation.....	112
7.4	Timing of phase modulation signals.....	113
7.5	Timebase counters for QAM	113
7.5.1	Timing counters for QAM	113
7.5.2	Values of the counters for QAM.....	113
7.6	Timing of QAM signals	114
7.7	BS requirements for synchronization	114
7.8	MS requirements for synchronization	115
8	Channel coding and scrambling	116
8.1	Introduction	116
8.2	General	116
8.2.1	Interfaces in the error control structure.....	116
8.2.1.1	Interfaces for phase modulation	116
8.2.1.2	Interfaces for QAM	118
8.2.2	Notation	119
8.2.3	Definition of error control codes.....	119
8.2.3.1	16-state Rate-Compatible Punctured Convolutional (RCPC) codes	119
8.2.3.1.1	Encoding by the 16-state mother code of rate 1/4	119
8.2.3.1.2	Puncturing of the mother code.....	120
8.2.3.1.3	Puncturing scheme of the RCPC code of rate 2/3.....	120

8.2.3.1.4	Puncturing scheme of the RCPC code of rate 1/3.....	120
8.2.3.1.5	Puncturing scheme of the RCPC code of rate 292/432.....	120
8.2.3.1.6	Puncturing scheme of the RCPC code of rate 148/432.....	120
8.2.3.2	Shortened (30,14) Reed-Muller (RM) code	121
8.2.3.3	$(K_1 + 16, K_1)$ block code	121
8.2.3.4	8-state Parallel Concatenated Convolutional Code (PCCC) for QAM	122
8.2.3.4.1	Encoding by the upper 8-state RSC encoder of rate 1/2.....	122
8.2.3.4.2	Interleaving by the quadratic-congruence interleaver.....	123
8.2.3.4.3	Encoding the interleaved bits by the lower 8-state RSC encoder of rate 1/2.....	124
8.2.3.4.4	Merging the systematic and parity bits for the PCCC encoder.....	124
8.2.3.4.5	Puncturing scheme for the PCCC encoder	125
8.2.3.4.6	Puncturing scheme for the PCCC encoder with coding rate 2/3.....	125
8.2.3.4.7	Puncturing scheme for the PCCC encoder with coding rate 1/2.....	125
8.2.3.5	(16,5) Reed-Muller (RM) code for QAM	125
8.2.4	Definition of interleaving schemes	125
8.2.4.1	Block interleaving for phase modulation	125
8.2.4.2	Interleaving over N blocks	126
8.2.4.3	Block interleaving for QAM	126
8.2.5	Definition of scrambling.....	127
8.2.5.1	Scrambling method	127
8.2.5.2	Scrambling sequence.....	127
8.3	Error control schemes.....	128
8.3.1	Error control schemes for phase modulation	128
8.3.1.1	Access Assignment Channel (AACH)	130
8.3.1.2	Broadcast Synchronization Channel (BSCH)	130
8.3.1.3	Traffic channels in circuit switched mode	131
8.3.1.3.1	Frame stealing and multi-slot transmission	131
8.3.1.3.2	Traffic CHannel, net rate = 4,8 kbit/s (TCH/4,8)	131
8.3.1.3.3	Traffic CHannel, net rate = 2,4 kbit/s (TCH/2,4)	132
8.3.1.3.4	Traffic CHannel, net rate = 7,2 kbit/s (TCH/7,2)	132
8.3.1.3.5	Traffic Channel-P8, net rate = 10,8 kbit/s (TCH-P8/10,8)	133
8.3.1.3.6	Speech Traffic Channel, full slot (TCH/S)	133
8.3.1.3.7	Speech Traffic Channel, half slot (TCH/S)	133
8.3.1.4	Signalling channels for signalling and packet mode data.....	134
8.3.1.4.1	Signalling CHannel for mapping onto Half-bursts on the Downlink (SCH/HD), Broadcast Network CHannel (BNCH), and STEaling CHannel (STCH)	134
8.3.1.4.2	Signalling CHannel for mapping onto Half-bursts on the Downlink (SCH-P8/HD).....	134
8.3.1.4.3	Signalling CHannel for mapping onto Half-bursts on the Uplink (SCH/HU).....	135
8.3.1.4.4	Signalling CHannel for mapping onto Half-bursts on the Uplink (SCH-P8/HU).....	135
8.3.1.4.5	Signalling CHannel for mapping onto Full bursts (SCH/F)	135
8.3.1.4.6	Signalling CHannel for mapping onto Full bursts (SCH-P8/F).....	136
8.3.2	Error control schemes for QAM	137
8.3.2.1	Slot Information Channel - QAM/Uplink (SICH-Q/U)	137
8.3.2.2	Slot Information Channel - QAM/Downlink (SICH-Q/D).....	138
8.3.2.3	Access Assignment Channel - QAM (AACH-Q)	138
8.3.2.4	Signalling Channel - QAM/Half slot Uplink (SCH-Q/HU)	138
8.3.2.5	Signalling Channel - QAM/Uplink (SCH-Q/U).....	139
8.3.2.6	Signalling Channel - QAM/Downlink (SCH-Q/D) and Broadcast Network Channel - QAM (BNCH-Q).....	140
8.3.2.7	Signalling Channel - QAM/Random Access (SCH-Q/RA)	141
8.3.2.8	Broadcast Synchronization Channel - QAM (BSCH-Q).....	141
8.3.2.9	Signalling Channel Data set B - QAM (SCH-Q/B).....	142
9	Channel multiplexing.....	143
9.1	Introduction	143
9.2	Logical channels.....	143
9.2.1	Logical channels hierarchy	143
9.2.2	Traffic channels for $\pi/4$ -DQPSK	143
9.2.2a	Traffic channels for $\pi/8$ -D8PSK.....	143
9.2.3	Control CHannels (CCH) for phase modulation.....	144
9.2.3.1	General	144
9.2.3.2	BCCH.....	144

9.2.3.3	LCH.....	144
9.2.3.4	SCH for $\pi/4$ -DQPSK.....	144
9.2.3.4a	SCH for $\pi/8$ -D8PSK	145
9.2.3.5	AACH	145
9.2.3.6	STCH	145
9.2.4	QAM Control CHannels (CCH-Q)	145
9.2.4.1	General.....	145
9.2.4.2	BCCH-Q	145
9.2.4.3	LCH-Q	146
9.2.4.4	SCH-Q.....	146
9.2.4.4a	SCH-Q/B.....	147
9.2.4.5	AACH-Q	147
9.2.4.6	SICH-Q	147
9.3	The physical resource	148
9.3.1	General.....	148
9.3.2	RF channels for phase modulation.....	148
9.3.2a	RF channels for QAM.....	149
9.3.2b	Random access RF channels for QAM.....	149
9.3.3	Timeslots	149
9.3.4	TDMA frame	150
9.3.5	Timeslot numbering.....	150
9.3.6	Subslot	150
9.3.6a	Random access uplink RF channel subslots for QAM.....	150
9.3.7	Multiframe	150
9.3.8	Hyperframe	150
9.3.9	Frame alignment	150
9.4	Physical channels	150
9.4.1	General.....	150
9.4.2	Types of physical channels for phase modulation	151
9.4.2.1	CP channel for phase modulation.....	151
9.4.2.2	TP channel.....	151
9.4.2.3	UP channel	151
9.4.3	Bursts for phase modulation	151
9.4.3.1	General.....	151
9.4.3.2	Phase modulation symbol numbering	152
9.4.3.3	Phase modulation bit numbering.....	152
9.4.3.4	Burst timing.....	152
9.4.4	Type of bursts for phase modulation	153
9.4.4.1	General.....	153
9.4.4.2	Modulation bits allocation.....	155
9.4.4.2.1	Control uplink Burst (CB)	156
9.4.4.2.2	Linearization uplink Burst (LB)	156
9.4.4.2.3	Linearization downlink burst.....	156
9.4.4.2.4	Normal Uplink Burst (NUB)	156
9.4.4.2.5	Normal continuous downlink burst	157
9.4.4.2.6	Synchronization continuous downlink burst.....	158
9.4.4.2.7	Normal discontinuous downlink burst.....	158
9.4.4.2.8	Synchronization discontinuous downlink burst.....	159
9.4.4.3	Burst fields	159
9.4.4.3.1	Frequency correction field.....	159
9.4.4.3.2	Normal training sequence	159
9.4.4.3.3	Extended training sequence	160
9.4.4.3.4	Synchronization training sequence	160
9.4.4.3.5	Tail bits.....	161
9.4.4.3.6	Phase adjustment bits	161
9.4.5	Transmission modes for phase modulation.....	162
9.4.5.1	BS continuous transmission	162
9.4.5.2	BS timesharing transmission	162
9.4.5.3	MS multiple slot transmission.....	163
9.4.6	Types of physical channels for QAM	163
9.4.6.1	CP channel for QAM	164
9.4.6.2	UP channel	164