

ETSI TS 101 376-4-12 V3.2.1 (2011-02)

Technical Specification

**GEO-Mobile Radio Interface Specifications (Release 3);
Third Generation Satellite Packet Radio Service;
Part 4: Radio interface protocol specifications;
Sub-part 12: Mobile Earth Station (MES) -
Base Station System (BSS) interface;
Radio Link Control/Medium Access Control (RLC/MAC) protocol;
GMR-1 3G 44.060**

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI TS 101 376-4-12 V3.2.1 \(2011-02\)](https://standards.iteh.ai/catalog/standards/etsi/58a7ffad-f9d8-4906-8b97-99af3c398179/etsi-ts-101-376-4-12-v3-2-1-2011-02)

<https://standards.iteh.ai/catalog/standards/etsi/58a7ffad-f9d8-4906-8b97-99af3c398179/etsi-ts-101-376-4-12-v3-2-1-2011-02>



Reference

RTS/SES-00315-4-12

Keywords3G, GMPRS, GMR, GPRS, GSM, GSO, MES,
mobile, MSS, radio, satellite, S-PCN**ETSI**650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2011.
All rights reserved.

DECTTM, PLUGTESTSTM, UMTSTM, TIPHONTM, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPPTM is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTETM is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	11
Foreword.....	11
Introduction	12
1 Scope	14
2 References	15
2.1 Normative references	15
2.2 Informative references.....	17
3 Definitions and abbreviations.....	17
3.1 Definitions.....	17
3.2 Abbreviations	19
4 Layered overview of radio interface.....	19
4.1 Layer services.....	20
4.2 Layer functions.....	20
4.3 Service primitives.....	21
4.4 Services required from lower layers.....	21
5 Introduction to the Medium Access Control (MAC) procedures	21
5.1 General	21
5.2 Multiplexing principles	21
5.2.1 Temporary Block Flow (TBF).....	21
5.2.2 Temporary Flow Identity (TFI).....	22
5.2.3 Uplink state flag.....	22
5.2.4 Medium access modes	22
5.2.4a Multiplexing of GMPRS and future MESS.....	23
5.3 Packet idle mode	23
5.4 Packet transfer mode	23
5.5 General procedures in packet idle and packet transfer modes	23
5.5.1 Mobile earth station side	23
5.5.1.1 Cell reselection.....	23
5.5.1.1a Network Assisted Cell Change	24
5.5.1.1a.1 Neighbour Cell System Information Distribution	24
5.5.1.1a.2 CCN Mode	24
5.5.1.2 System Information (SI) on PBCCH.....	24
5.5.1.3 System Information (SI) on BCCH	24
5.5.1.3.1 Supervision of BCCH_CHANGE_MARK and update of BCCH information	24
5.5.1.3.2 GPRS SI reception failure	24
5.5.1.4 Acquisition of system information on the broadcast channel.....	24
5.5.1.4.1 Suspension of operation to receive system information	24
5.5.1.4.2 Request for acquisition of system information	24
5.5.1.5 Discontinuous reception (DRX).....	24
5.5.1.6 Page mode procedures on PCCCH.....	25
5.5.1.7 Frequency parameters	25
5.5.2 Network side	25
5.5.2.1 System Information broadcasting.....	25
5.5.2.1.1 System information on PBCCH	25
5.5.2.1.2 System information on BCCH.....	25
5.5.2.1.3 System information on PACCH (and other logical channels)	25
5.5.2.1.4 Consistent sets of system information messages	25
5.5.2.2 Paging	25
5.6 Measurement reports	26
5.6.0 General.....	26
5.6.1 Network Control (NC) measurement reporting	26
5.6.2 Void	26
5.6.3 Additional measurement and reporting parameters	26

5.6.3.1	Deriving the 3G Neighbour Cell list from the 3G Neighbour Cell description.....	27
5.6.3.2	Deriving BA(GPRS) and the GSM Neighbour Cell list.....	27
5.6.3.3	Deriving the Neighbour Cell list from the GSM Neighbour Cell list and the 3G Neighbour Cell list.....	27
5.6.3.4	GPRS Real Time Differences	27
5.6.3.5	GPRS Report Priority Descriptions.....	27
5.6.3.6	GPRS Measurement Parameters and GPRS 3G Measurement Parameters.....	27
5.6.3.7	The GPRS 3G Cell Reselection list.....	28
6	Paging procedures (A/Gb mode only).....	28
6.1	Paging procedure for RR connection establishment.....	28
6.1.1	Paging initiation using paging subchannel on CCCH.....	28
6.1.2	Paging initiation using paging subchannel on PCCCH.....	28
6.1.3	Paging initiation using PACCH	28
6.1.4	Paging response	28
6.2	Paging procedure for downlink packet transfer.....	29
6.2.1	Paging procedure using paging subchannel on CCCH	29
6.2.2	Paging using paging subchannel on PCCCH	29
6.2.3	Paging response to a page on CCCH	29
7	Medium Access Control (MAC) procedures on PCCCH.....	29
7.0a	Support of multiple TBF procedures	30
7.1	TBF establishment initiated by the mobile earth station on PCCCH	30
7.1.1	Permission to access the network	30
7.1.2	Initiation of a TBF establishment	31
7.1.2.1	Initiation of the packet access procedure	31
7.1.2.1.1	Access persistence control on PRACH.....	32
7.1.2.1.2	Handling of T3202 expiry	33
7.1.2.2	Packet assignment procedure	33
7.1.2.2.1	On receipt of a PACKET CHANNEL REQUEST or PACKET CHANNEL REQ TYPE 2 message	33
7.1.2.2.2	Void.....	34
7.1.2.2.3	Void.....	34
7.1.2.2.4	Packet access reject procedure	34
7.1.2.3	One phase packet access completion.....	34
7.1.2.4	Timing and frequency correction	35
7.1.3	Packet Resource Request Procedure (Iu mode only)	35
7.1.3.1	Initiation of the Packet resource request procedure	35
7.1.3.2	On receipt of a PACKET RESOURCE REQUEST message	35
7.1.3.3	Completion of Packet resource request procedure	35
7.1.4	Initiation of TBF Establishment on CCCH.....	36
7.1.5	Abnormal cases.....	36
7.2	TBF establishment initiated by the network on CCCH (A/Gb mode only).....	37
7.2.1	Entering the packet transfer mode	37
7.2.1.1	Packet downlink assignment procedure	37
7.2.1.2	Packet downlink assignment procedure completion	38
7.2.1.3	Void.....	38
7.2.2	Abnormal cases.....	38
7.3	Procedure for measurement report sending in packet idle mode.....	38
7.4	Cell change order procedures in packet idle mode	39
7.4.1	Cell change order procedure initiated on PCCCH	39
7.4.2	Cell change order procedure initiated on CCCH	39
7.5	Measurement order procedures in packet idle mode	39
7.6	Void.....	39
7.7	Void.....	39
7.8	TBF establishment on PACCH by network	39
7.9	GMPRS Resume procedure on PCCCH (A/Gb mode only)	39
7.9.1	Initiation of GMPRS resume procedure.....	39
7.9.2	Completion of GMPRS resume procedure	40
7.9.3	Abnormal cases.....	40
8	Medium access control (MAC) procedures in packet transfer mode	40
8.1	Transfer of RLC data blocks	40

8.1.1	Uplink RLC data block transfer	40
8.1.1.1	Dynamic allocation uplink RLC data block transfer	41
8.1.1.1.1	PACCH operation (A/Gb mode only)	41
8.1.1.1.1a	PDCH3 PACCH operation (Iu mode only)	42
8.1.1.1.2	Resource reallocation for uplink TBF	42
8.1.1.1.3	Establishment of downlink TBF	44
8.1.1.2	Uplink PDCH(5,3) and PDCH(5,12) multiplexing	45
8.1.1.3	Void	45
8.1.1.4	Network initiated release of uplink TBF	45
8.1.1.5	Abnormal cases	46
8.1.2	Downlink RLC data block transfer	46
8.1.2.1	Downlink RLC data block transfer	47
8.1.2.1.1	Abnormal cases	47
8.1.2.2	Polling for packet downlink ACK/NACK	48
8.1.2.3	Downlink PDCH(5,3) and PDCH(5,12) mutiplexing	48
8.1.2.4	Resource reassignment for downlink	48
8.1.2.4a	Establishment of downlink TBF after downlink TBF release	49
8.1.2.4a.1	Abnormal cases	49
8.1.2.5	Establishment of uplink TBF	50
8.1.2.5.1	Abnormal cases (A/Gb mode)	52
8.1.2.5.1a	Abnormal cases (Iu mode)	52
8.1.2.6	Void	53
8.1.2.7	Void	53
8.1.2.8	Network initiated abnormal release of downlink TBF	53
8.1.2.9	Network initiated release of downlink TBF	53
8.1.3	Void	54
8.1.4	Multiplexing of control and data messages	54
8.1.5	Multiplexing multiple TBFs on the same burst (Iu mode only)	54
8.2	Packet PDCH release (Iu mode only)	55
8.3	Procedure for measurement report sending in Packet Transfer mode (Iu mode only)	55
8.4	Network controlled cell reselection procedure (Iu mode only)	55
8.4.1	Network controlled cell reselection completion	56
8.4.2	Abnormal cases	56
8.5	Measurement order procedures in packet transfer mode (Iu mode only)	57
8.6	Packet control acknowledgement	57
8.7	Abnormal cases	57
8.7.1	Abnormal release with return to CCCH or PCCCH	57
8.7.2	Abnormal release with random access	57
8.7.3	Abnormal release with system information	57
8.8	Packet link quality reporting in packet transfer mode (A/Gb mode only)	58
8.9	Coding rate change procedure in packet transfer mode	58
8.9.1	Downlink TBF coding rate change procedure	58
8.9.2	Uplink TBF coding rate change procedure	58
9	Radio Link Control (RLC) procedures in packet transfer mode	58
9.1	Procedures and parameters for peer-to-peer operation	59
9.1.1	Send state variable V(S)	59
9.1.1a	Control send state variable V(CS)	59
9.1.2	Acknowledge state variable V(A)	59
9.1.3	Acknowledge state array V(B)	59
9.1.3.1	Acknowledge state array V(B) for GMPRS	59
9.1.3.2	Void	60
9.1.4	Block Sequence Number BSN	60
9.1.4.1	Block Sequence Number BSN for GPRS TBF	60
9.1.4.2	Void	60
9.1.4a	Void	60
9.1.5	Receive state variable V(R)	60
9.1.6	Receive window state variable V(Q)	60
9.1.7	Receive state array V(N)	61
9.1.7.1	Receive state array V(N) in GMPRS TBF	61
9.1.7.2	Void	61
9.1.8	Starting Sequence Number (SSN) and Received Block Bitmap (RBB)	61

9.1.8.1	Starting Sequence Number (SSN) and Received Block Bitmap (RBB) in GMPRS TBF	61
9.1.8.1.1	Generation of the bitmap	61
9.1.8.1.2	Interpretation of the bitmap	62
9.1.8.2	Void.....	62
9.1.9	Window size	62
9.1.9a	Filler octets	62
9.1.10	Compression	62
9.1.11	Segmentation of upper layer PDUs into RLC data units	64
9.1.12	Re-assembly of upper layer PDUs from RLC data units	65
9.1.12a	Void	65
9.1.12b	Void	65
9.1.12c	Dummy Data Block (Iu mode only)	65
9.1.13	Void	66
9.2	Operation during RLC/MAC control message transfer	66
9.3	Operation during RLC data block transfer	66
9.3.1	Void	66
9.3.2	Acknowledged mode operation	66
9.3.2.1	Additional functionality in acknowledged mode on PDCH3 (Iu mode only)	66
9.3.2.2	Establishment of temporary block flow	66
9.3.2.3	Operation of uplink temporary block flow	67
9.3.2.4	Release of uplink temporary block flow	67
9.3.2.5	Operation of downlink temporary block flow	68
9.3.2.6	Release of downlink temporary block flow	69
9.3.3	Unacknowledged mode operation.....	69
9.3.3.1	Establishment of temporary block flow	69
9.3.3.2	Operation of uplink temporary block flow.....	69
9.3.3.3	Release of uplink temporary block flow	70
9.3.3.4	Operation of downlink temporary block flow	71
9.3.3.5	Release of downlink temporary block flow	71
9.4	Abnormal release cases	71
9.4.1	Abnormal release with random access.....	71
9.4.2	Abnormal release with spotbeam reselection.....	72
10	RLC/MAC block structure	72
10.0a	PNB(m,n) bursts - A/Gb mode.....	72
10.0b	PNB2(m,n) bursts - A/Gb mode.....	72
10.0c	PNB3(m,n) bursts - Iu mode	73
10.0d	PNB(1,6) bursts - Iu Mode	74
10.1	Radio block structure.....	75
10.2	Public information bits	78
10.2.1	Downlink PUI for PDCH (4,n) and PDCH (5,n) and PDCH2(5,3)	81
10.2.1a	Downlink PUI for PDCH3(5,3)	82
10.2.1b	Downlink PUI for PDCH3(5,12)	82
10.2.1c	Downlink PUI for PDCH3(10,3)	83
10.2.2	Downlink Extended PUI for PDCH2(5,12)	84
10.2.3	Uplink PUI for PDCH (4,3), PDCH (5,n), PDCH2(5,n) and PDCH3(5,n).....	85
10.2.4	Downlink PUI for PDCH (2,6)	85
10.2.4a	Downlink PUI for PDCH3(2,6)	85
10.2.5	Uplink PUI for PDCH (1,n), PDCH3(1,n) and PDCH3(2,6).....	86
10.3	RLC/MAC header	86
10.3.1	Downlink RLC/MAC header for PNB(m,n) and PNB2(m,n) bursts	86
10.3.1a	Downlink RLC/MAC Data header for PNB3(m,n) bursts - Iu mode only	87
10.3.1b	Downlink RLC/MAC Control header for PNB3(m,n) bursts - Iu mode only.....	87
10.3.2	Uplink RLC/MAC header for PNB(m,n) and PNB2(m,n) bursts - A/Gb mode only	87
10.3.2a	Uplink RLC/MAC Data header for PNB3(m,n) bursts - Iu mode only	88
10.3.2b	Uplink RLC/MAC Control header for PNB3(m,n) bursts - Iu mode only.....	88
10.4	Header fields	88
10.4.1	Uplink state flag (USF) field.....	88
10.4.1.1	PDCH(4,3), PDCH(5,3) PDCH2(5,3) and PDCH2(5,12) - A/Gb mode only	88
10.4.1.1a	PDCH3(5,3),PDCH3(5,12) and PDCH3(10,3) - Iu mode only	88
10.4.1.2	PDCH(2,6) - A/Gb mode only	89
10.4.1.2a	PDCH3(2,6) and PDCH3(1,6) - Iu mode only	89

10.4.2	Void	89
10.4.3	Stall indicator (SI) bit	89
10.4.4	Supplementary/polling (S/P) bit	90
10.4.5	Unsolicited uplink grant (UUG) field	90
10.4.5.1	UUG field for terminal type A and C - A/Gb mode only	90
10.4.5.2	UUG field for terminal type D - A/Gb mode only	91
10.4.5.3	PDCH3 UUG field - Iu mode only	91
10.4.5.3.1	PDCH3(10,3) and PDCH3(5,3) - Iu mode only	91
10.4.5.3.2	PDCH3(5,12) and PDCH3(2,6) - Iu mode only	92
10.4.5.3.3	DACCH - Iu mode only	92
10.4.6	Void	92
10.4.7	Payload type field	92
10.4.7a	Void	92
10.4.8	Final Block Indicator (FBI) bit	92
10.4.8a	Void	93
10.4.8b.1	Split Block Number (SPBN) - Iu mode only	93
10.4.8b.2	Final Split Block (FSB) - Iu mode only	93
10.4.9	Void	93
10.4.9a	Void	93
10.4.9b	Void	93
10.4.9c	Void	93
10.4.9d	Direction (D) bit	93
10.4.9e	SRB field (Iu mode only)	93
10.4.10	Temporary flow identifier (TFI) field	94
10.4.10.1	Downlink header TFI	94
10.4.10.1a	Downlink header TFI (bit7)	94
10.4.10.1.1	Data-only downlink RLC/MAC block	94
10.4.10.1.2	Control-only downlink RLC/MAC block (A/Gb mode only)	94
10.4.10.1.3	Control+data downlink RLC/MAC block (A/Gb mode only)	94
10.4.10.2	Uplink header TFI	94
10.4.10.2.1	Data-only uplink RLC/MAC block	94
10.4.10.2.2	Control-only uplink RLC/MAC block (A/Gb mode only)	95
10.4.10.2.3	Control+data uplink RLC/MAC block (A/Gb mode only)	95
10.4.10a	Power control (PC) field	95
10.4.11	Extension (E) bit	95
10.4.12	Block Sequence Number (BSN) field	95
10.4.12a	Void	96
10.4.13	Void	96
10.4.14	Void	96
10.4.14a	Void	96
10.4.15	Last Part Size (LPS) field	96
10.4.15a	PDU Length	96
10.4.15b	Length Indicator (LI)	96
10.4.16	RLC data field	96
10.4.17	Control message contents field	96
10.4.18	Unsatisfied Demand (UD)	96
10.4.19	Immediate Termination Request (ITR)	97
11	Message functional definitions and contents	97
11.1	Handling of erroneous protocol data	98
11.1.1	Message classification	98
11.1.1.1	Distribution messages	99
11.1.1.2	Non-distribution messages	99
11.1.1.2.1	Format of the address information	99
11.1.2	Error detection mechanism	99
11.1.3	Error labels	100
11.1.3.1	Generic error labels	100
11.1.3.2	"Ignore" error label	100
11.1.3.3	"Message escape" error label	101
11.1.4	Error detection and order of precedence	101
11.1.4.1	Unknown message type	101
11.1.4.2	Message not compatible with current protocol state	101