



**GEO-Mobile Radio Interface Specifications (Release 3);
Third Generation Satellite Packet Radio Service;
Part 4: Radio interface protocol specifications;
Sub-part 12: Mobile Earth Station (MES) -
Base Station System (BSS) interface;
Radio Link Control/Medium Access Control (RLC/MAC)
protocol;
GMR-1 3G 44.060**

<https://standards.iteh.ai/catalog/standards/etsi/e0d22877-8c0b-475b-a1dd-c9b578c9d4cc/etsi-ts-101-376-4-12-v3-3-1-2012-12>

Reference

RTS/SES-00328-4-12

Keywords3G, GMPRS, GMR, GPRS, GSM, GSO, MES,
mobile, MSS, radio, satellite, S-PCN**ETSI**650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2012.
All rights reserved.

DECTTM, PLUGTESTSTM, UMTSTM and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPPTM and LTETM are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	11
Foreword.....	11
Introduction	12
1 Scope	14
2 References	15
2.1 Normative references	15
2.2 Informative references.....	17
3 Definitions and abbreviations.....	17
3.1 Definitions.....	17
3.2 Abbreviations	19
4 Layered overview of radio interface.....	19
4.1 Layer services.....	20
4.2 Layer functions.....	20
4.3 Service primitives.....	21
4.4 Services required from lower layers.....	21
5 Introduction to the Medium Access Control (MAC) procedures	21
5.1 General	21
5.2 Multiplexing principles	21
5.2.1 Temporary Block Flow (TBF).....	21
5.2.2 Temporary Flow Identity (TFI)	22
5.2.3 Uplink state flag.....	22
5.2.4 Medium access modes	22
5.2.4a Multiplexing of GMPRS and future MESS.....	23
5.3 Packet idle mode	23
5.4 Packet transfer mode	23
5.5 General procedures in packet idle and packet transfer modes	24
5.5.1 Mobile earth station side.....	24
5.5.1.1 Cell reselection.....	24
5.5.1.1a Network Assisted Cell Change	24
5.5.1.1a.1 Neighbour Cell System Information Distribution	24
5.5.1.1a.2 CCN Mode	24
5.5.1.2 System Information (SI) on PBCCH.....	24
5.5.1.3 System Information (SI) on BCCH	24
5.5.1.3.1 Supervision of BCCH_CHANGE_MARK and update of BCCH information	24
5.5.1.3.2 GPRS SI reception failure	24
5.5.1.4 Acquisition of system information on the broadcast channel.....	24
5.5.1.4.1 Suspension of operation to receive system information	25
5.5.1.4.2 Request for acquisition of system information	25
5.5.1.5 Discontinuous reception (DRX).....	25
5.5.1.6 Page mode procedures on PCCCH.....	25
5.5.1.7 Frequency parameters	25
5.5.2 Network side.....	25
5.5.2.1 System Information broadcasting.....	25
5.5.2.1.1 System information on PBCCH	25
5.5.2.1.2 System information on BCCH.....	25
5.5.2.1.3 System information on PACCH (and other logical channels)	25
5.5.2.1.4 Consistent sets of system information messages	26
5.5.2.2 Paging	26
5.6 Measurement reports	26
5.6.0 General.....	26
5.6.1 Network Control (NC) measurement reporting	26
5.6.2 Void	27
5.6.3 Additional measurement and reporting parameters	27

5.6.3.1	Deriving the 3G Neighbour Cell list from the 3G Neighbour Cell description.....	27
5.6.3.2	Deriving BA(GPRS) and the GSM Neighbour Cell list.....	27
5.6.3.3	Deriving the Neighbour Cell list from the GSM Neighbour Cell list and the 3G Neighbour Cell list.....	27
5.6.3.4	GPRS Real Time Differences	28
5.6.3.5	GPRS Report Priority Descriptions.....	28
5.6.3.6	GPRS Measurement Parameters and GPRS 3G Measurement Parameters.....	28
5.6.3.7	The GPRS 3G Cell Reselection list.....	28
6	Paging procedures (A/Gb mode only).....	28
6.1	Paging procedure for RR connection establishment.....	28
6.1.1	Paging initiation using paging subchannel on CCCH.....	28
6.1.2	Paging initiation using paging subchannel on PCCCH.....	28
6.1.3	Paging initiation using PACCH	29
6.1.4	Paging response	29
6.2	Paging procedure for downlink packet transfer.....	29
6.2.1	Paging procedure using paging subchannel on CCCH	29
6.2.2	Paging using paging subchannel on PCCCH	29
6.2.3	Paging response to a page on CCCH	29
7	Medium Access Control (MAC) procedures on PCCCH.....	30
7.0a	Support of multiple TBF procedures	30
7.1	TBF establishment initiated by the mobile earth station on PCCCH	30
7.1.1	Permission to access the network	31
7.1.2	Initiation of a TBF establishment	31
7.1.2.1	Initiation of the packet access procedure	31
7.1.2.1.1	Access persistence control on PRACH.....	32
7.1.2.1.2	Handling of T3202 expiry.....	33
7.1.2.2	Packet assignment procedure	33
7.1.2.2.1	On receipt of a PACKET CHANNEL REQUEST or PACKET CHANNEL REQ TYPE 2 message	33
7.1.2.2.2	Void.....	34
7.1.2.2.3	Void.....	34
7.1.2.2.4	Packet access reject procedure	34
7.1.2.3	One phase packet access completion.....	35
7.1.2.4	Timing and frequency correction	35
7.1.3	Packet Resource Request Procedure (Iu mode only)	35
7.1.3.1	Initiation of the Packet resource request procedure	35
7.1.3.2	On receipt of a PACKET RESOURCE REQUEST message	35
7.1.3.3	Completion of Packet resource request procedure	36
7.1.4	Initiation of TBF Establishment on CCCH.....	36
7.1.5	Abnormal cases.....	37
7.2	TBF establishment initiated by the network on CCCH (A/Gb mode only).....	37
7.2.1	Entering the packet transfer mode	37
7.2.1.1	Packet downlink assignment procedure	37
7.2.1.2	Packet downlink assignment procedure completion	38
7.2.1.3	Void.....	38
7.2.2	Abnormal cases.....	38
7.3	Procedure for measurement report sending in packet idle mode.....	39
7.4	Cell change order procedures in packet idle mode	39
7.4.1	Cell change order procedure initiated on PCCCH	39
7.4.2	Cell change order procedure initiated on CCCH	39
7.5	Measurement order procedures in packet idle mode	39
7.6	Void.....	39
7.7	Void.....	39
7.8	TBF establishment on PACCH by network	39
7.9	GMPRS Resume procedure on PCCCH (A/Gb mode only)	39
7.9.1	Initiation of GMPRS resume procedure.....	39
7.9.2	Completion of GMPRS resume procedure	40
7.9.3	Abnormal cases.....	40
7.10	Talk Burst Request Transmission on PCCCH.....	40
7.10.1	Access persistence control on PRACH	40

7.10.2	On receipt of a PACKET CHANNEL REQ TYPE 2 message with Talk Burst Request Indication	41
7.10.3	Absence of PACKET UPLINK TALK BURST CONTROL RESPONSE	41
7.11	Uplink Talk Burst Control Transmission on Established TBF	41
7.11.1	On receipt of a PACKET UPLINK TALK BURST CONTROL message	41
8	Medium access control (MAC) procedures in packet transfer mode	42
8.1	Transfer of RLC data blocks	42
8.1.1	Uplink RLC data block transfer	42
8.1.1.1	Dynamic allocation uplink RLC data block transfer	43
8.1.1.1.1	PACCH operation (A/Gb mode only)	44
8.1.1.1.1a	PDCH3 PACCH operation (Iu mode only)	44
8.1.1.1.2	Resource reallocation for uplink TBF	44
8.1.1.1.3	Establishment of downlink TBF	46
8.1.1.2	Uplink PDCH(5,3) and PDCH(5,12) multiplexing	47
8.1.1.3	Void	47
8.1.1.4	Network initiated release of uplink TBF	47
8.1.1.5	Abnormal cases	48
8.1.1.6	Network initiated establishment of uplink TBF	48
8.1.1.7	Fixed allocation uplink RLC data block transfer	49
8.1.2	Downlink RLC data block transfer	49
8.1.2.1	Downlink RLC data block transfer	49
8.1.2.1.1	Abnormal cases	50
8.1.2.2	Polling for packet downlink ACK/NACK	50
8.1.2.3	Downlink PDCH(5,3) and PDCH(5,12) multiplexing	51
8.1.2.4	Resource reassignment for downlink	51
8.1.2.4a	Establishment of downlink TBF after downlink TBF release	52
8.1.2.4a.1	Abnormal cases	52
8.1.2.5	Establishment of uplink TBF	53
8.1.2.5.1	Abnormal cases (A/Gb mode)	55
8.1.2.5.1a	Abnormal cases (Iu mode)	55
8.1.2.6	Void	56
8.1.2.7	Void	56
8.1.2.8	Network initiated abnormal release of downlink TBF	56
8.1.2.9	Network initiated release of downlink TBF	56
8.1.2.10	Network initiated Establishment of Uplink TBF	57
8.1.3	Void	57
8.1.4	Multiplexing of control and data messages (A/Gb mode only)	57
8.1.5	Multiplexing multiple TBFs on the same burst (Iu mode only)	57
8.2	Packet PDCH release (Iu mode only)	58
8.3	Procedure for measurement report sending in Packet Transfer mode (Iu mode only)	58
8.4	Network controlled cell reselection procedure (Iu mode only)	59
8.4.1	Network controlled cell reselection completion	59
8.4.2	Abnormal cases	59
8.5	Measurement order procedures in packet transfer mode (Iu mode only)	60
8.6	Packet control acknowledgement	60
8.7	Abnormal cases	61
8.7.1	Abnormal release with return to CCCH or PCCCH	61
8.7.2	Abnormal release with random access	61
8.7.3	Abnormal release with system information	61
8.8	Packet link quality reporting in packet transfer mode (A/Gb mode only)	61
8.8a	Packet link quality reporting in packet transfer mode (Iu mode only)	61
8.9	Coding rate change procedure in packet transfer mode	61
8.9.1	Downlink TBF coding rate change procedure	61
8.9.2	Uplink TBF coding rate change procedure	62
9	Radio Link Control (RLC) procedures in packet transfer mode	62
9.1	Procedures and parameters for peer-to-peer operation	62
9.1.1	Send state variable V(S)	63
9.1.1a	Control send state variable V(CS)	63
9.1.2	Acknowledge state variable V(A)	63
9.1.3	Acknowledge state array V(B)	63
9.1.3.1	Acknowledge state array V(B) for GMPRS	63

9.1.3.2	Void.....	64
9.1.4	Block Sequence Number BSN.....	64
9.1.4.1	Block Sequence Number BSN for GPRS TBF.....	64
9.1.4.2	Void.....	64
9.1.4a	Void.....	64
9.1.5	Receive state variable V(R).....	64
9.1.6	Receive window state variable V(Q).....	64
9.1.7	Receive state array V(N).....	64
9.1.7.1	Receive state array V(N) in GMPRS TBF.....	64
9.1.7.2	Void.....	65
9.1.8	Starting Sequence Number (SSN) and Received Block Bitmap (RBB).....	65
9.1.8.1	Starting Sequence Number (SSN) and Received Block Bitmap (RBB) in GMPRS TBF.....	65
9.1.8.1.1	Generation of the bitmap.....	65
9.1.8.1.2	Interpretation of the bitmap.....	65
9.1.8.2	Void.....	66
9.1.9	Window size.....	66
9.1.9a	Filler octets.....	66
9.1.10	Compression.....	66
9.1.11	Segmentation of upper layer PDUs into RLC data units.....	68
9.1.12	Re-assembly of upper layer PDUs from RLC data units.....	68
9.1.12a	Void.....	69
9.1.12b	Void.....	69
9.1.12c	Dummy Data Block (Iu mode only).....	69
9.1.13	Void.....	69
9.2	Operation during RLC/MAC control message transfer.....	69
9.3	Operation during RLC data block transfer.....	69
9.3.1	Void.....	70
9.3.2	Acknowledged mode operation.....	70
9.3.2.1	Additional functionality in acknowledged mode on PDCH3 (Iu mode only).....	70
9.3.2.2	Establishment of temporary block flow.....	70
9.3.2.3	Operation of uplink temporary block flow.....	70
9.3.2.4	Release of uplink temporary block flow.....	71
9.3.2.5	Operation of downlink temporary block flow.....	72
9.3.2.6	Release of downlink temporary block flow.....	72
9.3.3	Unacknowledged mode operation.....	73
9.3.3.1	Establishment of temporary block flow.....	73
9.3.3.2	Operation of uplink temporary block flow.....	73
9.3.3.3	Release of uplink temporary block flow.....	74
9.3.3.4	Operation of downlink temporary block flow.....	75
9.3.3.5	Release of downlink temporary block flow.....	75
9.4	Abnormal release cases.....	75
9.4.1	Abnormal release with random access.....	75
9.4.2	Abnormal release with spotbeam reselection.....	75
9.5	Radio Link Control (RLC) procedures in packet transfer mode when using PNB3(1,6) Data in shared mode.....	76
10	RLC/MAC block structure.....	76
10.0a	PNB(m,n) bursts - A/Gb mode.....	76
10.0b	PNB2(m,n) bursts - A/Gb mode.....	76
10.0c	PDCH - Iu mode.....	77
10.1	Radio block structure.....	78
10.2	Public information bits.....	81
10.2.1	Downlink PUI for PDCH (4,n) and PDCH (5,n) and PDCH2(5,3).....	84
10.2.1a	Downlink PUI for PDCH3(5,3).....	85
10.2.1b	Downlink PUI for PDCH3(5,12).....	85
10.2.1c	Downlink PUI for PDCH3(10,3).....	86
10.2.2	Downlink Extended PUI for PDCH2(5,12).....	87
10.2.3	Uplink PUI for PDCH (4,3), PDCH (5,n), PDCH2(5,n) and PDCH3(5,n).....	88
10.2.4	Downlink PUI for PDCH (2,6).....	88
10.2.4a	Downlink PUI for PDCH3(2,6).....	88
10.2.5	Uplink PUI for PDCH (1,n), PDCH3(1,n) and PDCH3(2,6).....	89
10.3	RLC/MAC header.....	89

10.3.1	Downlink RLC/MAC header for PNB(m,n) and PNB2(m,n) bursts	89
10.3.1a	Downlink RLC/MAC Data header for PNB3(m,n) bursts - Iu mode only	90
10.3.1b	Downlink RLC/MAC Control header for PNB3(m,n) bursts - Iu mode only.....	90
10.3.2	Uplink RLC/MAC header for PNB(m,n) and PNB2(m,n) bursts - A/Gb mode only	90
10.3.2a	Uplink RLC/MAC Data header for PNB3(m,n) bursts - Iu mode only	91
10.3.2b	Uplink RLC/MAC Control header for PNB3(m,n) bursts - Iu mode only.....	91
10.3.2c	Header type 2: Uplink RLC/MAC Data header for PNB3(1,6) Data in dynamic allocation mode - Iu mode only	91
10.4	Header fields	91
10.4.1	Uplink state flag (USF) field.....	91
10.4.1.1	PDCH(4,3), PDCH(5,3) PDCH2(5,3) and PDCH2(5,12) - A/Gb mode only	91
10.4.1.1a	PDCH3(5,3),PDCH3(5,12) and PDCH3(10,3) - Iu mode only	91
10.4.1.2	PDCH(2,6) - A/Gb mode only	92
10.4.1.2a	PDCH3(2,6) and PDCH3(1,6) - Iu mode only	92
10.4.2	Void	93
10.4.3	Stall indicator (SI) bit	93
10.4.4	Supplementary/polling (S/P) bit	93
10.4.5	Unsolicited uplink grant (UUG) field	93
10.4.5.1	UUG field for terminal type A and C - A/Gb mode only	93
10.4.5.2	UUG field for terminal type D - A/Gb mode only	94
10.4.5.3	PDCH3 UUG field - Iu mode only.....	94
10.4.5.3.1	PDCH3(10,3) and PDCH3(5,3) - Iu mode only	94
10.4.5.3.2	PDCH3(5,12) and PDCH3(2,6) - Iu mode only	95
10.4.5.3.3	DACCH - Iu mode only	95
10.4.6	Void	95
10.4.7	Payload type field	95
10.4.7a	Void	96
10.4.8	Final Block Indicator (FBI) bit	96
10.4.8a	Void	96
10.4.8b.1	Split Block Number (SPBN) - Iu mode only	96
10.4.8b.2	Final Split Block (FSB) - Iu mode only.....	96
10.4.9	Void	96
10.4.9a	Void	96
10.4.9b	Void	96
10.4.9c	Void	96
10.4.9d	Direction (D) bit (A/Gb mode only)	96
10.4.9e	SRB field (Iu mode only).....	97
10.4.10	Temporary flow identifier (TFI) field.....	97
10.4.10.1	Downlink header TFI	97
10.4.10.1a	Downlink header TFI (bit7)	97
10.4.10.1.1	Data-only downlink RLC/MAC block	97
10.4.10.1.2	Control-only downlink RLC/MAC block (A/Gb mode only)	97
10.4.10.1.3	Control+data downlink RLC/MAC block (A/Gb mode only).....	98
10.4.10.2	Uplink header TFI	98
10.4.10.2.1	Data-only uplink RLC/MAC block	98
10.4.10.2.2	Control-only uplink RLC/MAC block (A/Gb mode only)	98
10.4.10.2.3	Control+data uplink RLC/MAC block (A/Gb mode only).....	98
10.4.10a	Power control (PC) Parameters field	98
10.4.11	Extension (E) bit.....	98
10.4.12	Block Sequence Number (BSN) field.....	99
10.4.12a	Void	99
10.4.13	Void	99
10.4.14	Void	99
10.4.14a	Void	99
10.4.15	Last Part Size (LPS) field	99
10.4.15a	PDU Length.....	99
10.4.15b	Length Indicator (LI)	100
10.4.16	RLC data field.....	100
10.4.17	Control message contents field	100
10.4.18	Unsatisfied Demand (UD)	100
10.4.19	Immediate Termination Request (ITR).....	101