



**GEO-Mobile Radio Interface Specifications (Release 3);
Third Generation Satellite Packet Radio Service;
Part 5: Radio interface physical layer specifications;
Sub-part 5: Radio Transmission and Reception;
GMR-1 3G 45.005**

[ETSI TS 101 376-5-5 V3.3.1 \(2012-12\)](https://standards.iteh.ai/catalog/standards/etsi/269699cc-1442-443c-9576-c4b04d5d3648/etsi-ts-101-376-5-5-v3-3-1-2012-12)

[https://standards.iteh.ai/catalog/standards/etsi/269699cc-1442-443c-9576-c4b04d5d3648/etsi-ts-101-376-5-5-v3-3-1-2012-](https://standards.iteh.ai/catalog/standards/etsi/269699cc-1442-443c-9576-c4b04d5d3648/etsi-ts-101-376-5-5-v3-3-1-2012-12)

Reference

RTS/SES-00328-5-5

Keywords3G, earth station, GMPRS, GMR, GPRS, GSM,
GSO, MES, mobile, MSS, radio, satellite**ETSI**650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2012.
All rights reserved.

DECTTM, PLUGTESTSTM, UMTSTM and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPPTM and LTETM are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	5
Foreword.....	5
Introduction	6
1 Scope	8
2 References	8
2.1 Normative references	8
2.2 Informative references	9
3 Definitions, abbreviations and symbols	9
3.1 Definitions	9
3.2 Abbreviations	10
3.3 Symbols.....	10
3.4 Terminal Types (informative)	10
4 Frequency bands and channel arrangement.....	11
4.1 Frequency bands and duplex method	11
4.2 RF carrier spacing and designation	12
4.3 RF carrier used for synchronization and spot beam selection	14
4.4 Frequency assignment to spot beams	14
5 Stability requirements.....	14
5.1 Frequency and symbol timing stability	14
5.1.1 Definition of operating conditions	14
5.1.2 Frequency and timing stability requirement	14
5.1.3 Frequency and timing stability requirements for packet data	14
5.2 Frequency switching time	15
5.3 MES time alignment accuracy.....	15
6 Transmitter characteristics	16
6.1 Power output characteristics and power class	16
6.1.1 Average EIRP - Extreme Conditions	16
6.1.2 Average EIRP - Normal Conditions	16
6.1.3 Single Burst EIRP	17
6.1.4 Access Burst EIRP	17
6.2 Antenna radiation pattern	17
6.2.1 Boresight Oriented Radiation Patterns.....	18
6.2.2 Non-Boresight Oriented Radiation Patterns	18
6.3 Transmit polarization	18
6.4 Carrier-off conditions	19
6.4a Carrier-standby conditions	19
6.5 Droop, ramp-up and ramp-down	19
6.6 Power control range and accuracy.....	20
6.6.1 Approach	20
6.6.2 Procedures and timing	20
6.6.3 Range	20
6.6.4 Accuracy	20
6.6.5 Attenuation step size	21
6.6.6 Initial power level P_{init}	21
6.7 Adjacent channel interference	21
6.7.1 Interference due to modulation	21
6.7.2 Interference due to switching transients.....	23
6.8 Unwanted emissions.....	23
6.8.1 Unwanted emissions in the carrier-on state and carrier-standby state (L-band)	23
6.8.2 Unwanted emissions in the carrier-off state (L-band).....	23
6.8.3 Unwanted emissions in the carrier-on state and carrier-standby state (S-Band).....	24
6.8.4 Unwanted emissions in the carrier-off state (S-band).....	24

7	Receiver characteristics	24
7.1	Receive antenna pattern.....	24
7.1.1	Boresight Oriented Radiation Patterns.....	24
7.1.2	Non-Boresight Oriented Radiation Patterns	24
7.2	Receive polarization.....	25
7.3	Receiver figure of merit	25
7.4	Receiver sensitivity	26
7.4.1	Receiver BER in static conditions	27
7.4.2	Receiver BER in Rician fading (A/Gb mode only)	28
7.4.3	FER of logical channels (A/Gb mode only).....	28
7.4.4	FER of PUI (A/Gb mode only).....	28
7.4.5	FER of PUI and ULMAP (Iu mode only).....	29
7.4.6	FER of Common Control Channels (system using FCCH3)	29
7.5	Receiver selectivity	29
7.6	Receiver intermodulation	30
7.7	Receiver blocking characteristics	30
7.7.1	L-Band	30
7.7.2	S-Band	30
7.8	Receive signal strength.....	31
7.9	Erroneous frame Indication Performance.....	32
7.10	Maximum Received Power Level	32
8	GPS receiver characteristics	32
Annex A (informative):	Antenna factor equation.....	33
Annex B (normative):	Environmental conditions	34
Annex C (normative):	Channel model.....	35
Annex D (informative):	Derivation of receiver sensitivity specifications	36
D.1	Introduction	36
D.2	Definitions.....	36
D.2.1	Integral sensitivity	36
D.2.2	Radiated sensitivity	37
D.2.3	Conducted sensitivity	37
D.3	Parameters	38
D.4	Calculations.....	38
Annex E (informative):	Bibliography.....	40
History		41

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Satellite Earth Stations and Systems (SES).

The contents of the present document are subject to continuing work within TC-SES and may change following formal TC-SES approval. Should TC-SES modify the contents of the present document it will then be republished by ETSI with an identifying change of release date and an increase in version number as follows:

Version 3.m.n

where:

- the third digit (n) is incremented when editorial only changes have been incorporated in the specification;
- the second digit (m) is incremented for all other types of changes, i.e. technical enhancements, corrections, updates, etc.

The present document is part 5, sub-part 5 of a multi-part deliverable covering the GEO-Mobile Radio Interface Specifications (Release 3); Third Generation Satellite Packet Radio Service, as identified below:

Part 1: "General specifications";

Part 2: "Service specifications";

Part 3: "Network specifications";

Part 4: "Radio interface protocol specifications";

Part 5: "Radio interface physical layer specifications";

Sub-part 1: "Physical Layer on the Radio Path: General Description; GMR-1 3G 45.001";

Sub-part 2: "Multiplexing and Multiple Access; Stage 2 Service Description; GMR-1 3G 45.002";

Sub-part 3: "Channel Coding; GMR-1 3G 45.003";

Sub-part 4: "Modulation; GMR-1 3G 45.004";

Sub-part 5: "Radio Transmission and Reception; GMR-1 3G 45.005";

Sub-part 6: "Radio Subsystem Link Control; GMR-1 3G 45.008";

Sub-part 7: "Radio Subsystem Synchronization; GMR-1 3G 45.010";

Part 6: "Speech coding specifications";

Part 7: "Terminal adaptor specifications".

Introduction

GMR stands for GEO (Geostationary Earth Orbit) Mobile Radio interface, which is used for Mobile Satellite Services (MSS) utilizing geostationary satellite(s). GMR is derived from the terrestrial digital cellular standard GSM and supports access to GSM core networks.

The present document is part of the GMR Release 3 specifications. Release 3 specifications are identified in the title and can also be identified by the version number:

- Release 1 specifications have a GMR 1 prefix in the title and a version number starting with "1" (V1.x.x).
- Release 2 specifications have a GMPRS 1 prefix in the title and a version number starting with "2" (V2.x.x).
- Release 3 specifications have a GMR-1 3G prefix in the title and a version number starting with "3" (V3.x.x).

The GMR release 1 specifications introduce the GEO-Mobile Radio interface specifications for circuit mode Mobile Satellite Services (MSS) utilizing geostationary satellite(s). GMR release 1 is derived from the terrestrial digital cellular standard GSM (phase 2) and it supports access to GSM core networks.

The GMR release 2 specifications add packet mode services to GMR release 1. The GMR release 2 specifications introduce the GEO-Mobile Packet Radio Service (GMPRS). GMPRS is derived from the terrestrial digital cellular standard GPRS (included in GSM Phase 2+) and it supports access to GSM/GPRS core networks.

The GMR release 3 specifications evolve packet mode services of GMR release 2 to 3rd generation UMTS compatible services. The GMR release 3 specifications introduce the GEO-Mobile Radio Third Generation (GMR-1 3G) service. Where applicable, GMR-1 3G is derived from the terrestrial digital cellular standard 3GPP and it supports access to 3GPP core networks.

Due to the differences between terrestrial and satellite channels, some modifications to the GSM or 3GPP standard are necessary. Some GSM and 3GPP specifications are directly applicable, whereas others are applicable with modifications. Similarly, some GSM and 3GPP specifications do not apply, while some GMR specifications have no corresponding GSM or 3GPP specification.

Since GMR is derived from GSM and 3GPP, the organization of the GMR specifications closely follows that of GSM or 3GPP as appropriate. The GMR numbers have been designed to correspond to the GSM and 3GPP numbering system. All GMR specifications are allocated a unique GMR number. This GMR number has a different prefix for Release 2 and Release 3 specifications as follows:

- Release 1: GMR n xx.zyy.
- Release 2: GMPRS n xx.zyy.
- Release 3: GMR-1 3G xx.zyy.

where:

- xx.0yy (z = 0) is used for GMR specifications that have a corresponding GSM or 3GPP specification. In this case, the numbers xx and yy correspond to the GSM or 3GPP numbering scheme.
- xx.2yy (z = 2) is used for GMR specifications that do not correspond to a GSM or 3GPP specification. In this case, only the number xx corresponds to the GSM or 3GPP numbering scheme and the number yy is allocated by GMR.
- n denotes the first (n = 1) or second (n = 2) family of GMR specifications.