

ETSI TS 101 569-1 V1.1.1 (2013-10)



Integrated Broadband Cable Telecommunication Networks (CABLE); Cable Network Transition to IPv6 Part 1: IPv6 Transition Requirements

[ETSI TS 101 569-1 V1.1.1 \(2013-10\)](https://standards.iteh.ai/catalog/standards/etsi/b8444920-903c-48bc-9978-995b3233b62a/etsi-ts-101-569-1-v1-1-1-2013-10)

<https://standards.iteh.ai/catalog/standards/etsi/b8444920-903c-48bc-9978-995b3233b62a/etsi-ts-101-569-1-v1-1-1-2013-10>

ReferenceDTS/CABLE-00003

Keywords

CABLE, IPCable, IPv6

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2013.
All rights reserved.

DECTTM, PLUGTESTSTM, UMTSTM and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPPTM and LTETM are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	13
Foreword.....	13
Introduction	13
1 Scope	14
2 References	15
2.1 Normative references	15
2.2 Informative references.....	24
3 Symbols and abbreviations.....	25
3.1 Symbols.....	25
3.2 Abbreviations	25
4 Specification Construct	28
5 Background and Concept of Transition.....	28
5.1 Broadband Cable Network Providers.....	29
5.2 IP Connectivity in Cable Networks	29
5.2.1 Customer Host	30
5.2.2 Home Network.....	30
5.2.3 Access Gateway	30
5.2.4 Access Network	30
5.2.5 Headend	31
5.2.6 Internet.....	31
5.2.6.1 Transition Technology Summary.....	31
6 IPv6 Transition Technologies Specifications.....	33
6.1 CPE Specification.....	36
6.1.1 Introduction.....	36
6.1.2 Functional Description.....	36
6.1.3 Summary Base Function: Device Initialization	37
6.1.3.1 Feature:Device Initialization	37
6.1.4 Disabled Mode.....	37
6.1.5 IPv4 Protocol Enabled Mode.....	37
6.1.6 Dual IP Protocol Enabled Mode	37
6.1.7 IPv6 Protocol Enabled Mode.....	38
6.1.8 Transition Technology Provisioning.....	38
6.1.9 LAN Functionality	39
6.1.9.1 Address Assignment.....	39
6.1.9.2 DNS.....	40
6.1.10 Device Management	40
6.1.11 Security	40
6.2 General Requirements for Core Network Elements (AFTR/BR/GN)	40
6.2.1 Device Management Requirements	40
6.2.1.1 Feature: LLDP.....	40
6.2.1.2 Feature: NTP, IPv4.....	41
6.2.1.3 Feature: NTP, IPv6.....	41
6.2.1.4 Feature: SSH, IPv4.....	41
6.2.1.5 Feature: SSH, IPv6.....	41
6.2.1.6 Feature: Telnet, IPv4.....	41
6.2.1.7 Feature: Telnet, IPv6.....	41
6.2.1.8 Feature: SNMPv2, IPv4	42
6.2.1.9 Feature: SNMPv2, IPv6	42
6.2.1.10 Feature: SNMPv3, IPv4	42
6.2.1.11 Feature: SNMPv3, IPv6	42
6.2.1.12 Feature: Remote Access - TACACS+, IPv4	42
6.2.1.13 Feature: Remote Access - TACACS+, IPv6	42

6.2.1.14	Feature: Remote Access - RADIUS, IPv4	43
6.2.1.15	Feature: Remote access: Radius, IPv6	43
6.2.2	General Specification Performance Requirements	43
6.2.2.1	Feature: Node Latency below 0,2 ms	43
6.2.2.2	Feature: Forwarding performance	43
6.2.3	General Feature Requirements	43
6.2.3.1	Feature: Load Balancing ECMP	43
6.2.3.2	Feature: LAG/LACP	43
6.2.3.3	Feature: Dot1Q interfaces	44
6.2.3.4	Feature: Traffic monitoring	44
6.2.3.5	Feature: Netflow IPv4	44
6.2.3.6	Feature: Netflow IPv6	44
6.2.3.7	Feature: CoPP IPv4	45
6.2.3.8	Feature: CoPP IPv6	45
6.2.3.9	Feature: ACL support IPv4	45
6.2.3.10	Feature: ACL support IPv6	45
6.2.3.11	Feature: ISSU	46
6.2.3.12	Feature: RP / RE redundancy - Non Stop Forwarding - Non Stop Routing	46
6.2.3.13	Feature: Jumbo Frames IPv4	46
6.2.3.14	Feature: Jumbo Frames IPv6	46
6.2.3.15	Feature: NDP, NUD, DAD	46
6.2.3.16	Feature: Ethernet OAM	47
6.2.3.17	Feature: QoS	47
6.2.4	Routing Protocol Requirements	47
6.2.4.1	Feature: Static Routes, IPv4	47
6.2.4.2	Feature: Static Routes, IPv6	47
6.2.4.3	Feature: OSPFv2	48
6.2.4.4	Feature: OSPFv3	48
6.2.4.5	Feature: ISIS IPv4	48
6.2.4.6	Feature: ISIS IPv6	48
6.2.4.7	Feature: BGP IPv4	49
6.2.4.8	Feature: BGP IPv6	49
6.2.4.9	Feature: MP-BGP IPv4	50
6.2.4.10	Feature: MP-BGP IPv6	50
6.2.4.11	Feature: BFD IPv4	51
6.2.4.12	Feature: BFD IPv6	51
6.2.4.13	Feature: Policy Based Routing IPv4	51
6.2.4.14	Feature: Policy Based Routing IPv6	52
6.2.5	MPLS Requirements	52
6.2.5.1	Feature: MPLS LDP IPv4	52
6.2.6	Service Requirements	52
6.2.6.1	Feature: IP-VPN's IPv4	52
6.2.6.2	Feature: IP-VPN's IPv6	52
6.2.6.3	Feature: Point-to-Point L2VPN	52
6.2.6.4	Feature: VPLS	53
6.2.6.5	Feature: 6PE	53
6.2.6.6	Feature: 6VPE	53
6.3	DS-Lite	53
6.3.1	DS-Lite Technology Feature Summary	53
6.3.2	Main DS-Lite RFC References	58
6.3.3	DS-Lite AFTR CORE Device (LSN/CGN) Specification and Requirements	59
6.3.4	Hardware/Software Requirements	59
6.3.4.1	Feature: HA Physical Redundancy NPUs	59
6.3.4.2	Feature: ISSU	59
6.3.4.3	Feature: RP/RE redundancy	59
6.3.4.4	Feature: Shared/Split Resources	60
6.3.4.5	Feature: Traffic Based Load Balanced NPUs	60
6.3.5	Performance Requirements	60
6.3.5.1	Feature: Node latency	60
6.3.5.2	Feature: Max throughput per NPU	60
6.3.5.3	Feature: Chassis Throughput	61
6.3.5.4	Feature: Min Sessions per AFTR Chassis	61

6.3.5.5	Feature: Minimum Customer IPv4 Addresses per NPU	61
6.3.5.6	Feature: Min Customer B4s per NPU	61
6.3.6	Feature Specifications	61
6.3.6.1	Feature: Tunnel Identifiers/Client-Customer ID	61
6.3.6.2	Feature: ICMPv6: Neighbour Discovery and Stateless Auto-Configuration	62
6.3.6.3	Feature: IPv6 Global Unicast Address Format	63
6.3.6.4	Feature: DS-Lite timers	64
6.3.6.5	Feature: Thresholds and Watermarks	64
6.3.6.6	Feature: Software Initialization Dynamic Tunnels	65
6.3.6.7	Feature: Port Block Allocation per IP	65
6.3.6.8	Feature: Deterministic NAT / Deterministic Dynamic Allocation and Thresholds	65
6.3.6.9	Feature: IP Ranges per Chassis	66
6.3.6.10	Feature: NAT Grouping resource Sharing	67
6.3.6.11	Feature: Virtual interface per Chassis	67
6.3.6.12	Feature: NPU to Interface throughput ratio	67
6.3.6.13	Feature: AFTR Address (es)	67
6.3.6.14	Feature: Anycast Gateway Address	68
6.3.6.15	Feature: Multiple Source Prefix Filtering per AFTR Interface / Address	68
6.3.6.16	Feature: AFTR Address Withdrawal	68
6.3.6.17	Feature: Chassis DS-Lite Clustering	68
6.3.6.18	Feature: Multiple Transition Technology Resource Sharing	69
6.3.6.19	Feature: NPU / chassis Buffering	69
6.3.6.20	Feature: Tunnel MTU Sizing	70
6.3.6.21	Feature: MSS Clamping	70
6.3.6.22	Feature: DS-Lite Fragmentation and Buffering according to RFC 6333	70
6.3.6.23	Feature: Stateful ICMP with PMTU	71
6.3.6.24	Feature: Port Reservation	71
6.3.6.25	Feature: Static Port Forwards	71
6.3.6.26	Feature: PCP Mode	71
6.3.6.27	Feature: PCP Failure	72
6.3.6.28	Feature: PCP (SI-ID Extension Base) Multi-session Dynamic Forwarding	73
6.3.7	Monitoring and Management	73
6.3.7.1	Feature: LLDP	73
6.3.7.2	Feature: NTP, IPv4	73
6.3.7.3	Feature: NTP, IPv6	73
6.3.7.4	Feature: SSH, IPv4	74
6.3.7.5	Feature: SSH, IPv6	74
6.3.7.6	Feature: Telnet, IPv4	74
6.3.7.7	Feature: Telnet, IPv6	74
6.3.7.8	Feature: SNMP DS-Lite General	74
6.3.7.9	Feature: SNMPv2, IPv4	75
6.3.7.10	Feature: SNMPv2, IPv6	75
6.3.7.11	Feature: SNMPv3, IPv4	75
6.3.7.12	Feature: SNMPv3, IPv6	75
6.3.7.13	Feature: Remote Access - TACACS+, IPv4	75
6.3.7.14	Feature: Remote Access: TACACS+, IPv6	75
6.3.8	DS-Lite CPE Requirements	76
6.3.8.1	CPE Definition	78
6.3.8.1.1	Feature: Cable Router B4 Functionality	78
6.3.8.1.2	Feature: SLAAC	78
6.3.8.1.3	Feature: DNS	78
6.3.8.1.4	Feature: IPv6 LAN IP Addressing	78
6.3.8.1.5	Feature: IPv4 LAN IP Addressing	78
6.3.8.1.6	Feature: Packet Encapsulation	79
6.3.8.1.7	Feature: Packet Decapsulation	79
6.3.8.1.8	Feature: MTU and fragmentation	79
6.3.8.1.9	Feature: MSS clamping	80
6.3.8.1.10	Feature: DHCPv4 option 26	80
6.3.8.1.11	Feature: Recommendations	81
6.3.8.1.12	Feature: Inbound sessions	81
6.3.8.1.13	Feature: Dual Stack Lite QoS using the IPv6 Flow label	81
6.3.8.1.14	Feature: MIB Support for DS Lite	82

6.3.8.1.15	Feature: Port Reservation	82
6.3.8.1.16	Feature: PCP Mode.....	82
6.3.8.1.17	Feature: PCP Failure.....	83
6.3.9	DS-Lite Technical Viability.....	84
6.4	NAT64 Technology Summary	84
6.4.1	NAT64 LSN Technology Feature Summary	86
6.4.2	Main NAT64 RFC References.....	89
6.4.3	CORE Device (LSN/CGN).....	90
6.4.4	Hardware / Software Requirements	90
6.4.4.1	Feature: HA Physical Redundancy NPUs	90
6.4.4.2	Feature: ISSU	90
6.4.4.3	Feature: RP / RE redundancy	90
6.4.4.4	Feature: Shared/Split Resources.....	91
6.4.4.5	Feature: Traffic Based Load Balanced NPUs	91
6.4.5	Performance Requirements.....	91
6.4.5.1	Feature: Node latency	91
6.4.5.2	Feature: Max throughput per NPU.....	91
6.4.5.3	Feature: Chassis Throughput.....	92
6.4.5.4	Feature: Min Sessions per NAT64 Chassis	92
6.4.5.5	Feature: Minimum Customer IPv4 Addresses per NPU	92
6.4.5.6	Feature: Min Customer CPEs per NPU.....	92
6.4.6	Feature Specifications.....	92
6.4.6.1	Feature: Source Ipv6/Client-Customer ID	92
6.4.6.2	Feature: ICMPv6: Neighbour Discovery and Stateless Auto-Configuration	93
6.4.6.3	Feature: IPv6 Global Unicast Address Format.....	93
6.4.6.4	Feature: NAT64 LSN timers	93
6.4.6.5	Feature: NAT64 DNS64	93
6.4.6.6	Feature: Thresholds and Watermarks.....	94
6.4.6.7	Feature: Port Block Allocation per IP	94
6.4.6.8	Feature: Deterministic NAT / Deterministic Dynamic thresholds	94
6.4.6.9	Feature: IP Ranges per Chassis	96
6.4.6.10	Feature: NAT Grouping resource Sharing	96
6.4.6.11	Feature: Virtual interface per Chassis	96
6.4.6.12	Feature: NPU to Interface throughput ratio.....	97
6.4.6.13	Feature: NAT64 Address (es)	97
6.4.6.14	Feature: Anycast Gateway Address	97
6.4.6.15	Feature: Multiple Source Prefixes per NAT64 Interface.....	97
6.4.6.16	Feature: NAT64 Address Withdrawal.....	98
6.4.6.17	Feature: Chassis Clustering.....	98
6.4.6.18	Feature: Multiple Transition Technology Resource Sharing	98
6.4.6.19	Feature: NPU / chassis Buffering.....	99
6.4.6.20	Feature: NAT64 LSN Fragmentation and Buffering.....	99
6.4.6.21	Feature: Stateful ICMP	99
6.4.6.22	Feature: Port Reservation.....	100
6.4.7	Monitoring and Management.....	100
6.4.7.1	Feature: LLDP.....	100
6.4.7.2	Feature: NTP, IPv4.....	100
6.4.7.3	Feature: NTP, IPv6.....	100
6.4.7.4	Feature: SSH, IPv4.....	100
6.4.7.5	Feature: SSH, IPv6.....	101
6.4.7.6	Feature: Telnet, IPv4.....	101
6.4.7.7	Feature: Telnet, IPv6.....	101
6.4.7.8	Feature: SNMPv2, IPv4	101
6.4.7.9	Feature: SNMPv2, IPv6	101
6.4.7.10	Feature: SNMPv3, IPv4	101
6.4.7.11	Feature: SNMPv3, IPv6	102
6.4.7.12	Feature: Remote Access - TACACS+, IPv4	102
6.4.7.13	Feature: Remote Access - TACACS+, IPv6	102
6.4.8	NAT64 CPE requirements	102
6.4.8.1	Feature: WAN Interface Address Requirements.....	103
6.4.8.2	Feature: Local Area Networking Interfaces	103
6.4.8.3	Feature: IP address provision	103

6.4.8.4	Feature: Integrated IPv6 Statefull Firewall	103
6.4.8.5	Feature: Recursive DNS Server	104
6.4.8.6	Feature: User Interface Provision.....	104
6.4.8.7	Feature: Access Control	104
6.4.8.8	Feature: Device Localization	104
6.4.8.9	Feature: CPE Device Status Indication	104
6.4.8.10	Feature: Router Basic Configuration.....	105
6.4.8.11	Feature: Advanced router control and configuration.....	105
6.4.8.12	Feature: The CPE device has to implement a Firewall user interface with user accessible configuration control.....	105
6.4.8.13	Feature: User Interface - Parental Control	106
6.4.8.14	Feature: Wireless Status and configuration.....	106
6.4.8.15	Feature: CPE Configuration Options	106
6.4.9	Technical Viability	106
6.5	NAT44.....	107
6.5.1	NAT44 Technical Summary	107
6.5.2	Technical Specifications	108
6.5.3	Main NAT44 RFC References.....	111
6.5.4	CORE Device (LSN/CGN).....	111
6.5.5	Hardware/Software Requirements	111
6.5.5.1	Feature: HA Physical Redundancy NPUs	111
6.5.5.2	Feature: ISSU	111
6.5.5.3	Feature: RP / RE redundancy	112
6.5.5.4	Feature: Shared/Split Resources.....	112
6.5.5.5	Feature: Traffic Based Load Balanced NPUs	112
6.5.5.6	Feature: Routing and MPLS.....	112
6.5.6	Performance Requirements.....	113
6.5.6.1	Feature: Node latency	113
6.5.6.2	Feature: Max throughput per NPU.....	113
6.5.6.3	Feature: Chassis Throughput.....	113
6.5.6.4	Feature: Min Sessions per NAT44 CGN Chassis.....	114
6.5.6.5	Feature: Minimum Customer IPv4 Addresses per NPU	114
6.5.6.6	Feature: Min Customer CPEs per NPU.....	114
6.5.7	Feature Specifications.....	114
6.5.7.1	Feature: NAT44 - RFC 4787	114
6.5.7.2	Feature: NAT44 - RFC 5382.....	115
6.5.7.3	Feature: NAT44 - RFC 5508.....	115
6.5.7.4	Feature: NAT44 - Network Address and Port Mapping - Endpoint Independent Mapping.....	116
6.5.7.5	Feature: NAT44 - Translation Filtering - Endpoint Independent Filtering	117
6.5.7.6	Feature: NAT44 - Paired IP Address Assignment	117
6.5.7.7	Feature: NAT44 - Port Parity Assignment	117
6.5.7.8	Feature: NAT44 - Hair-pinning.....	117
6.5.7.9	Feature: NAT44 - 1:1 IP Mapping.....	117
6.5.7.10	Feature: NAT44 - Outside-Service-App mapping for inside-VRF	117
6.5.7.11	Feature: Private IPv4/Client-Customer ID	118
6.5.7.12	Feature: NAT44 CGN timers	118
6.5.7.13	Feature: Thresholds and Watermarks.....	118
6.5.7.14	Feature: Port Block Allocation per IP	119
6.5.7.15	Feature: Deterministic NAT / Deterministic Dynamic thresholds	119
6.5.7.16	Feature: IP Ranges per Chassis	120
6.5.7.17	Feature: NAT Grouping resource Sharing	121
6.5.7.18	Feature: NPU to Interface throughput ratio.....	121
6.5.7.19	Feature: NAT44 CGN Address (es).....	121
6.5.7.20	Feature: Source IP per NAT44 CGN Interface	121
6.5.7.21	Feature: NAT44 CGN default route Withdrawal	122
6.5.7.22	Feature: Chassis Clustering.....	122
6.5.7.23	Feature: Multiple Transition Technology Resource Sharing	122
6.5.7.24	Feature: NPU/chassis Buffering.....	123
6.5.7.25	Feature: Stateful ICMP	123
6.5.7.26	Feature: Port Reservation.....	123
6.5.7.27	Feature: Static Port Forwards.....	123
6.5.7.28	Feature: PCP Mode	124