

ETSI TS 102 527-1 V1.3.1 (2012-01)



**Digital Enhanced Cordless Telecommunications (DECT);
New Generation DECT;
Part 1: Wideband speech**

(<https://standards.iteh.ai>)
Document Preview

[ETSI TS 102 527-1 V1.3.1 \(2012-01\)](https://standards.iteh.ai/catalog/standards/etsi/7117dddf-4fe1-48d8-bf20-179df8c16d85/etsi-ts-102-527-1-v1-3-1-2012-01)

<https://standards.iteh.ai/catalog/standards/etsi/7117dddf-4fe1-48d8-bf20-179df8c16d85/etsi-ts-102-527-1-v1-3-1-2012-01>

ReferenceRTS/DECT-NG0260

Keywords

7 kHz, audio, codec, DECT, GAP, IMT-2000,
interoperability, mobility, profile, radio, speech,
TDD, TDMA

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iteh Standards
(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chairecor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2012.
All rights reserved.

DECTTM, PLUGTESTSTM, UMTSTM and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPPTM and LTETM are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	8
Foreword.....	8
1 Scope	9
2 References	9
2.1 Normative references	9
2.2 Informative references.....	10
3 Definitions, symbols and abbreviations	11
3.1 Definitions.....	11
3.2 Symbols.....	11
3.3 Abbreviations	12
4 Description of services	13
4.1 Enhanced wideband speech.....	13
4.1.1 Audio performance requirements	14
4.2 Wideband speech scenarios.....	14
4.2.1 Internal calls inside a New Generation DECT system.....	14
4.2.2 Calls between two New Generation DECT systems interconnected by ISDN	14
4.2.3 Calls between two New Generation DECT systems interconnected by IP packet based network.....	15
4.2.4 Calls between a New Generation DECT system and a digital phone supporting compatible codecs.....	15
4.2.4.1 Via ISDN	15
4.2.4.2 Via IP network	15
4.2.4.3 Internal PABX calls	15
4.2.5 Legacy scenarios.....	15
5 Service and feature definitions.....	16
5.1 New Generation DECT Speech Services	16
5.2 Network (NWK) features	16
5.3 Data Link Control (DLC) service definitions.....	16
5.4 Medium Access Control (MAC) service definitions.....	17
5.5 Physical Layer (PHL) service definitions.....	17
5.6 Speech coding and audio feature definitions	17
5.7 Application features	21
6 Inter-operability requirements.....	21
6.1 General	21
6.2 New Generation DECT Speech Services support status	21
6.3 Services to DECT feature implementation mappings.....	21
6.4 NWK features.....	29
6.5 Data Link Control (DLC) services	30
6.6 Medium Access Control (MAC) services	31
6.7 Physical layer (PHL) services	31
6.8 Speech coding and audio features	32
6.9 Application features	33
6.10 Network (NWK) feature to procedure mapping.....	33
6.11 Data Link Control (DLC) Service to procedure mapping	34
6.12 Medium Access Control (MAC) service to procedure mapping	35
6.13 Application feature to procedure mapping	36
6.14 General requirements	36
6.14.1 Network (NWK) layer message contents.....	36
6.14.2 Transaction identifier.....	36
6.14.3 Length of a Network (NWK) layer message	36
6.14.4 Handling of error and exception conditions.....	37
6.14.5 Generic Access Profile (GAP) default setup attributes	37
6.14.6 Coexistence of Mobility Management (MM) and Call Control (CC) procedures	37
6.14.7 Coding rules for information elements	37

7	Procedure description.....	38
7.1	Backward compatibility with Generic Access Profile (GAP)	38
7.1.1	Requirement for New Generation DECT Fixed Parts (FPs) requirement.....	38
7.1.2	Requirement for New Generation DECT Portable Parts (PPs) registered on GAP compliant FPs	38
7.2	Generic Access Profile (GAP) procedures	38
7.3	Network (NWK) layer procedures	38
7.3.1	Exchange of codec list during registration and location registration	39
7.3.2	Basic service wideband speech and default attributes	39
7.3.3	Codec Negotiation during call establishment	39
7.3.4	Codec Change	41
7.3.4.1	Service change info	41
7.3.5	Slot type modification.....	41
7.3.5.1	Failure of slot type modification	41
7.3.6	Internal call setup.....	42
7.3.7	Terminal capability indication	42
7.3.8	Indirect FT initiated link establishment	44
7.3.8.1	Paging messages	44
7.3.8.1.1	LCE-REQUEST-PAGE message	44
7.3.8.1.2	LCE-PAGE-RESPONSE message	46
7.3.8.2	Associated procedure	46
7.3.8.2.1	Timer F-<LCE.03> management	46
7.3.8.3	Exceptional cases	46
7.3.8.3.1	The IPUI received in the {LCE-PAGE-RESPONSE} does not match	46
7.3.8.3.2	Timer <LCE.03> expiry	47
7.3.8.3.3	Release from the higher entity	47
7.3.9	Higher layer information FP broadcast.....	47
7.3.9.1	Higher layer information in standard FP broadcast (Qh= 3)	48
7.3.9.2	Higher layer information in Extended FP broadcast (Qh= 4)	48
7.3.9.3	Higher layer information in Extended FP broadcast part 2 (Qh= 11)	48
7.4	Implementation examples of specific procedures.....	48
7.5	Data Link Control (DLC) layer procedures.....	48
7.5.1	FU1 frame operation.....	49
7.5.2	FU12 frame operation for G.729.1 codec	49
7.6	Medium Access Control (MAC) layer procedures.....	49
7.6.1	MAC services	49
7.6.2	Frame formats and multiplexers	50
7.6.3	Downlink broadcast	50
7.6.3.1	N _T message.....	51
7.6.3.2	Q _T - static system information.....	51
7.6.3.3	Q _T - Fixed Part capabilities	52
7.6.3.4	Q _T - Extended Fixed Part capabilities	52
7.6.3.5	Q _T - Extended Fixed Part capabilities part 2	53
7.6.3.6	Q _T - SARI list contents	53
7.6.4	Paging broadcast.....	53
7.6.4.1	Short page, normal/extended paging	54
7.6.4.2	Zero page normal/extended paging	54
7.6.4.3	Full page, normal/extended paging	55
7.6.4.4	Blind slot information	55
7.6.4.5	Bearer handover information	55
7.6.5	Setup of advanced connection, advanced bearer setup (A-field)	55
7.6.5.1	M _T message	56
7.6.5.2	Associated procedures.....	56
7.6.5.2.1	Timer T200 management.....	56
7.6.5.2.2	Counter N200 management	56
7.6.5.3	Exceptional cases	57
7.6.5.3.1	Bearer setup attempt fails N200+1 times.....	57
7.6.5.3.2	Timer T200 expiry.....	58
7.6.6	Connection type modification: basic to/from advanced.....	58
7.6.7	Slot type modification.....	58
7.6.7.1	Failure of slot type modification	58
7.6.8	Service type modification	59
7.6.9	ECN number modification.....	59

7.6.10	Connection/bearer release.....	59
7.6.10.1	M _T message	59
7.6.11	Bearer handover request	60
7.6.11.1	M _T message	60
7.6.12	Connection handover request.....	60
7.6.12.1	M _T message	60
7.7	Physical layer (PHL) requirements.....	61
7.7.1	Modulation.....	61
7.7.2	Slot type (Physical packets)	61
7.8	Requirements regarding the speech transmission.....	61
7.8.1	General.....	61
7.8.2	Speech codecs	61
7.8.3	Audio performance requirements	61
7.9	Management procedures.....	62
7.10	Application procedures.....	62

Annex A (informative): Audio codecs.....63

A.1	Speech and audio coding.....	63
A.1.1	Overview	63
A.1.2	Narrow band speech coding	64
A.1.3	Wideband Speech coding	64
A.1.4	Super-wideband speech and audio coding.....	65

Annex B (normative): Audio patterns to indicate IP packet losses on the DECT link.....67

B.1	Audio patterns to indicate IP packet losses	67
B.1.1	Insertion of audio patterns	67
B.1.2	Reception of audio patterns	67
B.1.3	Contents of the audio patterns	67
B.1.4	Packet loss patterns for ITU-T Recommendation G.722.....	68
B.1.5	Packet loss patterns for ITU-T Recommendation G.711.....	68
B.1.6	Packet loss patterns for ITU-T Recommendation G.726.....	68
B.1.7	Packet loss patterns for ITU-T Recommendation G.729.1.....	69
B.1.8	Packet loss patterns for MPEG-4 ER AAC-LD	69

Annex C (normative): Configuration signalling for specific codecs.....70

C.1	MPEG-4 ER AAC-LD configuration signalling.....	70
C.1.1	<<IWU to IWU>> element to signal the supported capabilities (MPEG4CapabilityElement).....	70
C.1.2	<<IWU to IWU>> element to signal the used Configuration (MPEG4ConfigurationElement)	71

Annex D (informative): Recommended implementation of procedures.....73

D.1	Examples of implementation of specific procedures.....	73
D.1.1	General	73
D.1.2	Outgoing wideband call.....	74
D.1.2.1	Outgoing wideband call, no codec list, ITU-T Recommendation G.722 chosen.....	74
D.1.2.2	Outgoing Call Wideband, codec list, negotiation results in Wideband.....	75
D.1.2.3	Outgoing call with progress indicator with negotiation results in CC-INFO.....	77
D.1.2.4	Outgoing call with progress indicator; with negotiation results in CC-INFO codec change in 200 OK	78
D.1.2.5	Outgoing Call Wideband, negotiation results in Narrowband	79
D.1.2.6	Outgoing Call Wideband, negotiation results in longslot	79
D.1.3	Incoming Call Wideband.....	80
D.1.3.1	Incoming Call Wideband, negotiation results in Wideband	80
D.1.3.2	Incoming Call Wideband, negotiation results in Narrowband	80
D.1.3.3	Incoming Call Wideband, No SDP Offer in Invite, negotiation results in Narrowband.....	81
D.1.4	Service Change.....	82
D.1.4.1	Service Change from Wideband to Narrowband; re-negotiation initiated from IP-Network	82
D.1.4.2	Service Change from Wideband to Narrowband; re-negotiation initiated from FP.....	83
D.1.4.3	Service Change from Wideband to Narrowband; PP initiated; IP Network accepts Narrowband Codec	84
D.1.4.4	Service Change from Wideband ITU-T Recommendation G.722 to Narrowband; PP initiated; IP Network does not accept Narrowband Codec.....	84

D.1.5	Internal Call.....	85
D.1.5.1	Intercom Call, PP2 confirms Wideband	85
D.1.5.2	Intercom Call, PP2 confirms narrowband.....	86
D.1.5.3	Intercom Call with Interworking: WB Handset -> NB Handset.....	86
D.1.5.4	Internal Call transfer, WB -> NB.....	87
D.1.5.5	Internal Call transfer, NB -> WB.....	88
D.1.5.6	Internal Call transfer, NB -> WB, IP negotiation results in NB	89
D.1.6	Special cases.....	89
D.1.6.1	Service Change from Wideband to Narrowband with Call Waiting.....	89
D.1.6.2	Service Change from Wideband to Narrowband with Call Hold.....	90
D.1.6.3	Service Change from Wideband to Narrowband; Network layer Acknowledgment	91
D.1.6.4	Service Change from Narrowband to Wideband fails; Network layer Acknowledgment	92
D.1.6.5	Outgoing Call, slot type modification fails.....	93
D.1.7	Slot type and/or connection type modification.....	93
D.1.7.1	General.....	93
D.1.7.2	FT initiated connection modification.....	94
D.1.7.2.1	FT initiated connection modification (full slot I _N _minimum_delay -> long slot I _N _minimum delay).....	94
D.1.7.2.2	FT initiated connection modification (full slot I _N _minimum_delay -> long slot I _N _minimum_delay).....	96
D.1.7.2.3	FT initiated connection modification (long slot I _N _minimum_delay -> full slot I _N _minimum delay).....	98
D.1.7.2.4	FT initiated connection modification (long slot I _N _normal_delay -> full slot I _N _minimum delay)....	99
D.1.7.3	PT initiated connection modification.....	100
D.1.7.3.1	PT initiated connection modification (full slot I _N _minimum_delay -> long slot I _N _minimum delay).....	100
D.1.7.3.2	PT initiated connection modification (full slot I _N _minimum_delay -> long slot I _N _normal delay)..	102
D.1.7.3.3	PT initiated connection modification (long slot I _N _minimum_delay -> full slot I _N _minimum delay).....	104
D.1.7.3.4	PT initiated connection modification (long slot I _N _normal_delay -> full slot I _N _minimum delay)..	105
D.2	Examples of implementation of procedures for MPEG-4 ER AAC-LD voice service.....	106
D.2.1	MPEG-4 ER AAC-LD voice service codec configuration and negotiation process	106
D.2.1.1	Transmitting non default configuration using <<LOCATE-REQUEST>>, <<LOCATE-ACCEPT>> Message	106
D.2.1.2	Transmitting non default configuration using <<ACCESS-RIGHTS-REQUEST>>, <<ACCESS-RIGHTS-ACCEPT>> Message.....	107
D.2.1.3	Outgoing Call Super-wideband, codec MPEG-4 ER AAC-LD.....	108
D.2.1.3.1	Outgoing Call Super-wideband, INVITE command: AudioSpecificConfig()	108
D.2.1.3.2	Outgoing Call Super-wideband, OK command: AudioSpecificConfig().....	109
D.2.1.4	Incoming Call Super-wideband, codec MPEG-4 ER AAC-LD.....	109
D.2.1.4.1	Incoming Call Super-wideband, INVITE command: AudioSpecificConfig().....	109
D.2.1.4.2	Incoming Call Super-wideband, OK command: AudioSpecificConfig().....	110
Annex E (informative):	Services and features defined in other specifications	111
E.1	Services and features defined in EN 300 444 (GAP).....	111
E.1.1	GAP Network (NWK) features (clause 4.1 of EN 300 444)	111
E.1.2	GAP Speech coding and audio features (clause 4.2 of EN 300 444)	112
E.1.3	GAP Application features (clause 4.3 of EN 300 444).....	114
E.1.4	DLC service definitions (clause 5.1 of EN 300 444).....	114
E.1.5	GAP MAC service definitions (clause 5.2 of EN 300 444).....	115
E.2	GAP Feature/service to procedure mapping tables	115
E.2.1	GAP NWK feature to procedure mapping table (clause 6.8.1 of EN 300 444).....	116
E.2.2	GAP DLC service to procedure mapping table (clause 6.8.2 of EN 300 444)	119
E.2.3	GAP MAC service to procedure mapping table (clause 6.8.3 of EN 300 444)	120
E.2.4	GAP Application feature to procedure mapping table (clause 6.8.4 of EN 300 444).....	121

Annex F (informative):	Bibliography.....	122
History		123

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI TS 102 527-1 V1.3.1 \(2012-01\)](#)

<https://standards.iteh.ai/catalog/standards/etsi/7117dddf-4fe1-48d8-bf20-179df8c16d85/etsi-ts-102-527-1-v1-3-1-2012-01>