

ETSI TS 102 527-3 V1.4.1 (2012-01)



Digital Enhanced Cordless Telecommunications (DECT); New Generation DECT; Part 3: Extended wideband speech services

Document Preview

[ETSI TS 102 527-3 V1.4.1 \(2012-01\)](https://standards.iteh.ai/catalog/standards/etsi/ffb8aa46-f9ba-4174-9722-fdce4b65f660/etsi-ts-102-527-3-v1-4-1-2012-01)

<https://standards.iteh.ai/catalog/standards/etsi/ffb8aa46-f9ba-4174-9722-fdce4b65f660/etsi-ts-102-527-3-v1-4-1-2012-01>

ReferenceRTS/DECT-NG0265

Keywords7 kHz, audio, codec, DECT, GAP, IMT-2000,
interoperability, IP, profile, radio, speech

ETSI650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iteh Standards
(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2012.
All rights reserved.

DECTTM, PLUGTESTSTM, UMTSTM and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPPTM and LTETM are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	11
Foreword.....	11
1 Scope	12
2 References	13
2.1 Normative references	13
2.2 Informative references.....	14
3 Definitions, symbols and abbreviations	15
3.1 Definitions.....	15
3.2 Symbols.....	16
3.3 Abbreviations	16
4 Description of Services	18
4.1 Enhanced wideband speech.....	18
4.1.1 Back-compatibility with GAP.....	18
4.1.2 Further enhancement in audio performance requirements.....	18
4.2 Wideband speech scenarios.....	19
4.3 Extended wideband speech services defined in the present document.....	19
5 Service and feature definitions	20
5.1 New Generation DECT Speech Services	20
5.2 Network (NWK) features	20
5.3 Data Link Control (DLC) service definitions.....	21
5.4 Medium Access Control (MAC) service definitions.....	21
5.5 Physical Layer (PHL) service definitions.....	21
5.6 Speech coding and audio feature definitions.....	21
5.7 Application features	21
6 Inter-operability requirements.....	21
6.1 General	21
6.2 New Generation DECT Speech Services support status	22
6.3 Services to DECT feature implementation mappings.....	22
6.4 NWK features.....	31
6.5 Data Link Control (DLC) services	32
6.6 Medium Access Control (MAC) services	33
6.7 Physical layer (PHL) services	34
6.8 Speech coding and audio features	34
6.9 Application features	35
6.10 Network (NWK) feature to procedure mapping.....	36
6.11 Data Link Control (DLC) Service to procedure mapping	42
6.12 Medium Access Control (MAC) service to procedure mapping	43
6.13 Application feature to procedure mapping	45
6.14 General requirements	45
6.14.1 Network (NWK) layer message contents.....	45
6.14.2 Transaction identifier.....	45
6.14.3 Length of a Network (NWK) layer message	45
6.14.4 Handling of error and exception conditions.....	45
6.14.5 Generic Access Profile (GAP) default setup attributes.....	45
6.14.6 Coexistence of Mobility Management (MM) and Call Control (CC) procedures	46
6.14.7 Coding rules for information elements	46
7 Procedure description.....	46
7.1 Backward compatibility with Generic Access Profile (GAP) and with New Generation DECT part 1 (wideband speech) equipment	46
7.1.1 Backward compatibility with Generic Access Profile (GAP); Requirements for NG-DECT, part 3 Fixed Parts (FPs).....	46

7.1.2	Backward compatibility with Generic Access Profile (GAP); Requirements for NG-DECT, part 3 Portable Parts (PPs) registered on GAP compliant FPs	47
7.1.3	Backward compatibility with New Generation DECT, part 1; Requirements for NG-DECT, part 3 Fixed Parts (FPs).....	47
7.1.4	Backward compatibility with New Generation DECT, part 1; Requirements for NG-DECT, part 3 Portable Parts (PPs) registered on NG-DECT Part 1 FPs	47
7.2	Generic Access Profile (GAP) procedures	47
7.3	New Generation DECT; part 1: Wideband Speech procedures.....	47
7.3.1	Implementation examples of part 1: Wideband Speech specific procedures	47
7.4	Network (NWK) layer procedures specific to part 3.....	47
7.4.1	Generic events notification	48
7.4.1.1	General	48
7.4.1.2	Voice Message waiting notification.....	49
7.4.1.3	Missed call notification	50
7.4.1.4	List change notification.....	52
7.4.2	Date and Time synchronization	53
7.4.2.1	FT initiated Date and Time synchronization	54
7.4.2.2	PT initiated Date and Time synchronization	54
7.4.3	Handling of parallel calls	54
7.4.3.1	Parallel call common requirements	54
7.4.3.2	Control messages	55
7.4.3.3	Codec change for parallel calls	57
7.4.3.4	Sending negative acknowledgement	57
7.4.3.5	Common parallel call procedures (external or internal).....	58
7.4.3.5.1	Outgoing parallel call initiation (external or internal)	59
7.4.3.5.2	Call waiting indication (external or internal).....	62
7.4.3.5.3	Call toggle (external or internal).....	63
7.4.3.5.4	Call release and call release rejection	64
7.4.3.5.5	Void.....	67
7.4.3.5.6	Call waiting acceptance (from PP to FP)	67
7.4.3.5.7	Call waiting rejection (from PP to FP)	69
7.4.3.5.8	Putting a call on-hold.....	70
7.4.3.5.9	Resuming a call put on-hold	71
7.4.3.5.10	CLIP on call waiting.....	71
7.4.3.5.11	CNIP on call waiting indication	72
7.4.3.5.12	Active call release with replacement (from PP to FP).....	73
7.4.3.6	Call transfer.....	74
7.4.3.6.1	Announced call transfer procedure.....	75
7.4.3.6.2	Unannounced call transfer procedure	78
7.4.3.6.3	Call re-injection to the system (external or internal)	80
7.4.3.6.4	Remote party CLIP on call transfer.....	81
7.4.3.6.5	Remote party CNIP on call transfer.....	82
7.4.3.7	3-party conference with established external and/or internal calls.....	84
7.4.3.7.1	Unsuccessful 3-party conference call	86
7.4.3.7.2	3-party conference call release	86
7.4.3.8	Intrusion call (from PP to FP).....	88
7.4.3.8.1	Implicit intrusion call into a line in "single call" mode	88
7.4.3.8.2	Explicit intrusion call	92
7.4.3.9	Internal call codec priority	96
7.4.3.9.1	Description	96
7.4.3.9.2	Exception cases	98
7.4.3.10	Handling of lines where second calls are signalled in-band.....	98
7.4.3.10.1	General requirements.....	98
7.4.3.10.2	Basic 'double call with in-band signalling' lines.....	99
7.4.3.10.3	Off-hook CLIP enabled 'double call with in-band signalling' lines	100
7.4.3.10.4	Use of transparent commands on DCIBS lines (Basic or Off-hook CLIP enabled) or any other line	106
7.4.4	Handling of single call services	107
7.4.4.1	Control messages	107
7.4.4.1.1	Call deflection control messages	107
7.4.4.2	Call deflection	107
7.4.5	Line identification.....	111

7.4.5.1	Line identification general requirements.....	111
7.4.5.2	Line identification for external outgoing calls	111
7.4.5.2.1	General line identification requirements for external outgoing calls.....	111
7.4.5.2.2	Line identification for a <i>first</i> external outgoing call using <<CALL INFORMATION>>	112
7.4.5.2.3	Backward compatible line identification for a <i>first</i> external outgoing call using <<MULTI-KEYPAD >> IE.....	116
7.4.5.2.4	FP managed line selection for a <i>first</i> external outgoing call.....	117
7.4.5.3	Line identification for external incoming call	123
7.4.5.3.1	General line identification requirements for external incoming calls.....	123
7.4.5.3.2	Line identification for a <i>first</i> external incoming call	123
7.4.6	Call identification	124
7.4.6.1	Call identification general requirements	124
7.4.6.2	Call identifier assignment on first outgoing call (FP to PP).....	126
7.4.6.3	Call identifier assignment on first incoming call (FP to PP)	128
7.4.6.4	Call status indication to the handset (FP to PP)	128
7.4.6.4.1	Call status indication general requirements.....	128
7.4.6.4.2	Call status indication as call information.....	130
7.4.6.4.3	Call status principles and values.....	130
7.4.6.4.4	Call status reasons summary and MMI mapping.....	132
7.4.6.4.5	Call statuses for a first "Outgoing external call"	134
7.4.6.4.6	Call statuses for a first "Outgoing external call" using early {CC-CONNECT} message	135
7.4.6.4.7	Call statuses for an "Outgoing external call" - user busy	136
7.4.6.4.8	Call statuses for an "Outgoing external call" - number not available	137
7.4.6.4.9	Call statuses for a first "Incoming external call"	138
7.4.7	Multiple lines handling	139
7.4.7.1	Multiple lines common requirements.....	139
7.4.7.1.1	Pre-requisites	139
7.4.7.1.2	Minimum requirements	139
7.4.7.2	Terminal attachment and line settings.....	140
7.4.7.2.1	Initial attachment	140
7.4.7.2.2	Attachment modification	140
7.4.7.2.3	Line settings	140
7.4.7.3	Incoming and outgoing external calls on a multiple line system	140
7.4.7.4	Internal calls in multiple line context.....	141
7.4.7.5	Compatibility with non multiple line PP or FP	141
7.4.7.5.1	Non multiple line PP in front of a multiple line PP	141
7.4.7.5.2	Non multiple line FP in front of a multiple line PP	142
7.4.8	Multiple call line handling	142
7.4.8.1	Multiple calls general requirements	142
7.4.8.1.1	Pre-requisites	142
7.4.8.1.2	Minimum requirements	143
7.4.8.2	Incoming and outgoing external calls on a multiple call line.....	143
7.4.8.2.1	Line set in "single call" mode.....	143
7.4.8.2.2	Line set in "multiple call" mode	144
7.4.8.3	Busy system or line notification.....	144
7.4.9	PP and FP capabilities indication and broadcast.....	145
7.4.9.1	Terminal capability indication	145
7.4.9.2	Higher layer information FP broadcast	147
7.4.9.2.1	Higher layer information in standard FP broadcast (Qh = 3)	147
7.4.9.2.2	Higher layer information in Extended FP broadcast (Qh = 4).....	147
7.4.9.2.3	Extended Higher Layer capabilities part 2 (Qh = 11).....	147
7.4.10	List access service.....	148
7.4.10.1	General considerations	148
7.4.10.2	List change notification.....	153
7.4.10.2.1	General rule	153
7.4.10.2.2	Mandatory notifications.....	155
7.4.10.3	List identifier codings	156
7.4.10.4	List Access Commands	156
7.4.10.4.1	Start and end session	158
7.4.10.4.2	Query supported entry fields	162
7.4.10.4.3	Read entries	163
7.4.10.4.4	Edit entry	167

7.4.10.4.5	Save entry	168
7.4.10.4.6	Delete entry	172
7.4.10.4.7	Delete list.....	174
7.4.10.4.8	Search entries	175
7.4.10.4.9	Negative Acknowledgement.....	177
7.4.10.4.10	Data packet / Data packet last.....	178
7.4.10.5	Lists and entry fields	180
7.4.10.5.1	Fields description.....	181
7.4.10.5.2	"List of supported lists" entry fields	187
7.4.10.5.3	"Missed call list" entry fields.....	187
7.4.10.5.4	"Outgoing call list" entry fields	189
7.4.10.5.5	"Incoming accepted call list" entry fields	190
7.4.10.5.6	"All call list" entry fields	190
7.4.10.5.7	"Contact list" entry fields	191
7.4.10.5.8	"Internal names list" entry fields	193
7.4.10.5.9	"DECT system settings list" entry fields	194
7.4.10.5.10	"Line settings list" entry fields	194
7.4.10.5.11	"All incoming calls list" entry fields.....	194
7.4.10.6	List access service call and interactions with voice calls	194
7.4.10.6.1	List access setup	195
7.4.10.6.2	List access with possible first voice call initiation.....	196
7.4.10.6.3	Incoming first voice call during existing list access session.....	199
7.4.10.6.4	List access during existing voice call with possible second call initiation	200
7.4.10.6.5	Switching between LiA session and voice call.....	203
7.4.10.6.6	Returning to LiA session after voice call termination	203
7.4.10.7	Generic sequence charts for list access.....	204
7.4.10.8	Use case examples for list access	204
7.4.11	DECT system and line settings	204
7.4.11.1	DECT system and line settings considerations	204
7.4.11.2	Interactions between registration, attachments of handsets and lists	207
7.4.11.3	DECT system settings list	208
7.4.11.3.1	Field 'Current PIN code'	209
7.4.11.3.2	Field 'Clock master'	209
7.4.11.3.3	Field 'Base reset'	210
7.4.11.3.4	Field 'FP IP address / type'.....	210
7.4.11.3.5	Field 'FP IP address / value'.....	211
7.4.11.3.6	Field 'FP IP address / subnet mask'	211
7.4.11.3.7	Field 'FP IP address / gateway'	212
7.4.11.3.8	Field 'FP IP address / DNS server'.....	212
7.4.11.3.9	Field 'FP version / Firmware version'	213
7.4.11.3.10	Field 'FP version / Eeprom version'.....	213
7.4.11.3.11	Field 'FP version / Hardware version' field.....	214
7.4.11.3.12	Field 'Emission mode'	214
7.4.11.3.13	Field 'New PIN code'	215
7.4.11.4	Line settings list	216
7.4.11.4.1	Field 'Line name'	217
7.4.11.4.2	Field 'Line id'	217
7.4.11.4.3	Field 'Attached handsets'	217
7.4.11.4.4	Field 'Dialling Prefix'.....	218
7.4.11.4.5	Field 'FP melody'	218
7.4.11.4.6	Field 'FP volume'	218
7.4.11.4.7	Field 'Blocked number'	219
7.4.11.4.8	Field 'Multiple calls mode'.....	219
7.4.11.4.9	Field 'Intrusion call'	219
7.4.11.4.10	Field 'Permanent CLIR'	220
7.4.11.4.11	Field 'Call forwarding unconditional'	221
7.4.11.4.12	Field 'Call forwarding on No Answer'	222
7.4.11.4.13	Field 'Call forwarding on Busy subscriber'.....	223
7.4.11.5	Virtual contact list and call list per line.....	223
7.4.12	Calling line identity restriction (CLIR).....	224
7.4.12.1	Considerations.....	224
7.4.12.2	Permanent CLIR mode (all calls).....	224

7.4.12.3	Temporary CLIR mode (call by call)	225
7.4.13	Call forwarding (external calls)	225
7.4.13.1	Call forwarding common requirements.....	225
7.4.13.2	External Call Forwarding Unconditional (CFU) to external number	226
7.4.13.3	External Call Forwarding on No Answer (CFNA) to external number	227
7.4.13.4	External Call Forwarding on Busy subscriber (CFB) to external number	228
7.4.14	DTMF handling	229
7.4.14.1	Uplink DTMF transmission	229
7.4.14.1.1	Uplink DTMF transmission at call setup when FP connected to classic switching network.....	229
7.4.14.1.2	Uplink DTMF transmission when connected	230
7.4.14.2	Downlink DTMF reception	231
7.4.14.3	Local DTMF feedback of dialled digits	231
7.4.15	Tones provision	233
7.4.15.1	General considerations	233
7.4.15.2	Tones provision by the system	234
7.4.15.2.1	Tones provision for a NG-DECT Part 3 FP in front of a NG-DECT Part 3 PP.....	234
7.4.15.2.2	Tones provision for a NG-DECT Part 3 FP in front of a GAP or NG-DECT Part 1 PP	237
7.4.15.3	Transparency to tones provision by the network or PABX	242
7.4.16	Headset management	243
7.4.16.1	Headset considerations	243
7.4.16.2	Headset call interception	244
7.4.16.2.1	Initiation of the call	244
7.4.16.2.2	Call interception	244
7.4.16.3	Headset incoming call	248
7.4.16.4	Re-dial of last outgoing call	248
7.4.16.5	Re-dial of last incoming call	249
7.4.16.6	Switching from headset to headset (headset initiated)	249
7.4.16.7	Switching from headset to handset (handset initiated).....	249
7.4.16.8	Compatibility with other telephony features and profiles	250
7.4.16.8.1	Compatibility with other telephony features for a headset portable part (HPP)	250
7.4.16.8.2	Compatibility of a NG-DECT Part 3 headset portable part with other profiles.....	251
7.4.17	UTF-8 CNIP	252
7.4.17.1	UTF-8 CNIP sending from the FP to PP	252
7.4.17.2	Display of UTF-8 characters on PP side	252
7.4.18	Location registration after re-lock	252
7.4.19	PT alerting using pattern signalling	253
7.4.19.1	External call additional requirements for systems supporting 'Associated melody' field per contact in the contact list.....	253
7.4.20	Date and Time recovery	253
7.4.20.1	Addressed use cases and definitions - PP capability bit.....	253
7.4.20.2	PT Date and Time recovery	254
7.4.20.3	FT Date and Time recovery	255
7.5	Data Link Control (DLC) layer procedures.....	257
7.5.1	DLC services	257
7.6	Medium Access Control (MAC) layer procedures	257
7.6.1	MAC services	257
7.6.2	Frame formats and multiplexers	257
7.6.3	Downlink broadcast	258
7.6.3.1	N _T message.....	258
7.6.3.2	Q _T - static system information.....	258
7.6.3.3	Q _T - Fixed Part capabilities	258
7.6.3.4	Q _T - Extended Fixed Part capabilities	258
7.6.3.5	Q _T - Extended Fixed Part capabilities part 2	258
7.6.3.6	Q _T - SARI list contents	259
7.6.4	Paging broadcast.....	259
7.6.5	"no-emission" mode.....	259
7.7	Physical layer (PHL) requirements.....	259
7.7.1	Modulation.....	259
7.7.2	Slot type (Physical packets)	259
7.8	Requirements regarding the speech transmission.....	259
7.8.1	General.....	259
7.8.2	Speech codecs	259