

ETSI TS 102 887-1 V1.1.1 (2013-07)



Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices; Smart Metering Wireless Access Protocol; Part 1: PHY layer

[ETSI TS 102 887-1 V1.1.1 \(2013-07\)](https://standards.iteh.ai/catalog/standards/etsi/44227642-d302-4067-8f79-938250eccc59/etsi-ts-102-887-1-v1-1-1-2013-07)

<https://standards.iteh.ai/catalog/standards/etsi/44227642-d302-4067-8f79-938250eccc59/etsi-ts-102-887-1-v1-1-1-2013-07>

Reference

DTS/ERM-TG28-0427-1

Keywords

protocol, smart meter, SRD

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2013.
All rights reserved.

DECTTM, PLUGTESTSTM, UMTSTM and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPPTM and LTETM are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	6
Foreword.....	6
Introduction	6
1 Scope	7
2 References	7
2.1 Normative references	7
2.2 Informative references	7
3 Definitions and abbreviations.....	7
3.1 Definitions	7
3.2 Abbreviations	7
4 Overview	8
4.1 Introduction to smart metering utility network (SUN).....	8
4.2 General PHY requirements.....	8
4.3 Channel numbering	9
4.4 Receiver sensitivity definition.....	9
4.5 PHY constants	10
4.6 PHY PIB attributes	10
5 GFSK PHY specification	10
5.1 PPDU format for GFSK	10
5.2 Preamble field	10
5.2.1 SFD	10
5.2.2 PHR	11
5.2.3 PSDU field.....	11
5.3 Modulation and coding for GFSK.....	11
5.3.1 Bit-to-symbol mapping	11
5.3.2 Forward error correction (FEC).....	11
5.3.3 Code-symbol interleaving.....	11
5.4 Data whitening for GFSK.....	11
5.5 GFSK PHY RF requirements	11
5.5.1 Operating frequency range.....	11
5.5.2 Radio frequency tolerance	11
5.5.3 Transmitter symbol rate tolerance	11
5.5.4 Channel switch time.....	11
5.5.5 Receiver sensitivity.....	12
5.5.6 Tx-to-Rx turnaround time.....	12
5.5.7 Rx-to-Tx turnaround time.....	12
5.5.8 Receiver interference rejection	12
5.5.9 Transmitter accuracy.....	12
5.5.9.1 Frequency deviation tolerance	12
5.5.9.2 Zero crossing tolerance	12
5.5.10 Transmit power	12
5.5.11 Receiver maximum input level of desired signal.....	13
5.5.12 Receiver ED.....	13
5.5.13 Clear channel assessment (CCA).....	13
6 O-QPSK PHY specification	13
6.1 PPDU format for O-QPSK	13
6.1.1 Preamble field.....	13
6.1.2 SFD	13
6.1.3 PHR	14
6.1.4 PSDU field.....	14
6.2 Modulation and coding for O-QPSK.....	14
6.2.1 Overview	14

6.2.2	SHR coding and spreading	14
6.2.3	PHR coding and spreading	15
6.2.4	PSDU coding and spreading	15
6.2.5	Forward error correction (FEC)	15
6.2.6	Code-bit interleaving	15
6.2.7	Bit differential encoding (BDE).....	15
6.2.8	Spreading	16
6.2.9	Pilot insertion.....	16
6.2.10	PPDU Chip sequence	17
6.2.11	Modulation.....	17
6.3	O-QPSK PHY RF requirements.....	17
6.3.1	Operating frequency range.....	17
6.3.2	Radio frequency and symbol rate tolerance	17
6.3.3	Channel switch time.....	17
6.3.4	Receiver sensitivity.....	17
6.3.5	Tx-to-Rx turnaround time.....	18
6.3.6	Rx-to-Tx turnaround time.....	18
6.3.7	Receiver Interference Rejection.....	18
6.3.8	Error-vector magnitude (EVM) definition	18
6.3.9	Transmit power	18
6.3.10	Receiver maximum input level of desired signal.....	18
6.3.11	Receiver ED.....	18
6.3.12	Clear channel assessment (CCA).....	18
7	OFDM PHY specification	19
7.1	PPDU format for OFDM.....	19
7.1.1	Short Training field (STF)	19
7.1.1.1	Frequency domain STF	19
7.1.1.2	Time domain STF generation.....	19
7.1.1.3	Time domain STF repetition	19
7.1.1.4	STF normalization.....	19
7.1.2	Long Training field (LTF)	19
7.1.2.1	Frequency domain LTF.....	19
7.1.2.2	Time domain LTF generation	19
7.1.2.3	LTF normalization	19
7.1.3	PHR	19
7.1.4	PSDU field.....	19
7.2	Data rates for OFDM.....	20
7.3	Modulation and coding for OFDM.....	20
7.3.1	Reference modulator diagram.....	20
7.3.2	Bit-to-symbol mapping	20
7.3.3	PIB attribute values for <i>phySymbolsPerOctet</i>	20
7.3.4	Forward error correction (FEC).....	20
7.3.5	Interleaver	20
7.3.6	Frequency spreading	20
7.3.7	Pilot tones/null tones.....	20
7.3.8	Cyclic prefix (CP).....	20
7.3.9	PPDU Tail Bit field (TAIL).....	20
7.3.10	Pad bits (PAD)	20
7.3.11	Scrambler and scrambler seeds.....	20
7.4	OFDM PHY RF requirements.....	21
7.4.1	Operating frequency range.....	21
7.4.2	Transmit power spectral density (PSD) mask.....	21
7.4.3	Receiver sensitivity.....	21
7.4.4	Receiver interference rejection	21
7.4.5	Tx-to-Rx turnaround time.....	21
7.4.6	Rx-to-Tx turnaround time.....	21
7.4.7	Error-vector magnitude (EVM) definition	21
7.4.8	Transmit centre frequency and symbol tolerance	21
7.4.9	Transmit power	22
7.4.10	Receiver maximum input level of desired signal.....	22
7.4.11	Receiver ED.....	22