

ETSI TS 102 902 V1.1.1 (2011-02)

Technical Specification

**Electromagnetic compatibility
and radio spectrum matters (ERM);
Methods, parameters and test procedures for cognitive
interference mitigation towards ER-GSM for use by UHF RFID
using Detect-And-Avoid (DAA) or other similar techniques**

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI TS 102 902 V1.1.1 \(2011-02\)](https://standards.iteh.ai/catalog/standards/etsi/bc032691-4841-47a6-84dd-b2d00adeecab/etsi-ts-102-902-v1-1-1-2011-02)

<https://standards.iteh.ai/catalog/standards/etsi/bc032691-4841-47a6-84dd-b2d00adeecab/etsi-ts-102-902-v1-1-1-2011-02>



Reference

DTS/ERM-TG34-010

Keywords

RFID, SRD, UHF

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2011.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTE™ is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	5
Foreword.....	5
Introduction	6
1 Scope	7
2 References	7
2.1 Normative references	7
2.2 Informative references.....	7
3 Definitions, symbols and abbreviations	8
3.1 Definitions.....	8
3.2 Symbols.....	9
3.3 Abbreviations	9
4 UHF RFID deployment scenario.....	10
4.1 Introduction	10
4.2 Frequency plan	10
4.3 Basic operational principal of RFID technology	12
4.3.1 Introduction.....	12
4.3.2 Characteristics of RFID at UHF	12
4.3.2.1 Antennas	13
4.3.2.2 Data Rates	13
4.3.2.3 Intermodulation Products.....	14
4.3.2.4 De-tuning and absorption.....	14
4.3.2.5 Shielding	15
4.3.2.6 Transparent materials.....	15
4.4 Static deployment scenario.....	16
4.4.1 Overview	16
4.4.2 RFID equipped portal system	16
4.4.3 Packing table.....	17
4.4.4 Point of sales system (PoS).....	18
4.4.5 Industrial applications.....	19
4.5 Dynamic deployment scenario	21
4.5.1 Introduction.....	21
4.5.2 Hand held readers	21
4.5.3 Vehicle mounted readers	22
5 ER-GSM 900 system deployment scenario and protection criteria	22
5.1 Introduction	22
5.2 Frequency plan	22
5.3 Basic operational principle	23
5.4 Signal Formats.....	23
5.5 Deployment scenarios	24
5.6 Summary	26
6 Mitigation techniques.....	26
6.1 Introduction	26
6.2 Site licensing	26
6.3 Mitigation zone definition	27
6.3.1 Introduction.....	27
6.3.2 Required Isolation.....	27
6.3.3 Protection distances	28
6.3.3.1 Non specific RFID systems (Portal Systems)	28
6.3.3.2 Indoor RFID systems (Handheld Systems)	28
6.3.3.3 Indoor low power RFID systems (PoS, Packaging Table).....	28
6.4 Dynamic Mitigation techniques	29
6.4.1 Overview	29

6.4.2	Service area detection and identification	30
6.4.2.1	Access to ER-GSM Network planning information.....	30
6.4.2.2	Detection of ER-GSM base station signals (DL detection).....	30
6.4.2.3	Combination of database access and DL detection	31
6.5	Victim terminal detection (UL Detection).....	31
6.5.1	Overview	31
6.5.2	Slow victim terminal detection and identification	32
6.5.3	Fast victim terminal detection and identification.....	33
6.6	Combination of Service Area detection (DL Detection) and Victim terminal detection (UL Detection)	33
7	Summary and Conclusion	33
Annex A (informative): Future requirements for RFID.....		36
A.1	General	36
A.2	RFID applications	36
A.3	Technical Radio Spectrum requirements and justification.....	36
A.3.1	Current regulations for RFID	36
Annex B (informative): Detailed market information - Market size, Applications and requirements.....		38
Annex C (informative): Technical information		39
C.1	RFID.....	39
C.1.1	Performance requirements from leading RFID manufacturers and users.....	39
C.1.2	Power.....	39
C.1.3	Bandwidth	39
Annex D (informative): Avoidance options.....		41
D.1	Introduction	41
D.2	Transmit power management	41
D.3	Band relocation	41
D.4	LDC.....	41
D.5	Antenna techniques	42
D.6	Combinations	42
D.7	Avoidance parameters	42
D.7.1	Minimum avoidance bandwidth.....	42
D.7.2	Maximum avoidance power level	42
Annex E (informative): Bibliography.....		43
History		44

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI TS 102 902 V1.1.1 \(2011-02\)](#)

<https://standards.iteh.ai/catalog/standards/etsi/bc032691-4841-47a6-84dd-b2d00adeecab/etsi-ts-102-902-v1-1-1-2011-02>

Introduction

In order to accommodate the spectrum needs for the increasing number of RFID devices and systems, an extension band for high power RFID systems in the frequency range between 915 MHz and 921 MHz is under discussion. This band is already used by RFID in several countries worldwide and its availability in Europe would simplify the global movement of tagged goods. In Europe, part of this new frequency band will be shared between the primary user ER-GSM and RFID. In order to guarantee an interference-free coexistence between the two systems, mechanisms have to be implemented on the RFID side to reduce the probability of interference to a minimum. These mechanisms can be regulatory, technical mechanisms or operational restrictions.

In the present document a set of these mechanisms will be defined together with the necessary parameters to avoid interference with the ER-GSM system in the frequency band 918 MHz to 921 MHz. Besides the main goal of reducing the potential for interference with ER-GSM, the overall achievable performance of RFID systems should be optimized. The main strategy adopted in the present document has been to split the task into phases with three different time horizons:

- Short term solution for the next 1 to 3 years;
- Mid term solutions for the coming 3 to 6 years; and
- Long term solutions for a stable deployment of RFID systems in the shared bands.

This strategy will allow for the fast implementation of initial systems in the band without having to wait for the full implementation of the final solution. Some of the proposed techniques will be based on software upgrades of existing systems and only the mechanisms for the long term solution will require additional hardware and the implementation of new reader systems. On the other hand the long term solution will use all available mechanisms and procedures and thus will guarantee the best performance.

The values used in the present document are working assumption and therefore this values have to be verified in practical measurements and adopted to the state of the art technology.

The present document will be complemented by TR 102 903 [i.11], which will include the results of an initial practical evaluation of the proposed mechanisms, and a description of the conformance test procedures necessary for testing compliant RFID devices and systems.

ETSI TS 102 902 V1.1.1 (2011-02)

<https://standards.iteh.ai/catalog/standards/etsi/bc032691-4841-47a6-84dd-b2d00adeecab/etsi-ts-102-902-v1-1-1-2011-02>