

ETSI TS 103 161-11 V1.1.1 (2011-10)



**Access, Terminals, Transmission and Multiplexing (ATTM);
Integrated Broadband Cable and Television Networks;
IPCablecom 1.5;
Part 11: Media terminal adapter (MTA) device provisioning**

[ETSI TS 103 161-11 V1.1.1 \(2011-10\)](https://standards.iteh.ai/catalog/standards/etsi/8667803d-eb0e-4a88-af6e-d0cbd9dddefa/etsi-ts-103-161-11-v1-1-1-2011-10)

<https://standards.iteh.ai/catalog/standards/etsi/8667803d-eb0e-4a88-af6e-d0cbd9dddefa/etsi-ts-103-161-11-v1-1-1-2011-10>

Reference

DTS/ATTM-003011-11

Keywords

access, broadband, cable, IP, multimedia, PSTN

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2011.
All rights reserved.

DECTTM, PLUGTESTSTM, UMTSTM and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPPTM and LTETM are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	6
Foreword.....	6
1 Introduction	8
1.1 Scope	8
2 References	8
2.1 Normative references	8
2.2 Informative references.....	10
3 Definitions and abbreviations.....	10
3.1 Definitions	10
3.2 Abbreviations	11
4 Void.....	12
5 Background	12
5.1 Service Goals.....	12
5.2 Document Goals	12
5.3 IP/Cablecom Reference Architecture	13
5.4 Components and Interfaces	14
5.4.1 MTA	14
5.4.1.1 MTA Security Requirements	15
5.4.1.2 MTA SNMP Requirements	15
5.4.2 Provisioning Server.....	15
5.4.3 MTA to Telephony Syslog Server	16
5.4.4 MTA to DHCP Server	16
5.4.5 MTA to Provisioning Application	16
5.4.6 MTA to CMS	17
5.4.7 MTA to Security Server (KDC).....	17
5.4.8 MTA and Configuration Data File Access	17
5.4.9 DOCSIS® extensions for MTA Provisioning	17
6 Provisioning Overview.....	18
6.1 Device Provisioning	18
6.2 Endpoint Provisioning	18
6.3 Secure Flow Provisioning State Transitions.....	18
6.4 Basic and Hybrid Flow Provisioning State Transitions	19
7 Provisioning Flows.....	20
7.1 Backoff, Retries, and Timeouts	21
7.2 Embedded-MTA Power-On Initialization Flow (Secure Flow)	22
7.2.1 Embedded-MTA Secure Power-on Initialization Flow (IPv4 eCM)	22
7.2.2 Embedded-MTA Secure Power-on Initialization Flow (IPv6 eCM)	28
7.3 Embedded-MTA Power-On Initialization Flow (Basic Flow)	30
7.4 Embedded-MTA Power-On Initialization Flow (Hybrid Flow).....	31
7.5 Endpoint Provisioning Completion Notifications	33
7.6 Post Initialization Incremental Provisioning	34
7.6.1 Synchronization of Provisioning Attributes with Configuration File	34
7.6.2 Adding/Enabling Telephony Services on an MTA Endpoint	34
7.6.3 Deleting/Disabling Telephony Services on an MTA Endpoint.....	35
7.6.4 Modifying Telephony Services on an MTA Endpoint.....	36
7.7 Reflecting the State of the Endpoint Interface in the ifTable	36
7.8 Provisioning of the Signalling Communication Path Between the MTA and CMS	37
7.9 MTA Replacement	37
7.10 Temporary Signal Loss	37
7.11 MTA Hard Reboot/Soft Reset scenarios.	37
8 DHCP Options.....	37

8.1	DHCP Option 122: CableLabs® Client Configuration Option	38
8.1.1	Service Provider's DHCP Address (sub-option 1 and 2)	39
8.1.2	Service Provider's Provisioning Entity Address (sub-option 3)	39
8.1.3	AS-REQ/REP Exchange Backoff and Retry for SNMPv3 Key Management (sub-option 4)	39
8.1.4	AP-REQ/REP Kerberized Provisioning Backoff and Retry (sub-option 5)	40
8.1.5	Kerberos Realm of SNMP Entity (sub-option 6)	40
8.1.5.1	SNMPv3 Key Establishment	41
8.1.6	Ticket Granting Server Usage (sub-option 7)	41
8.1.7	Provisioning Timer (sub-option 8)	41
8.1.8	Security Ticket Invalidation (sub-option 9)	41
8.2	DHCP Option 60: Vendor Client Identifier	42
8.3	DHCP Options 12 and 15	42
8.4	DHCP Option 6	42
8.5	DHCP Option 43	42
8.6	DHCP OPTION 1	44
8.7	DHCP OPTION 3	44
8.8	DHCP OPTION CL_V4_PACKETCABLE_MIB_ENV_OPTION	44
9	MTA Provisionable Attributes	44
9.1	MTA Configuration File	45
9.1.1	Device Level Configuration Data	49
9.1.2	Device Level Service Data	50
9.1.3	Per-Endpoint Configuration Data	52
9.1.4	Per-Realm Configuration Data	54
9.1.5	Per-CMS Configuration Data	55
9.1.6	Exclusion of MIB objects in configuration File	56
10	MTA Device Capabilities	56
10.1	IPCablecom Version	57
10.2	Number Of Telephony Endpoints	57
10.3	TGT Support	57
10.4	HTTP Download File Access Method Support	57
10.5	MTA-24 Event SYSLOG Notification Support	57
10.6	NCS Service Flow Support	58
10.7	Primary Line Support	58
10.8	Vendor Specific TLV Type(s)	58
10.9	NVRAM Ticket/Ticket Information Storage Support	58
10.10	Provisioning Event Reporting Support	58
10.11	Supported CODEC(s)	58
10.12	Silence Suppression Support	59
10.13	Echo Cancellation Support	59
10.14	RSVP Support	59
10.15	UGS-AD Support	59
10.16	MTA's "ifIndex" starting number in "ifTable"	59
10.17	Provisioning Flow Logging Support	60
10.18	Supported Provisioning Flows	60
10.19	T38 Version Support	60
10.20	T38 Error Correction Support	61
10.21	RFC 2833 DTMF Support	61
10.22	Voice Metrics Support	61
10.23	Device MIB Support	61
10.23.1	Issuing Organization Assignments	62
10.23.2	Representing CableLabs® MIBs	62
10.23.3	Representing IETF MIBs	62
10.23.4	Example	62
10.24	Multiple Grants Per Interval Support	63
10.25	V.152 Support	63
11	TLV-38 SNMP Notification Receiver Specification	63
11.1	Sub-TLVs of TLV-38	63
11.1.1	SNMP Notification Receiver IP Address	63
11.1.2	SNMP Notification Receiver UDP Port Number	64
11.1.3	SNMP Notification Receiver Type	64

11.1.4	SNMP Notification Receiver Timeout.....	64
11.1.5	SNMP Notification Receiver Retries.....	64
11.1.6	SNMP Notification Receiver Filtering Parameters.....	64
11.1.7	SNMPv3 Notification Receiver Security Name	65
11.2	Mapping of TLV fields into SNMP Tables.....	65
11.2.1	Mapping of TLV fields into created SNMP Table rows	65
11.2.1.1	snmpNotifyTable	66
11.2.1.2	snmpTargetAddrTable	66
11.2.1.3	snmpTargetAddrExtTable	66
11.2.1.4	snmpTargetParamsTable	67
11.2.1.5	snmpNotifyFilterProfileTable	67
11.2.1.6	snmpNotifyFilterTable	67
11.2.1.7	snmpCommunityTable	67
11.2.1.8	usmUserTable	68
11.2.1.9	vacmSecurityToGroupTable	69
11.2.1.10	VacmAccessTable.....	69
11.2.1.11	vacmViewTreeFamilyTable.....	69
11.3	TLV38 and TLV11 Configuration Example	70
11.3.1	TLV-38 Example	70
11.3.2	Content of the SNMP framework tables after processing of the above example TLV38s.....	70
12	SNMPv2c Management Requirements	72
12.1	SNMPV2c Co-existence mode tables content created by MTA after MTA-4 for Hybrid and Basic Flows.	73
12.2	SNMP Default entries for SNMPv2c Access	73
13	Service interruption impact reporting and other enhanced features support	75
13.1	eDOCSIS® Requirements support.....	75
13.1.1	Impact Analysis and Reporting Requirements:	75
13.1.1.1	Impact Analysis.....	76
13.1.1.2	Supported Impact Levels and Reporting.....	76
13.2	IPCablecom Extension MIB.....	76
13.2.1	MTA MIB Extension.....	76
13.2.2	Signalling MIB Extension	76
13.3	Battery Backup MIBS	76
13.4	Syslog MIBS	76
13.5	Foreign Potential Detection.....	76
Annex A (informative):	SNMPv2c co-existence Configuration Example - Template for service providers.....	77
Annex B (informative):	Bibliography.....	78
History		79

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Access, Terminals, Transmission and Multiplexing (ATTM).

The present document is part 11 of a multi-part IPCablecom 1.5 deliverable covering the Digital Broadband Cable Access to the Public Telecommunications Network; IP Multimedia Time Critical Services, as identified below:

- Part 1: "Overview";
- Part 2: "Architectural framework for the delivery of time critical services over Cable Television Networks using Cable Modems";
- Part 3: "Audio Codec Requirements for the Provision of Bi-Directional Audio Service over Cable Television Networks using Cable Modems";
- Part 4: "Network Call Signalling Protocol";
- Part 5: "Dynamic Quality of Service for the Provision of Real Time Services over Cable Television Networks using Cable Modems";
- Part 6: "Event Message Specification";
- Part 7: "Media Terminal Adapter (MTA) Management Information Base (MIB)";
- Part 8: "Network Call Signalling (NCS) MIB Requirements";
- Part 9: "Security";
- Part 10: "Management Information Base (MIB) Framework";
- Part 11: "Media terminal adapter (MTA) device provisioning";**
- Part 12: "Management Event Mechanism";
- Part 13: "Trunking Gateway Control Protocol - MGCP option";
- Part 14: "Embedded MTA Analog Interface and Powering Specification"
- Part 15: "Analog Trunking for PBX Specification";
- Part 16: "Signalling for Call Management Server";
- Part 17: "CMS Subscriber Provisioning Specification";
- Part 18: "Media Terminal Adapter Extension MIB";
- Part 19: "IPCablecom Audio Server Protocol Specification - MGCP option";
- Part 20: "Management Event MIB Specification";

Part 21: "Signalling Extension MIB Specification".

NOTE 1: Additional parts may be proposed and will be added to the list in future versions.

NOTE 2: The choice of a multi-part format for this deliverable is to facilitate maintenance and future enhancements.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI TS 103 161-11 V1.1.1 \(2011-10\)](https://standards.iteh.ai/catalog/standards/etsi/8667803d-eb0e-4a88-af6e-d0cbd9dddefa/etsi-ts-103-161-11-v1-1-1-2011-10)

<https://standards.iteh.ai/catalog/standards/etsi/8667803d-eb0e-4a88-af6e-d0cbd9dddefa/etsi-ts-103-161-11-v1-1-1-2011-10>