

ETSI TS 103 161-14 V1.1.1 (2011-04)

Technical Specification

**Access, Terminals, Transmission and Multiplexing (ATTM);
Integrated Broadband Cable and Television Networks;
IPCablecom 1.5;
Part 14: Embedded MTA Analog Interface
and Powering Specification**

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI TS 103 161-14 V1.1.1 \(2011-04\)](https://standards.iteh.ai/catalog/standards/etsi/e3de816d-abe6-403a-a075-347c1a690a13/etsi-ts-103-161-14-v1-1-1-2011-04)

<https://standards.iteh.ai/catalog/standards/etsi/e3de816d-abe6-403a-a075-347c1a690a13/etsi-ts-103-161-14-v1-1-1-2011-04>



Reference

DTS/ATTM-003011-14

Keywords

access, broadband, cable, IP, multimedia, PSTN

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2011.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTE™ is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	5
Foreword.....	5
1 Scope	7
2 References	7
2.1 Normative references	8
2.2 Informative references.....	9
3 Definitions and abbreviations.....	9
3.1 Definitions.....	9
3.2 Abbreviations	9
4 Void.....	10
5 Introduction	10
5.1 IPCom Overview	10
5.2 Service Goals.....	10
5.3 IPCom Reference Architecture	11
5.3.1 Multimedia Terminal Adapter (MTA).....	11
6 E-MTA Monitoring Requirements	12
6.1 E-MTA Alarms	12
6.1.1 CM Failures	12
6.1.2 MTA Failures.....	13
6.2 E-MTA Telemetry.....	13
6.2.1 Telemetry Signals (External Interface).....	13
6.2.1.1 Telemetry Signal 1 - AC Fail	13
6.2.1.2 Telemetry Signal 2 - Replace Battery	14
6.2.1.3 Telemetry Signal 3 - Battery Missing	14
6.2.1.4 Telemetry Signal - Battery Low	14
6.2.2 OSS Event Reporting.....	14
7 E-MTA Power Requirements.....	14
7.1 Power Considerations.....	14
7.2 Typical E-MTA Traffic Model.....	15
7.3 Power Passing Tap Limitations	15
7.4 Average Power Calculations	15
7.5 Power Factor Considerations.....	16
7.6 E-MTA Average Power Requirements.....	16
7.7 Service Requirements Under AC Fail Conditions.....	16
7.8 Power Source Compatibility.....	16
7.9 Network Powering.....	16
7.9.1 Centre Conductor Delivery	16
7.9.2 Composite Pair Delivery.....	17
7.9.3 Network Power Characteristics.....	17
7.10 Local Powering with Battery Backup.....	17
7.10.1 E-MTA to UPS Interface	17
7.10.1.1 Physical Connection.....	17
7.10.1.2 Power Signals (External UPS)	17
8 MTA Analog Port Requirements	18
8.1 Loop Start Signalling.....	18
8.1.1 DC Supervisory Range	18
8.1.2 Idle State Voltage	18
8.1.3 Loop Closure Detection	19
8.1.4 Loop Open Detection.....	19
8.1.5 Off-Hook Delay	19
8.1.6 On-Hook Delay.....	19

8.1.7	Ringsplash.....	19
8.1.8	Distinctive Ringing.....	19
8.1.9	Transmission Path.....	20
8.2	General Supervision	20
8.2.1	Off-Hook Loop Current	20
8.2.2	Immunity to Line Crosses.....	20
8.2.3	System Generated Open Intervals.....	20
8.2.4	Open Switching Interval Distortion	20
8.2.5	Dial Pulsing	20
8.2.6	DTMF Signalling.....	21
8.2.7	Dialtone Removal	21
8.3	General Ringing	21
8.3.1	Alerting Signals	21
8.3.2	Ringling Delay	21
8.3.3	Ringling Source	21
8.3.4	Ringling Capability	22
8.3.5	Ringling Capacity	22
8.3.6	Ring Trip.....	22
8.3.7	Ring Trip Reporting Delay	22
8.3.8	Ring Trip Immunity	22
8.4	Voice Grade Analog Transmission	22
8.4.1	Input Impedance	23
8.4.2	Hybrid Balance	23
8.4.3	Longitudinal Balance.....	23
8.4.4	MTA Loss.....	23
8.4.5	MTA Loss Tolerance.....	23
8.4.6	Frequency Response	24
8.4.7	60 Hz Loss	24
8.4.8	Amplitude Tracking	24
8.4.9	Overload Compression	24
8.4.10	Idle Channel Noise.....	24
8.4.11	Signal to Distortion.....	24
8.4.12	Impulse Noise	25
8.4.13	Intermodulation Distortion	25
8.4.14	Single Frequency Distortion.....	25
8.4.15	Generated Tones.....	25
8.4.16	Peak-to-Average Ratio.....	25
8.4.17	Channel Crosstalk.....	25
	History	26