



TECHNICAL SPECIFICATION

**Universal Mobile Telecommunications System (UMTS);
LTE;
5G;
Non-Access-Stratum (NAS)
protocol for Evolved Packet System (EPS);
Stage 3
(3GPP TS 24.301 version 19.6.0 Release 19)**



Reference

RTS/TSGC-0124301 vj60

Keywords

5G,LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed, this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our [Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2026.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found at [3GPP to ETSI numbering cross-referencing](#).

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	21
1 Scope	22
2 References	22
3 Definitions and abbreviations.....	26
3.1 Definitions	26
3.2 Abbreviations	34
4 General	35
4.1 Overview	35
4.2 Linkage between the protocols for EPS mobility management and EPS session management	36
4.2.A Handling of NAS signalling low priority indication	36
4.3 UE mode of operation	37
4.3.1 General.....	37
4.3.2 Change of UE mode of operation	38
4.3.2.1 General.....	38
4.3.2.2 Change of UE's usage setting	40
4.3.2.3 Change of voice domain preference for E-UTRAN.....	41
4.3.2.4 Change or determination of IMS registration status.....	42
4.3.2.5 Change of configuration regarding the use of SMS.....	43
4.4 NAS security	43
4.4.1 General.....	43
4.4.2 Handling of EPS security contexts	44
4.4.2.1 General	44
4.4.2.2 Establishment of a mapped EPS security context during intersystem handover	45
4.4.2.3 Establishment of secure exchange of NAS messages	46
4.4.2.4 Change of security keys	48
4.4.2.5 Derivation of keys at CS to PS SRVCC handover from A/Gb mode to S1 mode or from Iu mode to S1 mode	49
4.4.3 Handling of NAS COUNT and NAS sequence number	50
4.4.3.1 General	50
4.4.3.2 Replay protection	51
4.4.3.3 Integrity protection and verification.....	51
4.4.3.4 Cipherng and deciphering	51
4.4.3.5 NAS COUNT wrap around	52
4.4.4 Integrity protection of NAS signalling messages.....	52
4.4.4.1 General	52
4.4.4.2 Integrity checking of NAS signalling messages in the UE	53
4.4.4.3 Integrity checking of NAS signalling messages in the MME	53
4.4.5 Cipherng of NAS signalling messages	55
4.5 Disabling and re-enabling of UE's E-UTRA capability	56
4.6 Applicability of procedures	59
4.6.1 Relay nodes.....	59
4.7 EPS mobility management and EPS session management in NB-S1 mode	59
4.8 EPS mobility management and EPS session management in WB-S1 mode for IoT.....	60
4.8.1 UE not using satellite E-UTRAN access	60
4.8.2 UE using satellite E-UTRAN access	60
4.9 Disabling and re-enabling of UE's NB-IoT capability	61
4.9.A Disabling and re-enabling of UE's satellite E-UTRAN capability	62
4.10 Support of MUSIM features.....	62
4.11 Satellite access for EPS	62
4.11.1 General.....	62
4.11.2 Handling list of "PLMNs not allowed to operate at the present UE location"	63

4.11.3	Handling multiple tracking area codes from the lower layers.....	64
4.11.4	Support for enhanced discontinuous coverage.....	64
4.11.5	Support for store and forward (S&F) satellite operation.....	66
4.11.5.1	General.....	66
4.11.5.2	Handling of timers.....	66
4.11.5.3	Handling of S&F monitoring list and estimated S&F uplink delivery time duration.....	67
4.12	MINT-EPS for UE to obtain service in EPS under disaster condition.....	68
5	Elementary procedures for EPS mobility management.....	69
5.1	Overview.....	69
5.1.1	General.....	69
5.1.2	Types of EMM procedures.....	70
5.1.3	EMM sublayer states.....	71
5.1.3.1	General.....	71
5.1.3.2	EMM sublayer states in the UE.....	71
5.1.3.2.1	General.....	71
5.1.3.2.2	Main states.....	71
5.1.3.2.3	Substates of state EMM-DEREGISTERED.....	73
5.1.3.2.4	Substates of state EMM-REGISTERED.....	74
5.1.3.3	EPS update status.....	75
5.1.3.4	EMM sublayer states in the MME.....	76
5.1.3.4.1	EMM-DEREGISTERED.....	76
5.1.3.4.2	EMM-COMMON-PROCEDURE-INITIATED.....	76
5.1.3.4.3	EMM-REGISTERED.....	76
5.1.3.4.4	EMM-DEREGISTERED-INITIATED.....	76
5.1.4	Coordination between EMM and GMM.....	77
5.1.5	Coordination between EMM and MM.....	78
5.2	Behaviour of the UE in state EMM-DEREGISTERED and state EMM-REGISTERED.....	78
5.2.1	General.....	78
5.2.2	UE behaviour in state EMM-DEREGISTERED.....	78
5.2.2.1	General.....	78
5.2.2.2	Primary substate selection.....	79
5.2.2.2.1	Selection of the substate after power on.....	79
5.2.2.3	Detailed description of UE behaviour in state EMM-DEREGISTERED.....	79
5.2.2.3.1	NORMAL-SERVICE.....	79
5.2.2.3.2	LIMITED-SERVICE.....	79
5.2.2.3.3	ATTEMPTING-TO-ATTACH.....	79
5.2.2.3.4	PLMN-SEARCH.....	80
5.2.2.3.5	NO-IMSI.....	80
5.2.2.3.6	ATTACH-NEEDED.....	81
5.2.2.3.7	NO-CELL-AVAILABLE.....	81
5.2.2.3.8	eCALL-INACTIVE.....	81
5.2.2.4	Substate when back to state EMM-DEREGISTERED from another EMM state.....	81
5.2.3	UE behaviour in state EMM-REGISTERED.....	82
5.2.3.1	General.....	82
5.2.3.2	Detailed description of UE behaviour in state EMM-REGISTERED.....	82
5.2.3.2.1	NORMAL-SERVICE.....	82
5.2.3.2.2	ATTEMPTING-TO-UPDATE.....	82
5.2.3.2.3	LIMITED-SERVICE.....	84
5.2.3.2.4	PLMN-SEARCH.....	84
5.2.3.2.5	UPDATE-NEEDED.....	84
5.2.3.2.6	NO-CELL-AVAILABLE.....	84
5.2.3.2.7	ATTEMPTING-TO-UPDATE-MM.....	85
5.2.3.2.8	IMSI-DETACH-INITIATED.....	85
5.3	General on elementary EMM procedures.....	85
5.3.1	EMM modes and NAS signalling connection.....	85
5.3.1.1	Establishment of the NAS signalling connection.....	85
5.3.1.2	Release of the NAS signalling connection.....	87
5.3.1.2.1	General.....	87
5.3.1.2.2	UE is using EPS services with control plane CIoT EPS optimization.....	91
5.3.1.3	Suspend and resume of the NAS signalling connection.....	91
5.3.2	Lists of forbidden tracking areas.....	92

5.3.3	List of forbidden PLMNs for attach in S101 mode.....	92
5.3.3a	Forbidden PLMNs for EPS services	93
5.3.4	Equivalent PLMNs list.....	93
5.3.5	Handling of the periodic tracking area update timer and mobile reachable timer (S1 mode only).....	93
5.3.6	Handling of timer T3402	95
5.3.7	Handling of the Local Emergency Numbers List and the Extended Local Emergency Numbers List	95
5.3.7a	Specific requirements for UE configured to use timer T3245	96
5.3.7b	Specific requirements for UE when receiving non-integrity protected reject messages	97
5.3.8	Abnormal cases in the UE	100
5.3.9	Handling of NAS level mobility management congestion control	101
5.3.9A	Handling of congestion control for transport of user data via the control plane	102
5.3.10	Access class control.....	102
5.3.11	Power saving mode.....	103
5.3.12	Extended idle-mode DRX cycle	104
5.3.13	Interaction between power saving mode and extended idle mode DRX cycle	104
5.3.14	Dedicated core network	104
5.3.15	CIoT EPS optimizations	105
5.3.16	Restriction on use of enhanced coverage.....	107
5.3.17	Service Gap Control.....	107
5.3.18	Restricted local operator services	109
5.3.19	Core Network selection and redirection for UEs using CIoT optimizations.....	109
5.3.19.1	Core network selection.....	109
5.3.19.2	Redirection of the UE by the core network.....	109
5.3.20	UE radio capability signalling optimisation.....	110
5.3.21	Wake-up signal assistance	111
5.3.22	Void	112
5.3.23	Control of UE access technology utilization by EPS.....	112
5.3.23.1	General	112
5.3.23.2	List of PLMNs with associated access technology restrictions.....	112
5.4	EMM common procedures	112
5.4.1	GUTI reallocation procedure	112
5.4.1.1	General	112
5.4.1.2	GUTI reallocation initiation by the network	113
5.4.1.3	GUTI reallocation completion by the UE	113
5.4.1.4	GUTI reallocation completion by the network.....	114
5.4.1.5	Abnormal cases in the UE.....	114
5.4.1.6	Abnormal cases on the network side.....	114
5.4.2	Authentication procedure.....	116
5.4.2.1	General	116
5.4.2.2	Authentication initiation by the network.....	116
5.4.2.3	Authentication response by the UE.....	117
5.4.2.4	Authentication completion by the network	118
5.4.2.5	Authentication not accepted by the network	118
5.4.2.6	Authentication not accepted by the UE.....	119
5.4.2.7	Abnormal cases	119
5.4.3	Security mode control procedure	124
5.4.3.1	General	124
5.4.3.2	NAS security mode control initiation by the network.....	125
5.4.3.3	NAS security mode command accepted by the UE.....	128
5.4.3.4	NAS security mode control completion by the network	129
5.4.3.5	NAS security mode command not accepted by the UE.....	130
5.4.3.6	Abnormal cases in the UE.....	130
5.4.3.7	Abnormal cases on the network side.....	130
5.4.4	Identification procedure	131
5.4.4.1	General	131
5.4.4.2	Identification initiation by the network	131
5.4.4.3	Identification response by the UE	132
5.4.4.4	Identification completion by the network	132
5.4.4.5	Abnormal cases in the UE.....	132
5.4.4.6	Abnormal cases on the network side.....	132
5.4.5	EMM information procedure	133
5.4.5.1	General	133

5.4.5.2	EMM information procedure initiation by the network	133
5.4.5.3	EMM information procedure in the UE	134
5.4.5.4	Abnormal cases on the network side	134
5.5	EMM specific procedures	134
5.5.1	Attach procedure.....	134
5.5.1.1	General	134
5.5.1.2	Attach procedure for EPS services.....	136
5.5.1.2.1	General	136
5.5.1.2.2	Attach procedure initiation	136
5.5.1.2.3	EMM common procedure initiation	142
5.5.1.2.4	Attach accepted by the network.....	142
5.5.1.2.4A	Attach successful for EPS services and not accepted for SMS services.....	151
5.5.1.2.5	Attach not accepted by the network.....	152
5.5.1.2.5A	Attach for emergency bearer services not accepted by the network.....	161
5.5.1.2.5B	Attach for initiating a PDN connection for emergency bearer services not accepted by the network.....	163
5.5.1.2.5B1	Attach by a UE transferring an emergency PDU session using a standalone PDN CONNECTIVITY REQUEST message	163
5.5.1.2.5C	Attach for access to RLOS not accepted by the network.....	164
5.5.1.2.6	Abnormal cases in the UE	164
5.5.1.2.6A	Abnormal cases in the UE, SMS services not accepted.....	168
5.5.1.2.7	Abnormal cases on the network side	169
5.5.1.3	Combined attach procedure for EPS services and non-EPS services (S1 mode only).....	170
5.5.1.3.1	General	170
5.5.1.3.2	Combined attach procedure initiation.....	171
5.5.1.3.3	EMM common procedure initiation	171
5.5.1.3.4	Combined attach accepted by the network	171
5.5.1.3.5	Combined attach not accepted by the network	174
5.5.1.3.6	Abnormal cases in the UE	180
5.5.1.3.7	Abnormal cases on the network side	181
5.5.2	Detach procedure	181
5.5.2.1	General	181
5.5.2.2	UE initiated detach procedure	182
5.5.2.2.1	UE initiated detach procedure initiation	182
5.5.2.2.2	UE initiated detach procedure completion for EPS services only	183
5.5.2.2.3	UE initiated combined detach procedure completion.....	184
5.5.2.2.4	Abnormal cases in the UE	184
5.5.2.2.5	Abnormal cases on the network side	186
5.5.2.3	Network initiated detach procedure	186
5.5.2.3.1	Network initiated detach procedure initiation	186
5.5.2.3.2	Network initiated detach procedure completion by the UE.....	188
5.5.2.3.3	Network initiated detach procedure completion by the network	194
5.5.2.3.4	Abnormal cases in the UE	194
5.5.2.3.5	Abnormal cases on the network side	194
5.5.3	Tracking area updating procedure (S1 mode only).....	196
5.5.3.1	General	196
5.5.3.2	Normal and periodic tracking area updating procedure	198
5.5.3.2.1	General	198
5.5.3.2.2	Normal and periodic tracking area updating procedure initiation	198
5.5.3.2.3	EMM common procedure initiation	207
5.5.3.2.4	Normal and periodic tracking area updating procedure accepted by the network	207
5.5.3.2.4A	Tracking area updating successful for EPS services and not accepted for SMS services.....	222
5.5.3.2.5	Normal and periodic tracking area updating procedure not accepted by the network	223
5.5.3.2.5A	Tracking area updating procedure for initiating a PDN connection for emergency bearer services not accepted by the network	233
5.5.3.2.5B	Tracking area updating for access to RLOS not accepted by the network	234
5.5.3.2.6	Abnormal cases in the UE	235
5.5.3.2.6A	Abnormal cases in the UE, SMS services not accepted.....	241
5.5.3.2.7	Abnormal cases on the network side	241
5.5.3.3	Combined tracking area updating procedure.....	244
5.5.3.3.1	General	244
5.5.3.3.2	Combined tracking area updating procedure initiation.....	244

5.5.3.3.3	EMM common procedure initiation	247
5.5.3.3.4	Combined tracking area updating procedure accepted by the network	247
5.5.3.3.5	Combined tracking area updating procedure not accepted by the network	250
5.5.3.3.6	Abnormal cases in the UE	258
5.5.3.3.7	Abnormal cases on the network side	260
5.5.4	eCall inactivity procedure	260
5.5.5	Tracking area update request message (for N1 mode only)	260
5.5.6	Attach request message (for N1 mode only)	261
5.6	EMM connection management procedures (S1 mode only)	261
5.6.1	Service request procedure	261
5.6.1.1	General	261
5.6.1.2	Service request procedure initiation	267
5.6.1.2.0A	General	267
5.6.1.2.1	UE is not using EPS services with control plane CIoT EPS optimization	267
5.6.1.2.2	UE is using EPS services with control plane CIoT EPS optimization	268
5.6.1.2.3	UE is using EPS services with control plane CIoT EPS optimization with overhead reduction	269
5.6.1.3	EMM common procedure initiation	269
5.6.1.4	Service request procedure accepted by the network	269
5.6.1.4.1	UE is not using EPS services with control plane CIoT EPS optimization	269
5.6.1.4.2	UE is using EPS services with control plane CIoT EPS optimization	272
5.6.1.4.3	UE is using EPS services with control plane CIoT EPS optimization with overhead reduction	277
5.6.1.5	Service request procedure not accepted by the network	280
5.6.1.5A	Service request procedure for initiating a PDN connection for emergency bearer services not accepted by the network	292
5.6.1.5B	Service request procedure for UE attached for access to RLOS not accepted by the network	292
5.6.1.6	Abnormal cases in the UE	293
5.6.1.7	Abnormal cases on the network side	300
5.6.2	Paging procedure	301
5.6.2.1	General	301
5.6.2.2	Paging for EPS services	302
5.6.2.2.1	Paging for EPS services through E-UTRAN using S-TMSI	302
5.6.2.2.2	Paging for EPS services through E-UTRAN using IMSI	305
5.6.2.3	Paging for CS fallback to A/Gb or Iu mode	306
5.6.2.3.1	General	306
5.6.2.3.2	Abnormal cases in the UE	307
5.6.2.3.3	Abnormal cases on the network side	307
5.6.2.4	Paging for SMS	308
5.6.3	Transport of NAS messages procedure	308
5.6.3.1	General	308
5.6.3.2	UE initiated transport of NAS messages	308
5.6.3.3	Network initiated transport of NAS messages	309
5.6.3.4	Abnormal cases in the UE	309
5.6.3.5	Abnormal cases on the network side	309
5.6.4	Generic transport of NAS messages procedure	309
5.6.4.1	General	309
5.6.4.2	UE initiated generic transport of NAS messages	310
5.6.4.3	Network initiated transport of NAS messages	310
5.6.4.4	Abnormal cases in the UE	310
5.6.4.5	Abnormal cases on the network side	311
5.6.5	EMM data transport procedure	311
5.6.5.1	General	311
5.6.5.2	UE initiated EMM data transport procedure	311
5.6.5.3	Network initiated EMM data transport procedure	312
5.6.5.4	Abnormal cases in the UE	313
5.6.5.5	Abnormal cases on the network side	314
5.7	Reception of an EMM STATUS message by an EMM entity	314
6	Elementary procedures for EPS session management	314
6.1	Overview	314
6.1.1	General	314
6.1.2	Types of ESM procedures	315
6.1.3	ESM sublayer states	316

6.1.3.1	General	316
6.1.3.2	ESM sublayer states in the UE	316
6.1.3.2.1	BEARER CONTEXT INACTIVE	316
6.1.3.2.2	BEARER CONTEXT ACTIVE	316
6.1.3.2.3	PROCEDURE TRANSACTION INACTIVE	317
6.1.3.2.4	PROCEDURE TRANSACTION PENDING	317
6.1.3.3	ESM sublayer states in the MME	317
6.1.3.3.1	BEARER CONTEXT INACTIVE	317
6.1.3.3.2	BEARER CONTEXT ACTIVE PENDING	317
6.1.3.3.3	BEARER CONTEXT ACTIVE	317
6.1.3.3.4	BEARER CONTEXT INACTIVE PENDING	317
6.1.3.3.5	BEARER CONTEXT MODIFY PENDING	317
6.1.3.3.6	PROCEDURE TRANSACTION INACTIVE	318
6.1.3.3.7	PROCEDURE TRANSACTION PENDING	318
6.1.4	Coordination between ESM and SM	318
6.1.4A	Coordination between ESM and 5GSM	319
6.1.5	Coordination between ESM and EMM for supporting ISR	319
6.2	IP address allocation	320
6.2.1	General	320
6.2.2	IP address allocation via NAS signalling	320
6.2A	IP header compression	321
6.3	General on elementary ESM procedures	322
6.3.1	Services provided by lower layers	322
6.3.2	Principles of address handling for ESM procedures	322
6.3.3	Abnormal cases in the UE	324
6.3.4	Abnormal cases in the network	325
6.3.5	Handling of APN based congestion control	325
6.3.5A	Handling of group specific session management congestion control	326
6.3.6	Handling of network rejection not due to APN based congestion control	326
6.3.7	Handling of WLAN offload control	327
6.3.8	Handling of serving PLMN rate control	327
6.3.9	Handling of APN rate control	327
6.3.10	Handling of 3GPP PS data off	328
6.3.11	Handling of Reliable Data Service	329
6.3.12	Handling of Ethernet PDN type	329
6.3.13	Handling of Uncrewed aerial vehicle identification, authentication, authorization and operational restrictions	329
6.3.13.1	General	329
6.3.13.2	Authentication and authorization of UAV	329
6.3.13.3	Authorization of C2 communication	330
6.3.13.4	Void	330
6.3.13.5	Support of no-transmit zone (NTZ)	330
6.3.14	Handling of URSP provisioning	331
6.4	Network initiated ESM procedures	331
6.4.1	Default EPS bearer context activation procedure	331
6.4.1.1	General	331
6.4.1.2	Default EPS bearer context activation initiated by the network	332
6.4.1.3	Default EPS bearer context activation accepted by the UE	332
6.4.1.4	Default EPS bearer context activation not accepted by the UE	334
6.4.1.5	Abnormal cases in the UE	334
6.4.1.6	Abnormal cases on the network side	335
6.4.2	Dedicated EPS bearer context activation procedure	335
6.4.2.1	General	335
6.4.2.2	Dedicated EPS bearer context activation initiated by the network	336
6.4.2.3	Dedicated EPS bearer context activation accepted by the UE	336
6.4.2.4	Dedicated EPS bearer context activation not accepted by the UE	338
6.4.2.5	Abnormal cases in the UE	339
6.4.2.6	Abnormal cases on the network side	339
6.4.3	EPS bearer context modification procedure	340
6.4.3.1	General	340
6.4.3.2	EPS bearer context modification initiated by the network	340
6.4.3.3	EPS bearer context modification accepted by the UE	341

6.4.3.4	EPS bearer context modification not accepted by the UE.....	344
6.4.3.5	Abnormal cases in the UE.....	346
6.4.3.6	Abnormal cases on the network side.....	346
6.4.4	EPS bearer context deactivation procedure.....	347
6.4.4.1	General.....	347
6.4.4.2	EPS bearer context deactivation initiated by the network.....	347
6.4.4.3	EPS bearer context deactivation accepted by the UE.....	348
6.4.4.4	Abnormal cases in the UE.....	350
6.4.4.5	Abnormal cases on the network side.....	350
6.4.4.6	Local EPS bearer context deactivation without NAS signalling.....	351
6.5	UE requested ESM procedures.....	352
6.5.0	General.....	352
6.5.1	UE requested PDN connectivity procedure.....	353
6.5.1.1	General.....	353
6.5.1.2	UE requested PDN connectivity procedure initiation.....	354
6.5.1.3	UE requested PDN connectivity procedure accepted by the network.....	357
6.5.1.4	UE requested PDN connectivity procedure not accepted by the network.....	359
6.5.1.4.1	General.....	359
6.5.1.4.2	Handling of network rejection due to ESM cause #26.....	361
6.5.1.4.3	Handling of network rejection due to ESM cause other than ESM cause #26.....	364
6.5.1.4A	Handling the maximum number of active EPS bearer contexts.....	370
6.5.1.4B	Void.....	371
6.5.1.4C	Handling the maximum number of active user plane radio bearers in NB-S1 mode.....	371
6.5.1.5	Abnormal cases in the UE.....	371
6.5.1.6	Abnormal cases on the network side.....	372
6.5.1.7	Handling PDN connectivity request for UE configured for dual priority.....	373
6.5.2	UE requested PDN disconnect procedure.....	373
6.5.2.1	General.....	373
6.5.2.2	UE requested PDN disconnection procedure initiation.....	373
6.5.2.3	UE requested PDN disconnection procedure accepted by the network.....	374
6.5.2.4	UE requested PDN disconnection procedure not accepted by the network.....	374
6.5.2.5	Abnormal cases in the UE.....	375
6.5.2.6	Abnormal cases on the network side.....	375
6.5.3	UE requested bearer resource allocation procedure.....	375
6.5.3.1	General.....	375
6.5.3.2	UE requested bearer resource allocation procedure initiation.....	376
6.5.3.3	UE requested bearer resource allocation procedure accepted by the network.....	376
6.5.3.4	UE requested bearer resource allocation procedure not accepted by the network.....	377
6.5.3.4.1	General.....	377
6.5.3.4.2	Handling of network rejection due to ESM cause #26.....	379
6.5.3.4.3	Handling of network rejection due to ESM cause other than ESM cause #26.....	380
6.5.3.4A	Handling the maximum number of active EPS bearer contexts.....	382
6.5.3.5	Abnormal cases in the UE.....	383
6.5.3.6	Abnormal cases on the network side.....	383
6.5.4	UE requested bearer resource modification procedure.....	383
6.5.4.1	General.....	383
6.5.4.2	UE requested bearer resource modification procedure initiation.....	384
6.5.4.3	UE requested bearer resource modification procedure accepted by the network.....	387
6.5.4.4	UE requested bearer resource modification procedure not accepted by the network.....	387
6.5.4.4.1	General.....	387
6.5.4.4.2	Handling of network rejection due to ESM cause #26.....	390
6.5.4.4.3	Handling of network rejection due to ESM cause other than ESM cause #26.....	391
6.5.4.5	Abnormal cases in the UE.....	393
6.5.4.6	Abnormal cases on the network side.....	394
6.5.5	Handling session management request for UE configured for dual priority.....	395
6.6	Miscellaneous procedures.....	396
6.6.1	Exchange of protocol configuration options.....	396
6.6.1.1	General.....	396
6.6.1.2	ESM information request procedure.....	396
6.6.1.2.1	General.....	396
6.6.1.2.2	ESM information request initiated by the network.....	397
6.6.1.2.3	ESM information request completion by the UE.....	397

6.6.1.2.4	ESM information request completion by the network	397
6.6.1.2.5	Abnormal cases in the UE	397
6.6.1.2.6	Abnormal cases on the network side	397
6.6.1.3	Exchange of protocol configuration options in other messages	398
6.6.2	Notification procedure	398
6.6.2.1	General	398
6.6.2.2	Notification procedure initiation by the network	398
6.6.2.3	Notification procedure in the UE	398
6.6.2.4	Abnormal cases on the network side	398
6.6.3	Remote UE Report procedure	399
6.6.3.1	General	399
6.6.3.2	Remote UE Report initiated by the UE	399
6.6.3.3	Remote UE Report completion by the network	399
6.6.3.4	Remote UE Report completion by the UE	399
6.6.3.5	Abnormal cases in the UE	399
6.6.3.6	Abnormal cases on the network side	400
6.6.4	Transport of user data via the control plane procedure	400
6.6.4.1	General	400
6.6.4.2	UE initiated transport of user data via the control plane	400
6.6.4.3	Network initiated transport of user data via the control plane	401
6.6.4.4	Abnormal cases in the UE	401
6.6.4.5	Abnormal cases on the network side	402
6.6.5	Transport of user data via the control plane procedure with overhead reduction	402
6.6.5.1	General	402
6.6.5.2	UE initiated transport of user data via the control plane with overhead reduction	402
6.6.5.3	Network initiated transport of user data via the control plane with overhead reduction	402
6.6.5.4	Abnormal cases in the UE	403
6.6.5.5	Abnormal cases on the network side	403
6.7	Reception of an ESM STATUS message by an ESM entity	403
7	Handling of unknown, unforeseen, and erroneous protocol data	404
7.1	General	404
7.2	Message too short	405
7.3	Unknown or unforeseen procedure transaction identity or EPS bearer identity	405
7.3.1	Procedure transaction identity	405
7.3.2	EPS bearer identity	406
7.4	Unknown or unforeseen message type	408
7.5	Non-semantic mandatory information element errors	408
7.5.1	Common procedures	408
7.5.2	EPS mobility management	408
7.5.3	EPS session management	409
7.6	Unknown and unforeseen IEs in the non-imperative message part	409
7.6.1	IEs unknown in the message	409
7.6.2	Out of sequence IEs	409
7.6.3	Repeated IEs	409
7.7	Non-imperative message part errors	410
7.7.1	Syntactically incorrect optional IEs	410
7.7.2	Conditional IE errors	410
7.8	Messages with semantically incorrect contents	410
8	Message functional definitions and contents	410
8.1	Overview	410
8.2	EPS mobility management messages	411
8.2.1	Attach accept	411
8.2.1.1	Message definition	411
8.2.1.2	GUTI	414
8.2.1.3	Location area identification	414
8.2.1.4	MS identity	414
8.2.1.5	EMM cause	414
8.2.1.6	T3402 value	414
8.2.1.7	T3423 value	414
8.2.1.8	Equivalent PLMNs	414

8.2.1.9	Emergency number list	414
8.2.1.9A	Extended emergency number list	415
8.2.1.10	EPS network feature support.....	415
8.2.1.11	Additional update result	415
8.2.1.12	T3412 extended value	415
8.2.1.13	T3324 value.....	415
8.2.1.14	Extended DRX parameters.....	415
8.2.1.15	DCN-ID.....	415
8.2.1.16	SMS services status.....	415
8.2.1.17	Non-3GPP NW provided policies	415
8.2.1.18	T3448 value.....	416
8.2.1.19	Network policy.....	416
8.2.1.20	T3447 value.....	416
8.2.1.21	Ciphering key data	416
8.2.1.22	UE radio capability ID	416
8.2.1.23	UE radio capability ID deletion indication.....	416
8.2.1.24	Negotiated WUS assistance information.....	416
8.2.1.25	Negotiated DRX parameter in NB-S1 mode.....	416
8.2.1.26	Negotiated IMSI offset.....	416
8.2.1.27	Forbidden TAI(s) for the list of "forbidden tracking areas for roaming"	416
8.2.1.28	Forbidden TAI(s) for the list of "forbidden tracking areas for regional provision of service"	417
8.2.1.29	Unavailability configuration	417
8.2.1.30	Access technology utilization control	417
8.2.1.31	S&F satellite operation parameters	417
8.2.1.32	Disaster roaming wait range.....	417
8.2.1.33	Disaster return wait range	417
8.2.1.34	List of PLMNs to be used in disaster condition	417
8.2.2	Attach complete	417
8.2.3	Attach reject.....	418
8.2.3.1	Message definition	418
8.2.3.2	ESM message container	418
8.2.3.3	T3346 value.....	418
8.2.3.4	T3402 value.....	418
8.2.3.5	Extended EMM cause	418
8.2.3.5A	Lower bound timer value	419
8.2.3.6	Forbidden TAI(s) for the list of "forbidden tracking areas for roaming"	419
8.2.3.7	Forbidden TAI(s) for the list of "forbidden tracking areas for regional provision of service"	419
8.2.3.8	Access technology utilization control	419
8.2.3.9	S&F satellite operation parameters	419
8.2.3.10	Void.....	419
8.2.4	Attach request	419
8.2.4.1	Message definition	419
8.2.4.2	Old P-TMSI signature.....	422
8.2.4.3	Additional GUTI.....	422
8.2.4.4	Last visited registered TAI.....	422
8.2.4.5	DRX parameter	422
8.2.4.6	MS network capability	422
8.2.4.7	Old location area identification	422
8.2.4.8	TMSI status	422
8.2.4.9	Mobile station classmark 2.....	422
8.2.4.10	Mobile station classmark 3.....	422
8.2.4.11	Supported Codecs	422
8.2.4.12	Additional update type	423
8.2.4.13	Voice domain preference and UE's usage setting.....	423
8.2.4.14	Device properties	423
8.2.4.15	Old GUTI type	423
8.2.4.16	MS network feature support.....	423
8.2.4.17	TMSI based NRI container	423
8.2.4.18	T3324 value.....	423
8.2.4.19	T3412 extended value	423
8.2.4.20	Extended DRX parameters.....	423
8.2.4.21	UE additional security capability	423

8.2.4.22	UE status	423
8.2.4.23	Additional information requested.....	423
8.2.4.24	N1 UE network capability.....	423
8.2.4.25	UE radio capability ID availability IE.....	424
8.2.4.26	Requested WUS assistance information.....	424
8.2.4.27	DRX parameter in NB-S1 mode	424
8.2.4.28	Requested IMSI offset.....	424
8.2.4.29	UE determined PLMN with disaster condition	424
8.2.5	Authentication failure	424
8.2.5.1	Message definition	424
8.2.5.2	Authentication failure parameter.....	424
8.2.6	Authentication reject.....	424
8.2.7	Authentication request	425
8.2.8	Authentication response.....	425
8.2.9	CS service notification.....	426
8.2.9.1	Message definition	426
8.2.9.2	CLI	426
8.2.9.3	SS Code.....	426
8.2.9.4	LCS indicator	426
8.2.9.5	LCS client identity	427
8.2.9.6	Void.....	427
8.2.10	Detach accept.....	427
8.2.10.1	Detach accept (UE originating detach)	427
8.2.10.2	Detach accept (UE terminated detach).....	427
8.2.11	Detach request	427
8.2.11.1	Detach request (UE originating detach)	427
8.2.11.2	Detach request (UE terminated detach).....	428
8.2.11.2.1	Message definition.....	428
8.2.11.2.2	EMM cause.....	428
8.2.11.2.3	Forbidden TAI(s) for the list of "forbidden tracking areas for roaming"	429
8.2.11.2.4	Forbidden TAI(s) for the list of "forbidden tracking areas for regional provision of service"	429
8.2.11.2.5	Lower bound timer value.....	429
8.2.11.2.6	Access technology utilization control	429
8.2.11.2.7	S&F satellite operation parameters.....	429
8.2.11.2.8	Disaster return wait range.....	429
8.2.12	Downlink NAS Transport.....	429
8.2.13	EMM information.....	429
8.2.13.1	Message definition	429
8.2.13.2	Full name for network.....	430
8.2.13.3	Short name for network.....	430
8.2.13.4	Local time zone	430
8.2.13.5	Universal time and local time zone	430
8.2.13.6	Network daylight saving time	431
8.2.14	EMM status.....	431
8.2.15	Extended service request	431
8.2.15.1	Message definition	431
8.2.15.2	CSFB response	432
8.2.15.3	EPS bearer context status	432
8.2.15.4	Device properties	432
8.2.15.5	UE request type	432
8.2.15.6	Paging restriction	432
8.2.16	GUTI reallocation command	432
8.2.16.1	Message definition	432
8.2.16.2	TAI list	433
8.2.16.3	DCN-ID.....	433
8.2.16.4	UE radio capability ID	433
8.2.16.5	UE radio capability ID deletion indication.....	433
8.2.16.6	Access technology utilization control	433
8.2.17	GUTI reallocation complete	433
8.2.18	Identity request	434
8.2.19	Identity response.....	434
8.2.20	Security mode command	435

8.2.20.1	Message definition	435
8.2.20.2	IMEISV request	435
8.2.20.3	Replayed nonce _{UE}	435
8.2.20.4	Nonce _{MME}	435
8.2.20.5	Hash _{MME}	435
8.2.20.6	Replayed UE additional security capability	436
8.2.20.7	UE radio capability ID request.....	436
8.2.20.8	UE coarse location information request.....	436
8.2.21	Security mode complete.....	436
8.2.21.1	Message definition	436
8.2.21.2	IMEISV	436
8.2.21.3	Replayed NAS message container	436
8.2.21.4	UE radio capability ID	437
8.2.21.5	UE coarse location information.....	437
8.2.22	Security mode reject	437
8.2.23	Security protected NAS message.....	437
8.2.24	Service reject	438
8.2.24.1	Message definition	438
8.2.24.2	T3442 value.....	438
8.2.24.3	T3346 value.....	438
8.2.24.4	T3448 value.....	438
8.2.24.5	Forbidden TAI(s) for the list of "forbidden tracking areas for roaming"	438
8.2.24.6	Forbidden TAI(s) for the list of "forbidden tracking areas for regional provision of service"	439
8.2.24.7	Lower bound timer value	439
8.2.24.8	Access technology utilization control	439
8.2.24.9	S&F satellite operation parameters	439
8.2.24.10	Disaster return wait range	439
8.2.25	Service request.....	439
8.2.26	Tracking area update accept.....	439
8.2.26.1	Message definition	439
8.2.26.2	T3412 value.....	442
8.2.26.3	GUTI.....	442
8.2.26.4	TAI list	442
8.2.26.5	EPS bearer context status	442
8.2.26.6	Location area identification.....	442
8.2.26.7	MS identity.....	442
8.2.26.8	EMM cause	443
8.2.26.9	T3402 value.....	443
8.2.26.10	T3423 value.....	443
8.2.26.11	Equivalent PLMNs.....	443
8.2.26.12	Emergency number list	443
8.2.26.12A	Extended emergency number list	443
8.2.26.13	EPS network feature support.....	443
8.2.26.14	Additional update result	443
8.2.26.15	T3412 extended value	443
8.2.26.16	T3324 value.....	443
8.2.26.17	Extended DRX parameters.....	444
8.2.26.18	DCN-ID.....	444
8.2.26.19	SMS services status.....	444
8.2.26.20	Non-3GPP NW provided policies	444
8.2.26.21	T3448 value.....	444
8.2.26.22	Network policy.....	444
8.2.26.23	T3447 value.....	444
8.2.26.24	Ciphering key data	444
8.2.26.25	UE radio capability ID	444
8.2.26.26	UE radio capability ID deletion indication.....	444
8.2.26.27	Negotiated WUS assistance information.....	444
8.2.26.28	Negotiated DRX parameter in NB-S1 mode.....	445
8.2.26.29	Negotiated IMSI offset.....	445
8.2.26.30	EPS additional request result.....	445
8.2.26.31	Forbidden TAI(s) for the list of "forbidden tracking areas for roaming"	445
8.2.26.32	Forbidden TAI(s) for the list of "forbidden tracking areas for regional provision of service"	445

8.2.26.33	Maximum time offset.....	445
8.2.26.34	Unavailability configuration	445
8.2.26.35	Access technology utilization control	445
8.2.26.36	S&F satellite operation parameters	445
8.2.26.37	Disaster roaming wait range.....	445
8.2.26.38	Disaster return wait range	445
8.2.26.39	List of PLMNs to be used in disaster condition	446
8.2.27	Tracking area update complete.....	446
8.2.28	Tracking area update reject.....	446
8.2.28.1	Message definition	446
8.2.28.2	T3346 value.....	447
8.2.28.3	Extended EMM cause	447
8.2.28.4	Forbidden TAI(s) for the list of "forbidden tracking areas for roaming"	447
8.2.28.5	Forbidden TAI(s) for the list of "forbidden tracking areas for regional provision of service"	447
8.2.28.6	Lower bound timer value	447
8.2.28.7	Access technology utilization control	447
8.2.28.8	S&F satellite operation parameters	448
8.2.28.9	Disaster return wait range	448
8.2.29	Tracking area update request	448
8.2.29.1	Message definition	448
8.2.29.2	Non-current native NAS key set identifier.....	451
8.2.29.3	GPRS ciphering key sequence number	451
8.2.29.4	Old P-TMSI signature	451
8.2.29.5	Additional GUTI	451
8.2.29.6	Nonce _{UE}	451
8.2.29.7	UE network capability.....	451
8.2.29.8	Last visited registered TAI.....	451
8.2.29.9	DRX parameter	452
8.2.29.10	UE radio capability information update needed.....	452
8.2.29.11	EPS bearer context status	452
8.2.29.12	MS network capability	452
8.2.29.13	Old location area identification.....	452
8.2.29.14	TMSI status	452
8.2.29.15	Mobile station classmark 2.....	452
8.2.29.16	Mobile station classmark 3.....	452
8.2.29.17	Supported Codecs	452
8.2.29.18	Additional update type	452
8.2.29.19	Voice domain preference and UE's usage setting.....	452
8.2.29.20	Old GUTI type	452
8.2.29.21	Device properties	453
8.2.29.22	MS network feature support.....	453
8.2.29.23	TMSI based NRI container	453
8.2.29.24	T3324 value.....	453
8.2.29.25	T3412 extended value	453
8.2.29.26	Extended DRX parameters.....	453
8.2.29.27	UE additional security capability	453
8.2.29.28	UE status	453
8.2.29.29	Additional information requested.....	453
8.2.29.30	N1 UE network capability.....	453
8.2.29.31	UE radio capability ID availability	453
8.2.29.32	DRX parameter in NB-S1 mode	453
8.2.29.33	Requested WUS assistance information.....	453
8.2.29.34	Requested IMSI offset.....	454
8.2.29.35	UE request type	454
8.2.29.36	Paging restriction	454
8.2.29.37	Unavailability information	454
8.2.29.38	UE determined PLMN with disaster condition	454
8.2.30	Uplink NAS Transport.....	454
8.2.31	Downlink generic NAS transport.....	454
8.2.31.1	Message definition	454
8.2.31.2	Additional information.....	455
8.2.32	Uplink generic NAS transport	455