

ETSI TS 124 501 V18.12.0 (2025-10)



TECHNICAL SPECIFICATION

5G;
Non-Access-Stratum (NAS) protocol for 5G System (5GS);
Stage 3
(3GPP TS 24.501 version 18.12.0 Release 18)

[ETSI TS 124 501 V18.12.0 \(2025-10\)](https://standards.iteh.ai/catalog/standards/etsi/95012bfc-e564-4927-abd7-e7804d660c9a/etsi-ts-124-501-v18-12-0-2025-10)

<https://standards.iteh.ai/catalog/standards/etsi/95012bfc-e564-4927-abd7-e7804d660c9a/etsi-ts-124-501-v18-12-0-2025-10>



Reference

RTS/TSGC-0124501vic0

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards application](#).

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver repository](#).

Users should be aware that the present document may be revised or have its status changed, this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our [Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2025.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables. (2025-10)

The cross reference between 3GPP and ETSI identities can be found at [3GPP to ETSI numbering cross-referencing](#).

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	26
1 Scope	27
2 References	27
3 Definitions and abbreviations.....	32
3.1 Definitions	32
3.2 Abbreviations	44
4 General	48
4.1 Overview	48
4.2 Coordination between the protocols for 5GS mobility management and 5GS session management	48
4.3 UE domain selection	49
4.3.1 UE's usage setting	49
4.3.2 Domain selection for UE originating sessions / calls.....	49
4.3.3 Change of UE's usage setting.....	51
4.3.4 Change or determination of IMS voice availability	51
4.4 NAS security	52
4.4.1 General.....	52
4.4.2 Handling of 5G NAS security contexts.....	52
4.4.2.1 General	52
4.4.2.1.1 Establishment of 5G NAS security context.....	52
4.4.2.1.2 UE leaving state 5GMM-DEREGISTERED.....	55
4.4.2.1.3 UE entering state 5GMM-DEREGISTERED.....	55
4.4.2.2 Establishment of a mapped 5G NAS security context during inter-system change from S1 mode to N1 mode in 5GMM-CONNECTED mode.....	55
4.4.2.3 Establishment of a 5G NAS security context during N1 mode to N1 mode handover	56
4.4.2.4 Establishment of an EPS security context during inter-system change from N1 mode to S1 mode in 5GMM-CONNECTED mode	57
4.4.2.5 Establishment of secure exchange of NAS messages	58
4.4.2.6 Change of security keys	60
4.4.3 Handling of NAS COUNT and NAS sequence number	60
4.4.3.1 General	60
4.4.3.2 Replay protection	61
4.4.3.3 Integrity protection and verification.....	61
4.4.3.4 Cipherring and deciphering	62
4.4.3.5 NAS COUNT wrap around.....	62
4.4.4 Integrity protection of NAS signalling messages.....	63
4.4.4.1 General	63
4.4.4.2 Integrity checking of NAS signalling messages in the UE	63
4.4.4.3 Integrity checking of NAS signalling messages in the AMF	64
4.4.5 Cipherring of NAS signalling messages	65
4.4.6 Protection of initial NAS signalling messages.....	66
4.4.7 Protection of NAS IEs	68
4.5 Unified access control	69
4.5.1 General.....	69
4.5.2 Determination of the access identities and access category associated with a request for access for UEs not operating in SNPN access operation mode over 3GPP access.....	70
4.5.2A Determination of the access identities and access category associated with a request for access for UEs operating in SNPN access operation mode over 3GPP access.....	76
4.5.3 Operator-defined access categories.....	81
4.5.4 Access control and checking.....	83
4.5.4.1 Access control and checking in 5GMM-IDLE mode and in 5GMM-IDLE mode with suspend indication.....	83

4.5.4.2	Access control and checking in 5GMM-CONNECTED mode and in 5GMM-CONNECTED mode with RRC inactive indication	85
4.5.5	Exception handling and avoiding double barring	87
4.5.6	Mapping between access categories/access identities and RRC establishment cause	91
4.6	Network slicing	93
4.6.1	General.....	93
4.6.2	Mobility management aspects.....	96
4.6.2.1	General	96
4.6.2.2	NSSAI storage.....	97
4.6.2.3	Provision of NSSAI to lower layers in 5GMM-IDLE mode.....	104
4.6.2.4	Network slice-specific authentication and authorization.....	106
4.6.2.5	Mobility management based network slice admission control.....	108
4.6.2.6	Provision of NSAG information to lower layers.....	109
4.6.2.7	Mobility management based network slice replacement.....	110
4.6.2.8	Mobility management for optimised handling of temporarily available network slices	111
4.6.2.9	Mobility management based network slice usage control.....	113
4.6.2.10	Mobility management aspects of handling network slices with NS-AoS not matching deployed tracking areas	114
4.6.2.11	Mobility management for partial network slice	115
4.6.3	Session management aspects	116
4.6.3.0	General	116
4.6.3.1	Session management based network slice admission control	116
4.6.3.2	Support of network slice admission control and interworking with EPC	116
4.6.3.3	Session management based network slice data rate limitation control.....	117
4.6.3.4	Session management based network slice replacement	117
4.6.3.5	Session management for optimized handling of temporarily available network slices.....	118
4.6.3.6	Session management for partial network slice	118
4.6.3.7	Session management aspect of handling network slices with NS-AoS not matching deployed tracking areas	119
4.7	NAS over non-3GPP access	120
4.7.1	General.....	120
4.7.2	5GS mobility management aspects	120
4.7.2.1	General	120
4.7.2.2	Establishment cause for non-3GPP access.....	121
4.7.3	5GS session management aspects	122
4.7.4	Limited service state over non-3GPP access	123
4.7.5	NAS signalling using trusted WLAN access network	123
4.8	Interworking with E-UTRAN connected to EPC	124
4.8.1	General.....	124
4.8.2	Single-registration mode.....	124
4.8.2.1	General	124
4.8.2.2	Single-registration mode with N26 interface	124
4.8.2.3	Single-registration mode without N26 interface	124
4.8.2.3.1	Interworking between NG-RAN and E-UTRAN	124
4.8.2.3.2	Interworking between TNGF or N3IWF connected to 5GCN and E-UTRAN.....	126
4.8.3	Dual-registration mode	127
4.8.4	Core Network selection for UEs not using CIoT 5GS optimizations	128
4.8.4A	Core Network selection and redirection for UEs using CIoT optimizations.....	129
4.8.4A.1	Core network selection.....	129
4.8.4A.2	Redirection of the UE by the core network.....	129
4.9	Disabling and re-enabling of UE's N1 mode capability	129
4.9.1	General.....	129
4.9.2	Disabling and re-enabling of UE's N1 mode capability for 3GPP access.....	130
4.9.3	Disabling and re-enabling of UE's N1 mode capability for non-3GPP access.....	133
4.9.4	Disabling and re-enabling of UE's satellite NG-RAN capability.....	133
4.10	Interworking with ePDG connected to EPC.....	134
4.11	UE configuration parameter updates	134
4.12	Access traffic steering, switching and splitting (ATSSS).....	135
4.13	Support of NAS signalling using wireline access network.....	135
4.14	Non-public network (NPN)	136
4.14.1	General.....	136
4.14.2	Stand-alone non-public network (SNPN)	136

4.14.3	Public network integrated non-public network (PNI-NPN).....	139
4.15	Time synchronization and time sensitive communication.....	140
4.15.1	General.....	140
4.15.2	Void.....	140
4.15.2.1	Void.....	140
4.15.2.2	Void.....	140
4.15.2.3	Void.....	140
4.15.3	Time synchronization.....	140
4.15.4	User plane node management.....	141
4.16	UE radio capability signalling optimisation.....	141
4.17	5GS mobility management in NB-N1 mode.....	142
4.18	5GS session management in NB-N1 mode.....	143
4.19	5GS mobility management in WB-N1 mode for IoT.....	143
4.20	5GS session management in WB-N1 mode for IoT.....	144
4.21	Authentication and Key Management for Applications (AKMA).....	144
4.22	Uncrewed aerial vehicle identification, authentication, and authorization.....	145
4.22.1	General.....	145
4.22.2	Authentication and authorization of UAV.....	145
4.22.3	Authorization of C2 communication.....	146
4.22.4	Void.....	146
4.23	NAS over Non-Terrestrial Network.....	146
4.23.1	General.....	146
4.23.2	List of "PLMNs not allowed to operate at the present UE location".....	146
4.23.3	5GS mobility management via a satellite NG-RAN cell.....	147
4.23.4	5GS session management via a satellite NG-RAN cell.....	148
4.23.5	Handling multiple tracking area codes from the lower layers.....	148
4.24	Minimization of service interruption.....	149
4.25	Support of MUSIM features.....	150
4.26	Support for Personal IoT Network service.....	151
4.27	Mobile base station relay support.....	152
5	Elementary procedures for 5GS mobility management.....	152
5.1	Overview.....	152
5.1.1	General.....	152
5.1.2	Types of 5GMM procedures.....	152
5.1.3	5GMM sublayer states.....	154
5.1.3.1	General.....	154
5.1.3.2	5GMM sublayer states.....	154
5.1.3.2.1	5GMM sublayer states in the UE.....	154
5.1.3.2.1.1	General.....	154
5.1.3.2.1.2	Main states.....	154
5.1.3.2.1.2.1	5GMM-NUL.....	154
5.1.3.2.1.2.2	5GMM-DEREGISTERED.....	154
5.1.3.2.1.2.3	5GMM-REGISTERED-INITIATED.....	154
5.1.3.2.1.2.4	5GMM-REGISTERED.....	155
5.1.3.2.1.2.5	5GMM-DEREGISTERED-INITIATED.....	155
5.1.3.2.1.2.6	5GMM-SERVICE-REQUEST-INITIATED.....	155
5.1.3.2.1.3	Substates of state 5GMM-DEREGISTERED.....	155
5.1.3.2.1.3.1	General.....	155
5.1.3.2.1.3.2	5GMM-DEREGISTERED.NORMAL-SERVICE.....	155
5.1.3.2.1.3.3	5GMM-DEREGISTERED.LIMITED-SERVICE.....	155
5.1.3.2.1.3.4	5GMM-DEREGISTERED.ATTEMPTING-REGISTRATION.....	155
5.1.3.2.1.3.5	5GMM-DEREGISTERED.PLMN-SEARCH.....	155
5.1.3.2.1.3.6	5GMM-DEREGISTERED.NO-SUPI.....	156
5.1.3.2.1.3.7	5GMM-DEREGISTERED.NO-CELL-AVAILABLE.....	156
5.1.3.2.1.3.8	5GMM-DEREGISTERED.eCALL-INACTIVE.....	156
5.1.3.2.1.3.9	5GMM-DEREGISTERED.INITIAL-REGISTRATION-NEEDED.....	156
5.1.3.2.1.4	Substates of state 5GMM-REGISTERED.....	156
5.1.3.2.1.4.1	General.....	156
5.1.3.2.1.4.2	5GMM-REGISTERED.NORMAL-SERVICE.....	156
5.1.3.2.1.4.3	5GMM-REGISTERED.NON-ALLOWED-SERVICE.....	157
5.1.3.2.1.4.4	5GMM-REGISTERED.ATTEMPTING-REGISTRATION-UPDATE.....	157

5.1.3.2.1.4.5	5GMM-REGISTERED.LIMITED-SERVICE	157
5.1.3.2.1.4.6	5GMM-REGISTERED.PLMN-SEARCH	157
5.1.3.2.1.4.7	5GMM-REGISTERED.NO-CELL-AVAILABLE	157
5.1.3.2.1.4.8	5GMM-REGISTERED.UPDATE-NEEDED	157
5.1.3.2.2	5GS update status in the UE	158
5.1.3.2.3	5GMM sublayer states in the network side	158
5.1.3.2.3.1	General	158
5.1.3.2.3.2	5GMM-DEREGISTERED	159
5.1.3.2.3.3	5GMM-COMMON-PROCEDURE-INITIATED	159
5.1.3.2.3.4	5GMM-REGISTERED	159
5.1.3.2.3.5	5GMM-DEREGISTERED-INITIATED	159
5.1.4	Coordination between 5GMM and EMM	159
5.1.4.1	General	159
5.1.4.2	Coordination between 5GMM for 3GPP access and EMM with N26 interface	160
5.1.4.3	Coordination between 5GMM for 3GPP access and EMM without N26 interface	160
5.1.5	Coordination between 5GMM and GMM	161
5.2	Behaviour of the UE in state 5GMM-DEREGISTERED and state 5GMM-REGISTERED	161
5.2.1	General	161
5.2.2	UE behaviour in state 5GMM-DEREGISTERED	161
5.2.2.1	General	161
5.2.2.2	Primary substate selection	161
5.2.2.2.1	Selection of the substate after power on	161
5.2.2.3	Detailed description of UE behaviour in state 5GMM-DEREGISTERED	162
5.2.2.3.1	NORMAL-SERVICE	162
5.2.2.3.2	LIMITED-SERVICE	162
5.2.2.3.3	ATTEMPTING-REGISTRATION	162
5.2.2.3.4	PLMN-SEARCH	164
5.2.2.3.5	NO-SUPI	164
5.2.2.3.6	NO-CELL-AVAILABLE	164
5.2.2.3.7	eCALL-INACTIVE	164
5.2.2.3.8	INITIAL-REGISTRATION-NEEDED	164
5.2.2.4	Substate when back to state 5GMM-DEREGISTERED from another 5GMM state	165
5.2.3	UE behaviour in state 5GMM-REGISTERED	165
5.2.3.1	General	165
5.2.3.2	Detailed description of UE behaviour in state 5GMM-REGISTERED	165
5.2.3.2.1	NORMAL-SERVICE	165
5.2.3.2.2	NON-ALLOWED-SERVICE	166
5.2.3.2.3	ATTEMPTING-REGISTRATION-UPDATE	166
5.2.3.2.4	LIMITED-SERVICE	167
5.2.3.2.5	PLMN-SEARCH	168
5.2.3.2.6	NO-CELL-AVAILABLE	168
5.2.3.2.7	UPDATE-NEEDED	168
5.3	General on elementary 5GMM procedures	168
5.3.1	5GMM modes and N1 NAS signalling connection	168
5.3.1.1	Establishment of the N1 NAS signalling connection	168
5.3.1.2	Re-establishment of the N1 NAS signalling connection	170
5.3.1.3	Release of the N1 NAS signalling connection	171
5.3.1.4	5GMM-CONNECTED mode with RRC inactive indication	176
5.3.1.5	Suspend and resume of the N1 NAS signalling connection	180
5.3.2	Permanent identifiers	181
5.3.3	Temporary identities	184
5.3.4	Registration areas	185
5.3.5	Service area restrictions	185
5.3.5.1	General	185
5.3.5.2	3GPP access service area restrictions	186
5.3.5.3	Wireline access service area restrictions	190
5.3.6	Mobile initiated connection only mode	191
5.3.7	Handling of the periodic registration update timer and mobile reachable timer	193
5.3.8	Handling of timer T3502	195
5.3.9	Handling of NAS level mobility management congestion control	196
5.3.10	Handling of DNN based congestion control	197
5.3.11	Handling of S-NSSAI based congestion control	197