

ETSI TS 124 501 V19.6.2 (2026-04)



TECHNICAL SPECIFICATION

**5G;
Non-Access-Stratum (NAS) protocol for 5G System (5GS);
Stage 3
(3GPP TS 24.501 version 19.6.2 Release 19)**

get full document from standards.iteh.ai



Reference

RTS/TSGC-0124501 vj62

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed, this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our [Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2026.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found at [3GPP to ETSI numbering cross-referencing](#).

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

| | |
|---|----|
| Intellectual Property Rights | 2 |
| Legal Notice | 2 |
| Modal verbs terminology..... | 2 |
| Foreword..... | 27 |
| 1 Scope | 28 |
| 2 References | 28 |
| 3 Definitions and abbreviations..... | 33 |
| 3.1 Definitions | 33 |
| 3.2 Abbreviations | 46 |
| 4 General | 49 |
| 4.1 Overview | 49 |
| 4.2 Coordination between the protocols for 5GS mobility management and 5GS session management | 50 |
| 4.2A Control of UE access technology utilization by 5GS | 51 |
| 4.2A.1 General..... | 51 |
| 4.2A.2 List of PLMNs with associated access technology restrictions | 51 |
| 4.3 UE domain selection | 52 |
| 4.3.1 UE's usage setting | 52 |
| 4.3.2 Domain selection for UE originating sessions / calls..... | 52 |
| 4.3.3 Change of UE's usage setting..... | 54 |
| 4.3.4 Change or determination of IMS voice availability | 54 |
| 4.4 NAS security | 55 |
| 4.4.1 General..... | 55 |
| 4.4.2 Handling of 5G NAS security contexts..... | 55 |
| 4.4.2.1 General | 55 |
| 4.4.2.1.1 Establishment of 5G NAS security context | 55 |
| 4.4.2.1.2 UE leaving state 5GMM-DEREGISTERED | 58 |
| 4.4.2.1.3 UE entering state 5GMM-DEREGISTERED..... | 58 |
| 4.4.2.2 Establishment of a mapped 5G NAS security context during inter-system change from S1 mode to N1 mode in 5GMM-CONNECTED mode..... | 58 |
| 4.4.2.3 Establishment of a 5G NAS security context during N1 mode to N1 mode handover | 59 |
| 4.4.2.4 Establishment of an EPS security context during inter-system change from N1 mode to S1 mode in 5GMM-CONNECTED mode | 60 |
| 4.4.2.5 Establishment of secure exchange of NAS messages | 61 |
| 4.4.2.6 Change of security keys | 63 |
| 4.4.3 Handling of NAS COUNT and NAS sequence number | 63 |
| 4.4.3.1 General | 63 |
| 4.4.3.2 Replay protection | 64 |
| 4.4.3.3 Integrity protection and verification..... | 64 |
| 4.4.3.4 Cipherring and deciphering | 65 |
| 4.4.3.5 NAS COUNT wrap around..... | 65 |
| 4.4.4 Integrity protection of NAS signalling messages..... | 66 |
| 4.4.4.1 General | 66 |
| 4.4.4.2 Integrity checking of NAS signalling messages in the UE | 66 |
| 4.4.4.3 Integrity checking of NAS signalling messages in the AMF | 67 |
| 4.4.5 Cipherring of NAS signalling messages | 69 |
| 4.4.6 Protection of initial NAS signalling messages..... | 69 |
| 4.4.7 Protection of NAS IEs | 71 |
| 4.5 Unified access control | 72 |
| 4.5.1 General..... | 72 |
| 4.5.2 Determination of the access identities and access category associated with a request for access for UEs not operating in SNPN access operation mode over 3GPP access..... | 74 |
| 4.5.2A Determination of the access identities and access category associated with a request for access for UEs operating in SNPN access operation mode over 3GPP access..... | 80 |
| 4.5.3 Operator-defined access categories..... | 86 |

| | | |
|-----------|--|-----|
| 4.5.4 | Access control and checking..... | 88 |
| 4.5.4.1 | Access control and checking in 5GMM-IDLE mode and in 5GMM-IDLE mode with suspend indication..... | 88 |
| 4.5.4.2 | Access control and checking in 5GMM-CONNECTED mode and in 5GMM-CONNECTED mode with RRC inactive indication | 90 |
| 4.5.5 | Exception handling and avoiding double barring | 92 |
| 4.5.6 | Mapping between access categories/access identities and RRC establishment cause | 97 |
| 4.6 | Network slicing | 98 |
| 4.6.1 | General..... | 98 |
| 4.6.2 | Mobility management aspects..... | 101 |
| 4.6.2.1 | General | 101 |
| 4.6.2.2 | NSSAI storage..... | 103 |
| 4.6.2.3 | Provision of NSSAI to lower layers in 5GMM-IDLE mode..... | 110 |
| 4.6.2.4 | Network slice-specific authentication and authorization..... | 112 |
| 4.6.2.5 | Mobility management-based network slice admission control | 114 |
| 4.6.2.6 | Provision of NSAG information to lower layers..... | 115 |
| 4.6.2.7 | Mobility management-based network slice replacement | 116 |
| 4.6.2.8 | Mobility management for optimised handling of temporarily available network slices | 117 |
| 4.6.2.9 | Mobility management based network slice usage control..... | 119 |
| 4.6.2.10 | Mobility management aspects of handling network slices with NS-AoS not matching deployed tracking areas | 120 |
| 4.6.2.11 | Mobility management for partial network slice | 121 |
| 4.6.3 | Session management aspects | 122 |
| 4.6.3.0 | General | 122 |
| 4.6.3.1 | Session management based network slice admission control | 122 |
| 4.6.3.2 | Support of network slice admission control and interworking with EPC | 123 |
| 4.6.3.3 | Session management based network slice data rate limitation control..... | 123 |
| 4.6.3.4 | Session management based network slice replacement | 123 |
| 4.6.3.5 | Session management for optimized handling of temporarily available network slices..... | 124 |
| 4.6.3.6 | Session management for partial network slice | 125 |
| 4.6.3.7 | Session management aspect of handling network slices with NS-AoS not matching deployed tracking areas | 126 |
| 4.7 | NAS over non-3GPP access | 127 |
| 4.7.1 | General..... | 127 |
| 4.7.2 | 5GS mobility management aspects..... | 127 |
| 4.7.2.1 | General | 127 |
| 4.7.2.2 | Establishment cause for non-3GPP access..... | 128 |
| 4.7.3 | 5GS session management aspects..... | 129 |
| 4.7.4 | Limited service state over non-3GPP access | 129 |
| 4.7.5 | NAS signalling using trusted WLAN access network | 130 |
| 4.8 | Interworking with E-UTRAN connected to EPC | 130 |
| 4.8.1 | General..... | 130 |
| 4.8.2 | Single-registration mode..... | 131 |
| 4.8.2.1 | General | 131 |
| 4.8.2.2 | Single-registration mode with N26 interface | 131 |
| 4.8.2.3 | Single-registration mode without N26 interface | 131 |
| 4.8.2.3.1 | Interworking between NG-RAN and E-UTRAN | 131 |
| 4.8.2.3.2 | Interworking between TNGF or N3IWF connected to 5GCN and E-UTRAN..... | 133 |
| 4.8.3 | Dual-registration mode | 134 |
| 4.8.4 | Core Network selection for UEs not using CiIoT 5GS optimizations | 135 |
| 4.8.4A | Core Network selection and redirection for UEs using CiIoT optimizations..... | 135 |
| 4.8.4A.1 | Core network selection..... | 135 |
| 4.8.4A.2 | Redirection of the UE by the core network..... | 136 |
| 4.9 | Disabling and re-enabling of UE's N1 mode capability | 136 |
| 4.9.1 | General..... | 136 |
| 4.9.2 | Disabling and re-enabling of UE's N1 mode capability for 3GPP access..... | 136 |
| 4.9.3 | Disabling and re-enabling of UE's N1 mode capability for non-3GPP access..... | 140 |
| 4.9.4 | Disabling and re-enabling of UE's satellite NG-RAN capability..... | 141 |
| 4.10 | Interworking with ePDG connected to EPC..... | 141 |
| 4.11 | UE configuration parameter updates | 142 |
| 4.12 | Access traffic steering, switching and splitting (ATSSS)..... | 142 |
| 4.13 | Support of NAS signalling using wireline access network..... | 142 |

| | | |
|---------------|--|-----|
| 4.14 | Non-public network (NPN) | 144 |
| 4.14.1 | General | 144 |
| 4.14.2 | Stand-alone non-public network (SNPN) | 144 |
| 4.14.3 | Public network integrated non-public network (PNI-NPN) | 146 |
| 4.15 | Time synchronization and time sensitive communication | 148 |
| 4.15.1 | General | 148 |
| 4.15.2 | Void | 148 |
| 4.15.2.1 | Void | 148 |
| 4.15.2.2 | Void | 148 |
| 4.15.2.3 | Void | 148 |
| 4.15.3 | Time synchronization | 148 |
| 4.15.4 | User plane node management | 148 |
| 4.16 | UE radio capability signalling optimisation | 149 |
| 4.17 | 5GS mobility management in NB-N1 mode | 150 |
| 4.18 | 5GS session management in NB-N1 mode | 150 |
| 4.19 | 5GS mobility management in WB-N1 mode for IoT | 151 |
| 4.20 | 5GS session management in WB-N1 mode for IoT | 151 |
| 4.21 | Authentication and key management for applications (AKMA) | 152 |
| 4.22 | Uncrewed aerial vehicle identification, authentication, authorization and operational restrictions | 152 |
| 4.22.1 | General | 152 |
| 4.22.2 | Authentication and authorization of UAV | 152 |
| 4.22.3 | Authorization of C2 communication | 153 |
| 4.22.4 | Void | 154 |
| 4.22.5 | Support of no-transmit zone (NTZ) | 154 |
| 4.23 | NAS over Non-Terrestrial Network | 154 |
| 4.23.1 | General | 154 |
| 4.23.2 | List of "PLMNs not allowed to operate at the present UE location" | 154 |
| 4.23.3 | 5GS mobility management via a satellite NG-RAN cell | 155 |
| 4.23.4 | 5GS session management via a satellite NG-RAN cell | 156 |
| 4.23.5 | Handling multiple tracking area codes from the lower layers | 156 |
| 4.24 | Minimization of service interruption | 157 |
| 4.25 | Support of MUSIM features | 159 |
| 4.26 | Support for Personal IoT Network service | 159 |
| 4.27 | Mobile base station relay support | 160 |
| 4.28 | NAS-specific aspects of mobile gNB with wireless access backhauling (MWAB) | 160 |
| 4.28.1 | General | 160 |
| 4.28.2 | Authorization of MWAB-UE | 161 |
| 4.28.3 | Control of UE access via MWAB | 161 |
| 4.29 | Support of indirect network sharing | 161 |
| 4.30 | QoS differentiation of traffic for non-3GPP device identifier | 163 |
| 5 | Elementary procedures for 5GS mobility management | 164 |
| 5.1 | Overview | 164 |
| 5.1.1 | General | 164 |
| 5.1.2 | Types of 5GMM procedures | 164 |
| 5.1.3 | 5GMM sublayer states | 165 |
| 5.1.3.1 | General | 165 |
| 5.1.3.2 | 5GMM sublayer states | 165 |
| 5.1.3.2.1 | 5GMM sublayer states in the UE | 165 |
| 5.1.3.2.1.1 | General | 165 |
| 5.1.3.2.1.2 | Main states | 166 |
| 5.1.3.2.1.2.1 | 5GMM-NULL | 166 |
| 5.1.3.2.1.2.2 | 5GMM-DEREGISTERED | 166 |
| 5.1.3.2.1.2.3 | 5GMM-REGISTERED-INITIATED | 166 |
| 5.1.3.2.1.2.4 | 5GMM-REGISTERED | 166 |
| 5.1.3.2.1.2.5 | 5GMM-DEREGISTERED-INITIATED | 166 |
| 5.1.3.2.1.2.6 | 5GMM-SERVICE-REQUEST-INITIATED | 166 |
| 5.1.3.2.1.3 | Substates of state 5GMM-DEREGISTERED | 167 |
| 5.1.3.2.1.3.1 | General | 167 |
| 5.1.3.2.1.3.2 | 5GMM-DEREGISTERED.NORMAL-SERVICE | 167 |
| 5.1.3.2.1.3.3 | 5GMM-DEREGISTERED.LIMITED-SERVICE | 167 |
| 5.1.3.2.1.3.4 | 5GMM-DEREGISTERED.ATTEMPTING-REGISTRATION | 167 |

| | | |
|---------------|--|-----|
| 5.1.3.2.1.3.5 | 5GMM-DEREGISTERED.PLMN-SEARCH | 167 |
| 5.1.3.2.1.3.6 | 5GMM-DEREGISTERED.NO-SUPI | 167 |
| 5.1.3.2.1.3.7 | 5GMM-DEREGISTERED.NO-CELL-AVAILABLE | 167 |
| 5.1.3.2.1.3.8 | 5GMM-DEREGISTERED.eCALL-INACTIVE | 168 |
| 5.1.3.2.1.3.9 | 5GMM-DEREGISTERED.INITIAL-REGISTRATION-NEEDED | 168 |
| 5.1.3.2.1.4 | Substates of state 5GMM-REGISTERED | 168 |
| 5.1.3.2.1.4.1 | General | 168 |
| 5.1.3.2.1.4.2 | 5GMM-REGISTERED.NORMAL-SERVICE | 168 |
| 5.1.3.2.1.4.3 | 5GMM-REGISTERED.NON-ALLOWED-SERVICE | 168 |
| 5.1.3.2.1.4.4 | 5GMM-REGISTERED.ATTEMPTING-REGISTRATION-UPDATE | 168 |
| 5.1.3.2.1.4.5 | 5GMM-REGISTERED.LIMITED-SERVICE | 169 |
| 5.1.3.2.1.4.6 | 5GMM-REGISTERED.PLMN-SEARCH | 169 |
| 5.1.3.2.1.4.7 | 5GMM-REGISTERED.NO-CELL-AVAILABLE | 169 |
| 5.1.3.2.1.4.8 | 5GMM-REGISTERED.UPDATE-NEEDED | 169 |
| 5.1.3.2.2 | 5GS update status in the UE | 170 |
| 5.1.3.2.3 | 5GMM sublayer states in the network side | 170 |
| 5.1.3.2.3.1 | General | 170 |
| 5.1.3.2.3.2 | 5GMM-DEREGISTERED | 171 |
| 5.1.3.2.3.3 | 5GMM-COMMON-PROCEDURE-INITIATED | 171 |
| 5.1.3.2.3.4 | 5GMM-REGISTERED | 171 |
| 5.1.3.2.3.5 | 5GMM-DEREGISTERED-INITIATED | 171 |
| 5.1.4 | Coordination between 5GMM and EMM | 171 |
| 5.1.4.1 | General | 171 |
| 5.1.4.2 | Coordination between 5GMM for 3GPP access and EMM with N26 interface | 172 |
| 5.1.4.3 | Coordination between 5GMM for 3GPP access and EMM without N26 interface | 172 |
| 5.1.5 | Coordination between 5GMM and GMM | 173 |
| 5.2 | Behaviour of the UE in state 5GMM-DEREGISTERED and state 5GMM-REGISTERED | 173 |
| 5.2.1 | General | 173 |
| 5.2.2 | UE behaviour in state 5GMM-DEREGISTERED | 173 |
| 5.2.2.1 | General | 173 |
| 5.2.2.2 | Primary substate selection | 173 |
| 5.2.2.2.1 | Selection of the substate after power on | 173 |
| 5.2.2.3 | Detailed description of UE behaviour in state 5GMM-DEREGISTERED | 174 |
| 5.2.2.3.1 | NORMAL-SERVICE | 174 |
| 5.2.2.3.2 | LIMITED-SERVICE | 174 |
| 5.2.2.3.3 | ATTEMPTING-REGISTRATION | 174 |
| 5.2.2.3.4 | PLMN-SEARCH | 176 |
| 5.2.2.3.5 | NO-SUPI | 176 |
| 5.2.2.3.6 | NO-CELL-AVAILABLE | 176 |
| 5.2.2.3.7 | eCALL-INACTIVE | 176 |
| 5.2.2.3.8 | INITIAL-REGISTRATION-NEEDED | 177 |
| 5.2.2.4 | Substate when back to state 5GMM-DEREGISTERED from another 5GMM state | 177 |
| 5.2.3 | UE behaviour in state 5GMM-REGISTERED | 177 |
| 5.2.3.1 | General | 177 |
| 5.2.3.2 | Detailed description of UE behaviour in state 5GMM-REGISTERED | 177 |
| 5.2.3.2.1 | NORMAL-SERVICE | 177 |
| 5.2.3.2.2 | NON-ALLOWED-SERVICE | 178 |
| 5.2.3.2.3 | ATTEMPTING-REGISTRATION-UPDATE | 178 |
| 5.2.3.2.4 | LIMITED-SERVICE | 180 |
| 5.2.3.2.5 | PLMN-SEARCH | 180 |
| 5.2.3.2.6 | NO-CELL-AVAILABLE | 180 |
| 5.2.3.2.7 | UPDATE-NEEDED | 180 |
| 5.3 | General on elementary 5GMM procedures | 181 |
| 5.3.1 | 5GMM modes and N1 NAS signalling connection | 181 |
| 5.3.1.1 | Establishment of the N1 NAS signalling connection | 181 |
| 5.3.1.2 | Re-establishment of the N1 NAS signalling connection | 183 |
| 5.3.1.3 | Release of the N1 NAS signalling connection | 184 |
| 5.3.1.4 | 5GMM-CONNECTED mode with RRC inactive indication | 189 |
| 5.3.1.5 | Suspend and resume of the N1 NAS signalling connection | 193 |
| 5.3.2 | Permanent identifiers | 194 |
| 5.3.3 | Temporary identities | 197 |
| 5.3.4 | Registration areas | 198 |

| | | |
|--------------|---|-----|
| 5.3.5 | Service area restrictions | 199 |
| 5.3.5.1 | General | 199 |
| 5.3.5.2 | 3GPP access service area restrictions..... | 199 |
| 5.3.5.3 | Wireline access service area restrictions | 203 |
| 5.3.6 | Mobile initiated connection only mode | 204 |
| 5.3.7 | Handling of the periodic registration update timer and mobile reachable timer | 207 |
| 5.3.8 | Handling of timer T3502 | 209 |
| 5.3.9 | Handling of NAS level mobility management congestion control | 209 |
| 5.3.10 | Handling of DNN based congestion control..... | 210 |
| 5.3.11 | Handling of S-NSSAI based congestion control..... | 210 |
| 5.3.12 | Handling of local emergency numbers | 211 |
| 5.3.12A | Handling of local emergency numbers received via 3GPP access and non-3GPP access | 212 |
| 5.3.12A.1 | General | 212 |
| 5.3.12A.2 | Receiving a REGISTRATION ACCEPT message via non-3GPP access..... | 212 |
| 5.3.13 | Lists of 5GS forbidden tracking areas..... | 213 |
| 5.3.13A | Forbidden PLMN lists | 214 |
| 5.3.14 | List of equivalent PLMNs..... | 215 |
| 5.3.14A | List of equivalent SNPNs | 215 |
| 5.3.15 | Transmission failure abnormal case in the UE | 216 |
| 5.3.15A | Abnormal cases in the UE | 216 |
| 5.3.16 | Extended DRX cycle for UEs in 5GMM-IDLE and 5GMM-CONNECTED mode with RRC inactive indication | 216 |
| 5.3.17 | Service Gap Control..... | 217 |
| 5.3.18 | Restriction on use of enhanced coverage | 219 |
| 5.3.19 | Handling of congestion control for transport of user data via the control plane | 219 |
| 5.3.19A | Specific requirements for UE configured to use timer T3245 | 220 |
| 5.3.19A.1 | UE not operating in SNPN access operation mode | 220 |
| 5.3.19A.2 | UE operating in SNPN access operation mode | 220 |
| 5.3.20 | Specific requirements for UE when receiving non-integrity protected reject messages | 221 |
| 5.3.20.1 | General | 221 |
| 5.3.20.2 | Requirements for UE in a PLMN..... | 221 |
| 5.3.20.3 | Requirements for UE in an SNPN..... | 226 |
| 5.3.21 | CIoT 5GS optimizations | 231 |
| 5.3.22 | Interaction between MICO mode with active time and extended idle mode DRX cycle | 233 |
| 5.3.23 | Forbidden wireline access area | 233 |
| 5.3.24 | WUS assistance | 233 |
| 5.3.25 | Core network assistance for paging early indication with paging subgrouping assistance (PEIPS)..... | 234 |
| 5.3.26 | Support for unavailability period | 235 |
| 5.3.27 | Low power wake up signal (LP-WUS)..... | 237 |
| 5.3.27.1 | General | 237 |
| 5.3.27.2 | LP-WUS disabling | 237 |
| 5.3.27.3 | Core network assistance for low power wake up signal with paging subgrouping (LP-WUSPS) | 237 |
| 5.4 | 5GMM common procedures..... | 238 |
| 5.4.1 | Primary authentication and key agreement procedure | 238 |
| 5.4.1.1 | General | 238 |
| 5.4.1.2 | EAP based primary authentication and key agreement procedure | 238 |
| 5.4.1.2.1 | General | 238 |
| 5.4.1.2.2 | EAP-AKA' related procedures..... | 241 |
| 5.4.1.2.2.1 | General..... | 241 |
| 5.4.1.2.2.2 | Initiation..... | 241 |
| 5.4.1.2.2.3 | UE successfully authenticates network | 241 |
| 5.4.1.2.2.4 | Errors when handling EAP-request/AKA'-challenge message | 242 |
| 5.4.1.2.2.5 | Network successfully authenticates UE..... | 242 |
| 5.4.1.2.2.6 | UE handling EAP-AKA' notification message | 243 |
| 5.4.1.2.2.6A | EAP based Identification initiation by the network | 243 |
| 5.4.1.2.2.6B | EAP based Identification response by the UE | 243 |
| 5.4.1.2.2.7 | Network sending EAP-success message..... | 243 |
| 5.4.1.2.2.8 | UE handling EAP-success message | 244 |
| 5.4.1.2.2.9 | Network not successfully authenticates UE | 244 |
| 5.4.1.2.2.10 | Network sending EAP-failure message | 244 |
| 5.4.1.2.2.11 | UE handling EAP-failure message | 245 |
| 5.4.1.2.2.12 | Abnormal cases in the UE..... | 247 |

| | | |
|--------------|---|-----|
| 5.4.1.2.3 | EAP-TLS related procedures | 248 |
| 5.4.1.2.3.1 | General | 248 |
| 5.4.1.2.3A | Procedures related to EAP methods other than EAP-AKA' and EAP-TLS | 252 |
| 5.4.1.2.3A.1 | General | 252 |
| 5.4.1.2.3A.2 | EAP-TTLS with two phases of authentication | 256 |
| 5.4.1.2.3B | Procedures related to EAP methods used for primary authentication of an N5GC device | 256 |
| 5.4.1.2.3B.1 | General | 256 |
| 5.4.1.2.3C | Procedures related to EAP methods used for primary authentication of an AUN3 device | 258 |
| 5.4.1.2.3C.1 | General | 258 |
| 5.4.1.2.4 | EAP message reliable transport procedure | 259 |
| 5.4.1.2.4.1 | General | 259 |
| 5.4.1.2.4.2 | EAP message reliable transport procedure initiation by the network | 259 |
| 5.4.1.2.4.3 | EAP message reliable transport procedure accepted by the UE | 260 |
| 5.4.1.2.4.4 | Abnormal cases on the network side | 260 |
| 5.4.1.2.4.5 | Abnormal cases in the UE | 260 |
| 5.4.1.2.5 | EAP result message transport procedure | 262 |
| 5.4.1.2.5.1 | General | 262 |
| 5.4.1.2.5.2 | EAP result message transport procedure initiation by the network | 263 |
| 5.4.1.3 | 5G AKA based primary authentication and key agreement procedure | 263 |
| 5.4.1.3.1 | General | 263 |
| 5.4.1.3.2 | Authentication initiation by the network | 264 |
| 5.4.1.3.3 | Authentication response by the UE | 265 |
| 5.4.1.3.4 | Authentication completion by the network | 265 |
| 5.4.1.3.5 | Authentication not accepted by the network | 266 |
| 5.4.1.3.6 | Authentication not accepted by the UE | 268 |
| 5.4.1.3.7 | Abnormal cases | 269 |
| 5.4.2 | Security mode control procedure | 273 |
| 5.4.2.1 | General | 273 |
| 5.4.2.2 | NAS security mode control initiation by the network | 274 |
| 5.4.2.3 | NAS security mode command accepted by the UE | 277 |
| 5.4.2.4 | NAS security mode control completion by the network | 280 |
| 5.4.2.5 | NAS security mode command not accepted by the UE | 281 |
| 5.4.2.6 | Abnormal cases in the UE | 281 |
| 5.4.2.7 | Abnormal cases on the network side | 282 |
| 5.4.3 | Identification procedure | 282 |
| 5.4.3.1 | General | 282 |
| 5.4.3.2 | Identification initiation by the network | 282 |
| 5.4.3.3 | Identification response by the UE | 283 |
| 5.4.3.4 | Identification completion by the network | 283 |
| 5.4.3.5 | Abnormal cases in the UE | 283 |
| 5.4.3.6 | Abnormal cases on the network side | 283 |
| 5.4.4 | Generic UE configuration update procedure | 284 |
| 5.4.4.1 | General | 284 |
| 5.4.4.2 | Generic UE configuration update procedure initiated by the network | 288 |
| 5.4.4.3 | Generic UE configuration update accepted by the UE | 295 |
| 5.4.4.4 | Generic UE configuration update completion by the network | 304 |
| 5.4.4.5 | Abnormal cases in the UE | 305 |
| 5.4.4.6 | Abnormal cases on the network side | 306 |
| 5.4.5 | NAS transport procedure(s) | 308 |
| 5.4.5.1 | General | 308 |
| 5.4.5.2 | UE-initiated NAS transport procedure | 308 |
| 5.4.5.2.1 | General | 308 |
| 5.4.5.2.2 | UE-initiated NAS transport procedure initiation | 309 |
| 5.4.5.2.3 | UE-initiated NAS transport of messages accepted by the network | 312 |
| 5.4.5.2.4 | UE-initiated NAS transport of messages not accepted by the network | 317 |
| 5.4.5.2.5 | Abnormal cases on the network side | 319 |
| 5.4.5.2.6 | Abnormal cases in the UE | 325 |
| 5.4.5.3 | Network-initiated NAS transport procedure | 327 |
| 5.4.5.3.1 | General | 327 |
| 5.4.5.3.2 | Network-initiated NAS transport procedure initiation | 328 |
| 5.4.5.3.3 | Network-initiated NAS transport of messages accepted by the UE | 333 |
| 5.4.6 | 5GMM status procedure | 339 |

| | | |
|------------|--|-----|
| 5.4.6.1 | General | 339 |
| 5.4.6.2 | 5GMM status received in the UE | 339 |
| 5.4.6.3 | 5GMM status received in the network | 340 |
| 5.4.7 | Network slice-specific authentication and authorization procedure | 340 |
| 5.4.7.1 | General | 340 |
| 5.4.7.2 | Network slice-specific EAP message reliable transport procedure | 341 |
| 5.4.7.2.1 | Network slice-specific EAP message reliable transport procedure initiation | 341 |
| 5.4.7.2.2 | Network slice-specific EAP message reliable transport procedure accepted by the UE | 342 |
| 5.4.7.2.3 | Abnormal cases on the network side | 342 |
| 5.4.7.2.4 | Abnormal cases in the UE | 343 |
| 5.4.7.3 | Network slice-specific EAP result message transport procedure | 344 |
| 5.4.7.3.1 | Network slice-specific EAP result message transport procedure initiation | 344 |
| 5.5 | 5GMM specific procedures | 345 |
| 5.5.1 | Registration procedure | 345 |
| 5.5.1.1 | General | 345 |
| 5.5.1.2 | Registration procedure for initial registration | 346 |
| 5.5.1.2.1 | General | 346 |
| 5.5.1.2.2 | Initial registration initiation | 346 |
| 5.5.1.2.3 | 5GMM common procedure initiation | 358 |
| 5.5.1.2.4 | Initial registration accepted by the network | 358 |
| 5.5.1.2.5 | Initial registration not accepted by the network | 387 |
| 5.5.1.2.6 | Initial registration for emergency services not accepted by the network | 403 |
| 5.5.1.2.6A | Initial registration for initiating an emergency PDU session not accepted by the network | 404 |
| 5.5.1.2.7 | Abnormal cases in the UE | 405 |
| 5.5.1.2.8 | Abnormal cases on the network side | 409 |
| 5.5.1.3 | Registration procedure for mobility and periodic registration update | 411 |
| 5.5.1.3.1 | General | 411 |
| 5.5.1.3.2 | Mobility and periodic registration update initiation | 411 |
| 5.5.1.3.3 | 5GMM common procedure initiation | 429 |
| 5.5.1.3.4 | Mobility and periodic registration update accepted by the network | 429 |
| 5.5.1.3.5 | Mobility and periodic registration update not accepted by the network | 466 |
| 5.5.1.3.6 | Mobility and periodic registration update for initiating an emergency PDU session not accepted by the network | 484 |
| 5.5.1.3.6A | Mobility and periodic registration update for an emergency services fallback not accepted by the network | 485 |
| 5.5.1.3.6B | Mobility and periodic registration update when an emergency services fallback is pending | 485 |
| 5.5.1.3.7 | Abnormal cases in the UE | 485 |
| 5.5.1.3.8 | Abnormal cases on the network side | 491 |
| 5.5.2 | De-registration procedure | 495 |
| 5.5.2.1 | General | 495 |
| 5.5.2.2 | UE-initiated de-registration procedure | 497 |
| 5.5.2.2.1 | UE-initiated de-registration procedure initiation | 497 |
| 5.5.2.2.2 | UE-initiated de-registration procedure completion | 498 |
| 5.5.2.2.3 | UE-initiated de-registration procedure completion for 5GS services over 3GPP access | 499 |
| 5.5.2.2.4 | UE-initiated de-registration procedure completion for 5GS services over non-3GPP access | 499 |
| 5.5.2.2.5 | UE-initiated de-registration procedure completion for 5GS services over both 3GPP access and non-3GPP access | 500 |
| 5.5.2.2.6 | Abnormal cases in the UE | 500 |
| 5.5.2.2.7 | Abnormal cases in the network side | 502 |
| 5.5.2.3 | Network-initiated de-registration procedure | 503 |
| 5.5.2.3.1 | Network-initiated de-registration procedure initiation | 503 |
| 5.5.2.3.2 | Network-initiated de-registration procedure completion by the UE | 505 |
| 5.5.2.3.3 | Network-initiated de-registration procedure completion by the network | 518 |
| 5.5.2.3.4 | Abnormal cases in the UE | 518 |
| 5.5.2.3.5 | Abnormal cases in the network side | 518 |
| 5.5.3 | eCall inactivity procedure | 520 |
| 5.5.4 | Authentication and key agreement procedure for 5G ProSe UE-to-network relay and 5G ProSe UE- to-UE relay | 520 |
| 5.5.4.1 | General | 520 |
| 5.5.4.2 | ProSe relay transaction identity (PRTI) | 522 |
| 5.5.4.3 | UE-initiated authentication and key agreement procedure initiation | 522 |
| 5.5.4.4 | UE-initiated authentication and key agreement procedure accepted by the network | 523 |

| | | |
|-----------|---|-----|
| 5.5.4.5 | UE-initiated authentication and key agreement procedure not accepted by the network..... | 524 |
| 5.5.4.6 | Abnormal cases in the UE..... | 524 |
| 5.5.4.7 | Abnormal cases on the network side..... | 524 |
| 5.6 | 5GMM connection management procedures..... | 525 |
| 5.6.1 | Service request procedure..... | 525 |
| 5.6.1.1 | General..... | 525 |
| 5.6.1.2 | Service request procedure initiation..... | 529 |
| 5.6.1.2.1 | UE is not using 5GS services with control plane CIoT 5GS optimization..... | 529 |
| 5.6.1.2.2 | UE is using 5GS services with control plane CIoT 5GS optimization..... | 533 |
| 5.6.1.3 | Common procedure initiation..... | 535 |
| 5.6.1.4 | Service request procedure accepted by the network..... | 535 |
| 5.6.1.4.1 | UE is not using 5GS services with control plane CIoT 5GS optimization..... | 535 |
| 5.6.1.4.2 | UE is using 5GS services with control plane CIoT 5GS optimization..... | 540 |
| 5.6.1.5 | Service request procedure not accepted by the network..... | 545 |
| 5.6.1.6 | Service request procedure for initiating an emergency PDU session not accepted by the network.... | 558 |
| 5.6.1.6A | Service request procedure for an emergency services fallback not accepted by the network..... | 559 |
| 5.6.1.7 | Abnormal cases in the UE..... | 559 |
| 5.6.1.8 | Abnormal cases on the network side..... | 564 |
| 5.6.2 | Paging procedure..... | 566 |
| 5.6.2.1 | General..... | 566 |
| 5.6.2.2 | Paging for 5GS services..... | 566 |
| 5.6.2.2.1 | General..... | 566 |
| 5.6.2.2.2 | Abnormal cases on the network side..... | 569 |
| 5.6.2.2.3 | Abnormal cases in the UE..... | 569 |
| 5.6.3 | Notification procedure..... | 569 |
| 5.6.3.1 | General..... | 569 |
| 5.6.3.2 | Notification procedure initiation..... | 570 |
| 5.6.3.3 | Notification procedure completion..... | 572 |
| 5.6.3.4 | Abnormal cases on the network side..... | 573 |
| 5.6.3.5 | Abnormal cases on the UE side..... | 573 |
| 6 | Elementary procedures for 5GS session management..... | 574 |
| 6.1 | Overview..... | 574 |
| 6.1.1 | General..... | 574 |
| 6.1.2 | Types of 5GSM procedures..... | 574 |
| 6.1.3 | 5GSM sublayer states..... | 575 |
| 6.1.3.1 | General..... | 575 |
| 6.1.3.2 | 5GSM sublayer states in the UE..... | 575 |
| 6.1.3.2.1 | Overview..... | 575 |
| 6.1.3.2.2 | PDU SESSION INACTIVE..... | 576 |
| 6.1.3.2.3 | PDU SESSION ACTIVE PENDING..... | 576 |
| 6.1.3.2.4 | PDU SESSION ACTIVE..... | 576 |
| 6.1.3.2.5 | PDU SESSION INACTIVE PENDING..... | 576 |
| 6.1.3.2.6 | PDU SESSION MODIFICATION PENDING..... | 576 |
| 6.1.3.2.7 | PROCEDURE TRANSACTION INACTIVE..... | 576 |
| 6.1.3.2.8 | PROCEDURE TRANSACTION PENDING..... | 576 |
| 6.1.3.3 | 5GSM sublayer states in the network side..... | 577 |
| 6.1.3.3.1 | Overview..... | 577 |
| 6.1.3.3.2 | PDU SESSION INACTIVE..... | 577 |
| 6.1.3.3.3 | PDU SESSION ACTIVE..... | 577 |
| 6.1.3.3.4 | PDU SESSION INACTIVE PENDING..... | 577 |
| 6.1.3.3.5 | PDU SESSION MODIFICATION PENDING..... | 578 |
| 6.1.3.3.6 | PROCEDURE TRANSACTION INACTIVE..... | 578 |
| 6.1.3.3.7 | PROCEDURE TRANSACTION PENDING..... | 578 |
| 6.1.4 | Coordination between 5GSM and ESM..... | 578 |
| 6.1.4.1 | Coordination between 5GSM and ESM with N26 interface..... | 578 |
| 6.1.4.2 | Coordination between 5GSM and ESM without N26 interface..... | 592 |
| 6.1.4A | Coordination between 5GSM and SM..... | 594 |
| 6.1.5 | Coordination for interworking with ePDG connected to EPC..... | 594 |
| 6.2 | General on elementary 5GSM procedures..... | 595 |
| 6.2.1 | Principles of PTI handling for 5GSM procedures..... | 595 |
| 6.2.2 | PDU session types..... | 597 |

| | | |
|-------------|--|-----|
| 6.2.3 | PDU session management | 597 |
| 6.2.4 | IP address allocation | 598 |
| 6.2.4.1 | General | 598 |
| 6.2.4.2 | IP address allocation via NAS signalling | 598 |
| 6.2.4.2a | IPv6 prefix delegation via DHCPv6..... | 599 |
| 6.2.4.3 | Additional RG related requirements for IP address allocation..... | 599 |
| 6.2.4.4 | Additional requirements of the UE acting as 5G ProSe layer-3 UE-to-network relay UE for IP address allocation..... | 600 |
| 6.2.5 | Quality of service..... | 600 |
| 6.2.5.1 | General | 600 |
| 6.2.5.1.1 | QoS rules | 600 |
| 6.2.5.1.1.1 | General..... | 600 |
| 6.2.5.1.1.2 | Signalled QoS rules | 600 |
| 6.2.5.1.1.3 | Derived QoS rules..... | 602 |
| 6.2.5.1.1.4 | QoS flow descriptions..... | 602 |
| 6.2.5.1.2 | Session-AMBR..... | 603 |
| 6.2.5.1.2A | Void..... | 603 |
| 6.2.5.1.3 | UL user data packet matching | 603 |
| 6.2.5.1.4 | Reflective QoS..... | 603 |
| 6.2.5.1.4.1 | General..... | 603 |
| 6.2.5.1.4.2 | Derivation of packet filter for UL direction from DL user data packet | 604 |
| 6.2.5.1.4.3 | Creating a derived QoS rule by reflective QoS in the UE..... | 606 |
| 6.2.5.1.4.4 | Updating a derived QoS rule by reflective QoS in the UE | 606 |
| 6.2.5.1.4.5 | Deleting a derived QoS rule in the UE | 606 |
| 6.2.5.1.4.6 | Ignoring RQI in the UE..... | 607 |
| 6.2.5.2 | QoS in MA PDU session..... | 607 |
| 6.2.6 | Local area data network (LADN) | 607 |
| 6.2.7 | Handling of DNN based congestion control..... | 609 |
| 6.2.8 | Handling of S-NSSAI based congestion control..... | 610 |
| 6.2.9 | Interaction with upper layers | 614 |
| 6.2.9.1 | General | 614 |
| 6.2.9.2 | URSP..... | 614 |
| 6.2.9.3 | ProSeP..... | 614 |
| 6.2.10 | Handling of 3GPP PS data off | 615 |
| 6.2.11 | Multi-homed IPv6 PDU session | 616 |
| 6.2.12 | Handling of network rejection not due to congestion control | 617 |
| 6.2.13 | Handling of Small data rate control | 619 |
| 6.2.14 | Handling of Serving PLMN rate control..... | 619 |
| 6.2.15 | Handling of Reliable Data Service | 620 |
| 6.2.16 | Handling of header compression for control plane CIoT optimizations | 620 |
| 6.2.17 | Handling of edge computing enhancements | 620 |
| 6.2.18 | Support of redundant PDU sessions | 621 |
| 6.2.19 | Handling of maximum group data rate limitation control..... | 621 |
| 6.2.20 | Support of UL PDU set based handling..... | 622 |
| 6.3 | Network-requested 5GSM procedures | 622 |
| 6.3.1 | PDU session authentication and authorization procedure..... | 622 |
| 6.3.1.1 | General | 622 |
| 6.3.1.2 | PDU EAP message reliable transport procedure..... | 624 |
| 6.3.1.2.1 | PDU EAP message reliable transport procedure initiation..... | 624 |
| 6.3.1.2.2 | PDU EAP message reliable transport procedure accepted by the UE | 626 |
| 6.3.1.2.3 | Abnormal cases on the network side | 626 |
| 6.3.1.2.4 | Abnormal cases in the UE | 627 |
| 6.3.1.3 | PDU EAP result message transport procedure..... | 627 |
| 6.3.1.3.1 | PDU EAP result message transport procedure initiation | 627 |
| 6.3.1.3.2 | Abnormal cases in the UE | 627 |
| 6.3.1A | Service-level authentication and authorization procedure | 628 |
| 6.3.1A.1 | General | 628 |
| 6.3.1A.2 | Service-level authentication and authorization procedure initiation | 629 |
| 6.3.1A.3 | Service-level authentication and authorization procedure accepted by the UE..... | 631 |
| 6.3.1A.4 | Abnormal cases on the network side..... | 631 |
| 6.3.1A.5 | Abnormal cases in the UE..... | 631 |
| 6.3.2 | Network-requested PDU session modification procedure | 632 |

| | | |
|-----------|---|-----|
| 6.3.2.1 | General | 632 |
| 6.3.2.2 | Network-requested PDU session modification procedure initiation | 632 |
| 6.3.2.3 | Network-requested PDU session modification procedure accepted by the UE..... | 638 |
| 6.3.2.4 | Network-requested PDU session modification procedure not accepted by the UE..... | 648 |
| 6.3.2.5 | Abnormal cases on the network side..... | 653 |
| 6.3.2.6 | Abnormal cases in the UE..... | 654 |
| 6.3.3 | Network-requested PDU session release procedure | 655 |
| 6.3.3.1 | General | 655 |
| 6.3.3.2 | Network-requested PDU session release procedure initiation | 655 |
| 6.3.3.3 | Network-requested PDU session release procedure accepted by the UE..... | 658 |
| 6.3.3.4 | N1 SM delivery skipped..... | 674 |
| 6.3.3.5 | Abnormal cases on the network side..... | 674 |
| 6.3.3.6 | Abnormal cases in the UE..... | 675 |
| 6.4 | UE-requested 5GSM procedures..... | 675 |
| 6.4.1 | UE-requested PDU session establishment procedure | 675 |
| 6.4.1.1 | General | 675 |
| 6.4.1.2 | UE-requested PDU session establishment procedure initiation | 676 |
| 6.4.1.3 | UE-requested PDU session establishment procedure accepted by the network | 688 |
| 6.4.1.4 | UE-requested PDU session establishment procedure not accepted by the network..... | 704 |
| 6.4.1.4.1 | General | 704 |
| 6.4.1.4.2 | Handling of network rejection due to congestion control..... | 708 |
| 6.4.1.4.3 | Handling of network rejection not due to congestion control..... | 720 |
| 6.4.1.5 | Handling the maximum number of established PDU sessions..... | 730 |
| 6.4.1.5A | Handling the maximum number of allowed active user-plane resources for PDU sessions of UEs in NB-N1 mode | 731 |
| 6.4.1.6 | Abnormal cases in the UE..... | 731 |
| 6.4.1.7 | Abnormal cases on the network side..... | 734 |
| 6.4.2 | UE-requested PDU session modification procedure..... | 734 |
| 6.4.2.1 | General | 734 |
| 6.4.2.2 | UE-requested PDU session modification procedure initiation..... | 736 |
| 6.4.2.3 | UE-requested PDU session modification procedure accepted by the network | 742 |
| 6.4.2.4 | UE-requested PDU session modification procedure not accepted by the network | 742 |
| 6.4.2.4.1 | General | 742 |
| 6.4.2.4.2 | Handling of network rejection due to congestion control..... | 744 |
| 6.4.2.4.3 | Handling of network rejection not due to congestion control..... | 758 |
| 6.4.2.5 | Abnormal cases in the UE..... | 763 |
| 6.4.2.6 | Abnormal cases on the network side..... | 764 |
| 6.4.3 | UE-requested PDU session release procedure | 765 |
| 6.4.3.1 | General | 765 |
| 6.4.3.2 | UE-requested PDU session release procedure initiation | 766 |
| 6.4.3.3 | UE-requested PDU session release procedure accepted by the network..... | 767 |
| 6.4.3.4 | UE-requested PDU session release procedure not accepted by the network..... | 767 |
| 6.4.3.5 | Abnormal cases in the UE..... | 767 |
| 6.4.3.6 | Abnormal cases on the network side..... | 768 |
| 6.5 | 5GSM status procedure | 769 |
| 6.5.1 | General..... | 769 |
| 6.5.2 | 5GSM status received in the UE..... | 769 |
| 6.5.3 | 5GSM status received in the SMF | 769 |
| 6.6 | Miscellaneous procedures | 770 |
| 6.6.1 | Exchange of extended protocol configuration options..... | 770 |
| 6.6.2 | Remote UE report procedure | 770 |
| 6.6.2.1 | General | 770 |
| 6.6.2.2 | Remote UE report procedure initiation | 770 |
| 6.6.2.3 | Remote UE report procedure accepted by the network..... | 771 |
| 6.6.2.4 | Abnormal cases in the UE..... | 771 |
| 6.6.2.5 | Abnormal cases on the network side..... | 772 |
| 7 | Handling of unknown, unforeseen, and erroneous protocol data..... | 772 |
| 7.1 | General | 772 |
| 7.2 | Message too short or too long | 773 |
| 7.2.1 | Message too short | 773 |
| 7.2.2 | Message too long | 773 |

| | | |
|----------|---|-----|
| 7.3 | Unknown or unforeseen procedure transaction identity or PDU Session identity..... | 773 |
| 7.3.1 | Procedure transaction identity..... | 773 |
| 7.3.2 | PDU Session identity..... | 774 |
| 7.4 | Unknown or unforeseen message type..... | 775 |
| 7.5 | Non-semantic mandatory information element errors..... | 775 |
| 7.5.1 | Common procedures..... | 775 |
| 7.5.2 | 5GS mobility management..... | 776 |
| 7.5.3 | 5GS session management..... | 776 |
| 7.6 | Unknown and unforeseen IEs in the non-imperative message part..... | 776 |
| 7.6.1 | IEs unknown in the message..... | 776 |
| 7.6.2 | Out of sequence IEs..... | 776 |
| 7.6.3 | Repeated IEs..... | 776 |
| 7.6.4 | Unknown and unforeseen IEs in a Type 6 IE container information element..... | 777 |
| 7.6.4.1 | IEs unknown in the Type 6 IE container information element..... | 777 |
| 7.6.4.2 | Out of sequence IEs..... | 777 |
| 7.6.4.3 | Repeated IEs..... | 777 |
| 7.7 | Non-imperative message part errors..... | 777 |
| 7.7.1 | Syntactically incorrect optional IEs..... | 777 |
| 7.7.2 | Conditional IE errors..... | 777 |
| 7.7.3 | Errors in a Type 6 IE container information element..... | 778 |
| 7.7.3.1 | Syntactically incorrect optional IEs..... | 778 |
| 7.7.3.2 | Conditional IE errors..... | 778 |
| 7.8 | Messages with semantically incorrect contents..... | 778 |
| 8 | Message functional definitions and contents..... | 778 |
| 8.1 | Overview..... | 778 |
| 8.2 | 5GS mobility management messages..... | 780 |
| 8.2.1 | Authentication request..... | 780 |
| 8.2.1.1 | Message definition..... | 780 |
| 8.2.1.2 | Authentication parameter RAND..... | 780 |
| 8.2.1.3 | Authentication parameter AUTN..... | 780 |
| 8.2.1.4 | Void..... | 780 |
| 8.2.1.5 | EAP message..... | 780 |
| 8.2.2 | Authentication response..... | 781 |
| 8.2.2.1 | Message definition..... | 781 |
| 8.2.2.2 | Authentication response parameter..... | 781 |
| 8.2.2.3 | EAP message..... | 781 |
| 8.2.3 | Authentication result..... | 781 |
| 8.2.3.1 | Message definition..... | 781 |
| 8.2.3.2 | ABBA..... | 782 |
| 8.2.3.3 | AUN3 device security key..... | 782 |
| 8.2.4 | Authentication failure..... | 782 |
| 8.2.4.1 | Message definition..... | 782 |
| 8.2.4.2 | Authentication failure parameter..... | 783 |
| 8.2.5 | Authentication reject..... | 783 |
| 8.2.5.1 | Message definition..... | 783 |
| 8.2.5.2 | EAP message..... | 783 |
| 8.2.6 | Registration request..... | 783 |
| 8.2.6.1 | Message definition..... | 783 |
| 8.2.6.2 | Non-current native NAS key set identifier..... | 787 |
| 8.2.6.3 | 5GMM capability..... | 787 |
| 8.2.6.4 | UE security capability..... | 787 |
| 8.2.6.5 | Requested NSSAI..... | 787 |
| 8.2.6.6 | Last visited registered TAI..... | 787 |
| 8.2.6.7 | S1 UE network capability..... | 788 |
| 8.2.6.8 | Uplink data status..... | 788 |
| 8.2.6.9 | PDU session status..... | 788 |
| 8.2.6.10 | MICO indication..... | 788 |
| 8.2.6.11 | UE status..... | 788 |
| 8.2.6.12 | Additional GUTI..... | 788 |
| 8.2.6.13 | Allowed PDU session status..... | 788 |
| 8.2.6.14 | UE's usage setting..... | 788 |

| | | |
|-----------|--|-----|
| 8.2.6.15 | Requested DRX parameters | 788 |
| 8.2.6.16 | EPS NAS message container..... | 788 |
| 8.2.6.17 | LADN indication..... | 789 |
| 8.2.6.17A | Payload container type | 789 |
| 8.2.6.18 | Payload container..... | 789 |
| 8.2.6.19 | Network slicing indication | 789 |
| 8.2.6.20 | 5GS update type | 789 |
| 8.2.6.21 | NAS message container | 789 |
| 8.2.6.22 | Requested extended DRX parameters | 790 |
| 8.2.6.23 | EPS bearer context status | 790 |
| 8.2.6.24 | T3324 value..... | 790 |
| 8.2.6.25 | Mobile station classmark 2..... | 790 |
| 8.2.6.26 | Supported codecs | 790 |
| 8.2.6.27 | UE radio capability ID | 790 |
| 8.2.6.28 | Requested mapped NSSAI..... | 790 |
| 8.2.6.29 | Additional information requested..... | 790 |
| 8.2.6.30 | Requested WUS assistance information..... | 790 |
| 8.2.6.31 | Void..... | 790 |
| 8.2.6.32 | N5GC indication | 790 |
| 8.2.6.33 | Requested NB-N1 mode DRX parameters..... | 790 |
| 8.2.6.34 | UE request type | 790 |
| 8.2.6.35 | Paging restriction | 791 |
| 8.2.6.35 | Service-level-AA container..... | 791 |
| 8.2.6.36 | NID | 791 |
| 8.2.6.37 | UE determined PLMN with disaster condition | 791 |
| 8.2.6.38 | Requested PEIPS assistance information | 791 |
| 8.2.6.38A | Void..... | 791 |
| 8.2.6.39 | Requested T3512 value..... | 791 |
| 8.2.6.40 | Unavailability information | 791 |
| 8.2.6.41 | Non-3GPP path switching information | 791 |
| 8.2.6.42 | AUN3 indication | 791 |
| 8.2.6.43 | Requested LP-WUSPS assistance information | 791 |
| 8.2.7 | Registration accept..... | 791 |
| 8.2.7.1 | Message definition | 791 |
| 8.2.7.2 | 5G-GUTI..... | 796 |
| 8.2.7.3 | Equivalent PLMNs..... | 796 |
| 8.2.7.4 | TAI list | 796 |
| 8.2.7.5 | Allowed NSSAI | 796 |
| 8.2.7.6 | Rejected NSSAI | 796 |
| 8.2.7.7 | Configured NSSAI..... | 796 |
| 8.2.7.8 | 5GS network feature support..... | 797 |
| 8.2.7.9 | PDU session status | 797 |
| 8.2.7.10 | PDU session reactivation result..... | 797 |
| 8.2.7.11 | PDU session reactivation result error cause | 797 |
| 8.2.7.12 | LADN information..... | 797 |
| 8.2.7.13 | MICO indication | 797 |
| 8.2.7.14 | Network slicing indication | 797 |
| 8.2.7.15 | Service area list | 797 |
| 8.2.7.16 | T3512 value..... | 797 |
| 8.2.7.17 | Non-3GPP de-registration timer value | 797 |
| 8.2.7.18 | T3502 value..... | 798 |
| 8.2.7.19 | Emergency number list | 798 |
| 8.2.7.20 | Extended emergency number list | 798 |
| 8.2.7.21 | SOR transparent container | 798 |
| 8.2.7.22 | EAP message..... | 798 |
| 8.2.7.23 | NSSAI inclusion mode..... | 798 |
| 8.2.7.24 | Operator-defined access category definitions | 798 |
| 8.2.7.25 | Negotiated DRX parameters | 798 |
| 8.2.7.26 | Non-3GPP NW policies | 798 |
| 8.2.7.26A | EPS bearer context status | 798 |
| 8.2.7.27 | Negotiated extended DRX parameters | 798 |
| 8.2.7.28 | T3447 value..... | 799 |