

ETSI TS 124 548 V19.2.0 (2026-03)



TECHNICAL SPECIFICATION

**5G;
Network Resource Management - Service Enabler Architecture
Layer for Verticals (SEAL);
Protocol specification
(3GPP TS 24.548 version 19.2.0 Release 19)**



Reference

RTS/TSGC-0124548vj20

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed, this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our [Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2026.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found at [3GPP to ETSI numbering cross-referencing](#).

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	9
1 Scope	11
2 References	11
3 Definitions of terms and abbreviations.....	12
3.1 Terms.....	12
3.2 Abbreviations	13
4 General description.....	13
5 Functional entities	13
5.1 SEAL network resource management client (SNRM-C)	13
5.2 SEAL network resource management SEAL server (SNRM-S).....	14
6 Network resource management procedures.....	15
6.1 General	15
6.2 On-network procedures	15
6.2.1 General.....	15
6.2.1.1 Authenticated identity in HTTP request.....	15
6.2.1.2 Authenticated identity in CoAP request.....	15
6.2.2 Unicast resource management	15
6.2.2.1 General	15
6.2.2.2 Request for unicast resource at VAL service communication establishment procedure with SIP core.....	16
6.2.2.2.1 VAL server procedure	16
6.2.2.2.2 Server procedure.....	16
6.2.2.3 Request for modification of unicast resources procedure with SIP core.....	17
6.2.2.3.1 VAL server procedure	17
6.2.2.3.2 Server procedure.....	17
6.2.2.4 Network resource adaptation procedure with SIP core	18
6.2.2.4.1 VAL server procedure	18
6.2.2.4.2 Server procedure.....	19
6.2.3 Multicast resource management	19
6.2.3.1 General	19
6.2.3.2 Use of pre-established MBMS bearers procedure.....	19
6.2.3.2.1 VAL server procedure	19
6.2.3.2.2 SNRM server HTTP procedure	20
6.2.3.2.3 SNRM client HTTP procedure	22
6.2.3.2.4 SNRM server CoAP procedure	22
6.2.3.2.5 SNRM client CoAP procedure	24
6.2.3.3 MBMS bearer announcement over MBMS bearer procedure.....	24
6.2.3.3.1 General	24
6.2.3.3.2 SNRM server SIP and HTTP procedures	24
6.2.3.3.3 SNRM client SIP and HTTP procedures	26
6.2.3.3.4 SNRM Server CoAP procedures	27
6.2.3.3.5 SNRM Client CoAP procedures.....	28
6.2.3.4 MBMS bearer quality detection procedure	29
6.2.3.4.1 SNRM client SIP and HTTP procedures	29
6.2.3.4.2 SNRM server SIP and HTTP procedure.....	30
6.2.3.4.3 SNRM client CoAP procedure	31
6.2.3.4.4 SNRM server CoAP procedure	31
6.2.3.5 Service continuity in MBMS scenarios.....	32
6.2.3.5.1 SNRM client procedures	32

6.2.3.5.2	SNRM server HTTP procedure	32
6.2.3.5.3	SNRM server CoAP procedure	33
6.2.3.6	MBMS suspension notification procedure	34
6.2.3.6.1	SNRM client HTTP procedure	34
6.2.3.6.2	SNRM server HTTP procedure	34
6.2.3.6.3	SNRM client CoAP procedure	35
6.2.3.6.4	SNRM server CoAP procedure	35
6.2.3.7	MBMS bearer event notification procedure	36
6.2.3.7.1	SNRM server procedure	36
6.2.3.8	Switching between MBMS bearer and unicast bearer procedure	36
6.2.3.8.1	SNRM client HTTP and CoAP procedure	36
6.2.3.8.2	SNRM server HTTP and CoAP procedure	36
6.2.3.9	Use of dynamic MBMS bearers procedure	36
6.2.3.9.1	VAL server procedure	36
6.2.3.9.2	SNRM server HTTP and CoAP procedures	36
6.2.3.9.3	SNRM client HTTP and CoAP procedures	37
6.2.3.10	MBS session creation and MBS session announcement procedure	37
6.2.3.10.1	General	37
6.2.3.10.2	SNRM server SIP and HTTP procedures	37
6.2.3.10.3	SNRM client SIP and HTTP procedures	39
6.2.3.10.4	SNRM server CoAP procedure	41
6.2.3.10.5	SNRM client CoAP procedure	42
6.2.3.10.6	Generate MBS session announcement message in XML	43
6.2.3.10.7	VAL server procedure	43
6.2.3.11	MBS listening status report procedure	44
6.2.3.11.1	Generate MBS listening status reporting message in XML	44
6.2.3.11.2	SNRM server SIP and HTTP procedures	44
6.2.3.11.3	SNRM client SIP and HTTP procedures	45
6.2.3.11.4	SNRM server CoAP procedure	46
6.2.3.11.5	SNRM client CoAP procedure	46
6.2.3.12	MBS UE session join notification procedure	47
6.2.3.12.1	SNRM server SIP and HTTP procedures	47
6.2.3.12.2	SNRM client SIP and HTTP procedures	48
6.2.3.13	Application coordinated UE-to-UE communication requirements management procedure	49
6.2.3.13.1	General	49
6.2.3.13.2	Application coordinated connectivity initiation procedure	49
6.2.3.13.3	Application coordinated connectivity notification procedure	50
6.2.3.13.4	Application connectivity context fetch procedure	51
6.2.3.13.5	Mobile meta service connectivity procedure	52
6.2.3.14	VAL service group media transmissions over 5G MBS sessions procedure	55
6.2.3.15	Application level control signalling over 5G MBS sessions procedure	55
6.2.3.16	Service continuity between 5G MBS delivery and unicast delivery procedure	55
6.2.3.17	VAL service inter-system switching between 5G and LTE procedure	55
6.2.4	Network assisted UE-to-UE communications resource management	56
6.2.4.1	General	56
6.2.4.2	Network assisted QoS management initiation	56
6.2.4.2.1	SNRM client HTTP procedure	56
6.2.4.2.2	SNRM server HTTP procedure	57
6.2.4.2.3	SNRM client CoAP procedure	57
6.2.4.2.4	SNRM server CoAP procedure	58
6.2.4.3	Network assisted QoS management provisioning	58
6.2.4.3.1	SNRM client HTTP procedure	58
6.2.4.3.2	SNRM server HTTP procedure	58
6.2.4.3.3	SNRM client CoAP procedure	59
6.2.4.3.4	SNRM server CoAP procedure	59
6.2.6	Satellite S&F events information	60
6.2.6.1	General	60
6.2.6.2	S&F event subscription procedure	60
6.2.6.2.1	SNRM client HTTP procedure	60
6.2.6.2.2	SNRM server HTTP procedure	60
6.2.6.2.3	SNRM client CoAP procedure	61
6.2.6.2.4	SNRM server CoAP procedure	61

6.2.6.3	S&F event reporting subscription notification procedure	62
6.2.6.3.1	SNRM client HTTP procedure	62
6.2.6.3.2	SNRM server HTTP procedure	62
6.2.6.3.3	SNRM client CoAP procedure	62
6.2.6.3.4	SNRM server CoAP procedure	63
6.2.6.4	S&F event reporting unsubscription procedure.....	63
6.2.6.4.1	SNRM server HTTP procedure	63
6.2.6.4.2	SNRM client HTTP procedure.....	63
6.2.6.4.3	SNRM server CoAP procedure	64
6.2.6.4.4	SNRM client CoAP procedure	64
6.2.6.5	On-demand S&F event reporting procedure	64
6.2.6.5.1	SNRM client HTTP procedure.....	64
6.2.6.5.2	SNRM server HTTP procedure.....	65
6.2.6.5.3	SNRM client CoAP procedure	65
6.2.6.5.4	SNRM server CoAP procedure	65
6.2.6.6	S&F event configuration procedure	66
6.2.6.6.1	SNRM server HTTP procedure.....	66
6.2.6.6.2	SNRM client HTTP procedure.....	66
6.2.6.6.3	SNRM server CoAP procedure	66
6.2.6.6.4	SNRM client CoAP procedure	67
6.3	Off-network procedures	67
7	Coding	67
7.1	General	67
7.2	Application unique ID	67
7.3	Structure	67
7.3.1	VALInfo document.....	67
7.3.2	UnicastInfo document.....	67
7.3.3	MBMSInfo document.....	68
7.3.4	NetworkQoSManagementInfo document	70
7.3.5	Application communication requirements info document	70
7.3.6	SEAL MBS Usage Info document.....	72
7.3.7	SEAL application satellite S&F events Info document	74
7.4	XML schema	75
7.4.1	General.....	75
7.4.2	XML schema for application/vnd.3gpp.seal-info+xml	75
7.4.3	XML schema for application/vnd.3gpp.seal-unicast-info+xml	75
7.4.4	XML schema for application/vnd.3gpp.seal-mbms-usage-info+xml.....	76
7.4.5	XML schema for application/vnd.3gpp.seal-network-QoS-management-info+xml.....	78
7.4.6	XML schema for application/vnd.3gpp.seal-app-comm-requirements-info+xml.....	79
7.4.7	XML schema for application/vnd.3gpp.seal-mbs-usage-info+xml.....	83
7.4.8	XML schema for application/vnd.3gpp.seal-store-forward-events-info+xml.....	85
7.5	Data semantics.....	87
7.5.1	VALInfo document.....	87
7.5.2	UnicastInfo document.....	87
7.5.3	MBMSInfo document.....	88
7.5.4	NetworkQoSManagementInfo document	90
7.5.5	ApplicationCommunicationRequirementsInfo document.....	91
7.5.6	SEALMBSUsageInfo document.....	93
7.5.7	SEALSatelliteS&FEventsInfo document.....	94
7.6	MIME types.....	96
7.7	IANA registration template	96
7.7.1	IANA registration template for VALInfo	97
7.7.2	IANA registration template for UnicastInfo	98
7.7.3	IANA registration template for MBMSInfo	100
7.7.4	IANA registration template for NetworkQoSManagementInfo.....	101
7.7.5	IANA registration template for ApplicationCommunicationRequirementsInfo	103
7.7.6	IANA registration template for SEALMBSUsageInfo	104
7.7.7	IANA registration template for SEALSatelliteS&FEventsInfo.....	106
Annex A (normative): CoAP resource representation and encoding	108	
A.1 General	108	

A.2	Resource representation and APIs for QoS session	108
A.2.1	SU_QoSSessionManagement API	108
A.2.1.1	API URI	108
A.2.1.2	Resources	108
A.2.1.2.1	Overview	108
A.2.1.2.2	Resource: QoS Sessions	109
A.2.1.2.2.1	Description	109
A.2.1.2.2.2	Resource Definition	109
A.2.1.2.2.3	Resource Standard Methods	109
A.2.1.2.3	Resource: Individual QoS Session	111
A.2.1.2.3.1	Description	111
A.2.1.2.3.2	Resource Definition	111
A.2.1.2.3.3	Resource Standard Methods	111
A.2.1.2.4	Resource: Individual QoS Session Participant	113
A.2.1.2.4.1	Description	113
A.2.1.2.4.2	Resource Definition	113
A.2.1.2.4.3	Resource Standard Methods	113
A.2.1.3	Data Model	114
A.2.1.3.1	General	114
A.2.1.3.2	Structured data types	115
A.2.1.3.2.1	Introduction	115
A.2.1.3.2.2	Type: QoSSession	115
A.2.1.3.2.3	Type: SessionParticipant	115
A.2.1.3.2.4	Type: ParticipantState	116
A.2.1.4	Error Handling	116
A.2.1.5	CDDL Specification	116
A.2.1.5.1	Introduction	116
A.2.1.5.2	CDDL document	116
A.2.1.6	Media Types	117
A.2.1.7	Void	117
A.2.1.8	Void	117
A.3	Resource representation and APIs for MBMS resource configuration and monitoring	117
A.3.1	SU_MbmsResourceManagement API provided by SNRM-C	117
A.3.1.1	API URI	117
A.3.1.2	Resources	118
A.3.1.2.1	Overview	118
A.3.1.2.2	Resource: MBMS Resource Configuration	119
A.3.1.2.2.1	Description	119
A.3.1.2.2.2	Resource Definition	119
A.3.1.2.2.3	Resource Standard Methods	119
A.3.1.2.3	Resource: MBMS Resource State	120
A.3.1.2.3.1	Description	120
A.3.1.2.3.2	Resource Definition	120
A.3.1.2.3.3	Resource Standard Methods	120
A.3.1.3	Data Model	121
A.3.1.3.1	General	121
A.3.1.3.2	Structured data types	122
A.3.1.3.2.1	Type: MbmsResourceConfig	122
A.3.1.3.2.2	Type: MbmsResourceMonitoringConfig	122
A.3.1.3.2.3	Type: MbmsResourceState	123
A.3.1.4	Error Handling	123
A.3.1.5	CDDL Specification	123
A.3.1.5.1	Introduction	123
A.3.1.5.2	CDDL document	123
A.3.1.6	Media Types	124
A.3.1.7	Void	124
A.3.1.8	Void	124
A.3.2	SU_MbsResourceManagement API provided by SNRM-C	124
A.3.2.1	API URI	124
A.3.2.2	Resources	125
A.3.2.2.1	Overview	125

A.3.2.2.2	Resource: MBS resource configuration	126
A.3.2.2.2.1	Description	126
A.3.2.2.2.2	Resource Definition	126
A.3.2.2.2.3	Resource Standard Methods	126
A.3.2.2.3	Resource: MBS resource state.....	127
A.3.2.2.3.1	Description	127
A.3.2.2.3.2	Resource Definition.....	127
A.3.2.2.3.3	Resource Standard Methods	127
A.3.2.3	Data Model	128
A.3.2.3.1	General	128
A.3.2.3.2	Structured data types	129
A.3.2.3.2.1	Type: MbsResourceConfig.....	129
A.3.2.3.2.2	Type: MbsResourceMonitoringConfig.....	129
A.3.2.3.2.3	Type: MbsResourceState	130
A.3.2.3.2.4	Type: MbsSessionId	130
A.3.2.3.3	Simple data types and enumerations	130
A.3.2.3.3.1	Enumeration: DeliveryMode	130
A.3.2.4	Error Handling	130
A.3.2.5	CDDL Specification	130
A.3.2.5.1	Introduction	130
A.3.2.5.2	CDDL document	131
A.3.2.6	Media Types	132
A.3A	Resource representation and APIs for mobile meta service	132
A.3A.1	SU_MobileMetaService API.....	132
A.3A.1.1	API URI	132
A.3A.1.2	Resources	132
A.3A.1.3	Custom operations without associated resources	132
A.3A.1.3.1	Overview	132
A.3A.1.3.2	Operations for mobile meta service connectivity	132
A.3A.1.3.2.1	POST	132
A.3A.1.4	Data Model	133
A.3A.1.4.1	General	133
A.3B	Resource representation and APIs for store and forward	133
A.3B.1	SU_StoreForward API provided by SNRM-C	133
A.3B.1.1	API URI	133
A.3B.1.2	Resources	134
A.3B.1.2.1	Overview	134
A.3B.1.2.2	Resource: Notification	134
A.3B.1.2.2.1	Description	134
A.3B.1.2.2.2	Resource Definition	134
A.3B.1.2.2.3	Resource Standard Methods	135
A.3B.1.2.3	Resource: Report.....	135
A.3B.1.2.3.1	Description	135
A.3B.1.2.3.2	Resource Definition	135
A.3B.1.2.3.3	Resource Standard Methods	135
A.3B.1.3	Data Model	135
A.3B.1.3.1	General	135
A.3B.1.3.2	Structured data types	136
A.3B.1.3.2.1	Type: Notification	136
A.3B.1.3.2.2	Type: Report.....	136
A.3B.2	SU_StoreForward API provided by SNRM-S	136
A.3B.2.1	API URI	136
A.3B.2.2	Resources	137
A.3B.2.2.1	Overview	137
A.3B.2.2.2	Resource: Subscription	137
A.3B.2.2.2.1	Description	137
A.3B.2.2.2.2	Resource Definition	137
A.3B.2.2.2.3	Resource Standard Methods	138
A.3B.2.2.3	Resource: Report.....	138
A.3B.2.2.3.1	Description	138

A.3B.2.2.3.2	Resource Definition	138
A.3B.2.2.3.3	Resource Standard Methods	138
A.3B.2.3	Data Model	139
A.3B.2.3.1	General	139
A.3B.2.3.2	Structured data types	139
A.3B.2.3.2.1	Type: Subscription.....	139
A.3B.2.3.2.2	Type: Report.....	139
A.3B.3	Data types applicable to multiple resource representations for store and forward events	139
A.3B.3.1	Referenced simple data types.....	139
A.3B.3.2	Common structured data types.....	140
A.3B.3.2.1	Type: StoreForwardEvents.....	140
A.3B.3.2.2	Type: SatelliteInfo.....	140
A.3B.3.3	Common enumerations	140
A.3B.3.3.1	Enumeration: UeStoreForwardMode	140
A.3B.3.3.2	Enumeration: StoreForwardTrigger	141
A.3B.3.3.3	Enumeration: UEType	141
A.3B.3.3.4	Enumeration: RatType	141
A.4	Media types	141
A.4.1	General	141
A.4.2	Media type structure and definition.....	141
A.4.3	Media type registration template for application/vnd.3gpp.seal-location-info+cbor.....	142
Annex B (informative): Change history		144
History		147

Sample Document

get full document from standards.iteh.ai

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

In the present document, modal verbs have the following meanings:

shall indicates a mandatory requirement to do something

shall not indicates an interdiction (prohibition) to do something

The constructions "shall" and "shall not" are confined to the context of normative provisions, and do not appear in Technical Reports.

The constructions "must" and "must not" are not used as substitutes for "shall" and "shall not". Their use is avoided insofar as possible, and they are not used in a normative context except in a direct citation from an external, referenced, non-3GPP document, or so as to maintain continuity of style when extending or modifying the provisions of such a referenced document.

should indicates a recommendation to do something

should not indicates a recommendation not to do something

may indicates permission to do something

need not indicates permission not to do something

The construction "may not" is ambiguous and is not used in normative elements. The unambiguous constructions "might not" or "shall not" are used instead, depending upon the meaning intended.

can indicates that something is possible

cannot indicates that something is impossible

The constructions "can" and "cannot" are not substitutes for "may" and "need not".

will indicates that something is certain or expected to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document

will not indicates that something is certain or expected not to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document

might indicates a likelihood that something will happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

might not indicates a likelihood that something will not happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

In addition:

is (or any other verb in the indicative mood) indicates a statement of fact

is not (or any other negative verb in the indicative mood) indicates a statement of fact

The constructions "is" and "is not" do not indicate requirements.

Sample Document

get full document from standards.iteh.ai

1 Scope

The present document specifies the protocol aspects for the network resource management capability of SEAL to support vertical applications (e.g. V2X) over the 3GPP system.

The present document is applicable to the user equipment (UE) supporting the network resource management client functionality as described in 3GPP TS 23.434 [2], to the application server supporting the network resource management server functionality as described in 3GPP TS 23.434 [2] and to the application server supporting the vertical application server (VAL server) functionality as defined in the specific vertical application service (VAL service) specifications.

NOTE: The specification of the VAL server for a specific VAL service is out of scope of present document.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document in the same Release as the present document.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 23.434: "Service Enabler Architecture Layer for Verticals (SEAL); Functional architecture and information flows".
- [3] 3GPP TS 23.003: "Numbering, addressing and identification".
- [4] 3GPP TS 23.203: "Policy and charging control architecture".
- [5] 3GPP TS 24.008: "Mobile Radio Interface Layer 3 specification; Core Network Protocols; Stage 3".
- [6] 3GPP TS 24.229: "IP multimedia call control protocol based on Session Initiation Protocol (SIP) and Session Description Protocol (SDP); Stage 3".
- [7] 3GPP TS 24.486: "Vehicle-to-Everything (V2X) Application Enabler (VAE) layer; Protocol aspects; Stage 3".
- [8] 3GPP TS 24.545: "Location Management - Service Enabler Architecture Layer for Verticals (SEAL); Protocol specification".
- [9] 3GPP TS 24.547: "Identity management - Service Enabler Architecture Layer for Verticals (SEAL); Protocol specification".
- [10] 3GPP TS 26.346: "Multimedia Broadcast/Multicast Service (MBMS); Protocols and codecs".
- [11] 3GPP TS 29.061: "Interworking between the Public Land Mobile Network (PLMN) supporting packet based services and Packet Data Networks (PDN)".
- [12] 3GPP TS 29.214: "Policy and Charging Control over Rx reference point".
- [13] 3GPP TS 29.468: "Group Communication System Enablers for LTE (GCSE_LTE); MB2 reference point; Stage 3".
- [14] 3GPP TS 29.514: "5G System; Policy Authorization Service; Stage 3".

- [15] Void.
- [16] IETF RFC 3095: "RObust Header Compression (ROHC): Framework and four profiles: RTP, UDP, ESP, and uncompressed".
- [17] IETF RFC 3428: "Session Initiation Protocol (SIP) Extension for Instant Messaging".
- [18] IETF RFC 3841: "Caller Preferences for the Session Initiation Protocol (SIP)".
- [19] IETF RFC 4825: "The Extensible Markup Language (XML) Configuration Access Protocol (XCAP)".
- [20] IETF RFC 5795: "The Robust Header Compression (ROHC) Framework".
- [21] Void
- [21A] IETF RFC 6838: "Media Type Specifications and Registration Procedures".
- [22] IETF RFC 9110: "HTTP Semantics".
- [23] IETF RFC 7252: "The Constrained Application Protocol (CoAP)".
- [24] IETF RFC 7959: "Block-Wise Transfers in the Constrained Application Protocol (CoAP)".
- [25] IETF RFC 7641: "Observing Resources in the Constrained Application Protocol (CoAP)".
- [26] IETF RFC 8323: "CoAP (Constrained Application Protocol) over TCP, TLS, and WebSockets".
- [27] IETF RFC 8949: "Concise Binary Object Representation (CBOR)".
- [28] Void
- [29] IETF RFC 9177: "Constrained Application Protocol (CoAP) Block- Wise Transfer Options Supporting Robust Transmission".
- [30] IETF RFC 8610: "Concise Data Definition Language (CDDL): A Notational Convention to Express Concise Binary Object Representation (CBOR) and JSON Data Structures".
- [31] 3GPP TS 24.546: "Configuration management - Service Enabler Architecture Layer for Verticals (SEAL); Protocol specification".
- [32] OMA OMA-TS-XDM_Core-V2_1-20120403-A: "XML Document Management (XDM) Specification".
- [33] 3GPP TS 23.246: "Multimedia Broadcast/Multicast Service (MBMS); Architecture and functional description".
- [34] 3GPP TS 23.247: "Architectural enhancements for 5G multicast-broadcast services; Stage 2".
- [35] 3GPP TS 26.517: "5G Multicast-Broadcast User Services; Protocols and Formats".
- [36] Open API: "OpenAPI Specification Version 3.0.0", <https://spec.openapis.org/oas/v3.0.0>.
- [37] 3GPP TS 36.331: "Evolved Universal Terrestrial Radio Access (E-UTRA); Radio Resource Control (RRC) protocol specification".

3 Definitions of terms and abbreviations

3.1 Terms

For the purposes of the present document, the terms given in 3GPP TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [1].

MBMS bearer: The MBMS bearer (and its LTE variant, the eMBMS bearer) is the point-to-multipoint transport service for delivering the same multimedia content (data) simultaneously to multiple UEs. Definition derived from 3GPP TS 23.246 [33]. The present document makes no distinction between MBMS bearer and eMBMS bearer.

SEAL network resource management client: An entity that provides the client side functionalities corresponding to the SEAL network resource management service.

SEAL network resource management server: An entity that provides the server side functionalities corresponding to the SEAL network resource management service.

For the purposes of the present document, the following terms and definitions given in 3GPP TS 23.434 [2] apply:

SEAL client
SEAL server
SEAL service
VAL server
VAL service
VAL user
Vertical
Vertical application

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in 3GPP TR 21.905 [1].

BM-SC	Broadcast-Multicast Service Centre
CoAP	Constrained Application Protocol
eMBMS	Evolved MBMS
MBS	Multicast/Broadcast Services
MBMS	Multimedia Broadcast/Multicast Service
PCF	Policy Control Function
PCF	Policy Control Function
SEAL	Service Enabler Architecture Layer for verticals
SNRM-C	SEAL Network Resource Management Client
SNRM-S	SEAL Network Resource Management Server
VAL	Vertical Application Layer

4 General description

Network resource management is a SEAL service that provides the network resource management related capabilities (e.g. unicast and multicast network resources) to one or more vertical applications. The present document enables a SEAL network resource management client (SNRM-C) and a VAL server that communicate with a SEAL network resource management server (SNRM-S).

The SNRM-S obtains and controls multicast resources from the underlying 3GPP network system via the BM-SC and controls unicast resources from the underlying 3GPP network system via the PCRF/PCF.

5 Functional entities

5.1 SEAL network resource management client (SNRM-C)

The SNRM-C functional entity acts as the application client for network resource management related transactions.

To be compliant with the HTTP procedures in the present document the SNRM-C:

- a) shall support the role of XCAP client as specified in IETF RFC 4825 [19];

- b) shall support the role of XDMC as specified in OMA OMA-TS-XDM_Core-V2_1 [32]; and
- c) shall support the multicast resource management procedures in clause 6.2.3.

To be compliant with the CoAP procedures in the present document the SNRM-C:

- a)- shall support the role of CoAP client as specified in IETF RFC 7252 [23];
- b)- shall support the capability to observe resources as specified in IETF RFC 7641 [25];
- c)- shall support the block-wise transfer as specified in IETF RFC 7959 [24];
- d)- may support the robust block transfer as specified in IETF RFC 9177 [29];
- e)- should support CoAP over TCP and WebSocket as specified in IETF RFC 8323 [26];
- f)- shall support CBOR encoding as specified in IETF RFC 8949 [27];
- g)- shall support the procedures in clause 6.2.3; and
- h)- shall support the procedure in clause 6.2.4.

NOTE 1: The security mechanism to be supported for the CoAP procedures is described in 3GPP TS 24.547 [9].

NOTE 2: Support for TCP for the CoAP procedures is required if the client connects over the network which blocks or impedes the use of UDP, e.g. when NATs are present in the communication path.

NOTE 3: The CoAP protocol supports mechanism for reliable message exchange over UDP. Use of TCP can also be beneficial if reliable transport is required for other reasons, e.g. better observability of resources. Usage of CoAP over TCP is an implementation choice.

NOTE 4: Support for the robust block transfer mechanism for the CoAP procedures is beneficial in environments where packet loss is highly asymmetrical and where performance optimization of block transfers is required.

5.2 SEAL network resource management SEAL server (SNRM-S)

The SNRM-S is a functional entity used to provide resource management of 3GPP system network resources (e.g. unicast, multicast) to one or more vertical applications.

To be compliant with the HTTP procedures in the present document the SNRM-S shall:

- a) shall support the role of XCAP server as specified in IETF RFC 4825 [19];
- b) shall support the role of XDMS as specified in OMA OMA-TS-XDM_Core-V2_1 [32];
- c) shall support the unicast resource management procedures in clause 6.2.2; and
- d) shall support the multicast resource management procedures in clause 6.2.3.

To be compliant with the CoAP procedures in the present document the SNRM-C:

- a)- shall support the role of CoAP server as specified in IETF RFC 7252 [23];
- b)- shall support the capability to observe resources as specified in IETF RFC 7641 [25];
- c)- shall support the block-wise transfer as specified in IETF RFC 7959 [24];
- d)- shall support the robust block transfer as specified in IETF RFC 9177 [29];
- e)- shall support CoAP over TCP and WebSocket as specified in IETF RFC 8323 [26];
- f)- shall support CBOR encoding as specified in IETF RFC 8949 [27];
- g)- shall support the procedure in clause 6.2.3; and