

ETSI TS 133 128 V19.6.0 (2026-04)



TECHNICAL SPECIFICATION

**Digital cellular telecommunications system (Phase 2+) (GSM);
Universal Mobile Telecommunications System (UMTS);
LTE;
5G;
Security;
Protocol and procedures for Lawful Interception (LI);
Stage 3
(3GPP TS 33.128 version 19.6.0 Release 19)**



Reference

RTS/TSGS-0333128vj60

Keywords

5G,GSM,LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed, this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our [Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2026.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found at [3GPP to ETSI numbering cross-referencing](#).

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	22
Introduction	22
1 Scope	23
2 References	23
3 Definitions, symbols and abbreviations	29
3.1 Definitions	29
3.2 Symbols.....	29
3.3 Abbreviations	29
4 General	30
4.1 Introduction	30
4.2 Basic principles for internal interfaces	32
4.3 Basic principles for external handover interfaces.....	33
4.4 Service scoping	34
4.4.1 General.....	34
4.4.2 CSP service type	34
4.4.3 Delivery type	34
4.4.4 Location Reporting	35
4.4.5 LALS Triggering	35
4.4.6 Roaming Interception	35
4.5 LI product filtering	35
4.5.1 General.....	35
4.5.2 Traffic policies.....	35
5 Transport and Communications Protocol.....	36
5.1 General	36
5.2 Protocols for LI_X1 and LI_T interfaces	36
5.2.1 General usage of ETSI TS 103 221-1	36
5.2.2 Usage for realising LI_X1	36
5.2.2.1 General	36
5.2.2.2 Provisioning of the MDF2 and MDF3	37
5.2.2.2.1 General	37
5.2.2.2.2 ActivateTask message for the MDF2 and MDF3.....	37
5.2.2.2.3 MediationDetails for the MDF2 and MDF3	38
5.2.2.3 Provisioning of the POIs and TFs	38
5.2.2.3.1 General	38
5.2.2.3.2 ActivateTask message for the POIs and TFs.....	38
5.2.3 Usage for realising LI_X1 (management)	38
5.2.4 Service scoping	38
5.2.5 Usage for realising LI_T2 and LI_T3	39
5.2.6 Void	40
5.2.7 Usage for realising LI_XEM1	40
5.2.8 Traffic policies.....	41
5.3 Protocols for LI_X2 and LI_X3	41
5.3.1 General usage of ETSI TS 103 221-2	41
5.3.2 Usage for realising LI_X2	42
5.3.3 Usage for realising LI_X3	43
5.3.4 Service scoping	43
5.3.5 Usage for realising LI_X2_LA	43
5.4 Protocols for LI_H11	44
5.4.1 General.....	44

5.4.2	Service scoping	44
5.4.3	Location acquisition.....	45
5.4.4	Traffic policies.....	45
5.5	Protocols for LI_HI2 and LI_HI3.....	45
5.5.1	General.....	45
5.5.2	Usage for realising LI_HI2	46
5.5.3	Usage for realising LI_HI3	47
5.5.4	Service scoping	48
5.5.5	IRI Target Identifiers	48
5.6	Protocols for LI_HI4	48
5.6.1	General.....	48
5.6.2	Usage for realising LI_HI4	48
5.7	Protocols for LI_HIQR.....	48
5.7.1	General.....	48
5.7.2	Usage for realising LI_HIQR.....	49
5.7.2.1	Request structure.....	49
5.7.2.2	Request parameters	49
5.7.2.3	Response structure	51
5.8	Protocols for LI_XQR.....	52
5.8.1	General.....	52
5.8.2	Identity association requests	52
5.8.3	Ongoing identity association requests.....	52
5.8.4	Latest association requests.....	53
5.9	Protocols for LI_XER	53
5.10	Protocols for LI_ST interface.....	54
5.10.1	Overview	54
5.10.2	Storage	54
5.10.3	Retrieval.....	54
5.10.4	Removal.....	54
5.11	Protocols for LI_HILA.....	54
5.11.1	General.....	54
5.11.2	Usage for realising LI_HILA.....	55
5.11.2.1	Request structure.....	55
5.11.2.2	Request parameters	55
5.11.2.3	Response structure	56
5.12	Protocols for LI_XLA	58
5.12.1	General.....	58
5.12.2	Usage for realising LI_XLA	58
6	Network Layer Based Interception.....	59
6.1	Introduction	59
6.2	5G.....	60
6.2.1	General.....	60
6.2.2	LI at AMF.....	60
6.2.2.1	Provisioning over LI_X1.....	60
6.2.2.1.1	General	60
6.2.2.2	Generation of xIRI over LI_X2.....	61
6.2.2.2.1	General	61
6.2.2.2.1A	Simple data types for AMF	61
6.2.2.2.2	Registration	61
6.2.2.2.3	Deregistration	64
6.2.2.2.4	Location update	65
6.2.2.2.5	Start of interception with registered UE	67
6.2.2.2.6	AMF unsuccessful procedure	68
6.2.2.2.7	AMF identifier association/deassociation.....	69
6.2.2.2.8	Positioning info transfer	71
6.2.2.2.9	Handovers.....	72
6.2.2.2.10	UE Configuration Update	74
6.2.2.2.11	Trace.....	75
6.2.2.2.11.1	General.....	75
6.2.2.2.11.2	AMF RAN trace report.....	76
6.2.2.2.12	UE policy transfer.....	77

6.2.2.2.13	Service Accept.....	77
6.2.2.2.14	UE context update	78
6.2.2.2A	Definitions for AMF message Types	79
6.2.2.2A.1	Type: InitialRANUEContextSetup.....	79
6.2.2.2A.2	Type: PDUSessionSetupRequestItem	80
6.2.2.2A.3	Type: UERadioCapability	81
6.2.2.2A.4	Type: UERadioCapabilityForPaging.....	81
6.2.2.2A.5	Type: NRV2XServicesAuthorization.....	81
6.2.2.2A.6	Type: LTEV2XServicesAuthorization	82
6.2.2.2A.7	Type: TargetNSSAIInfo	82
6.2.2.2A.8	Type: FiveGProSeAuthorizationIndication	82
6.2.2.2A.9	Enumeration: IABAuthorizedIndicator	83
6.2.2.2A.10	Enumeration: V2XUEAuthorizationIndicator.....	83
6.2.2.2A.11	Enumeration: FiveGProSeAuthorizationIndicator	83
6.2.2.2A.12	Type: UEDifferentiationInfo	83
6.2.2.2A.13	Enumeration: MobileIABAuthorizedIndicator.....	84
6.2.2.2A.14	Type: NASTransportInitialInformation.....	84
6.2.2.2A.15	Type: RANUEContextModification.....	85
6.2.2.2A.16	Type: RANDownlinkNASTransport.....	86
6.2.2.3	Generation of IRI over LI_HI2	87
6.2.2.4	Identity privacy	88
6.2.2A	Identifier Reporting for AMF	88
6.2.2A.1	Activation of reporting over LI_XEM1	88
6.2.2A.2	Generation of records over LI_XER	88
6.2.2A.2.2	Association Events	89
6.2.2A.2.3	Transmission to the ICF	90
6.2.2A.2.4	Additional location reporting.....	90
6.2.2A.2.4.1	Type: AdditionalCGIs.....	90
6.2.2A.2.4.2	Type: AdditionalNCGI	90
6.2.3	LI for SMF/UPF	91
6.2.3.1	Provisioning over LI_X1	91
6.2.3.1.1	General	91
6.2.3.1.2	Provisioning of the IRI-POI, IRI-TF and CC-TF in the SMF	91
6.2.3.1.3	Provisioning of the MDF2.....	92
6.2.3.1.4	Provisioning of the MDF3.....	92
6.2.3.2	Generation of xIRI at IRI-POI in SMF over LI_X2.....	93
6.2.3.2.1	General	93
6.2.3.2.2	PDU session establishment.....	93
6.2.3.2.3	PDU session modification	99
6.2.3.2.4	PDU session release	102
6.2.3.2.5	Start of interception with an established PDU session	104
6.2.3.2.6	SMF unsuccessful procedure.....	106
6.2.3.2.7	MA PDU sessions.....	110
6.2.3.2.8	PDU to MA PDU session modification.....	123
6.2.3.2.9	ProSe remote UE report.....	124
6.2.3.2.10	Start of interception with connected ProSe remote UE	125
6.2.3.3	Triggering of the IRI-POI/CC-POI in the UPF from IRI-TF/CC-TF in the SMF	126
6.2.3.3.1	LI_T2/LI_T3 interface specifics.....	126
6.2.3.3.2	CC interception with multi-homed PDU session.....	127
6.2.3.3.3	CC Interception only at PDU Session Anchor UPFs.....	127
6.2.3.4	Additional details for triggering the IRI-POI in the UPF.....	127
6.2.3.5	Generation of xIRI at UPF over LI_X2.....	128
6.2.3.5.1	Packet data header reporting.....	128
6.2.3.5.2	Fragmentation.....	128
6.2.3.5.3	Packet Data Header Report (PDHR)	128
6.2.3.5.4	Packet Data Summary Report (PDSR)	128
6.2.3.6	Generation of xCC at CC-POI in the UPF over LI_X3.....	128
6.2.3.7	Generation of IRI over LI_HI2	129
6.2.3.8	Generation of CC over LI_HI3	130
6.2.3.9	Packet header information reporting	130
6.2.3.9.1	General	130
6.2.3.9.2	Provisioning details	131

6.2.3.9.3	PDHeaderReport record (deprecated).....	131
6.2.3.9.4	PDSummaryReport record (deprecated).....	132
6.2.3.9.5	Usage of the Internet Protocol Packet Reporting record	134
6.2.3.10	Sharing LI state information over LI_ST	134
6.2.3.10.1	Overview	134
6.2.3.10.2	Storing LI state	134
6.2.3.10.3	Retrieving LI state	135
6.2.3.10.4	Removing LI state	136
6.2.4	LI at UDM for 5G.....	136
6.2.4.1	General description	136
6.2.5	LI at SMSF	136
6.2.5.1	Provisioning over LI_X1.....	136
6.2.5.2	Generation of xIRI over LI_X2.....	137
6.2.5.3	SMS Message.....	137
6.2.5.4	Generation of IRI over LI_HI2	140
6.2.6	LI support at NRF.....	141
6.3	4G.....	141
6.3.1	General.....	141
6.3.2	LI at MME	141
6.3.2.1	Provisioning over LI_X1.....	141
6.3.2.2	Generation of xIRI over LI_X2.....	142
6.3.2.2.1	General	142
6.3.2.2.2	MME identifier association/deassociation.....	143
6.3.2.2.3	Attach	144
6.3.2.2.4	Detach.....	145
6.3.2.2.5	Tracking Area/EPS Location update	147
6.3.2.2.6	Start of interception with EPS attached UE.....	148
6.3.2.2.7	MME unsuccessful procedure	149
6.3.2.2.8	Positioning info transfer	150
6.3.2.2.9	Handovers.....	151
6.3.2.2.10	Trace.....	153
6.3.2.2.10.1	General.....	153
6.3.2.2.10.2	MME RAN trace report	153
6.3.2.2.11	Service Accept.....	154
6.3.2.2A	Definitions for MME message Types	154
6.3.2.2A.1	Simple data types.....	154
6.3.2.2A.2	Type: EPSHandoverType	155
6.3.2.2A.3	Type: ERABContextList	155
6.3.2.2A.4	Type: ERABContext	155
6.3.2.2A.5	Type: ERABReleaseList.....	155
6.3.2.2A.6	Type: ERABError.....	156
6.3.2.2A.7	Type: EPSRANCause.....	156
6.3.2.2A.8	Type: EPSHandoverRestrictionList.....	156
6.3.2.2A.9	Type: EPSCSGInfo	156
6.3.2.2A.10	Type: EPSProSeAuthorization	157
6.3.2.2A.11	Type: EPSSubscriptionBasedUEDifferentiationIndication	157
6.3.2.2A.12	Type: S1Information	157
6.3.2.2A.13	Type: MMEServedGUMMEIList	158
6.3.2.2A.14	Type: MMEServedGUMMEI.....	158
6.3.2.2A.15	Type: EPSNASTransportInitialInformation	158
6.3.2.2A.16	Type: BBFTunnelInformation	159
6.3.2.2A.17	Type: LTENTNTAIInformation.....	159
6.3.2.2A.18	Type: EPSRANUEContext.....	160
6.3.2.2A.19	Enumeration: EPSCSFallbackIndicator.....	161
6.3.2.3	Generation of IRI over LI_HI2	161
6.3.2.3.1	General	161
6.3.2.3.2	Option A.....	161
6.3.2.3.3	Option B and Option C.....	162
6.3.3	LI at SGW/PGW and ePDG	162
6.3.3.0	General.....	162
6.3.3.1	Provisioning over LI_X1.....	162
6.3.3.1.1	General	162

6.3.3.1.2	Non-CUPS Architecture	164
6.3.3.1.3	CUPS Architecture	164
6.3.3.1.4	Provisioning of the MDF2	164
6.3.3.1.5	Provisioning of the MDF3	164
6.3.3.2	Generation of xIRI over LI_X2	165
6.3.3.2.1	General	165
6.3.3.2.2	PDN Connection Establishment or PDU Session Establishment in interworked EPS/5GS	165
6.3.3.2.3	PDN Connection Modification or PDU Session Modification in interworked EPS/5GS or inter-system handover	170
6.3.3.2.4	PDN Connection Release or PDU Session Release in interworked EPS/5GS	174
6.3.3.2.5	Start of Interception with Already Established PDN Connection or SMF Start of Interception with Already Established PDU Session in interworked EPS/5GS	176
6.3.3.2.6	MA PDU Session Establishment message in interworked EPS/5GS	178
6.3.3.2.7	MA PDU Session Modification message in interworked EPS/5GS	179
6.3.3.2.8	MA PDU Session Release message in interworked EPS/5GS	179
6.3.3.2.9	SMF Start of Interception with Already Established MA PDU Session in interworked EPS/5GS	180
6.3.3.2A	Triggering of the CC-POI from CC-TF over LI_T3	181
6.3.3.3	Generation of xCC at CC-POI in the SGW/PGW and ePDG over LI_X3	182
6.3.3.3.1	Non-CUPS architecture	182
6.3.3.3.2	CUPS architecture	182
6.3.3.4	Generation of IRI over LI_HI2	182
6.3.3.4.1	General	182
6.3.3.4.2	Option A	182
6.3.3.4.3	Option B and C	183
6.3.3.5	Generation of CC over LI_HI3	183
6.4	3G	183
7	Service Layer Based Interception	184
7.1	Introduction	184
7.2	Central Subscriber Management	184
7.2.1	General description	184
7.2.2	LI at UDM	184
7.2.2.1	General description	184
7.2.2.2	Provisioning over LI_X1	184
7.2.2.3	Generation of xIRI over LI_X2	185
7.2.2.3.1	General description	185
7.2.2.3.2	Serving system	185
7.2.2.3.3	Subscriber record change	186
7.2.2.3.4	Cancel location	188
7.2.2.3.5	Location information request	189
7.2.2.3.6	Location information result	189
7.2.2.3.7	UE information response	189
7.2.2.3.8	UE Authentication response	190
7.2.2.3.9	Start of Interception with UE registered at the UDM	191
7.2.2.3.10	Proximity services reporting at the UDM	191
7.2.2.3.10.1	General	191
7.2.2.3.10.2	ProSe target identifier deconcealment	192
7.2.2.3.10.3	ProSe target authentication	192
7.2.2.4	Generation of IRI over LI_HI2	192
7.2.3	LI at HSS	193
7.2.3.1	General	193
7.2.3.2	Provisioning over LI_X1	193
7.2.3.3	Generation of xIRI over LI_X2	194
7.2.3.3.1	General description	194
7.2.3.3.2	Serving system	194
7.2.3.3.3	Start of Interception with target registered at the HSS	194
7.2.3.3.4	Subscriber record change at the HSS	195
7.2.3.4	Generation of IRI over LI_HI2	195
7.2.4	LI at the IMS-HSS	196
7.2.4.1	General	196
7.2.4.2	Provisioning over LI_X1	196

7.2.4.3	Generation of xIRI over LI_X2.....	197
7.2.4.3.1	General description.....	197
7.2.4.3.2	Serving system	197
7.2.4.3.3	Start of Interception with target registered at the IMS-HSS	197
7.2.4.3.4	Subscriber record change at the IMS-HSS	198
7.2.4.4	Generation of IRI over LI_HI2	199
7.3	Location.....	199
7.3.1	Lawful Access Location Services (LALS)	199
7.3.1.1	General description	199
7.3.1.2	Provisioning over LI_X1	200
7.3.1.2.1	Target positioning service	200
7.3.1.2.2	Triggered location service.....	201
7.3.1.3	Triggering over LI_T2	201
7.3.1.4	Generation of xIRI over LI_X2.....	202
7.3.1.5	Generation of IRI over LI_HI2	202
7.3.2	Cell database information reporting.....	203
7.3.2.1	General description	203
7.3.2.2	Delivery of cell site information over LI_HI2	203
7.3.3	Use of the Location structure.....	204
7.3.3.1	General description	204
7.3.3.2	Location structure data types.....	205
7.3.3.2.1	Simple data types for location	205
7.3.3.2.2	Type: Location.....	207
7.3.3.2.3	Type: LocationInfo	208
7.3.3.2.4	Type: UserLocation	209
7.3.3.2.5	Type: EUTRALocation	210
7.3.3.2.6	Type: NRLocation	211
7.3.3.2.7	Type: N3GALocation.....	213
7.3.3.2.8	Type: UTRALocation.....	213
7.3.3.2.9	Type: GERALocation.....	214
7.3.3.2.10	Type: GeographicArea	215
7.3.3.2.11	Type: Point	216
7.3.3.2.12	Type: GeographicalCoordinates	216
7.3.3.2.13	Type: PointUncertaintyCircle	216
7.3.3.2.14	Type: PointUncertaintyEllipse	217
7.3.3.2.15	Type: UncertaintyEllipse	217
7.3.3.2.16	Type: Polygon	217
7.3.3.2.17	Type: PointAltitude	218
7.3.3.2.18	Type: PointAltitudeUncertainty	218
7.3.3.2.19	Type: EllipsoidArc	218
7.3.3.2.20	Enumeration: RATType	219
7.3.3.2.21	Type: CellInformation	220
7.3.3.2.22	Type: RANCGI	220
7.3.3.2.23	Type: TAI.....	220
7.3.3.2.24	Type: ECGI	221
7.3.3.2.25	Type: GlobalRANNodeID.....	221
7.3.3.2.26	Type: ANNodeID	221
7.3.3.2.27	Type: NgENBID.....	222
7.3.3.2.28	Type: NCGI.....	222
7.3.3.2.29	Type: IPAddr.....	222
7.3.3.2.30	Type: TNAPID	223
7.3.3.2.31	Type: TWAPID	223
7.3.3.2.32	Enumeration: W5GBANLineType.....	223
7.3.3.2.33	Enumeration: TransportProtocol	224
7.3.3.2.34	Type: PLMNID	224
7.3.3.2.35	Type: ENbID	224
7.3.3.2.36	Type: PositioningInfo.....	224
7.3.3.2.37	Type: LocationData	225
7.3.3.2.38	Type: RawMLPResponse	226
7.3.3.2.39	Type: VelocityEstimate	227
7.3.3.2.40	Type: CivicAddress	227
7.3.3.2.41	Type: PositioningMethodAndUsage	229

7.3.3.2.42	Type: GNSSPositioningMethodAndUsage	229
7.3.3.2.43	Type: HorizontalVelocity	229
7.3.3.2.44	Type: HorizontalWithVerticalVelocity	230
7.3.3.2.45	Type: HorizontalVelocityWithUncertainty	230
7.3.3.2.46	Type: HorizontalWithVerticalVelocityAndUncertainty	230
7.3.3.2.47	Type: LocationPresenceReport	231
7.3.3.2.48	Type: AMFEventArea	232
7.3.3.2.49	Type: RMInfo	232
7.3.3.2.50	Type: CMInfo	232
7.3.3.2.51	Enumeration: AccuracyFulfilmentIndicator	232
7.3.3.2.52	Enumeration: PositioningMethod	233
7.3.3.2.53	Enumeration: PositioningMode	233
7.3.3.2.54	Enumeration: GNSSID	233
7.3.3.2.55	Enumeration: Usage	234
7.3.3.2.56	Enumeration: VerticalDirection	234
7.3.3.2.57	Type: IMSLocation	234
7.3.3.2.58	Type: PANIHeaderInfo	235
7.3.3.2.59	Type: SIPGeolocationHeaderInfo	235
7.3.3.2.60	Type: SIPLocationInfo	236
7.3.3.2.61	Type: SIPCNIHeaderInfo	236
7.3.3.2.62	Type: PresenceInfo	236
7.3.3.2.63	Type: LADNInfo	237
7.3.3.2.64	Enumeration: AMFEventType	237
7.3.3.2.65	Enumeration: AccessType	238
7.3.3.2.66	Enumeration: UEReachability	238
7.3.3.2.67	Enumeration: RMState	238
7.3.3.2.68	Enumeration: CMState	238
7.3.3.2.69	Enumeration: PresenceState	239
7.3.3.2.70	Type: FourGPositioningInfo	239
7.3.3.2.71	Type: FourGLocationInfo	240
7.3.3.2.72	Type: CGI	240
7.3.3.2.73	Type: SAI	241
7.3.3.2.74	Type: ESMLCCellInfo	241
7.3.3.2.75	Type: GERANPositioningInfo	241
7.3.3.2.76	Type: UTRANPositioningInfo	242
7.3.3.2.77	Type: EPSLocationInformation	242
7.3.3.2.78	Type: MMELocationInformation	243
7.3.3.2.79	Type: SGSNLocationInformation	243
7.3.3.2.80	Type: UserCSGInformation	244
7.3.3.2.81	Type: LAI	244
7.3.3.2.82	Type: RAI	245
7.3.3.2.83	Enumeration: CSGAccessMode	245
7.3.3.2.84	Enumeration: CSGMembershipIndication	245
7.3.3.2.85	Type: CoarseLocation	245
7.3.3.3	Reference datum	246
7.3.4	Separated location reporting	246
7.3.4.1	General description	246
7.3.5	Location acquisition	247
7.3.5.1	General description	247
7.3.5.2	Acquisition request over LI_HILA	247
7.3.5.3	Acquisition request over LI_XLA	247
7.3.5.4	Location acquisition procedure at the LARF	247
7.3.5.4.1	General description	247
7.3.5.4.2	Location acquisition procedure at the LARF in case of EPC	248
7.3.5.4.3	Location acquisition procedure at the LARF in case of 5GC	248
7.3.5.5	Location acquisition delivery via the LI_HILA	249
7.3.5.5.1	Location acquisition response over LI_XLA	249
7.3.5.5.2	Location acquisition response over LI_HILA	249
7.3.5.6	Location acquisition delivery via the LI_HI2	249
7.3.5.6.1	Provisioning of the MDF2	249
7.3.5.6.2	LI_X2_LA delivery	250
7.3.5.6.3	LI_HI2 delivery	250

7.3.6	Location Only Reporting	250
7.3.6.1	General Information	250
7.3.6.2	Provisioning Information	250
7.3.6.3	Generation of Location Only xIRI	251
7.3.6.3.1	General	251
7.3.6.3.2	Location Only xIRI in 5GS	251
7.3.6.3.3	Location Only xIRI in EPS	251
7.3.6.4	Generation of Location Only IRI	251
7.4	Messaging	252
7.4.1	Introduction	252
7.4.2	LI at the MMS Proxy-Relay	252
7.4.2.1	Provisioning over LI_X1	252
7.4.2.2	Generation of xIRI over LI_X2	253
7.4.2.3	Generation of xCC over LI_X3	253
7.4.2.4	MMS Record Generation Cases	253
7.4.3	MMS Records	253
7.4.3.1	MMSSend	253
7.4.3.2	MMSSendByNonLocalTarget	257
7.4.3.2A	MMSConvertedFromEmail	261
7.4.3.3	MMSNotification	261
7.4.3.4	MMSSendToNonLocalTarget	262
7.4.3.4A	MMSConvertedToEmail	265
7.4.3.5	MMSNotificationResponse	266
7.4.3.6	MMSRetrieval	267
7.4.3.7	MMSDeliveryAck	270
7.4.3.8	MMSForward	271
7.4.3.9	MMSDeleteFromRelay	274
7.4.3.10	MMSMBoxStore	275
7.4.3.11	MMSMBoxUpload	275
7.4.3.12	MMSMBoxDelete	276
7.4.3.13	MMSDeliveryReport	277
7.4.3.14	MMSDeliveryReportNonLocalTarget	277
7.4.3.15	MMSReadReport	278
7.4.3.16	MMSReadReportNonLocalTarget	279
7.4.3.17	MMSCancel	280
7.4.3.18	MMSMBoxViewRequest	281
7.4.3.19	MMSMBoxViewResponse	281
7.4.3.20	MMBoxDescription	282
7.4.3.21	MMS Content	285
7.4.4	IRI and CC Generation	285
7.4.4.1	Generation of IRI over LI_HI2	285
7.4.4.2	Generation of CC over LI_HI3	285
7.4.5	Redaction of unauthorised information from encapsulated messages	285
7.4.5.1	General	285
7.4.5.2	SMS Redaction	285
7.4.5.2.1	3GPP SMS Redaction	285
7.4.5.2.2	3GPP2 SMS Redaction	286
7.5	PTC service	286
7.5.1	Introduction	286
7.5.1.0	General	286
7.5.1.1	Provisioning over LI_X1	286
7.5.1.2	Generating xIRI over LI_X2	287
7.5.1.3	Generation of xCC over LI_X3	287
7.5.2	IRI events	287
7.5.2.1	PTC registration	287
7.5.2.2	PTC session initiation	287
7.5.2.3	PTC session abandon attempt	288
7.5.2.4	PTC session start	289
7.5.2.5	PTC session end	289
7.5.2.6	PTC start of interception	290
7.5.2.7	PTC preestablished session	291
7.5.2.8	PTC instant personal alert	292

7.5.2.9	PTC party join	292
7.5.2.10	PTC party drop	293
7.5.2.11	PTC party hold	293
7.5.2.12	PTC media modification	294
7.5.2.13	PTC group advertisement	294
7.5.2.14	PTC floor control	295
7.5.2.15	PTC target presence	296
7.5.2.16	PTC participant presence	297
7.5.2.17	PTC list management	297
7.5.2.18	PTC access policy	298
7.5.3	IRI and CC Generation	299
7.5.3.1	Generation of IRI over LI_HI2	299
7.5.3.2	Generation of CC over LI_HI3	300
7.6	Identifier Association Reporting	300
7.6.1	General	300
7.6.2	ICF	300
7.6.2.1	General	300
7.6.2.2	ICF receipt of records over LI_XER	300
7.6.2.3	ICF Query and Response over LI_XQR	300
7.6.2.4	ICF Identifier Association Event Handling	300
7.6.3	IQF	302
7.6.3.1	General	302
7.6.3.2	IQF Query and Response over LI_HIQR	302
7.6.3.3	IQF Query and Response over LI_XQR	302
7.7	LI at NEF	302
7.7.1	Provisioning over LI_X1	302
7.7.1.1	General	302
7.7.1.2	Provisioning of the IRI-POI and CC-POI in NEF	302
7.7.2	LI for NIDD using NEF	303
7.7.2.1	Generation of xIRI at IRI-POI in NEF over LI_X2	303
7.7.2.1.1	General	303
7.7.2.1.2	PDU session establishment	303
7.7.2.1.3	PDU session modification	304
7.7.2.1.4	PDU session release	305
7.7.2.1.5	Unsuccessful procedure	305
7.7.2.1.6	Start of interception with established PDU session	306
7.7.2.2	Generation of xCC at CC-POI in NEF over LI_X3	306
7.7.2.3	Generation of IRI over LI_HI2	306
7.7.2.4	Generation of CC over LI_HI3	307
7.7.3	LI for device triggering	307
7.7.3.1	Generation of xIRI LI_X2 at IRI-POI in NEF over LI_X2	307
7.7.3.1.1	General	307
7.7.3.1.2	Device trigger	307
7.7.3.1.3	Device trigger replace	308
7.7.3.1.4	Device trigger cancellation	308
7.7.3.1.5	Device trigger report notification	309
7.7.3.2	Generation of IRI over LI_HI2	309
7.7.4	LI for MSISDN-less MO SMS	310
7.7.4.1	Generation of xIRI LI_X2 at IRI-POI in NEF over LI_X2	310
7.7.4.1.1	General	310
7.7.4.1.2	MSISDN-less MO SMS	310
7.7.4.2	Generation of IRI over LI_HI2	310
7.7.5	LI for parameter provisioning	311
7.7.5.1	Generation of xIRI LI_X2 at IRI-POI in NEF over LI_X2	311
7.7.5.1.1	General	311
7.7.5.1.2	Expected UE behaviour update	311
7.7.5.2	Generation of IRI over LI_HI2	311
7.7.6	LI for AF session with QoS	312
7.7.6.1	Generation of xIRI at IRI-POI in NEF over LI_X2	312
7.7.6.1.1	General	312
7.7.6.1.2	AF session with QoS provision	312
7.7.6.1.3	AF session with QoS notification	313

7.7.6.2	Generation of IRI over LI_HI2	313
7.7.7	LI for 5G LAN parameter provisioning.....	313
7.7.7.1	Generation of xIRI at IRI-POI in NEF	313
7.7.7.1.1	General	313
7.7.7.1.2	5G VN group creation	313
7.7.7.1.3	5G VN group update	314
7.7.7.1.4	5G VN group deletion	314
7.7.7.1.5	5G VN group query	315
7.7.7.2	Generation of IRI over LI_HI2	315
7.8	LI at SCEF.....	315
7.8.1	Provisioning over LI_X1	315
7.8.1.1	General	315
7.8.1.2	Provisioning of the IRI-POI and CC-POI in the SCEF/IWK-SCEF	316
7.8.2	LI for NIDD using SCEF.....	316
7.8.2.1	Generation of xIRI at IRI-POI in SCEF over LI_X2	316
7.8.2.1.1	General	316
7.8.2.1.2	SCEF PDN connection establishment	316
7.8.2.1.3	PDN connection update	317
7.8.2.1.4	PDN connection release.....	318
7.8.2.1.5	Unsuccessful procedure.....	319
7.8.2.1.6	Start of interception with established PDN connection	320
7.8.2.2	Generation of xCC at CC-POI in SCEF over LI_X3	320
7.8.2.3	Generation of IRI over LI_HI2	321
7.8.2.4	Generation of CC over LI_HI3	321
7.8.3	LI for device triggering.....	321
7.8.3.1	Generation of xIRI LI_X2 at IRI-POI in SCEF over LI_X2.....	321
7.8.3.1.1	General	321
7.8.3.1.2	Device trigger.....	321
7.8.3.1.3	Device trigger replacement.....	322
7.8.3.1.4	Device trigger cancellation	322
7.8.3.1.5	Device trigger report notification	323
7.8.3.2	Generation of IRI over LI_HI2	323
7.8.4	LI for MSISDN-less MO SMS	324
7.8.4.1	Generation of xIRI LI_X2 at IRI-POI in SCEF over LI_X2.....	324
7.8.4.1.1	General	324
7.8.4.1.2	MSISDN-less MO SMS	324
7.8.4.2	Generation of IRI over LI_HI2	324
7.8.5	LI for parameter provisioning.....	325
7.8.5.1	Generation of xIRI LI_X2 at IRI-POI in SCEF over LI_X2.....	325
7.8.5.1.1	General	325
7.8.5.1.2	Communication pattern update.....	325
7.8.5.2	Generation of IRI over LI_HI2	326
7.8.6	LI for AS session with QoS	326
7.8.6.1	Generation of xIRI at IRI-POI in SCEF over LI_X2	326
7.8.6.1.1	General	326
7.8.6.1.2	AS session with QoS provision	327
7.8.6.1.3	AS session with QoS notification	327
7.8.6.2	Generation of IRI over LI_HI2	328
7.9	LI for services encrypted by CSP-provided keys	328
7.9.1	LI for general AKMA-based service	328
7.9.1.1	General	328
7.9.1.2	Provisioning over LI_X1	328
7.9.1.2.1	General	328
7.9.1.2.2	Provisioning of the IRI-POI and IRI-TF in AAnF	329
7.9.1.2.3	Triggering of the IRI-POI in AF.....	329
7.9.1.3	Generation of xIRI at IRI-POI in AAnF over LI_X2.....	329
7.9.1.3.1	General	329
7.9.1.3.2	AAnF Anchor Key Register	329
7.9.1.3.3	AAnF AKMA application key get.....	330
7.9.1.3.4	AAnF Start of intercept with established AKMA key material.....	330
7.9.1.3.5	AAnF AKMA context removal	330
7.9.1.4	Generation of xIRI at IRI-POI in AF over LI_X2.....	331

7.9.1.4.1	General	331
7.9.1.4.2	AF Application key refresh	331
7.9.1.4.3	AF Start of intercept with established AKMA application key	331
7.9.1.4.4	AF Auxiliary security parameter establishment	331
7.9.1.4.5	AF Application key removal	332
7.9.1.5	Generation of IRI over LI_HI2	332
7.10	LI in VPLMN for IMS-based services with home-routed roaming	332
7.10.1	Background	332
7.10.2	Backward compatibility	333
7.10.3	HR LI Phase 1	333
7.10.3.1	Overview	333
7.10.3.2	Provisioning over LI_X1	334
7.10.3.2.1	General	334
7.10.3.2.2	Provisioning of BBIFF-C and BBIFF	334
7.10.3.2.3	Provisioning of LMISF-IRI	334
7.10.3.3	Generation of xIRI over LI_X2_LITE	335
7.10.3.3.1	General	335
7.10.3.3.2	N9HR LI	335
7.10.3.3.3	S8HR LI	337
7.10.3.4	LMISF-IRI handling of xIRIs received over LI_X2_LITE	339
7.10.3.4.1	Handling of xIRIs	339
7.10.3.4.2	Handling of the stored record	339
7.10.3.5	Triggering of BBIFF-U from BBIFF-C over LI_T3	339
7.10.3.5.1	General	339
7.10.3.5.2	N9HR LI	340
7.10.3.5.3	S8HR LI	340
7.10.3.6	Generation of xCC over LI_X3_LITE_S	341
7.10.3.6.1	BBIFF-U	341
7.10.3.6.2	BBIFF	342
7.10.3.6.3	X3 PDU format	342
7.10.3.7	LMISF-IRI handling of xCC received over LI_X3_LITE_S	342
7.10.4	HR LI Phase 2	342
7.10.4.1	Overview	342
7.10.4.1.1	General	342
7.10.4.1.2	Service Scoping for Phase 2 of HR LI	343
7.10.4.2	Provisioning over LI_X1	343
7.10.4.2.1	General	343
7.10.4.2.2	Provisioning of LMISF-IRI	344
7.10.4.2.3	Provisioning of the MDF2	344
7.10.4.2.4	Provisioning of the MDF3	344
7.10.4.3	Generation of xIRI over LI_X2	344
7.10.4.3.1	General concepts	344
7.10.4.3.2	Target match	345
7.10.4.3.2.1	General	345
7.10.4.3.2.2	LMISF-IRI provisioned for voice	345
7.10.4.3.2.3	LMISF-IRI provisioned for messaging	346
7.10.4.3.3	xIRIs	346
7.10.4.4	Triggering of BBIFF-C from LMISF over LI_T1	347
7.10.4.4.1	General	347
7.10.4.4.2	N9HR LI	347
7.10.4.4.3	S8HR LI	348
7.10.4.5	Triggering of BBIFF-U from BBIFF-C over LI_T3	348
7.10.4.5.1	General	348
7.10.4.5.2	N9HR LI	349
7.10.4.5.3	S8HR LI	349
7.10.4.6	Generation of xCC over LI_X3_LITE_M	350
7.10.4.7	Generation of xCC over LI_X3	350
7.10.4.8	Correlation identifier	350
7.10.4.9	Generation of IRI over LI_HI2	351
7.10.4.10	Generation of CC over LI_HI3	351
7.11	STIR/SHAKEN and RCD/eCNAM	351
7.11.1	Provisioning over LI_X1	351

7.11.1.1	General	351
7.11.1.2	Provisioning of the IRI-POI in the IMS network functions	352
7.11.1.3	Provisioning of the MDF2	352
7.11.2	Generation of xIRI at IRI-POI in the IMS Network Functions over LI_X2	353
7.11.2.1	General	353
7.11.2.2	Signature generation.....	353
7.11.2.3	Signature validation	356
7.11.2.4	IMS Network Function that interacts with signing AS	357
7.11.2.5	IMS Network Function that interacts with the verification AS	358
7.11.3	Generation of IRI over LI_HI2	358
7.12	LI for IMS based services	359
7.12.1	General.....	359
7.12.2	Overview	359
7.12.2.1	General	359
7.12.2.2	Target type and target identifiers	359
7.12.2.3	Roaming considerations	360
7.12.2.4	Service specific aspects.....	360
7.12.2.4.1	General	360
7.12.2.4.2	LI for normal sessions	360
7.12.2.4.3	LI for redirected sessions.....	360
7.12.2.4.4	LI for conferencing.....	360
7.12.2.4.5	STIR/SHAKEN	361
7.12.2.4.6	RCD/eCNAM.....	361
7.12.2.4.7	Called party address translation.....	361
7.12.2.4.8	IMS Data Channel	361
7.12.2.5	Service scoping	361
7.12.2.5.1	General	361
7.12.2.5.2	LI for voice.....	362
7.12.2.5.3	LI for Messaging	362
7.12.2.5.4	LI for voice-mail.....	362
7.12.2.5.5	LI for RCS.....	363
7.12.2.5.6	LI for PTC service.....	363
7.12.2.5.7	LALS triggering	363
7.12.2.5.8	LI for IMS Data Channel.....	363
7.12.2.6	Location reporting.....	363
7.12.2.7	Deployment considerations.....	363
7.12.2.8	Identifying the intercepted IMS-based communications.....	364
7.12.2.8.1	General concepts	364
7.12.2.8.2	Target match.....	364
7.12.2.8.2.1	General.....	364
7.12.2.8.2.2	Session based IMS services	364
7.12.2.8.2.3	Session independent IMS services.....	365
7.12.2.9	Handling of correlation information.....	366
7.12.2.9.1	Correlation of IRI and CC	366
7.12.2.9.2	Correlation for sessions with called party address translation.....	367
7.12.3	Provisioning over LI_X1	367
7.12.3.1	General	367
7.12.3.2	Provisioning of IRI-POI.....	367
7.12.3.2.1	Session-based IMS services.....	367
7.12.3.2.2	Session-independent IMS services	368
7.12.3.3	Provisioning of CC-TF.....	368
7.12.3.4	Provisioning of the MDF2	369
7.12.3.5	Provisioning of the MDF3	369
7.12.4	Generation of xIRIs over LI_X2.....	369
7.12.4.1	IRI-POIs in IMS signalling functions	369
7.12.4.1.1	General	369
7.12.4.1.2	IRI-POI in P-CSCF.....	370
7.12.4.1.2.1	Session-based IMS communications	370
7.12.4.1.2.2	Session-independent IMS communications	370
7.12.4.1.3	IRI-POI in S-CSCF.....	370
7.12.4.1.3.1	Session-based IMS communications	370
7.12.4.1.3.2	Session-independent IMS communications	371