

ETSI TS 136 101 V16.25.0 (2025-10)



TECHNICAL SPECIFICATION

**LTE;
Evolved Universal Terrestrial Radio Access (E-UTRA);
User Equipment (UE) radio transmission and reception
(3GPP TS 36.101 version 16.25.0 Release 16)**

[ETSI TS 136 101 V16.25.0 \(2025-10\)](https://standards.iteh.ai/catalog/standards/etsi/5d8c48bc-d564-4ef4-b7a3-8a07b3412ebe/etsi-ts-136-101-v16-25-0-2025-10)

<https://standards.iteh.ai/catalog/standards/etsi/5d8c48bc-d564-4ef4-b7a3-8a07b3412ebe/etsi-ts-136-101-v16-25-0-2025-10>



Reference

RTS/TSGR-0436101vgp0

Keywords

LTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed, this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our [Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2025.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by the ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables. (2025-10)

The cross reference between 3GPP and ETSI identities can be found at [3GPP to ETSI numbering cross-referencing](#).

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	32
1 Scope	34
2 References	34
3 Definitions, symbols and abbreviations	34
3.1 Definitions	34
3.2 Symbols.....	36
3.3 Abbreviations	39
4 General	41
4.1 Relationship between minimum requirements and test requirements	41
4.2 Applicability of minimum requirements	41
4.3 Void.....	41
4.3A Applicability of minimum requirements (CA, UL-MIMO, ProSe, Dual Connectivity, UE category 0, UE category M1, UE category M2, UE category 1bis, UE category NB1 and NB2, V2X Communication, MBMS UE)	41
4.4 RF requirements in later releases	43
5 Operating bands and channel arrangement.....	43
5.1 General	43
5.2 Void.....	43
5.3 Void.....	43
5.4 Void.....	43
5.5 Operating bands.....	43
5.5A Operating bands for CA	45
5.5B Operating bands for UL-MIMO	59
5.5C Operating bands for Dual Connectivity	59
5.5D Operating bands for ProSe.....	60
5.5E Operating bands for UE category 0, UE category M1 and M2 and UE category 1bis	61
5.5F Operating bands for category NB1 and NB2.....	61
5.5G Operating bands for V2X Communication.....	62
5.6 Channel bandwidth.....	63
5.6.1 Channel bandwidths per operating band.....	64
5.6A Channel bandwidth for CA.....	65
5.6A.1 Channel bandwidths per operating band for CA.....	67
5.6B Channel bandwidth for UL-MIMO	159
5.6B.1 Void	159
5.6C Channel bandwidth for Dual Connectivity.....	159
5.6C.1 Void	159
5.6D Channel bandwidth for ProSe.....	159
5.6D.1 Channel bandwidths per operating band for ProSe.....	159
5.6F Channel bandwidth for category NB1 and NB2.....	160
5.6G Channel bandwidth for V2X Communication.....	161
5.6G.1 Channel bandwidths per operating band for V2X Communication	161
5.7 Channel arrangement.....	163
5.7.1 Channel spacing.....	163
5.7.1A Channel spacing for CA.....	163
5.7.1F Channel spacing for category NB1 and NB2.....	164
5.7.2 Channel raster	164
5.7.2A Channel raster for CA.....	164
5.7.2F Channel raster for category NB1 and NB2.....	164
5.7.3 Carrier frequency and EARFCN.....	164
5.7.3F Carrier frequency and EARFCN for category NB1 and NB2.....	166

5.7.4	TX–RX frequency separation	166
5.7.4A	TX–RX frequency separation for CA	167
5.7.4E	TX–RX frequency separation for category M1 and M2	167
5.7.4F	TX–RX frequency separation for category NB1 and NB2	167
6	Transmitter characteristics	167
6.1	General	167
6.2	Transmit power	168
6.2.1	Void	168
6.2.2	UE maximum output power	168
6.2.2A	UE maximum output power for CA	170
6.2.2B	UE maximum output power for UL-MIMO	173
6.2.2C	Void	175
6.2.2D	UE maximum output power for ProSe	175
6.2.2E	UE maximum output power for Category M1 and M2 UE	175
6.2.2F	UE maximum output power for category NB1 and NB2	176
6.2.2G	UE maximum output power for V2X Communication	177
6.2.3	UE maximum output power for modulation / channel bandwidth	178
6.2.3A	UE Maximum Output power for modulation / channel bandwidth for CA	179
6.2.3B	UE maximum output power for modulation / channel bandwidth for UL-MIMO	183
6.2.3D	UE maximum output power for modulation / channel bandwidth for ProSe	184
6.2.3E	UE maximum output power for modulation / channel bandwidth for category M1 and M2	185
6.2.3F	UE maximum output power for modulation / channel bandwidth for category NB1 and NB2	186
6.2.3G	UE maximum output power for modulation / channel bandwidth for V2X Communication	187
6.2.3G.1	MPR for Power class 3 V2X UE	187
6.2.3G.2	MPR for Power class 2 V2X UE	188
6.2.4	UE maximum output power with additional requirements	189
6.2.4A	UE maximum output power with additional requirements for CA	204
6.2.4A.1	A-MPR for CA_NS_01 for CA_1C	206
6.2.4A.2	A-MPR for CA_NS_02 for CA_1C	206
6.2.4A.3	A-MPR for CA_NS_03 for CA_1C	207
6.2.4A.4	A-MPR for CA_NS_04	208
6.2.4A.5	A-MPR for CA_NS_05 for CA_38C	210
6.2.4A.6	A-MPR for CA_NS_06	211
6.2.4A.7	A-MPR for CA_NS_07	212
6.2.4A.8	A-MPR for CA_NS_08	213
6.2.4A.9	Void	214
6.2.4A.10	A-MPR for CA_NS_10	214
6.2.4B	UE maximum output power with additional requirements for UL-MIMO	217
6.2.4D	UE maximum output power with additional requirements for ProSe	218
6.2.4E	UE maximum output power with additional requirements for category M1 and M2 UE	218
6.2.4F	UE maximum output power with additional requirements for category NB1 and NB2 UE	226
6.2.4G	UE maximum output power with additional requirements for V2X Communication	226
6.2.5	Configured transmitted power	228
6.2.5A	Configured transmitted power for CA	253
6.2.5B	Configured transmitted power for UL-MIMO	257
6.2.5C	Configured transmitted power for Dual Connectivity	257
6.2.5D	Configured transmitted power for ProSe	259
6.2.5F	Configured transmitted Power for category NB1 and NB2	260
6.2.5G	Configured transmitted power for V2X Communication	261
6.3	Output power dynamics	265
6.3.1	(Void)	265
6.3.2	Minimum output power	265
6.3.2.1	Minimum requirement	265
6.3.2A	UE Minimum output power for CA	265
6.3.2A.1	Minimum requirement for CA	265
6.3.2B	UE Minimum output power for UL-MIMO	266
6.3.2B.1	Minimum requirement	266
6.3.2C	Void	266
6.3.2D	UE Minimum output power for ProSe	266
6.3.2F	UE Minimum output power for category NB1 and NB2	266
6.3.2G	UE Minimum output power for V2X Communication	267

6.3.3	Transmit OFF power.....	267
6.3.3.1.	Minimum requirement	267
6.3.3A	UE Transmit OFF power for CA	267
6.3.3A.1	Minimum requirement for CA	268
6.3.3B	UE Transmit OFF power for UL-MIMO	268
6.3.3B.1	Minimum requirement	268
6.3.3D	Transmit OFF power for ProSe.....	268
6.3.3F	Transmit OFF power for category NB1 and NB2.....	269
6.3.3G	Transmit OFF power for V2X Communication.....	269
6.3.4	ON/OFF time mask.....	269
6.3.4.1	General ON/OFF time mask	269
6.3.4.2	PRACH and SRS time mask	271
6.3.4.2.1	PRACH time mask	271
6.3.4.2.2	SRS time mask	271
6.3.4.3	Slot / Sub frame boundary time mask for subframe TTI.....	273
6.3.4.4	PUCCH / PUSCH / SRS time mask for subframe TTI	275
6.3.4.5	Symbol / Subslot boundary time mask for subslot TTI.....	277
6.3.4.6	Subslot PUCCH / subslot PUSCH / SRS time mask for subslot TTI.....	278
6.3.4.7	Symbol / Slot boundary time mask for slot TTI.....	281
6.3.4.8	Slot PUCCH / slot PUSCH / SRS time mask for slot TTI	282
6.3.4.9	Consecutive subslot and slot TTI or consecutive subslot and subframe TTI time mask.....	282
6.3.4.10	Consecutive subframe and subslot TTI or consecutive slot and subslot TTI time mask.....	282
6.3.4.11	Consecutive TTI and slot TTI or consecutive slot TTI and TTI time mask.....	283
6.3.4A	ON/OFF time mask for CA	284
6.3.4B	ON/OFF time mask for UL-MIMO	284
6.3.4D	ON/OFF time mask for ProSe.....	284
6.3.4D.1	General time mask for ProSe	284
6.3.4D.2	PSSS/SSSS time mask	285
6.3.4D.3	PSSS / SSSS / PSBCH time mask.....	286
6.3.4D.4	PSSCH / SRS time mask.....	286
6.3.4F	ON/OFF time mask for category NB1 and NB2.....	286
6.3.4F.1	General ON/OFF time mask	286
6.3.4F.2	NPRACH time mask	287
6.3.4G	ON/OFF time mask for V2X Communication.....	287
6.3.4G.1	PSSS / SSSS / PSBCH time mask.....	288
6.3.5	Power Control.....	288
6.3.5.1	Absolute power tolerance.....	288
6.3.5.1.1	Minimum requirements	288
6.3.5.2	Relative Power tolerance.....	289
6.3.5.2.1	Minimum requirements	289
6.3.5.3	Aggregate power control tolerance	290
6.3.5.3.1	Minimum requirement.....	290
6.3.5A	Power control for CA.....	290
6.3.5A.1	Absolute power tolerance.....	290
6.3.5A.1.1	Minimum requirements	290
6.3.5A.2	Relative power tolerance	291
6.3.5A.2.1	Minimum requirements	291
6.3.5A.3	Aggregate power control tolerance	291
6.3.5A.3.1	Minimum requirements	291
6.3.5B	Power control for UL-MIMO	292
6.3.5D	Power Control for ProSe.....	292
6.3.5D.1	Absolute power tolerance.....	292
6.3.5E	Power control for category M1 and M2.....	292
6.3.5E.1	Absolute power tolerance.....	292
6.3.5E.2	Relative Power tolerance.....	292
6.3.5E.3	Aggregate power control tolerance	293
6.3.5E.3.1	Minimum requirement.....	293
6.3.5F	Power Control for category NB1 and NB2.....	293
6.3.5F.1	Absolute power tolerance.....	294
6.3.5F.2	Relative power tolerance	294
6.3.5F.3	Aggregate power control tolerance for category NB1 and NB2	295
6.3.5F.3.1	Minimum requirement.....	295

6.3.5G	Power Control for V2X Communication	295
6.3.5G.1	Absolute power tolerance	295
6.4	Void	296
6.5	Transmit signal quality	296
6.5.1	Frequency error	296
6.5.1A	Frequency error for CA	296
6.5.1B	Frequency error for UL-MIMO	296
6.5.1D	Frequency error for ProSe	296
6.5.1E	Frequency error for UE category M1 and M2	296
6.5.1F	Frequency error for UE category NB1 and NB2	297
6.5.1G	Frequency error for V2X Communication	297
6.5.2	Transmit modulation quality	297
6.5.2.1	Error Vector Magnitude	298
6.5.2.1.1	Minimum requirement	298
6.5.2.2	Carrier leakage	298
6.5.2.2.1	Minimum requirements	299
6.5.2.3	In-band emissions	299
6.5.2.3.1	Minimum requirements	299
6.5.2.4	EVM equalizer spectrum flatness	300
6.5.2.4.1	Minimum requirements	300
6.5.2A	Transmit modulation quality for CA	301
6.5.2A.1	Error Vector Magnitude	302
6.5.2A.2	Carrier leakage for CA	302
6.5.2A.2.1	Minimum requirements	302
6.5.2A.3	In-band emissions	302
6.5.2A.3.1	Minimum requirement for CA	302
6.5.2B	Transmit modulation quality for UL-MIMO	304
6.5.2B.1	Error Vector Magnitude	304
6.5.2B.2	Carrier leakage	305
6.5.2B.3	In-band emissions	305
6.5.2B.4	EVM equalizer spectrum flatness for UL-MIMO	305
6.5.2D	Transmit modulation quality for ProSe	305
6.5.2D.1	Error Vector Magnitude	305
6.5.2D.2	Carrier leakage	305
6.5.2D.3	In-band emissions	305
6.5.2D.4	EVM equalizer spectrum flatness for ProSe	305
6.5.2E	Transmit modulation quality for category M1 and M2	305
6.5.2E.1	Error Vector Magnitude	305
6.5.2E.2	Carrier leakage	306
6.5.2E.2.1	Minimum requirements	306
6.5.2E.3	In-band emissions	306
6.5.2E.3.1	Minimum requirements	306
6.5.2F	Transmit modulation quality for Category NB1 and NB2	307
6.5.2F.1	Error Vector Magnitude	307
6.5.2F.2	Carrier leakage	307
6.5.2F.3	In-band emissions	307
6.5.2G	Transmit modulation quality for V2X Communication	308
6.5.2G.1	Error Vector Magnitude	308
6.5.2G.2	Carrier leakage	308
6.5.2G.3	In-band emissions	309
6.5.2G.4	EVM equalizer spectrum flatness	309
6.6	Output RF spectrum emissions	309
6.6.1	Occupied bandwidth	309
6.6.1.1	Additional minimum requirement for E-UTRA (network signalled value "NS_29")	310
6.6.1A	Occupied bandwidth for CA	310
6.6.1B	Occupied bandwidth for UL-MIMO	310
6.6.1F	Occupied bandwidth for category NB1 and NB2	310
6.6.1G	Occupied bandwidth for V2X Communication	311
6.6.2	Out of band emission	311
6.6.2.1	Spectrum emission mask	311
6.6.2.1.1	Minimum requirement	311
6.6.2.1A	Spectrum emission mask for CA	312