



TECHNICAL SPECIFICATION

**LTE;
Evolved Universal Terrestrial Radio Access (E-UTRA);
User Equipment (UE) radio transmission and reception
(3GPP TS 36.101 version 17.19.0 Release 17)**

get full document from standards.iteh.ai



ReferenceRTS/TSGR-0436101vhj0

KeywordsLTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed, this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our [Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2026.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by the ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found at [3GPP to ETSI numbering cross-referencing](#).

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	32
1 Scope	34
2 References	34
3 Definitions, symbols and abbreviations	34
3.1 Definitions	34
3.2 Symbols.....	36
3.3 Abbreviations	39
4 General	40
4.1 Relationship between minimum requirements and test requirements	40
4.2 Applicability of minimum requirements	41
4.3 Void.....	41
4.3A Applicability of minimum requirements (CA, UL-MIMO, ProSe, Dual Connectivity, UE category 0, UE category M1, UE category M2, UE category 1bis, UE category NB1 and NB2, V2X Communication, MBMS UE)	41
4.4 RF requirements in later releases	43
5 Operating bands and channel arrangement.....	43
5.1 General	43
5.2 Void.....	43
5.3 Void.....	43
5.4 Void.....	43
5.5 Operating bands.....	43
5.5A Operating bands for CA	45
5.5B Operating bands for UL-MIMO	61
5.5C Operating bands for Dual Connectivity.....	61
5.5D Operating bands for ProSe.....	62
5.5E Operating bands for UE category 0, UE category M1 and M2 and UE category 1bis	63
5.5F Operating bands for category NB1 and NB2.....	63
5.5G Operating bands for V2X Communication.....	64
5.6 Channel bandwidth.....	65
5.6.1 Channel bandwidths per operating band.....	66
5.6A Channel bandwidth for CA.....	67
5.6A.1 Channel bandwidths per operating band for CA.....	69
5.6B Channel bandwidth for UL-MIMO	182
5.6B.1 Void	182
5.6C Channel bandwidth for Dual Connectivity.....	182
5.6C.1 Void	182
5.6D Channel bandwidth for ProSe.....	182
5.6D.1 Channel bandwidths per operating band for ProSe.....	182
5.6F Channel bandwidth for category NB1 and NB2.....	183
5.6G Channel bandwidth for V2X Communication.....	184
5.6G.1 Channel bandwidths per operating band for V2X Communication	184
5.7 Channel arrangement.....	186
5.7.1 Channel spacing.....	186
5.7.1A Channel spacing for CA.....	186
5.7.1F Channel spacing for category NB1 and NB2.....	187
5.7.2 Channel raster	187
5.7.2A Channel raster for CA.....	187
5.7.2F Channel raster for category NB1 and NB2.....	187
5.7.3 Carrier frequency and EARFCN.....	187
5.7.3F Carrier frequency and EARFCN for category NB1 and NB2.....	189

5.7.4	TX–RX frequency separation	189
5.7.4A	TX–RX frequency separation for CA	190
5.7.4E	TX–RX frequency separation for category M1 and M2	190
5.7.4F	TX–RX frequency separation for category NB1 and NB2	190
6	Transmitter characteristics	190
6.1	General	190
6.2	Transmit power	191
6.2.1	Void	191
6.2.2	UE maximum output power	191
6.2.2A	UE maximum output power for CA	193
6.2.2B	UE maximum output power for UL-MIMO	196
6.2.2C	Void	198
6.2.2D	UE maximum output power for ProSe	198
6.2.2E	UE maximum output power for Category M1 and M2 UE	198
6.2.2F	UE maximum output power for category NB1 and NB2	199
6.2.2G	UE maximum output power for V2X Communication	200
6.2.3	UE maximum output power for modulation / channel bandwidth	201
6.2.3A	UE Maximum Output power for modulation / channel bandwidth for CA	202
6.2.3B	UE maximum output power for modulation / channel bandwidth for UL-MIMO	207
6.2.3D	UE maximum output power for modulation / channel bandwidth for ProSe	207
6.2.3E	UE maximum output power for modulation / channel bandwidth for category M1 and M2	208
6.2.3F	UE maximum output power for modulation / channel bandwidth for category NB1 and NB2	210
6.2.3G	UE maximum output power for modulation / channel bandwidth for V2X Communication	210
6.2.3G.1	MPR for Power class 3 V2X UE	210
6.2.3G.2	MPR for Power class 2 V2X UE	211
6.2.4	UE maximum output power with additional requirements	212
6.2.4A	UE maximum output power with additional requirements for CA	228
6.2.4A.1	A-MPR for CA_NS_01 for CA_1C	230
6.2.4A.2	A-MPR for CA_NS_02 for CA_1C	230
6.2.4A.3	A-MPR for CA_NS_03 for CA_1C	231
6.2.4A.4	A-MPR for CA_NS_04	232
6.2.4A.5	A-MPR for CA_NS_05 for CA_38C	234
6.2.4A.6	A-MPR for CA_NS_06	235
6.2.4A.7	A-MPR for CA_NS_07	236
6.2.4A.8	A-MPR for CA_NS_08	237
6.2.4A.9	Void	238
6.2.4A.10	A-MPR for CA_NS_10	238
6.2.4B	UE maximum output power with additional requirements for UL-MIMO	241
6.2.4D	UE maximum output power with additional requirements for ProSe	242
6.2.4E	UE maximum output power with additional requirements for category M1 and M2 UE	242
6.2.4F	UE maximum output power with additional requirements for category NB1 and NB2 UE	252
6.2.4G	UE maximum output power with additional requirements for V2X Communication	252
6.2.5	Configured transmitted power	254
6.2.5A	Configured transmitted power for CA	284
6.2.5B	Configured transmitted power for UL-MIMO	288
6.2.5C	Configured transmitted power for Dual Connectivity	288
6.2.5D	Configured transmitted power for ProSe	290
6.2.5F	Configured transmitted Power for category NB1 and NB2	291
6.2.5G	Configured transmitted power for V2X Communication	293
6.3	Output power dynamics	296
6.3.1	(Void)	296
6.3.2	Minimum output power	296
6.3.2.1	Minimum requirement	296
6.3.2A	UE Minimum output power for CA	297
6.3.2A.1	Minimum requirement for CA	297
6.3.2B	UE Minimum output power for UL-MIMO	297
6.3.2B.1	Minimum requirement	297
6.3.2C	Void	297
6.3.2D	UE Minimum output power for ProSe	298
6.3.2F	UE Minimum output power for category NB1 and NB2	298
6.3.2G	UE Minimum output power for V2X Communication	298

6.3.3	Transmit OFF power.....	298
6.3.3.1.	Minimum requirement	298
6.3.3A	UE Transmit OFF power for CA	299
6.3.3A.1	Minimum requirement for CA	299
6.3.3B	UE Transmit OFF power for UL-MIMO.....	299
6.3.3B.1	Minimum requirement	299
6.3.3D	Transmit OFF power for ProSe.....	300
6.3.3F	Transmit OFF power for category NB1 and NB2.....	300
6.3.3G	Transmit OFF power for V2X Communication.....	300
6.3.4	ON/OFF time mask.....	301
6.3.4.1	General ON/OFF time mask	301
6.3.4.2	PRACH and SRS time mask	302
6.3.4.2.1	PRACH time mask	302
6.3.4.2.2	SRS time mask	303
6.3.4.3	Slot / Sub frame boundary time mask for subframe TTI.....	305
6.3.4.4	PUCCH / PUSCH / SRS time mask for subframe TTI	306
6.3.4.5	Symbol / Subslot boundary time mask for subslot TTI.....	308
6.3.4.6	Subslot PUCCH / subslot PUSCH / SRS time mask for subslot TTI.....	310
6.3.4.7	Symbol / Slot boundary time mask for slot TTI.....	313
6.3.4.8	Slot PUCCH / slot PUSCH / SRS time mask for slot TTI	313
6.3.4.9	Consecutive subslot and slot TTI or consecutive subslot and subframe TTI time mask.....	314
6.3.4.10	Consecutive subframe and subslot TTI or consecutive slot and subslot TTI time mask.....	314
6.3.4.11	Consecutive TTI and slot TTI or consecutive slot TTI and TTI time mask	315
6.3.4A	ON/OFF time mask for CA	315
6.3.4B	ON/OFF time mask for UL-MIMO	315
6.3.4D	ON/OFF time mask for ProSe.....	316
6.3.4D.1	General time mask for ProSe	316
6.3.4D.2	PSSS/SSSS time mask	316
6.3.4D.3	PSSS / SSSS / PSBCH time mask.....	317
6.3.4D.4	PSSCH / SRS time mask.....	318
6.3.4F	ON/OFF time mask for category NB1 and NB2.....	318
6.3.4F.1	General ON/OFF time mask	318
6.3.4F.2	NPRACH time mask	318
6.3.4G	ON/OFF time mask for V2X Communication.....	319
6.3.4G.1	PSSS / SSSS / PSBCH time mask.....	319
6.3.5	Power Control.....	320
6.3.5.1	Absolute power tolerance.....	320
6.3.5.1.1	Minimum requirements	320
6.3.5.2	Relative Power tolerance.....	321
6.3.5.2.1	Minimum requirements	321
6.3.5.3	Aggregate power control tolerance	322
6.3.5.3.1	Minimum requirement.....	322
6.3.5A	Power control for CA.....	322
6.3.5A.1	Absolute power tolerance.....	322
6.3.5A.1.1	Minimum requirements	322
6.3.5A.2	Relative power tolerance	323
6.3.5A.2.1	Minimum requirements	323
6.3.5A.3	Aggregate power control tolerance	323
6.3.5A.3.1	Minimum requirements	323
6.3.5B	Power control for UL-MIMO	324
6.3.5D	Power Control for ProSe.....	324
6.3.5D.1	Absolute power tolerance.....	324
6.3.5E	Power control for category M1 and M2.....	324
6.3.5E.1	Absolute power tolerance.....	324
6.3.5E.2	Relative Power tolerance.....	324
6.3.5E.3	Aggregate power control tolerance	324
6.3.5E.3.1	Minimum requirement.....	325
6.3.5F	Power Control for category NB1 and NB2.....	325
6.3.5F.1	Absolute power tolerance.....	325
6.3.5F.2	Relative power tolerance	326
6.3.5F.3	Aggregate power control tolerance for category NB1 and NB2	326
6.3.5F.3.1	Minimum requirement.....	327

6.3.5G	Power Control for V2X Communication	327
6.3.5G.1	Absolute power tolerance	327
6.4	Void	328
6.5	Transmit signal quality	328
6.5.1	Frequency error	328
6.5.1A	Frequency error for CA	328
6.5.1B	Frequency error for UL-MIMO	328
6.5.1D	Frequency error for ProSe	328
6.5.1E	Frequency error for UE category M1 and M2	328
6.5.1F	Frequency error for UE category NB1 and NB2	329
6.5.1G	Frequency error for V2X Communication	329
6.5.2	Transmit modulation quality	329
6.5.2.1	Error Vector Magnitude	329
6.5.2.1.1	Minimum requirement	330
6.5.2.2	Carrier leakage	330
6.5.2.2.1	Minimum requirements	330
6.5.2.3	In-band emissions	331
6.5.2.3.1	Minimum requirements	331
6.5.2.4	EVM equalizer spectrum flatness	332
6.5.2.4.1	Minimum requirements	332
6.5.2A	Transmit modulation quality for CA	333
6.5.2A.1	Error Vector Magnitude	333
6.5.2A.2	Carrier leakage for CA	334
6.5.2A.2.1	Minimum requirements	334
6.5.2A.3	In-band emissions	334
6.5.2A.3.1	Minimum requirement for CA	334
6.5.2B	Transmit modulation quality for UL-MIMO	336
6.5.2B.1	Error Vector Magnitude	336
6.5.2B.2	Carrier leakage	336
6.5.2B.3	In-band emissions	337
6.5.2B.4	EVM equalizer spectrum flatness for UL-MIMO	337
6.5.2D	Transmit modulation quality for ProSe	337
6.5.2D.1	Error Vector Magnitude	337
6.5.2D.2	Carrier leakage	337
6.5.2D.3	In-band emissions	337
6.5.2D.4	EVM equalizer spectrum flatness for ProSe	337
6.5.2E	Transmit modulation quality for category M1 and M2	337
6.5.2E.1	Error Vector Magnitude	337
6.5.2E.2	Carrier leakage	337
6.5.2E.2.1	Minimum requirements	338
6.5.2E.3	In-band emissions	338
6.5.2E.3.1	Minimum requirements	338
6.5.2F	Transmit modulation quality for Category NB1 and NB2	339
6.5.2F.1	Error Vector Magnitude	339
6.5.2F.2	Carrier leakage	339
6.5.2F.3	In-band emissions	339
6.5.2G	Transmit modulation quality for V2X Communication	340
6.5.2G.1	Error Vector Magnitude	340
6.5.2G.2	Carrier leakage	340
6.5.2G.3	In-band emissions	341
6.5.2G.4	EVM equalizer spectrum flatness	341
6.6	Output RF spectrum emissions	341
6.6.1	Occupied bandwidth	341
6.6.1.1	Additional minimum requirement for E-UTRA (network signalled value "NS_29")	342
6.6.1A	Occupied bandwidth for CA	342
6.6.1B	Occupied bandwidth for UL-MIMO	342
6.6.1F	Occupied bandwidth for category NB1 and NB2	342
6.6.1G	Occupied bandwidth for V2X Communication	343
6.6.2	Out of band emission	343
6.6.2.1	Spectrum emission mask	343
6.6.2.1.1	Minimum requirement	343
6.6.2.1A	Spectrum emission mask for CA	344

6.6.2.2	Additional spectrum emission mask	345
6.6.2.2.1	Minimum requirement (network signalled value "NS_03", "NS_11", "NS_20", and "NS_21")	345
6.6.2.2.2	Minimum requirement (network signalled value "NS_04")	346
6.6.2.2.3	Minimum requirement (network signalled value "NS_06" or "NS_07")	346
6.6.2.2.4	Minimum requirement (network signalled value "NS_33" or "NS_34")	347
6.6.2.2.5	Minimum requirement (network signalled value "NS_27" and "NS_43")	347
6.6.2.2.6	Minimum requirement (network signalled value "NS_28")	348
6.6.2.2.7	Minimum requirement (network signalled value "NS_35")	348
6.6.2.2A	Additional Spectrum Emission Mask for CA	348
6.6.2.2A.1	Minimum requirement (network signalled value "CA_NS_04")	348
6.6.2.2A.2	Minimum requirement CA_66B (network signalled value "CA_NS_09")	349
6.6.2.2A.3	Minimum requirement CA_66C (network signalled value "CA_NS_09")	350
6.6.2.2A.4	Minimum requirement CA_48B and CA_48C (network signalled value "CA_NS_10")	350
6.6.2.3	Adjacent Channel Leakage Ratio	351
6.6.2.3.1	Minimum requirement E-UTRA	351
6.6.2.3.1a	Additional minimum requirement for E-UTRA (network signalled value "NS_29")	352
6.6.2.3.1A	Void	353
6.6.2.3.1Aa	Void	353
6.6.2.3.2	Minimum requirements UTRA	353
6.6.2.3.2A	Minimum requirement UTRA for CA	353
6.6.2.3.3A	Minimum requirements for CA E-UTRA	355
6.6.2.4	Void	356
6.6.2.4.1	Void	356
6.6.2A	Void	356
6.6.2B	Out of band emission for UL-MIMO	356
6.6.2C	Void	356
6.6.2D	Out of band emission for ProSe	357
6.6.2F	Out of band emission for category NB1 and NB2	357
6.6.2F.1	Spectrum emission mask	357
6.6.2F.2	Additional Spectrum Emission Mask for Category NB1 and NB2	357
6.6.2F.2.1	Minimum requirement (network signalled value "NS_02")	357
6.6.2F.2.2	Minimum requirement (network signalled value "NS_03")	358
6.6.2F.3	Adjacent Channel Leakage Ratio for category NB1 and NB2	358
6.6.2G	Out of band emission for V2X Communication	358
6.6.3	Spurious emissions	359
6.6.3.1	Minimum requirements	359
6.6.3.1A	Minimum requirements for CA	360
6.6.3.2	Spurious emission band UE co-existence	361
6.6.3.2A	Spurious emission band UE co-existence for CA	369
6.6.3.3	Additional spurious emissions	374
6.6.3.3.1	Minimum requirement (network signalled value "NS_05")	374
6.6.3.3.2	Minimum requirement (network signalled value "NS_07")	375
6.6.3.3.3	Minimum requirement (network signalled value "NS_08")	375
6.6.3.3.4	Minimum requirement (network signalled value "NS_09")	375
6.6.3.3.5	Minimum requirement (network signalled value "NS_12")	376
6.6.3.3.6	Minimum requirement (network signalled value "NS_13")	376
6.6.3.3.7	Minimum requirement (network signalled value "NS_14")	376
6.6.3.3.8	Minimum requirement (network signalled value "NS_15")	376
6.6.3.3.9	Minimum requirement (network signalled value "NS_16")	377
6.6.3.3.10	Minimum requirement (network signalled value "NS_17")	377
6.6.3.3.11	Minimum requirement (network signalled value "NS_18")	377
6.6.3.3.12	Minimum requirement (network signalled value "NS_19")	378
6.6.3.3.13	Minimum requirement (network signalled value "NS_11")	378
6.6.3.3.14	Minimum requirement (network signalled value "NS_20")	378
6.6.3.3.15	Minimum requirement (network signalled value "NS_21")	378
6.6.3.3.16	Minimum requirement (network signalled value "NS_22")	379
6.6.3.3.17	Minimum requirement (network signalled value "NS_23")	379
6.6.3.3.18	Void	380
6.6.3.3.19	Minimum requirement (network signalled value "NS_04")	380
6.6.3.3.20	Minimum requirement (network signalled value "NS_24")	380
6.6.3.3.21	Minimum requirement (network signalled value "NS_25")	380
6.6.3.3.22	Minimum requirement (network signalled value "NS_26")	381

6.6.3.3.23	Minimum requirement (network signalled value "NS_27" and "NS_43")	381
6.6.3.3.24	Minimum requirement (network signalled value "NS_28")	381
6.6.3.3.25	Minimum requirement (network signalled value "NS_29")	381
6.6.3.3.26	Minimum requirement (network signalled value "NS_30")	382
6.6.3.3.27	Minimum requirement (network signalled value "NS_31")	383
6.6.3.3.28	Minimum requirement (network signalled value "NS_36")	383
6.6.3.3.29	Minimum requirement (network signalled value "NS_38")	384
6.6.3.3.30	Minimum requirement (network signalled value "NS_39")	384
6.6.3.3.31	Minimum requirement (network signalled value "NS_40" and "NS_41")	384
6.6.3.3.32	Minimum requirement (network signalled value "NS_42")	384
6.6.3.3.33	Minimum requirement (network signalled value "NS_44")	385
6.6.3.3.34	Minimum requirement (network signalled value "NS_45")	385
6.6.3.3.35	Minimum requirement (network signalled value "NS_56")	386
6.6.3.3A	Additional spurious emissions for CA	386
6.6.3.3A.1	Minimum requirement for CA_1C (network signalled value "CA_NS_01")	386
6.6.3.3A.2	Minimum requirement for CA_1C (network signalled value "CA_NS_02")	386
6.6.3.3A.3	Minimum requirement for CA_1C (network signalled value "CA_NS_03")	387
6.6.3.3A.4	Minimum requirement for CA_38C (network signalled value "CA_NS_05")	387
6.6.3.3A.5	Minimum requirement for CA_7C (network signalled value "CA_NS_06")	387
6.6.3.3A.6	Minimum requirement for CA_39C and CA_39C-41A (network signalled value "CA_NS_07")	388
6.6.3.3A.7	Minimum requirement for CA_42C (network signalled value "CA_NS_08")	388
6.6.3.3A.8	Minimum requirement for CA_41C and CA_41D (network signalled value "CA_NS_04")	388
6.6.3.3A.9	Void	389
6.6.3.3A.10	Minimum requirement for CA_48B and CA_48C (network signalled value "CA_NS_10")	389
6.6.3A	Void	389
6.6.3B	Spurious emission for UL-MIMO	389
6.6.3C	Void	389
6.6.3D	Spurious emission for ProSe	389
6.6.3F	Spurious emission for category NB1 and NB2	390
6.6.3G	Spurious emission for V2X Communication	390
6.6A	Void	392
6.6B	Void	392
6.7	Transmit intermodulation	392
6.7.1	Minimum requirement	392
6.7.1A	Minimum requirement for CA	392
6.7.1B	Minimum requirement for UL-MIMO	393
6.7.1F	Minimum requirement for category NB1 and NB2	393
6.7.1G	Minimum requirement for V2X Communication	393
6.8	Void	394
6.8A	Void	394
6.8B	Time alignment error for UL-MIMO	394
6.8B.1	Minimum Requirements	394
6.8C	Void	394
6.8D	Void	394
6.8E	Void	394
6.8F	Void	394
6.8G	Time alignment error	394
7	Receiver characteristics	394
7.1	General	394
7.2	Diversity characteristics	395
7.3	Reference sensitivity power level	395
7.3.1	Minimum requirements (QPSK)	396
7.3.1A	Minimum requirements (QPSK) for CA	429
7.3.1B	Minimum requirements (QPSK) for UL-MIMO	459
7.3.1D	Minimum requirements (QPSK) for ProSe	459
7.3.1E	Minimum requirements (QPSK) for UE category 0, M1, M2 and 1bis	461
7.3.1F	Minimum requirements for UE category NB1 and NB2	469
7.3.1F.1	Reference sensitivity for UE category NB1 and NB2	469
7.3.1F.2	Void	469
7.3.1G	Minimum requirements (QPSK) for V2X	469

7.3.2	Void	471
7.4	Maximum input level	471
7.4.1	Minimum requirements.....	471
7.4.1A	Minimum requirements for CA	472
7.4.1B	Minimum requirements for UL-MIMO	473
7.4.1D	Minimum requirements for ProSe	473
7.4.1F	Minimum requirements for category NB1 and NB2.....	473
7.4.1G	Minimum requirements for V2X	473
7.4A	Void.....	474
7.4A.1	Void	474
7.5	Adjacent Channel Selectivity (ACS).....	474
7.5.1	Minimum requirements.....	474
7.5.1A	Minimum requirements for CA	475
7.5.1B	Minimum requirements for UL-MIMO	479
7.5.1D	Minimum requirements for ProSe	479
7.5.1F	Minimum requirements for category NB1 and NB2.....	480
7.5.1G	Minimum requirements for V2X	481
7.6	Blocking characteristics	482
7.6.1	In-band blocking.....	482
7.6.1.1	Minimum requirements.....	483
7.6.1.1A	Minimum requirements for CA.....	484
7.6.1.1D	Minimum requirements for ProSe.....	487
7.6.1.1F	Minimum requirements for category NB1 and NB2.....	488
7.6.1.1G	Minimum requirements for V2X.....	488
7.6.2	Out-of-band blocking.....	490
7.6.2.1	Minimum requirements.....	490
7.6.2.1A	Minimum requirements for CA.....	491
7.6.2.1D	Minimum requirements for ProSe.....	494
7.6.2.1F	Minimum requirements for category NB1 and NB2.....	495
7.6.2.1G	Minimum requirements for V2X.....	496
7.6.3	Narrow band blocking	497
7.6.3.1	Minimum requirements.....	497
7.6.3.1A	Minimum requirements for CA.....	497
7.6.3.1D	Minimum requirements for ProSe.....	499
7.6A	Void.....	499
7.6B	Blocking characteristics for UL-MIMO	499
7.7	Spurious response.....	499
7.7.1	Minimum requirements.....	499
7.7.1A	Minimum requirements for CA	500
7.7.1B	Minimum requirements for UL-MIMO	501
7.7.1D	Minimum requirements for ProSe	501
7.7.1F	Minimum requirements for UE category NB1 and NB2	502
7.7.1G	Minimum requirements for V2X	502
7.8	Intermodulation characteristics	503
7.8.1	Wide band intermodulation.....	503
7.8.1.1	Minimum requirements.....	503
7.8.1A	Minimum requirements for CA	504
7.8.1B	Minimum requirements for UL-MIMO	506
7.8.1D	Minimum requirements for ProSe	506
7.8.1F	Minimum requirements for category NB1 and NB2.....	507
7.8.1G	Minimum requirements.....	507
7.8.2	Void	508
7.9	Spurious emissions	508
7.9.1	Minimum requirements.....	509
7.9.1A	Minimum requirements.....	509
7.10	Receiver image	510
7.10.1	Void	510
7.10.1A	Minimum requirements for CA	510
7.10.1G	Minimum requirements for V2X Communication.....	510
8	Performance requirement	511
8.1	General	511

8.1.1	Receiver antenna capability	511
8.1.1.1	Simultaneous unicast and MBMS operations.....	512
8.1.1.2	Dual-antenna receiver capability in idle mode	512
8.1.2	Applicability of requirements	512
8.1.2.1	Applicability of requirements for different channel bandwidths.....	512
8.1.2.2	Definition of CA capability	512
8.1.2.2A	Definition of dual connectivity capability	517
8.1.2.3	Applicability and test rules for different CA configurations and bandwidth combination sets.....	518
8.1.2.3A	Applicability and test rules for different dual connectivity configuration and bandwidth combination set	519
8.1.2.3B	Applicability and test rules for different TDD-FDD CA configurations and bandwidth combination sets.....	520
8.1.2.3C	Applicability and test rules for SDR tests for 4Rx capable UEs	521
8.1.2.3D	Applicability and test rules for different CA with LAA SCell(s) configurations and bandwidth combination sets.....	522
8.1.2.3E	Applicability and test rules for SDR tests for 8Rx capable UEs	523
8.1.2.4	Test coverage for different number of component carriers	523
8.1.2.5	Applicability of performance requirements for Type B receiver	524
8.1.2.6	Applicability of performance requirements for 4Rx capable UEs	525
8.1.2.6.1	Applicability rule and antenna connection for single carrier tests with 2Rx	525
8.1.2.6.2	Applicability rule and antenna connection for CA and DC tests with 2Rx	526
8.1.2.6.3	Applicability rule and antenna connection for single carrier tests with 4Rx	527
8.1.2.6.4	Applicability rule for 256QAM tests	527
8.1.2.6.5	Applicability rule and antenna connection for CA and DC tests with 4Rx	527
8.1.2.6.6	Applicability rule for Type C with 4Rx.....	529
8.1.2.6.7	Applicability rule for 1024QAM tests	530
8.1.2.7	Applicability of Enhanced Downlink Control Channel Performance Requirements	530
8.1.2.8	Applicability of performance requirements for CDM-multiplexed DM RS with interfering simultaneous transmission (FRC) with multiple CSI-RS configurations	531
8.1.2.8A	Applicability of performance requirements for UE supporting coverage enhancement	531
8.1.2.9	Applicability of SDR requirements for CA and LAA	533
8.1.2.10	Applicability of performance requirements for Multi-user Superposed Transmission	533
8.1.2.11	Applicability CRS interference mitigation receivers performance requirements	533
8.1.2.12	Applicability of performance requirements for 8Rx capable UEs	534
8.1.2.12.1	Applicability rule and antenna connection for single carrier PDSCH tests	534
8.1.2.12.2	Applicability rule and antenna connection for control channel tests	540
8.1.2.12.3	Applicability rule and antenna connection for CA and DC tests	540
8.1.3	UE category and UE DL category	541
8.2	Demodulation of PDSCH (Cell-Specific Reference Symbols)	541
8.2.1	FDD (Fixed Reference Channel)	541
8.2.1.1	Single-antenna port performance	542
8.2.1.1.1	Minimum Requirement	542
8.2.1.1.2	Void	546
8.2.1.1.3	Void	546
8.2.1.1.4	Minimum Requirement 1 PRB allocation in presence of MBSFN.....	546
8.2.1.1.4A	Minimum Requirement 1 PRB allocation in presence of FeMBMS Unicast-mixed Cell under CA	547
8.2.1.2	Transmit diversity performance	548
8.2.1.2.1	Minimum Requirement 2 Tx Antenna Port	548
8.2.1.2.2	Minimum Requirement 4 Tx Antenna Port	548
8.2.1.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	549
8.2.1.2.3A	Minimum Requirement 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	550
8.2.1.2.4	Enhanced Performance Requirement Type A - 2 Tx Antenna Ports with TM3 interference model	552
8.2.1.2.5	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM2 interference model	553
8.2.1.2.6	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM9 interference model	554
8.2.1.2.7	Minimum Requirement 2 Tx Antenna Port (Superposed transmission)	555
8.2.1.3	Open-loop spatial multiplexing performance.....	556

8.2.1.3.1	Minimum Requirement 2 Tx Antenna Port	556
8.2.1.3.1A	Soft buffer management test	559
8.2.1.3.1B	Enhanced Performance Requirement Type C – 2Tx Antenna Ports	560
8.2.1.3.1C	Enhanced Performance Requirement Type C - 2 Tx Antenna Ports with TM1 interference	561
8.2.1.3.2	Minimum Requirement 4 Tx Antenna Port	562
8.2.1.3.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	562
8.2.1.3.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	565
8.2.1.3.5	Minimum Requirement 2 Tx Antenna Port (Superposed transmission)	567
8.2.1.3.6	Minimum Requirement 2 Tx Antenna Port (network-based CRS interference mitigation).....	567
8.2.1.4	Closed-loop spatial multiplexing performance	568
8.2.1.4.1	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Port.....	568
8.2.1.4.1A	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Port.....	569
8.2.1.4.1B	Enhanced Performance Requirement Type A - Single-Layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	570
8.2.1.4.1C	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured).....	571
8.2.1.4.1D	Enhanced Performance Requirement Type B - Single-layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	573
8.2.1.4.1E	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports with CRS assistance information	574
8.2.1.4.1F	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Ports with CRS assistance information	575
8.2.1.4.2	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port	576
8.2.1.4.2A	Enhanced Performance Requirement Type C – Multi-layer Spatial Multiplexing 2Tx Antenna Ports.....	577
8.2.1.4.3	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port	577
8.2.1.4.3A	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port for dual connectivity	581
8.2.1.4.4	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port (Superposed transmission)	582
8.2.1.5	MU-MIMO.....	583
8.2.1.6	[Control channel performance: D-BCH and PCH]	583
8.2.1.7	Carrier aggregation with power imbalance	583
8.2.1.7.1	Minimum Requirement	583
8.2.1.8	Intra-band non-contiguous carrier aggregation with timing offset.....	584
8.2.1.8.1	Minimum Requirement	584
8.2.1.9	HST-SFN performance	585
8.2.1.9.1	Minimum Requirement	585
8.2.1.9.2	Minimum Requirement for Rel-16 further enhanced HST.....	587
8.2.1.10	Intra-band contiguous carrier aggregation with minimum channel spacing.....	588
8.2.1.10.1	Minimum Requirement	588
8.2.2	TDD (Fixed Reference Channel)	589
8.2.2.1	Single-antenna port performance	590
8.2.2.1.1	Minimum Requirement	590
8.2.2.1.2	Void	594
8.2.2.1.3	Void	594
8.2.2.1.4	Minimum Requirement 1 PRB allocation in presence of MBSFN.....	594
8.2.2.2	Transmit diversity performance	594
8.2.2.2.1	Minimum Requirement 2 Tx Antenna Port	594
8.2.2.2.2	Minimum Requirement 4 Tx Antenna Port	595
8.2.2.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	595
8.2.2.2.3A	Minimum Requirement 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	597
8.2.2.2.4	Enhanced Performance Requirement Type A – 2 Tx Antenna Ports with TM3 interference model.....	598
8.2.2.2.5	Minimum Requirement 2 Tx Antenna Port (when <i>EIMTA-MainConfigServCell-r12</i> is configured)	599
8.2.2.2.6	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM2 interference model.....	600

8.2.2.2.7	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM9 interference model	601
8.2.2.2.8	Minimum Requirement 2 Tx Antenna Port (Superposed transmission)	602
8.2.2.3	Open-loop spatial multiplexing performance	603
8.2.2.3.1	Minimum Requirement 2 Tx Antenna Port	603
8.2.2.3.1A	Soft buffer management test	606
8.2.2.3.1B	Enhanced Performance Requirement Type C - 2Tx Antenna Ports	607
8.2.2.3.1C	Enhanced Performance Requirement Type C - 2 Tx Antenna Ports with TM1 interference	607
8.2.2.3.2	Minimum Requirement 4 Tx Antenna Port	608
8.2.2.3.3	Minimum Requirement 2Tx antenna port (demodulation subframe overlaps with aggressor cell ABS)	608
8.2.2.3.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	611
8.2.2.3.5	Minimum Requirement 2 Tx Antenna Port (Superposed transmission)	613
8.2.2.3.6	Minimum Requirement 2 Tx Antenna Port (network-based CRS interference mitigation).....	613
8.2.2.4	Closed-loop spatial multiplexing performance	615
8.2.2.4.1	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Port	615
8.2.2.4.1A	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Port	615
8.2.2.4.1B	Enhanced Performance Requirement Type A – Single-Layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	616
8.2.2.4.1C	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured).....	617
8.2.2.4.1D	Enhanced Performance Requirement Type B - Single-layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	619
8.2.2.4.1E	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports with CRS assistance information	620
8.2.2.4.1F	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Ports with CRS assistance information	621
8.2.2.4.2	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port	622
8.2.2.4.2A	Enhanced Requirement Type C Multi-Layer Spatial Multiplexing 2 Tx Antenna Port	623
8.2.2.4.3	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port	624
8.2.2.4.3A	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port for dual connectivity	627
8.2.2.4.4	Void	629
8.2.2.4.5	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port (Superposed transmission)	629
8.2.2.5	MU-MIMO.....	629
8.2.2.6	[Control channel performance: D-BCH and PCH]	629
8.2.2.7	Carrier aggregation with power imbalance	629
8.2.2.7.1	Minimum Requirement	629
8.2.2.8	Intra-band contiguous carrier aggregation with minimum channel spacing.....	630
8.2.2.8.1	Minimum Requirement	630
8.2.2.9	HST-SFN performance	631
8.2.2.9.1	Minimum Requirement	631
8.2.2.9.2	Minimum Requirement for Rel-16 further enhanced HST	633
8.2.3	TDD FDD CA (Fixed Reference Channel).....	634
8.2.3.1	Single-antenna port performance	635
8.2.3.1.1	Minimum Requirement for FDD PCell	635
8.2.3.1.2	Minimum Requirement for TDD PCell	638
8.2.3.2	Open-loop spatial multiplexing performance 2Tx Antenna port.....	642
8.2.3.2.1	Minimum Requirement for FDD PCell	642
8.2.3.2.1A	Soft buffer management test for FDD PCell	645
8.2.3.2.2	Minimum Requirement for TDD PCell	646
8.2.3.2.2A	Soft buffer management test for TDD PCell	650
8.2.3.3	Closed-loop spatial multiplexing performance 4Tx Antenna Port	651
8.2.3.3.1	Minimum Requirement for FDD PCell	651
8.2.3.3.2	Minimum Requirement for TDD PCell	654
8.2.3.4	Minimum Requirement for Closed-loop spatial multiplexing performance 4Tx Antenna Port for dual connectivity	658
8.2.3.5	HST-SFN performance	660
8.2.3.5.0	General	660

8.2.3.5.1	Minimum Requirement for FDD PCell	660
8.2.3.5.2	Minimum Requirement for TDD PCell	663
8.2.4	LAA	666
8.2.4.1	Closed-loop spatial multiplexing performance 4Tx Antenna Port	666
8.2.4.1.1	FDD PCell (FDD single carrier)	666
8.2.4.1.2	TDD PCell (TDD single carrier)	669
8.3	Demodulation of PDSCH (User-Specific Reference Symbols)	672
8.3.1	FDD	672
8.3.1.1	Single-layer Spatial Multiplexing	673
8.3.1.1A	Enhanced Performance Requirement Type A – Single-layer Spatial Multiplexing with TM9 interference model	674
8.3.1.1B	Single-layer Spatial Multiplexing (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	676
8.3.1.1C	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM9 interference model	678
8.3.1.1D	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with CRS interference model	679
8.3.1.1E	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM3 interference model	680
8.3.1.1F	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM10 serving cell configuration and TM9 interference model	682
8.3.1.1G	Single-layer Spatial Multiplexing (CRS assistance information is configured)	683
8.3.1.1H	Single-layer Spatial Multiplexing (With Enhanced DMRS table configured)	684
8.3.1.1I	Single-layer Spatial Multiplexing (with assistance information for simultaneous transmission interfering PDSCH)	685
8.3.1.2	Dual-Layer Spatial Multiplexing	686
8.3.1.2A	Enhanced Performance Requirement Type C - Dual-Layer Spatial Multiplexing	687
8.3.1.3	Performance requirements for DCI format 2D and non Quasi Co-located Antenna Ports	688
8.3.1.3.1	Minimum requirement with Same Cell ID (with single NZP CSI-RS resource)	688
8.3.1.3.2	Minimum requirements with Same Cell ID (with multiple NZP CSI-RS resources)	690
8.3.1.3.3	Minimum requirement with Different Cell ID and Colliding CRS (with single NZP CSI-RS resource)	692
8.3.1.3.4	Minimum requirement with Different Cell ID and non-colliding CRS (with single NZP CSI-RS resource and CRS assistance information is configured)	693
8.3.1.3.5	Minimum requirements with different Cell ID and non-colliding CRS (with multiple NZP CSI-RS resources and CRS assistance information is configured)	695
8.3.1.3.6	Minimum requirements for QCL Type C and 2 Layers Spatial Multiplexing	696
8.3.1.4	Performance Requirements for semiOpenLoop transmission	698
8.3.2	TDD	699
8.3.2.1	Single-layer Spatial Multiplexing	700
8.3.2.1A	Single-layer Spatial Multiplexing (with multiple CSI-RS configurations)	701
8.3.2.1B	Enhanced Performance Requirement Type A – Single-layer Spatial Multiplexing with TM9 interference model	703
8.3.2.1C	Single-layer Spatial Multiplexing (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	705
8.3.2.1D	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM9 interference	707
8.3.2.1E	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with CRS interference model	708
8.3.2.1F	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM3 interference	709
8.3.2.1G	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM10 serving cell configuration and TM9 interference model	710
8.3.2.1H	Single-layer Spatial Multiplexing (CRS assistance information is configured)	712
8.3.2.1I	Single-layer Spatial Multiplexing (With Enhanced DMRS table configured)	713
8.3.2.1J	Single-layer Spatial Multiplexing (with assistance information for simultaneous transmission interfering PDSCH)	714
8.3.2.2	Dual-Layer Spatial Multiplexing	715
8.3.2.2A	Enhanced Performance Requirement Type C - Dual-Layer Spatial Multiplexing	716
8.3.2.3	Dual-Layer Spatial Multiplexing (with multiple CSI-RS configurations)	717
8.3.2.4	Performance requirements for DCI format 2D and non Quasi Co-located Antenna Ports	718
8.3.2.4.1	Minimum requirement with Same Cell ID (with single NZP CSI-RS resource)	718

8.3.2.4.2	Minimum requirements with Same Cell ID (with multiple NZP CSI-RS resources).....	719
8.3.2.4.3	Minimum requirement with Different Cell ID and Colliding CRS (with single NZP CSI-RS resource)	721
8.3.2.4.4	Minimum requirement with Different Cell ID and non-Colliding CRS (with single NZP CSI-RS resource and CRS assistance information is configured).....	722
8.3.2.4.5	Minimum requirements with different Cell ID and non-colliding CRS (with multiple NZP CSI-RS resources and CRS assistance information is configured).....	724
8.3.2.4.6	Minimum requirements for QCL Type C and 2 Layers Spatial Multiplexing.....	726
8.3.2.5	Performance Requirements for semiOpenLoop transmission	727
8.3.3	LAA.....	729
8.3.3.1	Dual-Layer Spatial Multiplexing with DM-RS.....	729
8.3.3.1.1	FDD PCell (FDD single carrier).....	729
8.3.3.1.2	TDD Pcell (TDD single carrier)	732
8.4	Demodulation of PDCCCH/PCFICH	736
8.4.1	FDD	736
8.4.1.1	Single-antenna port performance	737
8.4.1.2	Transmit diversity performance	737
8.4.1.2.1	Minimum Requirement 2 Tx Antenna Port	737
8.4.1.2.2	Minimum Requirement 4 Tx Antenna Port	737
8.4.1.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	737
8.4.1.2.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	740
8.4.1.2.5	Enhanced Downlink Control Channel Performance Requirement Type A - 2 Tx Antenna Port under Asynchronous Network	743
8.4.1.2.6	Enhanced Downlink Control Channel Performance Requirement Type A - 2 Tx Antenna Port with Non-Colliding CRS Dominant Interferer	744
8.4.1.2.7	Enhanced Downlink Control Channel Performance Requirement Type B - 2 Tx Antenna Port with Colliding CRS Dominant Interferer.....	745
8.4.1.2.8	Enhanced Downlink Control Channel Performance Requirement Type B - 2 Tx Antenna Port with Non-Colliding CRS Dominant Interferer	746
8.4.1.2.9	Enhanced Downlink Control Channel Performance Requirement Type A - 4 Tx Antenna Port with Non-Colliding CRS Dominant Interferer	747
8.4.2	TDD.....	748
8.4.2.1	Single-antenna port performance	749
8.4.2.2	Transmit diversity performance	749
8.4.2.2.1	Minimum Requirement 2 Tx Antenna Port	749
8.4.2.2.2	Minimum Requirement 4 Tx Antenna Port	749
8.4.2.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	750
8.4.2.2.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	752
8.4.2.2.5	Enhanced Downlink Control Channel Performance Requirement Type A - 2 Tx Antenna Port with Colliding CRS Dominant Interferer.....	755
8.4.2.2.6	Enhanced Downlink Control Channel Performance Requirement Type A - 2 Tx Antenna Port with Non-Colliding CRS Dominant Interferer	756
8.4.2.2.7	Enhanced Downlink Control Channel Performance Requirement Type B - 2 Tx Antenna Port with Colliding CRS Dominant Interferer.....	757
8.4.2.2.8	Enhanced Downlink Control Channel Performance Requirement Type B - 2 Tx Antenna Port with Non-Colliding CRS Dominant Interferer	758
8.4.2.2.9	Enhanced Downlink Control Channel Performance Requirement Type A - 4 Tx Antenna Port with Non-Colliding CRS Dominant Interferer	759
8.4.3	LAA.....	760
8.4.3.1	Transmit diversity performance	760
8.4.3.1.1	FDD Pcell (FDD single carrier).....	760
8.4.3.1.2	TDD Pcell (TDD single carrier)	761
8.5	Demodulation of PHICH.....	762
8.5.1	FDD	762
8.5.1.1	Single-antenna port performance	763
8.5.1.2	Transmit diversity performance	763
8.5.1.2.1	Minimum Requirement 2 Tx Antenna Port	763
8.5.1.2.2	Minimum Requirement 4 Tx Antenna Port	763