

ETSI TS 138 101-1 V16.26.0 (2026-04)



TECHNICAL SPECIFICATION

**5G;
NR;
User Equipment (UE) radio transmission and reception;
Part 1: Range 1 Standalone
(3GPP TS 38.101-1 version 16.26.0 Release 16)**



ReferenceRTS/TSGR-0438101-1vgq0

Keywords5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed, this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our [Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2026.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by the ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found at [3GPP to ETSI numbering cross-referencing](#).

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	16
1 Scope	18
2 References	18
3 Definitions, symbols and abbreviations	18
3.1 Definitions	18
3.2 Symbols.....	20
3.3 Abbreviations	22
4 General	23
4.1 Relationship between minimum requirements and test requirements	23
4.2 Applicability of minimum requirements	23
4.3 Specification suffix information.....	23
5 Operating bands and channel arrangement.....	24
5.1 General	24
5.2 Operating bands.....	24
5.2A Operating bands for CA	26
5.2A.0 General.....	26
5.2A.1 Intra-band CA	26
5.2A.2 Inter-band CA	27
5.2A.2.1 Inter-band CA (two bands).....	27
5.2A.2.2 Inter-band CA (three bands).....	29
5.2A.2.3 Inter-band CA (four bands).....	30
5.2B Operating bands for DC	30
5.2C Operating band combination for SUL	30
5.2D Operating bands for UL MIMO	31
5.2E Operating band for V2X.....	31
5.2E.1 V2X operating bands	31
5.2E.2 V2X operating bands for concurrent operation.....	32
5.3 UE channel bandwidth	32
5.3.1 General.....	32
5.3.2 Maximum transmission bandwidth configuration	33
5.3.3 Minimum guardband and transmission bandwidth configuration.....	33
5.3.4 RB alignment.....	35
5.3.5 UE channel bandwidth per operating band.....	35
5.3.6 Asymmetric channel bandwidths	38
5.3A UE channel bandwidth for CA	39
5.3A.1 General.....	39
5.3A.2 Maximum transmission bandwidth configuration for CA	39
5.3A.3 Minimum guardband and transmission bandwidth configuration for CA	39
5.3A.4 Void	41
5.3A.5 UE channel bandwidth per operating band for CA.....	41
5.3E Channel bandwidth for V2X	42
5.3E.1 General.....	42
5.3E.2 Channel bandwidth for V2X concurrent operation.....	42
5.4 Channel arrangement.....	43
5.4.1 Channel spacing.....	43
5.4.1.1 Channel spacing for adjacent NR carriers	43
5.4.2 Channel raster	43
5.4.2.1 NR-ARFCN and channel raster.....	43
5.4.2.2 Channel raster to resource element mapping.....	44
5.4.2.3 Channel raster entries for each operating band	44

5.4.3	Synchronization raster	46
5.4.3.1	Synchronization raster and numbering.....	46
5.4.3.3	Synchronization raster entries for each operating band.....	47
5.4.4	TX–RX frequency separation	48
5.4A	Channel arrangement for CA.....	49
5.4A.1	Channel spacing for CA.....	49
5.4A.2	Channel raster for CA.....	49
5.4A.3	Synchronization raster for CA	49
5.4A.4	Tx-Rx frequency separation for CA.....	49
5.4B	Reserved.....	50
5.4C	Reserved.....	50
5.4D	Reserved.....	50
5.4E	Channel arrangement for V2X	50
5.4E.1	Channel spacing.....	50
5.4E.2	Channel raster	50
5.4E.2.1	NR-ARFCN and channel raster.....	50
5.4E.2.2	Channel raster to resource element mapping.....	50
5.4E.2.3	Channel raster entries for each operating band	50
5.4E.3	Synchronization raster for V2X.....	50
5.5	Void.....	51
5.5A	Configurations for CA.....	51
5.5A.0	General.....	51
5.5A.1	Configurations for intra-band contiguous CA.....	51
5.5A.2	Configurations for intra-band non-contiguous CA	53
5.5A.3	Configurations for inter-band CA.....	53
5.5A.3.1	Configurations for inter-band CA (two bands)	53
5.5A.3.2	Configurations for inter-band CA (three bands)	63
5.5A.3.3	Configurations for inter-band CA (four bands).....	71
5.5B	Configurations for DC.....	73
5.5C	Configurations for SUL.....	73
6	Transmitter characteristics	75
6.1	General	75
6.1A	General	75
6.1F	General	75
6.2	Transmitter power	75
6.2.1	UE maximum output power.....	75
6.2.2	UE maximum output power reduction.....	77
6.2.3	UE additional maximum output power reduction.....	79
6.2.3.1	General	79
6.2.3.2	A-MPR for NS_04	82
6.2.3.3	A-MPR for NS_10	83
6.2.3.4	A-MPR for NS_05 and NS_05U.....	84
6.2.3.5	A-MPR for NS_40	86
6.2.3.6	A-MPR for NS_43 and NS_43U.....	87
6.2.3.7	A-MPR for NS_03 and NS_03U.....	88
6.2.3.8	A-MPR for NS_37	88
6.2.3.9	A-MPR for NS_38	89
6.2.3.10	A-MPR for NS_39	89
6.2.3.11	A-MPR for NS_41	89
6.2.3.12	A-MPR for NS_42	90
6.2.3.13	A-MPR for NS_18	90
6.2.3.14	A-MPR for NS_21	91
6.2.3.15	A-MPR for NS_24	91
6.2.3.16	A-MPR for NS_27	92
6.2.3.17	A-MPR for NS_46.....	93
6.2.3.18	A-MPR for NS_47	94
6.2.3.19	A-MPR for NS_50	95
6.2.3.20	A-MPR for NS_44.....	95
6.2.3.21	A-MPR for NS_12	96
6.2.3.22	A-MPR for NS_13	96
6.2.3.23	A-MPR for NS_14	97

6.2.3.24	A-MPR for NS_15	97
6.2.3.25	A-MPR for NS_45	98
6.2.3.26	A-MPR for NS_48	98
6.2.3.27	A-MPR for NS_49	99
6.2.3.28	A-MPR for NS_51	100
6.2.4	Configured transmitted power	100
6.2A	Transmitter power for CA	102
6.2A.1	UE maximum output power for CA	102
6.2A.1.1	UE maximum output power for Intra-band contiguous CA	102
6.2A.1.2	UE maximum output power for Intra-band non-contiguous CA	103
6.2A.1.3	UE maximum output power for Inter-band CA	103
6.2A.1.4	Void	105
6.2A.1.5	Void	105
6.2A.2	UE maximum output power reduction for CA	105
6.2A.2.1	UE maximum output power reduction for Intra-band contiguous CA	105
6.2A.2.2	UE maximum output power reduction for Intra-band non-contiguous CA	107
6.2A.2.2.0	General	107
6.2A.2.2.1	MPR to meet -30dBm/MHz	107
6.2A.2.2.2	MPR to meet -13dBm/MHz	108
6.2A.2.3	UE maximum output power reduction for Inter-band CA	108
6.2A.2.4	Void	108
6.2A.3	UE additional maximum output power reduction for CA	108
6.2A.3.1.1	UE additional maximum output power reduction for Intra-band contiguous CA	108
6.2A.3.1.1.1	A-MPR for CA_NS_04	109
6.2A.3.1.2	UE additional maximum output power reduction for Intra-band non-contiguous CA	115
6.2A.3.1.3	UE additional maximum output power reduction for Inter-band CA	117
6.2A.4	Configured output power for CA	118
6.2A.4.1	Configured transmitted power level	118
6.2A.4.1.1	Configured transmitted power for Intra-band contiguous CA	118
6.2A.4.1.2	Configured transmitted power for Intra-band non-contiguous CA	120
6.2A.4.1.3	Configured transmitted power for Inter-band CA	123
6.2A.4.1.4	Void	125
6.2A.4.2	$\Delta T_{IB,c}$ for CA	125
6.2A.4.2.1	Void	125
6.2A.4.2.2	Void	125
6.2A.4.2.3	$\Delta T_{IB,c}$ for Inter-band CA (two bands)	125
6.2A.4.2.4	$\Delta T_{IB,c}$ for Inter-band CA (three bands)	128
6.2A.4.2.5	$\Delta T_{IB,c}$ for Inter-band CA (four bands)	130
6.2B	Transmitter power for NR-DC	130
6.2B.0	General	130
6.2B.1	UE maximum output power for NR-DC	131
6.2B.2	UE maximum output power reduction for NR-DC	131
6.2B.3	UE additional maximum output power reduction for NR-DC	131
6.2B.4	Configured output power for NR-DC	131
6.2B.4.1	Configured transmitted power level for NR-DC	131
6.2B.4.2	$\Delta T_{IB,c}$ for NR-DC	134
6.2C	Transmitter power for SUL	134
6.2C.1	Configured transmitted power for SUL	134
6.2C.2	$\Delta T_{IB,c}$	134
6.2D	Transmitter power for UL MIMO	135
6.2D.1	UE maximum output power for UL MIMO	135
6.2D.2	UE maximum output power reduction for UL MIMO	136
6.2D.3	UE additional maximum output power reduction for UL MIMO	136
6.2D.4	Configured transmitted power for UL MIMO	137
6.2E	Transmitter power for V2X	138
6.2E.1	UE maximum output power for V2X	138
6.2E.1.1	General	138
6.2E.1.2	UE maximum output power for V2X con-current operation	138
6.2E.2	UE maximum output power reduction for V2X	139
6.2E.2.1	General	139
6.2E.2.2	MPR for Power class 3 V2X UE	139
6.2E.2.3	MPR for Power class 3 V2X concurrent operation	140

6.2E.3	UE additional maximum output power reduction for V2X.....	140
6.2E.3.1	General	140
6.2E.3.2	A-MPR for Power class 3 V2X UE by NS_33	141
6.2E.3.3	A-MPR for Power class 3 V2X UE by NS_52	143
6.2E.3.4	A-MPR for power class 3 V2X concurrent operation	144
6.2E.4	Configured transmitted power for V2X	144
6.2E.4.1	General	144
6.2E.4.2	Configured transmitted power for V2X concurrent operation	145
6.2F	Transmitter power for shared spectrum channel access	146
6.2F.1	UE maximum output power	146
6.2F.1A	UE maximum output power for CA.....	147
6.2F.1A.1	UE maximum output power for inter-band CA.....	147
6.2F.2	UE maximum output power reduction.....	147
6.2F.2A	UE maximum output power reduction for CA.....	148
6.2F.2A.1	UE maximum output power reduction for inter-band CA.....	148
6.2F.3	UE additional maximum output power reduction	148
6.2F.3.1	General	148
6.2F.3.2	A-MPR for NS_28	149
6.2F.3.3	A-MPR for NS_29	149
6.2F.3.4	A-MPR for NS_30	150
6.2F.3.5	A-MPR for NS_31	150
6.2F.3.6	A-MPR for NS_53	151
6.2F.3.7	A-MPR for NS_54	151
6.2F.3A	UE additional maximum output power reduction for CA.....	152
6.2F.3A.1	UE additional maximum output power reduction for inter-band CA.....	152
6.2F.4	Configured transmitted power	152
6.3	Output power dynamics.....	152
6.3.1	Minimum output power	152
6.3.2	Transmit OFF power.....	152
6.3.3	Transmit ON/OFF time mask	153
6.3.3.1	General	153
6.3.3.2	General ON/OFF time mask	153
6.3.3.3	Transmit power time mask for slot and short or long subslot boundaries.....	154
6.3.3.4	PRACH time mask.....	154
6.3.3.5	Void.....	155
6.3.3.6	SRS time mask	155
6.3.3.7	PUSCH-PUCCH and PUSCH-SRS time masks	157
6.3.3.8	Transmit power time mask for consecutive slot or long subslot transmission and short subslot transmission boundaries	158
6.3.3.9	Transmit power time mask for consecutive short subslot transmissions boundaries	158
6.3.4	Power control.....	159
6.3.4.1	General	159
6.3.4.2	Absolute power tolerance.....	159
6.3.4.3	Relative power tolerance	159
6.3.4.4	Aggregate power tolerance.....	160
6.3A	Output power dynamics for CA	160
6.3A.1	Minimum output power for CA	160
6.3A.1.1	Minimum output power for intra-band contiguous CA.....	160
6.3A.1.2	Minimum output power for intra-band non-contiguous CA	160
6.3A.1.3	Minimum output power for inter-band CA	160
6.3A.1.4	Void.....	161
6.3A.2	Transmit OFF power for CA.....	161
6.3A.2.1	Transmit OFF power for intra-band contiguous CA	161
6.3A.2.2	Transmit OFF power for intra-band non-contiguous CA.....	161
6.3A.2.3	Transmit OFF power for inter-band CA.....	161
6.3A.2.4	Void.....	161
6.3A.3	Transmit ON/OFF time mask for CA	161
6.3A.3.1	Transmit ON/OFF time mask for intra-band contiguous CA.....	161
6.3A.3.2	Transmit ON/OFF time mask for intra-band non-contiguous CA	161
6.3A.3.3	Transmit ON/OFF time mask for inter-band CA	161
6.3A.3.3.1	General	161
6.3A.3.3.2	Time mask for switching between two uplink carriers	162

6.3A.3.4	Void.....	163
6.3A.4	Power control for CA.....	163
6.3A.4.1	Power control for intra-band contiguous CA	163
6.3A.4.1.1	Absolute power tolerance	163
6.3A.4.1.2	Relative power tolerance	163
6.3A.4.1.3	Aggregate power control tolerance.....	164
6.3A.4.2	Power control for intra-band non-contiguous CA	164
6.3A.4.2.1	Absolute power tolerance.....	164
6.3A.4.2.1.1	Minimum requirements	164
6.3A.4.2.2	Relative power tolerance	164
6.3A.4.2.2.1	Minimum requirements	164
6.3A.4.2.3	Aggregate power control tolerance	164
6.3A.4.3	Power control for inter-band CA.....	165
6.3A.4.4	Void.....	165
6.3B	Output power dynamics for NR-DC.....	165
6.3C	Output power dynamics for SUL	165
6.3C.1	Void	165
6.3C.2	Void	165
6.3C.3	Transmit ON/OFF time mask for SUL	165
6.3C.3.1	Time mask for switching between two uplink carriers.....	165
6.3D	Output power dynamics for UL MIMO	166
6.3D.1	Minimum output power for UL MIMO	166
6.3D.2	Transmit OFF power for UL MIMO.....	166
6.3D.3	Transmit ON/OFF time mask for UL MIMO	166
6.3D.4	Power control for UL MIMO.....	167
6.3E	Output power dynamics for V2X	167
6.3E.1	Minimum output power for V2X.....	167
6.3E.1.1	General	167
6.3E.1.2	Minimum output power for V2X concurrent operation	167
6.3E.2	Transmit OFF power for V2X	167
6.3E.2.1	General	167
6.3E.2.2	Transmit OFF power for V2X concurrent operation.....	168
6.3E.3	Transmit ON/OFF time mask for V2X.....	168
6.3E.3.1	General	168
6.3E.3.2	General time mask.....	168
6.3E.3.3	S-SSB time mask	168
6.3E.3.4	Transmit ON/OFF time mask for V2X concurrent operation	169
6.3E.4	Power control for V2X	169
6.3E.4.1	General	169
6.3E.4.2	Absolute power tolerance.....	169
6.3E.4.3	Power control for V2X concurrent operation.....	169
6.3F	Output power dynamics for shared spectrum channel access.....	169
6.3F.1	Minimum output power	169
6.3F.2	Transmit OFF power.....	170
6.3F.3	Transmit ON/OFF time mask	170
6.3F.3.1	General	170
6.3F.3.2	General ON/OFF time mask	170
6.3F.3A	General ON/OFF mask for CA	170
6.3F.3A.1	General ON/OFF mask for inter-band CA	170
6.3F.4	Power control.....	170
6.3F.4.1	General	170
6.3F.4.2	Absolute power tolerance.....	171
6.3F.4.3	Relative power tolerance.....	171
6.3F.4.4	Aggregate power tolerance.....	171
6.4	Transmit signal quality	171
6.4.1	Frequency error.....	171
6.4.2	Transmit modulation quality.....	171
6.4.2.0	General	171
6.4.2.1	Error Vector Magnitude	171
6.4.2.1a	Error Vector Magnitude including symbols with transient period	172
6.4.2.2	Carrier leakage	173
6.4.2.3	In-band emissions	173

6.4.2.4	EVM equalizer spectrum flatness	174
6.4.2.4.1	Requirements for Pi/2 BPSK modulation.....	175
6.4A	Transmit signal quality for CA.....	176
6.4A.1	Frequency error for CA.....	176
6.4A.1.1	Frequency error for intra-band contiguous CA	176
6.4A.1.2	Frequency error for intra-band non-contiguous CA.....	176
6.4A.1.3	Frequency error for inter-band CA.....	176
6.4A.1.4	Void.....	177
6.4A.2	Transmit modulation quality for CA.....	177
6.4A.2.1	Transmit modulation quality for intra-band contiguous CA	177
6.4A.2.1.0	General	177
6.4A.2.1.1	Error Vector Magnitude.....	177
6.4A.2.1.2	In-band emissions.....	177
6.4A.2.1.3	Carrier leakage.....	179
6.4A.2.2	Transmit modulation quality for intra-band non-contiguous CA	180
6.4A.2.2.0	General	180
6.4A.2.2.1	Error Vector Magnitude.....	180
6.4A.2.2.2	In-band emissions	180
6.4A.2.2.3	Carrier leakage.....	180
6.4A.2.3	Transmit modulation quality for inter-band CA.....	181
6.4A.2.4	Void.....	181
6.4B	Transmit signal quality for NR-DC.....	181
6.4D	Transmit signal quality for UL MIMO.....	181
6.4D.0	General.....	181
6.4D.1	Frequency error for UL MIMO.....	181
6.4D.2	Transmit modulation quality for UL MIMO.....	181
6.4D.2.0	General	181
6.4D.2.1	Error Vector Magnitude	182
6.4D.2.2	Carrier leakage	182
6.4D.2.3	In-band emissions	182
6.4D.2.4	EVM equalizer spectrum flatness for UL MIMO	182
6.4D.3	Time alignment error for UL MIMO	182
6.4D.4	Requirements for coherent UL MIMO	182
6.4E	Transmit signal quality for V2X.....	183
6.4E.1	Frequency error for V2X	183
6.4E.1.1	General	183
6.4E.1.2	Frequency error for V2X concurrent operation.....	183
6.4E.2	Transmit modulation quality for V2X	183
6.4E.2.1	General	183
6.4E.2.2	Error Vector Magnitude for V2X.....	184
6.4E.2.3	Carrier leakage for V2X.....	184
6.4E.2.4	In-band emissions for V2X	184
6.4E.2.5	EVM equalizer spectrum flatness for V2X	184
6.4E.2.6	Transmit modulation quality for V2X concurrent operation.....	184
6.4F	Transmit signal quality for shared spectrum channel access.....	184
6.4F.1	Frequency error.....	184
6.4F.2	Transmit modulation quality.....	184
6.4F.2.0	General	184
6.4F.2.1	Error Vector Magnitude	185
6.4F.2.2	Carrier leakage	185
6.4F.2.3	In-band emissions	185
6.4F.2.4	EVM equalizer spectrum flatness	186
6.4F.2A	Transmit modulation quality for CA.....	186
6.4F.2A.1	Transmit modulation quality for inter-band CA.....	186
6.5	Output RF spectrum emissions.....	186
6.5.1	Occupied bandwidth	186
6.5.2	Out of band emission	186
6.5.2.1	General	186
6.5.2.2	Spectrum emission mask.....	187
6.5.2.3	Additional spectrum emission mask	187
6.5.2.3.1	Requirements for network signalling value "NS_35".....	187
6.5.2.3.2	Requirements for network signalling value "NS_04".....	188

6.5.2.3.3	Requirements for network signalling values "NS_03", "NS_03U", and "NS_21"	189
6.5.2.3.4	Requirements for network signalling value "NS_06"	189
6.5.2.3.5	Void	190
6.5.2.3.6	Void	190
6.5.2.3.7	Void	190
6.5.2.3.8	Requirements for network signalling value "NS_27"	190
6.5.2.4	Adjacent channel leakage ratio	190
6.5.2.4.1	NR ACLR	190
6.5.2.4.2	UTRA ACLR	191
6.5.3	Spurious emissions	191
6.5.3.0	General	191
6.5.3.1	General spurious emissions	192
6.5.3.2	Spurious emissions for UE co-existence	192
6.5.3.3	Additional spurious emissions	198
6.5.3.3.1	Requirement for network signalling value "NS_04"	199
6.5.3.3.2	Requirement for network signalling value "NS_17"	199
6.5.3.3.3	Requirement for network signalling value "NS_18"	199
6.5.3.3.4	Requirement for network signalling values "NS_05" and "NS_05U"	199
6.5.3.3.5	Requirement for network signalling values "NS_43" and "NS_43U"	200
6.5.3.3.6	Requirement for network signalling value "NS_37"	200
6.5.3.3.7	Requirement for network signalling value "NS_38"	200
6.5.3.3.8	Requirement for network signalling value "NS_39"	200
6.5.3.3.9	Requirement for network signalling value "NS_40"	201
6.5.3.3.10	Requirement for network signalling value "NS_41"	201
6.5.3.3.11	Requirement for network signalling value "NS_42"	201
6.5.3.3.12	Requirement for network signalling value "NS_21"	201
6.5.3.3.13	Requirement for network signalling value "NS_24"	202
6.5.3.3.14	Requirement for network signalling value "NS_27"	202
6.5.3.3.15	Requirement for network signalling value "NS_47"	202
6.5.3.3.16	Requirement for network signalling value "NS_50"	203
6.5.3.3.17	Requirement for network signalling value "NS_12"	203
6.5.3.3.18	Requirement for network signalling value "NS_13"	203
6.5.3.3.19	Requirement for network signalling value "NS_14"	203
6.5.3.3.20	Requirement for network signalling value "NS_15"	204
6.5.3.3.21	Requirement for network signalling value "NS_45"	204
6.5.3.3.22	Requirement for network signalling values "NS_48" and "NS_51"	204
6.5.3.3.23	Requirement for network signalling value "NS_49"	205
6.5.3.3.24	Requirement for network signalling value "NS_44"	205
6.5.3.3.25	Requirement for network signalling value "NS_46"	205
6.5.4	Transmit intermodulation	206
6.5.A	Output RF spectrum emissions for CA	206
6.5.A.0	General	206
6.5.A.1	Occupied bandwidth for CA	206
6.5.A.1.1	Void	206
6.5.A.1.1a	Occupied bandwidth for Intra-band contiguous CA	206
6.5.A.1.2	Occupied bandwidth for Intra-band non-contiguous CA	206
6.5.A.1.3	Occupied bandwidth for Inter-band CA	206
6.5.A.2	Out of band emission for CA	207
6.5.A.2.1	General	207
6.5.A.2.2	Spectrum emission mask	207
6.5.A.2.2.1	Spectrum emission mask for intra-band contiguous CA	207
6.5.A.2.2.2	Spectrum emission mask for intra-band non-contiguous CA	207
6.5.A.2.2.3	Spectrum emission mask for Inter-band CA	207
6.5.A.2.2.4	Void	208
6.5.A.2.3	Additional spectrum emission mask for CA	208
6.5.A.2.3.1	Additional spectrum emission mask for intra-band contiguous CA	208
6.5.A.2.3.1	Void	208
6.5.A.2.3.2	Additional spectrum emission mask for Intra-band non-contiguous CA	208
6.5.A.2.3.2.1	Minimum requirement (network signalling value "CA_NC_NS_04")	208
6.5.A.2.3.3	Additional spectrum emission mask for Inter-band CA	209
6.5.A.2.4	Adjacent channel leakage ratio	209
6.5.A.2.4.1	NR ACLR	209

6.5A.2.4.2	UTRA ACLR	210
6.5A.3	Spurious emission for CA.....	210
6.5A.3.1	General spurious emissions.....	210
6.5A.3.2	Spurious emissions for UE co-existence.....	211
6.5A.3.2.1	Spurious emissions for UE co-existence for intra-band contiguous CA.....	211
6.5A.3.2.2	Spurious emissions for UE co-existence for intra-band non-contiguous CA.....	212
6.5A.3.2.3	Spurious emissions for UE co-existence for Inter-band CA.....	212
6.5A.3.2.4	Void.....	214
6.5A.3.2.5	Void.....	214
6.5A.3.2.6	Void.....	214
6.5A.3.3	Additional spurious emissions for CA.....	214
6.5A.3.3.1	Additional spurious emissions for intra-band contiguous CA.....	214
6.5A.3.3.2	Additional spurious emissions for intra-band non-contiguous CA.....	215
6.5A.4	Transmit intermodulation for CA.....	215
6.5A.4.2.1	Transmit intermodulation for intra-band contiguous CA.....	215
6.5A.4.2.2	Void.....	216
6.5B	Output RF spectrum emissions for NR-DC.....	216
6.5D	Output RF spectrum emissions for UL MIMO.....	216
6.5D.1	Occupied bandwidth for UL MIMO.....	216
6.5D.2	Out of band emission for UL MIMO.....	216
6.5D.3	Spurious emission for UL MIMO.....	217
6.5D.4	Transmit intermodulation for UL MIMO.....	217
6.5E	Output RF spectrum emissions for V2X.....	217
6.5E.1	Occupied bandwidth for V2X.....	217
6.5E.1.1	General.....	217
6.5E.1.2	Occupied bandwidth for V2X concurrent operation.....	217
6.5E.2	Out of band emission for V2X.....	217
6.5E.2.1	General.....	217
6.5E.2.2	Spectrum emission mask.....	218
6.5E.2.2.1	General.....	218
6.5E.2.2.2	Spectrum emission mask for V2X concurrent operation.....	218
6.5E.2.3	Additional Spectrum emission mask.....	218
6.5E.2.3.1	Requirements for network signalling value "NS_33".....	218
6.5E.2.3.2	Requirements for network signalling value "NS_52".....	218
6.5E.2.4	Adjacent channel leakage ratio.....	219
6.5E.2.4.1	General.....	219
6.5E.2.4.2	ACLR for V2X concurrent operation.....	219
6.5E.3	Spurious emissions for V2X.....	219
6.5E.3.1	General spurious emissions.....	219
6.5E.3.2	Spurious emissions for UE co-existence.....	219
6.5E.3.3	Spurious emissions for UE co-existence for V2X concurrent operation.....	220
6.5E.3.4	Additional spurious emissions requirements for V2X.....	220
6.5E.3.4.1	General.....	220
6.5E.3.4.2	Requirements for network signalling value "NS_33".....	220
6.5E.3.4.3	Void.....	221
6.5E.4	Transmit intermodulation.....	221
6.5E.4.1	General.....	221
6.5E.4.2	Transmit intermodulation for V2X concurrent operation.....	221
6.5F	Output RF spectrum emissions.....	221
6.5F.1	Occupied bandwidth.....	221
6.5F.2	Out of band emission.....	221
6.5F.2.1	General.....	221
6.5F.2.2	Spectrum emission mask for operation with shared spectrum channel access.....	221
6.5F.2.2.0	General.....	221
6.5F.2.2.1	Spectrum emission mask for non-transmitted channels.....	222
6.5F.2.3	Additional spectrum emission mask.....	222
6.5F.2.4	Adjacent channel leakage ratio.....	222
6.5F.2.4.0	General.....	222
6.5F.2.4.1	Shared spectrum channel access ACLR.....	223
6.5F.2.4.2	Additional requirement for network signaled value "NS_29".....	223
6.5F.3	Spurious emissions.....	223
6.5F.3.0	General.....	223

6.5F.3.1	General spurious emissions	223
6.5F.3.2	Spurious emissions for UE co-existence	223
6.5F.3.3	Additional spurious emissions	224
6.5F.3.3.0	General	224
6.5F.3.3.1	Requirement for network signalling value "NS_28"	224
6.5F.3.3.2	Requirement for network signalling value "NS_29"	224
6.5F.3.3.3	Requirement for network signalling value "NS_30"	226
6.5F.3.3.4	Requirement for network signalling value "NS_31"	226
6.5F.3.3.5	Requirements for network signalling value "NS_53" or "NS_54"	227
6.5F.4	Transmit intermodulation	227
6.6	Void	227
6.6E	Time alignment error	227
7	Receiver characteristics	228
7.1	General	228
7.1A	General	228
7.1F	General	229
7.2	Diversity characteristics	229
7.3	Reference sensitivity	229
7.3.1	General	229
7.3.2	Reference sensitivity power level	229
7.3.3	$\Delta R_{IB,c}$	236
7.3A	Reference sensitivity for CA	236
7.3A.1	General	236
7.3A.2	Reference sensitivity power level for CA	237
7.3A.2.1	Reference sensitivity power level for Intra-band contiguous CA	237
7.3A.2.2	Reference sensitivity power level for Intra-band non-contiguous CA	237
7.3A.2.3	Reference sensitivity power level for Inter-band CA	238
7.3A.2.4	Void	238
7.3A.3	$\Delta R_{IB,c}$ for CA	238
7.3A.3.1	General	238
7.3A.3.2	$\Delta R_{IB,c}$ for Inter-band CA	238
7.3A.3.2.1	$\Delta R_{IB,c}$ for two bands	239
7.3A.3.2.2	Void	240
7.3A.3.2.3	$\Delta R_{IB,c}$ for three bands	240
7.3A.3.2.4	$\Delta R_{IB,c}$ for four bands	242
7.3A.4	Reference sensitivity exceptions due to UL harmonic interference for CA	242
7.3A.5	Reference sensitivity exceptions due to intermodulation interference due to 2UL CA	245
7.3A.6	Reference sensitivity exceptions due to cross band isolation for CA	249
7.3B	Reference sensitivity for NR-DC	250
7.3C	Reference sensitivity for SUL	250
7.3C.1	General	250
7.3C.2	Reference sensitivity power level for SUL	250
7.3C.3	$\Delta R_{IB,c}$ for SUL	252
7.3C.3.1	General	252
7.3C.3.2	SUL band combination	252
7.3C.3.2.1	$\Delta R_{IB,c}$ for two bands	253
7.3D	Reference sensitivity for UL MIMO	253
7.3E	Reference sensitivity for V2X	253
7.3E.1	General	253
7.3E.2	Minimum requirements	253
7.3E.3	Reference sensitivity power level for V2X concurrent operation	254
7.3F	Reference sensitivity for shared spectrum channel access	254
7.3F.1	General	254
7.3F.2	Reference sensitivity power level	255
7.3F.3	$\Delta R_{IB,c}$	256
7.3F.4	Intra-band contiguous shared spectrum channel access CA	256
7.3F.5	Inter-band CA with shared spectrum channel access	256
7.3F.5.1	Reference sensitivity exceptions due to UL harmonic interference	256
7.3F.5.2	Reference sensitivity exceptions due to receiver harmonic mixing	257
7.3F.5.3	Reference sensitivity exceptions due to cross band isolation	257
7.4	Maximum input level	258

7.4A	Maximum input level for CA	258
7.4A.1	Maximum input level for Intra-band contiguous CA	258
7.4A.2	Maximum input level for Intra-band non-contiguous CA	258
7.4A.3	Maximum input level for Inter-band CA	259
7.4B	Maximum input level for NR-DC	259
7.4D	Maximum input level for UL MIMO	259
7.4E	Maximum input level for V2X	259
7.4E.1	General	259
7.4E.2	Maximum input level for V2X concurrent operation	259
7.5	Adjacent channel selectivity	259
7.5A	Adjacent channel selectivity for CA	263
7.5A.1	Adjacent channel selectivity for Intra-band contiguous CA	263
7.5A.2	Adjacent channel selectivity Intra-band non-contiguous CA	265
7.5A.3	Adjacent channel selectivity Inter-band CA	265
7.5B	Adjacent channel selectivity for NR-DC	266
7.5D	Adjacent channel selectivity for UL MIMO	266
7.5E	Adjacent channel selectivity for V2X	266
7.5E.1	General	266
7.5E.2	Adjacent channel selectivity for V2X concurrent operation	267
7.5F	Adjacent channel selectivity	267
7.5F.1	General	267
7.5F.2	Intra-band contiguous shared spectrum channel access CA	268
7.6	Blocking characteristics	268
7.6.1	General	268
7.6.2	In-band blocking	268
7.6.3	Out-of-band blocking	271
7.6.4	Narrow band blocking	273
7.6A	Blocking characteristics for CA	275
7.6A.1	General	275
7.6A.2	In-band blocking for CA	275
7.6A.2.1	In-band blocking for Intra-band contiguous CA	275
7.6A.2.2	In-band blocking for Intra-band non-contiguous CA	276
7.6A.2.3	In-band blocking for Inter-band CA	276
7.6A.3	Out-of-band blocking for CA	277
7.6A.3.1	Out-of-band blocking for Intra-band contiguous CA	277
7.6A.3.2	Out-of-band blocking for Intra-band non-contiguous CA	278
7.6A.3.3	Out-of-band blocking for Inter-band CA	278
7.6A.4	Narrow band blocking for CA	279
7.6A.4.1	Narrow band blocking for Intra-band contiguous CA	279
7.6A.4.2	Narrow band blocking for Intra-band non-contiguous CA	280
7.6A.4.3	Narrow band blocking for Inter-band CA	280
7.6B	Blocking characteristics for NR-DC	280
7.6C	Blocking characteristics for SUL	281
7.6C.1	General	281
7.6C.2	In-band blocking for SUL	281
7.6C.3	Out-of-band blocking for SUL	281
7.6C.4	Narrow band blocking for SUL	281
7.6D	Blocking characteristics for UL MIMO	281
7.6E	Blocking characteristics for V2X	282
7.6E.1	General	282
7.6E.2	In-band blocking	282
7.6E.2.1	General	282
7.6E.2.2	In-band blocking for V2X concurrent operation	282
7.6E.3	Out-of-band blocking	283
7.6E.3.1	General	283
7.6E.3.2	Out-of-band blocking for V2X concurrent operation	283
7.6F	Blocking characteristics	283
7.6F.1	General	283
7.6F.2	In-band blocking	284
7.6F.2.1	General	284
7.6F.2.2	Intra-band contiguous shared spectrum channel access CA	284
7.6F.3	Out-of-band blocking	285

7.6F.3.1	General	285
7.6F.3.2	Intra-band contiguous shared spectrum channel access CA	286
7.7	Spurious response	287
7.7A	Spurious response for CA	288
7.7A.1	Spurious response for Intra-band contiguous CA	288
7.7A.2	Spurious response for Intra-band non-contiguous CA	288
7.7A.3	Spurious response for Inter-band CA	288
7.7B	Spurious response for NR-DC	289
7.7D	Spurious response for UL MIMO	289
7.7E	Spurious response for V2X	289
7.7E.1	General	289
7.7E.2	Spurious response for V2X concurrent operation	289
7.7F	Spurious response for shared spectrum channel access	290
7.7F.1	General	290
7.7F.2	Intra-band contiguous shared spectrum channel access CA	290
7.8	Intermodulation characteristics	291
7.8.1	General	291
7.8.2	Wide band Intermodulation	291
7.8A	Intermodulation characteristics for CA	292
7.8A.1	General	292
7.8A.2	Wide band intermodulation for CA	292
7.8A.2.1	Wide band intermodulation for Intra-band contiguous CA	292
7.8A.2.2	Wide band intermodulation for Intra-band non-contiguous CA	293
7.8A.2.3	Wide band intermodulation for Inter-band CA	293
7.8B	Intermodulation characteristics for NR-DC	293
7.8D	Intermodulation characteristics for UL MIMO	294
7.8E	Intermodulation characteristics for V2X	294
7.8E.1	General	294
7.8E.2	Wide band Intermodulation	294
7.8E.2.1	General	294
7.8E.2.2	Wide band Intermodulation for V2X concurrent operation	294
7.8F	Intermodulation characteristics for shared spectrum channel access	294
7.8F.1	General	294
7.8F.2	Wide band Intermodulation	295
7.9	Spurious emissions	295
7.9A	Spurious emissions for CA	296
7.9A.1	Void	296
7.9A.2	Void	296
7.9A.3	Spurious emissions for Inter-band CA	296
7.9B	Spurious emissions for NR-DC	296
Annex A (normative): Measurement channels		297
A.1	General	297
A.2	UL reference measurement channels	297
A.2.1	General	297
A.2.2	Reference measurement channels	299
A.2.2.1	DFT-s-OFDM Pi/2-BPSK	299
A.2.2.2	DFT-s-OFDM QPSK	300
A.2.2.3	DFT-s-OFDM 16QAM	301
A.2.2.4	DFT-s-OFDM 64QAM	302
A.2.2.5	DFT-s-OFDM 256QAM	303
A.2.2.6	CP-OFDM QPSK	304
A.2.2.7	CP-OFDM 16QAM	306
A.2.2.8	CP-OFDM 64QAM	308
A.2.2.9	CP-OFDM 256QAM	310
A.2.3	Reference measurement channels for TDD	312
A.2.3.1	DFT-s-OFDM Pi/2-BPSK	312
A.2.3.2	DFT-s-OFDM QPSK	312
A.2.3.3	DFT-s-OFDM 16QAM	312
A.2.3.4	DFT-s-OFDM 64QAM	312
A.2.3.5	DFT-s-OFDM 256QAM	312

A.2.3.6	CP-OFDM QPSK	313
A.2.3.7	CP-OFDM 16QAM	313
A.2.3.8	CP-OFDM 64QAM	313
A.2.3.9	CP-OFDM 256QAM	313
A.3	DL reference measurement channels	314
A.3.1	General	314
A.3.2	DL reference measurement channels for FDD	316
A.3.2.1	General.....	316
A.3.2.2	FRC for receiver requirements for QPSK.....	316
A.3.2.3	FRC for maximum input level for 64QAM.....	318
A.3.2.4	FRC for maximum input level for 256 QAM	321
A.3.3	DL reference measurement channels for TDD.....	324
A.3.3.1	General.....	324
A.3.3.2	FRC for receiver requirements for QPSK.....	324
A.3.3.3	FRC for maximum input level for 64QAM.....	328
A.3.3.4	FRC for maximum input level for 256 QAM	331
A.4	CSI reference measurement channels.....	334
A.5	OFDMA Channel Noise Generator (OCNG)	334
A.5.1	OCNG Patterns for FDD	334
A.5.1.1	OCNG FDD pattern 1: Generic OCNG FDD Pattern for all unused REs.....	334
A.5.2	OCNG Patterns for TDD.....	334
A.5.2.1	OCNG TDD pattern 1: Generic OCNG TDD Pattern for all unused REs	334
A.6	Void.....	335
A.7	V2X reference measurement channels	335
A.7.1	General	335
A.7.2	FRC for V2X receiver requirements for QPSK.....	335
A.7.3	FRC for maximum input level for 64QAM.....	337
A.7.4	FRC for maximum input level for 256QAM.....	338
Annex B (informative):	Void	340
Annex C (informative):	Downlink physical channels.....	341
C.1	General	341
C.2	Setup.....	341
C.3	Connection	341
C.3.1	Measurement of Receiver Characteristics	341
Annex D (normative):	Characteristics of the interfering signal	342
D.1	General.....	342
D.2	Void.....	342
Annex E (normative):	Environmental conditions	343
E.1	General	343
E.2	Environmental	343
E.2.1	Temperature	343
E.2.2	Voltage	343
E.2.3	Vibration.....	344
Annex F (normative):	Transmit modulation.....	345
F.0	General	345
F.1	Measurement Point.....	345
F.2	Basic Error Vector Magnitude measurement	345