

ETSI TS 138 101-1 V17.21.0 (2026-04)



TECHNICAL SPECIFICATION

**5G;
NR;
User Equipment (UE) radio transmission and reception;
Part 1: Range 1 Standalone
(3GPP TS 38.101-1 version 17.21.0 Release 17)**



ReferenceRTS/TSGR-0438101-1vh0

Keywords5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed, this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our [Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2026.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by the ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found at [3GPP to ETSI numbering cross-referencing](#).

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	19
1 Scope	21
2 References	21
3 Definitions, symbols and abbreviations	22
3.1 Definitions	22
3.2 Symbols.....	23
3.3 Abbreviations	25
4 General	26
4.1 Relationship between minimum requirements and test requirements	26
4.2 Applicability of minimum requirements	26
4.3 Specification suffix information.....	27
5 Operating bands and channel arrangement.....	28
5.1 General	28
5.2 Operating bands.....	28
5.2A Operating bands for CA	30
5.2A.0 General.....	30
5.2A.1 Intra-band CA	30
5.2A.2 Inter-band CA	31
5.2A.2.1 Inter-band CA (two bands).....	31
5.2A.2.2 Inter-band CA (three bands).....	35
5.2A.2.3 Inter-band CA (four bands).....	38
5.2A.2.4 Inter-band CA (five bands).....	40
5.2B Operating bands for DC	40
5.2C Operating band combination for SUL	40
5.2D Operating bands for UL MIMO	42
5.2E Operating band for V2X.....	43
5.2E.1 V2X operating bands	43
5.2E.2 V2X operating bands for concurrent operation.....	43
5.3 UE channel bandwidth	44
5.3.1 General.....	44
5.3.2 Maximum transmission bandwidth configuration	45
5.3.3 Minimum guardband and transmission bandwidth configuration.....	45
5.3.4 RB alignment.....	47
5.3.5 UE channel bandwidth per operating band	47
5.3.6 Asymmetric channel bandwidths	51
5.3A UE channel bandwidth for CA	52
5.3A.1 General.....	52
5.3A.2 Maximum transmission bandwidth configuration for CA	52
5.3A.3 Minimum guardband and transmission bandwidth configuration for CA	52
5.3A.4 Void	54
5.3A.5 UE channel bandwidth per operating band for CA	54
5.3E Channel bandwidth for V2X	55
5.3E.1 General.....	55
5.3E.2 Channel bandwidth for V2X concurrent operation.....	56
5.3I Channel bandwidth for RedCap	57
5.4 Channel arrangement.....	57
5.4.1 Channel spacing.....	57
5.4.1.1 Channel spacing for adjacent NR carriers.....	57
5.4.2 Channel raster	57
5.4.2.1 NR-ARFCN and channel raster.....	57

5.4.2.2	Channel raster to resource element mapping.....	58
5.4.2.3	Channel raster entries for each operating band	58
5.4.3	Synchronization raster	61
5.4.3.1	Synchronization raster and numbering.....	61
5.4.3.2	Synchronization raster to synchronization block resource element mapping.....	61
5.4.3.3	Synchronization raster entries for each operating band.....	61
5.4.4	TX–RX frequency separation	63
5.4A	Channel arrangement for CA.....	64
5.4A.1	Channel spacing for CA.....	64
5.4A.2	Channel raster for CA.....	64
5.4A.3	Synchronization raster for CA	65
5.4A.4	Tx-Rx frequency separation for CA.....	65
5.4B	Reserved.....	65
5.4C	Reserved.....	65
5.4D	Reserved.....	65
5.4E	Channel arrangement for V2X	65
5.4E.1	Channel spacing.....	65
5.4E.2	Channel raster	65
5.4E.2.1	NR-ARFCN and channel raster.....	65
5.4E.2.2	Channel raster to resource element mapping.....	65
5.4E.2.3	Channel raster entries for each operating band	65
5.4E.3	Synchronization raster for V2X.....	66
5.4I	Channel arrangement for RedCap	66
5.4I.1	Channel spacing for RedCap	66
5.4I.2	Channel raster for RedCap.....	66
5.4I.2.1	NR-ARFCN and channel raster.....	66
5.4I.2.2	Channel raster to resource element mapping.....	66
5.4I.2.3	Channel raster entries for each operating band	66
5.4I.3	Synchronization raster for RedCap.....	66
5.4I.4	Tx-Rx frequency separation for RedCap	66
5.5	Void.....	67
5.5A	Configurations for CA.....	67
5.5A.0	General.....	67
5.5A.1	Configurations for intra-band contiguous CA.....	67
5.5A.2	Configurations for intra-band non-contiguous CA	70
5.5A.3	Configurations for inter-band CA.....	74
5.5A.3.1	Configurations for inter-band CA (two bands)	74
5.5A.3.2	Configurations for inter-band CA (three bands)	104
5.5A.3.3	Configurations for inter-band CA (four bands).....	169
5.5A.3.4	Configurations for inter-band CA (five bands)	202
5.5B	Configurations for DC.....	205
5.5C	Configurations for SUL.....	209
6	Transmitter characteristics	215
6.1	General	215
6.1A	General	215
6.1F	General	215
6.2	Transmitter power	215
6.2.1	UE maximum output power.....	215
6.2.1I	Void	217
6.2.2	UE maximum output power reduction.....	217
6.2.3	UE additional maximum output power reduction.....	219
6.2.3.1	General	219
6.2.3.2	A-MPR for NS_04	223
6.2.3.3	A-MPR for NS_10	224
6.2.3.4	A-MPR for NS_05 and NS_05U.....	224
6.2.3.5	A-MPR for NS_40	228
6.2.3.6	A-MPR for NS_43 and NS_43U.....	228
6.2.3.7	A-MPR for NS_03 and NS_03U.....	229
6.2.3.8	A-MPR for NS_37	230
6.2.3.9	A-MPR for NS_38	231
6.2.3.10	A-MPR for NS_39	231

6.2.3.11	A-MPR for NS_41	231
6.2.3.12	A-MPR for NS_42	232
6.2.3.13	A-MPR for NS_18	232
6.2.3.14	A-MPR for NS_21	233
6.2.3.15	A-MPR for NS_24	234
6.2.3.16	A-MPR for NS_27	234
6.2.3.17	A-MPR for NS_46	236
6.2.3.18	A-MPR for NS_47	236
6.2.3.19	A-MPR for NS_50	238
6.2.3.20	A-MPR for NS_44	239
6.2.3.21	A-MPR for NS_12	240
6.2.3.22	A-MPR for NS_13	240
6.2.3.23	A-MPR for NS_14	241
6.2.3.24	A-MPR for NS_15	241
6.2.3.25	A-MPR for NS_45	242
6.2.3.26	A-MPR for NS_48	242
6.2.3.27	A-MPR for NS_49	244
6.2.3.28	A-MPR for NS_51	246
6.2.3.29	A-MPR for NS_07	246
6.2.3.30	A-MPR for NS_56	247
6.2.4	Configured transmitted power	247
6.2A	Transmitter power for CA	250
6.2A.0	General	250
6.2A.1	UE maximum output power for CA	250
6.2A.1.1	UE maximum output power for Intra-band contiguous CA	250
6.2A.1.2	UE maximum output power for Intra-band non-contiguous CA	251
6.2A.1.3	UE maximum output power for Inter-band CA	252
6.2A.1.4	Void	255
6.2A.1.5	Void	255
6.2A.2	UE maximum output power reduction for CA	255
6.2A.2.1	UE maximum output power reduction for Intra-band contiguous CA	255
6.2A.2.2	UE maximum output power reduction for Intra-band non-contiguous CA	258
6.2A.2.2.0	General	258
6.2A.2.2.1	MPR to meet -30dBm/MHz	259
6.2A.2.2.1.1	PC3 with indicating dualPA-Architecture supported	259
6.2A.2.2.1.2	PC2 with indicating dualPA-Architecture supported	260
6.2A.2.2.1.3	PC3 without indicating dualPA-Architecture supported	260
6.2A.2.2.1.4	PC2 without indicating dualPA-Architecture supported	260
6.2A.2.2.2	MPR to meet -13dBm/MHz	261
6.2A.2.2.2.1	PC3 with indicating dualPA-Architecture supported	261
6.2A.2.2.2.2	PC2 with indicating dualPA-Architecture supported	261
6.2A.2.2.2.3	PC3 without indicating dualPA-Architecture supported	262
6.2A.2.2.2.4	PC2 without indicating dualPA-Architecture supported	262
6.2A.2.3	UE maximum output power reduction for Inter-band CA	262
6.2A.2.4	Void	263
6.2A.3	UE additional maximum output power reduction for CA	263
6.2A.3.1	UE additional maximum output power reduction for Intra-band CA	263
6.2A.3.1.1	UE additional maximum output power reduction for Intra-band contiguous CA	263
6.2A.3.1.1.1	A-MPR for CA_NS_04	264
6.2A.3.1.1.1.2	Non-contiguous allocations	264
6.2A.3.1.2	UE additional maximum output power reduction for Intra-band non-contiguous CA	269
6.2A.3.1.3	UE additional maximum output power reduction for Inter-band CA	272
6.2A.4	Configured output power for CA	274
6.2A.4.1	Configured transmitted power level	274
6.2A.4.1.1	Configured transmitted power for Intra-band contiguous CA	274
6.2A.4.1.2	Configured transmitted power for Intra-band non-contiguous CA	276
6.2A.4.1.3	Configured transmitted power for Inter-band CA	278
6.2A.4.1.4	Void	282
6.2A.4.2	$\Delta T_{IB,c}$ for CA	282
6.2A.4.2.1	Void	282
6.2A.4.2.2	Void	282
6.2A.4.2.3	$\Delta T_{IB,c}$ for Inter-band CA (two bands)	282

6.2A.4.2.4	$\Delta T_{IB,c}$ for Inter-band CA (three bands)	288
6.2A.4.2.5	$\Delta T_{IB,c}$ for Inter-band CA (four bands)	296
6.2A.4.2.6	$\Delta T_{IB,c}$ for Inter-band CA (five bands)	301
6.2B	Transmitter power for NR-DC	302
6.2B.0	General	302
6.2B.1	UE maximum output power for NR-DC	302
6.2B.2	UE maximum output power reduction for NR-DC	303
6.2B.3	UE additional maximum output power reduction for NR-DC	303
6.2B.4.1	Configured transmitted power level for NR-DC	303
6.2B.4.2	$\Delta T_{IB,c}$ for NR-DC	307
6.2C	Transmitter power for SUL	307
6.2C.1	Configured transmitted power for SUL	307
6.2C.2	$\Delta T_{IB,c}$	308
6.2D	Transmitter power for UL MIMO	310
6.2D.1	UE maximum output power for UL MIMO	310
6.2D.2	UE maximum output power reduction for UL MIMO	311
6.2D.3	UE additional maximum output power reduction for UL MIMO	313
6.2D.4	Configured transmitted power for UL MIMO	313
6.2E	Transmitter power for V2X	314
6.2E.1	UE maximum output power for V2X	314
6.2E.1.1	General	314
6.2E.1.2	UE maximum output power for V2X concurrent operation	314
6.2E.2	UE maximum output power reduction for V2X	315
6.2E.2.1	General	315
6.2E.2.2	MPR for Power class 2 and Power class 3 V2X UE	315
6.2E.2.3	MPR for Power class 2 and Power class 3 V2X concurrent operation	317
6.2E.2.4	MPR for Power class 1 UE in Band n14	320
6.2E.3	UE additional maximum output power reduction for V2X	320
6.2E.3.1	General	320
6.2E.3.2	A-MPR for V2X UE by NS_33	321
6.2E.3.3	A-MPR for Power class 3 V2X UE by NS_52	324
6.2E.3.4	A-MPR for V2X concurrent operation	326
6.2E.4	Configured transmitted power for V2X	326
6.2E.4.1	General	326
6.2E.4.2	Configured transmitted power for inter-band V2X concurrent operation	327
6.2E.4.3	Configured transmitted power for intra-band V2X concurrent operation	327
6.2F	Transmitter power for shared spectrum channel access	330
6.2F.1	UE maximum output power	330
6.2F.1A	UE maximum output power for CA	331
6.2F.1A.1	UE maximum output power for inter-band CA	331
6.2F.1A.2	UE maximum output power for intra-band contiguous CA	331
6.2F.1B	UE maximum output power for NR-DC	331
6.2F.1D	UE maximum output power for UL MIMO	331
6.2F.2	UE maximum output power reduction	332
6.2F.2A	UE maximum output power reduction for CA	333
6.2F.2A.1	UE maximum output power reduction for inter-band CA	333
6.2F.2A.2	UE maximum output power reduction for intra-band contiguous CA	333
6.2F.2D	UE maximum output power reduction for UL MIMO	335
6.2F.3	UE additional maximum output power reduction	335
6.2F.3.1	General	335
6.2F.3.2	A-MPR for NS_28	336
6.2F.3.3	A-MPR for NS_29	336
6.2F.3.4	A-MPR for NS_30	337
6.2F.3.5	A-MPR for NS_31	337
6.2F.3.6	A-MPR for NS_53	338
6.2F.3.7	A-MPR for NS_54	338
6.2F.3.8	A-MPR for NS_58	339
6.2F.3.9	A-MPR for NS_59	339
6.2F.3.10	A-MPR for NS_60	340
6.2F.3.11	A-MPR for NS_61	340
6.2F.3A	UE additional maximum output power reduction for CA	341
6.2F.3A.1	UE additional maximum output power reduction for inter-band CA	341

6.2F.3D	UE additional maximum output power reduction for UL MIMO.....	341
6.2F.4	Configured transmitted power	341
6.2F.4D	Configured transmitted power UL MIMO	341
6.2G	Transmitter power for Tx Diversity.....	342
6.2G.1	UE maximum output power for Tx Diversity	342
6.2G.2	UE maximum output power reduction for Tx Diversity	342
6.2G.3	UE additional maximum output power reduction for Tx Diversity	342
6.2G.4	Configured transmitted power for Tx Diversity.....	342
6.2H	Transmitter power for CA with UL MIMO.....	343
6.2H.1	Transmitter power for intra-band UL contiguous CA with UL MIMO	343
6.2H.1.1	UE maximum output power for intra-band UL contiguous CA with UL MIMO	343
6.2H.1.2	UE maximum output power reduction for intra-band UL contiguous CA with UL MIMO	343
6.2H.1.3	UE additional maximum output power reduction for intra-band UL contiguous CA with UL MIMO	344
6.2H.1.4	Configured transmitted power for intra-band UL contiguous CA with UL MIMO	344
6.2I	Transmitter power for RedCap.....	344
6.2I.1	Maximum output power for RedCap	344
6.3	Output power dynamics.....	345
6.3.1	Minimum output power	345
6.3.2	Transmit OFF power.....	345
6.3.3	Transmit ON/OFF time mask	345
6.3.3.1	General	345
6.3.3.2	General ON/OFF time mask	346
6.3.3.3	Transmit power time mask for slot and short or long subslot boundaries.....	346
6.3.3.4	PRACH time mask.....	346
6.3.3.5	Void.....	348
6.3.3.6	SRS time mask	348
6.3.3.7	PUSCH-PUCCH and PUSCH-SRS time masks	349
6.3.3.8	Transmit power time mask for consecutive slot or long subslot transmission and short subslot transmission boundaries	350
6.3.3.9	Transmit power time mask for consecutive short subslot transmissions boundaries	351
6.3.4	Power control.....	352
6.3.4.1	General	352
6.3.4.2	Absolute power tolerance.....	352
6.3.4.3	Relative power tolerance.....	352
6.3.4.4	Aggregate power tolerance.....	353
6.3A	Output power dynamics for CA	353
6.3A.1	Minimum output power for CA	353
6.3A.1.1	Minimum output power for intra-band contiguous CA.....	353
6.3A.1.2	Minimum output power for intra-band non-contiguous CA	353
6.3A.1.3	Minimum output power for inter-band CA	353
6.3A.1.4	Void.....	354
6.3A.2	Transmit OFF power for CA.....	354
6.3A.2.1	Transmit OFF power for intra-band contiguous CA	354
6.3A.2.2	Transmit OFF power for intra-band non-contiguous CA.....	354
6.3A.2.3	Transmit OFF power for inter-band CA.....	354
6.3A.2.4	Void.....	354
6.3A.3	Transmit ON/OFF time mask for CA	354
6.3A.3.1	Transmit ON/OFF time mask for intra-band contiguous CA.....	354
6.3A.3.2	Transmit ON/OFF time mask for intra-band non-contiguous CA	354
6.3A.3.3	Transmit ON/OFF time mask for inter-band CA	355
6.3A.3.3.1	General	355
6.3A.3.3.2	Time mask for switching between two uplink carriers	355
6.3A.3.3.3	Time mask for switching between two uplink carriers with two transmit antenna connectors	356
6.3A.3.3.4	Time mask for switching between one uplink band with one transmit antenna connector and one uplink band with two transmit antenna connectors.....	358
6.3A.3.3.5	Time mask for switching between two uplink bands with two transmit antenna connectors	359
6.3A.3.4	Void.....	360
6.3A.4	Power control for CA.....	360
6.3A.4.1	Power control for intra-band contiguous CA	360
6.3A.4.1.1	Absolute power tolerance	360
6.3A.4.1.2	Relative power tolerance	361

6.3A.4.1.3	Aggregate power control tolerance.....	361
6.3A.4.2	Power control for intra-band non-contiguous CA	361
6.3A.4.2.1	Absolute power tolerance.....	361
6.3A.4.2.1.1	Minimum requirements	361
6.3A.4.2.2	Relative power tolerance	361
6.3A.4.2.2.1	Minimum requirements	361
6.3A.4.2.3	Aggregate power control tolerance	362
6.3A.4.3	Power control for inter-band CA.....	362
6.3A.4.4	Void.....	362
6.3B	Output power dynamics for NR-DC.....	362
6.3C	Output power dynamics for SUL	362
6.3C.1	Void	362
6.3C.2	Void	362
6.3C.3	Transmit ON/OFF time mask for SUL	362
6.3C.3.1	Time mask for switching between two uplink carriers.....	362
6.3C.3.2	Time mask for switching between two uplink carriers with two transmit antenna connectors	363
6.3C.3.3	Time mask for switching between one uplink band with one transmit antenna connector and one uplink band with two transmit antenna connectors	364
6.3C.3.4	Time mask for switching between two uplink bands with two transmit antenna connectors.....	366
6.3D	Output power dynamics for UL MIMO	367
6.3D.1	Minimum output power for UL MIMO	367
6.3D.2	Transmit OFF power for UL MIMO.....	367
6.3D.3	Transmit ON/OFF time mask for UL MIMO	367
6.3D.4	Power control for UL MIMO.....	367
6.3E	Output power dynamics for V2X	368
6.3E.1	Minimum output power for V2X.....	368
6.3E.1.1	General	368
6.3E.1.2	Minimum output power for V2X concurrent operation	368
6.3E.2	Transmit OFF power for V2X	368
6.3E.2.1	General	368
6.3E.2.2	Transmit OFF power for V2X concurrent operation.....	369
6.3E.3	Transmit ON/OFF time mask for V2X.....	369
6.3E.3.1	General	369
6.3E.3.2	General time mask.....	369
6.3E.3.3	S-SSB time mask	369
6.3E.3.4	Transmit ON/OFF time mask for V2X concurrent operation	370
6.3E.4	Power control for V2X	371
6.3E.4.1	General	371
6.3E.4.2	Absolute power tolerance.....	371
6.3E.4.3	Power control for V2X concurrent operation.....	371
6.3F	Output power dynamics for shared spectrum channel access.....	371
6.3F.1	Minimum output power	371
6.3F.2	Transmit OFF power.....	371
6.3F.3	Transmit ON/OFF time mask	372
6.3F.3.1	General	372
6.3F.3.2	General ON/OFF time mask	372
6.3F.3A	General ON/OFF mask for CA.....	372
6.3F.3A.1	General ON/OFF mask for inter-band CA	372
6.3F.4	Power control.....	372
6.3F.4.1	General	372
6.3F.4.2	Absolute power tolerance.....	372
6.3F.4.3	Relative power tolerance.....	373
6.3F.4.4	Aggregate power tolerance.....	373
6.3F.4A	Power control for inter-band CA	373
6.3G	Output power dynamics for Tx Diversity.....	373
6.3G.1	Minimum output power for Tx Diversity	373
6.3G.2	Transmit OFF power for Tx Diversity.....	373
6.3G.3	Transmit ON/OFF time mask for Tx Diversity	373
6.3G.4	Power control for Tx Diversity	373
6.3H	Output power dynamics for CA with UL MIMO.....	373
6.3H.1	Output power dynamics for intra-band UL contiguous CA with UL MIMO	373
6.3H.1.1	Minimum output power for intra-band UL contiguous CA with UL MIMO.....	373

6.3H.1.2	Transmit OFF power for intra-band UL contiguous CA with UL MIMO	374
6.3H.1.3	Transmit ON/OFF time mask for intra-band UL contiguous CA with UL MIMO	374
6.3H.1.4	Power control for intra-band UL contiguous CA with UL MIMO	374
6.4	Transmit signal quality	374
6.4.1	Frequency error	374
6.4.2	Transmit modulation quality	374
6.4.2.0	General	374
6.4.2.1	Error Vector Magnitude	375
6.4.2.1a	Error Vector Magnitude including symbols with transient period	375
6.4.2.2	Carrier leakage	376
6.4.2.3	In-band emissions	377
6.4.2.4	EVM equalizer spectrum flatness	378
6.4.2.4.1	Requirements for Pi/2 BPSK modulation	379
6.4.2.5	Phase continuity requirements for DMRS bundling	379
6.4A	Transmit signal quality for CA	381
6.4A.1	Frequency error for CA	381
6.4A.1.1	Frequency error for intra-band contiguous CA	381
6.4A.1.2	Frequency error for intra-band non-contiguous CA	381
6.4A.1.3	Frequency error for inter-band CA	381
6.4A.1.4	Void	381
6.4A.2	Transmit modulation quality for CA	381
6.4A.2.1	Transmit modulation quality for intra-band contiguous CA	381
6.4A.2.1.0	General	381
6.4A.2.1.1	Error Vector Magnitude	382
6.4A.2.1.2	In-band emissions	382
6.4A.2.1.3	Carrier leakage	384
6.4A.2.2	Transmit modulation quality for intra-band non-contiguous CA	384
6.4A.2.2.0	General	384
6.4A.2.2.1	Error Vector Magnitude	385
6.4A.2.2.2	In-band emissions	385
6.4A.2.2.3	Carrier leakage	385
6.4A.2.3	Transmit modulation quality for inter-band CA	385
6.4A.2.4	Void	386
6.4B	Transmit signal quality for NR-DC	386
6.4C	Transmit signal quality for SUL	386
6.4D	Transmit signal quality for UL MIMO	387
6.4D.0	General	387
6.4D.1	Frequency error for UL MIMO	387
6.4D.2	Transmit modulation quality for UL MIMO	387
6.4D.2.0	General	387
6.4D.2.1	Error Vector Magnitude	387
6.4D.2.2	Carrier leakage	388
6.4D.2.3	In-band emissions	388
6.4D.2.4	EVM equalizer spectrum flatness for UL MIMO	388
6.4D.3	Time alignment error for UL MIMO	388
6.4D.4	Requirements for coherent UL MIMO	388
6.4E	Transmit signal quality for V2X	389
6.4E.1	Frequency error for V2X	389
6.4E.1.1	General	389
6.4E.1.2	Frequency error for V2X concurrent operation	389
6.4E.2	Transmit modulation quality for V2X	389
6.4E.2.1	General	389
6.4E.2.2	Error Vector Magnitude for V2X	389
6.4E.2.3	Carrier leakage for V2X	389
6.4E.2.4	In-band emissions for V2X	390
6.4E.2.5	EVM equalizer spectrum flatness for V2X	390
6.4E.2.6	Transmit modulation quality for V2X concurrent operation	390
6.4F	Transmit signal quality for shared spectrum channel access	390
6.4F.1	Frequency error	390
6.4F.2	Transmit modulation quality	390
6.4F.2.0	General	390
6.4F.2.1	Error Vector Magnitude	390

6.4F.2.2	Carrier leakage	390
6.4F.2.3	In-band emissions	391
6.4F.2.4	EVM equalizer spectrum flatness	391
6.4F.2A	Transmit modulation quality for CA.....	392
6.4F.2A.1	Transmit modulation quality for inter-band CA.....	392
6.4G	Transmit signal quality for Tx Diversity	392
6.4G.1	Frequency error for Tx Diversity	392
6.4G.2	Transmit modulation quality for Tx Diversity	392
6.4G.2.0	General	392
6.4H	Transmit signal quality for CA with UL MIMO	393
6.4H.1	Transmit signal quality for intra-band UL contiguous CA with UL MIMO.....	393
6.4H.1.1	Frequency error for intra-band UL contiguous CA with UL MIMO	393
6.4H.1.2	Transmit modulation quality for intra-band UL contiguous CA with UL MIMO	393
6.4H.1.2.0	General	393
6.4H.1.2.1	Error Vector Magnitude.....	394
6.4H.1.2.2	Carrier leakage.....	394
6.4H.1.2.3	In-band emissions	394
6.4H.1.3	Time alignment error for intra-band UL contiguous CA with UL MIMO	394
6.4H.1.4	Coherent UL MIMO requirement for intra-band UL contiguous CA with UL MIMO.....	394
6.5	Output RF spectrum emissions.....	394
6.5.1	Occupied bandwidth	394
6.5.2	Out of band emission	394
6.5.2.1	General	394
6.5.2.2	Spectrum emission mask	395
6.5.2.3	Additional spectrum emission mask	395
6.5.2.3.1	Requirements for network signalling value "NS_35"	395
6.5.2.3.2	Requirements for network signalling value "NS_04"	396
6.5.2.3.3	Requirements for network signalling values "NS_03" and "NS_03U"	396
6.5.2.3.4	Requirements for network signalling value "NS_06" or "NS_07"	397
6.5.2.3.5	Void	398
6.5.2.3.6	Void	398
6.5.2.3.7	Void	398
6.5.2.3.8	Requirements for network signalling value "NS_27"	398
6.5.2.3.9	Requirements for network signalling value "NS_21"	398
6.5.2.4	Adjacent channel leakage ratio	399
6.5.2.4.1	NR ACLR.....	399
6.5.2.4.2	UTRA ACLR	399
6.5.3	Spurious emissions	400
6.5.3.0	General	400
6.5.3.1	General spurious emissions	400
6.5.3.2	Spurious emissions for UE co-existence	401
6.5.3.3	Additional spurious emissions	408
6.5.3.3.1	Requirement for network signalling value "NS_04"	408
6.5.3.3.2	Requirement for network signalling value "NS_17"	408
6.5.3.3.3	Requirement for network signalling value "NS_18"	408
6.5.3.3.4	Requirement for network signalling values "NS_05" and "NS_05U"	408
6.5.3.3.5	Requirement for network signalling values "NS_43" and "NS_43U"	409
6.5.3.3.6	Requirement for network signalling value "NS_37"	409
6.5.3.3.7	Requirement for network signalling value "NS_38"	409
6.5.3.3.8	Requirement for network signalling value "NS_39"	409
6.5.3.3.9	Requirement for network signalling value "NS_40"	410
6.5.3.3.10	Requirement for network signalling value "NS_41"	410
6.5.3.3.11	Requirement for network signalling value "NS_42"	410
6.5.3.3.12	Requirement for network signalling value "NS_21"	411
6.5.3.3.13	Requirement for network signalling value "NS_24"	411
6.5.3.3.14	Requirement for network signalling value "NS_27"	411
6.5.3.3.15	Requirement for network signalling value "NS_47"	411
6.5.3.3.16	Requirement for network signalling value "NS_50"	412
6.5.3.3.17	Requirement for network signalling value "NS_12"	412
6.5.3.3.18	Requirement for network signalling value "NS_13"	412
6.5.3.3.19	Requirement for network signalling value "NS_14"	413
6.5.3.3.20	Requirement for network signalling value "NS_15"	413

6.5.3.3.21	Requirement for network signalling value "NS_45"	413
6.5.3.3.22	Requirement for network signalling values "NS_48" and "NS_51"	414
6.5.3.3.23	Requirement for network signalling value "NS_49"	414
6.5.3.3.24	Requirement for network signalling value "NS_44"	414
6.5.3.3.25	Requirement for network signalling value "NS_46"	414
6.5.3.3.26	Requirement for network signalling value "NS_07"	415
6.5.3.3.27	Requirement for network signalling value "NS_56"	415
6.5.4	Transmit intermodulation	415
6.5A	Output RF spectrum emissions for CA.....	416
6.5A.0	General.....	416
6.5A.1	Occupied bandwidth for CA	416
6.5A.1.1	Void.....	416
6.5A.1.1a	Occupied bandwidth for Intra-band contiguous CA	416
6.5A.1.2	Occupied bandwidth for Intra-band non-contiguous CA	416
6.5A.1.3	Occupied bandwidth for Inter-band CA	416
6.5A.2	Out of band emission for CA	416
6.5A.2.1	General	416
6.5A.2.2	Spectrum emission mask	417
6.5A.2.2.1	Spectrum emission mask for intra-band contiguous CA	417
6.5A.2.2.2	Spectrum emission mask for intra-band non-contiguous CA	417
6.5A.2.2.3	Spectrum emission mask for Inter-band CA	417
6.5A.2.2.4	Void	418
6.5A.2.3	Additional spectrum emission mask for CA	418
6.5A.2.3.1	Additional spectrum emission mask for intra-band contiguous CA	418
6.5A.2.3.2	Additional spectrum emission mask for Intra-band non-contiguous CA.....	418
6.5A.2.3.3	Additional spectrum emission mask for Inter-band CA	419
6.5A.2.4	Adjacent channel leakage ratio	419
6.5A.2.4.1	NR ACLR	419
6.5A.2.4.2	UTRA ACLR	420
6.5A.3	Spurious emission for CA.....	421
6.5A.3.1	General spurious emissions	421
6.5A.3.2	Spurious emissions for UE co-existence	422
6.5A.3.2.1	Spurious emissions for UE co-existence for intra-band contiguous CA.....	422
6.5A.3.2.2	Spurious emissions for UE co-existence for intra-band non-contiguous CA	423
6.5A.3.2.3	Spurious emissions for UE co-existence for Inter-band CA	424
6.5A.3.2.4	Void	428
6.5A.3.2.5	Void	428
6.5A.3.2.6	Void	428
6.5A.3.3	Additional spurious emissions for CA	428
6.5A.3.3.1	Additional spurious emissions for intra-band contiguous CA	428
6.5A.3.3.2	Additional spurious emissions for intra-band non-contiguous CA.....	429
6.5A.4	Transmit intermodulation for CA	429
6.5A.4.2.1	Transmit intermodulation for intra-band contiguous CA	429
6.5A.4.2.2	Void	430
6.5B	Output RF spectrum emissions for NR-DC.....	430
6.5D	Output RF spectrum emissions for UL MIMO.....	430
6.5D.1	Occupied bandwidth for UL MIMO	430
6.5D.2	Out of band emission for UL MIMO	431
6.5D.3	Spurious emission for UL MIMO.....	431
6.5D.4	Transmit intermodulation for UL MIMO	431
6.5E	Output RF spectrum emissions for V2X	431
6.5E.1	Occupied bandwidth for V2X.....	431
6.5E.1.1	General	431
6.5E.1.2	Occupied bandwidth for V2X concurrent operation	432
6.5E.2	Out of band emission for V2X.....	432
6.5E.2.1	General	432
6.5E.2.2	Spectrum emission mask	432
6.5E.2.2.1	General	432
6.5E.2.2.2	Spectrum emission mask for V2X concurrent operation	432
6.5E.2.3	Additional Spectrum emission mask.....	432
6.5E.2.3.1	Requirements for network signalling value "NS_33".....	432
6.5E.2.3.2	Requirements for network signalling value "NS_52".....	433

6.5E.2.3.3	Requirements for network signalling value "NS_06"	433
6.5E.2.4	Adjacent channel leakage ratio	434
6.5E.2.4.1	General	434
6.5E.2.4.2	ACLR for V2X concurrent operation	434
6.5E.3	Spurious emissions for V2X	434
6.5E.3.1	General spurious emissions	434
6.5E.3.2	Spurious emissions for UE co-existence	434
6.5E.3.3	Spurious emissions for UE co-existence for V2X concurrent operation	434
6.5E.3.4	Additional spurious emissions requirements for V2X	435
6.5E.3.4.1	General	435
6.5E.3.4.2	Requirements for network signalling value "NS_33"	435
6.5E.3.4.3	Void	436
6.5E.4	Transmit intermodulation	436
6.5E.4.1	General	436
6.5E.4.2	Transmit intermodulation for V2X concurrent operation	436
6.5F	Output RF spectrum emissions for shared spectrum channel access	436
6.5F.1	Occupied bandwidth	436
6.5F.2	Out of band emission	436
6.5F.2.1	General	436
6.5F.2.2	Spectrum emission mask for operation with shared spectrum channel access	437
6.5F.2.2.0	General	437
6.5F.2.2.1	Spectrum emission mask for non-transmitted channels	437
6.5F.2.3	Additional spectrum emission mask	437
6.5F.2.4	Adjacent channel leakage ratio	438
6.5F.2.4.0	General	438
6.5F.2.4.1	Shared spectrum channel access ACLR	438
6.5F.2.4.2	Additional requirement for network signalled value "NS_29"	438
6.5F.2A	Out of band emission for CA	438
6.5F.2A.1	Spectrum emission mask for CA	438
6.5F.2A.1.1	Spectrum emission mask for Inter-band CA	438
6.5F.2A.1.2	Spectrum emission mask for Intra-band contiguous CA	439
6.5F.2A.1.2.1	General	439
6.5F.2A.1.2.2	Intra-band contiguous CA spectrum emission mask for non-transmitted channels	439
6.5F.2A.2	Adjacent channel leakage ratio for CA	439
6.5F.2A.2.1	Adjacent channel leakage ratio for inter-band CA	439
6.5F.2A.2.2	Adjacent channel leakage ratio for intra-band contiguous CA	440
6.5F.3	Spurious emissions	440
6.5F.3.0	General	440
6.5F.3.1	General spurious emissions	440
6.5F.3.2	Spurious emissions for UE co-existence	440
6.5F.3.3	Additional spurious emissions	441
6.5F.3.3.0	General	441
6.5F.3.3.1	Requirement for network signalling value "NS_28"	441
6.5F.3.3.2	Requirement for network signalling value "NS_29"	441
6.5F.3.3.3	Requirement for network signalling value "NS_30"	443
6.5F.3.3.4	Requirement for network signalling value "NS_31"	443
6.5F.3.3.5	Requirements for network signalling value "NS_53" or "NS_54" or "NS_60"	444
6.5F.3.3.6	Requirements for network signalling value "NS_58"	444
6.5F.3.3.7	Requirements for network signalling value "NS_61"	445
6.5F.4	Transmit intermodulation	445
6.5G	Output RF spectrum emissions for Tx Diversity	445
6.5G.1	Occupied bandwidth for Tx Diversity	445
6.5G.2	Out of band emission for Tx Diversity	445
6.5G.3	Spurious emission for Tx Diversity	445
6.5G.4	Transmit intermodulation for Tx Diversity	445
6.5H	Output RF spectrum emissions for CA with UL MIMO	446
6.5H.1	Output RF spectrum emissions for intra-band UL contiguous CA with UL MIMO	446
6.5H.1.1	Occupied bandwidth for intra-band UL contiguous CA with UL MIMO	446
6.5H.1.2	Out of band emission for intra-band UL contiguous CA with UL MIMO	446
6.5H.1.3	Spurious emission for intra-band UL contiguous CA with UL MIMO	446
6.5H.1.4	Transmit intermodulation for intra-band UL contiguous CA with UL MIMO	446
6.6	Void	446

6.6E	Time alignment error.....	446
7	Receiver characteristics.....	447
7.1	General.....	447
7.1A	General.....	447
7.1F	General.....	448
7.1I	General.....	448
7.2	Diversity characteristics.....	448
7.3	Reference sensitivity.....	448
7.3.1	General.....	448
7.3.2	Reference sensitivity power level.....	448
7.3.3	$\Delta R_{IB,c}$	456
7.3A	Reference sensitivity for CA.....	456
7.3A.1	General.....	456
7.3A.2	Reference sensitivity power level for CA.....	457
7.3A.2.1	Reference sensitivity power level for Intra-band contiguous CA.....	457
7.3A.2.2	Reference sensitivity power level for Intra-band non-contiguous CA.....	457
7.3A.2.3	Reference sensitivity power level for Inter-band CA.....	458
7.3A.2.4	Void.....	458
7.3A.3	$\Delta R_{IB,c}$ for CA.....	459
7.3A.3.1	General.....	459
7.3A.3.2	$\Delta R_{IB,c}$ for Inter-band CA.....	459
7.3A.3.2.1	$\Delta R_{IB,c}$ for two bands.....	459
7.3A.3.2.2	Void.....	462
7.3A.3.2.3	$\Delta R_{IB,c}$ for three bands.....	462
7.3A.3.2.4	$\Delta R_{IB,c}$ for four bands.....	468
7.3A.3.2.5	$\Delta R_{IB,c}$ for five bands.....	473
7.3A.3.3	$\Delta R_{IB,c}$ for Intra-band CA.....	474
7.3A.4	Reference sensitivity exceptions due to UL harmonic interference for CA.....	474
7.3A.5	Reference sensitivity exceptions due to intermodulation interference due to 2UL CA.....	484
7.3A.6	Reference sensitivity exceptions due to cross band isolation for CA.....	507
7.3B	Reference sensitivity for NR-DC.....	511
7.3C	Reference sensitivity for SUL.....	511
7.3C.1	General.....	511
7.3C.2	Reference sensitivity power level for SUL.....	511
7.3C.3	$\Delta R_{IB,c}$ for SUL.....	514
7.3C.3.1	General.....	514
7.3C.3.2	SUL band combination.....	514
7.3C.3.2.1	$\Delta R_{IB,c}$ for two bands.....	515
7.3C.3.2.2	$\Delta R_{IB,c}$ for three bands.....	515
7.3C.3.2.3	$\Delta R_{IB,c}$ for four bands.....	515
7.3D	Reference sensitivity for UL MIMO.....	516
7.3E	Reference sensitivity for V2X.....	516
7.3E.1	General.....	516
7.3E.2	Minimum requirements.....	516
7.3E.3	Reference sensitivity power level for V2X concurrent operation.....	517
7.3F	Reference sensitivity for shared spectrum channel access.....	518
7.3F.1	General.....	518
7.3F.2	Reference sensitivity power level.....	519
7.3F.3	Void.....	520
7.3F.4	Void.....	520
7.3F.4A	Shared spectrum channel access CA.....	520
7.3F.4A.1	Intra-band contiguous shared spectrum channel access CA.....	520
7.3F.5	Void.....	520
7.3F.5.1	Void.....	520
7.3F.5.2	Void.....	520
7.3F.5.3	Void.....	520
7.3G	Reference sensitivity for Tx Diversity.....	520
7.3G.5	Void.....	520
7.3G.5.0	Void.....	520
7.3I	Reference sensitivity for RedCap.....	520
7.3I.1	General.....	520

7.3I.2	Reference sensitivity power level	520
7.4	Maximum input level	524
7.4A	Maximum input level for CA	525
7.4A.1	Maximum input level for Intra-band contiguous CA	525
7.4A.2	Maximum input level for Intra-band non-contiguous CA	525
7.4A.3	Maximum input level for Inter-band CA	525
7.4B	Maximum input level for NR-DC	526
7.4D	Maximum input level for UL MIMO	526
7.4E	Maximum input level for V2X	526
7.4E.1	General	526
7.4E.2	Maximum input level for V2X concurrent operation	526
7.5	Adjacent channel selectivity	526
7.5A	Adjacent channel selectivity for CA	528
7.5A.1	Adjacent channel selectivity for Intra-band contiguous CA	528
7.5A.2	Adjacent channel selectivity Intra-band non-contiguous CA	530
7.5A.3	Adjacent channel selectivity Inter-band CA	531
7.5B	Adjacent channel selectivity for NR-DC	531
7.5D	Adjacent channel selectivity for UL MIMO	531
7.5E	Adjacent channel selectivity for V2X	531
7.5E.1	General	531
7.5E.2	Adjacent channel selectivity for V2X concurrent operation	533
7.5F	Adjacent channel selectivity for shared spectrum channel access	533
7.5F.1	General	533
7.5F.1A	Adjacent channel selectivity for shared spectrum channel access CA	534
7.5F.1A.1	Intra-band contiguous shared spectrum channel access CA	534
7.5F.2	Void	534
7.6	Blocking characteristics	534
7.6.1	General	534
7.6.2	In-band blocking	535
7.6.3	Out-of-band blocking	537
7.6.4	Narrow band blocking	539
7.6A	Blocking characteristics for CA	540
7.6A.1	General	540
7.6A.2	In-band blocking for CA	540
7.6A.2.1	In-band blocking for Intra-band contiguous CA	540
7.6A.2.2	In-band blocking for Intra-band non-contiguous CA	541
7.6A.2.3	In-band blocking for Inter-band CA	542
7.6A.3	Out-of-band blocking for CA	542
7.6A.3.1	Out-of-band blocking for Intra-band contiguous CA	542
7.6A.3.2	Out-of-band blocking for Intra-band non-contiguous CA	543
7.6A.3.3	Out-of-band blocking for Inter-band CA	543
7.6A.4	Narrow band blocking for CA	545
7.6A.4.1	Narrow band blocking for Intra-band contiguous CA	545
7.6A.4.2	Narrow band blocking for Intra-band non-contiguous CA	546
7.6A.4.3	Narrow band blocking for Inter-band CA	546
7.6B	Blocking characteristics for NR-DC	546
7.6C	Blocking characteristics for SUL	546
7.6C.1	General	546
7.6C.2	In-band blocking for SUL	546
7.6C.3	Out-of-band blocking for SUL	547
7.6C.4	Narrow band blocking for SUL	547
7.6D	Blocking characteristics for UL MIMO	547
7.6E	Blocking characteristics for V2X	547
7.6E.1	General	547
7.6E.2	In-band blocking	548
7.6E.2.1	General	548
7.6E.2.2	In-band blocking for V2X concurrent operation	549
7.6E.3	Out-of-band blocking	549
7.6E.3.1	General	549
7.6E.3.2	Out-of-band blocking for V2X concurrent operation	550
7.6F	Blocking characteristics for shared spectrum channel access	550
7.6F.1	General	550