



TECHNICAL SPECIFICATION

**5G;
NR;
User Equipment (UE) radio transmission and reception;
Part 1: Range 1 Standalone
(3GPP TS 38.101-1 version 19.5.0 Release 19)**



Reference

RTS/TSGR-0438101-1vJ50

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed, this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our [Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2026.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by the ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found at [3GPP to ETSI numbering cross-referencing](#).

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	26
1 Scope	28
2 References	28
3 Definitions, symbols and abbreviations	29
3.1 Definitions	29
3.2 Symbols.....	30
3.3 Abbreviations	33
4 General	35
4.1 Relationship between minimum requirements and test requirements	35
4.2 Applicability of minimum requirements	35
4.3 Specification suffix information.....	35
5 Operating bands and channel arrangement.....	37
5.1 General	37
5.2 Operating bands.....	37
5.2A Operating bands for CA	39
5.2A.0 General.....	39
5.2A.1 Intra-band CA	39
5.2A.2 Inter-band CA	40
5.2A.2.1 Inter-band CA (two bands).....	40
5.2A.2.2 Inter-band CA (three bands).....	45
5.2A.2.3 Inter-band CA (four bands).....	51
5.2A.2.4 Inter-band CA (five bands).....	55
5.2A.2.5 Inter-band CA (six bands).....	56
5.2B Operating bands for DC	56
5.2C Operating band combination for SUL	56
5.2D Operating bands for UL MIMO	59
5.2E Operating band for V2X.....	59
5.2E.1 V2X operating bands	60
5.2E.1A Sidelink CA operating bands	60
5.2E.1F Operating bands for Sidelink Unlicensed	60
5.2E.2 V2X operating bands for concurrent operation.....	60
5.2E.2F Operating bands for SL-U concurrent operation.....	61
5.2J Operating band for ATG	61
5.2J.1 General.....	61
5.2J.1A Operating band for ATG CA	61
5.2J.1A.1 Operating band for ATG intra-band CA	62
5.2J.1A.2 Operating band for ATG inter-band CA	62
5.2J.1D Operating band for ATG UL MIMO	62
5.2K Operating bands for Aerial UE.....	62
5.2M Operating bands for LP-WUS/WUR.....	62
5.3 UE channel bandwidth	62
5.3.1 General.....	62
5.3.2 Maximum transmission bandwidth configuration	64
5.3.3 Minimum guardband and transmission bandwidth configuration.....	64
5.3.4 RB alignment	66
5.3.5 UE channel bandwidth per operating band	66
5.3.6 Asymmetric channel bandwidths	73
5.3A UE channel bandwidth for CA	74
5.3A.1 General.....	74
5.3A.2 Maximum transmission bandwidth configuration for CA	74

5.3A.3	Minimum guardband and transmission bandwidth configuration for CA	74
5.3A.4	Void	76
5.3A.5	UE channel bandwidth per operating band for CA	76
5.3E	Channel bandwidth for V2X	77
5.3E.1	General.....	77
5.3E.1A	Channel bandwidth for Sidelink CA.....	78
5.3E.1F	Channel bandwidth for Sidelink Unlicensed	78
5.3E.2	Channel bandwidth for V2X concurrent operation.....	79
5.3E.2F	Channel bandwidth for SL-U concurrent operation.....	80
5.3I	Channel bandwidth for (e)RedCap.....	81
5.3M	UE channel bandwidth for LP-WUS/WUR.....	81
5.3M.1	General.....	81
5.3M.2	Maximum transmission bandwidth configuration	81
5.4	Channel arrangement.....	81
5.4.1	Channel spacing.....	81
5.4.1.1	Channel spacing for adjacent NR carriers.....	81
5.4.2	Channel raster	82
5.4.2.1	NR-ARFCN and channel raster.....	82
5.4.2.2	Channel raster to resource element mapping.....	82
5.4.2.3	Channel raster entries for each operating band	83
5.4.3	Synchronization raster	87
5.4.3.1	Synchronization raster and numbering.....	87
5.4.3.3	Synchronization raster entries for each operating band.....	88
5.4.4	TX-RX frequency separation	90
5.4A	Channel arrangement for CA.....	91
5.4A.1	Channel spacing for CA.....	91
5.4A.2	Channel raster for CA.....	91
5.4A.3	Synchronization raster for CA	92
5.4A.4	Tx-Rx frequency separation for CA.....	92
5.4B	Reserved.....	92
5.4C	Reserved.....	92
5.4D	Reserved.....	92
5.4E	Channel arrangement for V2X	92
5.4E.1	Channel spacing.....	92
5.4E.1A	Channel spacing for Sidelink CA	92
5.4E.1F	Channel spacing for Sidelink Unlicensed	92
5.4E.2	Channel raster	92
5.4E.2.1	NR-ARFCN and channel raster.....	92
5.4E.2.1A	Void.....	92
5.4E.2.1F	Void.....	92
5.4E.2.2	Channel raster to resource element mapping.....	93
5.4E.2.2A	Void.....	93
5.4E.2.2F	Void.....	93
5.4E.2.3	Channel raster entries for each operating band	93
5.4E.2.3A	Void.....	93
5.4E.2.3F	Void.....	93
5.4E.3	Synchronization raster for V2X.....	94
5.4E.3A	Synchronization raster for Sidelink CA	94
5.4E.3F	Synchronization raster for Sidelink Unlicensed.....	94
5.4I	Channel arrangement for (e)RedCap.....	94
5.4I.1	Channel spacing for (e)RedCap.....	94
5.4I.2	Channel raster for (e)RedCap	94
5.4I.2.1	NR-ARFCN and channel raster.....	94
5.4I.2.2	Channel raster to resource element mapping.....	94
5.4I.2.3	Channel raster entries for each operating band	94
5.4I.3	Synchronization raster for (e)RedCap.....	94
5.4I.4	Tx-Rx frequency separation for (e)RedCap.....	95
5.5	Void.....	96
5.5A	Configurations for CA.....	96
5.5A.0	General.....	96
5.5A.1	Configurations for intra-band contiguous CA.....	97
5.5A.2	Configurations for intra-band non-contiguous CA	101

5.5A.3	Configurations for inter-band CA	105
5.5A.3.0	General	105
5.5A.3.1	Configurations for inter-band CA (two bands)	105
Table 5.5A.3.1-1a ~ Table 5.5A.3.1-1e.....		105
Table 5.5A.3.1-1f ~ Table 5.5A.3.1-1j.....		126
Table 5.5A.3.1-1k ~ Table 5.5A.3.1-1o		149
5.5A.3.2	Configurations for inter-band CA (three bands)	166
Table 5.5A.3.2-1a	166	
Table 5.5A.3.2-1b	262	
Table 5.5A.3.2-1c	317	
5.5A.3.3	Configurations for inter-band CA (four bands).....	342
Table 5.5A.3.3-1a	343	
Table 5.5A.3.3-1b	434	
5.5A.3.4	Configurations for inter-band CA (five bands)	492
5.5A.3.5	Configurations for inter-band CA (six bands).....	530
5.5B	Configurations for DC.....	533
5.5C	Configurations for SUL.....	546
5.5D	Reserved	558
5.5E	Configurations for Sidelink	558
5.5E.1A	Configurations for Sidelink CA	558
5.5E.1A.1	Configurations for Sidelink intra-band contiguous CA.....	558
5.5E.1A.2	Configurations for Sidelink intra-band non-contiguous CA	559
5.5J	Configurations for ATG	559
5.5J.1A	Configurations for ATG CA	559
5.5J.1A.1	Configurations for ATG intra-band contiguous CA.....	559
5.5J.1A.2	Configurations for ATG inter-band CA	559
6	Transmitter characteristics	561
6.1	General	561
6.1A	General	561
6.1F	General	561
6.1G	(Reserved)	561
6.1H	(Reserved)	561
6.1I	(Reserved)	561
6.1J	General	561
6.1K	(Reserved)	562
6.1L	(Reserved)	562
6.2	Transmitter power	562
6.2.1	UE maximum output power	562
6.2.1I	Void	564
6.2.2	UE maximum output power reduction.....	564
6.2.3	UE additional maximum output power reduction	568
6.2.3.1	General	568
6.2.3.2	A-MPR for NS_04	572
6.2.3.3	A-MPR for NS_10	575
6.2.3.4	A-MPR for NS_05 and NS_05U.....	576
6.2.3.5	A-MPR for NS_40	579
6.2.3.6	A-MPR for NS_43 and NS_43U.....	579
6.2.3.7	A-MPR for NS_03 and NS_03U.....	582
6.2.3.8	A-MPR for NS_37	583
6.2.3.9	A-MPR for NS_38	583
6.2.3.10	A-MPR for NS_39	584
6.2.3.11	A-MPR for NS_41	584
6.2.3.12	A-MPR for NS_42	584
6.2.3.13	A-MPR for NS_18	585
6.2.3.14	A-MPR for NS_21	587
6.2.3.15	A-MPR for NS_24	589
6.2.3.16	A-MPR for NS_27	590
6.2.3.17	A-MPR for NS_46	592
6.2.3.18	A-MPR for NS_47	595
6.2.3.19	A-MPR for NS_50	597
6.2.3.20	A-MPR for NS_44	600

6.2.3.21	A-MPR for NS_12	600
6.2.3.22	A-MPR for NS_13	601
6.2.3.23	A-MPR for NS_14	602
6.2.3.24	A-MPR for NS_15	603
6.2.3.25	A-MPR for NS_45	606
6.2.3.26	A-MPR for NS_48	606
6.2.3.27	A-MPR for NS_49	608
6.2.3.28	A-MPR for NS_51	611
6.2.3.29	A-MPR for NS_07	611
6.2.3.30	A-MPR for NS_56	613
6.2.3.31	A-MPR for NS_35	613
6.2.3.32	A-MPR for NS_06	614
6.2.3.33	A-MPR for NS_17	614
6.2.3.34	A-MPR for NS_26	615
6.2.3.35	A-MPR for NS_36	616
6.2.4	Configured transmitted power	616
6.2A	Transmitter power for CA	623
6.2A.0	General	623
6.2A.1	UE maximum output power for CA	623
6.2A.1.1	UE maximum output power for Intra-band contiguous CA	623
6.2A.1.2	UE maximum output power for Intra-band non-contiguous CA	625
6.2A.1.3	UE maximum output power for Inter-band CA	626
6.2A.1.4	Void	632
6.2A.1.5	Void	632
6.2A.2	UE maximum output power reduction for CA	632
6.2A.2.1	UE maximum output power reduction for Intra-band contiguous CA	632
6.2A.2.2	UE maximum output power reduction for Intra-band non-contiguous CA	638
6.2A.2.2.0	General	638
6.2A.2.2.1	MPR to meet -30dBm/MHz	639
6.2A.2.2.2	MPR to meet -13dBm/MHz	641
6.2A.2.3	UE maximum output power reduction for Inter-band CA	643
6.2A.2.4	Void	643
6.2A.3	UE additional maximum output power reduction for CA	643
6.2A.3.1	UE additional maximum output power reduction for Intra-band CA	643
6.2A.3.1.1	UE additional maximum output power reduction for Intra-band contiguous CA	643
6.2A.3.1.2	UE additional maximum output power reduction for Intra-band non-contiguous CA	651
6.2A.3.1.3	UE additional maximum output power reduction for Inter-band CA	654
6.2A.4	Configured output power for CA	657
6.2A.4.1	Configured transmitted power level	657
6.2A.4.1.1	Configured transmitted power for Intra-band contiguous CA	657
6.2A.4.1.2	Configured transmitted power for Intra-band non-contiguous CA	659
6.2A.4.1.3	Configured transmitted power for Inter-band CA	662
6.2A.4.1.4	Void	666
6.2A.4.2	$\Delta T_{IB,c}$ for CA	666
6.2A.4.2.1	Void	666
6.2A.4.2.2	Void	666
6.2A.4.2.3	$\Delta T_{IB,c}$ for Inter-band CA (two bands)	666
6.2A.4.2.4	$\Delta T_{IB,c}$ for Inter-band CA (three bands)	671
6.2A.4.2.5	$\Delta T_{IB,c}$ for Inter-band CA (four bands)	678
6.2A.4.2.6	$\Delta T_{IB,c}$ for Inter-band CA (five bands)	683
6.2A.4.2.7	$\Delta T_{IB,c}$ for Inter-band CA (six bands)	684
6.2B	Transmitter power for NR-DC	684
6.2B.0	General	684
6.2B.1	UE maximum output power for NR-DC	684
6.2B.2	UE maximum output power reduction for NR-DC	686
6.2B.3	UE additional maximum output power reduction for NR-DC	686
6.2B.4.1	Configured transmitted power level for NR-DC	687
6.2B.4.2	$\Delta T_{IB,c}$ for NR-DC	691
6.2C	Transmitter power for SUL	691
6.2C.1	Configured transmitted power for SUL	691
6.2C.2	$\Delta T_{IB,c}$	692
6.2D	Transmitter power for UL MIMO	694

6.2D.1	UE maximum output power for UL MIMO.....	694
6.2D.2	UE maximum output power reduction for UL MIMO.....	696
6.2D.3	UE additional maximum output power reduction for UL MIMO.....	699
6.2D.4	Configured transmitted power for UL MIMO.....	699
6.2E	Transmitter power for V2X.....	701
6.2E.1	UE maximum output power for V2X.....	701
6.2E.1.1	General.....	701
6.2E.1.1A	Void.....	701
6.2E.1.2	UE maximum output power for V2X concurrent operation.....	701
6.2E.1A	UE maximum output power for Sidelink CA.....	703
6.2E.1F	UE maximum output power for Sidelink Unlicensed.....	703
6.2E.1F.1	General.....	703
6.2E.1.2F	Void.....	704
6.2E.1F.2	UE Maximum output power for SL-U concurrent operation.....	704
6.2E.2	UE maximum output power reduction for V2X.....	705
6.2E.2.1	General.....	705
6.2E.2.1A	MPR for sidelink CA.....	705
6.2E.2.1A.1	MPR for sidelink intra-band contiguous CA.....	705
6.2E.2.1A.2	MPR for sidelink intra-band non-contiguous CA.....	707
6.2E.2.1A.2.0	General.....	707
6.2E.2.1A.2.1	MPR with indicating dualPA-Architecture supported.....	708
6.2E.2.1A.2.2	MPR without indicating dualPA-Architecture supported.....	710
6.2E.2.2	MPR for Power class 2 and Power class 3 V2X UE.....	711
6.2E.2.3	MPR for Power class 2 and Power class 3 V2X concurrent operation.....	713
6.2E.2.4	MPR for Power class 1 UE in Band n14.....	715
6.2E.2F	UE maximum output power reduction for Sidelink Unlicensed.....	715
6.2E.2F.1	General.....	715
6.2E.2F.2	MPR for NR SL-U UE.....	716
6.2E.2F.3	MPR for SL-U concurrent operation.....	717
6.2E.3	UE additional maximum output power reduction for V2X.....	717
6.2E.3.1	General.....	717
6.2E.3.2	A-MPR for V2X UE by NS_33.....	718
6.2E.3.2A	A-MPR for sidelink CA by NS_33.....	723
6.2E.3.2A.1	A-MPR for sidelink intra-band non-contiguous CA.....	723
6.2E.3.2A.1.1	A-MPR for SLCA_NC_NS_33 (SLCA_n47(2A)).....	723
6.2E.3.3	A-MPR for Power class 3 V2X UE by NS_52.....	727
6.2E.3.4	A-MPR for V2X concurrent operation.....	728
6.2E.3F	UE additional maximum output power reduction for Sidelink Unlicensed.....	729
6.2E.3F.1	General.....	729
6.2E.3F.2	A-MPR for NS_31.....	730
6.2E.3F.3	Void.....	731
6.2E.3F.4	Void.....	731
6.2E.3F.5	Void.....	731
6.2E.3F.6	A-MPR for NS_61.....	731
6.2E.3F.7	A-MPR for SL-U concurrent operation.....	732
6.2E.3F.8	A-MPR for NS_28.....	732
6.2E.3F.9	A-MPR for NS_29.....	733
6.2E.3F.10	A-MPR for NS_30.....	734
6.2E.3F.11	A-MPR for NS_54.....	736
6.2E.3F.12	A-MPR for NS_64.....	737
6.2E.3F.13	A-MPR for NS_65.....	738
6.2E.3F.14	A-MPR for NS_66.....	739
6.2E.3F.15	A-MPR for NS_67 or NS_71.....	740
6.2E.3F.16	A-MPR for NS_68.....	741
6.2E.3F.17	A-MPR for NS_69.....	742
6.2E.4	Configured transmitted power for V2X.....	743
6.2E.4.1	General.....	743
6.2E.4.2	Configured transmitted power for inter-band V2X concurrent operation.....	744
6.2E.4.3	Configured transmitted power for intra-band V2X concurrent operation.....	745
6.2E.4A	Configured transmitted power for Sidelink CA.....	747
6.2E.4F	Configured transmitted power for Sidelink Unlicensed.....	748
6.2E.4F.1	General.....	748

6.2E.4F.2	Configured transmitted power for inter-band concurrent operation.....	749
6.2F	Transmitter power for shared spectrum channel access	750
6.2F.1	UE maximum output power.....	750
6.2F.1A	UE maximum output power for CA.....	751
6.2F.1A.1	UE maximum output power for inter-band CA.....	751
6.2F.1A.2	UE maximum output power for intra-band contiguous CA	752
6.2F.1A.2.1	Additional requirements for transmit power density for intra-band contiguous CA for CA_NS_53	752
6.2F.1A.2.2	Additional requirements for transmit power density for intra-band contiguous CA for CA_NS_54	752
6.2F.1B	UE maximum output power for NR-DC.....	753
6.2F.1D	UE maximum output power for UL MIMO.....	753
6.2F.2	UE maximum output power reduction.....	753
6.2F.2A	UE maximum output power reduction for CA.....	756
6.2F.2A.1	UE maximum output power reduction for inter-band CA.....	756
6.2F.2A.2	UE maximum output power reduction for intra-band contiguous CA	756
6.2F.2D	UE maximum output power reduction for UL MIMO.....	758
6.2F.3	UE additional maximum output power reduction	758
6.2F.3.1	General	758
6.2F.3.2	A-MPR for NS_28	759
6.2F.3.3	A-MPR for NS_29	760
6.2F.3.4	A-MPR for NS_30	760
6.2F.3.5	A-MPR for NS_31	761
6.2F.3.6	A-MPR for NS_53	762
6.2F.3.7	A-MPR for NS_54	763
6.2F.3.8	A-MPR for NS_58	764
6.2F.3.9	A-MPR for NS_59	765
6.2F.3.10	A-MPR for NS_60	765
6.2F.3.11	A-MPR for NS_61	767
6.2F.3.12	A-MPR for NS_63	767
6.2F.3.13	A-MPR for NS_64	768
6.2F.3.14	A-MPR for NS_65	768
6.2F.3.15	A-MPR for NS_66	769
6.2F.3.16	A-MPR for "NS_67" or "NS_71"	769
6.2F.3.17	A-MPR for NS_68	770
6.2F.3.18	A-MPR for NS_69	770
6.2F.3A	UE additional maximum output power reduction for CA.....	771
6.2F.3A.1	UE additional maximum output power reduction for inter-band CA.....	771
6.2F.3A.2	UE additional maximum output power reduction for intra-band CA.....	771
6.2F.3A.2.0	General	771
6.2F.3A.2.1	UE additional maximum output power reduction for intra-band contiguous CA.....	771
6.2F.3A.2.2	A-MPR for CA_NS_53	773
6.2F.3A.2.3	A-MPR for CA_NS_54	774
6.2F.3D	UE additional maximum output power reduction for UL MIMO.....	774
6.2F.4	Configured transmitted power	774
6.2F.4D	Configured transmitted power UL MIMO.....	774
6.2G	Transmitter power for Tx Diversity.....	775
6.2G.1	UE maximum output power for Tx Diversity	775
6.2G.2	UE maximum output power reduction for Tx Diversity	775
6.2G.3	UE additional maximum output power reduction for Tx Diversity	775
6.2G.4	Configured transmitted power for Tx Diversity.....	775
6.2H	Transmitter power for CA with UL MIMO.....	776
6.2H.1	Transmitter power for intra-band UL contiguous CA with UL MIMO	776
6.2H.1.1	UE maximum output power for intra-band UL contiguous CA with UL MIMO	776
6.2H.1.2	UE maximum output power reduction for intra-band UL contiguous CA with UL MIMO	777
6.2H.1.3	UE additional maximum output power reduction for intra-band UL contiguous CA with UL MIMO	777
6.2H.1.4	Configured transmitted power for intra-band UL contiguous CA with UL MIMO.....	777
6.2H.2	Void	778
6.2H.3	Transmitter power for inter-band UL CA with UL MIMO	778
6.2H.3.1	UE maximum output power for inter-band UL CA with UL MIMO.....	778
6.2H.3.2	UE maximum output power reduction for inter-band UL CA with UL MIMO.....	781

6.2H.3.3	UE additional maximum output power reduction for inter-band UL CA with UL MIMO	781
6.2H.3.4	Configured transmitted power for inter-band UL CA with UL MIMO	781
6.2I	Transmitter power for (e)RedCap.....	781
6.2I.1	Maximum output power for RedCap	781
6.2J	Transmitter power for ATG.....	782
6.2J.0	Reserved	782
6.2J.0D	General.....	782
6.2J.1	UE maximum output power for ATG	782
6.2J.1A	UE maximum output power for ATG CA	782
6.2J.1A.1	UE maximum output power for ATG intra-band contiguous CA	782
6.2J.1A.2	UE maximum output power for ATG inter-band CA	782
6.2J.1A.3	(void).....	782
6.2J.1D	UE maximum output power for ATG UL MIMO	782
6.2J.2	Configured transmitted power for ATG.....	783
6.2J.2D	Configured transmitted power for UL MIMO	784
6.2K	Transmitter power for Aerial UE	785
6.2K.1	Maximum output power for Aerial UE.....	785
6.2K.2	Maximum output power reduction for Aerial UE.....	785
6.2K.3	Additional maximum output power reduction for Aerial UE	785
6.2K.3.1	General	785
6.2K.3.2	A-MPR for NS_UAV_44.....	786
6.2K.3.3	A-MPR for NS_UAV_70.....	786
6.2K.4	Configured transmitted power for Aerial UE.....	788
6.2L	Transmitter power for CA with Tx Diversity	788
6.2L.1	Void	788
6.2L.2	Void	788
6.2L.3	Transmitter power for inter-band UL CA with Tx Diversity	788
6.2L.3.1	UE maximum output power for inter-band UL CA with Tx Diversity	788
6.2L.3.2	UE maximum output power reduction for inter-band UL CA with Tx Diversity	790
6.2L.3.3	UE additional maximum output power reduction for inter-band UL CA with Tx Diversity	790
6.2L.3.4	Configured transmitted power for inter-band UL CA with Tx Diversity	790
6.3	Output power dynamics.....	791
6.3.1	Minimum output power	791
6.3.2	Transmit OFF power.....	791
6.3.3	Transmit ON/OFF time mask	791
6.3.3.1	General	791
6.3.3.2	General ON/OFF time mask	792
6.3.3.3	Transmit power time mask for slot and short or long subslot boundaries.....	792
6.3.3.4	PRACH time mask.....	792
6.3.3.5	Void.....	793
6.3.3.6	SRS time mask	793
6.3.3.7	PUSCH-PUCCH and PUSCH-SRS time masks	795
6.3.3.8	Transmit power time mask for consecutive slot or long subslot transmission and short subslot transmission boundaries	796
6.3.3.9	Transmit power time mask for consecutive short subslot transmissions boundaries	797
6.3.4	Power control.....	797
6.3.4.1	General	797
6.3.4.2	Absolute power tolerance.....	797
6.3.4.3	Relative power tolerance	798
6.3.4.4	Aggregate power tolerance.....	798
6.3A	Output power dynamics for CA	799
6.3A.1	Minimum output power for CA	799
6.3A.1.1	Minimum output power for intra-band contiguous CA.....	799
6.3A.1.2	Minimum output power for intra-band non-contiguous CA	799
6.3A.1.3	Minimum output power for inter-band CA	799
6.3A.1.4	Void.....	799
6.3A.2	Transmit OFF power for CA.....	799
6.3A.2.1	Transmit OFF power for intra-band contiguous CA	799
6.3A.2.2	Transmit OFF power for intra-band non-contiguous CA	799
6.3A.2.3	Transmit OFF power for inter-band CA.....	799
6.3A.2.4	Void.....	800
6.3A.3	Transmit ON/OFF time mask for CA	800

6.3A.3.1	Transmit ON/OFF time mask for intra-band contiguous CA.....	800
6.3A.3.2	Transmit ON/OFF time mask for intra-band non-contiguous CA	800
6.3A.3.3	Transmit ON/OFF time mask for inter-band CA	800
6.3A.3.3.1	General	800
6.3A.3.3.2	Time mask for switching between two uplink carriers.....	801
6.3A.3.3.3	Time mask for switching between two uplink carriers with two transmit antenna connectors	802
6.3A.3.3.4	Time mask for switching between one uplink band with one transmit antenna connector and one uplink band with two transmit antenna connectors.....	803
6.3A.3.3.5	Time mask for switching between two uplink bands with two transmit antenna connectors	805
6.3A.3.3.6	Time mask for switching across up to four uplink bands	806
6.3A.3.3.6a	Additional requirements for three-band switching with dual TAG	810
6.3A.3.3.7	Time mask for low NR band carrier aggregation via switching	810
6.3A.3.3.8	Time mask for switching between two uplink bands with three transmit antenna connectors and maximum two transmit antenna connectors for each band	810
6.3A.3.4	Void.....	812
6.3A.4	Power control for CA.....	812
6.3A.4.1	Power control for intra-band contiguous CA	812
6.3A.4.1.1	Absolute power tolerance	812
6.3A.4.1.2	Relative power tolerance	812
6.3A.4.1.3	Aggregate power control tolerance.....	812
6.3A.4.2	Power control for intra-band non-contiguous CA	812
6.3A.4.2.1	Absolute power tolerance.....	812
6.3A.4.2.1.1	Minimum requirements	813
6.3A.4.2.2	Relative power tolerance	813
6.3A.4.2.2.1	Minimum requirements	813
6.3A.4.2.3	Aggregate power control tolerance	813
6.3A.4.3	Power control for inter-band CA.....	813
6.3A.4.4	Void.....	813
6.3B	Output power dynamics for NR-DC.....	813
6.3C	Output power dynamics for SUL	814
6.3C.1	Void.....	814
6.3C.2	Void.....	814
6.3C.3	Transmit ON/OFF time mask for SUL	814
6.3C.3.0	General	814
6.3C.3.1	Time mask for switching between two uplink carriers.....	814
6.3C.3.2	Time mask for switching between two uplink carriers with two transmit antenna connectors	815
6.3C.3.3	Time mask for switching between one uplink band with one transmit antenna connector and one uplink band with two transmit antenna connectors	816
6.3C.3.4	Time mask for switching between two uplink bands with two transmit antenna connectors.....	818
6.3C.3.5	Time mask for switching across up to four uplink bands.....	819
6.3C.3.5a	Additional requirements for three-band switching with dual TAG.....	823
6.3D	Output power dynamics for UL MIMO	823
6.3D.1	Minimum output power for UL MIMO	823
6.3D.2	Transmit OFF power for UL MIMO.....	823
6.3D.3	Transmit ON/OFF time mask for UL MIMO	823
6.3D.4	Power control for UL MIMO.....	823
6.3E	Output power dynamics for V2X	824
6.3E.1	Minimum output power for V2X.....	824
6.3E.1.1	General	824
6.3E.1.1A	Minimum output power for sidelink CA.....	824
6.3E.1.2	Minimum output power for V2X concurrent operation	824
6.3E.1F	Minimum output power for Sidelink Unlicensed.....	824
6.3E.1F.1	Minimum output power for SL-U concurrent operation	825
6.3E.2	Transmit OFF power for V2X	825
6.3E.2.1	General	825
6.3E.2.1A	Transmit OFF power for sidelink CA	825
6.3E.2.2	Transmit OFF power for V2X concurrent operation.....	825
6.3E.2F	Transmit OFF power for Sidelink Unlicensed.....	825
6.3E.2F.1	Transmit OFF power for SL-U concurrent operation.....	826
6.3E.3	Transmit ON/OFF time mask for V2X.....	826
6.3E.3.1	General	826
6.3E.3.1A	Transmit ON/OFF time mask for sidelink CA	826

6.3E.3.2	General time mask.....	826
6.3E.3.3	S-SSB time mask	826
6.3E.3.4	Transmit ON/OFF time mask for V2X concurrent operation	827
6.3E.3F	Transmit ON/OFF time mask for Sidelink Unlicensed.....	828
6.3E.3F.1	General	828
6.3E.3F.2	General ON/OFF time mask	828
6.3E.3F.3	S-SSB time mask	829
6.3E.3F.4	Transmit ON/OFF time mask for NR SL-U concurrent operation.....	829
6.3E.4	Power control for V2X	829
6.3E.4.1	General	829
6.3E.4.1A	Power control for sidelink CA	829
6.3E.4.2	Absolute power tolerance.....	829
6.3E.4.3	Power control for V2X concurrent operation.....	830
6.3E.4F	Power control for Sidelink Unlicensed	830
6.3E.4F.1	General.....	830
6.3E.4F.2	Absolute power tolerance.....	830
6.3E.4F.3	Power control for SL-U concurrent operation.....	830
6.3F	Output power dynamics for shared spectrum channel access.....	830
6.3F.1	Minimum output power	830
6.3F.2	Transmit OFF power.....	830
6.3F.3	Transmit ON/OFF time mask	830
6.3F.3.1	General	830
6.3F.3.2	General ON/OFF time mask	830
6.3F.3A	General ON/OFF mask for CA	831
6.3F.3A.1	General ON/OFF mask for inter-band CA	831
6.3F.4	Power control.....	831
6.3F.4.1	General	831
6.3F.4.2	Absolute power tolerance.....	831
6.3F.4.3	Relative power tolerance.....	831
6.3F.4.4	Aggregate power tolerance.....	831
6.3F.4A	Power control for inter-band CA	831
6.3G	Output power dynamics for Tx Diversity.....	832
6.3G.1	Minimum output power for Tx Diversity	832
6.3G.2	Transmit OFF power for Tx Diversity.....	832
6.3G.3	Transmit ON/OFF time mask for Tx Diversity	832
6.3G.4	Power control for Tx Diversity	832
6.3H	Output power dynamics for CA with UL MIMO.....	832
6.3H.1	Output power dynamics for intra-band UL contiguous CA with UL MIMO	832
6.3H.1.1	Minimum output power for intra-band UL contiguous CA with UL MIMO.....	832
6.3H.1.2	Transmit OFF power for intra-band UL contiguous CA with UL MIMO	832
6.3H.1.3	Transmit ON/OFF time mask for intra-band UL contiguous CA with UL MIMO.....	832
6.3H.1.4	Power control for intra-band UL contiguous CA with UL MIMO	833
6.3H.3	Output power dynamics for inter-band UL CA with UL MIMO.....	833
6.3H.3.1	Minimum output power for inter-band UL CA with UL MIMO	833
6.3H.3.2	Transmit OFF power for inter-band UL CA with UL MIMO.....	833
6.3H.3.3	Transmit ON/OFF time mask for inter-band UL CA with UL MIMO	833
6.3H.3.4	Power control for inter-band UL CA with UL MIMO	833
6.3I	(Reserved)	833
6.3J	Output power dynamics for ATG.....	833
6.3J.1	Minimum output power for ATG	833
6.3J.1D	Minimum output power for ATG UL MIMO	834
6.3J.2	Transmit OFF power for ATG.....	834
6.3J.2D	Transmit OFF power for ATG UL MIMO	834
6.3J.3	Transmit ON/OFF time mask for ATG.....	834
6.3J.3D	Transmit ON/OFF time mask for ATG UL MIMO	834
6.3J.4	Power control for ATG	835
6.3J.4D	Power control for ATG UL MIMO	835
6.3K	(Reserved)	835
6.3L	Output power dynamics for CA with Tx Diversity	835
6.3L.1	Void	835
6.3L.2	Void	835
6.3L.3	Output power dynamics for inter-band UL CA with Tx Diversity	835

6.3L.3.1	Minimum output power for inter-band UL CA with Tx Diversity.....	835
6.3L.3.2	Transmit OFF power for inter-band UL CA with Tx Diversity	835
6.3L.3.3	Transmit ON/OFF time mask for inter-band UL CA with Tx Diversity.....	835
6.3L.3.4	Power control for inter-band UL CA with Tx Diversity	836
6.4	Transmit signal quality	836
6.4.1	Frequency error.....	836
6.4.2	Transmit modulation quality.....	836
6.4.2.0	General	836
6.4.2.1	Error Vector Magnitude	836
6.4.2.1a	Error Vector Magnitude including symbols with transient period	837
6.4.2.2	Carrier leakage	838
6.4.2.3	In-band emissions	838
6.4.2.4	EVM equalizer spectrum flatness	840
6.4.2.4.1	Requirements for Pi/2 BPSK modulation with <i>powerBoosting-pi2BPSK</i> capability	841
6.4.2.4.2	Requirements for Pi/2 BPSK and QPSK modulation with <i>powerBoosting-pi2BPSK-QPSK-Modified-r18</i> capability	841
6.4.2.5	Phase continuity requirements for DMRS bundling	842
6.4A	Transmit signal quality for CA.....	843
6.4A.1	Frequency error for CA.....	843
6.4A.1.1	Frequency error for intra-band contiguous CA	843
6.4A.1.2	Frequency error for intra-band non-contiguous CA	843
6.4A.1.3	Frequency error for inter-band CA.....	843
6.4A.1.4	Void.....	844
6.4A.2	Transmit modulation quality for CA.....	844
6.4A.2.1	Transmit modulation quality for intra-band contiguous CA	844
6.4A.2.1.0	General	844
6.4A.2.1.1	Error Vector Magnitude.....	844
6.4A.2.1.2	In-band emissions	844
6.4A.2.1.3	Carrier leakage.....	846
6.4A.2.2	Transmit modulation quality for intra-band non-contiguous CA	847
6.4A.2.2.0	General	847
6.4A.2.2.1	Error Vector Magnitude.....	847
6.4A.2.2.2	In-band emissions.....	847
6.4A.2.2.3	Carrier leakage.....	848
6.4A.2.3	Transmit modulation quality for inter-band CA.....	848
6.4A.2.4	Void.....	848
6.4B	Transmit signal quality for NR-DC.....	848
6.4C	Transmit signal quality for SUL.....	849
6.4D	Transmit signal quality for UL MIMO.....	849
6.4D.0	General.....	849
6.4D.1	Frequency error for UL MIMO.....	849
6.4D.2	Transmit modulation quality for UL MIMO.....	849
6.4D.2.0	General	849
6.4D.2.1	Error Vector Magnitude	850
6.4D.2.2	Carrier leakage	850
6.4D.2.3	In-band emissions	850
6.4D.2.4	EVM equalizer spectrum flatness for UL MIMO	850
6.4D.3	Time alignment error for UL MIMO	850
6.4D.4	Requirements for coherent UL MIMO	850
6.4E	Transmit signal quality for V2X.....	851
6.4E.1	Frequency error for V2X	851
6.4E.1.1	General	851
6.4E.1.1A	Frequency error for sidelink CA	851
6.4E.1.2	Frequency error for V2X concurrent operation.....	851
6.4E.1F	Frequency error for Sidelink Unlicensed	851
6.4E.1F.1	Frequency error for SL-U concurrent operation.....	852
6.4E.2	Transmit modulation quality for V2X	852
6.4E.2.1	General	852
6.4E.2.2	Error Vector Magnitude for V2X.....	852
6.4E.2.2A	Error Vector Magnitude for sidelink CA	852
6.4E.2.3	Carrier leakage for V2X.....	852
6.4E.2.3A	Carrier leakage for sidelink CA	852

6.4E.2.4	In-band emissions for V2X	852
6.4E.2.4A	In-band emissions for sidelink CA.....	852
6.4E.2.5	EVM equalizer spectrum flatness for V2X	852
6.4E.2.6	Transmit modulation quality for V2X concurrent operation.....	853
6.4E.2F	Transmit modulation quality for Sidelink Unlicensed	853
6.4E.2F.0	General	853
6.4E.2F.1	Error Vector Magnitude	853
6.4E.2F.2	Carrier leakage	853
6.4E.2F.3	In-band emissions	853
6.4E.2F.4	EVM equalizer spectrum flatness	853
6.4E.2F.5	Transmit modulation quality for SL-U concurrent operation.....	853
6.4F	Transmit signal quality for shared spectrum channel access.....	853
6.4F.1	Frequency error.....	853
6.4F.2	Transmit modulation quality.....	854
6.4F.2.0	General.....	854
6.4F.2.1	Error Vector Magnitude	854
6.4F.2.2	Carrier leakage	854
6.4F.2.3	In-band emissions	854
6.4F.2.4	EVM equalizer spectrum flatness	855
6.4F.2A	Transmit modulation quality for CA.....	855
6.4F.2A.1	Transmit modulation quality for inter-band CA.....	855
6.4G	Transmit signal quality for Tx Diversity	855
6.4G.1	Frequency error for Tx Diversity	855
6.4G.2	Transmit modulation quality for Tx Diversity	855
6.4G.2.0	General	855
6.4H	Transmit signal quality for CA with UL MIMO	856
6.4H.1	Transmit signal quality for intra-band UL contiguous CA with UL MIMO.....	856
6.4H.1.1	Frequency error for intra-band UL contiguous CA with UL MIMO	856
6.4H.1.2	Transmit modulation quality for intra-band UL contiguous CA with UL MIMO	856
6.4H.1.2.0	General	856
6.4H.1.2.1	Error Vector Magnitude.....	857
6.4H.1.2.2	Carrier leakage.....	857
6.4H.1.2.3	In-band emissions.....	857
6.4H.1.3	Time alignment error for intra-band UL contiguous CA with UL MIMO.....	857
6.4H.1.4	Coherent UL MIMO requirement for intra-band UL contiguous CA with UL MIMO.....	857
6.4H.2	Void	858
6.4H.3	Transmit signal quality for inter-band UL CA with UL MIMO	858
6.4H.3.1	Frequency error for inter-band UL CA with UL MIMO.....	858
6.4H.3.2	Transmit modulation quality for inter-band UL CA with UL MIMO.....	858
6.4I	(Reserved)	858
6.4J	Transmit signal quality for ATG	858
6.4J.0	Reserved	858
6.4J.0D	General.....	858
6.4J.1	Frequency error for ATG.....	858
6.4J.2	Transmit modulation quality for ATG.....	859
6.4J.2D	Transmit modulation quality for ATG UL MIMO	859
6.4J.2D.0	General	859
6.4J.2D.1	Error Vector Magnitude for ATG UL MIMO	859
6.4J.2D.2	Carrier leakage for ATG UL MIMO.....	859
6.4J.2D.3	In-band emissions for ATG UL MIMO	859
6.4J.2D.4	EVM equalizer spectrum flatness for ATG UL MIMO	859
6.4J.3D	Time alignment error for ATG	859
6.4J.3D.1	Time alignment error for ATG UL MIMO	859
6.4J.3D	Requirement for ATG coherent UL MIMO.....	859
6.4K	(Reserved)	860
6.4L	Transmit signal quality for CA with Tx Diversity.....	860
6.4L.1	Void	860
6.4L.2	Void	860
6.4L.3	Transmit signal quality for inter-band UL CA with Tx Diversity	860
6.4L.3.1	Frequency error for inter-band UL CA with Tx Diversity	860
6.4L.3.2	Transmit modulation quality for inter-band UL CA with Tx Diversity	860
6.5	Output RF spectrum emissions.....	860

6.5.1	Occupied bandwidth	860
6.5.2	Out of band emission	860
6.5.2.1	General	860
6.5.2.2	Spectrum emission mask	861
6.5.2.3	Additional spectrum emission mask	861
6.5.2.3.1	Requirements for network signalling value "NS_35"	861
6.5.2.3.2	Requirements for network signalling value "NS_04"	862
6.5.2.3.3	Requirements for network signalling values "NS_03" and "NS_03U"	862
6.5.2.3.4	Requirements for network signalling value "NS_06" or "NS_07"	863
6.5.2.3.5	Void	864
6.5.2.3.6	Void	864
6.5.2.3.7	Void	864
6.5.2.3.8	Requirements for network signalling value "NS_27"	864
6.5.2.3.9	Requirements for network signalling value "NS_21"	864
6.5.2.4	Adjacent channel leakage ratio	865
6.5.2.4.1	NR ACLR	865
6.5.2.4.2	UTRA ACLR	866
6.5.3	Spurious emissions	866
6.5.3.0	General	866
6.5.3.1	General spurious emissions	866
6.5.3.2	Spurious emissions for UE co-existence	867
6.5.3.3	Additional spurious emissions	875
6.5.3.3.1	Requirement for network signalling value "NS_04"	875
6.5.3.3.2	Requirement for network signalling value "NS_17"	875
6.5.3.3.3	Requirement for network signalling value "NS_18"	875
6.5.3.3.4	Requirement for network signalling values "NS_05" and "NS_05U"	876
6.5.3.3.5	Requirement for network signalling values "NS_43" and "NS_43U"	876
6.5.3.3.6	Requirement for network signalling value "NS_37"	876
6.5.3.3.7	Requirement for network signalling value "NS_38"	877
6.5.3.3.8	Requirement for network signalling value "NS_39"	877
6.5.3.3.9	Requirement for network signalling value "NS_40"	877
6.5.3.3.10	Requirement for network signalling value "NS_41"	877
6.5.3.3.11	Requirement for network signalling value "NS_42"	878
6.5.3.3.12	Requirement for network signalling value "NS_21"	878
6.5.3.3.13	Requirement for network signalling value "NS_24"	878
6.5.3.3.14	Requirement for network signalling value "NS_27"	879
6.5.3.3.15	Requirement for network signalling value "NS_47"	879
6.5.3.3.16	Requirement for network signalling value "NS_50"	879
6.5.3.3.17	Requirement for network signalling value "NS_12"	879
6.5.3.3.18	Requirement for network signalling value "NS_13"	880
6.5.3.3.19	Requirement for network signalling value "NS_14"	880
6.5.3.3.20	Requirement for network signalling value "NS_15"	880
6.5.3.3.21	Requirement for network signalling value "NS_45"	881
6.5.3.3.22	Requirement for network signalling values "NS_48" and "NS_51"	881
6.5.3.3.23	Requirement for network signalling value "NS_49"	881
6.5.3.3.24	Requirement for network signalling value "NS_44"	882
6.5.3.3.25	Requirement for network signalling value "NS_46"	882
6.5.3.3.26	Requirement for network signalling value "NS_07"	882
6.5.3.3.27	Requirement for network signalling value "NS_56"	882
6.5.3.3.28	Requirement for network signalling value "NS_62"	883
6.5.3.3.29	Requirement for network signalling value "NS_26"	883
6.5.3.3.30	Requirement for network signalling value "NS_36"	883
6.5.4	Transmit intermodulation	884
6.5A	Output RF spectrum emissions for CA	884
6.5A.0	General	884
6.5A.1	Occupied bandwidth for CA	884
6.5A.1.1	Void	884
6.5A.1.1a	Occupied bandwidth for Intra-band contiguous CA	884
6.5A.1.2	Occupied bandwidth for Intra-band non-contiguous CA	884
6.5A.1.3	Occupied bandwidth for Inter-band CA	885
6.5A.2	Out of band emission for CA	885
6.5A.2.1	General	885