



TECHNICAL SPECIFICATION

**5G;  
NR;  
User Equipment (UE) radio transmission and reception;  
Part 4: Performance requirements  
(3GPP TS 38.101-4 version 16.24.0 Release 16)**



---

**Reference**

RTS/TSGR-0438101-4vgo0

---

**Keywords**

5G

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° w061004871

---

**Important notice**

The present document can be downloaded from the  
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed, this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our [Coordinated Vulnerability Disclosure \(CVD\)](#) program.

---

**Notice of disclaimer & limitation of liability**

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2026.  
All rights reserved.

---

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

---

# Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found at [3GPP to ETSI numbering cross-referencing](#).

---

# Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

# Contents

Intellectual Property Rights .....	2
Legal Notice .....	2
Modal verbs terminology.....	2
Foreword.....	12
1 Scope .....	14
2 References .....	14
3.1 Definitions .....	15
3.2 Symbols.....	15
3.3 Abbreviations .....	15
4 General .....	17
4.1 Relationship between minimum requirements and test requirements .....	17
4.2 Applicability of minimum requirements .....	17
4.3 Specification suffix information.....	17
4.4 Conducted requirements.....	17
4.4.0 Introduction.....	17
4.4.1 Reference point.....	18
4.4.2 SNR definition.....	18
4.4.3 Noc.....	18
4.4.3.1 Introduction.....	18
4.4.3.2 Noc for NR operating bands in FR1.....	18
4.4.3.2.1 Derivation of Noc values for NR operating bands in FR1.....	18
4.4.4 Es.....	19
4.4.4.1 Introduction.....	19
4.4.4.2 Es for NR operating bands in FR1 .....	19
4.4.4.2.1 Derivation of Es values for NR operating bands in FR1 .....	19
4.5 Radiated requirements.....	20
4.5.0 Introduction.....	20
4.5.1 Reference point.....	20
4.5.2 SNR definition.....	20
4.5.3 Noc.....	21
4.5.3.1 Introduction.....	21
4.5.3.2 Noc for NR operating bands in FR2.....	21
4.5.3.3 Derivation of Noc values for NR operating bands in FR2 .....	21
4.5.4 Angle of arrival.....	22
4.5.5 Es.....	22
5 Demodulation performance requirements (Conducted requirements) .....	22
5.1 General .....	22
5.1.1 Applicability of requirements .....	22
5.1.1.1 General .....	22
5.1.1.2 Applicability of requirements for different number of RX antenna ports .....	22
5.1.1.3 Applicability of requirements for optional UE features .....	23
5.1.1.4 Applicability of requirements for mandatory UE features with capability signalling.....	27
5.1.1.5 Applicability of different requirements for HST.....	30
5.1.1.6 Applicability and test rules for PDSCH performance requirements with power imbalance for intra-band contiguous CA .....	31
5.1.1.7 Applicability of CA requirements .....	31
5.1.1.7.1 Definition of CA capability .....	31
5.1.1.7.2 Applicability and test rules for different CA configurations and bandwidth combination sets .....	31
5.1.1.7.3 Applicability rule and antenna connection for CA tests with 4 RX.....	33
5.1.1.8 Applicability of different requirements with Multi-TRxP .....	33
5.1.1.9 Applicability of requirements for PDSCH on bands with shared spectrum access.....	33
5.2 PDSCH demodulation requirements .....	33
5.2.1 1RX requirements .....	37
5.2.2 2RX requirements .....	37

5.2.2.1	FDD.....	37
5.2.2.1.1	Minimum requirements for PDSCH Mapping Type A.....	37
5.2.2.1.2	Minimum requirements for PDSCH Mapping Type A and CSI-RS overlapped with PDSCH .....	39
5.2.2.1.3	Minimum requirements for PDSCH Mapping Type B.....	40
5.2.2.1.4	Minimum requirements for PDSCH Mapping Type A and LTE-NR coexistence .....	41
5.2.2.1.5	Minimum requirements for PDSCH 0.001% BLER.....	42
5.2.2.1.6	Minimum requirements for PDSCH repetitions over multiple slots.....	43
5.2.2.1.7	Minimum requirements for PDSCH Mapping Type B and UE processing capability 2 .....	44
5.2.2.1.8	Minimum requirements for PDSCH pre-emption.....	45
5.2.2.1.9	Minimum requirements for PDSCH HST-SFN .....	46
5.2.2.1.10	Minimum requirements for HST-DPS.....	47
5.2.2.1.11	Minimum requirements for PDSCH Single-DCI based SDM scheme .....	50
5.2.2.1.12	Minimum requirements for PDSCH Multi-DCI based transmission scheme .....	53
5.2.2.1.13	Minimum requirements for PDSCH with single-DCI based FDM Scheme A .....	56
5.2.2.1.14	Minimum requirements for PDSCH with single-DCI based Inter-slot TDM scheme .....	59
5.2.2.2	TDD .....	62
5.2.2.2.1	Minimum requirements for PDSCH Mapping Type A.....	62
5.2.2.2.2	Minimum requirements for PDSCH Mapping Type A and CSI-RS overlapped with PDSCH .....	64
5.2.2.2.3	Minimum requirements for PDSCH Mapping Type B.....	65
5.2.2.2.4	Minimum requirements for PDSCH Mapping Type A and LTE-NR coexistence .....	66
5.2.2.2.5	Minimum requirements for PDSCH 0.001% BLER.....	67
5.2.2.2.6	Minimum requirements for PDSCH repetitions over multiple slots.....	68
5.2.2.2.7	Minimum requirements for PDSCH Mapping Type B and UE processing capability 2 .....	69
5.2.2.2.8	Minimum requirements for PDSCH pre-emption.....	70
5.2.2.2.9	Minimum requirements for HST-SFN.....	71
5.2.2.2.10	Minimum requirements for HST-DPS.....	72
5.2.2.2.11	Minimum requirements for PDSCH Single-DCI based SDM scheme .....	75
5.2.2.2.12	Minimum requirements for PDSCH Multi-DCI based transmission scheme .....	78
5.2.2.2.13	Minimum requirements for PDSCH with single-DCI based FDM Scheme A .....	81
5.2.2.2.14	Minimum requirements for PDSCH with single-DCI based Inter-slot TDM scheme .....	84
5.2.2.2.15	Minimum requirements for PDSCH of PCell on band with shared spectrum access .....	87
5.2.3	4RX requirements .....	88
5.2.3.1	FDD.....	88
5.2.3.1.1	Minimum requirements for PDSCH Mapping Type A.....	88
5.2.3.1.2	Minimum requirements for PDSCH Mapping Type A and CSI-RS overlapped with PDSCH .....	91
5.2.3.1.3	Minimum requirements for PDSCH Mapping Type B.....	92
5.2.3.1.4	Minimum requirements for PDSCH Mapping Type A and LTE-NR coexistence .....	93
5.2.3.1.5	Minimum requirements for PDSCH 0.001% BLER.....	94
5.2.3.1.6	Minimum requirements for PDSCH repetitions over multiple slots.....	94
5.2.3.1.7	Minimum requirements for PDSCH Mapping Type B and UE processing capability 2 .....	95
5.2.3.1.8	Minimum requirements for PDSCH pre-emption.....	96
5.2.3.1.9	Minimum requirements for PDSCH HST-SFN .....	97
5.2.3.1.10	Minimum requirements for HST-DPS.....	98
5.2.3.1.11	Minimum requirements for PDSCH Single-DCI based SDM scheme .....	101
5.2.3.1.12	Minimum requirements for PDSCH Multi-DCI based transmission scheme .....	104
5.2.3.1.13	Minimum requirements for PDSCH with single-DCI based FDM Scheme A .....	107
5.2.3.1.14	Minimum requirements for PDSCH with single-DCI based Inter-slot TDM scheme .....	110
5.2.3.2	TDD .....	113
5.2.3.2.1	Minimum requirements for PDSCH Mapping Type A.....	113
5.2.3.2.2	Minimum requirements for PDSCH Mapping Type A and CSI-RS overlapped with PDSCH .....	116
5.2.3.2.3	Minimum requirements for PDSCH Mapping Type B.....	117
5.2.3.2.4	Minimum requirements for PDSCH Mapping Type A and LTE-NR coexistence .....	118
5.2.3.2.5	Minimum requirements for PDSCH 0.001% BLER.....	119
5.2.3.2.6	Minimum requirements for PDSCH repetitions over multiple slots.....	120
5.2.3.2.7	Minimum requirements for PDSCH Mapping Type B and UE processing capability 2 .....	121
5.2.3.2.8	Minimum requirements for PDSCH pre-emption.....	122
5.2.3.2.9	Minimum requirements for HST-SFN.....	123
5.2.3.2.10	Minimum requirements for HST-DPS.....	124
5.2.3.2.11	Minimum requirements for PDSCH Single-DCI based SDM scheme .....	127
5.2.3.2.12	Minimum requirements for PDSCH Multi-DCI based transmission scheme .....	130
5.2.3.2.13	Minimum requirements for PDSCH with single-DCI based FDM Scheme A .....	133
5.2.3.2.14	Minimum requirements for PDSCH with single-DCI based Inter-slot TDM scheme .....	136

5.2.3.2.15	Minimum requirements for PDSCH of PCell on band with shared spectrum access .....	139
5.2A	PDSCH demodulation requirements for CA .....	140
5.2A.1	1RX requirements .....	142
5.2A.2	2RX requirements .....	142
5.2A.2.1	Minimum requirements .....	142
5.2A.2.2	Minimum requirements for carrier aggregation with power imbalance .....	144
5.2A.2.3	Minimum requirements for PDSCH of SCell on band with shared spectrum access .....	145
5.2A.3	4RX requirements .....	146
5.2A.3.1	Minimum requirements .....	146
5.2A.3.2	Minimum requirements for carrier aggregation with power imbalance .....	148
5.2A.3.3	Minimum requirements for PDSCH of SCell on band with shared spectrum access .....	149
5.3	PDCCH demodulation requirements .....	150
5.3.1	1RX requirements .....	153
5.3.2	2RX requirements .....	153
5.3.2.1	FDD .....	153
5.3.2.1.1	Minimum requirements with 1TX antenna .....	153
5.3.2.1.2	Minimum requirements with 2TX antenna .....	154
5.3.2.1.3	Minimum requirements for power saving .....	154
5.3.2.2	TDD .....	155
5.3.2.2.1	Minimum requirements with 1TX antenna .....	155
5.3.2.2.2	Minimum requirements with 2TX antenna .....	156
5.3.2.2.3	Minimum requirements for power saving .....	156
5.3.3	4RX requirements .....	157
5.3.3.1	FDD .....	157
5.3.3.1.1	Minimum requirements with 1TX antenna .....	157
5.3.3.1.2	Minimum requirements with 2TX antenna .....	157
5.3.3.1.3	Minimum requirements for power saving .....	158
5.3.3.2	TDD .....	158
5.3.3.2.1	Minimum requirements with 1TX antenna .....	159
5.3.3.2.2	Minimum requirements with 2TX antenna .....	159
5.3.3.2.3	Minimum requirements for power saving .....	159
5.4	PBCH demodulation requirements .....	160
5.4.1	1RX requirements .....	160
5.4.2	2RX requirements .....	161
5.4.2.1	FDD .....	161
5.4.2.2	TDD .....	161
5.4.3	4RX requirements .....	162
5.4.3.1	FDD .....	162
5.4.3.2	TDD .....	163
5.5	Sustained downlink data rate provided by lower layers .....	163
5.5.1	FR1 single carrier requirements .....	163
5.5A	Sustained downlink data rate provided by lower layers .....	163
5.5A.1	FR1 CA requirements .....	163
6	CSI reporting requirements (Conducted requirements) .....	170
6.1	General .....	170
6.1.1	Applicability of requirements .....	170
6.1.1.1	General .....	170
6.1.1.2	Applicability of requirements for different number of RX antenna ports .....	170
6.1.1.3	Applicability of requirements for optional UE features .....	170
6.1.1.4	Applicability of requirements for mandatory UE features with capability signalling .....	171
6.1.1.5	Applicability of Channel Quality Indicator (CQI) reporting requirements for CA .....	172
6.1.1.5.1	Applicability and test rules for different duplex modes and SCS combinations .....	172
6.1.1.5.2	Applicability and test rules for different CA configurations and bandwidth combination sets .....	172
6.1.1.5.3	Test coverage for different number of component carriers .....	173
6.1.1.5.4	Applicability rule and antenna connection for CA tests with 4 RX .....	173
6.1.2	Common test parameters .....	173
6.2	Reporting of Channel Quality Indicator (CQI) .....	178
6.2.1	1RX requirements .....	178
6.2.2	2RX requirements .....	178
6.2.2.1	FDD .....	178
6.2.2.1.1	CQI reporting definition under AWGN conditions .....	178

6.2.2.1.2	CQI reporting under fading conditions.....	181
6.2.2.2	TDD .....	186
6.2.2.2.1	CQI reporting definition under AWGN conditions .....	186
6.2.2.2.2	CQI reporting under fading conditions.....	191
6.2.3	4RX requirements .....	196
6.2.3.1	FDD.....	196
6.2.3.1.1	CQI reporting definition under AWGN conditions .....	196
6.2.3.1.2	CQI reporting under fading conditions.....	199
6.2.3.2	TDD .....	204
6.2.3.2.1	CQI reporting definition under AWGN.....	204
6.2.3.2.2	CQI reporting under fading conditions.....	209
6.2A	Reporting of Channel Quality Indicator (CQI) for CA.....	214
6.2A.1	General.....	214
6.2A.2	1RX requirements .....	214
6.2A.3	2RX requirements .....	214
6.2A.3.1	CQI reporting definition under AWGN conditions.....	214
6.2A.3.1.1	Minimum requirement for periodic CQI reporting .....	214
6.2A.4	4RX requirements .....	219
6.2A.4.1	CQI reporting definition under AWGN conditions.....	219
6.2A.4.1.1	Minimum requirement for CQI reporting for SCell on band with shared spectrum access.....	219
6.3	Reporting of Precoding Matrix Indicator (PMI).....	221
6.3.1	1RX requirements .....	222
6.3.2	2RX requirements .....	222
6.3.2.1	FDD.....	222
6.3.2.1.1	Single PMI with 4TX TypeI-SinglePanel Codebook .....	222
6.3.2.1.2	Single PMI with 8TX TypeI-SinglePanel Codebook .....	225
6.3.2.1.3	Multiple PMI with 16TX TypeI-SinglePanel Codebook.....	228
6.3.2.1.4	Single PMI with 32TX TypeI-SinglePanel Codebook .....	230
6.3.2.1.5	Multiple PMI with 16TX TypeII Codebook.....	232
6.3.2.1.6	Multiple PMI with 16TX Enhanced Type II Codebook .....	235
6.3.2.2	TDD .....	238
6.3.2.2.1	Single PMI with 4TX TypeI-SinglePanel Codebook .....	238
6.3.2.2.2	Single PMI with 8TX TypeI-SinglePanel Codebook .....	241
6.3.2.2.3	Multiple PMI with 16TX TypeI-SinglePanel Codebook.....	244
6.3.2.2.4	Single PMI with 32TX TypeI-SinglePanel Codebook .....	247
6.3.2.2.5	Multiple PMI with 16TX TypeII Codebook.....	249
6.3.2.2.6	Multiple PMI with 16Tx Enhanced Type II Codebook .....	252
6.3.3	4RX requirements .....	255
6.3.3.1	FDD.....	255
6.3.3.1.1	Single PMI with 4TX TypeI-SinglePanel Codebook .....	255
6.3.3.1.2	Single PMI with 8TX TypeI-SinglePanel Codebook .....	258
6.3.3.1.3	Multiple PMI with 16TX TypeI-SinglePanel Codebook.....	261
6.3.3.1.4	Single PMI with 32TX TypeI-SinglePanel Codebook .....	264
6.3.3.1.5	Multiple PMI with 16TX TypeII Codebook.....	266
6.3.3.1.6	Multiple PMI with 16Tx Enhanced Type II Codebook .....	269
6.3.3.2	TDD .....	272
6.3.3.2.1	Single PMI with 4TX TypeI-SinglePanel Codebook .....	272
6.3.3.2.2	Single PMI with 8TX TypeI-SinglePanel Codebook .....	275
6.3.3.2.3	Multiple PMI with 16TX TypeI-SinglePanel Codebook.....	278
6.3.3.2.4	Single PMI with 32TX TypeI-SinglePanel Codebook .....	281
6.3.3.2.5	Multiple PMI with 16TX TypeII Codebook.....	283
6.3.3.2.6	Multiple PMI with 16Tx Enhanced Type II Codebook .....	286
6.4	Reporting of Rank Indicator (RI) .....	289
6.4.1	1RX requirements .....	289
6.4.2	2RX requirements .....	289
6.4.2.1	FDD.....	289
6.4.2.2	TDD .....	293
6.4.3	4RX requirements .....	296
6.4.3.1	FDD.....	296
6.4.3.2	TDD .....	299
7	Demodulation performance requirements (Radiated requirements) .....	302

7.1	General .....	302
7.1.1	Applicability of requirements .....	302
7.1.1.1	General .....	302
7.1.1.2	Applicability of requirements for different number of RX antenna ports .....	302
7.1.1.3	Applicability of requirements for optional UE features .....	302
7.1.1.5	Applicability of CA requirements .....	304
7.1.1.5.1	Definition of CA capability .....	304
7.1.1.5.2	Applicability and test rules for different CA configurations and bandwidth combination sets .....	304
7.2	PDSCH demodulation requirements .....	304
7.2.1	1RX requirements .....	309
7.2.2	2RX requirements .....	309
7.2.2.1	FDD .....	309
7.2.2.2	TDD .....	309
7.2.2.2.1	Minimum requirements for PDSCH Mapping Type-A .....	309
7.2.2.2.2	Minimum requirements for PDSCH repetitions over multiple slots .....	311
7.2.2.2.3	Minimum requirements for PDSCH Mapping Type B .....	312
7.2A	PDSCH demodulation requirements for CA .....	313
7.2A.1	1RX requirements .....	313
7.2A.2	2RX requirements .....	313
7.2A.2.1	Minimum requirements .....	313
7.3	PDCCH demodulation requirements .....	314
7.3.1	1RX requirements .....	317
7.3.2	2RX requirements .....	317
7.3.2.1	FDD .....	317
7.3.2.2	TDD .....	317
7.3.2.2.1	Minimum requirements with 1TX antenna .....	318
7.3.2.2.2	Minimum requirements with 2TX antenna .....	318
7.3.2.2.3	Minimum requirements for power saving .....	318
7.4	PBCH demodulation requirements .....	319
7.4.1	1RX requirements .....	319
7.4.2	2RX requirements .....	319
7.4.2.1	FDD .....	319
7.4.2.2	TDD .....	320
7.5	Sustained downlink data rate provided by lower layers .....	320
7.5.1	FR2 single carrier requirements .....	320
7.5A	Sustained downlink data rate provided by lower layers .....	320
7.5A.1	FR2 CA requirements .....	320
8	CSI reporting requirements (Radiated requirements) .....	327
8.1	General .....	327
8.1.1	Applicability of requirements .....	327
8.1.1.1	General .....	327
8.1.1.2	Applicability of requirements for different number of RX antenna ports .....	327
8.1.1.3	Applicability of requirements for optional UE features .....	327
8.1.1.4	Applicability of requirements for mandatory UE features with capability signalling .....	327
8.1.1.5	Applicability of Channel Quality Indicator (CQI) reporting requirements for CA .....	328
8.1.1.5.1	Applicability and test rules for different CA configurations and bandwidth combination sets .....	328
8.1.1.5.2	Test coverage for different number of component carriers .....	328
8.1.2	Common test parameters .....	328
8.2	Reporting of Channel Quality Indicator (CQI) .....	333
8.2.1	1RX requirements .....	333
8.2.2	2RX requirements .....	333
8.2.2.1	FDD .....	333
8.2.2.2	TDD .....	333
8.2.2.2.1	CQI reporting under AWGN conditions .....	333
8.2.2.2.2	CQI reporting under fading conditions .....	335
8.2A	Reporting of Channel Quality Indicator (CQI) for CA .....	338
8.2A.1	General .....	338
8.2A.2	1RX requirements .....	338
8.2A.3	2RX requirements .....	338
8.2A.3.1	CQI reporting definition under AWGN conditions .....	338
8.2A.3.1.1	Minimum requirement for periodic CQI reporting .....	338

8.3	Reporting of Precoding Matrix Indicator (PMI).....	340
8.3.1	1RX requirements .....	340
8.3.2	2RX requirements .....	340
8.3.2.1	FDD.....	340
8.3.2.2	TDD .....	340
8.3.2.2.1	Single PMI with 2TX TypeI-SinglePanel Codebook .....	340
8.4	Reporting of Rank Indicator (RI) .....	344
8.4.1	1RX requirements .....	344
8.4.2	2RX requirements .....	344
8.4.2.1	FDD.....	344
8.4.2.2	TDD .....	344
9	Demodulation performance requirements for interworking.....	347
9.1	General .....	347
9.1.1	Applicability of requirements .....	347
9.1.1.1	Applicability of requirements for optional UE features .....	349
9.1.1.2	Applicability of requirements for mandatory UE features with capability signalling.....	349
9.1.2	E-UTRA Cell setup.....	349
9.1.2.1	FDD.....	349
9.1.2.2	TDD .....	350
9.2	PDSCH Demodulation .....	351
9.2A	PDSCH demodulation for CA .....	351
9.2A.1	NR CA between FR1 and FR2.....	351
9.2B	PDSCH demodulation for DC .....	352
9.2B.1	EN-DC .....	352
9.2B.1.1	EN-DC within FR1 .....	352
9.2B.1.1.1	PDSCH .....	352
9.2B.1.2	EN-DC including FR2 NR carrier only.....	352
9.2B.1.2.1	PDSCH .....	352
9.2B.1.3	EN-DC including FR1 and FR2 NR carriers.....	352
9.2B.2	NR DC between FR1 and FR2.....	352
9.3	PDCCH demodulation.....	352
9.3A	PDCCH demodulation for CA.....	352
9.3A.1	NR CA between FR1 and FR2.....	352
9.3B	PDCCH demodulation for DC.....	352
9.3B.1	EN-DC .....	352
9.3B.1.1	EN-DC within FR1 .....	352
9.3B.1.1.1	PDCCH.....	352
9.3B.1.2	EN-DC including FR2 NR carrier only.....	353
9.3B.1.2.1	PDCCH.....	353
9.3B.1.3	EN-DC including FR1 and FR2 NR carriers.....	353
9.3B.2	NR DC between FR1 and FR2.....	353
9.4	Void.....	353
9.4A	SDR test for CA .....	353
9.4A.1	NR CA between FR1 and FR2.....	353
9.4B	SDR test for DC .....	354
9.4B.1	EN-DC .....	354
9.4B.1.1	EN-DC within FR1 .....	354
9.4B.1.1.1	SDR test.....	354
9.4B.1.2	EN-DC including FR2 NR carrier.....	355
9.4B.1.2.1	SDR test.....	355
9.4B.1.3	EN-DC including FR1 and FR2 NR carriers.....	356
9.4B.3.1	NE-DC within FR1 .....	357
9.5B	PDSCH demodulation for DC with power imbalance.....	357
9.5B.1	EN-DC .....	357
9.5B.1.1	Intra-band contiguous EN-DC within FR1 .....	357
9.5B.1.1.1	PDSCH .....	357
9.5B.1.2	Intra-band non-contiguous EN-DC within FR1 .....	358
9.5B.1.2.1	PDSCH .....	358
10	CSI reporting requirements for interworking .....	360
10.1	General .....	360

10.1.1	Applicability of requirements .....	360
10.1.1.1	Applicability of requirements for optional UE features .....	361
10.1.1.2	Applicability of requirements for mandatory UE features with capability signalling .....	361
10.2	Reporting of Channel Quality Indicator (CQI) .....	361
10.2A	Reporting of Channel Quality Indicator (CQI) for CA .....	361
10.2B	Reporting of Channel Quality Indicator (CQI) for DC .....	361
10.2B.1	EN-DC .....	361
10.2B.1.1	EN-DC within FR1 .....	361
10.2B.1.2	EN-DC including FR2 NR carrier .....	361
10.2B.1.3	EN-DC including FR1 and FR2 NR carriers .....	361
10.2B.2	NR DC between FR1 and FR2 .....	362
10.3	Reporting of Precoding Matrix Indicator (PMI) .....	362
10.3A	Reporting of Precoding Matrix Indicator (PMI) for CA .....	362
10.3B	Reporting of Precoding Matrix Indicator (PMI) for DC .....	362
10.3B.1	EN-DC .....	362
10.3B.1.1	EN-DC within FR1 .....	362
10.3B.1.2	EN-DC including NR FR2 carrier .....	362
10.3B.1.3	EN-DC including FR1 and FR2 NR carriers .....	362
10.3B.2	NR DC between FR1 and FR2 .....	362
10.4	Reporting of Rank Indicator (RI) .....	362
10.4A	Reporting of Rank Indicator (RI) for CA .....	362
10.4B	Reporting of Rank Indicator (RI) for DC .....	362
10.4B.1	EN-DC .....	362
10.4B.1.1	EN-DC within FR1 .....	362
10.4B.1.2	EN-DC including NR FR2 carrier .....	363
10.4B.1.3	EN-DC including FR1 and FR2 NR carriers .....	363
10.4B.2	NR DC between FR1 and FR2 .....	363
11	V2X requirements .....	363
11.1	Demodulation performance requirements (Conducted requirements) .....	363
11.1.1	General .....	363
11.1.1.1	Applicability of requirements .....	363
11.1.1.1.1	General .....	363
11.1.1.1.2	Applicability of requirements for mandatory UE V2X features with capability signalling .....	363
11.1.1.2	Common test parameters .....	364
11.1.2	PSSCH demodulation requirements .....	365
11.1.2.1	2Rx requirements .....	365
11.1.2.1.1	Minimum requirements .....	365
11.1.3.1	2Rx requirements .....	365
11.1.3.1.1	Minimum requirements .....	365
11.1.4	PSBCH demodulation requirements .....	366
11.1.4.1	2Rx requirements .....	366
11.1.4.1.1	Minimum requirements .....	366
11.1.5	PSFCH demodulation requirements .....	367
11.1.5.1	2Rx requirements .....	367
11.1.5.1.1	Minimum requirements .....	367
11.1.6	Power imbalance performance with two links .....	368
11.1.6.1	2RX requirements .....	368
11.1.6.1.1	Minimum requirements .....	368
11.1.7	HARQ buffer soft combining test .....	368
11.1.7.1	2Rx requirement .....	368
11.1.7.1.1	Minimum requirement .....	368
11.1.8	PSCCH decoding capability test .....	369
11.1.8.1	2RX requirements .....	369
11.1.8.1.1	Minimum requirements .....	369
11.1.9	PSFCH decoding capability test .....	371
11.1.9.1	2RX requirements .....	371
11.1.9.1.1	Minimum requirements .....	371
<b>Annex A (normative): Measurement channels .....</b>		<b>372</b>
A.1	General .....	372
A.1.1	Throughput definition .....	372

A.1.2	TDD UL-DL configurations for FR1 .....	372
A.1.3	TDD UL-DL configurations for FR2 .....	377
A.2	Void.....	378
A.3	DL reference measurement channels .....	379
A.3.1	General .....	379
A.3.2	Reference measurement channels for PDSCH performance requirements .....	379
A.3.2.1	FDD .....	380
A.3.2.1.1	Reference measurement channels for SCS 15 kHz FR1 .....	380
A.3.2.1.2	Reference measurement channels for SCS 30 kHz FR1 .....	392
A.3.2.1.3	Reference measurement channels for SCS 60 kHz FR1 .....	393
A.3.2.1.4	Reference measurement channels for E-UTRA .....	393
A.3.2.2	TDD.....	399
A.3.2.2.1	Reference measurement channels for SCS 15 kHz FR1 .....	399
A.3.2.2.2	Reference measurement channels for SCS 30 kHz FR1 .....	402
A.3.2.2.3	Reference measurement channels for SCS 60 kHz FR1 .....	431
A.3.2.2.4	Reference measurement channels for SCS 60 kHz FR2 .....	431
A.3.2.2.5	Reference measurement channels for SCS 120 kHz FR2 .....	433
A.3.2.2.6	Reference measurement channels for E-UTRA .....	446
A.3.3	Reference measurement channels for PDCCH performance requirements .....	452
A.3.3.1	FDD .....	452
A.3.3.1.1	Reference measurement channels for SCS 15 kHz FR1 .....	452
A.3.3.1.2	Reference measurement channels for SCS 30 kHz FR1 .....	453
A.3.3.2	TDD.....	453
A.3.3.2.1	Reference measurement channels for SCS 15 kHz FR1 .....	453
A.3.3.2.2	Reference measurement channels for SCS 30 kHz FR1 .....	454
A.3.3.2.3	Reference measurement channels for SCS 60 kHz FR1 .....	455
A.3.3.2.4	Reference measurement channels for SCS 60 kHz FR2 .....	455
A.3.3.2.5	Reference measurement channels for SCS 120 kHz FR2 .....	455
A.3.4	Reference measurement channels for PBCH demodulation requirements .....	455
A.3.4.1	Reference measurement channels for FR1.....	455
A.3.4.2	Reference measurement channels for FR2.....	456
A.4	CSI reference measurement channels.....	456
A.5	OFDMA Channel Noise Generator (OCNG).....	459
A.5.1	OCNG Patterns for FDD .....	459
A.5.1.1	OCNG FDD pattern 1: Generic OCNG FDD Pattern for all unused REs.....	459
A.5.2	OCNG Patterns for TDD.....	460
A.5.2.1	OCNG TDD pattern 1: Generic OCNG TDD Pattern for all unused REs .....	460
A.6	SL reference measurement channels .....	461
A.6.1	General .....	461
A.6.2	Reference measurement channels for PSSCH performance requirements .....	461
A.6.3	Reference measurement channels for PSCCH performance requirements.....	462
A.6.4	Reference measurement for PSBCH performance requirements.....	462
<b>Annex B (normative): Propagation conditions .....</b>		<b>463</b>
B.1	Static propagation condition.....	463
B.1.1	UE Receiver with 2Rx.....	463
B.1.2	UE Receiver with 4Rx.....	463
B.2	Multi-path fading propagation conditions .....	464
B.2.1	Delay profiles .....	464
B.2.1.1	Delay profiles for FR1 .....	465
B.2.1.2	Delay profiles for FR2 .....	466
B.2.2	Combinations of channel model parameters .....	467
B.2.3	MIMO Channel Correlation Matrices .....	468
B.2.3.1	MIMO Correlation Matrices using Uniform Linear Array (ULA) .....	468
B.2.3.1.1	Definition of MIMO Correlation Matrices.....	468
B.2.3.1.2	MIMO Correlation Matrices at High, Medium and Low Level .....	470
B.2.3.2	MIMO Correlation Matrices using Cross Polarized Antennas (X-pol) .....	474

B.2.3.2.1	Definition of MIMO Correlation Matrices using cross polarized antennas .....	475
B.2.3.2.2	MIMO Correlation Matrices using cross polarized antennas .....	477
B.2.3.2.3	Beam steering approach .....	479
B.2.3.2.3A	Beam steering approach with dual cluster beams.....	481
B.2.4	Two-tap propagation conditions for CQI tests .....	482
B.3	High Speed Train Scenario.....	482
B.3.1	Single Tap Channel Profile .....	482
B.3.2	HST-SFN Channel Profile.....	486
B.3.3	HST-DPS Channel Profile.....	489
B.4	Physical signals, channels mapping and precoding.....	493
B.4.1	General .....	493
<b>Annex C (normative): Downlink physical channels .....</b>		<b>494</b>
C.1	General .....	494
C.2	Setup (Conducted).....	495
C.3	Connection (Conducted).....	495
C.3.1	Measurement of Performance requirements.....	495
C.4	Setup (Radiated).....	495
<b>Annex D (informative): Void .....</b>		<b>497</b>
<b>Annex E (normative): Environmental conditions.....</b>		<b>498</b>
E.1	General .....	498
E.2	Environmental (Conducted) .....	498
E.2.1	Temperature .....	498
E.2.2	Voltage .....	498
E.2.3	Vibration.....	499
E.3	Environmental (Radiated) .....	499
E.3.1	Temperature .....	499
E.3.2	Voltage .....	499
E.3.3	Void.....	500
<b>Annex F (informative): Void .....</b>		<b>501</b>
<b>Annex G (informative): Void .....</b>		<b>501</b>
<b>Annex H (informative): Void .....</b>		<b>501</b>
<b>Annex I (informative): Void .....</b>		<b>501</b>
<b>Annex J (informative): Void .....</b>		<b>501</b>
<b>Annex K (informative): Void .....</b>		<b>501</b>
<b>Annex L (informative): Change history .....</b>		<b>502</b>
History .....		511

---

# Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

In the present document, modal verbs have the following meanings:

**shall** indicates a mandatory requirement to do something

**shall not** indicates an interdiction (prohibition) to do something

The constructions "shall" and "shall not" are confined to the context of normative provisions, and do not appear in Technical Reports.

The constructions "must" and "must not" are not used as substitutes for "shall" and "shall not". Their use is avoided insofar as possible, and they are not used in a normative context except in a direct citation from an external, referenced, non-3GPP document, or so as to maintain continuity of style when extending or modifying the provisions of such a referenced document.

**should** indicates a recommendation to do something

**should not** indicates a recommendation not to do something

**may** indicates permission to do something

**need not** indicates permission not to do something

The construction "may not" is ambiguous and is not used in normative elements. The unambiguous constructions "might not" or "shall not" are used instead, depending upon the meaning intended.

**can** indicates that something is possible

**cannot** indicates that something is impossible

The constructions "can" and "cannot" are not substitutes for "may" and "need not".

**will** indicates that something is certain or expected to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document

**will not** indicates that something is certain or expected not to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document

**might** indicates a likelihood that something will happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

**might not** indicates a likelihood that something will not happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

In addition:

**is** (or any other verb in the indicative mood) indicates a statement of fact

**is not** (or any other negative verb in the indicative mood) indicates a statement of fact

The constructions "is" and "is not" do not indicate requirements.

# Sample Document

get full document from [standards.iteh.ai](https://standards.iteh.ai)

---

# 1 Scope

The present document establishes the minimum performance requirements for NR User Equipment (UE).

---

# 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 38.521-4: "NR; User Equipment (UE) radio transmission and reception; Part 4: Performance requirements".
- [3] Recommendation ITU-R M.1545: "Measurement uncertainty as it applies to test limits for the terrestrial component of International Mobile Telecommunications-2000".
- [4] 3GPP TS 36.101: "Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) radio transmission and reception".
- [5] 3GPP TR 38.901: "Study on channel model for frequencies from 0.5 to 100 GHz".
- [6] 3GPP TS 38.101-1: "NR; User Equipment (UE) radio transmission and reception; Part 1: Range 1 Standalone".
- [7] 3GPP TS 38.101-2: "NR; User Equipment (UE) radio transmission and reception; Part 2: Range 2 Standalone".
- [8] 3GPP TS 38.101-3: "NR; User Equipment (UE) radio transmission and reception; Part 3: Range 1 and Range 2 Interworking operation with other radios".
- [9] 3GPP TS 38.211: "NR; Physical channels and modulation".
- [10] 3GPP TS 38.212: "NR; Multiplexing and channel coding".
- [11] 3GPP TS 38.213: "NR; Physical layer procedures for control".
- [12] 3GPP TS 38.214: "NR; Physical layer procedures for data".
- [13] 3GPP TS 37.340: "Evolved Universal Terrestrial Radio Access (E-UTRA) and NR; Multi-connectivity", Stage 2.
- [14] 3GPP TS 38.306: "NR; User Equipment (UE) radio access capabilities".
- [15] 3GPP TS 36.211: "Evolved Universal Terrestrial Radio Access (E-UTRA); Physical Channels and Modulation".
- [16] 3GPP TS 38.521-4, "User Equipment (UE) conformance specification; Radio transmission and reception; Part 4: Performance"
- [17] 3GPP TS 38.331: "Radio Resource Control (RRC) protocol specification".