

ETSI TS 138 101-4 V17.20.0 (2026-04)



TECHNICAL SPECIFICATION

**5G;
NR;**
User Equipment (UE) radio transmission and reception;
Part 4: Performance requirements
(3GPP TS 38.101-4 version 17.20.0 Release 17)



Reference

RTS/TSGR-0438101-4vhk0

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed, this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our [Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2026.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by the ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found at [3GPP to ETSI numbering cross-referencing](#).

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	15
1 Scope	17
2 References	17
3 Definitions, symbols and abbreviations	18
3.1 Definitions	18
3.2 Symbols.....	18
3.3 Abbreviations	18
4 General	20
4.1 Relationship between minimum requirements and test requirements	20
4.2 Applicability of minimum requirements	20
4.3 Specification suffix information.....	20
4.4 Conducted requirements.....	21
4.4.0 Introduction.....	21
4.4.1 Reference point.....	21
4.4.2 SNR definition.....	21
4.4.3 Noc.....	21
4.4.3.1 Introduction.....	21
4.4.3.2 Noc for NR operating bands in FR1.....	21
4.4.3.2.1 Derivation of Noc values for NR operating bands in FR1.....	22
4.4.4 Es	22
4.4.4.1 Introduction.....	22
4.4.4.2 Es for NR operating bands in FR1	22
4.4.4.2.1 Derivation of Es values for NR operating bands in FR1	22
4.4.5 SINR definition.....	23
4.5 Radiated requirements.....	23
4.5.0 Introduction.....	23
4.5.1 Reference point.....	24
4.5.2 SNR definition	24
4.5.3 Noc.....	24
4.5.3.1 Introduction.....	24
4.5.3.2 Noc for NR operating bands in FR2.....	24
4.5.3.3 Derivation of Noc values for NR operating bands in FR2	25
4.5.4 Angle of arrival.....	25
4.5.5 Es	26
5 Demodulation performance requirements (Conducted requirements)	26
5.1 General	26
5.1.1 Applicability of requirements	26
5.1.1.1 General	26
5.1.1.2 Applicability of requirements for different number of RX antenna ports	26
5.1.1.3 Applicability of requirements for optional UE features	26
5.1.1.4 Applicability of requirements for mandatory UE features with capability signalling.....	30
5.1.1.5 Applicability of different requirements for HST.....	32
5.1.1.6 Applicability and test rules for PDSCH performance requirements with power imbalance for intra-band contiguous CA	33
5.1.1.7 Applicability of CA requirements	33
5.1.1.7.1 Definition of CA capability	33
5.1.1.7.2 Applicability and test rules for different CA configurations and bandwidth combination sets	33
5.1.1.7.3 Applicability rule and antenna connection for CA tests with 4 RX.....	34
5.1.1.7.4 Applicability of different requirements for HST.....	35
5.1.1.8 Applicability of different requirements with Multi-TRxP	37

5.1.1.9	Applicability of requirements for PDSCH on bands with shared spectrum access.....	37
5.1.1.10	Applicability of requirements for PDSCH with inter cell interference	38
5.1.1.11	Applicability of requirements for RedCap	38
5.2	PDSCH demodulation requirements	39
5.2.1	1RX requirements	41
5.2.1.1	FDD.....	41
5.2.1.1.1	Minimum requirements for RedCap.....	41
5.2.1.2	TDD	42
5.2.1.2.1	Minimum requirements for RedCap.....	42
5.2.2	2RX requirements	44
5.2.2.1	FDD.....	44
5.2.2.1.1	Minimum requirements for PDSCH Mapping Type A.....	44
5.2.2.1.2	Minimum requirements for PDSCH Mapping Type A and CSI-RS overlapped with PDSCH	45
5.2.2.1.3	Minimum requirements for PDSCH Mapping Type B.....	46
5.2.2.1.4	Minimum requirements for PDSCH Mapping Type A and LTE-NR coexistence	47
5.2.2.1.5	Minimum requirements for PDSCH 0.001% BLER.....	48
5.2.2.1.6	Minimum requirements for PDSCH repetitions over multiple slots.....	49
5.2.2.1.7	Minimum requirements for PDSCH Mapping Type B and UE processing capability 2	50
5.2.2.1.8	Minimum requirements for PDSCH pre-emption.....	51
5.2.2.1.9	Minimum requirements for PDSCH HST-SFN	52
5.2.2.1.10	Minimum requirements for HST-DPS.....	53
5.2.2.1.11	Minimum requirements for PDSCH Single-DCI based SDM scheme	55
5.2.2.1.12	Minimum requirements for PDSCH Multi-DCI based transmission scheme	56
5.2.2.1.13	Minimum requirements for PDSCH with single-DCI based FDM Scheme A	58
5.2.2.1.14	Minimum requirements for PDSCH with single-DCI based Inter-slot TDM scheme	60
5.2.2.1.15	Minimum requirements for PDSCH with inter-cell interference.....	61
5.2.2.1.16	Minimum requirements for PDSCH with intra cell inter user interference	62
5.2.2.1.17	Minimum requirements for RedCap.....	64
5.2.2.1.18	Minimum requirements for PDSCH CRS interference mitigation under NR-LTE coexistence scenario.....	65
5.2.2.1.19	Minimum requirements for PDSCH with inter cell CRS interference	67
5.2.2.1.20	Minimum requirements for HST-SFN Scheme A	69
5.2.2.1.21	Minimum requirements for HST-SFN Scheme B	71
5.2.2.2	TDD	73
5.2.2.2.1	Minimum requirements for PDSCH Mapping Type A.....	73
5.2.2.2.2	Minimum requirements for PDSCH Mapping Type A and CSI-RS overlapped with PDSCH	75
5.2.2.2.3	Minimum requirements for PDSCH Mapping Type B.....	76
5.2.2.2.4	Minimum requirements for PDSCH Mapping Type A and LTE-NR coexistence	76
5.2.2.2.5	Minimum requirements for PDSCH 0.001% BLER.....	78
5.2.2.2.6	Minimum requirements for PDSCH repetitions over multiple slots.....	78
5.2.2.2.7	Minimum requirements for PDSCH Mapping Type B and UE processing capability 2	79
5.2.2.2.8	Minimum requirements for PDSCH pre-emption.....	80
5.2.2.2.9	Minimum requirements for HST-SFN.....	81
5.2.2.2.10	Minimum requirements for HST-DPS.....	82
5.2.2.2.11	Minimum requirements for PDSCH Single-DCI based SDM scheme	84
5.2.2.2.12	Minimum requirements for PDSCH Multi-DCI based transmission scheme	86
5.2.2.2.13	Minimum requirements for PDSCH with single-DCI based FDM Scheme A	87
5.2.2.2.14	Minimum requirements for PDSCH with single-DCI based Inter-slot TDM scheme	89
5.2.2.2.15	Minimum requirements for PDSCH of PCell on band with shared spectrum access	90
5.2.2.2.16	Minimum requirements for PDSCH with inter-cell interference.....	91
5.2.2.2.17	Minimum requirements for PDSCH with intra cell inter user interference	93
5.2.2.2.18	Minimum requirements for RedCap.....	94
5.2.2.2.19	Minimum requirements for PDSCH CRS interference mitigation under NR-LTE coexistence scenario.....	95
5.2.2.2.20	Minimum requirements for PDSCH with inter cell CRS interference	97
5.2.2.2.21	Minimum requirements for HST-SFN Scheme A	99
5.2.2.2.22	Minimum requirements for HST-SFN Scheme B	101
5.2.3	4RX requirements	103
5.2.3.1	FDD.....	103
5.2.3.1.1	Minimum requirements for PDSCH Mapping Type A.....	103
5.2.3.1.2	Minimum requirements for PDSCH Mapping Type A and CSI-RS overlapped with PDSCH	105
5.2.3.1.3	Minimum requirements for PDSCH Mapping Type B.....	106

5.2.3.1.4	Minimum requirements for PDSCH Mapping Type A and LTE-NR coexistence	107
5.2.3.1.5	Minimum requirements for PDSCH 0.001% BLER.....	108
5.2.3.1.6	Minimum requirements for PDSCH repetitions over multiple slots.....	109
5.2.3.1.7	Minimum requirements for PDSCH Mapping Type B and UE processing capability 2	110
5.2.3.1.8	Minimum requirements for PDSCH pre-emption.....	111
5.2.3.1.9	Minimum requirements for PDSCH HST-SFN	112
5.2.3.1.10	Minimum requirements for HST-DPS.....	112
5.2.3.1.11	Minimum requirements for PDSCH Single-DCI based SDM scheme	114
5.2.3.1.12	Minimum requirements for PDSCH Multi-DCI based transmission scheme	116
5.2.3.1.13	Minimum requirements for PDSCH with single-DCI based FDM Scheme A	118
5.2.3.1.14	Minimum requirements for PDSCH with single-DCI based Inter-slot TDM scheme	119
5.2.3.1.15	Minimum requirements for PDSCH with inter-cell interference.....	121
5.2.3.1.16	Minimum requirements for PDSCH with intra-cell inter-user interference	122
5.2.3.1.17	Minimum requirements for PDSCH CRS interference mitigation under NR-LTE coexistence scenario.....	124
5.2.3.1.18	Minimum requirements for PDSCH with inter cell CRS interference	125
5.2.3.1.19	Minimum requirements for HST-SFN Scheme A	127
5.2.3.1.20	Minimum requirements for HST-SFN Scheme B	129
5.2.3.2	TDD	131
5.2.3.2.1	Minimum requirements for PDSCH Mapping Type A.....	131
5.2.3.2.2	Minimum requirements for PDSCH Mapping Type A and CSI-RS overlapped with PDSCH	133
5.2.3.2.3	Minimum requirements for PDSCH Mapping Type B	134
5.2.3.2.4	Minimum requirements for PDSCH Mapping Type A and LTE-NR coexistence	135
5.2.3.2.5	Minimum requirements for PDSCH 0.001% BLER.....	136
5.2.3.2.6	Minimum requirements for PDSCH repetitions over multiple slots.....	137
5.2.3.2.7	Minimum requirements for PDSCH Mapping Type B and UE processing capability 2	138
5.2.3.2.8	Minimum requirements for PDSCH pre-emption.....	139
5.2.3.2.9	Minimum requirements for HST-SFN.....	140
5.2.3.2.10	Minimum requirements for HST-DPS.....	141
5.2.3.2.11	Minimum requirements for PDSCH Single-DCI based SDM scheme	143
5.2.3.2.12	Minimum requirements for PDSCH Multi-DCI based transmission scheme	144
5.2.3.2.13	Minimum requirements for PDSCH with single-DCI based FDM Scheme A	146
5.2.3.2.14	Minimum requirements for PDSCH with single-DCI based Inter-slot TDM scheme	147
5.2.3.2.16	Minimum requirements for PDSCH with inter-cell interference.....	150
5.2.3.2.17	Minimum requirements for PDSCH with intra-cell inter-user interference	152
5.2.3.2.18	Minimum requirements for PDSCH CRS interference mitigation under NR-LTE coexistence scenario.....	153
5.2.3.2.19	Minimum requirements for PDSCH with inter cell CRS interference	155
5.2.3.2.20	Minimum requirements for HST-SFN Scheme A	157
5.2.3.2.21	Minimum requirements for HST-SFN Scheme B	159
5.2.A	PDSCH demodulation requirements for CA	161
5.2.A.1	1RX requirements	162
5.2.A.2	2RX requirements	162
5.2.A.2.1	Minimum requirements	162
5.2.A.2.2	Minimum requirements for carrier aggregation with power imbalance	164
5.2.A.2.3	Minimum requirements for PDSCH of SCell on band with shared spectrum access.....	165
5.2.A.2.5	Minimum requirements for PDSCH HST-DPS CA	168
5.2.A.3	4RX requirements	172
5.2.A.3.1	Minimum requirements	172
5.2.A.3.2	Minimum requirements for carrier aggregation with power imbalance	174
5.2.A.3.3	Minimum requirements for PDSCH of SCell on band with shared spectrum access.....	175
5.2.A.3.4	Minimum requirements for HST-SFN CA.....	176
5.2.A.3.5	Minimum requirements for PDSCH HST-DPS CA	178
5.3	PDCCH demodulation requirements	182
5.3.1	1RX requirements	184
5.3.1.1	FDD.....	184
5.3.1.1.1	Minimum requirements for RedCap.....	184
5.3.1.2	TDD	184
5.3.1.2.1	Minimum requirements for RedCap.....	185
5.3.2	2RX requirements	185
5.3.2.1	FDD.....	185
5.3.2.1.1	Minimum requirements with 1TX antenna.....	185

5.3.2.1.2	Minimum requirements with 2TX antenna.....	186
5.3.2.1.3	Minimum requirements for power saving	186
5.3.2.1.4	Minimum requirements for RedCap.....	187
5.3.2.1.5	Minimum requirements for PDCCH with intra-slot repetition.....	187
5.3.2.2	TDD	188
5.3.2.2.1	Minimum requirements with 1TX antenna.....	188
5.3.2.2.2	Minimum requirements with 2TX antenna.....	189
5.3.2.2.3	Minimum requirements for power saving	189
5.3.2.2.4	Minimum requirements for RedCap.....	190
5.3.2.2.5	Minimum requirements for PDCCH with intra-slot repetition.....	190
5.3.3	4RX requirements	191
5.3.3.1	FDD.....	191
5.3.3.1.1	Minimum requirements with 1TX antenna.....	191
5.3.3.1.2	Minimum requirements with 2TX antenna.....	192
5.3.3.1.3	Minimum requirements for power saving	192
5.3.3.1.4	Minimum requirements for PDCCH with intra-slot repetition.....	193
5.3.3.2	TDD	194
5.3.3.2.1	Minimum requirements with 1TX antenna.....	194
5.3.3.2.2	Minimum requirements with 2TX antenna.....	194
5.3.3.2.3	Minimum requirements for power saving	195
5.3.3.2.4	Minimum requirements for PDCCH with intra-slot repetition.....	195
5.4	PBCH demodulation requirements	196
5.4.1	1RX requirements	197
5.4.1.1	FDD.....	197
5.4.1.2	TDD	197
5.4.2	2RX requirements	197
5.4.2.1	FDD.....	197
5.4.2.2	TDD	198
5.4.3	4RX requirements	199
5.4.3.1	FDD.....	199
5.4.3.2	TDD	199
5.5	Sustained downlink data rate provided by lower layers	200
5.5.1	FR1 single carrier requirements.....	200
5.5A	Sustained downlink data rate provided by lower layers	200
5.5A.1	FR1 CA requirements	200
6	CSI reporting requirements (Conducted requirements)	206
6.1	General	206
6.1.1	Applicability of requirements	206
6.1.1.1	General	206
6.1.1.2	Applicability of requirements for different number of RX antenna ports	206
6.1.1.3	Applicability of requirements for optional UE features	206
6.1.1.4	Applicability of requirements for mandatory UE features with capability signalling.....	207
6.1.1.5	Applicability of Channel Quality Indicator (CQI) reporting requirements for CA.....	208
6.1.1.5.1	Applicability and test rules for different duplex modes and SCS combinations	208
6.1.1.5.2	Applicability and test rules for different CA configurations and bandwidth combination sets	208
6.1.1.5.3	Test coverage for different number of component carriers.....	209
6.1.1.5.4	Applicability rule and antenna connection for CA tests with 4 RX.....	209
6.1.1.6	Applicability of requirements for RedCap	209
6.1.2	Common test parameters	209
6.2	Reporting of Channel Quality Indicator (CQI).....	212
6.2.1	1RX requirements	213
6.2.1.1	FDD.....	213
6.2.1.1.1	CQI reporting definition under AWGN conditions	213
6.2.1.1.1.1	Minimum requirement for periodic CQI reporting for RedCap.....	213
6.2.1.1.2	CQI reporting under fading conditions.....	214
6.2.1.2	TDD	215
6.2.1.2.1	CQI reporting definition under AWGN conditions	215
6.2.1.2.2	CQI reporting under fading conditions.....	217
6.2.2	2RX requirements	218
6.2.2.1	FDD.....	218
6.2.2.1.1	CQI reporting definition under AWGN conditions	218

6.2.2.1.1.1	Minimum requirement for periodic CQI reporting	218
6.2.2.1.1.2	Minimum requirement for periodic CQI reporting with Table 3	220
6.2.2.1.1.3	Minimum requirement for periodic CQI reporting with Table 4	221
6.2.2.1.1.4	Minimum requirement for periodic CQI reporting for RedCap	222
6.2.2.1.2	CQI reporting under fading conditions	223
6.2.2.1.2.1	Minimum requirement for wideband CQI reporting	223
6.2.2.1.2.2	Minimum requirement for sub-band CQI reporting	225
6.2.2.1.2.3	Minimum requirement for wideband CQI reporting with inter-cell interference	226
6.2.2.1.2.4	Minimum requirement for wideband CQI reporting for RedCap	228
6.2.2.2	TDD	230
6.2.2.2.1	CQI reporting definition under AWGN conditions	230
6.2.2.2.1.1	Minimum requirement for periodic CQI reporting	230
6.2.2.2.1.2	Minimum requirement for periodic CQI reporting with Table 3	231
6.2.2.2.1.3	Minimum requirement for CQI reporting for PCell on band with shared spectrum access	232
6.2.2.2.1.4	Minimum requirement for periodic CQI reporting with Table 4	234
6.2.2.2.1.5	Minimum requirement for periodic CQI reporting for RedCap	235
6.2.2.2.2	CQI reporting under fading conditions	237
6.2.2.2.2.1	Minimum requirement for wideband CQI reporting	237
6.2.2.2.2.2	Minimum requirement for sub-band CQI reporting	238
6.2.2.2.2.3	Minimum requirement for wideband CQI reporting with inter-cell interference	240
6.2.2.2.2.4	Minimum requirement for wideband CQI reporting for RedCap	242
6.2.3	4RX requirements	243
6.2.3.1	FDD	243
6.2.3.1.1	CQI reporting definition under AWGN conditions	243
6.2.3.1.1.1	Minimum requirement for period CQI reporting	243
6.2.3.1.1.2	Minimum requirement for period CQI reporting with Table 3	245
6.2.3.1.1.3	Minimum requirement for periodic CQI reporting with Table 4	246
6.2.3.1.2	CQI reporting under fading conditions	247
6.2.3.1.2.1	Minimum requirement for wideband CQI reporting	247
6.2.3.1.2.2	Minimum requirement for sub-band CQI reporting	248
6.2.3.1.2.3	Minimum requirement for wideband CQI reporting with inter-cell interference	250
6.2.3.2	TDD	252
6.2.3.2.1	CQI reporting definition under AWGN	252
6.2.3.2.1.1	Minimum requirement for CQI periodic reporting	252
6.2.3.2.1.2	Minimum requirement for CQI periodic reporting with Table 3	253
6.2.3.2.1.3	Minimum requirement for CQI reporting for PCell on band with shared spectrum access	255
6.2.3.2.1.4	Minimum requirement for CQI periodic reporting with Table 4	256
6.2.3.2.2	CQI reporting under fading conditions	258
6.2.3.2.2.1	Minimum requirement for wideband CQI reporting	258
6.2.3.2.2.2	Minimum requirement for sub-band CQI reporting	259
6.2.3.2.2.3	Minimum requirement for wideband CQI reporting with inter-cell interference	261
6.2A	Reporting of Channel Quality Indicator (CQI) for CA	263
6.2A.1	General	263
6.2A.2	1RX requirements	263
6.2A.3	2RX requirements	263
6.2A.3.1	CQI reporting definition under AWGN conditions	263
6.2A.3.1.1	Minimum requirement for periodic CQI reporting	263
6.2A.3.1.2	Minimum requirement for CQI reporting for SCell on band with shared spectrum access	266
6.2A.4	4RX requirements	268
6.2A.4.1	CQI reporting definition under AWGN conditions	268
6.2A.4.1.1	Minimum requirement for CQI reporting for SCell on band with shared spectrum access	268
6.3	Reporting of Precoding Matrix Indicator (PMI)	270
6.3.1	1RX requirements	270
6.3.1.1	FDD	270
6.3.1.1.1	Single PMI with 4TX TypeI-SinglePanel Codebook for RedCap	270
6.3.1.2	TDD	272
6.3.1.2.1	Single PMI with 4TX TypeI-SinglePanel Codebook for RedCap	272
6.3.2	2RX requirements	274
6.3.2.1	FDD	274
6.3.2.1.1	Single PMI with 4TX TypeI-SinglePanel Codebook	274
6.3.2.1.2	Single PMI with 8TX TypeI-SinglePanel Codebook	275
6.3.2.1.3	Multiple PMI with 16TX TypeI-SinglePanel Codebook	277

6.3.2.1.4	Single PMI with 32TX TypeI-SinglePanel Codebook	279
6.3.2.1.5	Multiple PMI with 16TX TypeII Codebook.....	280
6.3.2.1.6	Multiple PMI with 16TX Enhanced Type II Codebook	282
6.3.2.1.7	Single PMI with 8 ports TypeI-SinglePanel Codebook for Single-DCI based transmission scheme	284
6.3.2.2	TDD	287
6.3.2.2.1	Single PMI with 4TX TypeI-SinglePanel Codebook	287
6.3.2.2.2	Single PMI with 8TX TypeI-SinglePanel Codebook	288
6.3.2.2.3	Multiple PMI with 16TX TypeI-SinglePanel Codebook.....	290
6.3.2.2.4	Single PMI with 32TX TypeI-SinglePanel Codebook	292
6.3.2.2.5	Multiple PMI with 16TX TypeII Codebook.....	293
6.3.2.2.6	Multiple PMI with 16Tx Enhanced Type II Codebook	295
6.3.2.2.7	Single PMI with 4TX TypeI-SinglePanel Codebook for RedCap.....	297
6.3.2.2.8	Single PMI with 8 ports TypeI-SinglePanel Codebook for Single-DCI based transmission scheme	299
6.3.3	4RX requirements	301
6.3.3.1	FDD.....	301
6.3.3.1.1	Single PMI with 4TX TypeI-SinglePanel Codebook	301
6.3.3.1.2	Single PMI with 8TX TypeI-SinglePanel Codebook	303
6.3.3.1.3	Multiple PMI with 16TX TypeI-SinglePanel Codebook.....	305
6.3.3.1.4	Single PMI with 32TX TypeI-SinglePanel Codebook	307
6.3.3.1.5	Multiple PMI with 16TX TypeII Codebook.....	308
6.3.3.1.6	Multiple PMI with 16Tx Enhanced Type II Codebook	310
6.3.3.1.7	Single PMI with 8 ports TypeI-SinglePanel Codebook for Single-DCI based transmission scheme	312
6.3.3.2	TDD	315
6.3.3.2.1	Single PMI with 4TX TypeI-SinglePanel Codebook	315
6.3.3.2.2	Single PMI with 8TX TypeI-SinglePanel Codebook	317
6.3.3.2.3	Multiple PMI with 16TX TypeI-SinglePanel Codebook.....	318
6.3.3.2.4	Single PMI with 32TX TypeI-SinglePanel Codebook	320
6.3.3.2.5	Multiple PMI with 16TX TypeII Codebook.....	322
6.3.3.2.6	Multiple PMI with 16Tx Enhanced Type II Codebook	324
6.3.3.2.7	Single PMI with 8 ports TypeI-SinglePanel Codebook for Single-DCI based transmission scheme	326
6.4	Reporting of Rank Indicator (RI)	328
6.4.1	1RX requirements	329
6.4.2	2RX requirements	329
6.4.2.1	FDD.....	329
6.4.2.1.1	Minimum requirements for RedCap.....	330
6.4.2.2	TDD	331
6.4.2.2.1	Minimum requirements for RedCap.....	333
6.4.3	4RX requirements	334
6.4.3.1	FDD.....	334
6.4.3.2	TDD	335
7	Demodulation performance requirements (Radiated requirements)	337
7.1	General	337
7.1.1	Applicability of requirements	337
7.1.1.1	General	337
7.1.1.2	Applicability of requirements for different number of RX antenna ports	337
7.1.1.3	Applicability of requirements for optional UE features	338
7.1.1.5	Applicability of CA requirements	339
7.1.1.5.1	Definition of CA capability	339
7.1.1.5.2	Applicability and test rules for different CA configurations and bandwidth combination sets	339
7.1.1.6	Applicability of requirements for operating bands in FR2-1	340
7.1.1.7	Applicability of requirements for RedCap	340
7.1.1.8	Applicability of requirements for operating bands in FR2-2	341
7.2	PDSCH demodulation requirements	341
7.2.1	1RX requirements	345
7.2.2	2RX requirements	345
7.2.2.1	FDD.....	345
7.2.2.2	TDD	345

7.2.2.2.1	Minimum requirements for PDSCH Mapping Type-A	345
7.2.2.2.2	Minimum requirements for PDSCH repetitions over multiple slots.....	348
7.2.2.2.3	Minimum requirements for PDSCH Mapping Type B	349
7.2.2.2.4	Minimum requirements for HST-DPS.....	350
7.2A	PDSCH demodulation requirements for CA	357
7.2A.1	1RX requirements	357
7.2A.2	2RX requirements	357
7.2A.2.1	Minimum requirements	357
7.3	PDCCH demodulation requirements	358
7.3.1	1RX requirements	360
7.3.2	2RX requirements	360
7.3.2.1	FDD.....	360
7.3.2.2	TDD	360
7.3.2.2.1	Minimum requirements with 1TX antenna.....	360
7.3.2.2.2	Minimum requirements with 2TX antenna.....	361
7.3.2.2.3	Minimum requirements for power saving	362
7.4	PBCH demodulation requirements	362
7.4.1	1RX requirements	362
7.4.2	2RX requirements	363
7.4.2.1	FDD.....	363
7.4.2.2	TDD	363
7.5	Sustained downlink data rate provided by lower layers	363
7.5.1	FR2 single carrier requirements.....	363
7.5A	Sustained downlink data rate provided by lower layers	364
7.5A.1	FR2 CA requirements	364
8	CSI reporting requirements (Radiated requirements).....	368
8.1	General	368
8.1.1	Applicability of requirements	368
8.1.1.1	General	368
8.1.1.2	Applicability of requirements for different number of RX antenna ports	369
8.1.1.3	Applicability of requirements for optional UE features	369
8.1.1.4	Applicability of requirements for mandatory UE features with capability signalling	369
8.1.1.5	Applicability of Channel Quality Indicator (CQI) reporting requirements for CA	369
8.1.1.5.1	Applicability and test rules for different CA configurations and bandwidth combination sets	369
8.1.1.5.2	Test coverage for different number of component carriers	370
8.1.1.6	Applicability of requirements for RedCap	370
8.1.2	Common test parameters	370
8.2	Reporting of Channel Quality Indicator (CQI).....	373
8.2.1	1RX requirements	373
8.2.2	2RX requirements	373
8.2.2.1	FDD.....	373
8.2.2.2	TDD	373
8.2.2.2.1	CQI reporting under AWGN conditions.....	373
8.2.2.2.1.1	Minimum requirement for periodic CQI reporting	374
8.2.2.2.2	CQI reporting under fading conditions.....	376
8.2.2.2.2.1	Minimum requirement for wideband CQI reporting	376
8.2A	Reporting of Channel Quality Indicator (CQI) for CA.....	377
8.2A.1	General.....	377
8.2A.2	1RX requirements	377
8.2A.3	2RX requirements	378
8.2A.3.1	CQI reporting definition under AWGN conditions.....	378
8.2A.3.1.1	Minimum requirement for periodic CQI reporting.....	378
8.3	Reporting of Precoding Matrix Indicator (PMI).....	379
8.3.1	1RX requirements	380
8.3.2	2RX requirements	380
8.3.2.1	FDD.....	380
8.3.2.2	TDD	380
8.3.2.2.1	Single PMI with 2TX TypeI-SinglePanel Codebook	380
8.4	Reporting of Rank Indicator (RI)	382
8.4.1	1RX requirements	382
8.4.2	2RX requirements	382

8.4.2.1	FDD.....	382
8.4.2.2	TDD	382
9	Demodulation performance requirements for interworking.....	384
9.1	General	384
9.1.1	Applicability of requirements	384
9.1.1.1	Applicability of requirements for optional UE features	386
9.1.1.2	Applicability of requirements for mandatory UE features with capability signalling.....	386
9.1.1.3	Applicability of requirements for operating bands in FR2-2	386
9.1.2	E-UTRA Cell setup.....	387
9.1.2.1	FDD.....	387
9.1.2.2	TDD	388
9.2	PDSCH Demodulation	389
9.2A	PDSCH demodulation for CA.....	389
9.2A.1	NR CA between FR1 and FR2.....	389
9.2A.1.1	NR CA between FR1 and FR2-2.....	389
9.2B	PDSCH demodulation for DC.....	390
9.2B.1	EN-DC	390
9.2B.1.1	EN-DC within FR1	390
9.2B.1.1.1	PDSCH	390
9.2B.1.2	EN-DC including FR2 NR carrier only.....	390
9.2B.1.2.1	PDSCH	390
9.2B.1.3	EN-DC including FR1 and FR2 NR carriers.....	391
9.2B.2	NR DC between FR1 and FR2.....	391
9.3	PDCCH demodulation.....	391
9.3A	PDCCH demodulation for CA.....	391
9.3A.1	NR CA between FR1 and FR2.....	391
9.3A.1.1	NR CA between FR1 and FR2-2.....	391
9.3B	PDCCH demodulation for DC.....	391
9.3B.1	EN-DC	391
9.3B.1.1	EN-DC within FR1	391
9.3B.1.1.1	PDCCH.....	391
9.3B.1.2	EN-DC including FR2 NR carrier only.....	391
9.3B.1.2.1	PDCCH.....	391
9.3B.1.3	EN-DC including FR1 and FR2 NR carriers.....	391
9.3B.2	NR DC between FR1 and FR2.....	391
9.4	Void.....	392
9.4A	SDR test for CA	392
9.4A.1	NR CA between FR1 and FR2.....	392
9.4B	SDR test for DC	392
9.4B.1	EN-DC	392
9.4B.1.1	EN-DC within FR1	392
9.4B.1.1.1	SDR test.....	392
9.4B.1.2	EN-DC including FR2 NR carrier.....	394
9.4B.1.2.1	SDR test.....	394
9.4B.1.3	EN-DC including FR1 and FR2 NR carriers.....	395
9.4B.2	NR DC between FR1 and FR2.....	395
9.4B.3.1	NE-DC within FR1	396
9.5B	PDSCH demodulation for DC with power imbalance.....	396
9.5B.1	EN-DC	396
9.5B.1.1	Intra-band contiguous EN-DC within FR1	396
9.5B.1.1.1	PDSCH	396
9.5B.1.2	Intra-band non-contiguous EN-DC within FR1	397
9.5B.1.2.1	PDSCH	397
10	CSI reporting requirements for interworking	398
10.1	General	398
10.1.1	Applicability of requirements	398
10.1.1.1	Applicability of requirements for optional UE features	399
10.1.1.2	Applicability of requirements for mandatory UE features with capability signalling.....	399
10.2	Reporting of Channel Quality Indicator (CQI).....	399
10.2A	Reporting of Channel Quality Indicator (CQI) for CA.....	399

10.2A.1	NR CA between FR1 and FR2.....	399
10.2A.1.1	NR CA between FR1 and FR2-2.....	399
10.2B	Reporting of Channel Quality Indicator (CQI) for DC.....	400
10.2B.1	EN-DC	400
10.2B.1.1	EN-DC within FR1	400
10.2B.1.2	EN-DC including FR2 NR carrier.....	400
10.2B.1.3	EN-DC including FR1 and FR2 NR carriers.....	400
10.2B.2	NR DC between FR1 and FR2.....	400
10.3	Reporting of Precoding Matrix Indicator (PMI).....	400
10.3A	Reporting of Precoding Matrix Indicator (PMI) for CA.....	400
10.3B	Reporting of Precoding Matrix Indicator (PMI) for DC.....	400
10.3B.1	EN-DC	400
10.3B.1.1	EN-DC within FR1	400
10.3B.1.2	EN-DC including NR FR2 carrier.....	400
10.3B.1.3	EN-DC including FR1 and FR2 NR carriers.....	400
10.3B.2	NR DC between FR1 and FR2.....	401
10.4	Reporting of Rank Indicator (RI)	401
10.4A	Reporting of Rank Indicator (RI) for CA	401
10.4B	Reporting of Rank Indicator (RI) for DC	401
10.4B.1	EN-DC	401
10.4B.1.1	EN-DC within FR1	401
10.4B.1.2	EN-DC including NR FR2 carrier.....	401
10.4B.1.3	EN-DC including FR1 and FR2 NR carriers.....	401
10.4B.2	NR DC between FR1 and FR2.....	401
11	V2X requirements	402
11.1	Demodulation performance requirements (Conducted requirements).....	402
11.1.1.1	Applicability of requirements.....	402
11.1.1.1.1	General	402
11.1.1.1.2	Applicability of requirements for mandatory UE V2X features with capability signalling	402
11.1.1.2	Common test parameters.....	402
11.1.2	PSSCH demodulation requirements	403
11.1.2.1	2Rx requirements	403
11.1.2.1.1	Minimum requirements	403
11.1.3.1	2Rx requirements	404
11.1.3.1.1	Minimum requirements	404
11.1.4.1	2Rx requirements	404
11.1.4.1.1	Minimum requirements	404
11.1.5.1	2Rx requirements	405
11.1.5.1.1	Minimum requirements	405
11.1.5.1.1.1	NACK missed detection requirements.....	405
11.1.5.1.1.2	DTX to NACK requirements	405
11.1.6	Power imbalance performance with two links.....	406
11.1.6.1	2RX requirements	406
11.1.6.1.1	Minimum requirements	406
11.1.7	HARQ buffer soft combining test.....	407
11.1.7.1	2Rx requirement.....	407
11.1.7.1.1	Minimum requirement.....	407
11.1.8	PSCCH decoding capability test.....	407
11.1.8.1	2RX requirements	407
11.1.8.1.1	Minimum requirements	407
11.1.9	PSFCH decoding capability test	409
11.1.9.1	2RX requirements	409
11.1.9.1.1	Minimum requirements	409
Annex A (normative):	Measurement channels.....	410
A.1	General	410
A.1.1	Throughput definition.....	410
A.1.2	TDD UL-DL configurations for FR1	410
A.1.3	TDD UL-DL configurations for FR2	414
A.2	Void.....	415

A.3	DL reference measurement channels	416
A.3.1	General	416
A.3.2	Reference measurement channels for PDSCH performance requirements	416
A.3.2.1	FDD	416
A.3.2.1.1	Reference measurement channels for SCS 15 kHz FR1	416
A.3.2.1.2	Reference measurement channels for SCS 30 kHz FR1	429
A.3.2.1.3	Reference measurement channels for SCS 60 kHz FR1	430
A.3.2.1.4	Reference measurement channels for E-UTRA	430
A.3.2.1.5	Reference measurement channels for Intra-cell Inter-UE interference scenario	434
A.3.2.2	TDD	435
A.3.2.2.1	Reference measurement channels for SCS 15 kHz FR1	435
A.3.2.2.2	Reference measurement channels for SCS 30 kHz FR1	439
A.3.2.2.3	Reference measurement channels for SCS 60 kHz FR1	473
A.3.2.2.4	Reference measurement channels for SCS 60 kHz FR2	473
A.3.2.2.5	Reference measurement channels for SCS 120 kHz FR2	474
A.3.2.2.6	Reference measurement channels for E-UTRA	489
A.3.2.2.7	Reference measurement channels for Intra-cell Inter-UE interference scenario	494
A.3.2.2.8	Reference measurement channels for SCS 480 kHz FR2-2	495
A.3.2.3	HD-FDD	499
A.3.2.3.1	Reference measurement channels for SCS 15 kHz FR1	499
A.3.3	Reference measurement channels for PDCCH performance requirements	502
A.3.3.1	FDD	502
A.3.3.1.1	Reference measurement channels for SCS 15 kHz FR1	502
A.3.3.1.2	Reference measurement channels for SCS 30 kHz FR1	503
A.3.3.2	TDD	503
A.3.3.2.1	Reference measurement channels for SCS 15 kHz FR1	503
A.3.3.2.2	Reference measurement channels for SCS 30 kHz FR1	504
A.3.3.2.3	Reference measurement channels for SCS 60 kHz FR1	505
A.3.3.2.4	Reference measurement channels for SCS 60 kHz FR2	505
A.3.3.2.5	Reference measurement channels for SCS 120 kHz FR2	505
A.3.3.2.6	Reference measurement channels for SCS 480 kHz FR2-2	505
A.3.4	Reference measurement channels for PBCH demodulation requirements	506
A.3.4.1	Reference measurement channels for FR1	506
A.3.4.2	Reference measurement channels for FR2	506
A.4	CSI reference measurement channels	506
A.5	OFDMA Channel Noise Generator (OCNG)	509
A.5.1	OCNG Patterns for FDD	509
A.5.1.1	OCNG FDD pattern 1: Generic OCNG FDD Pattern for all unused REs	509
A.5.2	OCNG Patterns for TDD	510
A.5.2.1	OCNG TDD pattern 1: Generic OCNG TDD Pattern for all unused REs	510
A.6	SL reference measurement channels	510
A.6.1	General	510
A.6.2	Reference measurement channels for PSSCH performance requirements	510
A.6.2.1	Reference measurement channels for SCS 15 kHz FR1	510
A.6.2.2	Reference measurement channels for SCS 30 kHz FR1	510
A.6.3	Reference measurement channels for PSCCH performance requirements	511
A.6.3.1	Reference measurement channels for SCS 15 kHz FR1	511
A.6.3.2	Reference measurement channels for SCS 30 kHz FR1	511
A.6.4	Reference measurement for PSBCH performance requirements	512
A.6.4.1	Reference measurement channels for SCS 15 kHz FR1	512
A.6.4.2	Reference measurement channels for SCS 30 kHz FR1	512
Annex B (normative):	Propagation conditions	513
B.1	Static propagation condition	513
B.1.0	UE Receiver with 1Rx	513
B.1.1	UE Receiver with 2Rx	513
B.1.2	UE Receiver with 4Rx	513
B.2	Multi-path fading propagation conditions	514
B.2.1	Delay profiles	514

B.2.1.1	Delay profiles for FR1	516
B.2.1.2	Delay profiles for FR2	517
B.2.2	Combinations of channel model parameters	519
B.2.3	MIMO Channel Correlation Matrices	519
B.2.3.1	MIMO Correlation Matrices using Uniform Linear Array (ULA)	519
B.2.3.1.1	Definition of MIMO Correlation Matrices.....	519
B.2.3.1.2	MIMO Correlation Matrices at High, Medium and Low Level	521
B.2.3.1.3	Beam steering approach	524
B.2.3.2	MIMO Correlation Matrices using Cross Polarized Antennas (X-pol)	524
B.2.3.2.1	Definition of MIMO Correlation Matrices using cross polarized antennas	525
B.2.3.2.2	MIMO Correlation Matrices using cross polarized antennas	526
B.2.3.2.3	Beam steering approach	529
B.2.3.2.3A	Beam steering approach with dual cluster beams.....	531
B.2.4	Two-tap propagation conditions for CQI tests	532
B.3	High Speed Train Scenario.....	532
B.3.1	Single Tap Channel Profile	532
B.3.2	HST-SFN Channel Profile.....	536
B.3.3	HST-DPS Channel Profile.....	539
B.3.4	FR2 HST-DPS Channel Profile.....	543
B.3.4.1	Unidirectional Deployment Channel Profile.....	543
B.3.4.2	Bidirectional Deployment Channel Profile.....	546
B.3.5	HST-SFN Scheme A Channel Profile	548
B.3.6	HST-SFN Scheme B Channel Profile	551
B.4	Physical signals, channels mapping and precoding.....	554
B.4.1	General	554
B.4.2	Beamforming for MU-MIMO	555
B.5	Downlink Transmission Model for requirements on bands with shared spectrum access	556
B.5.1	Downlink Transmission Model for bands with shared spectrum access	556
B.6	Interference model for PDSCH requirements with intercell interference	557
B.6.1	Interference to Noise ratio (INR).....	557
B.6.2	Interference model for PDSCH and CSI Reporting requirements	557
B.7	Interference model for PDSCH requirements with LTE-NR spectrum sharing.....	557
Annex C (normative):	Downlink physical channels.....	559
C.1	General	559
C.2	Setup (Conducted).....	559
C.3	Connection (Conducted).....	559
C.3.1	Measurement of Performance requirements.....	559
C.4	Setup (Radiated).....	560
Annex D (informative):	Void	561
Annex E (normative):	Environmental conditions	562
E.1	General	562
E.2	Environmental (Conducted)	562
E.2.1	Temperature	562
E.2.2	Voltage	562
E.2.3	Vibration.....	562
E.3	Environmental (Radiated)	563
E.3.1	Temperature	563
E.3.2	Voltage	563
E.3.3	Void.....	563
Annex F (informative):	Void	564

Annex G (informative): **Void**565

Annex H (informative): **Void**566

Annex I (informative): **Void**567

Annex J (informative): **Void**568

Annex K (informative): **Void**569

Annex L (informative): **Change history**570

History580

Sample Document

get full document from standards.iteh.ai