

# ETSI TS 138 101-4 V18.10.0 (2026-03)



TECHNICAL SPECIFICATION

**5G;  
NR;**  
**User Equipment (UE) radio transmission and reception;**  
**Part 4: Performance requirements**  
**(3GPP TS 38.101-4 version 18.10.0 Release 18)**



---

**Reference**

RTS/TSGR-0438101-4via0

---

**Keywords**

5G

**ETSI**

---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° w061004871

---

**Important notice**

The present document can be downloaded from the  
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed, this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to  
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our  
[Coordinated Vulnerability Disclosure \(CVD\)](#) program.

---

**Notice of disclaimer & limitation of liability**

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2026.  
All rights reserved.

---

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

---

# Legal Notice

This Technical Specification (TS) has been produced by the ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found at [3GPP to ETSI numbering cross-referencing](#).

---

# Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

# Contents

Intellectual Property Rights .....	2
Legal Notice .....	2
Modal verbs terminology.....	2
Foreword.....	16
1 Scope .....	18
2 References .....	18
3 Definitions, symbols and abbreviations .....	19
3.1 Definitions .....	19
3.2 Symbols.....	20
3.3 Abbreviations .....	20
4 General .....	21
4.1 Relationship between minimum requirements and test requirements .....	21
4.2 Applicability of minimum requirements .....	22
4.3 Specification suffix information.....	22
4.4 Conducted requirements.....	22
4.4.0 Introduction.....	22
4.4.1 Reference point.....	22
4.4.2 SNR definition.....	22
4.4.3 Noc.....	23
4.4.3.1 Introduction.....	23
4.4.3.2 Noc for NR operating bands in FR1.....	23
4.4.3.2.1 Derivation of Noc values for NR operating bands in FR1.....	23
4.4.4 Es .....	24
4.4.4.1 Introduction.....	24
4.4.4.2 Es for NR operating bands in FR1 .....	24
4.4.4.2.1 Derivation of Es values for NR operating bands in FR1 .....	24
4.5 Radiated requirements.....	25
4.5.0 Introduction.....	25
4.5.1 Reference point.....	25
4.5.2 SNR definition.....	25
4.5.3 Noc.....	26
4.5.3.1 Introduction.....	26
4.5.3.2 Noc for NR operating bands in FR2.....	26
4.5.3.3 Derivation of Noc values for NR operating bands in FR2 .....	26
4.5.4 Angle of arrival.....	27
4.5.5 Es .....	27
5 Demodulation performance requirements (Conducted requirements) .....	27
5.1 General .....	27
5.1.1 Applicability of requirements .....	27
5.1.1.1 General .....	27
5.1.1.2 Applicability of requirements for different number of RX antenna ports .....	27
5.1.1.3 Applicability of requirements for optional UE features .....	28
5.1.1.4 Applicability of requirements for mandatory UE features with capability signalling.....	34
5.1.1.5 Applicability of different requirements for HST.....	36
5.1.1.6 Applicability and test rules for PDSCH performance requirements with power imbalance for intra-band contiguous CA .....	37
5.1.1.7 Applicability of CA requirements .....	37
5.1.1.7.1 Definition of CA capability .....	37
5.1.1.7.2 Applicability and test rules for different CA configurations and bandwidth combination sets .....	38
5.1.1.7.3 Applicability rule and antenna connection for CA tests with 4 RX.....	39
5.1.1.7.4 Applicability of different requirements for HST .....	39
5.1.1.7.5 Applicability and test rules for different CA configurations and bandwidth combination sets for 8Rx UE .....	41

5.1.1.7.6	Applicability rule and antenna connection for CA tests with 8 RX	43
5.1.1.7.7	Applicability rule for optional UE features for 8Rx	43
5.1.1.8	Applicability of different requirements with Multi-TRxP	43
5.1.1.9	Applicability of requirements for PDSCH on bands with shared spectrum access	44
5.1.1.10	Applicability of requirements for PDSCH with inter cell interference	44
5.1.1.11	Applicability of requirements for RedCap	44
5.1.1.14	Applicability of requirements for eRedCap	47
5.2	PDSCH demodulation requirements	47
5.2.1	1RX requirements	50
5.2.1.1	FDD	50
5.2.1.1.1	Minimum requirements for RedCap	50
5.2.1.1.2	Minimum requirements for eRedCap	51
5.2.1.2	TDD	53
5.2.1.2.1	Minimum requirements for RedCap	53
5.2.1.2.2	Minimum requirements for eRedCap	54
5.2.2	2RX requirements	55
5.2.2.1	FDD	55
5.2.2.1.1	Minimum requirements for PDSCH Mapping Type A	55
5.2.2.1.2	Minimum requirements for PDSCH Mapping Type A and CSI-RS overlapped with PDSCH	57
5.2.2.1.3	Minimum requirements for PDSCH Mapping Type B	58
5.2.2.1.4	Minimum requirements for PDSCH Mapping Type A and LTE-NR coexistence	59
5.2.2.1.5	Minimum requirements for PDSCH 0.001% BLER	60
5.2.2.1.6	Minimum requirements for PDSCH repetitions over multiple slots	61
5.2.2.1.7	Minimum requirements for PDSCH Mapping Type B and UE processing capability 2	62
5.2.2.1.8	Minimum requirements for PDSCH pre-emption	63
5.2.2.1.9	Minimum requirements for PDSCH HST-SFN	64
5.2.2.1.10	Minimum requirements for HST-DPS	64
5.2.2.1.11	Minimum requirements for PDSCH Single-DCI based SDM scheme	67
5.2.2.1.12	Minimum requirements for PDSCH Multi-DCI based transmission scheme	68
5.2.2.1.13	Minimum requirements for PDSCH with single-DCI based FDM Scheme A	70
5.2.2.1.14	Minimum requirements for PDSCH with single-DCI based Inter-slot TDM scheme	71
5.2.2.1.15	Minimum requirements for PDSCH with inter-cell interference	73
5.2.2.1.16	Minimum requirements for PDSCH with intra cell inter user interference	74
5.2.2.1.17	Minimum requirements for RedCap	76
5.2.2.1.18	Minimum requirements for PDSCH CRS interference mitigation under NR-LTE coexistence scenario	78
5.2.2.1.19	Minimum requirements for PDSCH with inter cell CRS interference	79
5.2.2.1.20	Minimum requirements for HST-SFN Scheme A	81
5.2.2.1.21	Minimum requirements for HST-SFN Scheme B	83
5.2.2.1.23	Minimum requirements for eRedCap	86
5.2.2.2	TDD	88
5.2.2.2.1	Minimum requirements for PDSCH Mapping Type A	88
5.2.2.2.2	Minimum requirements for PDSCH Mapping Type A and CSI-RS overlapped with PDSCH	90
5.2.2.2.3	Minimum requirements for PDSCH Mapping Type B	91
5.2.2.2.4	Minimum requirements for PDSCH Mapping Type A and LTE-NR coexistence	92
5.2.2.2.5	Minimum requirements for PDSCH 0.001% BLER	93
5.2.2.2.6	Minimum requirements for PDSCH repetitions over multiple slots	94
5.2.2.2.7	Minimum requirements for PDSCH Mapping Type B and UE processing capability 2	95
5.2.2.2.8	Minimum requirements for PDSCH pre-emption	96
5.2.2.2.9	Minimum requirements for HST-SFN	97
5.2.2.2.10	Minimum requirements for HST-DPS	97
5.2.2.2.11	Minimum requirements for PDSCH Single-DCI based SDM scheme	99
5.2.2.2.12	Minimum requirements for PDSCH Multi-DCI based transmission scheme	101
5.2.2.2.13	Minimum requirements for PDSCH with single-DCI based FDM Scheme A	103
5.2.2.2.14	Minimum requirements for PDSCH with single-DCI based Inter-slot TDM scheme	104
5.2.2.2.15	Minimum requirements for PDSCH of PCell on band with shared spectrum access	106
5.2.2.2.16	Minimum requirements for PDSCH with inter-cell interference	107
5.2.2.2.17	Minimum requirements for PDSCH with intra cell inter user interference	108
5.2.2.2.18	Minimum requirements for RedCap	110
5.2.2.2.19	Minimum requirements for PDSCH CRS interference mitigation under NR-LTE coexistence scenario	111
5.2.2.2.20	Minimum requirements for PDSCH with inter cell CRS interference	113

5.2.2.2.21	Minimum requirements for HST-SFN Scheme A .....	115
5.2.2.2.22	Minimum requirements for HST-SFN Scheme B .....	117
5.2.2.2.24	Minimum requirements for eRedCap .....	121
5.2.3	4RX requirements .....	122
5.2.3.1	FDD .....	122
5.2.3.1.1	Minimum requirements for PDSCH Mapping Type A .....	122
5.2.3.1.2	Minimum requirements for PDSCH Mapping Type A and CSI-RS overlapped with PDSCH .....	125
5.2.3.1.3	Minimum requirements for PDSCH Mapping Type B .....	126
5.2.3.1.4	Minimum requirements for PDSCH Mapping Type A and LTE-NR coexistence .....	126
5.2.3.1.5	Minimum requirements for PDSCH 0.001% BLER .....	127
5.2.3.1.6	Minimum requirements for PDSCH repetitions over multiple slots .....	128
5.2.3.1.7	Minimum requirements for PDSCH Mapping Type B and UE processing capability 2 .....	129
5.2.3.1.8	Minimum requirements for PDSCH pre-emption .....	130
5.2.3.1.9	Minimum requirements for PDSCH HST-SFN .....	131
5.2.3.1.10	Minimum requirements for HST-DPS .....	132
5.2.3.1.11	Minimum requirements for PDSCH Single-DCI based SDM scheme .....	134
5.2.3.1.12	Minimum requirements for PDSCH Multi-DCI based transmission scheme .....	135
5.2.3.1.13	Minimum requirements for PDSCH with single-DCI based FDM Scheme A .....	137
5.2.3.1.14	Minimum requirements for PDSCH with single-DCI based Inter-slot TDM scheme .....	138
5.2.3.1.15	Minimum requirements for PDSCH with inter-cell interference .....	140
5.2.3.1.16	Minimum requirements for PDSCH with intra-cell inter-user interference .....	141
5.2.3.1.17	Minimum requirements for PDSCH CRS interference mitigation under NR-LTE coexistence scenario .....	144
5.2.3.1.18	Minimum requirements for PDSCH with inter cell CRS interference .....	145
5.2.3.1.19	Minimum requirements for HST-SFN Scheme A .....	147
5.2.3.1.20	Minimum requirements for HST-SFN Scheme B .....	149
5.2.3.2	TDD .....	152
5.2.3.2.1	Minimum requirements for PDSCH Mapping Type A .....	152
5.2.3.2.2	Minimum requirements for PDSCH Mapping Type A and CSI-RS overlapped with PDSCH .....	155
5.2.3.2.3	Minimum requirements for PDSCH Mapping Type B .....	155
5.2.3.2.4	Minimum requirements for PDSCH Mapping Type A and LTE-NR coexistence .....	156
5.2.3.2.5	Minimum requirements for PDSCH 0.001% BLER .....	157
5.2.3.2.6	Minimum requirements for PDSCH repetitions over multiple slots .....	158
5.2.3.2.7	Minimum requirements for PDSCH Mapping Type B and UE processing capability 2 .....	159
5.2.3.2.8	Minimum requirements for PDSCH pre-emption .....	160
5.2.3.2.9	Minimum requirements for HST-SFN .....	161
5.2.3.2.10	Minimum requirements for HST-DPS .....	162
5.2.3.2.11	Minimum requirements for PDSCH Single-DCI based SDM scheme .....	164
5.2.3.2.12	Minimum requirements for PDSCH Multi-DCI based transmission scheme .....	165
5.2.3.2.13	Minimum requirements for PDSCH with single-DCI based FDM Scheme A .....	167
5.2.3.2.14	Minimum requirements for PDSCH with single-DCI based Inter-slot TDM scheme .....	169
5.2.3.2.16	Minimum requirements for PDSCH with inter-cell interference .....	171
5.2.3.2.17	Minimum requirements for PDSCH with intra-cell inter-user interference .....	173
5.2.3.2.18	Minimum requirements for PDSCH CRS interference mitigation under NR-LTE coexistence scenario .....	175
5.2.3.2.19	Minimum requirements for PDSCH with inter cell CRS interference .....	177
5.2.3.2.20	Minimum requirements for HST-SFN Scheme A .....	179
5.2.3.2.21	Minimum requirements for HST-SFN Scheme B .....	181
5.2.3.2.22	Minimum requirements for ATG .....	183
5.2.4	8RX requirements .....	184
5.2.4.1	FDD .....	184
5.2.4.1.1	Minimum requirements for PDSCH Mapping Type A .....	184
5.2.4.2	TDD .....	186
5.2.4.2.1	Minimum requirements for PDSCH Mapping Type A .....	186
5.2.A	PDSCH demodulation requirements for CA .....	188
5.2.A.1	1RX requirements .....	189
5.2.A.2	2RX requirements .....	189
5.2.A.2.1	Minimum requirements .....	189
5.2.A.2.2	Minimum requirements for carrier aggregation with power imbalance .....	191
5.2.A.2.3	Minimum requirements for PDSCH of SCell on band with shared spectrum access .....	192
5.2.A.2.6	Minimum requirements for non-collocated scenarios for intra-band non-contiguous NR-CA .....	199
5.2.A.3	4RX requirements .....	200

5.2A.3.1	Minimum requirements .....	200
5.2A.3.2	Minimum requirements for carrier aggregation with power imbalance .....	202
5.2A.3.3	Minimum requirements for PDSCH of SCell on band with shared spectrum access .....	203
5.2A.3.4	Minimum requirements for HST-SFN CA .....	204
5.2A.3.5	Minimum requirements for PDSCH HST-DPS CA .....	206
5.2A.4	8RX requirements .....	210
5.2A.4.1	Minimum requirements .....	210
5.3	PDCCH demodulation requirements .....	214
5.3.1	1RX requirements .....	215
5.3.1.1	FDD .....	216
5.3.1.1.1	Minimum requirements for RedCap .....	216
5.3.1.2	TDD .....	216
5.3.1.2.1	Minimum requirements for RedCap .....	216
5.3.2	2RX requirements .....	216
5.3.2.1	FDD .....	216
5.3.2.1.1	Minimum requirements with 1TX antenna .....	217
5.3.2.1.2	Minimum requirements with 2TX antenna .....	217
5.3.2.1.3	Minimum requirements for power saving .....	217
5.3.2.1.4	Minimum requirements for RedCap .....	218
5.3.2.1.5	Minimum requirements for PDCCH with intra-slot repetition .....	218
5.3.2.1.6	Minimum requirements for PDCCH overlapping with LTE CRS .....	219
5.3.2.1.7	Minimum requirements for 3 MHz channel bandwidth .....	220
5.3.2.2	TDD .....	221
5.3.2.2.1	Minimum requirements with 1TX antenna .....	221
5.3.2.2.2	Minimum requirements with 2TX antenna .....	221
5.3.2.2.3	Minimum requirements for power saving .....	221
5.3.2.2.4	Minimum requirements for RedCap .....	222
5.3.2.2.5	Minimum requirements for PDCCH with intra-slot repetition .....	222
5.3.3	4RX requirements .....	225
5.3.3.1	FDD .....	225
5.3.3.1.1	Minimum requirements with 1TX antenna .....	225
5.3.3.1.2	Minimum requirements with 2TX antenna .....	225
5.3.3.1.3	Minimum requirements for power saving .....	225
5.3.3.1.4	Minimum requirements for PDCCH with intra-slot repetition .....	226
5.3.3.1.5	Minimum requirements for PDCCH overlapping with LTE CRS .....	227
5.3.3.1.6	Minimum requirements for 3 MHz channel bandwidth .....	228
5.3.3.2	TDD .....	228
5.3.3.2.1	Minimum requirements with 1TX antenna .....	229
5.3.3.2.2	Minimum requirements with 2TX antenna .....	229
5.3.3.2.3	Minimum requirements for power saving .....	229
5.3.3.2.4	Minimum requirements for PDCCH with intra-slot repetition .....	230
5.3.3.2.5	Minimum requirement for PDCCH overlapping with LTE CRS .....	231
5.4	PBCH demodulation requirements .....	232
5.4.1	1RX requirements .....	232
5.4.1.1	FDD .....	232
5.4.1.2	TDD .....	233
5.4.2	2RX requirements .....	233
5.4.2.1	FDD .....	233
5.4.2.2	TDD .....	234
5.4.3	4RX requirements .....	235
5.4.3.1	FDD .....	235
5.4.3.2	TDD .....	235
5.5	Sustained downlink data rate provided by lower layers .....	236
5.5.1	FR1 single carrier requirements .....	236
5.5A	Sustained downlink data rate provided by lower layers .....	236
5.5A.1	FR1 CA requirements .....	236
5.6	PDSCH absolute physical layer throughput requirements .....	242
5.6.1	1RX requirements .....	242
5.6.2	2RX requirements .....	242
5.6.2.1	FDD .....	242
5.6.2.1.1	Minimum requirements with Link Adaptation .....	242
5.6.2.2	TDD .....	243

5.6.2.2.1	Minimum requirements with Link Adaptation .....	243
5.6.3	4Rx requirements .....	245
5.6.3.1	FDD .....	245
5.6.3.1.1	Minimum requirements with Link Adaptation .....	245
5.6.3.2	TDD .....	246
5.6.3.2.1	Minimum requirements with Link Adaptation .....	246
6	CSI reporting requirements (Conducted requirements) .....	249
6.1	General .....	249
6.1.1	Applicability of requirements .....	249
6.1.1.1	General .....	249
6.1.1.2	Applicability of requirements for different number of RX antenna ports .....	249
6.1.1.3	Applicability of requirements for optional UE features .....	250
6.1.1.4	Applicability of requirements for mandatory UE features with capability signalling .....	251
6.1.1.5	Applicability of Channel Quality Indicator (CQI) reporting requirements for CA .....	252
6.1.1.5.1	Applicability and test rules for different duplex modes and SCS combinations .....	252
6.1.1.5.2	Applicability and test rules for different CA configurations and bandwidth combination sets .....	252
6.1.1.5.3	Test coverage for different number of component carriers .....	252
6.1.1.5.4	Applicability rule and antenna connection for CA tests with 4 RX .....	252
6.1.1.6	Applicability of requirements for RedCap .....	252
6.1.1.7	Applicability of requirements for eRedCap .....	253
6.1.1.8	Applicability of requirements for ATG .....	253
6.1.2	Common test parameters .....	254
6.2	Reporting of Channel Quality Indicator (CQI) .....	257
6.2.1	1RX requirements .....	257
6.2.1.1	FDD .....	257
6.2.1.1.1	CQI reporting definition under AWGN conditions .....	257
6.2.1.1.1.1	Minimum requirement for periodic CQI reporting for RedCap .....	257
6.2.1.1.2	CQI reporting under fading conditions .....	259
6.2.1.1.2.2	Minimum requirement for wideband CQI reporting for eRedCap .....	261
6.2.1.2	TDD .....	263
6.2.1.2.1	CQI reporting definition under AWGN conditions .....	263
6.2.1.2.2	CQI reporting under fading conditions .....	265
6.2.1.2.2.2	Minimum requirement for wideband CQI reporting for eRedCap .....	267
6.2.2	2RX requirements .....	268
6.2.2.1	FDD .....	268
6.2.2.1.1	CQI reporting definition under AWGN conditions .....	268
6.2.2.1.1.1	Minimum requirement for periodic CQI reporting .....	269
6.2.2.1.1.2	Minimum requirement for periodic CQI reporting with Table 3 .....	270
6.2.2.1.1.3	Minimum requirement for periodic CQI reporting with Table 4 .....	271
6.2.2.1.1.4	Minimum requirement for periodic CQI reporting for RedCap .....	272
6.2.2.1.2	CQI reporting under fading conditions .....	274
6.2.2.1.2.1	Minimum requirement for wideband CQI reporting .....	274
6.2.2.1.2.2	Minimum requirement for sub-band CQI reporting .....	276
6.2.2.1.2.3	Minimum requirement for wideband CQI reporting with inter-cell interference .....	277
6.2.2.1.2.4	Minimum requirement for wideband CQI reporting for RedCap .....	279
6.2.2.1.2.5	Minimum requirement for wideband CQI reporting for eRedCap .....	281
6.2.2.2	TDD .....	283
6.2.2.2.1	CQI reporting definition under AWGN conditions .....	283
6.2.2.2.1.1	Minimum requirement for periodic CQI reporting .....	283
6.2.2.2.1.2	Minimum requirement for periodic CQI reporting with Table 3 .....	284
6.2.2.2.1.3	Minimum requirement for CQI reporting for PCell on band with shared spectrum access .....	285
6.2.2.2.1.4	Minimum requirement for periodic CQI reporting with Table 4 .....	287
6.2.2.2.1.5	Minimum requirement for periodic CQI reporting for RedCap .....	288
6.2.2.2.2	CQI reporting under fading conditions .....	291
6.2.2.2.2.1	Minimum requirement for wideband CQI reporting .....	291
6.2.2.2.2.2	Minimum requirement for sub-band CQI reporting .....	292
6.2.2.2.2.3	Minimum requirement for wideband CQI reporting with inter-cell interference .....	294
6.2.2.2.2.4	Minimum requirement for wideband CQI reporting for RedCap .....	296
6.2.2.2.2.5	Minimum requirement for wideband CQI reporting for eRedCap .....	297
6.2.3	4RX requirements .....	299
6.2.3.1	FDD .....	299

6.2.3.1.1	CQI reporting definition under AWGN conditions .....	299
6.2.3.1.1.1	Minimum requirement for period CQI reporting .....	299
6.2.3.1.1.2	Minimum requirement for period CQI reporting with Table 3 .....	300
6.2.3.1.1.3	Minimum requirement for periodic CQI reporting with Table 4 .....	301
6.2.3.1.2	CQI reporting under fading conditions.....	303
6.2.3.1.2.1	Minimum requirement for wideband CQI reporting .....	303
6.2.3.1.2.2	Minimum requirement for sub-band CQI reporting .....	304
6.2.3.1.2.3	Minimum requirement for wideband CQI reporting with inter-cell interference.....	306
6.2.3.2	TDD .....	308
6.2.3.2.1	CQI reporting definition under AWGN.....	308
6.2.3.2.1.1	Minimum requirement for CQI periodic reporting .....	308
6.2.3.2.1.2	Minimum requirement for CQI periodic reporting with Table 3 .....	309
6.2.3.2.1.3	Minimum requirement for CQI reporting for PCell on band with shared spectrum access .....	310
6.2.3.2.1.4	Minimum requirement for CQI periodic reporting with Table 4 .....	312
6.2.3.2.2	CQI reporting under fading conditions.....	313
6.2.3.2.2.1	Minimum requirement for wideband CQI reporting .....	313
6.2.3.2.2.2	Minimum requirement for sub-band CQI reporting .....	315
6.2.3.2.2.3	Minimum requirement for wideband CQI reporting with inter-cell interference.....	316
6.2.4	8RX requirements .....	318
6.2.4.1	FDD.....	319
6.2.4.1.1	CQI reporting definition under AWGN conditions .....	319
6.2.4.1.1.1	Minimum requirement for period CQI reporting .....	319
6.2.4.2	TDD .....	320
6.2.4.2.1	CQI reporting definition under AWGN conditions .....	320
6.2A	Reporting of Channel Quality Indicator (CQI) for CA.....	321
6.2A.1	General.....	321
6.2A.2	1RX requirements .....	321
6.2A.3	2RX requirements .....	322
6.2A.3.1	CQI reporting definition under AWGN conditions.....	322
6.2A.3.1.1	Minimum requirement for periodic CQI reporting .....	322
6.2A.3.1.2	Minimum requirement for CQI reporting for SCell on band with shared spectrum access .....	324
6.2A.4	4RX requirements .....	326
6.2A.4.1	CQI reporting definition under AWGN conditions.....	326
6.2A.4.1.1	Minimum requirement for CQI reporting for SCell on band with shared spectrum access .....	326
6.3	Reporting of Precoding Matrix Indicator (PMI).....	328
6.3.1	1RX requirements .....	329
6.3.1.1	FDD.....	329
6.3.1.1.1	Single PMI with 4TX TypeI-SinglePanel Codebook for RedCap .....	329
6.3.1.1.2	Single PMI with 4TX TypeI-SinglePanel Codebook for eRedCap .....	330
6.3.1.2	TDD .....	332
6.3.1.2.1	Single PMI with 4TX TypeI-SinglePanel Codebook for RedCap .....	332
6.3.1.2.2	Single PMI with 4TX TypeI-SinglePanel Codebook for eRedCap .....	334
6.3.2	2RX requirements .....	335
6.3.2.1	FDD.....	335
6.3.2.1.1	Single PMI with 4TX TypeI-SinglePanel Codebook .....	335
6.3.2.1.2	Single PMI with 8TX TypeI-SinglePanel Codebook .....	337
6.3.2.1.3	Multiple PMI with 16TX TypeI-SinglePanel Codebook.....	339
6.3.2.1.4	Single PMI with 32TX TypeI-SinglePanel Codebook .....	340
6.3.2.1.5	Multiple PMI with 16TX TypeII Codebook.....	342
6.3.2.1.6	Multiple PMI with 16TX Enhanced Type II Codebook .....	344
6.3.2.1.7	Single PMI with 8 ports TypeI-SinglePanel Codebook for Single-DCI based transmission scheme .....	346
6.3.2.1.8	Multiple PMI with 16TX Enhanced Type II codebook for predicted PMI.....	348
6.3.2.1.9	Multiple PMI with 8 ports Enhanced Type II Codebook for CJT .....	350
6.3.2.1.10	Single PMI with 4TX TypeI-SinglePanel Codebook for eRedCap .....	353
6.3.2.2	TDD .....	354
6.3.2.2.1	Single PMI with 4TX TypeI-SinglePanel Codebook .....	354
6.3.2.2.2	Single PMI with 8TX TypeI-SinglePanel Codebook .....	356
6.3.2.2.3	Multiple PMI with 16TX TypeI-SinglePanel Codebook.....	358
6.3.2.2.4	Single PMI with 32TX TypeI-SinglePanel Codebook .....	359
6.3.2.2.5	Multiple PMI with 16TX TypeII Codebook.....	361
6.3.2.2.6	Multiple PMI with 16Tx Enhanced Type II Codebook .....	363

6.3.2.2.7	Single PMI with 4TX TypeI-SinglePanel Codebook for RedCap.....	365
6.3.2.2.8	Single PMI with 8 ports TypeI-SinglePanel Codebook for Single-DCI based transmission scheme.....	366
6.3.2.2.10	Single PMI with 4TX TypeI-SinglePanel Codebook for eRedCap.....	371
6.3.3	4RX requirements.....	373
6.3.3.1	FDD.....	373
6.3.3.1.1	Single PMI with 4TX TypeI-SinglePanel Codebook.....	373
6.3.3.1.2	Single PMI with 8TX TypeI-SinglePanel Codebook.....	374
6.3.3.1.3	Multiple PMI with 16TX TypeI-SinglePanel Codebook.....	376
6.3.3.1.4	Single PMI with 32TX TypeI-SinglePanel Codebook.....	378
6.3.3.1.5	Multiple PMI with 16TX TypeII Codebook.....	380
6.3.3.1.6	Multiple PMI with 16Tx Enhanced Type II Codebook.....	382
6.3.3.1.7	Single PMI with 8 ports TypeI-SinglePanel Codebook for Single-DCI based transmission scheme.....	384
6.3.3.1.8	Multiple PMI with 16TX Enhanced Type II codebook for predicted PMI.....	386
6.3.3.1.9	Multiple PMI with 8 ports Enhanced Type II Codebook for CJT.....	388
6.3.3.2	TDD.....	391
6.3.3.2.1	Single PMI with 4TX TypeI-SinglePanel Codebook.....	391
6.3.3.2.2	Single PMI with 8TX TypeI-SinglePanel Codebook.....	392
6.3.3.2.3	Multiple PMI with 16TX TypeI-SinglePanel Codebook.....	394
6.3.3.2.4	Single PMI with 32TX TypeI-SinglePanel Codebook.....	396
6.3.3.2.5	Multiple PMI with 16TX TypeII Codebook.....	398
6.3.3.2.6	Multiple PMI with 16Tx Enhanced Type II Codebook.....	400
6.3.3.2.7	Single PMI with 8 ports TypeI-SinglePanel Codebook for Single-DCI based transmission scheme.....	402
6.4	Reporting of Rank Indicator (RI).....	406
6.4.1	1RX requirements.....	406
6.4.2	2RX requirements.....	407
6.4.2.1	FDD.....	407
6.4.2.1.1	Minimum requirements for RedCap.....	408
6.4.2.2	TDD.....	409
6.4.2.2.1	Minimum requirements for RedCap.....	411
6.4.3	4RX requirements.....	412
6.4.3.1	FDD.....	412
6.4.3.2	TDD.....	413
7	Demodulation performance requirements (Radiated requirements).....	415
7.1	General.....	415
7.1.1	Applicability of requirements.....	415
7.1.1.1	General.....	415
7.1.1.2	Applicability of requirements for different number of RX antenna ports.....	415
7.1.1.3	Applicability of requirements for optional UE features.....	415
7.1.1.5	Applicability of CA requirements.....	418
7.1.1.5.1	Definition of CA capability.....	418
7.1.1.5.2	Applicability and test rules for different CA configurations and bandwidth combination sets.....	418
7.1.1.6	Applicability of requirements for operating bands in FR2-1.....	418
7.1.1.7	Applicability of requirements for RedCap.....	419
7.1.1.8	Applicability of requirements for operating bands in FR2-2.....	419
7.2	PDSCH demodulation requirements.....	420
7.2.1	1RX requirements.....	424
7.2.2	2RX requirements.....	424
7.2.2.1	FDD.....	424
7.2.2.2	TDD.....	424
7.2.2.2.1	Minimum requirements for PDSCH Mapping Type-A.....	424
7.2.2.2.2	Minimum requirements for PDSCH repetitions over multiple slots.....	427
7.2.2.2.3	Minimum requirements for PDSCH Mapping Type B.....	428
7.2.2.2.4	Minimum requirements for HST-DPS.....	428
7.2.2.2.5	Minimum requirements for Multi-DCI non-overlapping based transmission scheme.....	435
7.2.2.2.6	Minimum requirements for PDSCH Multi-DCI based transmission scheme.....	438
7.2.2.2.8	Minimum requirements for multi-Rx simultaneous reception in FR2 HST-DPS.....	442
7.2A	PDSCH demodulation requirements for CA.....	450
7.2A.1	1RX requirements.....	450

7.2A.2	2RX requirements .....	450
7.2A.2.1	Minimum requirements .....	450
7.3	PDCCH demodulation requirements .....	459
7.3.1	1RX requirements .....	461
7.3.2	2RX requirements .....	461
7.3.2.1	FDD .....	461
7.3.2.2	TDD .....	461
7.3.2.2.1	Minimum requirements with 1TX antenna .....	462
7.3.2.2.2	Minimum requirements with 2TX antenna .....	462
7.3.2.2.3	Minimum requirements for power saving .....	463
7.4	PBCH demodulation requirements .....	463
7.4.1	1RX requirements .....	464
7.4.2	2RX requirements .....	464
7.4.2.1	FDD .....	464
7.4.2.2	TDD .....	464
7.5	Sustained downlink data rate provided by lower layers .....	464
7.5.1	FR2 single carrier requirements .....	464
7.5A	Sustained downlink data rate provided by lower layers .....	465
7.5A.1	FR2 CA requirements .....	465
7.6	PDSCH absolute physical layer throughput requirements .....	469
7.6.1	1Rx requirements .....	469
7.6.2	2Rx requirements .....	469
7.6.2.1	FDD .....	469
7.6.2.2	TDD .....	470
7.6.2.2.1	Minimum requirements with Link Adaptation .....	470
8	CSI reporting requirements (Radiated requirements) .....	471
8.1	General .....	471
8.1.1	Applicability of requirements .....	471
8.1.1.1	General .....	471
8.1.1.2	Applicability of requirements for different number of RX antenna ports .....	471
8.1.1.3	Applicability of requirements for optional UE features .....	472
8.1.1.4	Applicability of requirements for mandatory UE features with capability signalling .....	472
8.1.1.5	Applicability of Channel Quality Indicator (CQI) reporting requirements for CA .....	472
8.1.1.5.1	Applicability and test rules for different CA configurations and bandwidth combination sets .....	472
8.1.1.5.2	Test coverage for different number of component carriers .....	473
8.1.1.6	Applicability of requirements for RedCap .....	473
8.1.2	Common test parameters .....	473
8.2	Reporting of Channel Quality Indicator (CQI) .....	476
8.2.1	1RX requirements .....	476
8.2.2	2RX requirements .....	477
8.2.2.1	FDD .....	477
8.2.2.2	TDD .....	477
8.2.2.2.1	CQI reporting under AWGN conditions .....	477
8.2.2.2.1.1	Minimum requirement for periodic CQI reporting .....	477
8.2.2.2.2	CQI reporting under fading conditions .....	479
8.2.2.2.2.1	Minimum requirement for wideband CQI reporting .....	479
8.2A	Reporting of Channel Quality Indicator (CQI) for CA .....	481
8.2A.1	General .....	481
8.2A.2	1RX requirements .....	481
8.2A.3	2RX requirements .....	481
8.2A.3.1	CQI reporting definition under AWGN conditions .....	481
8.2A.3.1.1	Minimum requirement for periodic CQI reporting .....	481
8.3	Reporting of Precoding Matrix Indicator (PMI) .....	482
8.3.1	1RX requirements .....	483
8.3.2	2RX requirements .....	483
8.3.2.1	FDD .....	483
8.3.2.2	TDD .....	483
8.3.2.2.1	Single PMI with 2TX TypeI-SinglePanel Codebook .....	483
8.3.3.2.2	Single PMI with 2 ports TypeI-SinglePanel Codebook for Single-DCI based transmission scheme with simultaneous reception .....	485
8.4	Reporting of Rank Indicator (RI) .....	488

8.4.1	IRX requirements .....	488
8.4.2	2RX requirements .....	488
8.4.2.1	FDD.....	488
8.4.2.2	TDD .....	488
9	Demodulation performance requirements for interworking.....	490
9.1	General .....	490
9.1.1	Applicability of requirements .....	490
9.1.1.1	Applicability of requirements for optional UE features .....	492
9.1.1.2	Applicability of requirements for mandatory UE features with capability signalling .....	492
9.1.1.3	Applicability of requirements for operating bands in FR2-2 .....	493
9.1.2	E-UTRA Cell setup.....	493
9.1.2.1	FDD.....	493
9.1.2.2	TDD .....	494
9.2	PDSCH Demodulation .....	495
9.2A	PDSCH demodulation for CA.....	495
9.2A.1	NR CA between FR1 and FR2.....	495
9.2A.1.1	NR CA between FR1 and FR2-2.....	495
9.2B	PDSCH demodulation for DC.....	497
9.2B.1	EN-DC .....	497
9.2B.1.1	EN-DC within FR1 .....	497
9.2B.1.1.1	PDSCH .....	497
9.2B.1.2	EN-DC including FR2 NR carrier only.....	497
9.2B.1.2.1	PDSCH .....	497
9.2B.1.3	EN-DC including FR1 and FR2 NR carriers.....	497
9.2B.2	NR DC between FR1 and FR2.....	497
9.3	PDCCH demodulation.....	497
9.3A	PDCCH demodulation for CA.....	497
9.3A.1	NR CA between FR1 and FR2.....	497
9.3A.1.1	NR CA between FR1 and FR2-2.....	497
9.3B	PDCCH demodulation for DC.....	498
9.3B.1	EN-DC .....	498
9.3B.1.1	EN-DC within FR1 .....	498
9.3B.1.1.1	PDCCH.....	498
9.3B.1.2	EN-DC including FR2 NR carrier only.....	498
9.3B.1.2.1	PDCCH.....	498
9.3B.1.3	EN-DC including FR1 and FR2 NR carriers.....	498
9.3B.2	NR DC between FR1 and FR2.....	498
9.4	Void.....	498
9.4A	SDR test for CA .....	498
9.4A.1	NR CA between FR1 and FR2.....	498
9.4B	SDR test for DC .....	499
9.4B.1	EN-DC .....	499
9.4B.1.1	EN-DC within FR1 .....	499
9.4B.1.1.1	SDR test.....	499
9.4B.1.2	EN-DC including FR2 NR carrier.....	501
9.4B.1.2.1	SDR test.....	501
9.4B.1.3	EN-DC including FR1 and FR2 NR carriers.....	501
9.4B.2	NR DC between FR1 and FR2.....	502
9.4B.3.1	NE-DC within FR1 .....	502
9.5B	PDSCH demodulation for DC with power imbalance.....	502
9.5B.1	EN-DC .....	502
9.5B.1.1	Intra-band contiguous EN-DC within FR1 .....	502
9.5B.1.1.1	PDSCH .....	502
9.5B.1.2	Intra-band non-contiguous EN-DC within FR1 .....	504
9.5B.1.2.1	PDSCH .....	504
10	CSI reporting requirements for interworking .....	505
10.1	General .....	505
10.1.1	Applicability of requirements .....	505
10.1.1.1	Applicability of requirements for optional UE features .....	506
10.1.1.2	Applicability of requirements for mandatory UE features with capability signalling.....	506

10.2	Reporting of Channel Quality Indicator (CQI).....	506
10.2A	Reporting of Channel Quality Indicator (CQI) for CA.....	506
10.2A.1	NR CA between FR1 and FR2.....	506
10.2A.1.1	NR CA between FR1 and FR2-2.....	506
10.2B	Reporting of Channel Quality Indicator (CQI) for DC.....	506
10.2B.1	EN-DC.....	506
10.2B.1.1	EN-DC within FR1.....	506
10.2B.1.2	EN-DC including FR2 NR carrier.....	506
10.2B.1.3	EN-DC including FR1 and FR2 NR carriers.....	506
10.2B.2	NR DC between FR1 and FR2.....	507
10.3	Reporting of Precoding Matrix Indicator (PMI).....	507
10.3A	Reporting of Precoding Matrix Indicator (PMI) for CA.....	507
10.3B	Reporting of Precoding Matrix Indicator (PMI) for DC.....	507
10.3B.1	EN-DC.....	507
10.3B.1.1	EN-DC within FR1.....	507
10.3B.1.2	EN-DC including NR FR2 carrier.....	507
10.3B.1.3	EN-DC including FR1 and FR2 NR carriers.....	507
10.3B.2	NR DC between FR1 and FR2.....	507
10.4	Reporting of Rank Indicator (RI).....	507
10.4A	Reporting of Rank Indicator (RI) for CA.....	507
10.4B	Reporting of Rank Indicator (RI) for DC.....	507
10.4B.1	EN-DC.....	507
10.4B.1.1	EN-DC within FR1.....	507
10.4B.1.2	EN-DC including NR FR2 carrier.....	508
10.4B.1.3	EN-DC including FR1 and FR2 NR carriers.....	508
10.4B.2	NR DC between FR1 and FR2.....	508
11	V2X requirements.....	509
11.1	Demodulation performance requirements (Conducted requirements).....	509
11.1.1.1	Applicability of requirements.....	509
11.1.1.1.1	General.....	509
11.1.1.1.2	Applicability of requirements for mandatory UE V2X features with capability signalling.....	509
11.1.1.1.3	Applicability of requirements for CA.....	509
11.1.1.1.4	Applicability of requirements for PSSCH with shared spectrum access.....	510
11.1.1.2	Common test parameters.....	510
11.1.2	PSSCH demodulation requirements.....	511
11.1.2.1	2Rx requirements.....	511
11.1.2.1.1	Minimum requirements.....	511
11.1.2.1.2	Minimum requirements for PSSCH with shared spectrum access.....	511
11.1.2A	PSSCH demodulation requirements for CA.....	512
11.1.2A.1	2Rx requirements.....	512
11.1.2A.1.1	Minimum requirements.....	512
11.1.3.1	2Rx requirements.....	513
11.1.3.1.1	Minimum requirements.....	513
11.1.4.1	2Rx requirements.....	514
11.1.4.1.1	Minimum requirements.....	514
11.1.5.1	2Rx requirements.....	514
11.1.5.1.1	Minimum requirements.....	514
11.1.5.1.1.1	NACK missed detection requirements.....	514
11.1.5.1.1.2	DTX to NACK requirements.....	515
11.1.6	Power imbalance performance with two links.....	515
11.1.6.1	2RX requirements.....	515
11.1.6.1.1	Minimum requirements.....	515
11.1.7	HARQ buffer soft combining test.....	516
11.1.7.1	2Rx requirement.....	516
11.1.7.1.1	Minimum requirement.....	516
11.1.8	PSCCH decoding capability test.....	517
11.1.8.1	2RX requirements.....	517
11.1.8.1.1	Minimum requirements.....	517
11.1.8A	PSCCH decoding capability test for CA.....	518
11.1.8A.1	2RX requirements.....	518
11.1.8A.1.1	Minimum requirements.....	518

11.1.9	PSFCH decoding capability test .....	520
11.1.9.1	2RX requirements .....	520
11.1.9.1.1	Minimum requirements .....	520
11.1.9A	PSFCH decoding capability test for CA .....	521
11.1.9A.1	2RX requirements .....	521
11.1.9A.1.1	Minimum requirements .....	521
<b>Annex A (normative): Measurement channels .....</b>		<b>523</b>
A.1	General .....	523
A.1.1	Throughput definition.....	523
A.1.2	TDD UL-DL configurations for FR1 .....	523
A.1.3	TDD UL-DL configurations for FR2 .....	527
A.2	Void.....	529
A.3	DL reference measurement channels .....	529
A.3.1	General .....	529
A.3.2	Reference measurement channels for PDSCH performance requirements .....	529
A.3.2.1	FDD .....	530
A.3.2.1.1	Reference measurement channels for SCS 15 kHz FR1 .....	530
A.3.2.1.2	Reference measurement channels for SCS 30 kHz FR1 .....	547
A.3.2.1.3	Reference measurement channels for SCS 60 kHz FR1 .....	548
A.3.2.1.4	Reference measurement channels for E-UTRA .....	548
A.3.2.1.5	Reference measurement channels for Intra-cell Inter-UE interference scenario .....	552
A.3.2.2	TDD.....	553
A.3.2.2.1	Reference measurement channels for SCS 15 kHz FR1 .....	553
A.3.2.2.2	Reference measurement channels for SCS 30 kHz FR1 .....	558
A.3.2.2.3	Reference measurement channels for SCS 60 kHz FR1 .....	609
A.3.2.2.4	Reference measurement channels for SCS 60 kHz FR2 .....	609
A.3.2.2.5	Reference measurement channels for SCS 120 kHz FR2 .....	610
A.3.2.2.6	Reference measurement channels for E-UTRA .....	629
A.3.2.2.7	Reference measurement channels for Intra-cell Inter-UE interference scenario .....	634
A.3.2.2.8	Reference measurement channels for SCS 480 kHz FR2-2 .....	635
A.3.2.3	HD-FDD .....	639
A.3.2.3.1	Reference measurement channels for SCS 15 kHz FR1 .....	639
A.3.3	Reference measurement channels for PDCCH performance requirements .....	643
A.3.3.1	FDD .....	643
A.3.3.1.1	Reference measurement channels for SCS 15 kHz FR1 .....	643
A.3.3.1.2	Reference measurement channels for SCS 30 kHz FR1 .....	644
A.3.3.2	TDD.....	645
A.3.3.2.1	Reference measurement channels for SCS 15 kHz FR1 .....	645
A.3.3.2.2	Reference measurement channels for SCS 30 kHz FR1 .....	647
A.3.3.2.3	Reference measurement channels for SCS 60 kHz FR1 .....	647
A.3.3.2.4	Reference measurement channels for SCS 60 kHz FR2 .....	647
A.3.3.2.5	Reference measurement channels for SCS 120 kHz FR2 .....	647
A.3.3.2.6	Reference measurement channels for SCS 480 kHz FR2-2 .....	648
A.3.4	Reference measurement channels for PBCH demodulation requirements .....	649
A.3.4.1	Reference measurement channels for FR1.....	649
A.3.4.2	Reference measurement channels for FR2.....	649
A.4	CSI reference measurement channels.....	649
A.5	OFDMA Channel Noise Generator (OCNG) .....	653
A.5.1	OCNG Patterns for FDD .....	653
A.5.1.1	OCNG FDD pattern 1: Generic OCNG FDD Pattern for all unused REs.....	653
A.5.2	OCNG Patterns for TDD .....	653
A.5.2.1	OCNG TDD pattern 1: Generic OCNG TDD Pattern for all unused REs .....	653
A.6	SL reference measurement channels .....	654
A.6.1	General .....	654
A.6.2	Reference measurement channels for PSSCH performance requirements .....	654
A.6.2.1	Reference measurement channels for SCS 15 kHz FR1 .....	654
A.6.2.2	Reference measurement channels for SCS 30 kHz FR1 .....	654

A.6.3	Reference measurement channels for PSCCH performance requirements.....	655
A.6.3.1	Reference measurement channels for SCS 15 kHz FR1 .....	655
A.6.3.2	Reference measurement channels for SCS 30 kHz FR1 .....	655
A.6.4	Reference measurement for PSBCH performance requirements.....	656
A.6.4.1	Reference measurement channels for SCS 15 kHz FR1 .....	656
A.6.4.2	Reference measurement channels for SCS 30 kHz FR1 .....	656
<b>Annex B (normative): Propagation conditions.....</b>		<b>657</b>
B.1	Static propagation condition.....	657
B.1.0	UE Receiver with 1Rx.....	657
B.1.1	UE Receiver with 2Rx.....	657
B.1.2	UE Receiver with 4Rx.....	657
B.1.3	UE Receiver with 8Rx.....	658
B.2	Multi-path fading propagation conditions .....	659
B.2.1	Delay profiles .....	659
B.2.1.1	Delay profiles for FR1 .....	661
B.2.1.2	Delay profiles for FR2 .....	662
B.2.2	Combinations of channel model parameters .....	664
B.2.3	MIMO Channel Correlation Matrices .....	664
B.2.3.1	MIMO Correlation Matrices using Uniform Linear Array (ULA) .....	664
B.2.3.1.1	Definition of MIMO Correlation Matrices.....	664
B.2.3.1.2	MIMO Correlation Matrices at High, Medium and Low Level .....	667
B.2.3.1.3	Beam steering approach .....	671
B.2.3.2	MIMO Correlation Matrices using Cross Polarized Antennas (X-pol) .....	671
B.2.3.2.1	Definition of MIMO Correlation Matrices using cross polarized antennas .....	671
B.2.3.2.2	MIMO Correlation Matrices using cross polarized antennas .....	673
B.2.3.2.3	Beam steering approach .....	675
B.2.3.2.3A	Beam steering approach with dual cluster beams.....	677
B.2.4	Two-tap propagation conditions for CQI tests .....	679
B.3	High Speed Train Scenario.....	679
B.3.1	Single Tap Channel Profile .....	679
B.3.2	HST-SFN Channel Profile.....	682
B.3.3	HST-DPS Channel Profile.....	686
B.3.4	FR2 HST-DPS Channel Profile.....	690
B.3.4.1	Unidirectional Deployment Channel Profile.....	690
B.3.4.2	Bidirectional Deployment Channel Profile.....	692
B.3.4.3	Bidirectional Deployment Channel Profile with Multi-Rx Chain Reception .....	694
B.3.5	HST-SFN Scheme A Channel Profile .....	696
B.3.6	HST-SFN Scheme B Channel Profile .....	699
B.4	Physical signals, channels mapping and precoding.....	702
B.4.1	General .....	702
B.4.2	Beamforming for MU-MIMO .....	703
B.5	Transmission Model for requirements on bands with shared spectrum access .....	704
B.5.1	Downlink Transmission Model for bands with shared spectrum access .....	704
B.5.2	Sidelink Transmission Model for bands with shared spectrum access .....	705
B.6	Interference model for PDSCH requirements with intercell interference .....	705
B.6.1	Interference to Noise ratio (INR).....	705
B.6.2	Interference model for PDSCH and CSI Reporting requirements.....	705
B.7	Interference model for PDSCH requirements with LTE-NR spectrum sharing.....	706
<b>Annex C (normative): Downlink physical channels.....</b>		<b>707</b>
C.1	General .....	707
C.2	Setup (Conducted).....	707
C.3	Connection (Conducted).....	707
C.3.1	Measurement of Performance requirements.....	707