

ETSI TS 138 104 V17.21.0 (2026-04)



TECHNICAL SPECIFICATION

**5G;
NR;
Base Station (BS) radio transmission and reception
(3GPP TS 38.104 version 17.21.0 Release 17)**

get full document from standards.iteh.ai



ReferenceRTS/TSGR-0438104v10

Keywords5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed, this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our [Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2026.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found at [3GPP to ETSI numbering cross-referencing](#).

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	13
1 Scope	15
2 References	15
3 Definitions, symbols and abbreviations	16
3.1 Definitions	16
3.2 Symbols.....	21
3.3 Abbreviations	23
4 General	25
4.1 Relationship with other core specifications.....	25
4.2 Relationship between minimum requirements and test requirements	25
4.3 Conducted and radiated requirement reference points	25
4.3.1 <i>BS type 1-C</i>	25
4.3.2 <i>BS type 1-H</i>	26
4.3.3 <i>BS type 1-O</i> and <i>BS type 2-O</i>	27
4.4 Base station classes	27
4.5 Regional requirements.....	28
4.6 Applicability of requirements.....	31
4.7 Requirements for contiguous and <i>non-contiguous spectrum</i>	31
4.8 Requirements for BS capable of multi-band operation	32
4.9 OTA co-location with other base stations	33
5 <i>Operating bands</i> and channel arrangement.....	35
5.1 General	35
5.2 <i>Operating bands</i>	35
5.3 <i>BS channel bandwidth</i>	38
5.3.1 General.....	38
5.3.2 <i>Transmission bandwidth configuration</i>	39
5.3.3 Minimum guardband and <i>transmission bandwidth configuration</i>	40
5.3.4 RB alignment.....	41
5.3.5 <i>BS channel bandwidth per operating band</i>	41
5.3A <i>BS channel bandwidth for CA</i>	46
5.3A.1 <i>Transmission bandwidth configuration for CA</i>	46
5.3A.2 Minimum guardband and <i>transmission bandwidth configuration for CA</i>	46
5.4 Channel arrangement.....	48
5.4.1 Channel spacing.....	48
5.4.1.1 Channel spacing for adjacent NR carriers	48
5.4.1.2 Channel spacing for CA	48
5.4.2 Channel raster	49
5.4.2.1 NR-ARFCN and channel raster.....	49
5.4.2.1A NB-IoT carrier frequency numbering.....	50
5.4.2.2 Channel raster to resource element mapping.....	50
5.4.2.3 Channel raster entries for each <i>operating band</i>	50
5.4.3 Synchronization raster	54
5.4.3.1 Synchronization raster and numbering.....	54
5.4.3.3 Synchronization raster entries for each operating band.....	55
6 Conducted transmitter characteristics	59
6.1 General	59
6.2 Base station output power	59
6.2.1 General.....	59
6.2.2 Minimum requirement for <i>BS type 1-C</i>	60

6.2.3	Minimum requirement for <i>BS type 1-H</i>	60
6.2.4	Additional requirements (regional).....	60
6.3	Output power dynamics.....	61
6.3.1	General.....	61
6.3.2	RE power control dynamic range	61
6.3.2.1	General	61
6.3.2.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	61
6.3.3	Total power dynamic range	61
6.3.3.1	General	61
6.3.3.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	62
6.3.4	NB-IoT RB power dynamic range for NB-IoT operation in NR in-band	62
6.3.4.1	General	62
6.3.4.2	Minimum Requirement	62
6.4	Transmit ON/OFF power	63
6.4.1	Transmitter OFF power	63
6.4.1.1	General	63
6.4.1.2	Minimum requirement for <i>BS type 1-C</i>	63
6.4.1.3	Minimum requirement for <i>BS type 1-H</i>	63
6.4.2	<i>Transmitter transient period</i>	63
6.4.2.1	General	63
6.4.2.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H 1-H</i>	64
6.4.2.3	Void.....	64
6.5	Transmitted signal quality	64
6.5.1	Frequency error.....	64
6.5.1.1	General	64
6.5.1.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	65
6.5.2	Modulation quality.....	65
6.5.2.1	General	65
6.5.2.2	Minimum Requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	65
6.5.2.3	EVM frame structure for measurement.....	65
6.5.3	Time alignment error	66
6.5.3.1	General	66
6.5.3.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	66
6.6	Unwanted emissions.....	66
6.6.1	General.....	66
6.6.2	Occupied bandwidth	67
6.6.2.1	General	67
6.6.2.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	67
6.6.3	Adjacent Channel Leakage Power Ratio	68
6.6.3.1	General	68
6.6.3.2	Limits and <i>Basic limits</i>	68
6.6.3.3	Minimum requirement for <i>BS type 1-C</i>	71
6.6.3.4	Minimum requirement for <i>BS type 1-H</i>	71
6.6.4	Operating band unwanted emissions	72
6.6.4.1	General	72
6.6.4.2	<i>Basic limits</i>	73
6.6.4.2.1	<i>Basic limits</i> for Wide Area BS (Category A)	73
6.6.4.2.2	<i>Basic limits</i> for Wide Area BS (Category B)	74
6.6.4.2.3	<i>Basic limits</i> for Medium Range BS (Category A and B).....	78
6.6.4.2.4	<i>Basic limits</i> for Local Area BS (Category A and B).....	80
6.6.4.2.4A	<i>Basic limits</i> for Local Area and Medium Range BS for bands n46, n96 and n102 (Category A and B).....	81
6.6.4.2.5	<i>Basic limits</i> for additional requirements	84
6.6.4.3	Minimum requirements for <i>BS type 1-C</i>	86
6.6.4.4	Minimum requirements for <i>BS type 1-H</i>	86
6.6.5	Transmitter spurious emissions.....	87
6.6.5.1	General	87
6.6.5.2	<i>Basic limits</i>	87
6.6.5.2.1	General transmitter spurious emissions requirements	87
6.6.5.2.2	Protection of the BS receiver of own or different BS	88
6.6.5.2.3	Additional spurious emissions requirements	88
6.6.5.2.4	Co-location with other base stations.....	99

6.6.5.3	Minimum requirements for <i>BS type 1-C</i>	105
6.6.5.4	Minimum requirements for <i>BS type 1-H</i>	105
6.7	Transmitter intermodulation	105
6.7.1	General	105
6.7.2	Minimum requirements for <i>BS type 1-C</i>	106
6.7.2.1	Co-location minimum requirements	106
6.7.2.2	Additional requirements	106
6.7.3	Minimum requirements for <i>BS type 1-H</i>	107
6.7.3.1	Co-location minimum requirements	107
6.7.3.2	Intra-system minimum requirements	108
6.7.3.3	Additional requirements	108
7	Conducted receiver characteristics	110
7.1	General	110
7.2	Reference sensitivity level	110
7.2.1	General	110
7.2.2	Minimum requirements for <i>BS type 1-C</i> and <i>BS type 1-H</i>	110
7.3	Dynamic range	115
7.3.1	General	115
7.3.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	115
7.4	In-band selectivity and blocking	127
7.4.1	Adjacent Channel Selectivity (ACS)	127
7.4.1.1	General	127
7.4.1.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	127
7.4.1.3	Void	130
7.4.1.4	Void	130
7.4.2	In-band blocking	130
7.4.2.1	General	130
7.4.2.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	130
7.4.2.3	Void	134
7.4.2.4	Void	134
7.4.2.5	Additional narrowband blocking requirement for Band n100	134
7.5	Out-of-band blocking	134
7.5.1	General	134
7.5.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	135
7.5.3	Co-location minimum requirements for <i>BS type 1-C</i> and <i>BS type 1-H</i>	136
7.5.4	Void	137
7.5.5	Additional out-of-band blocking requirements for the use of RMR bands	137
7.6	Receiver spurious emissions	137
7.6.1	General	137
7.6.2	<i>Basic limits</i>	137
7.6.3	Minimum requirement for <i>BS type 1-C</i>	138
7.6.4	Minimum requirement for <i>BS type 1-H</i>	138
7.7	Receiver intermodulation	139
7.7.1	General	139
7.7.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	139
7.7.3	Additional narrowband intermodulation requirement for Band n100	144
7.8	In-channel selectivity	144
7.8.1	General	144
7.8.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	144
8	Conducted performance requirements	155
8.1	General	155
8.1.1	Scope and definitions	155
8.1.2	Void	155
8.2	Performance requirements for PUSCH	155
8.2.1	Requirements for PUSCH with transform precoding disabled	155
8.2.1.1	General	155
8.2.1.2	Minimum requirements	156
8.2.2	Requirements for PUSCH with transform precoding enabled	164
8.2.2.1	General	164
8.2.2.2	Minimum requirements	164

8.2.3	Requirements for UCI multiplexed on PUSCH.....	165
8.2.3.1	General.....	165
8.2.3.2	Minimum requirements.....	166
8.2.4	Requirements for PUSCH for high speed train.....	167
8.2.4.1	General.....	167
8.2.4.2	Minimum requirements.....	168
8.2.5	Requirements for UL timing adjustment.....	170
8.2.5.1	Minimum requirements for high speed train.....	171
8.2.5.2	Minimum requirements for normal mode.....	172
8.2.6	Requirements for PUSCH 0.001% BLER.....	173
8.2.6.1	General.....	173
8.2.6.2	Minimum requirements.....	173
8.2.7	Requirements for PUSCH repetition Type A.....	174
8.2.7.1	General.....	174
8.2.7.2	Minimum requirements.....	175
8.2.8	Requirements for PUSCH mapping Type B with non-slot transmission.....	177
8.2.8.1	General.....	177
8.2.8.2	Minimum requirements.....	177
8.2.9	Requirements of PUSCH for 2-step RA type.....	178
8.2.9.1	General.....	178
8.2.9.2	Minimum requirements.....	179
8.2.10	Requirements for interlaced PUSCH.....	179
8.2.10.1	General.....	179
8.2.10.2	Minimum requirements.....	180
8.2.11	Performance requirements for CG-UCI multiplexed on interlaced PUSCH.....	181
8.2.11.1	General.....	181
8.2.11.2	Minimum requirements.....	182
8.2.12	Requirements for TB processing over multi-slot PUSCH (TBOMS).....	183
8.2.12.1	General.....	183
8.2.12.2	Minimum requirements.....	183
8.2.13	Requirements for PUSCH with DM-RS bundling.....	184
8.2.13.1	General.....	184
8.2.13.2	Minimum requirements.....	185
8.3	Performance requirements for PUCCH.....	187
8.3.1	DTX to ACK probability.....	187
8.3.1.1	General.....	187
8.3.1.2	Minimum requirement.....	188
8.3.2	Performance requirements for PUCCH format 0.....	188
8.3.2.1	General.....	188
8.3.2.2	Minimum requirements.....	188
8.3.3	Performance requirements for PUCCH format 1.....	189
8.3.3.1	NACK to ACK requirements.....	189
8.3.3.1.1	General.....	189
8.3.3.1.2	Minimum requirements.....	189
8.3.3.2	ACK missed detection requirements.....	190
8.3.3.2.1	General.....	190
8.3.3.2.2	Minimum requirements.....	190
8.3.4	Performance requirements for PUCCH format 2.....	191
8.3.4.1	ACK missed detection requirements.....	191
8.3.4.1.1	General.....	191
8.3.4.1.2	Minimum requirements.....	191
8.3.4.2	UCI BLER performance requirements.....	192
8.3.4.2.1	General.....	192
8.3.4.2.2	Minimum requirements.....	192
8.3.5	Performance requirements for PUCCH format 3.....	193
8.3.5.1	General.....	193
8.3.5.2	Minimum requirements.....	193
8.3.6	Performance requirements for PUCCH format 4.....	194
8.3.6.1	General.....	194
8.3.6.2	Minimum requirement.....	195
8.3.7	Performance requirements for multi-slot PUCCH.....	196
8.3.7.1	General.....	196

8.3.7.2	Performance requirements for multi-slot PUCCH format 1	196
8.3.7.2.1	NACK to ACK requirements	196
8.3.7.2.1.1	General	196
8.3.7.2.1.2	Minimum requirements	197
8.3.7.2.2	ACK missed detection requirements	197
8.3.8	Performance requirements for interlaced PUCCH format 0	197
8.3.8.1	General	197
8.3.8.2	Minimum requirements	198
8.3.9	Performance requirements for interlaced PUCCH format 1	198
8.3.9.1	NACK to ACK requirements	198
8.3.9.1.1	General	198
8.3.9.1.2	Minimum requirements	199
8.3.9.2	ACK missed detection requirements	199
8.3.9.2.1	General	199
8.3.9.2.2	Minimum requirements	199
8.3.10	Performance requirements for interlaced PUCCH format 2	200
8.3.10.1	General	200
8.3.10.2	Minimum requirements	200
8.3.11	Performance requirements for interlaced PUCCH format 3	201
8.3.11.1	General	201
8.3.11.2	Minimum requirements	201
8.3.12	Performance requirements for PUCCH format 1 with DM-RS bundling	202
8.3.12.1	NACK to ACK requirements	202
8.3.12.1.1	General	202
8.3.12.1.2	Minimum requirements	202
8.3.12.2	ACK missed detection requirements	203
8.3.12.2.1	General	203
8.3.12.2.2	Minimum requirements	203
8.3.13	Performance requirements for PUCCH format 3 with DMRS bundling	203
8.3.13.1	General	203
8.3.13.2	Minimum requirements	204
8.3.14	Performance requirements for sub-slot repetition PUCCH format 0	205
8.3.14.1	General	205
8.3.14.2	Minimum requirements	205
8.4	Performance requirements for PRACH	206
8.4.1	PRACH False alarm probability	206
8.4.1.1	General	206
8.4.1.2	Minimum requirement	206
8.4.2	PRACH detection requirements	206
8.4.2.1	General	206
8.4.2.2	Minimum requirements for Normal Mode	206
8.4.2.3	Minimum requirements for high speed train	207
8.4.2.4	Minimum requirements for PRACH with $L_{RA}=1151$ and $L_{RA}=571$	208
9	Radiated transmitter characteristics	210
9.1	General	210
9.2	Radiated transmit power	210
9.2.1	General	210
9.2.2	Minimum requirement for <i>BS type 1-H</i> and <i>BS type 1-O</i>	211
9.2.3	Minimum requirement for <i>BS type 2-O</i>	211
9.3	OTA base station output power	211
9.3.1	General	211
9.3.2	Minimum requirement for <i>BS type 1-O</i>	212
9.3.3	Minimum requirement for <i>BS type 2-O</i>	212
9.3.4	Additional requirements (regional)	212
9.4	OTA output power dynamics	212
9.4.1	General	212
9.4.2	OTA RE power control dynamic range	212
9.4.2.1	General	212
9.4.2.2	Minimum requirement for <i>BS type 1-O</i>	212
9.4.3	OTA total power dynamic range	212
9.4.3.1	General	212

9.4.3.2	Minimum requirement for <i>BS type 1-O</i>	213
9.4.3.3	Minimum requirement for <i>BS type 2-O</i>	213
9.5	OTA transmit ON/OFF power.....	213
9.5.1	General.....	213
9.5.2	OTA transmitter OFF power.....	213
9.5.2.1	General.....	213
9.5.2.2	Minimum requirement for <i>BS type 1-O</i>	213
9.5.2.3	Minimum requirement for <i>BS type 2-O</i>	214
9.5.3	OTA transient period.....	214
9.5.3.1	General.....	214
9.5.3.2	Minimum requirement for <i>BS type 1-O</i>	214
9.5.3.3	Minimum requirement for <i>BS type 2-O</i>	214
9.6	OTA transmitted signal quality.....	214
9.6.1	OTA frequency error.....	214
9.6.1.1	General.....	214
9.6.1.2	Minimum requirement for <i>BS type 1-O</i>	214
9.6.1.3	Minimum requirement for <i>BS type 2-O</i>	215
9.6.2	OTA modulation quality.....	215
9.6.2.1	General.....	215
9.6.2.2	Minimum Requirement for <i>BS type 1-O</i>	215
9.6.2.3	Minimum Requirement for <i>BS type 2-O</i>	215
9.6.2.3.1	EVM frame structure for measurement.....	215
9.6.3	OTA time alignment error.....	215
9.6.3.1	General.....	215
9.6.3.2	Minimum requirement for <i>BS type 1-O</i>	216
9.6.3.3	Minimum requirement for <i>BS type 2-O</i>	216
9.7	OTA unwanted emissions.....	216
9.7.1	General.....	216
9.7.2	OTA occupied bandwidth.....	217
9.7.2.1	General.....	217
9.7.2.2	Minimum requirement for <i>BS type 1-O</i> and <i>BS type 2-O</i>	217
9.7.3	OTA Adjacent Channel Leakage Power Ratio (ACLR).....	218
9.7.3.1	General.....	218
9.7.3.2	Minimum requirement for <i>BS type 1-O</i>	218
9.7.3.3	Minimum requirement for <i>BS type 2-O</i>	218
9.7.4	OTA operating band unwanted emissions.....	220
9.7.4.1	General.....	220
9.7.4.2	Minimum requirement for <i>BS type 1-O</i>	220
9.7.4.2.1	Additional requirements.....	221
9.7.4.2.1.1	Protection of DTT.....	221
9.7.4.2.1.2	Limits in FCC Title 47.....	221
9.7.4.3	Minimum requirement for <i>BS type 2-O</i>	221
9.7.4.3.1	General.....	221
9.7.4.3.2	OTA operating band unwanted emission limits (Category A).....	222
9.7.4.3.3	OTA operating band unwanted emission limits (Category B).....	223
9.7.4.3.4	Additional OTA operating band unwanted emission requirements.....	224
9.7.5	OTA transmitter spurious emissions.....	224
9.7.5.1	General.....	224
9.7.5.2	Minimum requirement for <i>BS type 1-O</i>	224
9.7.5.2.1	General.....	224
9.7.5.2.2	General OTA transmitter spurious emissions requirements.....	225
9.7.5.2.3	Protection of the BS receiver of own or different BS.....	225
9.7.5.2.4	Additional spurious emissions requirements.....	225
9.7.5.2.5	Co-location with other base stations.....	225
9.7.5.3	Minimum requirement for <i>BS type 2-O</i>	225
9.7.5.3.1	General.....	225
9.7.5.3.2	General OTA transmitter spurious emissions requirements.....	226
9.7.5.3.3	Additional OTA transmitter spurious emissions requirements.....	227
9.8	OTA transmitter intermodulation.....	227
9.8.1	General.....	227
9.8.2	Minimum requirement for <i>BS type 1-O</i>	227
9.8.3	Additional requirements (regional).....	228

10	Radiated receiver characteristics	229
10.1	General	229
10.2	OTA sensitivity	230
10.2.1	<i>BS type 1-H</i> and <i>BS type 1-O</i>	230
10.2.1.1	General	230
10.2.1.2	Minimum requirement	230
10.2.2	<i>BS type 2-O</i>	230
10.3	OTA reference sensitivity level	231
10.3.1	General	231
10.3.2	Minimum requirement for <i>BS type 1-O</i>	231
10.3.3	Minimum requirement for <i>BS type 2-O</i>	233
10.4	OTA dynamic range	234
10.4.1	General	234
10.4.2	Minimum requirement for <i>BS type 1-O</i>	234
10.5	OTA in-band selectivity and blocking	247
10.5.1	OTA adjacent channel selectivity	247
10.5.1.1	General	247
10.5.1.2	Minimum requirement for <i>BS type 1-O</i>	247
10.5.1.3	Minimum requirement for <i>BS type 2-O</i>	248
10.5.2	OTA in-band blocking	249
10.5.2.1	General	249
10.5.2.2	Minimum requirement for <i>BS type 1-O</i>	249
10.5.2.3	Minimum requirement for <i>BS type 2-O</i>	252
10.6	OTA out-of-band blocking	253
10.6.1	General	253
10.6.2	Minimum requirement for <i>BS type 1-O</i>	253
10.6.2.1	General minimum requirement	253
10.6.2.2	Co-location minimum requirement	254
10.6.3	Minimum requirement for <i>BS type 2-O</i>	254
10.6.3.1	General minimum requirement	254
10.7	OTA receiver spurious emissions	255
10.7.1	General	255
10.7.2	Minimum requirement for <i>BS type 1-O</i>	255
10.7.3	Minimum requirement for <i>BS type 2-O</i>	256
10.8	OTA receiver intermodulation	257
10.8.1	General	257
10.8.2	Minimum requirement for <i>BS type 1-O</i>	257
10.8.3	Minimum requirement for <i>BS type 2-O</i>	262
10.9	OTA in-channel selectivity	263
10.9.1	General	263
10.9.2	Minimum requirement for <i>BS type 1-O</i>	263
10.9.3	Minimum requirement for <i>BS type 2-O</i>	267
11	Radiated performance requirements	269
11.1	General	269
11.1.1	Scope and definitions	269
11.1.2	OTA demodulation branches	269
11.1.3	Void	270
11.2	Performance requirements for PUSCH	270
11.2.1	Requirements for <i>BS type 1-O</i>	270
11.2.1.1	Requirements for PUSCH with transform precoding disabled	270
11.2.1.2	Requirements for PUSCH with transform precoding enabled	270
11.2.1.3	Requirements for UCI multiplexed on PUSCH	270
11.2.1.4	Requirements for PUSCH for high speed train	270
11.2.1.5	Requirements for UL timing adjustment	270
11.2.1.6	Requirements for PUSCH 0.001% BLER	270
11.2.1.7	Requirements for PUSCH repetition Type A	270
11.2.1.8	Requirements for PUSCH mapping Type B with non-slot transmission	270
11.2.1.9	Requirements for PUSCH for 2-step RA type	270
11.2.1.10	Requirements for interlaced PUSCH	270
11.2.1.11	Requirements for CG-UCI multiplexed on interlaced PUSCH	270
11.2.1.12	Requirements for TB processing over multi-slot PUSCH (TBoMS)	270

11.2.1.13	Requirements for PUSCH with DM-RS bundling	271
11.2.2	Requirements for <i>BS type 2-O</i>	271
11.2.2.1	Requirements for PUSCH with transform precoding disabled	271
11.2.2.1.1	General	271
11.2.2.1.2	Minimum requirements	271
11.2.2.2	Requirements for PUSCH with transform precoding enabled	276
11.2.2.2.1	General	276
11.2.2.2.2	Minimum requirements	276
11.2.2.3	Requirements for UCI multiplexed on PUSCH	277
11.2.2.3.1	General	277
11.2.2.3.2	Minimum requirements	278
11.2.2.4	Requirements for PUSCH for 2-step RA type	280
11.2.2.4.1	General	280
11.2.2.4.2	Minimum requirements	281
11.2.2.5	Requirements for PUSCH repetition Type A	281
11.2.2.5.1	General	281
11.2.2.5.2	Minimum requirements	282
11.2.2.6	Requirements for PUSCH mapping Type B with non-slot transmission	283
11.2.2.6.1	General	283
11.2.2.6.2	Minimum requirements	283
11.2.2.7	Requirements for PUSCH for high speed train	284
11.2.2.7.1	General	284
11.2.2.7.2	Minimum requirements	284
11.2.2.8	Requirements for UL timing adjustment	285
11.2.2.8.1	General	285
11.2.2.8.2	Minimum requirements for high speed train	286
11.2.2.9	Requirements for TB processing over multi-slot PUSCH (TBoMS)	287
11.2.2.9.1	General	287
11.2.2.9.2	Minimum requirements	287
11.2.2.10	Requirements for PUSCH with DM-RS bundling	288
11.2.2.10.1	General	288
11.2.2.10.2	Minimum requirements	288
11.3	Performance requirements for PUCCH	289
11.3.1	Requirements for <i>BS type 1-O</i>	289
11.3.1.1	DTX to ACK probability	289
11.3.1.2	Performance requirements for PUCCH format 0	289
11.3.1.3	Performance requirements for PUCCH format 1	289
11.3.1.4	Performance requirements for PUCCH format 2	289
11.3.1.5	Performance requirements for PUCCH format 3	289
11.3.1.6	Performance requirements for PUCCH format 4	289
11.3.1.7	Performance requirements for multi-slot PUCCH	289
11.3.1.8	Performance requirements for PUCCH format 1 with DMRS bundling	289
11.3.1.9	Performance requirements for PUCCH format 3 with DMRS bundling	290
11.3.1.10	Performance requirements for sub-slot repetition PUCCH format 0	290
11.3.2	Requirements for <i>BS type 2-O</i>	290
11.3.2.1	DTX to ACK probability	290
11.3.2.2	Performance requirements for PUCCH format 0	290
11.3.2.2.1	General	290
11.3.2.2.2	Minimum requirements	290
11.3.2.3	Performance requirements for PUCCH format 1	291
11.3.2.3.1	NACK to ACK requirements	291
11.3.2.3.1.1	General	291
11.3.2.3.1.2	Minimum requirements	292
11.3.2.3.2	ACK missed detection requirements	293
11.3.2.3.2.1	General	293
11.3.2.3.2.2	Minimum requirements	293
11.3.2.4	Performance requirements for PUCCH format 2	294
11.3.2.4.1	ACK missed detection requirements	294
11.3.2.4.1.1	General	294
11.3.2.4.1.2	Minimum requirements	294
11.3.2.4.2	UCI BLER performance requirements	295
11.3.2.4.2.1	General	295

11.3.2.4.2.2	Minimum requirements.....	295
11.3.2.5	Performance requirements for PUCCH format 3	296
11.3.2.5.1	General	296
11.3.2.5.2	Minimum requirements	296
11.3.2.6	Performance requirements for PUCCH format 4	297
11.3.2.6.1	General	297
11.3.2.6.2	Minimum requirements	298
11.3.2.7	Performance requirements for PUCCH format 1 with DMRS bundling.....	299
11.3.2.7.1	NACK to ACK requirements	299
11.3.2.7.1.1	General.....	299
11.3.2.7.1.2	Minimum requirements.....	300
11.3.2.7.2	ACK missed detection requirements	300
11.3.2.7.2.1	General.....	300
11.3.2.7.2.2	Minimum requirements.....	301
11.3.2.8	Performance requirements for PUCCH format 3 with DMRS bundling.....	301
11.3.2.8.1	General	301
11.3.2.8.2	Minimum requirements	302
11.4	Performance requirements for PRACH.....	302
11.4.1	Requirements for <i>BS type 1-O</i>	302
11.4.1.1	PRACH False alarm probability	302
11.4.1.2	PRACH detection requirements	302
11.4.2	Requirements for <i>BS type 2-O</i>	302
11.4.2.1	PRACH False alarm probability	302
11.4.2.1.1	General	302
11.4.2.1.2	Minimum requirement.....	302
11.4.2.2	PRACH detection requirements	303
11.4.2.2.1	General	303
11.4.2.2.2	Minimum requirements for Normal mode.....	303
11.4.2.2.3	Minimum requirements for high speed train	304
11.4.2.2.4	Minimum requirements for PRACH with $L_{RA}=1151$ and $L_{RA}=571$	304
Annex A (normative): Reference measurement channels.....		306
A.1	Fixed Reference Channels for reference sensitivity level, ACS, in-band blocking, out-of-band blocking, receiver intermodulation and in-channel selectivity (QPSK, R=1/3).....	306
A.2	Fixed Reference Channels for dynamic range (16QAM, R=2/3).....	309
A.3	Fixed Reference Channels for performance requirements (QPSK, R=193/1024)	311
A.3A	Fixed Reference Channels for performance requirements (QPSK, R=99/1024)	319
A.3B	Fixed Reference Channels for performance requirements (QPSK, R=308/1024)	321
A.4	Fixed Reference Channels for performance requirements (16QAM, R=658/1024)	325
A.5	Fixed Reference Channels for performance requirements (64QAM, R=567/1024)	330
A.6	PRACH Test preambles	333
A.7	Fixed Reference Channels for performance requirements (16QAM, R=434/1024)	334
A.8	Fixed Reference Channels for performance requirements (QPSK, R=157/1024)	336
A.9	Fixed Reference Channels for performance requirements (256QAM, R=682.5/1024)	337
A.10	Fixed Reference Channels for performance requirements (64QAM, R=517/1024)	338
Annex B (normative): Error Vector Magnitude (FR1).....		342
B.1	Reference point for measurement.....	342
B.2	Basic unit of measurement	342
B.3	Modified signal under test.....	343
B.4	Estimation of frequency offset	343

B.5	Estimation of time offset	343
B.5.1	General	343
B.5.2	Window length	344
B.6	Estimation of TX chain amplitude and frequency response parameters	345
B.7	Averaged EVM	347
Annex C (normative): Error Vector Magnitude (FR2).....		349
C.1	Reference point for measurement.....	349
C.2	Basic unit of measurement	349
C.3	Modified signal under test.....	350
C.4	Estimation of frequency offset	350
C.5	Estimation of time offset	350
C.5.1	General	350
C.5.2	Window length	351
C.6	Estimation of TX chain amplitude and frequency response parameters	352
C.7	Averaged EVM	354
Annex D (normative): Characteristics of the interfering signals		356
Annex E: Void		357
Annex F (normative): Relationship between EIRP based regulatory requirements and 3GPP requirements.....		358
F.1	General	358
F.2	Relationship between EIRP based regulatory requirements and conducted requirements.....	358
F.3	Relationship between EIRP based regulatory requirements and OTA requirements.....	359
Annex G (Normative): Propagation conditions		360
G.1	Static propagation condition.....	360
G.2	Multi-path fading propagation conditions.....	360
G.2.1	Delay profiles	360
G.2.1.1	Delay profiles for FR1	361
G.2.1.2	Delay profiles for FR2	362
G.2.2	Combinations of channel model parameters	364
G.2.3	MIMO Channel Correlation Matrices	365
G.2.3.1	MIMO Correlation Matrices using Uniform Linear Array (ULA)	365
G.2.3.1.1	Definition of MIMO Correlation Matrices.....	365
G.2.3.1.2	MIMO Correlation Matrices at High, Medium and Low Level	369
G.2.3.2	Multi-Antenna channel models using cross polarized antennas	371
G.2.3.2.1	Definition of MIMO Correlation Matrices using cross polarized antennas	372
G.2.3.2.2	Spatial Correlation Matrices at UE and gNB sides	372
G.2.3.2.2.1	Spatial Correlation Matrices at UE side	372
G.2.3.2.2.2	Spatial Correlation Matrices at gNB side	373
G.2.3.2.3	MIMO Correlation Matrices using cross polarized antennas	373
G.3	High speed train condition	373
G.4	Moving propagation conditions.....	378
Annex H (informative): Change history		380
History		392

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

In the present document, modal verbs have the following meanings:

shall indicates a mandatory requirement to do something

shall not indicates an interdiction (prohibition) to do something

The constructions "shall" and "shall not" are confined to the context of normative provisions, and do not appear in Technical Reports.

The constructions "must" and "must not" are not used as substitutes for "shall" and "shall not". Their use is avoided insofar as possible, and they are not used in a normative context except in a direct citation from an external, referenced, non-3GPP document, or so as to maintain continuity of style when extending or modifying the provisions of such a referenced document.

should indicates a recommendation to do something

should not indicates a recommendation not to do something

may indicates permission to do something

need not indicates permission not to do something

The construction "may not" is ambiguous and is not used in normative elements. The unambiguous constructions "might not" or "shall not" are used instead, depending upon the meaning intended.

can indicates that something is possible

cannot indicates that something is impossible

The constructions "can" and "cannot" are not substitutes for "may" and "need not".

will indicates that something is certain or expected to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document

will not indicates that something is certain or expected not to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document

might indicates a likelihood that something will happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

might not indicates a likelihood that something will not happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

In addition:

is (or any other verb in the indicative mood) indicates a statement of fact

is not (or any other negative verb in the indicative mood) indicates a statement of fact

The constructions "is" and "is not" do not indicate requirements.

Sample Document

get full document from standards.iteh.ai