

ETSI TS 138 133 V16.27.0 (2026-04)



TECHNICAL SPECIFICATION

**5G;
NR;
Requirements for support of radio resource management
(3GPP TS 38.133 version 16.27.0 Release 16)**

get full document from standards.iteh.ai



Reference

RTS/TSGR-0438133vgr0

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed, this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our [Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2026.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by the ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found at [3GPP to ETSI numbering cross-referencing](#).

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	68
1 Scope	70
2 References	70
3 Definitions, symbols and abbreviations	71
3.1 Definitions	71
3.2 Symbols.....	72
3.3 Abbreviations	73
3.4 Test tolerances.....	76
3.5 Frequency bands grouping	76
3.5.1 Introduction.....	76
3.5.2 NR operating bands in FR1	76
3.5.3 NR operating bands in FR2	77
3.6 Applicability of requirements in this specification version	77
3.6.1 RRC connected state requirements in DRX.....	78
3.6.2 Number of serving carriers	78
3.6.2.1 Number of serving carriers for SA	78
3.6.2.2 Number of serving carriers for EN-DC.....	78
3.6.2.3 Number of serving carriers for NE-DC.....	78
3.6.2.4 Number of serving carriers for NR-DC.....	79
3.6.3 Applicability for intra-band FR2	79
3.6.4 Applicability for FR2 UE power classes.....	79
3.6.5 Applicability for SDL bands.....	79
3.6.6 Applicability of requirements for NGEN-DC operation.....	79
3.6.7 Applicability of QCL.....	79
3.6.9 Applicability of requirements for scheduling availability.....	80
3.6.10 Applicability of requirements for measurement restrictions.....	80
4 SA: RRC_IDLE state mobility.....	80
4.1 Cell Selection	80
4.2 Cell Re-selection	80
4.2.1 Introduction.....	80
4.2.2 Requirements	81
4.2.2.1 UE measurement capability	81
4.2.2.2 Measurement and evaluation of serving cell.....	81
4.2.2.3 Measurements of intra-frequency NR cells.....	82
4.2.2.4 Measurements of inter-frequency NR cells.....	83
4.2.2.5 Measurements of inter-RAT E-UTRAN cells.....	85
4.2.2.6 Maximum interruption in paging reception.....	87
4.2.2.7 General requirements	87
4.2.2.8 Minimum requirement at transitions	87
4.2.2.9 Measurements of intra-frequency NR cells for UE configured with relaxed measurement criterion	88
4.2.2.9.1 Introduction	88
4.2.2.9.2 Measurements for UE fulfilling low mobility criterion	88
4.2.2.9.3 Measurements for UE fulfilling not-at-cell edge criterion.....	89
4.2.2.9.4 Measurements for UE fulfilling low mobility and not-at-cell edge criteria.....	89
4.2.2.10 Measurements of inter-frequency NR cells for UE configured with relaxed measurement criterion	90
4.2.2.10.1 Introduction	90
4.2.2.10.2 Measurements for UE fulfilling low mobility criterion.....	90
4.2.2.10.3 Measurements for UE fulfilling not-at-cell edge criterion.....	91
4.2.2.10.4 Measurements for UE fulfilling low mobility and not-at-cell edge criterion	92

4.2.2.11	Measurements of inter-RAT E-UTRAN cells for UE configured with relaxed measurement criterion	93
4.2.2.11.1	Introduction	93
4.2.2.11.2	Measurements for UE fulfilling low mobility criterion	93
4.2.2.11.3	Measurements for UE fulfilling with not-at-cell edge criterion	94
4.2.2.11.4	Measurements for UE fulfilling low mobility and not-at-cell edge criterion	95
4.2A	Cell Re-selection when subject to CCA	95
4.2A.1	Introduction.....	95
4.2A.2	Requirements	96
4.2A.2.1	UE measurement capability	96
4.2A.2.2	Measurement and evaluation when subject to CCA on the serving cell	96
4.2A.2.3	Measurements of intra-frequency NR cells when subject to CCA on the serving cell and target cell.....	97
4.2A.2.4	Measurements of inter-frequency NR cells when subject to CCA on the target cell	98
4.2A.2.5	Measurements of inter-RAT E-UTRAN cells when subject to CCA on the serving cell.....	100
4.2A.2.6	Maximum interruption in paging reception when subject to CCA on the target cell	100
4.2A.2.7	General requirements	100
4.3	Minimization of Drive Tests (MDT).....	100
4.3.1	Introduction.....	100
4.3.2	Measurement Requirements.....	101
4.3.3	Requirements for Relative Time Stamp Accuracy.....	101
4.3.4	Requirements for Relative Time Stamp Accuracy for RRC Connection Establishment Failure Log Reporting	101
4.3.5	Requirements for Relative Time Stamp Accuracy for Radio Link Failure and Handover Failure Log Reporting	102
4.4	Idle Mode CA/DC Measurements	102
4.4.1	Introduction.....	102
4.4.2	Measurement Requirements.....	102
4.4.2.1	Detected cell requirement during state transition and Idle mode	102
4.4.2.2	Measurements of inter-frequency CA/DC candidate cells	103
4.4.2.3	Measurements on serving cell.....	104
4.4.2.4	Measurements of E-UTRAN inter-RAT DC candidate cells	104
5	SA: RRC_INACTIVE state mobility	105
5.1	Cell Re-selection	105
5.1.1	Introduction.....	105
5.1.2	Requirements	105
5.1.2.1	UE measurement capability	105
5.1.2.2	Measurement and evaluation of serving cell.....	105
5.1.2.3	Measurements of intra-frequency NR cells	105
5.1.2.4	Measurements of inter-frequency NR cells.....	105
5.1.2.5	Measurements of inter-RAT E-UTRAN cells.....	105
5.1.2.6	Maximum interruption in paging reception.....	105
5.1.2.7	General requirements	105
5.1A	Cell Re-selection with CCA	105
5.1A.1	Introduction.....	105
5.1A.2	Requirements	106
5.1A.2.1	UE measurement capability	106
5.1A.2.2	Measurement and evaluation when CCA is used on the serving cell.....	106
5.1A.2.3	Measurements of intra-frequency NR cells when CCA is used on the serving cell and target cell.....	106
5.1A.2.4	Measurements of inter-frequency NR cells when CCA is used on the target cell.....	106
5.1A.2.5	Measurements of inter-RAT E-UTRAN cells when CCA is used on the serving cell.....	106
5.1A.2.6	Maximum interruption in paging reception when CCA is used on the target cell	106
5.1A.2.7	General requirements	106
5.2	Void.....	106
5.3	Minimization of Drive Tests (MDT).....	106
5.3.1	Introduction.....	106
5.3.2	Measurement Requirements.....	107
5.3.3	Requirements for Relative Time Stamp Accuracy.....	107
5.3.4	Requirements for Relative Time Stamp Accuracy for RRC Connection Establishment Failure Log Reporting	107

5.3.5	Requirements for Relative Time Stamp Accuracy for Radio Link Failure and Handover Failure Log Reporting	107
5.3.6	Requirements for Relative Time Stamp Accuracy for RRC Resume Failure Log Reporting	107
5.4	Inactive Mode CA/DC Measurements	107
5.4.1	Introduction.....	107
5.4.2	Measurement Requirements.....	107
5.4.2.1	Detected cell requirement during state transition and inactive mode.....	108
5.4.2.2	Measurements of inter-frequency CA/DC candidate cells	108
5.4.2.3	Measurements on serving cell.....	108
5.4.2.4	Measurements on E-UTRAN inter-RAT DC candidate cells	108
6	RRC_CONNECTED state mobility	108
6.1	Handover	108
6.1.1	NR Handover	108
6.1.1.1	Introduction.....	108
6.1.1.2	NR FR1 - NR FR1 Handover	108
6.1.1.2.1	Handover delay.....	108
6.1.1.2.2	Interruption time.....	108
6.1.1.3	NR FR2- NR FR1 Handover	109
6.1.1.3.1	Handover delay.....	109
6.1.1.3.2	Interruption time.....	109
6.1.1.4	NR FR2- NR FR2 Handover	110
6.1.1.4.1	Handover delay.....	110
6.1.1.4.2	Interruption time.....	110
6.1.1.5	NR FR1- NR FR2 Handover	111
6.1.1.5.1	Handover delay.....	111
6.1.1.5.2	Interruption time.....	111
6.1.2	NR Handover to other RATs	112
6.1.2.1	NR – E-UTRAN Handover	112
6.1.2.1.1	Introduction	112
6.1.2.1.2	Handover delay.....	112
6.1.2.1.3	Interruption time.....	112
6.1.2.2	NR – UTRAN Handover	113
6.1.2.2.1	Introduction	113
6.1.2.2.2	Handover delay.....	113
6.1.2.2.3	Interruption time.....	113
6.1.3	NR DAPS Handover	114
6.1.3.1	Introduction.....	114
6.1.3.2	NR FR1 - NR FR1 DAPS Handover.....	114
6.1.3.2.1	DAPS handover delay	114
6.1.3.2.2	Interruption time.....	115
6.1.3.3	NR FR2- NR FR1 DAPS Handover.....	117
6.1.3.3.1	DAPS handover delay	117
6.1.3.3.2	Interruption time.....	117
6.1.3.4	NR FR1- NR FR2 DAPS Handover.....	118
6.1.3.4.1	DAPS handover delay	118
6.1.3.4.2	Interruption time.....	118
6.1.4	NR Conditional Handover	119
6.1.4.1	Introduction.....	119
6.1.4.2	NR FR1 – NR FR1 conditional handover	119
6.1.4.3	NR FR2 – NR FR1 conditional handover	120
6.1.4.4	NR FR2 – NR FR2 conditional handover	120
6.1.4.4.1	Handover delay.....	121
6.1.4.4.2	Measurement time	121
6.1.4.4.3	Preparation time.....	121
6.1.4.4.4	Interruption time.....	121
6.1.4.5	NR FR1 – NR FR2 conditional handover	122
6.1A	Void.....	122
6.1A.1	Void	122
6.1A.1.1	Void.....	122
6.1A.1.2	Void.....	122
6.1A.1.2.1	Void.....	122

6.1A.1.2.2	Void.....	122
6.1B	Handover to target cell using CCA.....	122
6.1B.1	NR Handover.....	122
6.1B.1.1	Introduction.....	122
6.1B.1.2	NR FR1 - NR FR1 Handover.....	123
6.1B.1.2.1	Handover delay.....	123
6.1B.1.2.2	Interruption time.....	123
6.2	RRC Connection Mobility Control.....	124
6.2.1	SA: RRC Re-establishment.....	124
6.2.1.1	Introduction.....	124
6.2.1.2	Requirements.....	124
6.2.1.2.1	UE Re-establishment delay requirement.....	124
6.2.1A	RRC Re-establishment with CCA.....	125
6.2.1A.1	Introduction.....	125
6.2.1A.2	Requirements.....	126
6.2.1A.2.1	UE Re-establishment with CCA delay requirement.....	126
6.2.2	Random access.....	127
6.2.2.1	Introduction.....	127
6.2.2.2	Requirements for 4-step RA type.....	128
6.2.2.2.1	Contention based random access.....	128
6.2.2.2.2	Non-Contention based random access.....	129
6.2.2.2.3	UE behaviour when configured with supplementary UL.....	130
6.2.2.3	Requirements for 2-step RA type.....	130
6.2.2.3.1	Contention based random access.....	130
6.2.2.3.2	Non-Contention based random access.....	131
6.2.2.3.3	UE behaviour when configured with supplementary UL.....	132
6.2.2A	Random access when CCA is used on target frequency.....	132
6.2.2A.1	Introduction.....	132
6.2.2A.2	Requirements for 4-step RA type.....	132
6.2.2A.2.1	Contention based random access.....	132
6.2.2A.2.2	Non-Contention based random access.....	133
6.2.2A.3	Requirements for 2-step RA type.....	134
6.2.2A.3.1	Contention based random access.....	135
6.2.2A.3.2	Non-Contention based random access.....	136
6.2.3	SA: RRC Connection Release with Redirection.....	136
6.2.3.1	Introduction.....	136
6.2.3.2	Requirements.....	137
6.2.3.2.1	RRC connection release with redirection to NR.....	137
6.2.3.2.2	RRC connection release with redirection to E-UTRAN.....	138
6.2.3.2.3	RRC connection release with redirection to NR carrier subject to CCA.....	138
7	Timing.....	139
7.1	UE transmit timing.....	139
7.1.1	Introduction.....	139
7.1.2	Requirements.....	139
7.1.2.1	Gradual timing adjustment.....	141
7.1.2.2	Void.....	141
7.2	UE timer accuracy.....	141
7.2.1	Introduction.....	141
7.2.2	Requirements.....	141
7.3	Timing advance.....	142
7.3.1	Introduction.....	142
7.3.2	Requirements.....	142
7.3.2.1	Timing Advance adjustment delay.....	142
7.3.2.2	Timing Advance adjustment accuracy.....	142
7.4	Cell phase synchronization accuracy.....	142
7.4.1	Definition.....	142
7.4.2	Minimum requirements.....	142
7.5	Maximum Transmission Timing Difference.....	143
7.5.1	Introduction.....	143
7.5.2	Minimum Requirements for inter-band EN-DC.....	143
7.5.2.1	Minimum Requirements for inter-band synchronous EN-DC.....	143

7.5.3	Minimum Requirements for intra-band EN-DC	144
7.5.4	Minimum Requirements for NR Carrier Aggregation	144
7.5.5	Minimum Requirements for inter-band NE-DC	145
7.5.5.1	Minimum Requirements for inter-band synchronous NE-DC	145
7.5.6	Minimum Requirements for inter-band NR DC	145
7.6	Maximum Receive Timing Difference.....	146
7.6.1	Introduction.....	146
7.6.2	Minimum Requirements for inter-band EN-DC	146
7.6.2.1	Minimum Requirements for inter-band synchronous EN-DC	147
7.6.3	Minimum Requirements for intra-band EN-DC	147
7.6.4	Minimum Requirements for NR Carrier Aggregation	148
7.6.5	Minimum Requirements for inter-band NE-DC	148
7.6.5.1	Minimum Requirements for inter-band synchronous NE-DC	149
7.6.6	Minimum Requirements for inter-band NR DC	149
7.7	<i>deriveSSB-IndexFromCell</i> tolerance	150
7.7.1	Minimum requirements.....	150
7.8	Void.....	150
8	Signalling characteristics.....	150
8.1	Radio Link Monitoring.....	150
8.1.1	Introduction.....	150
8.1.2	Requirements for SSB based radio link monitoring	151
8.1.2.1	Introduction.....	151
8.1.2.2	Minimum requirement	152
8.1.2.3	Measurement restrictions for SSB based RLM.....	153
8.1.3	Requirements for CSI-RS based radio link monitoring	154
8.1.3.1	Introduction.....	154
8.1.3.2	Minimum requirement	155
8.1.3.3	Measurement restrictions for CSI-RS based RLM.....	157
8.1.4	Minimum requirement at transitions.....	157
8.1.5	Minimum requirement for UE turning off the transmitter	158
8.1.6	Minimum requirement for L1 indication	158
8.1.7	Scheduling availability of UE during radio link monitoring.....	158
8.1.7.1	Scheduling availability of UE performing radio link monitoring with a same subcarrier spacing as PDSCH/PDCCH on FR1	158
8.1.7.2	Scheduling availability of UE performing radio link monitoring with a different subcarrier spacing than PDSCH/PDCCH on FR1	158
8.1.7.3	Scheduling availability of UE performing radio link monitoring on FR2.....	159
8.1.7.4	Scheduling availability of UE performing radio link monitoring on FR1 or FR2 in case of FR1-FR2 inter-band CA and NR-DC.....	159
8.1A	Radio Link Monitoring with CCA on Target Frequency	159
8.1A.1	Introduction.....	159
8.1A.2	Requirements for SSB Based Radio Link Monitoring.....	160
8.1A.2.1	Introduction.....	160
8.1A.2.2	Minimum Requirement	161
8.1A.3	Minimum requirement at transitions.....	162
8.1A.4	Minimum requirement for UE turning off the transmitter	162
8.1A.5	Minimum requirement for L1 indication	163
8.1A.6	Scheduling availability of UE during radio link monitoring.....	163
8.1A.6.1	Scheduling availability of UE performing radio link monitoring with the same subcarrier spacing as PDSCH/PDCCH	163
8.1A.6.2	Scheduling availability of UE performing radio link monitoring with a different subcarrier spacing than PDSCH/PDCCH	163
8.2	Interruption.....	163
8.2.1	EN-DC Interruption	163
8.2.1.1	Introduction.....	163
8.2.1.2	Requirements	164
8.2.1.2.1	Interruptions at transitions between active and non-active during DRX	164
8.2.1.2.2	Interruptions at transitions from non-DRX to DRX	165
8.2.1.2.3	Interruptions at SCell addition/release.....	165
8.2.1.2.4	Interruptions at SCell activation/deactivation.....	166
8.2.1.2.5	Interruptions during measurements on SCC.....	167

8.2.1.2.6	Interruptions at UL carrier RRC reconfiguration	169
8.2.1.2.7	Interruptions due to Active BWP switching Requirement	169
8.2.1.2.8	Interruptions at direct SCell activation and hibernation	170
8.2.1.2.9	Interruptions at SCell hibernation.....	171
8.2.1.2.10	Interruptions at SCell activation/deactivation with multiple downlink SCells	171
8.2.1.2.11	Interruptions due to UE-specific CBW change	171
8.2.1.2.12	Interruptions at NR SRS carrier based switching	172
8.2.1.2.13	Interruptions at E-UTRA SRS carrier based switching	173
8.2.1.2.14	DL Interruptions at switching between two uplink carriers.....	174
8.2.1.2.15	Interruptions due to SCell dormancy.....	174
8.2.1.2.16	Interruptions when identifying CGI of an NR cell with autonomous gaps.....	175
8.2.1.2.17	Interruptions when identifying CGI of an E-UTRA cell with autonomous gaps	175
8.2.2	SA: Interruptions with Standalone NR Carrier Aggregation	176
8.2.2.1	Introduction.....	176
8.2.2.2	Requirements	177
8.2.2.2.1	Interruptions at SCell addition/release.....	177
8.2.2.2.2	Interruptions at SCell activation/deactivation.....	178
8.2.2.2.3	Interruptions during measurements on deactivated SCC.....	178
8.2.2.2.4	Interruptions at UL carrier RRC reconfiguration	179
8.2.2.2.5	Interruptions due to Active BWP switching Requirement	179
8.2.2.2.6	Interruptions at inter-frequency SFTD measurement	180
8.2.2.2.7	Interruptions at SCell activation/deactivation with multiple downlink SCells	181
8.2.2.2.8	Interruptions due to UE-specific CBW change	182
8.2.2.2.9	Interruptions at NR SRS carrier based switching	182
8.2.2.2.10	DL Interruptions at UE switching between two uplink carriers	183
8.2.2.2.11	Interruptions at direct SCell activation.....	184
8.2.2.2.12	Interruptions due to SCell dormancy.....	184
8.2.2.2.13	Interruptions at transitions between active and non-active during DRX	184
8.2.2.2.14	Interruptions when identifying CGI of an NR cell with autonomous gaps.....	184
8.2.2.2.15	Interruptions when identifying CGI of an E-UTRA cell with autonomous gaps	185
8.2.3	NE-DC Interruptions.....	186
8.2.3.1	Introduction.....	186
8.2.3.2	Requirements	186
8.2.3.2.1	Interruptions at transitions between active and non-active during DRX	186
8.2.3.2.2	Interruptions at transitions from non-DRX to DRX	187
8.2.3.2.3	Interruptions at PSCell/SCell addition/release	187
8.2.3.2.4	Interruptions at SCell activation/deactivation.....	188
8.2.3.2.5	Interruptions during measurements on SCC.....	189
8.2.3.2.6	Interruptions at UL carrier RRC reconfiguration	190
8.2.3.2.7	Interruptions due to Active BWP switching Requirement	190
8.2.3.2.8	Interruptions at direct SCell activation and hibernation	191
8.2.3.2.9	Interruptions at SCell hibernation.....	191
8.2.3.2.10	Interruptions at SCell activation/deactivation with multiple downlink SCells	191
8.2.3.2.11	Interruptions at NR SRS carrier based switching	192
8.2.3.2.12	Interruptions at E-UTRA SRS carrier based switching	193
8.2.3.2.13	Interruptions due to SCell dormancy.....	194
8.2.3.2.14	Interruptions when identifying CGI of an NR cell with autonomous gaps.....	194
8.2.3.2.15	Interruptions when identifying CGI of an E-UTRA cell with autonomous gaps	195
8.2.3.2.16	Interruptions due to UE-specific CBW change	195
8.2.4	NR-DC: Interruptions	196
8.2.4.1	Introduction.....	196
8.2.4.2	Requirements	196
8.2.4.2.1	Interruptions at PSCell/SCell addition/release	196
8.2.4.2.3	Interruptions during measurements on SCC.....	198
8.2.4.2.4	Interruptions at UL carrier RRC reconfiguration	198
8.2.4.2.5	Interruptions due to Active BWP switching Requirement	198
8.2.4.2.6	Interruptions at transitions between active and non-active during DRX	199
8.2.4.2.7	Interruptions at transitions from non-DRX to DRX	199
8.2.4.2.8	Interruptions at SCell activation/deactivation with multiple downlink SCells	199
8.2.4.2.9	Interruptions at NR SRS carrier based switching	199
8.2.4.2.10	Interruptions at direct SCell activation.....	201
8.2.4.2.11	Interruptions when identifying CGI of an NR cell with autonomous gaps.....	201

8.2.4.2.12	Interruptions when identifying CGI of an E-UTRA cell with autonomous gaps	202
8.2.4.2.13	Interruptions due to SCell dormancy	202
8.2.4.2.14	Interruptions due to UE-specific CBW change	203
8.2.4.2A	Void.....	203
8.2.4.2A.1	Void.....	203
8.2.4.2A.2	Void.....	203
8.2.4.2A.3	Void.....	203
8.3	SCell Activation and Deactivation Delay	203
8.3.1	Introduction.....	203
8.3.2	SCell Activation Delay Requirement for Deactivated SCell	203
8.3.3	SCell Deactivation Delay Requirement for Activated SCell	207
8.3.4	Direct SCell Activation at SCell addition.....	208
8.3.5	Direct SCell Activation at Handover	209
8.3.7	SCell Activation Delay Requirement for Deactivated SCell with Multiple Downlink SCells	211
8.3.8	SCell Deactivation Delay Requirement for Activated SCell with Multiple Downlink SCells	215
8.3.9	Direct SCell Activation of Multiple Downlink SCells at SCell addition.....	215
8.3.10	Direct SCell Activation of Multiple Downlink SCells at Handover.....	217
8.3A	SCell Activation and Deactivation Delay in Carriers with CCA.....	218
8.3A.1	Introduction.....	218
8.3A.2	SCell Activation Delay Requirement for Deactivated SCell	218
8.3A.3	SCell Deactivation Delay Requirement for Activated SCell	221
8.4	UE UL carrier RRC reconfiguration delay.....	221
8.4.1	Introduction.....	221
8.4.2	UE UL carrier configuration delay requirement	222
8.4.3	UE UL carrier deconfiguration delay requirement	222
8.5	Link Recovery Procedures	222
8.5.1	Introduction.....	222
8.5.2	Requirements for SSB based beam failure detection.....	223
8.5.2.1	Introduction.....	223
8.5.2.2	Minimum requirement	223
8.5.2.3	Measurement restriction for SSB based beam failure detection.....	225
8.5.3	Requirements for CSI-RS based beam failure detection.....	225
8.5.3.1	Introduction.....	225
8.5.3.2	Minimum requirement	226
8.5.3.3	Measurement restrictions for CSI-RS beam failure detection.....	228
8.5.4	Minimum requirement for L1 indication	229
8.5.5	Requirements for SSB based candidate beam detection	229
8.5.5.1	Introduction.....	229
8.5.5.2	Minimum requirement	229
8.5.5.3	Measurement restriction for SSB based candidate beam detection.....	231
8.5.6	Requirements for CSI-RS based candidate beam detection.....	232
8.5.6.1	Introduction.....	232
8.5.6.2	Minimum requirement	232
8.5.6.3	Measurement restriction for CSI-RS based candidate beam detection	234
8.5.7	Scheduling availability of UE during beam failure detection	235
8.5.7.1	Scheduling availability of UE performing beam failure detection with a same subcarrier spacing as PDSCH/PDCCH on FR1	235
8.5.7.2	Scheduling availability of UE performing beam failure detection with a different subcarrier spacing than PDSCH/PDCCH on FR1	235
8.5.7.3	Scheduling availability of UE performing beam failure detection on FR2	235
8.5.7.4	Scheduling availability of UE performing beam failure detection on FR1 or FR2 in case of FR1-FR2 inter-band CA and NR DC	236
8.5.8	Scheduling availability of UE during candidate beam detection	236
8.5.8.1	Scheduling availability of UE performing L1-RSRP measurement with a same subcarrier spacing as PDSCH/PDCCH on FR1	236
8.5.8.2	Scheduling availability of UE performing L1-RSRP measurement with a different subcarrier spacing than PDSCH/PDCCH on FR1	236
8.5.8.3	Scheduling availability of UE performing L1-RSRP measurement on FR2	236
8.5.8.4	Scheduling availability of UE performing L1-RSRP measurement on FR1 or FR2 in case of FR1-FR2 inter-band CA and NR-DC.....	237
8.5.9	Requirements for Beam Failure Recovery in SCell.....	237
8.5.9.1	Introduction.....	237

8.5.9.2	Requirement	237
8.5.10	Minimum requirement at transitions for beam failure detection.....	238
8.5A	Link Recovery Procedures when CCA is used on target frequency	238
8.5A.1	Introduction.....	238
8.5A.2	Requirements for SSB based beam failure detection	239
8.5A.2.1	Introduction.....	239
8.5A.2.2	Minimum requirement	239
8.5A.2.3	Measurement restriction for SSB based beam failure detection.....	240
8.5A.4	Minimum requirement for L1 indication	240
8.5A.5	Requirements for SSB based candidate beam detection	240
8.5A.5.1	Introduction.....	240
8.5A.5.2	Minimum requirement	240
8.5A.5.3	Measurement restriction for SSB based candidate beam detection.....	241
8.5A.7	Scheduling availability of UE during beam failure detection	241
8.5A.7.1	Scheduling availability of UE performing beam failure detection with a same subcarrier spacing as PDSCH/PDCCH	241
8.5A.7.2	Scheduling availability of UE performing beam failure detection with a different subcarrier spacing than PDSCH/PDCCH	241
8.5A.8	Scheduling availability of UE during candidate beam detection	241
8.5A.8.1	Scheduling availability of UE performing L1-RSRP measurement with a same subcarrier spacing as PDSCH/PDCCH	242
8.5A.8.2	Scheduling availability of UE performing L1-RSRP measurement with a different subcarrier spacing than PDSCH/PDCCH	242
8.6	Active BWP switch delay.....	242
8.6.1	Introduction.....	242
8.6.2	DCI and timer based BWP switch delay on a single CC	242
8.6.2A	DCI based BWP switch delay on multiple CCs.....	243
8.6.2A.1	Simultaneous DCI based BWP switch delay on multiple CCs	243
8.6.2A.2	Non-simultaneous DCI based BWP switch delay on multiple CCs	245
8.6.2B	Timer based BWP switch delay on multiple CCs	245
8.6.2B.1	Simultaneous timer based BWP switch delay on multiple CCs	245
8.6.2B.2	Non-simultaneous timer based BWP switch delay on multiple CCs	246
8.6.3	RRC based BWP switch delay on a single CC	246
8.6.3A	RRC based BWP switch delay on multiple CCs.....	247
8.6.3A.1	Simultaneous RRC based BWP switch delay on multiple CCs	247
8.6.3A.2	Non-simultaneous RRC based BWP switch delay on multiple CCs	247
8.6.4	BWP switch delay on Consistent UL CCA recovery.....	248
8.7	Void.....	248
8.8	NE-DC: E-UTRAN PSCell Addition and Release Delay	248
8.8.1	Introduction.....	248
8.8.2	E-UTRAN PSCell Addition Delay Requirement.....	248
8.8.3	E-UTRAN PSCell Release Delay Requirement	249
8.9	NR-DC: PSCell Addition and Release Delay.....	249
8.9.1	Introduction.....	249
8.9.2	PSCell Addition Delay Requirement	249
8.9.3	PSCell Release Delay Requirement.....	250
8.10	Active TCI state switching delay	250
8.10.4	DCI based TCI state switch delay.....	252
8.10.5	RRC based TCI state switch delay.....	252
8.10.6	Active TCI state list update delay	252
8.10A	Active TCI state switching delay with CCA	253
8.10A.1	Introduction.....	253
8.10A.2	Known conditions for TCI state.....	253
8.10A.3	MAC-CE based TCI state switch delay	253
8.10A.4	DCI based TCI state switch delay.....	254
8.10A.5	RRC based TCI state switch delay.....	254
8.10A.6	Active TCI state list update delay	255
8.11	PSCell Change.....	255
8.11A	void.....	256
8.11B	Conditional PSCell Change	256
8.11B.1	Introduction.....	256
8.11B.2	Conditional PSCell Change delay.....	256

8.11B.2.1	Measurement time	256
8.12	Uplink spatial relation switch delay	257
8.12.1	Introduction.....	257
8.12.2	Known conditions for spatial relation when associated with DL-RS	257
8.12.3	MAC-CE based spatial relation switch delay	257
8.12.4	DCI based spatial relation switch delay.....	258
8.12.5	RRC based spatial relation switch delay.....	258
8.13	UE-specific CBW change.....	259
8.13.1	Introduction.....	259
8.13.2	UE-specific CBW change delay	259
8.14	Pathloss reference signal switching delay.....	259
8.14.1	Introduction.....	259
8.14.2	Known conditions for pathloss reference signal	259
8.14.3	MAC-CE based pathloss reference signal switch delay	260
9	Measurement Procedure	261
9.1	General measurement requirement.....	261
9.1.1	Introduction.....	261
9.1.2	Measurement gap.....	261
9.1.2.1	EN-DC: Measurement Gap Sharing.....	269
9.1.2.1a	SA: Measurement Gap Sharing.....	270
9.1.2.1b	NE-DC: Measurement Gap Sharing.....	271
9.1.2.1c	NR-DC: Measurement Gap Sharing	272
9.1.3	UE Measurement capability.....	273
9.1.3.1	EN-DC: Monitoring of multiple layers using gaps	273
9.1.3.1a	SA: Monitoring of multiple layers using gaps	273
9.1.3.1b	NE-DC: Monitoring of multiple layers using gaps	274
9.1.3.1c	NR-DC: Monitoring of multiple layers using gaps	274
9.1.3.2	EN-DC: Maximum allowed layers for multiple monitoring	275
9.1.3.2a	SA: Maximum allowed layers for multiple monitoring	276
9.1.3.2b	NE-DC: Maximum allowed layers for multiple monitoring	276
9.1.3.2c	NR-DC: Maximum allowed layers for multiple monitoring	277
9.1A.3.2	Void.....	278
9.1.3A	UE Measurement capability under operation mode with CCA.....	278
9.1.3A.1	EN-DC: Monitoring of multiple layers using gaps under CCA	278
9.1.3A.1A	SA: Monitoring of multiple layers using gaps under CCA	278
9.1.3A.2	EN-DC: Maximum allowed layers for multiple monitoring under CCA	278
9.1A.3.2a	Void.....	279
9.1.3A.2A	SA: Maximum allowed layers for multiple monitoring under CCA	279
9.1.4	Capabilities for Support of Event Triggering and Reporting Criteria.....	279
9.1.4.1	Introduction.....	279
9.1.4.2	Requirements	279
9.1.5	Carrier-specific scaling factor.....	282
9.1.5.1	Monitoring of multiple layers outside gaps.....	282
9.1.5.1.1	EN-DC mode: carrier-specific scaling factor for SSB-based, CSI-RS based L3 measurements and RSSI and channel occupancy measurements performed outside gaps.....	284
9.1.5.1.2	SA mode: carrier-specific scaling factor for SSB-based, CSI-RS based L3 measurements and RSSI and channel occupancy measurements performed outside gaps.....	285
9.1.5.1.3	NR-DC mode: carrier-specific scaling factor for SSB-based and CSI-RS based L3 measurements performed outside gaps.....	286
9.1.5.1.4	NE-DC mode: carrier-specific scaling factor for SSB-based and CSI-RS based measurements performed outside gaps.....	286
9.1.5.2	Monitoring of multiple layers within gaps	287
9.1.5.2.1	EN-DC mode: carrier-specific scaling factor for SSB, CSI-RS-based L3 measurements and RSSI and channel occupancy measurements performed within gaps	288
9.1.5.2.2	SA mode: carrier-specific scaling factor for SSB, CSI-RS-based L3 measurements and RSSI and channel occupancy measurements performed within gaps	290
9.1.5.2.3	NE-DC: carrier-specific scaling factor for SSB-based and CSI-RS based L3 measurements performed within gaps	291
9.1.5.2.4	NR-DC: carrier-specific scaling factor for SSB-based and CSI-RS-based L3 measurements performed within gaps	293
9.1.5.2.5	SA mode: carrier-specific scaling factor for PRS-based measurements performed within gaps.....	295

9.1.5.2.6	NE-DC: carrier-specific scaling factor for PRS-based measurements performed within gaps.....	295
9.1.5.2.7	NR-DC: carrier-specific scaling factor for PRS-based measurements performed within gaps	296
9.1.6	Minimum requirement at transitions.....	296
9.2	NR intra-frequency measurements	296
9.2.1	Introduction.....	296
9.2.2	Requirements applicability	297
9.2.3	Number of cells and number of SSB	297
9.2.3.1	Requirements for FR1	297
9.2.3.2	Requirements for FR2	297
9.2.4	Measurement Reporting Requirements.....	298
9.2.4.1	Periodic Reporting	298
9.2.4.2	Event-triggered Periodic Reporting.....	298
9.2.4.3	Event Triggered Reporting.....	298
9.2.5	Intrafrequency measurements without measurement gaps.....	298
9.2.5.1	Intrafrequency cell identification	298
9.2.5.2	Measurement period.....	301
9.2.5.3	Scheduling availability of UE during intra-frequency measurements.....	303
9.2.5.3.1	Scheduling availability of UE performing measurements in TDD bands on FR1	303
9.2.5.3.2	Scheduling availability of UE performing measurements with a different subcarrier spacing than PDSCH/PDCCH on FR1	303
9.2.5.3.3	Scheduling availability of UE performing measurements on FR2	304
9.2.5.3.4	Scheduling availability of UE performing measurements on FR1 or FR2 in case of FR1-FR2 inter-band CA	304
9.2.5.4	SFTD Measurements between PCell and PSCell.....	305
9.2.5.4.1	Introduction	305
9.2.5.4.2	SFTD Measurement delay.....	305
9.2.5.4.3	SFTD Measurement Reporting Delay	305
9.2.6	Intra-frequency measurements with measurement gaps	306
9.2.6.1	Void.....	306
9.2.6.2	Intra-frequency cell identification	306
9.2.6.3	Intrafrequency Measurement Period	307
9.2.A	NR intra-frequency measurements with CCA.....	308
9.2.A.1	Introduction.....	308
9.2.A.2	Requirements applicability	309
9.2.A.3	Number of cells and number of SSB	309
9.2.A.4	Measurement Reporting Requirements.....	309
9.2.A.5	Intra-frequency measurements without measurement gaps	310
9.2.A.5.2	Measurement period.....	312
9.2.A.5.3	Scheduling availability of UE during intra-frequency measurements.....	313
9.2.A.5.3.1	Scheduling availability of UE performing measurements in TDD bands.....	313
9.2.A.5.3.2	Scheduling availability of UE performing measurements with a different subcarrier spacing than PDSCH/PDCCH.....	314
9.2.A.6	Intra-frequency measurements with measurement gaps	314
9.2.A.6.1	Intra-frequency cell identification	314
9.2.A.6.2	Intra-frequency Measurement Period.....	315
9.2.A.7	Intra-frequency RSSI and Channel occupancy measurements.....	316
9.2.A.7.1	Intra-frequency RSSI measurements.....	316
9.2.A.7.2	Intra-frequency Channel occupancy measurements.....	317
9.2.A.7.3	Scheduling restriction during RSSI and Channel Occupancy measurements	318
9.3	NR inter-frequency measurements	318
9.3.1	Introduction.....	318
9.3.2	Requirements applicability	319
9.3.2.1	Void.....	319
9.3.2.2	Void.....	319
9.3.3	Number of cells and number of SSB	319
9.3.3.1	Requirements for FR1	319
9.3.3.2	Requirements for FR2	319
9.3.4	Inter-frequency measurement with measurement gaps.....	319
9.3.4.1	Void.....	321
9.3.4.2	Void.....	321
9.3.5	Inter-frequency measurements.....	321
9.3.5.1	Void.....	321

9.3.5.2	Void.....	321
9.3.5.3	Void.....	321
9.3.6	Inter-frequency measurements reporting requirements.....	321
9.3.6.1	Periodic Reporting	321
9.3.6.2	Event-triggered Periodic Reporting.....	321
9.3.6.3	Event-triggered Reporting.....	322
9.3.7	Void.....	322
9.3.8	Inter-frequency SFTD measurement requirements.....	322
9.3.8.1	Introduction.....	322
9.3.8.2	SFTD Measurement delay.....	322
9.3.8.3	SFTD Measurement reporting delay.....	323
9.3.9	Inter frequency measurements without measurement gaps.....	324
9.3.9.1	Inter frequency Cell identification	324
9.3.9.2	Measurement period.....	325
9.3.9.3	Scheduling availability of UE during inter-frequency measurements.....	326
9.3.9.3.1	Scheduling availability of UE performing measurements in TDD bands on FR1	326
9.3.9.3.2	Scheduling availability of UE performing measurements with a different subcarrier spacing than PDSCH/PDCCH on FR1	326
9.3.9.3.3	Scheduling availability of UE performing measurements on FR2	327
9.3.9.3.4	Scheduling availability of UE performing measurements on FR1 or FR2 in case of FR1-FR2 inter-band CA	327
9.3A	NR inter-frequency measurements in carrier frequencies with CCA.....	327
9.3A.1	Introduction.....	327
9.3A.2	Requirements applicability	328
9.3A.3	Number of cells and number of SSB	328
9.3A.3.1	Requirements	328
9.3A.4	Inter-frequency cell identification.....	328
9.3A.5	Inter-frequency measurements.....	330
9.3A.6	NR Inter-frequency measurements reporting requirements	330
9.3A.6.1	Periodic Reporting	330
9.3A.6.2	Event-triggered Periodic Reporting.....	330
9.3A.6.3	Event-triggered Reporting.....	330
9.3A.8	Inter-frequency RSSI measurements	331
9.3A.9	Inter-frequency channel occupancy measurements	331
9.4	Inter-RAT measurements	332
9.4.1	Introduction.....	332
9.4.2	NR – E-UTRAN FDD measurements	333
9.4.2.1	Introduction.....	333
9.4.2.2	Requirements when no DRX is used.....	334
9.4.2.3	Requirements when DRX is used.....	334
9.4.2.4	Measurement reporting requirements.....	335
9.4.2.4.1	Periodic Reporting.....	335
9.4.2.4.2	Event-Triggered Periodic Reporting.....	335
9.4.2.4.3	Event-Triggered Reporting.....	335
9.4.3	NR – E-UTRAN TDD measurements	336
9.4.3.1	Introduction.....	336
9.4.3.2	Requirements when no DRX is used.....	336
9.4.3.3	Requirements when DRX is used.....	337
9.4.3.4	Measurement reporting requirements.....	338
9.4.3.4.1	Periodic Reporting.....	338
9.4.3.4.2	Event-Triggered Periodic Reporting.....	338
9.4.3.4.3	Event-Triggered Reporting.....	338
9.4.4	Inter-RAT RSTD measurements.....	339
9.4.4.1	NR – E-UTRAN FDD RSTD measurements.....	339
9.4.4.1.1	Introduction	339
9.4.4.1.2	Requirements	340
9.4.4.2	NR – E-UTRAN TDD RSTD measurements	342
9.4.4.2.1	Introduction	342
9.4.4.2.2	Requirements	343
9.4.5	Inter-RAT E-CID measurements	346
9.4.5.1	NR–E-UTRAN FDD E-CID RSRP and RSRQ measurements	346
9.4.5.1.1	Introduction	346

9.4.5.1.2	Requirements	346
9.4.5.1.3	Measurement Reporting Delay	347
9.4.5.2	NR–E-UTRAN TDD E-CID RSRP and RSRQ measurements	347
9.4.5.2.1	Introduction	347
9.4.5.2.2	Requirements	347
9.4.5.2.3	Measurement Reporting Delay	347
9.4.6	NR – UTRAN FDD measurements	347
9.4.6.1	Introduction	347
9.4.6.2	Requirements when no DRX is used	347
9.4.6.3	Requirements when DRX is used	349
9.4.7	NR – E-UTRAN measurements with autonomous gaps	350
9.4.7.1	CGI identification of an E-UTRA cell with autonomous gaps	350
9.4.7.2	CGI reporting delay	351
9.5	L1-RSRP measurements for Reporting	351
9.5.1	Introduction	351
9.5.2	Requirements applicability	351
9.5.3	Measurement Reporting Requirements	352
9.5.3.1	Periodic Reporting	352
9.5.3.2	Semi-Persistent Reporting	352
9.5.3.3	Aperiodic Reporting	352
9.5.4	L1-RSRP measurement requirements	352
9.5.4.1	SSB based L1-RSRP Reporting	352
9.5.4.2	CSI-RS based L1-RSRP Reporting	354
9.5.4A	Void	357
9.5.4A.1	Void	357
9.5.5	Measurement restriction for CSI-RS and SSB for L1-RSRP measurement	357
9.5.5.1	Measurement restriction for SSB based L1-RSRP	357
9.5.5.2	Measurement restriction for CSI-RS based L1-RSRP	357
9.5.6	Scheduling availability of UE during L1-RSRP measurement	358
9.5.6.1	Scheduling availability of UE performing L1-RSRP measurement with a same subcarrier spacing as PDSCH/PDCCH on FR1	358
9.5.6.2	Scheduling availability of UE performing L1-RSRP measurement with a different subcarrier spacing than PDSCH/PDCCH on FR1	358
9.5.6.3	Scheduling availability of UE performing L1-RSRP measurement on FR2	359
9.5.6.4	Scheduling availability of UE performing L1-RSRP measurement on FR1 or FR2 in case of FR1-FR2 inter-band CA	359
9.5A	L1-RSRP measurements for Reporting under CCA	360
9.5A.1	Introduction	360
9.5A.2	Requirements applicability	360
9.5A.3	Measurement Reporting Requirements	360
9.5A.3.1	Periodic Reporting	360
9.5A.3.2	Semi-Persistent Reporting	361
9.5A.3.3	Aperiodic Reporting	361
9.5A.4	L1-RSRP measurement requirements	361
9.5A.4.1	SSB based L1-RSRP Reporting	361
9.5A.5	Measurement restriction for L1-RSRP measurement	362
9.5A.5.1	Measurement restriction for SSB based L1-RSRP	362
9.5A.6	Scheduling availability of UE during L1-RSRP measurement	362
9.5A.6.1	Scheduling availability of UE performing L1-RSRP measurement with a same subcarrier spacing as PDSCH/PDCCH	362
9.5A.6.2	Scheduling availability of UE performing L1-RSRP measurement with a different subcarrier spacing than PDSCH/PDCCH	363
9.5A.6.3	Scheduling availability of UE performing L1-RSRP measurement in case of FR1-FR2 inter-band CA	363
9.6	NE-DC: Measurements	363
9.6.1	Introduction	363
9.6.2	SFTD Measurements	363
9.6.2.1	Introduction	363
9.6.2.2	SFTD Measurement requirements	363
9.7	Cross Link Interference measurements	364
9.7.1	Introduction	364
9.7.2	SRS-RSRP measurements	364