

# ETSI TS 138 300 V19.2.0 (2026-04)



TECHNICAL SPECIFICATION

**5G;  
NR;  
NR and NG-RAN Overall description;  
Stage-2  
(3GPP TS 38.300 version 19.2.0 Release 19)**



---

**Reference**

RTS/TSGR-0238300vj20

---

**Keywords**

5G

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° w061004871

---

**Important notice**

The present document can be downloaded from the  
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed, this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our [Coordinated Vulnerability Disclosure \(CVD\)](#) program.

---

**Notice of disclaimer & limitation of liability**

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2026.  
All rights reserved.

---

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

---

# Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found at [3GPP to ETSI numbering cross-referencing](#).

---

# Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

# Contents

|   |    |
|---|----|
| Intellectual Property Rights .....                | 2  |
| Legal Notice .....                                | 2  |
| Modal verbs terminology.....                      | 2  |
| Foreword.....                                     | 14 |
| 1 Scope .....                                     | 15 |
| 2 References .....                                | 15 |
| 3 Abbreviations and Definitions.....              | 17 |
| 3.1 Abbreviations .....                           | 17 |
| 3.2 Definitions .....                             | 22 |
| 4 Overall Architecture and Functional Split.....  | 27 |
| 4.1 Overall Architecture .....                    | 27 |
| 4.2 Functional Split .....                        | 28 |
| 4.3 Network Interfaces .....                      | 30 |
| 4.3.1 NG Interface .....                          | 30 |
| 4.3.1.1 NG User Plane .....                       | 30 |
| 4.3.1.2 NG Control Plane.....                     | 31 |
| 4.3.2 Xn Interface .....                          | 31 |
| 4.3.2.1 Xn User Plane .....                       | 31 |
| 4.3.2.2 Xn Control Plane.....                     | 32 |
| 4.4 Radio Protocol Architecture .....             | 33 |
| 4.4.1 User Plane.....                             | 33 |
| 4.4.2 Control Plane .....                         | 33 |
| 4.5 Multi-Radio Dual Connectivity.....            | 33 |
| 4.6 Radio Access Network Sharing.....             | 34 |
| 4.7 Integrated Access and Backhaul.....           | 34 |
| 4.7.1 Architecture .....                          | 34 |
| 4.7.2 Protocol Stacks .....                       | 35 |
| 4.7.3 User-plane Aspects .....                    | 36 |
| 4.7.3.1 Backhaul transport .....                  | 36 |
| 4.7.3.2 Flow and Congestion Control .....         | 37 |
| 4.7.3.3 Uplink Scheduling Latency.....            | 37 |
| 4.7.4 Signalling procedures .....                 | 37 |
| 4.7.4.1 IAB-node Integration .....                | 37 |
| 4.7.4.2 IAB-node Migration.....                   | 38 |
| 4.7.4.3 Topological Redundancy .....              | 38 |
| 4.7.4.4 Backhaul RLF Recovery .....               | 38 |
| 4.7.4.5 OTA timing synchronization.....           | 38 |
| 4.7.4.6 Inter node discovery.....                 | 39 |
| 4.7.5 Mobile IAB .....                            | 39 |
| 4.7.5.1 General .....                             | 39 |
| 4.7.5.2 Void.....                                 | 39 |
| 4.8 Non-Public Networks .....                     | 39 |
| 4.9 Network-Controlled Repeaters .....            | 40 |
| 4.9.1 Architecture .....                          | 40 |
| 4.9.2 Capabilities .....                          | 40 |
| 4.9.3 Signalling procedures .....                 | 40 |
| 4.9.4 OAM aspects .....                           | 41 |
| 4.9.5 Network-controlled repeater management..... | 41 |
| 4.10 Support of NR Femto nodes.....               | 42 |
| 4.10.1 Architecture .....                         | 42 |
| 4.10.2 Functional Split.....                      | 43 |
| 4.10.2.1 NR Femto node .....                      | 43 |
| 4.10.2.2 AMF.....                                 | 44 |
| 4.10.2.3 NR Femto GW .....                        | 44 |

|          |   |    |
|----------|---|----|
| 4.10.3   | Interfaces.....   | 45 |
| 4.10.3.1 | Protocol Stack for NG User Plane.....                               | 45 |
| 4.10.3.2 | Protocol Stacks for NG Control Plane .....                          | 46 |
| 4.10.4   | Access Control.....   | 46 |
| 4.11     | Wireless Access Backhaul.....                                       | 46 |
| 5        | Physical Layer .....  | 46 |
| 5.1      | Waveform, numerology and frame structure.....                       | 46 |
| 5.2      | Downlink.....   | 47 |
| 5.2.1    | Downlink transmission scheme .....                                  | 47 |
| 5.2.2    | Physical-layer processing for physical downlink shared channel..... | 48 |
| 5.2.3    | Physical downlink control channels.....                             | 48 |
| 5.2.4    | Synchronization signal and PBCH block.....                          | 49 |
| 5.2.5    | Physical layer procedures .....                                     | 50 |
| 5.2.5.1  | Link adaptation .....   | 50 |
| 5.2.5.2  | Power Control .....   | 50 |
| 5.2.5.3  | Cell search.....  | 50 |
| 5.2.5.4  | HARQ .....  | 51 |
| 5.2.5.5  | Reception of SIB1 .....   | 51 |
| 5.2.6    | Downlink Reference Signals and Measurements for Positioning.....    | 51 |
| 5.3      | Uplink.....   | 51 |
| 5.3.1    | Uplink transmission scheme .....                                    | 51 |
| 5.3.2    | Physical-layer processing for physical uplink shared channel.....   | 52 |
| 5.3.3    | Physical uplink control channel.....                                | 52 |
| 5.3.4    | Random access.....  | 54 |
| 5.3.5    | Physical layer procedures .....                                     | 54 |
| 5.3.5.1  | Link adaptation .....   | 54 |
| 5.3.5.2  | Uplink Power control .....  | 54 |
| 5.3.5.3  | Uplink timing control.....  | 54 |
| 5.3.5.4  | HARQ .....  | 55 |
| 5.3.5.5  | Prioritization of overlapping transmissions.....                    | 55 |
| 5.3.6    | Uplink Reference Signals and Measurements for Positioning.....      | 55 |
| 5.4      | Carrier aggregation.....  | 55 |
| 5.4.1    | Carrier aggregation .....   | 55 |
| 5.4.2    | Supplementary Uplink .....  | 56 |
| 5.4.3    | Uplink Tx switching .....   | 56 |
| 5.4.4    | Low band carrier aggregation via switching.....                     | 56 |
| 5.5      | Transport Channels.....   | 56 |
| 5.6      | Access to Shared Spectrum .....                                     | 57 |
| 5.6.1    | Overview .....  | 57 |
| 5.6.2    | Channel Access Priority Classes.....                                | 58 |
| 5.7      | Sidelink .....  | 58 |
| 5.7.1    | General.....  | 58 |
| 5.7.2    | Sidelink resource allocation modes/schemes .....                    | 58 |
| 5.7.3    | Physical sidelink channels and signals.....                         | 58 |
| 5.7.4    | Physical layer procedures for sidelink .....                        | 59 |
| 5.7.4.1  | HARQ feedback.....  | 59 |
| 5.7.4.2  | Power Control .....   | 59 |
| 5.7.4.3  | CSI report.....   | 59 |
| 5.7.5    | Physical layer measurement definition .....                         | 59 |
| 5.7.6    | Sidelink Reference Signal and Measurements for Positioning .....    | 59 |
| 6        | Layer 2.....  | 60 |
| 6.1      | Overview .....  | 60 |
| 6.2      | MAC Sublayer.....   | 63 |
| 6.2.1    | Services and Functions .....  | 63 |
| 6.2.2    | Logical Channels .....  | 64 |
| 6.2.3    | Mapping to Transport Channels.....                                  | 64 |
| 6.2.4    | HARQ .....  | 64 |
| 6.3      | RLC Sublayer .....  | 64 |
| 6.3.1    | Transmission Modes .....  | 64 |
| 6.3.2    | Services and Functions .....  | 65 |

|           |   |     |
|-----------|---|-----|
| 6.3.3     | ARQ.....  | 65  |
| 6.4       | PDCP Sublayer.....  | 65  |
| 6.4.1     | Services and Functions .....  | 65  |
| 6.5       | SDAP Sublayer .....   | 66  |
| 6.6       | L2 Data Flow.....   | 66  |
| 6.7       | Carrier Aggregation.....  | 66  |
| 6.8       | Dual Connectivity.....  | 68  |
| 6.9       | Supplementary Uplink.....   | 68  |
| 6.10      | Bandwidth Adaptation.....   | 68  |
| 6.11      | Backhaul Adaptation Protocol Sublayer.....  | 69  |
| 6.11.1    | Services and Functions .....  | 69  |
| 6.11.2    | Traffic Mapping from Upper Layers to Layer-2.....   | 69  |
| 6.11.3    | Routing, BAP Header Rewriting and BH-RLC-channel Mapping on BAP sublayer .....                                  | 70  |
| 6.12      | Multiple Transmit/Receive Point Operation.....  | 72  |
| 6.12.0    | Overview .....  | 72  |
| 6.12.1    | Asymmetric DL single-TRP and UL multi-TRP .....   | 73  |
| 7         | RRC.....  | 73  |
| 7.1       | Services and Functions .....  | 73  |
| 7.2       | Protocol States.....  | 73  |
| 7.3       | System Information Handling .....   | 74  |
| 7.3.1     | Overview .....  | 74  |
| 7.3.2     | Scheduling .....  | 77  |
| 7.3.3     | SI Modification.....  | 77  |
| 7.4       | Access Control .....  | 77  |
| 7.5       | UE Capability Retrieval framework.....  | 78  |
| 7.6       | Transport of NAS Messages.....  | 78  |
| 7.7       | Carrier Aggregation.....  | 78  |
| 7.8       | Bandwidth Adaptation.....   | 78  |
| 7.9       | UE Assistance Information.....  | 79  |
| 7.10      | Segmentation of RRC messages.....   | 80  |
| 8         | NG Identities .....   | 80  |
| 8.1       | UE Identities.....  | 80  |
| 8.2       | Network Identities .....  | 81  |
| 8.3       | User Data Transport on the CN-RAN Interface .....   | 82  |
| 8.4       | NR sidelink communication, V2X sidelink communication and Ranging/Sidelink positioning related identities ..... | 82  |
| 9         | Mobility and State Transitions .....  | 83  |
| 9.1       | Overview .....  | 83  |
| 9.2       | Intra-NR .....  | 84  |
| 9.2.1     | Mobility in RRC_IDLE .....  | 84  |
| 9.2.1.1   | Cell Selection.....   | 84  |
| 9.2.1.2   | Cell Reselection .....  | 85  |
| 9.2.1.3   | State Transitions.....  | 85  |
| 9.2.2     | Mobility in RRC_INACTIVE.....   | 87  |
| 9.2.2.1   | Overview.....   | 87  |
| 9.2.2.2   | Cell Reselection .....  | 89  |
| 9.2.2.3   | RAN-Based Notification Area .....   | 89  |
| 9.2.2.4   | State Transitions.....  | 89  |
| 9.2.2.4.1 | UE triggered transition from RRC_INACTIVE to RRC_CONNECTED .....  | 89  |
| 9.2.2.4.2 | Network triggered transition from RRC_INACTIVE to RRC_CONNECTED .....   | 91  |
| 9.2.2.5   | RNA update.....   | 92  |
| 9.2.2.6   | Resume request responded with Release with Redirect, with UE context relocation .....                           | 94  |
| 9.2.3     | Mobility in RRC_CONNECTED .....   | 95  |
| 9.2.3.1   | Overview.....   | 95  |
| 9.2.3.2   | Handover.....   | 97  |
| 9.2.3.2.1 | C-Plane Handling .....  | 97  |
| 9.2.3.2.2 | U-Plane Handling .....  | 101 |
| 9.2.3.2.3 | Data Forwarding .....   | 103 |
| 9.2.3.3   | Re-establishment procedure .....  | 104 |
| 9.2.3.4   | Conditional Handover.....   | 105 |

|           |   |     |
|-----------|---|-----|
| 9.2.3.4.1 | General .....                                     | 105 |
| 9.2.3.4.2 | C-plane handling .....                            | 106 |
| 9.2.3.4.3 | U-plane handling .....                            | 108 |
| 9.2.3.4.4 | Data Forwarding .....                             | 108 |
| 9.2.3.5   | L1/L2 Triggered Mobility .....                    | 108 |
| 9.2.3.5.1 | General .....                                     | 108 |
| 9.2.3.5.2 | C-Plane Handling .....                            | 109 |
| 9.2.3.5.3 | U-Plane Handling .....                            | 115 |
| 9.2.3.6   | RACH-less handover .....                          | 115 |
| 9.2.3.7   | Conditional L1/L2 Triggered Mobility .....        | 115 |
| 9.2.3.7.1 | General .....                                     | 115 |
| 9.2.4     | Measurements .....                                | 117 |
| 9.2.5     | Paging .....                                      | 121 |
| 9.2.6     | Random Access Procedure .....                     | 124 |
| 9.2.7     | Radio Link Failure .....                          | 127 |
| 9.2.8     | Beam failure detection and recovery .....         | 129 |
| 9.2.9     | Timing Advance .....                              | 130 |
| 9.2.10    | Extended DRX for RRC_IDLE and RRC_INACTIVE .....  | 130 |
| 9.3       | Inter RAT .....                                   | 131 |
| 9.3.1     | NR-E-UTRA mobility: Intra 5GC .....               | 131 |
| 9.3.1.1   | Cell Reselection .....                            | 131 |
| 9.3.1.2   | Handover .....                                    | 131 |
| 9.3.1.3   | Measurements .....                                | 131 |
| 9.3.2     | NR-E-UTRA mobility: From 5GC to EPC .....         | 132 |
| 9.3.2.1   | Cell Reselection .....                            | 132 |
| 9.3.2.2   | Handover and redirection .....                    | 132 |
| 9.3.2.3   | Measurements .....                                | 132 |
| 9.3.2.4   | Data Forwarding for the Control Plane .....       | 132 |
| 9.3.2.5   | Data Forwarding for the User Plane .....          | 133 |
| 9.3.3     | NR-E-UTRA mobility: From EPC to 5GC .....         | 133 |
| 9.3.3.1   | Data Forwarding for the Control Plane .....       | 133 |
| 9.3.3.2   | Data Forwarding for the User Plane .....          | 134 |
| 9.3.4     | NR-UTRA mobility .....                            | 134 |
| 9.3.4.1   | Handover with SRVCC operation .....               | 134 |
| 9.3.4.2   | Measurements .....                                | 135 |
| 9.4       | Roaming and Access Restrictions .....             | 135 |
| 10        | Scheduling .....                                  | 136 |
| 10.1      | Basic Scheduler Operation .....                   | 136 |
| 10.2      | Downlink Scheduling .....                         | 136 |
| 10.3      | Uplink Scheduling .....                           | 137 |
| 10.4      | Measurements to Support Scheduler Operation ..... | 138 |
| 10.5      | Rate Control .....                                | 138 |
| 10.5.1    | Downlink .....                                    | 138 |
| 10.5.2    | Uplink .....                                      | 138 |
| 10.6      | Activation/Deactivation Mechanism .....           | 139 |
| 10.7      | E-UTRA-NR Cell Resource Coordination .....        | 140 |
| 10.8      | Cross Carrier Scheduling .....                    | 140 |
| 10.9      | IAB Resource Configuration .....                  | 140 |
| 10.10     | Autonomous Denial for IDC .....                   | 141 |
| 10.11     | Multi-cell scheduling by a single DCI .....       | 141 |
| 11        | UE Power Saving .....                             | 141 |
| 12        | QoS .....   | 144 |
| 12.1      | Overview .....                                    | 144 |
| 12.2      | Explicit Congestion Notification .....            | 147 |
| 13        | Security .....                                    | 147 |
| 13.1      | Overview and Principles .....                     | 147 |
| 13.2      | Security Termination Points .....                 | 149 |
| 13.3      | State Transitions and Mobility .....              | 149 |
| 14        | UE Capabilities .....                             | 150 |

|            |   |     |
|------------|---|-----|
| 15         | Self-Configuration and Self-Optimisation .....                              | 151 |
| 15.1       | Definitions .....   | 151 |
| 15.2       | Void.....   | 151 |
| 15.3       | Self-configuration.....   | 151 |
| 15.3.1     | Dynamic configuration of the NG-C interface.....                            | 151 |
| 15.3.1.1   | Prerequisites .....   | 151 |
| 15.3.1.2   | SCTP initialization .....   | 151 |
| 15.3.1.3   | Application layer initialization.....                                       | 151 |
| 15.3.2     | Dynamic Configuration of the Xn interface .....                             | 152 |
| 15.3.2.1   | Prerequisites .....   | 152 |
| 15.3.2.2   | SCTP initialization .....   | 152 |
| 15.3.2.3   | Application layer initialization.....                                       | 152 |
| 15.3.3     | Automatic Neighbour Cell Relation Function .....                            | 152 |
| 15.3.3.1   | General .....   | 152 |
| 15.3.3.2   | Intra-system Automatic Neighbour Cell Relation Function.....                | 153 |
| 15.3.3.3   | Void.....   | 154 |
| 15.3.3.4   | Void.....   | 154 |
| 15.3.3.5   | Inter-system Automatic Neighbour Cell Relation Function.....                | 154 |
| 15.3.4     | Xn-C TNL address discovery .....  | 155 |
| 15.4       | Support for Energy Saving .....   | 156 |
| 15.4.1     | General.....  | 156 |
| 15.4.2     | Solution description .....  | 156 |
| 15.4.2.1   | Intra-system energy saving .....  | 156 |
| 15.4.2.2   | Inter-system energy saving .....  | 156 |
| 15.4.2.3   | Cell DTX/DRX .....  | 157 |
| 15.4.2.4   | Conditional Handover .....  | 157 |
| 15.4.2.5   | Camping Restrictions .....  | 157 |
| 15.4.2.6   | SSB-less SCell .....  | 157 |
| 15.4.2.7   | Spatial and power domain adaptation .....                                   | 158 |
| 15.4.2.8   | On-demand SSB SCell.....  | 158 |
| 15.4.2.9   | On-demand SIB1.....   | 158 |
| 15.4.2.10  | Common signal/channel transmissions adaptation.....                         | 158 |
| 15.4.3     | O&M requirements.....   | 158 |
| 15.5       | Self-optimisation .....   | 159 |
| 15.5.1     | Support for Mobility Load Balancing.....                                    | 159 |
| 15.5.1.1   | General .....   | 159 |
| 15.5.1.2   | Load reporting for intra-RAT and intra-system inter-RAT load balancing..... | 159 |
| 15.5.1.3   | Load balancing action based on handovers .....                              | 160 |
| 15.5.1.4   | Adapting handover and/or reselection configuration .....                    | 160 |
| 15.5.1.5   | Load reporting for inter-system load balancing .....                        | 160 |
| 15.5.2     | Support for Mobility Robustness Optimization .....                          | 160 |
| 15.5.2.1   | General .....   | 160 |
| 15.5.2.2   | Connection failure .....  | 161 |
| 15.5.2.2.1 | General .....   | 161 |
| 15.5.2.2.2 | Connection failure due to intra-system mobility .....                       | 161 |
| 15.5.2.2.3 | Connection failure due to inter-system mobility .....                       | 163 |
| 15.5.2.3   | Inter-system Unnecessary HO.....  | 164 |
| 15.5.2.4   | Inter-system Ping-pong .....  | 164 |
| 15.5.2.5   | O&M Requirements .....  | 165 |
| 15.5.2.6   | PSCell addition/change failure .....  | 165 |
| 15.5.2.7   | Successful HO.....  | 165 |
| 15.5.2.8   | Successful PSCell Addition/Change Report .....                              | 166 |
| 15.5.3     | Support for RACH Optimization .....   | 166 |
| 15.5.4     | UE History Information .....  | 166 |
| 15.5.5     | Support for Coverage and Capacity Optimisation .....                        | 167 |
| 15.5.5.1   | General .....   | 167 |
| 15.5.5.2   | OAM requirements.....   | 167 |
| 15.5.5.3   | Dynamic coverage configuration changes .....                                | 167 |
| 15.5.6     | Support for PCI Optimisation .....  | 167 |
| 15.5.6.1   | Centralized PCI Assignment .....  | 167 |
| 15.5.6.2   | Distributed PCI Assignment .....  | 167 |

|          |   |     |
|----------|---|-----|
| 16       | Verticals Support.....  | 167 |
| 16.1     | URLLC.....  | 167 |
| 16.1.1   | Overview .....  | 167 |
| 16.1.2   | LCP Restrictions.....   | 168 |
| 16.1.3   | Packet Duplication.....   | 168 |
| 16.1.4   | CQI and MCS .....   | 169 |
| 16.1.5   | DCI formats .....   | 169 |
| 16.1.6   | Higher layer multi-connectivity.....                                    | 169 |
| 16.1.6.1 | Redundant user plane paths based on dual connectivity .....             | 169 |
| 16.1.6.2 | Redundant data transmission via single UPF and single RAN node.....     | 169 |
| 16.1.7   | URLLC in Unlicensed Controlled Environment.....                         | 169 |
| 16.1.8   | PUCCH cell switching for TDD cells.....                                 | 170 |
| 16.2     | IMS Voice .....   | 170 |
| 16.2.0   | Support for IMS voice .....   | 170 |
| 16.2.1   | Support for MMTEL IMS voice and video enhancements.....                 | 170 |
| 16.2.1.1 | RAN-assisted codec adaptation.....                                      | 170 |
| 16.2.1.2 | MMTEL voice quality/coverage enhancements.....                          | 171 |
| 16.3     | Network Slicing.....  | 171 |
| 16.3.1   | General Principles and Requirements .....                               | 171 |
| 16.3.2   | AMF and NW Slice Selection.....   | 173 |
| 16.3.2.1 | CN-RAN interaction and internal RAN aspects.....                        | 173 |
| 16.3.2.2 | Radio Interface Aspects .....   | 174 |
| 16.3.3   | Resource Isolation and Management .....                                 | 174 |
| 16.3.3.1 | General .....   | 174 |
| 16.3.3.2 | Handling of Slice Resources .....                                       | 174 |
| 16.3.3a  | Slice-based cell reselection .....                                      | 174 |
| 16.3.4   | Signalling Aspects .....  | 175 |
| 16.3.4.1 | General.....  | 175 |
| 16.3.4.2 | AMF and NW Slice Selection.....   | 175 |
| 16.3.4.3 | UE Context Handling.....  | 175 |
| 16.3.4.4 | PDU Session Setup Handling.....   | 176 |
| 16.3.4.5 | Mobility.....   | 176 |
| 16.4     | Public Warning System .....   | 177 |
| 16.5     | Emergency Services .....  | 178 |
| 16.5.1   | Overview .....  | 178 |
| 16.5.2   | IMS Emergency call .....  | 178 |
| 16.5.3   | eCall over IMS.....   | 178 |
| 16.5.4   | Fallback .....  | 178 |
| 16.5.5   | Barring exemption for emergency calls.....                              | 178 |
| 16.6     | Stand-Alone NPN.....  | 179 |
| 16.6.1   | General.....  | 179 |
| 16.6.2   | Mobility .....  | 179 |
| 16.6.2.1 | General .....   | 179 |
| 16.6.2.2 | Inactive Mode .....   | 179 |
| 16.6.2.3 | Connected Mode .....  | 179 |
| 16.6.3   | Self-Configuration for SNPN .....                                       | 179 |
| 16.6.4   | Access Control.....   | 180 |
| 16.6.5   | Access with subscription/credentials owned by a Credentials Holder..... | 180 |
| 16.6.6   | Support of UE onboarding and remote provisioning .....                  | 180 |
| 16.7     | Public Network Integrated NPN.....                                      | 180 |
| 16.7.1   | General.....  | 180 |
| 16.7.2   | Mobility .....  | 181 |
| 16.7.2.1 | General .....   | 181 |
| 16.7.2.2 | Inactive Mode .....   | 181 |
| 16.7.2.3 | Connected Mode .....  | 181 |
| 16.7.3   | Self-Configuration for PNI-NPN .....                                    | 181 |
| 16.7.4   | Access Control.....   | 181 |
| 16.7.5   | Paging .....  | 182 |
| 16.8     | Support for Time Sensitive Communications.....                          | 182 |
| 16.8.1   | General.....  | 182 |
| 16.8.2   | Network timing synchronization status monitoring.....                   | 183 |
| 16.8.2.1 | General.....  | 183 |

|             |  |     |
|-------------|--|-----|
| 16.8.2.2    | Network timing synchronization status monitoring towards CN .....                  | 184 |
| 16.8.2.3    | Network timing synchronization status monitoring towards UE .....                  | 184 |
| 16.8.3      | RAN feedback for adaptation of Burst Arrival Time and Periodicity .....            | 185 |
| 16.9        | Sidelink .....   | 185 |
| 16.9.1      | General.....   | 185 |
| 16.9.2      | Radio Protocol Architecture for NR sidelink communication .....                    | 186 |
| 16.9.2.1    | Overview .....   | 186 |
| 16.9.2.2    | MAC .....  | 187 |
| 16.9.2.3    | RLC.....   | 188 |
| 16.9.2.4    | PDCCP.....   | 188 |
| 16.9.2.5    | SDAP .....   | 188 |
| 16.9.2.6    | RRC.....   | 188 |
| 16.9.3      | Radio Resource Allocation .....  | 189 |
| 16.9.3.1    | General .....  | 189 |
| 16.9.3.2    | Scheduled Resource Allocation .....  | 189 |
| 16.9.3.3    | UE Autonomous Resource Selection .....   | 190 |
| 16.9.3.4    | LTE and NR Sidelink co-channel coexistence .....                                   | 190 |
| 16.9.4      | Uu Control .....   | 190 |
| 16.9.4.1    | General .....  | 190 |
| 16.9.4.2    | Control of connected UEs .....   | 190 |
| 16.9.4.3    | Control of idle/inactive UEs.....  | 191 |
| 16.9.5      | Sidelink Discovery.....  | 191 |
| 16.9.6      | SL DRX .....   | 191 |
| 16.9.6.1    | General .....  | 191 |
| 16.9.6.2    | Unicast .....  | 192 |
| 16.9.6.3    | Groupcast/Broadcast .....  | 192 |
| 16.9.6.4    | Alignment between Uu DRX and SL DRX .....  | 193 |
| 16.9.7      | Power Savings Resource Allocation.....   | 193 |
| 16.9.8      | Inter-UE Coordination (IUC).....   | 193 |
| 16.9.9      | Sidelink in Shared Spectrum (SL-U) .....   | 194 |
| 16.9.9.1    | Overview .....   | 194 |
| 16.9.9.2    | Channel Access Priority Classes for Sidelink (SL-CAPC) .....                       | 194 |
| 16.9.9.3    | Sidelink Specific Consistent LBT Failure .....                                     | 195 |
| 16.9.9.4    | COT Sharing .....  | 195 |
| 16.9.9.5    | Resource Allocation .....  | 195 |
| 16.9.10     | Sidelink CA .....  | 196 |
| 16.10       | Multicast and Broadcast Services.....  | 196 |
| 16.10.1     | General.....   | 196 |
| 16.10.2     | Network Architecture .....   | 197 |
| 16.10.3     | Protocol Architecture.....   | 197 |
| 16.10.4     | Group Scheduling .....   | 199 |
| 16.10.5     | Multicast Handling .....   | 200 |
| 16.10.5.1   | Session Management.....  | 200 |
| 16.10.5.2   | Configuration .....  | 200 |
| 16.10.5.3   | Service Continuity.....  | 201 |
| 16.10.5.3.1 | General .....  | 201 |
| 16.10.5.3.2 | Handover between Multicast supporting cells.....                                   | 202 |
| 16.10.5.3.3 | Handover between Multicast-supporting cell and Multicast non-supporting cell ..... | 202 |
| 16.10.5.3.4 | MRB reconfiguration.....   | 203 |
| 16.10.5.3.5 | Service Continuity in RRC_INACTIVE .....   | 203 |
| 16.10.5.4   | Reception of MBS Multicast data .....  | 203 |
| 16.10.5.5   | Support of CA .....  | 204 |
| 16.10.5.6   | DRX .....  | 204 |
| 16.10.5.7   | Physical Layer.....  | 204 |
| 16.10.6     | Broadcast Handling.....  | 204 |
| 16.10.6.1   | Session Management.....  | 204 |
| 16.10.6.2   | Configuration .....  | 205 |
| 16.10.6.3   | Support of CA .....  | 205 |
| 16.10.6.4   | DRX .....  | 205 |
| 16.10.6.5   | Service Continuity.....  | 205 |
| 16.10.6.5.0 | General .....  | 205 |
| 16.10.6.5.1 | Service Continuity in RRC_IDLE or RRC_INACTIVE .....                               | 205 |

|             |   |     |
|-------------|---|-----|
| 16.10.6.5.2 | Service Continuity in RRC_CONNECTED .....   | 206 |
| 16.10.6.5A  | Reception of MBS Broadcast data .....   | 206 |
| 16.10.6.6   | Physical Layer.....   | 206 |
| 16.10.6.7   | Shared processing for MBS broadcast and unicast reception.....                                    | 207 |
| 16.10.6.8   | Support of Resource Sharing across multiple Broadcast MBS sessions in RAN Sharing Scenario ...    | 207 |
| 16.11       | Minimization of Service Interruption.....   | 207 |
| 16.12       | Sidelink Relay .....  | 208 |
| 16.12.1     | General.....  | 208 |
| 16.12.2     | Protocol Architecture.....  | 208 |
| 16.12.2.1   | L2 UE-to-Network Relay .....  | 208 |
| 16.12.2.2   | L2 UE-to-UE Relay.....  | 211 |
| 16.12.3     | Relay Discovery.....  | 212 |
| 16.12.4     | Relay Selection/Reselection.....  | 213 |
| 16.12.5     | Control plane procedures for L2 U2N Relay .....   | 215 |
| 16.12.5.1   | RRC Connection Management.....  | 215 |
| 16.12.5.2   | Radio Link Failure .....  | 218 |
| 16.12.5.3   | RRC Connection Re-establishment.....  | 218 |
| 16.12.5.4   | RRC Connection Resume .....   | 218 |
| 16.12.5.5   | System Information.....   | 218 |
| 16.12.5.6   | Paging .....  | 219 |
| 16.12.5.7   | Access Control .....  | 220 |
| 16.12.5.8   | Mobility Registration Update and RAN Area Update.....   | 220 |
| 16.12.6     | Service Continuity for L2 U2N relay.....  | 220 |
| 16.12.6.0   | General .....   | 220 |
| 16.12.6.1   | Switching from single/multi-hop indirect to direct path .....                                     | 220 |
| 16.12.6.2   | Switching from direct to indirect path.....   | 223 |
| 16.12.6.3   | Switching from multi/single-hop indirect to multi/single-hop indirect path .....                  | 226 |
| 16.12.7     | Control plane procedures for L2 U2U Relay .....   | 230 |
| 16.13       | Support of Reduced Capability (RedCap) and enhanced Reduced Capability (eRedCap) NR devices ..... | 232 |
| 16.13.1     | Introduction.....   | 232 |
| 16.13.2     | Capabilities .....  | 232 |
| 16.13.3     | Identification, access and camping restrictions.....  | 232 |
| 16.13.4     | RRM measurement relaxations.....  | 233 |
| 16.13.5     | BWP operation.....  | 233 |
| 16.14       | Non-Terrestrial Networks.....   | 233 |
| 16.14.1     | Overview .....  | 233 |
| 16.14.2     | Timing and Synchronization.....   | 236 |
| 16.14.2.1   | Scheduling and Timing .....   | 236 |
| 16.14.2.2   | Timing Advance and Frequency Pre-compensation.....  | 237 |
| 16.14.3     | Mobility and State transition.....  | 238 |
| 16.14.3.1   | Mobility in RRC_IDLE and RRC_INACTIVE .....   | 238 |
| 16.14.3.2   | Mobility in RRC_CONNECTED.....  | 238 |
| 16.14.3.2.1 | Handover .....  | 238 |
| 16.14.3.2.2 | Conditional Handover .....  | 238 |
| 16.14.3.2.3 | Satellite switch with re-synchronization.....   | 239 |
| 16.14.3.3   | Measurements .....  | 239 |
| 16.14.4     | Switchover .....  | 240 |
| 16.14.4.1   | Definitions.....  | 240 |
| 16.14.4.2   | Assumptions.....  | 240 |
| 16.14.4.3   | Procedures.....   | 240 |
| 16.14.5     | NG-RAN signalling .....   | 241 |
| 16.14.6     | AMF (Re-)Selection .....  | 241 |
| 16.14.7     | O&M Requirements.....   | 242 |
| 16.14.8     | Coarse UE location reporting.....   | 242 |
| 16.14.9     | Support for NR NTN coverage enhancements.....   | 242 |
| 16.14.10    | Verification of UE location.....  | 243 |
| 16.14.11    | Support for NR NTN capacity enhancements.....   | 243 |
| 16.14.12    | Support of ISA for MBS Broadcast in NTN.....  | 243 |
| 16.14.13    | Support of Half-Duplex UE in NR NTN .....   | 243 |
| 16.14.14    | NG Removal .....  | 244 |
| 16.15       | eXtended Reality Services.....  | 244 |
| 16.15.1     | General.....  | 244 |

|             |  |     |
|-------------|--|-----|
| 16.15.2     | Awareness.....   | 244 |
| 16.15.3     | Power Saving.....  | 245 |
| 16.15.4     | Capacity.....  | 245 |
| 16.15.4.1   | Physical Layer Enhancements.....                                       | 245 |
| 16.15.4.2   | Layer 2 Enhancements.....  | 246 |
| 16.15.4.2.1 | Assistance Information.....  | 246 |
| 16.15.4.2.2 | Discard.....   | 246 |
| 16.15.4.2.3 | Logical Channel Priority Adjustment.....                               | 246 |
| 16.15.4.2.4 | RLC Retransmissions.....   | 246 |
| 16.15.4.2.5 | Uplink Rate Control.....   | 247 |
| 16.15.5     | Non-Homogeneous support of PDU set based handling in NG-RAN.....       | 247 |
| 16.15.6     | Measurement Gaps.....  | 247 |
| 16.16       | ECN marking for L4S and congestion information exposure.....           | 247 |
| 16.17       | Support for TSN enabled Transport Network.....                         | 248 |
| 16.18       | Support for Aerial UE Communication.....                               | 248 |
| 16.18.1     | General.....   | 248 |
| 16.18.2     | Subscription-based Identification of Aerial UE.....                    | 248 |
| 16.18.3     | Altitude-based Reporting for Aerial UE Communication.....              | 249 |
| 16.18.4     | Altitude-dependent Configurations for Aerial UE Communication.....     | 249 |
| 16.18.5     | Interference Detection and Mitigation for Aerial UE Communication..... | 249 |
| 16.18.6     | Flight Path Information Reporting for Aerial UE Communication.....     | 249 |
| 16.18.7     | Location Reporting for Aerial UE Communication.....                    | 249 |
| 16.18.8     | BRID and DAA Support via A2X Communication.....                        | 249 |
| 16.18.9     | Altitude-based CHO for Aerial UE Communication.....                    | 250 |
| 16.18.10    | UAV prioritized frequency for Aerial UE cell reselection.....          | 250 |
| 16.18.11    | Flight Information Reporting for Aerial UE.....                        | 250 |
| 16.19       | Support for Air to Ground Networks.....                                | 250 |
| 16.19.1     | Overview.....  | 250 |
| 16.19.2     | Timing and Synchronization.....  | 250 |
| 16.19.2.1   | Scheduling and Timing.....   | 250 |
| 16.19.2.2   | Timing Advance.....  | 250 |
| 16.19.3     | Mobility.....  | 251 |
| 16.19.3.1   | Mobility in RRC_IDLE and RRC_INACTIVE.....                             | 251 |
| 16.19.3.2   | Mobility in RRC_CONNECTED.....   | 251 |
| 16.19.3.2.1 | Handover.....  | 251 |
| 16.19.3.2.2 | Conditional Handover.....  | 251 |
| 16.19.3.3   | Measurements.....  | 251 |
| 16.20       | Support of AI/ML for NG-RAN.....                                       | 251 |
| 16.20.1     | General.....   | 251 |
| 16.20.2     | Principles.....  | 251 |
| 16.20.3     | Data Collection and Reporting.....                                     | 252 |
| 16.20.4     | OAM Requirements.....  | 252 |
| 16.21       | Multi-path Relay.....  | 253 |
| 16.21.1     | General.....   | 253 |
| 16.21.2     | Protocol Architecture.....   | 253 |
| 16.21.2.1   | L2 MP Relay using SL indirect path.....                                | 253 |
| 16.21.2.2   | L2 MP Relay using N3C indirect path.....                               | 254 |
| 16.21.3     | Control plane procedure for multi-path relaying.....                   | 256 |
| 16.21.3.1   | Path Management.....   | 256 |
| 16.21.3.2   | Path Failure Report.....   | 262 |
| 16.21.3.3   | System Information.....  | 262 |
| 16.22       | Support of 2Rx XR devices.....   | 262 |
| 16.22.1     | Introduction.....  | 262 |
| 16.22.2     | Identification, access and camping restrictions.....                   | 262 |
| 16.23       | Support of Ambient IoT.....  | 262 |
| 16.23.1     | General.....   | 262 |
| 16.23.2     | Architecture.....  | 263 |
| 16.23.3     | Radio Protocol Architecture for A-IoT Communication.....               | 263 |
| 16.23.4     | A-IoT Physical Layer Functions.....                                    | 264 |
| 16.23.4.1   | Waveform, numerology, time and frequency domain structure.....         | 264 |
| 16.23.4.2   | R2D.....   | 264 |
| 16.23.4.2.1 | Physical reader-to-device channel.....                                 | 264 |

|             |   |     |
|-------------|---|-----|
| 16.23.4.2.2 | Timing acquisition signal .....                                     | 264 |
| 16.23.4.2.3 | Postamble .....   | 264 |
| 16.23.4.3   | D2R .....   | 264 |
| 16.23.4.3.1 | Physical device-to-reader channel .....                             | 264 |
| 16.23.4.3.2 | D2R amble signals.....  | 265 |
| 16.23.5     | A-IoT MAC Layer Functions .....                                     | 265 |
| 16.23.5.1   | Services and functions.....   | 265 |
| 16.23.5.2   | A-IoT Paging.....   | 265 |
| 16.23.5.3   | A-IoT Access Procedure .....  | 265 |
| 16.23.5.4   | A-IoT Upper-layer Data Transmission.....                            | 266 |
| 16.23.5.4.1 | R2D and D2R data transmission.....                                  | 266 |
| 16.23.5.4.2 | Segmentation .....  | 266 |
| 16.23.5.5   | AS ID .....   | 266 |
| 16.23.6     | Inventory Procedure.....  | 267 |
| 16.23.7     | Command Procedure.....  | 268 |
| 16.23.8     | A-IoT CN node initiated A-IoT Session Release procedure.....        | 269 |
| 16.23.9     | gNB initiated A-IoT Session Release procedure .....                 | 269 |
| 16.23.10    | Locating A-IoT devices .....  | 270 |
| 17          | Interference Management.....  | 270 |
| 17.1        | Remote Interference Management .....                                | 270 |
| 17.2        | Cross-Link Interference Management .....                            | 271 |
| 18          | Small Data Transmission.....  | 271 |
| 18.0        | General .....   | 271 |
| 18.1        | Support of SDT procedure over RACH .....                            | 273 |
| 18.2        | SDT with UE context relocation .....                                | 273 |
| 18.3        | SDT without UE context relocation .....                             | 275 |
| 18.4        | MT-SDT with/without UE context relocation.....                      | 276 |
| 19          | Support for NR coverage enhancements .....                          | 277 |
| 20          | Support for Multi-USIM devices .....                                | 278 |
| 20.1        | General .....   | 278 |
| 20.2        | Paging Collision Avoidance .....                                    | 278 |
| 20.3        | UE notification on Network Switching .....                          | 279 |
| 20.4        | Temporary UE capability restriction and removal of restriction..... | 279 |
| 21          | Application Layer Measurement Collection .....                      | 280 |
| 21.1        | Overview .....  | 280 |
| 21.2        | QoE Measurement Configuration.....                                  | 280 |
| 21.2.1      | QoE Measurement Collection Activation and Reporting .....           | 280 |
| 21.2.2      | QoE Measurement Collection Deactivation .....                       | 281 |
| 21.2.3      | Handling of QMC during RAN Overload.....                            | 281 |
| 21.2.4      | QoE Measurement Handling in RRC_IDLE and RRC_INACTIVE States.....   | 281 |
| 21.2.5      | Per-slice QoE Measurement .....                                     | 282 |
| 21.3        | QoE Measurement Continuity for Mobility .....                       | 282 |
| 21.4        | RAN Visible QoE Measurements .....                                  | 283 |
| 21.5        | Alignment of MDT and QoE Measurements.....                          | 284 |
| 21.6        | QoE Measurement Collection in High Mobility Scenarios .....         | 284 |
| 21.7        | Void.....   | 284 |
| 22          | Support of AI/ML for NR Air Interface.....                          | 284 |
| 22.1        | Overview .....  | 284 |
| 22.2        | AI/ML-based Beam Management .....                                   | 285 |
| 22.2.1      | Introduction.....   | 285 |
| 22.2.2      | Void .....  | 285 |
| 22.2.3      | Applicability Reporting .....                                       | 285 |
| 22.2.4      | Inference, Monitoring and Management.....                           | 286 |
| 22.3        | AI/ML-based CSI prediction.....                                     | 286 |
| 22.4        | AI/ML-based Positioning .....                                       | 287 |
| 22.5        | Data Collection for Offline Model Training.....                     | 287 |
| 22.5.1      | Network-side data collection .....                                  | 287 |
| 22.5.2      | UE-side data collection .....                                       | 287 |

|   |   |            |
|---|---|------------|
| 23  | SBFD.....   | 287        |
| 23.1  | General.....  | 287        |
| 23.2  | SBFD Random Access.....                                 | 288        |
| <b>Annex A (informative): QoS Handling in RAN.....</b>  |   | <b>289</b> |
| A.1   | PDU Session Establishment.....                          | 289        |
| A.2   | New QoS Flow with RQoS.....                             | 289        |
| A.3   | New QoS Flow with Explicit RRC Signalling.....          | 290        |
| A.4   | New QoS Flow with Explicit NAS Signalling.....          | 291        |
| A.5   | Release of QoS Flow with Explicit Signalling.....       | 292        |
| A.6   | UE Initiated UL QoS Flow.....                           | 292        |
| <b>Annex B (informative): Deployment Scenarios.....</b>   |   | <b>294</b> |
| B.1   | Supplementary Uplink.....                               | 294        |
| B.2   | Multiple SSBs in a carrier.....                         | 294        |
| B.3   | NR Operation with Shared Spectrum.....                  | 295        |
| B.4   | Example implementation of Non-Terrestrial Networks..... | 295        |
| <b>Annex C (informative): I-RNTI Reference Profiles.....</b>  |   | <b>298</b> |
| <b>Annex D (informative): SPID ranges and mapping of SPID values to cell reselection and inter-RAT/inter frequency handover priorities.....</b> |   | <b>299</b> |
| <b>Annex E (informative): NG-RAN Architecture for Radio Access Network Sharing with multiple cell ID broadcast.....</b>                         |   | <b>300</b> |
| <b>Annex F (normative): Use and structure of the I-RNTI.....</b>  |   | <b>301</b> |
| <b>Annex G (informative): Components of Mobility Latency.....</b>   |   | <b>302</b> |
| <b>Annex H (informative): Change history.....</b>   |   | <b>304</b> |
| History.....  |   | 315        |

---

# Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

# Sample Document

get full document from [standards.iteh.ai](https://standards.iteh.ai)