

ETSI TS 138 521-1 V18.7.0 (2025-08)



TECHNICAL SPECIFICATION

**5G;
NR;**

**User Equipment (UE) conformance specification;
Radio transmission and reception;
Part 1: Range 1 standalone
(3GPP TS 38.521-1 version 18.7.0 Release 18)**

<https://standards.iteh.ai/catalog/standards/etsi/5f54e001-4a09-4fd1-832e-9596fabeb00d/etsi-ts-138-521-1-v18-7-0-2025-08>



Reference

RTS/TSGR-0538521-1vi70

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed, this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our [Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2025.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by the ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables. (2025-08)

The cross reference between 3GPP and ETSI identities can be found at [3GPP to ETSI numbering cross-referencing](#).

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	25
1 Scope	26
2 References	26
3 Definitions, symbols and abbreviations	27
3.1 Definitions	27
3.2 Symbols.....	28
3.3 Abbreviations	30
4 General	32
4.1 Relationship between minimum requirements and test requirements	32
4.2 Applicability of minimum requirements	33
4.3 Specification suffix information.....	33
4.4 Test points analysis	34
4.5 Applicability and test coverage rules.....	34
4.6 Pass fail decision rule of test case	34
5 Operating bands and Channel arrangement.....	35
5.1 General	35
5.2 Operating bands.....	35
5.2A Operating bands for CA	37
5.2A.1 Intra-band CA	37
5.2A.2 Inter-band CA	37
5.2A.2.1 Inter-band CA (two bands).....	38
5.2A.2.2 Inter-band CA (three bands).....	39
5.2A.2.3 Inter-band CA (four bands).....	40
5.2B Operating bands for DC	41
5.2C Operating band combination for SUL	41
5.2D Operating bands for UL MIMO	42
5.2E Operating band for V2X.....	43
5.2E.1 V2X operating bands	43
5.2E.2 V2X operating bands for concurrent operation.....	43
5.2J Operating band for ATG	43
5.2K Operating bands for Aerial UE.....	43
5.3 UE channel bandwidth	43
5.3.1 General.....	43
5.3.2 Maximum transmission bandwidth configuration	44
5.3.3 Minimum guard band and transmission bandwidth configuration.....	44
5.3.4 RB alignment	46
5.3.5 UE channel bandwidth per operating band	46
5.3.6 Asymmetric channel bandwidths	50
5.3A UE channel bandwidth for CA	51
5.3A.1 General.....	51
5.3A.2 Maximum transmission bandwidth configuration for CA	51
5.3A.3 Minimum guard band and transmission bandwidth configuration for CA.....	51
5.3A.4 Void	53
5.3A.5 UE channel bandwidth per operating band for CA.....	53
5.3E Channel bandwidth for V2X	54
5.3E.1 General.....	54
5.3E.2 Channel bandwidth for V2X concurrent operation.....	55
5.3I Channel bandwidth for (e)RedCap.....	55
5.4 Channel arrangement.....	55
5.4.1 Channel spacing.....	55

5.4.1.1	Channel spacing for adjacent NR carriers	55
5.4.2	Channel raster	56
5.4.2.1	NR-ARFCN and channel raster.....	56
5.4.2.2	Channel raster to resource element mapping.....	56
5.4.2.3	Channel raster entries for each operating band	56
5.4.3	Synchronization raster	59
5.4.3.1	Synchronization raster and numbering.....	59
5.4.3.2	Synchronization raster to synchronization block resource element mapping.....	60
5.4.3.3	Synchronization raster entries for each operating band.....	60
5.4.4	TX–RX frequency separation	61
5.4A	Channel arrangement for CA.....	62
5.4A.1	Channel spacing for CA.....	62
5.4A.2	Channel raster for CA.....	63
5.4A.3	Synchronization raster for CA	63
5.4A.4	Tx-Rx frequency separation for CA.....	63
5.4E	Channel arrangement for V2X	63
5.4E.1	Channel spacing.....	63
5.4E.2	Channel raster	63
5.4E.2.1	NR-ARFCN and channel raster.....	63
5.4E.2.2	Channel raster to resource element mapping.....	64
5.4E.2.3	Channel raster entries for each operating band	64
5.4E.3	Synchronization raster for V2X.....	64
5.4F	64	
5.4G	64	
5.4H	64	
5.4I	Channel arrangement for (e)RedCap.....	64
5.4I.1	Channel spacing for (e)RedCap.....	64
5.4I.2	Channel raster for (e)RedCap.....	64
5.4I.2.1	NR-ARFCN and channel raster.....	64
5.4I.2.2	Channel raster to resource element mapping.....	64
5.4I.2.3	Channel raster entries for each operating band	64
5.4I.3	Synchronization raster for (e)RedCap.....	65
5.4I.4	Tx-Rx frequency separation for (e)RedCap.....	65
5.5	Void.....	65
5.5A	Configurations for CA.....	65
5.5A.0	General.....	65
5.5A.1	Configurations for intra-band contiguous CA.....	65
5.5A.2	Configurations for intra-band non-contiguous CA	67
5.5A.3	Configurations for inter-band CA.....	67
5.5A.3.0	General.....	68
5.5A.3.1	Configurations for inter-band CA (two bands)	69
5.5A.3.2	Configurations for inter-band CA (three bands)	80
5.5A.3.3	Configurations for inter-band CA (four bands).....	95
5.5B	Configurations for DC.....	98
5.5C	Configurations for SUL.....	98
6	Transmitter characteristics	102
6.0	General test requirements for $\Delta T_{IB,c}$	102
6.1	General	102
6.1A	General	104
6.1E	General	113
6.1F	General	117
6.1I	General	117
6.1J	General	118
6.2	Transmitter power	118
6.2.1	UE maximum output power.....	118
6.2.2	UE maximum output power reduction.....	125
6.2.3	UE additional maximum output power reduction.....	155
6.2.4	Configured transmitted power	333
6.2A	Transmitter power for CA	341
6.2A.0	General.....	341
6.2A.1	UE maximum output power for CA.....	341

6.2A.1.0	Minimum conformance requirements	341
6.2A.1.0.1	Void	341
6.2A.1.0.2	Void	341
6.2A.1.0.3	UE maximum output power for Inter-band CA	341
6.2A.1.0.4	UE maximum output power for Intra-band contiguous CA	343
6.2A.1.0.5	UE maximum output power for Intra-band non-contiguous CA	344
6.2A.1.1	UE maximum output power for CA (2UL CA).....	344
6.2A.2	UE maximum output power reduction for CA.....	348
6.2A.2.0	Minimum conformance requirements	348
6.2A.2.0.1	FFS	348
6.2A.2.0.2	FFS	348
6.2A.2.0.3	Maximum Power Reduction for Inter-band CA	348
6.2A.2.0.4	Maximum Power Reduction for Intra-band contiguous CA.....	348
6.2A.2.0.5	Maximum Power Reduction for Intra-band non-contiguous CA.....	352
6.2A.2.1	UE maximum output power reduction for CA (2UL CA).....	353
6.2A.3	UE additional maximum output power reduction for CA.....	375
6.2A.3.0	Minimum conformance requirements	375
6.2A.3.0.1	UE additional maximum output power reduction for Intra-band contiguous CA.....	375
6.2A.3.0.1.1	A-MPR for CA_NS_04.....	376
6.2A.3.0.1.1.2	Non-contiguous allocations	376
6.2A.3.0.1.1.3	AMPR _{IM3} to meet -25dBm/MHz.....	377
6.2A.3.0.2	FFS	377
6.2A.3.0.3	UE additional maximum output power reduction for inter-band CA	377
6.2A.3.1	UE additional maximum output power reduction for CA (2UL CA).....	379
6.2A.4	Configured output power for CA.....	390
6.2A.4.0	Minimum conformance requirements	390
6.2A.4.0.1	Configured transmitted power level	390
6.2A.4.0.2	$\Delta T_{IB,c}$ for CA	397
6.2A.4.0.2.1	FFS	397
6.2A.4.0.2.2	FFS	397
6.2A.4.0.2.3	$\Delta T_{IB,c}$ for Inter-band CA.....	397
6.2A.4.1	Configured transmitted power for CA (2UL CA).....	401
6.2B	Transmitter power for NR-DC	408
6.2B.0	General.....	408
6.2B.1	UE maximum output power for NR-DC.....	408
6.2B.1.0	Minimum conformance requirements	408
6.2B.1.0.1	FFS	408
6.2B.1.0.2	FFS	408
6.2B.1.0.3	UE maximum output power for inter-band NR-DC	408
6.2B.1.1	UE maximum output power for NR-DC	408
6.2B.2	UE maximum output power reduction for NR-DC.....	411
6.2B.2.0	Minimum conformance requirements	411
6.2B.2.0.1	FFS	411
6.2B.2.0.2	FFS	411
6.2B.2.0.3	UE maximum output power reduction for Inter-band NR-DC	411
6.2B.2.1	UE maximum output power reduction for NR-DC	411
6.2B.3	UE additional maximum output power reduction for NR-DC	412
6.2B.3.0	Minimum conformance requirements	412
6.2B.3.0.1	FFS	412
6.2B.3.0.2	FFS	412
6.2B.3.0.3	UE additional maximum output power reduction for inter-band NR-DC	412
6.2B.3.1	UE additional maximum output power reduction for NR-DC	412
6.2B.4	Configured output power for NR-DC	414
6.2B.4.0	Minimum conformance requirements	414
6.2B.4.0.1	Configured transmitted power level for NR-DC	414
6.2B.4.0.2	$\Delta T_{IB,c}$ for NR-DC.....	417
6.2B.4.0.2.1	FFS.....	417
6.2B.4.0.2.2	FFS.....	417
6.2B.4.0.2.3	Void	417
6.2B.4.1	Configured transmitted power level for NR-DC	417
6.2C	Transmitter power for SUL	420
6.2C.1	Configured transmitted power for SUL	420

6.2C.2	$\Delta T_{IB,c}$	422
6.2C.3	UE maximum output power for SUL.....	423
6.2C.3_1	Void	425
6.2C.4	UE maximum output power reduction for SUL.....	425
6.2C.5	UE additional maximum output power reduction for SUL.....	433
6.2D	Transmitter power for UL MIMO	466
6.2D.1	UE maximum output power for UL MIMO.....	466
6.2D.1_1	UE maximum output power for SUL with UL MIMO	470
6.2D.1_2	UE maximum output power for UL MIMO for UE supporting 4Tx	473
6.2D.2	UE maximum output power reduction for UL MIMO.....	474
6.2D.2_1	UE maximum output power reduction for SUL with UL MIMO	492
6.2D.2_2	UE maximum output power reduction for UL MIMO for UE supporting 4Tx	497
6.2D.3	UE additional maximum output power reduction for UL MIMO.....	504
6.2D.3_1	UE additional maximum output power reduction for SUL with UL MIMO	555
6.2D.4	Configured transmitted power for UL MIMO	565
6.2D.4_1	Configured transmitted power for SUL with UL MIMO.....	569
6.2E	Transmitter power for V2X.....	571
6.2E.1	UE maximum output power for V2X	571
6.2E.1.0	Minimum conformance requirements	571
6.2E.1.1	UE maximum output power for V2X / non-concurrent operation	573
6.2E.1.1D	UE maximum output power for V2X / non-concurrent operation / SL-MIMO	573
6.2E.1.2	UE maximum output power for V2X / concurrent operation.....	573
6.2E.2	UE maximum output power reduction for V2X	577
6.2E.2.0	Minimum conformance requirements	577
6.2E.2.1	UE maximum output power reduction for V2X / non-concurrent operation	581
6.2E.2.1D	UE maximum output power reduction for V2X / non-concurrent operation / SL-MIMO	586
6.2E.2.2	UE maximum output power reduction for V2X / concurrent operation.....	587
6.2E.3	UE additional maximum output power reduction for V2X.....	592
6.2E.3.0	Minimum conformance requirements	592
6.2E.3.1	UE additional maximum output power reduction for V2X / non-concurrent operation.....	599
6.2E.3.1D	UE additional maximum output power reduction for V2X / non-concurrent operation / SL-MIMO	610
6.2E.3.2	UE maximum output power reduction for V2X / concurrent operation.....	613
6.2E.4	Configured transmitted power for V2X	615
6.2E.4.0	Minimum conformance requirements	615
6.2E.4.1	Configured transmitted power for V2X / non-concurrent operation	618
6.2E.4.1D	Configured transmitted power for V2X / non-concurrent operation / SL-MIMO.....	621
6.2E.4.2	Configured transmitted power for V2X / concurrent operation	621
6.2F	Transmitter power for shared spectrum channel access	626
6.2F.1	UE maximum output power for shared spectrum channel access.....	626
6.2F.1A	UE maximum output power for CA for shared spectrum access	626
6.2F.2	UE maximum output power reduction for shared spectrum access	627
6.2F.3	UE additional maximum output power reduction for shared spectrum access	630
6.2F.4	Configured transmitted power for shared spectrum access.....	641
6.2G	Transmitter power for Tx Diversity.....	643
6.2G.1	UE maximum output power for Tx Diversity	643
6.2G.1_1	UE maximum output power for Tx Diversity for UE supporting 4Tx.....	652
6.2G.2	UE maximum output power reduction for Tx Diversity	652
6.2G.2_1	UE maximum output power reduction for Tx Diversity for UE supporting 4Tx.....	675
6.2G.3	UE additional maximum output power reduction for Tx Diversity	680
6.2G.4	Configured transmitted power for Tx Diversity.....	699
6.2H	Transmitter power for CA with UL MIMO.....	703
6.2H.1	Transmitter power for intra-band UL contiguous CA with UL MIMO	703
6.2H.1.1	UE maximum output power for intra-band UL contiguous CA with UL MIMO	703
6.2H.1.2	UE maximum output power reduction for intra-band UL contiguous CA with UL MIMO	703
6.2H.1.3	UE additional maximum output power reduction for intra-band UL contiguous CA with UL MIMO	706
6.2H.1.4	Configured transmitted power for intra-band UL contiguous CA with UL MIMO.....	709
6.2H.2	713	
6.2H.3	Transmitter power for inter-band UL CA with UL MIMO	713
6.2H.3.1	UE maximum output power for inter-band UL CA with UL MIMO.....	713
6.2H.3.2	UE maximum output power reduction for inter-band UL CA with UL MIMO.....	718