

ETSI TS 138 521-2 V19.1.0 (2026-03)



TECHNICAL SPECIFICATION

**5G;
NR;
User Equipment (UE) conformance specification;
Radio transmission and reception;
Part 2: Range 2 standalone
(3GPP TS 38.521-2 version 19.1.0 Release 19)**



Reference

RTS/TSGR-0538521-2vj10

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed, this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our [Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2026.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by the ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found at [3GPP to ETSI numbering cross-referencing](#).

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	17
1 Scope	18
2 References	18
3 Definitions, symbols and abbreviations	19
3.1 Definitions	19
3.2 Symbols.....	21
3.3 Abbreviations	23
4 General	24
4.1 Relationship between minimum requirements and test requirements	24
4.2 Applicability of minimum requirements	24
4.3 Specification suffix information.....	25
4.4 Test point analysis.....	25
4.5 Applicability and test coverage rules.....	26
5 Operating bands and channel arrangement.....	26
5.1 General	26
5.2 Operating bands.....	26
5.2A Operating bands for CA	27
5.2A.2 Void	27
5.2A.3 Inter-band CA	27
5.2D Operating bands for UL MIMO	27
5.2K Operating bands for simultaneous reception or transmission in multiple directions	27
5.3 UE Channel bandwidth	28
5.3.1 General.....	28
5.3.2 Maximum transmission bandwidth configuration	28
5.3.3 Minimum guardband and transmission bandwidth configuration.....	29
5.3.4 RB alignment	30
5.3.5 Channel bandwidth per operating band	30
5.3A UE Channel bandwidth for CA	31
5.3A.1 General.....	31
5.3A.2 Minimum guardband and transmission bandwidth configuration for CA	31
5.3A.3 RB alignment with different numerologies for CA.....	33
5.3A.4 UE channel bandwidth per operating band for CA.....	33
5.3D Channel bandwidth for UL MIMO.....	35
5.4 Channel arrangement.....	35
5.4.1 Channel spacing.....	35
5.4.1.1 Channel spacing for adjacent NR carriers	35
5.4.2 Channel raster	35
5.4.2.1 NR-ARFCN and channel raster.....	35
5.4.2.2 Channel raster to resource element mapping.....	35
5.4.2.3 Channel raster entries for each operating band	36
5.4.3 Synchronization raster	36
5.4.3.1 Synchronization raster and numbering.....	36
5.4.3.2 Synchronization raster to synchronization block resource element mapping.....	37
5.4.3.3 Synchronization raster entries for each operating band.....	37
5.4A Channel arrangement for CA.....	37
5.4A.1 Channel spacing for CA.....	37
5.5 Configurations	38
5.5A Configurations for CA.....	38
5.5A.1 Configurations for intra-band contiguous CA.....	38
5.5A.2 Configurations for intra-band non-contiguous CA	39

5.5A.3	Configurations for inter-band CA	43
5.5D	Configurations for UL MIMO	43
6	Transmitter characteristics	44
6.1	General	44
6.2	Transmit power	46
6.2.1	UE maximum output power	46
6.2.1.0	General	46
6.2.1.1	UE maximum output power - EIRP and TRP	47
6.2.1.1_1	UE maximum output power - EIRP and TRP (Rel16 and forward)	59
6.2.1.2	UE maximum output power - Spherical coverage	61
6.2.1.2_1	UE maximum output power - Spherical coverage (Rel16 and forward)	67
6.2.2	UE maximum output power reduction	68
6.2.2.0	General	68
6.2.2.3.1	UE maximum output power reduction for power class 1	69
6.2.2.3.2	UE maximum output power reduction for power class 2	70
6.2.2.3.3	UE maximum output power reduction for power class 3	71
6.2.2.3.4	UE maximum output power reduction for power class 4	72
6.2.2.3.5	UE maximum output power reduction for power class 5	72
6.2.2.3.6	UE maximum output power reduction for power class 6	72
6.2.2.3.7	UE maximum output power reduction for power class 7	72
6.2.2_1	UE maximum output power reduction enhancements	88
6.2.2_1.0	General	88
6.2.3	UE maximum output power with additional requirements	95
6.2.3.3.1	General	95
6.2.3.3.2	Void	96
6.2.3.3.3	A-MPR for NS_202	96
6.2.3.3.4	A-MPR for NS_203	97
6.2.3.3.5	[Reserved]	97
6.2.3.3.6	A-MPR for NS_205	97
6.2.4	Configured transmitted power	107
6.2.4_1	Configured transmitted power with Power Boost	108
6.2.5	UE maximum output power – EIRP with UL Gaps	110
6.2A	Transmit power for CA	114
6.2A.1	UE maximum output power for CA	114
6.2A.1.0	Minimum conformance requirements	114
6.2A.1.1	UE maximum output power - EIRP and TRP for CA	114
6.2A.1.1.1	UE maximum output power - EIRP and TRP for CA (2UL CA)	114
6.2A.1.1.2	UE maximum output power - EIRP and TRP for CA (3UL CA)	119
6.2A.1.1.3	UE maximum output power - EIRP and TRP for CA (4UL CA)	121
6.2A.1.1.4	UE maximum output power - EIRP and TRP for CA (5UL CA)	123
6.2A.1.1.5	UE maximum output power - EIRP and TRP for CA (6UL CA)	124
6.2A.1.1.6	UE maximum output power - EIRP and TRP for CA (7UL CA)	124
6.2A.1.1.7	UE maximum output power - EIRP and TRP for CA (8UL CA)	124
6.2A.1.2	UE maximum output power - Spherical coverage	125
6.2A.1.2.1	UE maximum output power - Spherical coverage for CA (2UL CA)	125
6.2A.1.2.2	UE maximum output power - Spherical coverage for CA (3UL CA)	129
6.2A.1.2.3	UE maximum output power - Spherical coverage for CA (4UL CA)	132
6.2A.1.2.4	UE maximum output power - Spherical coverage for CA (5UL CA)	134
6.2A.1.2.5	UE maximum output power - Spherical coverage for CA (6UL CA)	134
6.2A.1.2.6	UE maximum output power - Spherical coverage for CA (7UL CA)	135
6.2A.1.2.7	UE maximum output power - Spherical coverage for CA (8UL CA)	135
6.2A.2	UE maximum output power reduction for CA	135
6.2A.2.0	Minimum conformance requirements	135
6.2A.2.0.1	General	135
6.2A.2.0.2	Maximum output power reduction for power class 1	135
6.2A.2.0.3	Maximum output power reduction for power class 2	138
6.2A.2.0.4	Maximum output power reduction for power class 3	139
6.2A.2.0.5	Maximum output power reduction for power class 4	141
6.2A.2.0.6	Maximum output power reduction for power class 5	141
6.2A.2.1	UE maximum output power reduction for CA (2UL CA)	141
6.2A.2.2	UE maximum output power reduction for CA (3UL CA)	164

6.2A.2.3	UE maximum output power reduction for CA (4UL CA).....	170
6.2A.2.4	UE maximum output power reduction for CA (5UL CA).....	176
6.2A.2.5	UE maximum output power reduction for CA (6UL CA).....	176
6.2A.2.6	UE maximum output power reduction for CA (7UL CA).....	176
6.2A.2.7	UE maximum output power reduction for CA (8UL CA).....	176
6.2A.3	UE maximum output power with additional requirements for CA.....	177
6.2A.3.0	Minimum conformance requirements	177
6.2A.3.0.1	General	177
6.2A.3.0.2	Void.....	177
6.2A.3.0.3	A-MPR for CA_NS_202	177
6.2A.3.0.4	A-MPR for CA_NS_203	178
6.2A.3.0.5	[Reserved]	179
6.2A.3.0.6	A-MPR for CA_NS_205	179
6.2A.3.1	UE maximum output power with additional requirements for CA (2UL CA).....	179
6.2A.3.2	UE maximum output power with additional requirements for CA (3UL CA).....	187
6.2A.3.3	UE maximum output power with additional requirements for CA (4UL CA).....	194
6.2A.3.4	UE maximum output power with additional requirements for CA (5UL CA).....	201
6.2A.3.5	UE maximum output power with additional requirements for CA (6UL CA).....	201
6.2A.3.6	UE maximum output power with additional requirements for CA (7UL CA).....	201
6.2A.3.7	UE maximum output power with additional requirements for CA (8UL CA).....	201
6.2A.4	Configured transmitted power for CA	201
6.2A.4.0	Minimum conformance requirements	201
6.2A.4.1	Configured transmitted power for CA (2UL CA)	202
6.2A.4.2	Configured transmitted power for CA (3UL CA)	203
6.2A.4.3	Configured transmitted power for CA (4UL CA)	203
6.2A.4.4	Configured transmitted power for CA (5UL CA)	203
6.2A.4.5	Configured transmitted power for CA (6UL CA)	203
6.2A.4.6	Configured transmitted power for CA (7UL CA)	203
6.2A.4.7	Configured transmitted power for CA (8UL CA)	203
6.2A.5	UE maximum output power - EIRP and TRP for CA (2UL CA) with UL Gaps.....	203
6.2D	Transmit power for UL MIMO	206
6.2D.1	UE maximum output power for UL MIMO.....	206
6.2D.1.0	General	206
6.2D.1.1	UE maximum output power - EIRP and TRP for UL MIMO	206
6.2D.1.2	UE maximum output power - Spherical coverage for UL MIMO	215
6.2D.2	UE maximum output power reduction for UL MIMO.....	219
6.2D.3	UE maximum output power with additional requirements for UL MIMO	231
6.2D.4	Configured transmitted power for UL MIMO	243
6.2K	Transmitter power for simultaneous transmission to multiple directions.....	244
6.2K.1	UE maximum output power for simultaneous transmission to multiple directions	244
6.2K.1.1	UE maximum output power - EIRP and TRP	244
6.2K.1.2	UE spherical coverage for simultaneous transmission to multiple directions	246
6.2K.2	UE maximum output power reduction for simultaneous transmission to multiple directions	247
6.3	Output power dynamics.....	248
6.3.1	Minimum output power	248
6.3.2	Transmit OFF power.....	252
6.3.3	Transmit ON/OFF time mask	254
6.3.3.1	General	254
6.3.3.2	General ON/OFF time mask	255
6.3.3.3	Transmit power time mask for slot and short or long subslot boundaries.....	258
6.3.3.4	PRACH time mask.....	258
6.3.3.5	Void.....	262
6.3.3.6	SRS time mask	262
6.3.3.7	PUSCH-PUCCH and PUSCH-SRS time masks	267
6.3.3.8	Transmit power time mask for consecutive slot or long subslot transmission and short subslot transmission boundaries	267
6.3.3.9	Transmit power time mask for consecutive short subslot transmissions boundaries	267
6.3.4	Power control.....	267
6.3.4.1	General	267
6.3.4.2	Absolute power tolerance.....	267
6.3.4.3	Relative power tolerance	272
6.3.4.4	Aggregate power tolerance.....	282

6.3A	Output power dynamics for CA	286
6.3A.1	Minimum output power for CA	286
6.3A.1.0	Minimum conformance requirements	286
6.3A.1.1	Minimum output power for CA (2UL CA)	287
6.3A.1.2	Minimum output power for CA (3UL CA)	290
6.3A.1.3	Minimum output power for CA (4UL CA)	292
6.3A.1.4	Minimum output power for CA (5UL CA)	294
6.3A.1.5	Minimum output power for CA (6UL CA)	296
6.3A.1.6	Minimum output power for CA (7UL CA)	298
6.3A.1.7	Minimum output power for CA (8UL CA)	300
6.3A.2	Transmit OFF power for CA	302
6.3A.2.0	Minimum conformance requirements	302
6.3A.2.1	Void.....	303
6.3A.2.2	Void.....	303
6.3A.2.3	Void.....	303
6.3A.3	Transmit ON/OFF time mask for CA	303
6.3A.3.0	Minimum conformance requirements	303
6.3A.3.1	General ON/OFF time mask for CA	303
6.3A.3.1.1	General ON/OFF time mask for CA (2UL CA)	303
6.3A.3.1.2	General ON/OFF time mask for CA (3UL CA)	306
6.3A.3.1.3	General ON/OFF time mask for CA (4UL CA)	308
6.3A.3.1.4	General ON/OFF time mask for CA (5UL CA)	309
6.3A.3.1.5	General ON/OFF time mask for CA (6UL CA)	309
6.3A.3.1.6	General ON/OFF time mask for CA (7UL CA)	309
6.3A.3.1.7	General ON/OFF time mask for CA (8UL CA)	309
6.3A.4	Power control for CA.....	310
6.3A.4.1	General	310
6.3A.4.2	Absolute power tolerance for CA.....	310
6.3A.4.2.0	Minimum conformance requirements	310
6.3A.4.2.1	Absolute power tolerance for CA (2UL CA).....	310
6.3A.4.2.2	Absolute power tolerance for CA (3UL CA).....	313
6.3A.4.2.3	Absolute power tolerance for CA (4UL CA).....	314
6.3A.4.2.4	Absolute power tolerance for CA (5UL CA).....	315
6.3A.4.2.5	Absolute power tolerance for CA (6UL CA).....	317
6.3A.4.2.6	Absolute power tolerance for CA (7UL CA).....	319
6.3A.4.2.7	Absolute power tolerance for CA (8UL CA).....	321
6.3A.4.3	Relative power tolerance for CA.....	324
6.3A.4.3.0	Minimum conformance requirements.....	324
6.3A.4.3.1	Relative power tolerance for CA (2UL CA).....	324
6.3A.4.3.2	Relative power tolerance for CA (3UL CA).....	324
6.3A.4.3.3	Relative power tolerance for CA (4UL CA).....	324
6.3A.4.3.4	Relative power tolerance for CA (5UL CA).....	324
6.3A.4.3.5	Relative power tolerance for CA (6UL CA).....	324
6.3A.4.3.6	Relative power tolerance for CA (7UL CA).....	324
6.3A.4.3.7	Relative power tolerance for CA (8UL CA).....	324
6.3A.4.4	Aggregate power tolerance for CA	324
6.3A.4.4.0	Minimum conformance requirements.....	324
6.3A.4.4.1	Aggregate power tolerance for CA (2UL CA)	324
6.3A.4.4.2	Aggregate power tolerance for CA (3UL CA)	327
6.3A.4.4.3	Aggregate power tolerance for CA (4UL CA)	329
6.3A.4.4.4	Aggregate power tolerance for CA (5UL CA)	330
6.3A.4.4.5	Aggregate power tolerance for CA (6UL CA)	332
6.3A.4.4.6	Aggregate power tolerance for CA (7UL CA)	333
6.3A.4.4.7	Aggregate power tolerance for CA (8UL CA)	335
6.3D	Output power dynamics for UL MIMO	337
6.3D.0	General.....	337
6.3D.1	Minimum output power for UL MIMO	337
6.3D.2	Transmit OFF power for UL MIMO.....	340
6.3D.3	Transmit ON/OFF time mask for UL MIMO	342
6.3D.3.1	General ON/OFF time mask for UL MIMO	342
6.3D.3.2	Void.....	345
6.3D.3.3	Void.....	345

6.3D.3.4	Void.....	345
6.4	Transmit signal quality	345
6.4.1	Frequency error.....	345
6.4.2	Transmit modulation quality.....	347
6.4.2.1	Error vector magnitude	348
6.4.2.1_1	Error vector magnitude with Power Boost.....	355
6.4.2.2	Carrier leakage	357
6.4.2.3	In-band emissions	362
6.4.2.4	EVM equalizer spectrum flatness	375
6.4.2.5	EVM spectral flatness for pi/2 BPSK modulation	378
6.4.2.6	Phase continuity requirements for DMRS bundling	381
6.4A	Transmit signal quality for CA.....	386
6.4A.1	Frequency error for CA.....	386
6.4A.1.0	Minimum conformance requirements.....	386
6.4A.1.1	Frequency error for CA (2UL CA).....	386
6.4A.1.2	Frequency error for CA (3UL CA).....	388
6.4A.1.3	Frequency error for CA (4UL CA).....	389
6.4A.1.4	Frequency error for CA (5UL CA).....	390
6.4A.1.5	Frequency error for CA (6UL CA).....	392
6.4A.1.6	Frequency error for CA (7UL CA).....	394
6.4A.1.7	Frequency error for CA (8UL CA).....	395
6.4A.2	Transmit modulation quality for CA.....	398
6.4A.2.0	General.....	398
6.4A.2.1	Error vector magnitude for CA	398
6.4A.2.1.0	Minimum conformance requirements.....	398
6.4A.2.1.1	Error vector magnitude for CA (2UL CA)	398
6.4A.2.1.2	Error vector magnitude for CA (3UL CA)	401
6.4A.2.1.3	Error vector magnitude for CA (4UL CA)	404
6.4A.2.1.4	Error Vector magnitude for CA (5UL CA)	406
6.4A.2.1.5	Error Vector magnitude for CA (6UL CA)	409
6.4A.2.1.6	Error vector magnitude for CA (7UL CA)	412
6.4A.2.1.7	Error vector magnitude for CA (8UL CA)	415
6.4A.2.2	Carrier leakage for CA.....	418
6.4A.2.2.0	Minimum conformance requirements.....	418
6.4A.2.2.1	Carrier leakage for CA (2UL CA).....	419
6.4A.2.2.2	Carrier leakage for CA (3UL CA).....	422
6.4A.2.2.3	Carrier leakage for CA (4UL CA).....	424
6.4A.2.2.4	Carrier leakage for CA (5UL CA).....	425
6.4A.2.2.5	Carrier leakage for CA (6UL CA).....	427
6.4A.2.2.6	Carrier leakage for CA (7UL CA).....	428
6.4A.2.2.7	Carrier leakage for CA (8UL CA).....	429
6.4A.2.3	In-band emissions for CA	431
6.4A.2.3.0	Minimum conformance requirements.....	431
6.4A.2.3.1	In-band emissions for CA (2UL CA)	435
6.4A.2.3.2	In-band emissions for CA (3UL CA)	441
6.4A.2.3.3	In-band emissions for CA (4UL CA)	445
6.4A.2.3.4	In-band emissions for CA (5UL CA)	449
6.4A.2.3.5	In-band emissions for CA (6UL CA)	453
6.4A.2.3.6	In-band emissions for CA (7UL CA)	458
6.4A.2.3.7	In-band emissions for CA (8UL CA)	462
6.4A.2.4	EVM equalizer spectrum flatness for CA	466
6.4A.2.4.0	Minimum conformance requirements.....	466
6.4A.2.4.1	EVM equalizer spectrum flatness for CA (2UL CA)	466
6.4A.2.4.2	EVM equalizer spectrum flatness for CA (3UL CA)	469
6.4A.2.4.3	EVM equalizer spectrum flatness for CA (4UL CA)	471
6.4A.2.4.4	EVM equalizer spectrum flatness for CA (5UL CA)	473
6.4A.2.4.5	EVM equalizer spectrum flatness for CA (6UL CA)	475
6.4A.2.4.6	EVM equalizer spectrum flatness for CA (7UL CA)	477
6.4A.2.4.7	EVM equalizer spectrum flatness for CA (8UL CA)	479
6.4A.2.5	Void.....	481
6.4D	Transmit signal quality for UL MIMO.....	481
6.4D.0	General.....	481

6.4D.1	Frequency error for UL MIMO.....	481
6.4D.2	Transmit signal quality for UL MIMO	483
6.4D.2.1	Error vector magnitude for UL MIMO	483
6.4D.2.2	Carrier leakage for UL MIMO	486
6.4D.2.3	In-band emissions for UL MIMO	490
6.4D.2.4	EVM equalizer spectrum flatness for UL MIMO	500
6.4D.3	Time alignment error for UL MIMO	506
6.5	Output RF spectrum emissions.....	509
6.5.1	Occupied bandwidth	509
6.5.2	Out of band emission	512
6.5.2.1	Spectrum Emission Mask.....	512
6.5.2.1_1	Spectrum Emission Mask with Power Boost	515
6.5.2.2	Void.....	516
6.5.2.3	Adjacent channel leakage ratio	516
6.5.3	Spurious emissions	521
6.5.3.1	Transmitter Spurious emissions	521
6.5.3.1_1	Transmitter Spurious emissions with Power Boost.....	526
6.5.3.2	Spurious emission band UE co-existence	527
6.5.3.2_1	Spurious emission band UE co-existence with Power Boost.....	531
6.5.3.3	Additional spurious emissions	533
6.5.3.3_1	Additional spurious emissions with Power Boost	539
6.5A	Output RF spectrum emissions for CA.....	540
6.5A.1	Occupied bandwidth for CA	540
6.5A.1.0	Minimum conformance requirements	540
6.5A.1.1	Occupied bandwidth for CA (2UL CA)	540
6.5A.1.2	Occupied bandwidth for CA (3UL CA)	543
6.5A.1.3	Occupied bandwidth for CA (4UL CA)	544
6.5A.1.4	Occupied bandwidth for CA (5UL CA)	545
6.5A.1.5	Occupied bandwidth for CA (6UL CA)	546
6.5A.1.6	Occupied bandwidth for CA (7UL CA)	547
6.5A.1.7	Occupied bandwidth for CA (8UL CA)	548
6.5A.2	Out of band emission for CA	549
6.5A.2.1	Spectrum Emission Mask for CA.....	549
6.5A.2.1.0	Minimum conformance requirements.....	549
6.5A.2.1.1	Spectrum Emission Mask for CA (2UL CA).....	550
6.5A.2.1.2	Spectrum Emission Mask for CA (3UL CA).....	554
6.5A.2.1.3	Spectrum Emission Mask for CA (4UL CA).....	555
6.5A.2.1.4	Spectrum Emission Mask for CA (5UL CA).....	556
6.5A.2.1.5	Spectrum Emission Mask for CA (6UL CA).....	557
6.5A.2.1.6	Spectrum Emission Mask for CA (7UL CA).....	558
6.5A.2.1.7	Spectrum Emission Mask for CA (8UL CA).....	559
6.5A.2.2	Adjacent channel leakage ratio for CA	560
6.5A.2.2.0	Minimum conformance requirements.....	560
6.5A.2.2.1	Adjacent channel leakage ratio for CA (2UL CA)	561
6.5A.2.2.2	Adjacent channel leakage ratio for CA (3UL CA)	565
6.5A.2.2.3	Adjacent channel leakage ratio for CA (4UL CA)	566
6.5A.2.2.4	Adjacent channel leakage ratio for CA (5UL CA)	567
6.5A.2.2.5	Adjacent channel leakage ratio for CA (6UL CA)	568
6.5A.2.2.6	Adjacent channel leakage ratio for CA (7UL CA)	569
6.5A.2.2.7	Adjacent channel leakage ratio for CA (8UL CA)	570
6.5A.3	Spurious emissions for CA	571
6.5A.3.1	General spurious emissions for CA.....	571
6.5A.3.1.0	Minimum conformance requirements.....	571
6.5A.3.1.1	General spurious emissions for CA (2UL CA).....	571
6.5A.3.1.2	General spurious emissions for CA (3UL CA).....	576
6.5A.3.1.3	General spurious emissions for CA (4UL CA).....	576
6.5A.3.1.4	General spurious emissions for CA (5UL CA).....	577
6.5A.3.1.5	General spurious emissions for CA (6UL CA).....	577
6.5A.3.1.6	General spurious emissions for CA (7UL CA).....	578
6.5A.3.1.7	General spurious emissions for CA (8UL CA).....	578
6.5A.3.2	Spurious emission band UE co-existence for UL CA	579
6.5A.3.2.0	Minimum conformance requirements.....	579

6.5A.3.2.1	Spurious emission band UE co-existence for CA (2UL CA)	580
6.5A.3.2.2	Spurious emission band UE co-existence for CA (3UL CA)	584
6.5A.3.2.3	Spurious emission band UE co-existence for CA (4UL CA)	585
6.5A.3.2.4	Spurious emission band UE co-existence for CA (5UL CA)	585
6.5A.3.2.5	Spurious emission band UE co-existence for CA (6UL CA)	586
6.5A.3.2.6	Spurious emission band UE co-existence for CA (7UL CA)	587
6.5A.3.2.7	Spurious emission band UE co-existence for CA (8UL CA)	587
6.5A.3.3	Additional spurious emissions for CA	588
6.5A.3.3.0	Minimum conformance requirements.....	588
6.5A.3.3.1	Additional spurious emissions for CA (2UL CA)	589
6.5A.3.3.2	Additional spurious emissions for CA (3UL CA)	595
6.5A.3.3.3	Additional spurious emissions for CA (4UL CA)	596
6.5A.3.3.4	Additional spurious emissions for CA (5UL CA)	596
6.5A.3.3.5	Additional spurious emissions for CA (6UL CA)	597
6.5A.3.3.6	Additional spurious emissions for CA (7UL CA)	597
6.5A.3.3.7	Additional spurious emissions for CA (8UL CA)	598
6.5D	Output RF spectrum emissions for UL MIMO.....	599
6.5D.1	Occupied bandwidth for UL MIMO	599
6.5D.2	Out of band emission for UL MIMO	601
6.5D.2.1	Spectrum Emission Mask for UL MIMO.....	601
6.5D.2.2	Adjacent channel leakage ratio for UL MIMO	602
6.5D.3	Spurious emissions for UL MIMO	605
6.5D.3.1	Transmitter Spurious emissions for UL MIMO	605
6.5D.3.2	Spurious emission band UE co-existence for UL MIMO	606
6.5D.3.3	Additional spurious emissions for UL MIMO	606
6.6	Beam correspondence.....	607
6.6.0	General.....	607
6.6.1	Beam correspondence - EIRP	608
6.6.2	Enhanced Beam correspondence – EIRP.....	618
6.6.3	Beam Correspondence in RRC_INACTIVE and initial access	625
6.6A	Beam correspondence for CA	626
7	Receiver characteristics.....	626
7.1	General	626
7.2	Diversity characteristics	627
7.3	Reference sensitivity	627
7.3.1	General.....	627
7.3.2	Reference sensitivity power level	627
7.3.4	EIS spherical coverage.....	636
7.3A	Reference sensitivity for CA	643
7.3A.1	General.....	643
7.3A.2	Reference sensitivity power level for CA	643
7.3A.2.0	Minimum Conformance Requirements.....	643
7.3A.2.0.1	Intra-band contiguous CA	643
7.3A.2.0.2	Intra-band non-contiguous CA	643
7.3A.2.0.3	Inter-band CA.....	643
7.3A.2.1	Reference sensitivity power level for CA (2DL CA).....	644
7.3A.2.2	Reference sensitivity power level for CA (3DL CA).....	649
7.3A.2.3	Reference sensitivity power level for CA (4DL CA).....	649
7.3A.2.4	Reference sensitivity power level for CA (5DL CA).....	650
7.3A.2.5	Reference sensitivity power level for CA (6DL CA).....	650
7.3A.2.6	Reference sensitivity power level for CA (7DL CA).....	651
7.3A.2.7	Reference sensitivity power level for CA (8DL CA).....	651
7.3A.3	EIS spherical coverage for DL CA	652
7.3A.3.0	Minimum Conformance Requirements.....	652
7.3A.3.0.1	Void.....	652
7.3A.3.0.2	Void.....	652
7.3A.3.0.3	EIS spherical coverage for inter-band CA.....	652
7.3A.3.1	EIS Spherical Coverage for Inter-band CA (2DL CA)	653
7.3A.3.2	EIS Spherical Coverage for Inter-band CA (3DL CA)	656
7.3A.3.3	EIS Spherical Coverage for Inter-band CA (4DL CA)	657
7.3D	Reference sensitivity for UL MIMO	657

7.3K	Spherical coverage requirement for simultaneous reception from multiple directions	658
7.3K.1	Spherical coverage with two Angle of Arrivals (AoAs) with simultaneous reception from multiple directions	658
7.3K.1.0	General	658
7.3K.1.1	UE spherical coverage for simultaneous reception from multiple directions (2 AoAs).....	658
7.4	Maximum input level	662
7.4A	Maximum input level for CA	665
7.4A.0	Minimum Conformance Requirements.....	665
7.4A.0.1	Maximum input level for Intra-band contiguous CA	665
7.4A.0.2	Maximum input level for Intra-band non-contiguous CA	665
7.4A.0.3	Maximum input level for inter-band CA.....	665
7.4A.1	Maximum input level for CA (2DL CA)	665
7.4A.2	Maximum input level for CA (3DL CA)	669
7.4A.3	Maximum input level for CA (4DL CA)	669
7.4A.4	Maximum input level for CA (5DL CA)	670
7.4A.5	Maximum input level for CA (6DL CA)	670
7.4A.6	Maximum input level for CA (7DL CA)	671
7.4A.7	Maximum input level for CA (8DL CA)	671
7.4D	Maximum input level for UL MIMO	672
7.5	Adjacent channel selectivity	672
7.5A	Adjacent channel selectivity for CA.....	678
7.5A.0	Minimum Conformance Requirements.....	678
7.5A.0.1	Adjacent channel selectivity for Intra-band contiguous CA	678
7.5A.0.2	Adjacent channel selectivity for Intra-band non-contiguous CA	679
7.5A.0.3	Adjacent channel selectivity for Inter-band CA	679
7.5A.1	Adjacent channel selectivity for CA (2DL CA).....	680
7.5A.2	Adjacent channel selectivity for CA (3DL CA).....	680
7.5A.3	Adjacent channel selectivity for CA (4DL CA).....	680
7.5A.4	Adjacent channel selectivity for CA (5DL CA).....	680
7.5A.5	Adjacent channel selectivity for CA (6DL CA).....	680
7.5A.6	Adjacent channel selectivity for CA (7DL CA).....	680
7.5A.7	Adjacent channel selectivity for CA (8DL CA).....	680
7.5D	Adjacent channel selectivity for UL MIMO.....	680
7.6	Blocking characteristics	680
7.6.1	General.....	680
7.6.2	In-band blocking	681
7.6.3	Void	686
7.6A	Blocking characteristics for CA	686
7.6A.1	General.....	686
7.6A.2	In-band blocking for CA.....	686
7.6A.2.0	Minimum Conformance Requirements.....	686
7.6A.2.0.1	In-band blocking for Intra-band contiguous CA.....	686
7.6A.2.0.2	In-band blocking for Intra-band non-contiguous CA	687
7.6A.2.0.3	In-band blocking for Inter-band CA	687
7.6A.2.1	In-band blocking for CA (2DL CA).....	687
7.6A.2.2	Void.....	690
7.6A.2.3	Void.....	690
7.6A.2.4	Void.....	690
7.6A.2.5	Void.....	690
7.6A.2.6	Void.....	690
7.6A.2.7	Void.....	690
7.6D	Blocking characteristics for UL MIMO	690
7.7	Void.....	690
7.8	Void.....	690
7.9	Spurious emissions	690
7.10	Void.....	693
Annex A (normative):	Measurement channels	694
A.1	General	694
A.2	UL reference measurement channels	694
A.2.1	General	694

A.2.2	Void.....	694
A.2.3	Reference measurement channels for TDD.....	695
A.2.3.1	DFT-s-OFDM Pi/2-BPSK	696
A.2.3.2	DFT-s-OFDM QPSK.....	696
A.2.3.3	DFT-s-OFDM 16QAM.....	697
A.2.3.4	DFT-s-OFDM 64QAM.....	698
A.2.3.5	CP-OFDM QPSK	699
A.2.3.6	CP-OFDM 16QAM	699
A.2.3.7	CP-OFDM 64QAM	700
A.3	DL reference measurement channels	702
A.3.1	General	702
A.3.2	Void.....	704
A.3.3	DL reference measurement channels for TDD.....	704
A.3.3.1	General.....	704
A.3.3.2	FRC for receiver requirements for QPSK.....	704
A.3.3.3	FRC for receiver requirements for 16QAM.....	706
A.3.3.4	FRC for receiver requirements for 64QAM.....	706
A.3.3.5	FRC for receiver requirements for 256QAM.....	707
A.4	Void.....	709
A.5	OFDMA Channel Noise Generator (OCNG)	709
A.5.1	OCNG Patterns for FDD	709
A.5.2	OCNG Patterns for TDD.....	709
A.5.2.1	OCNG TDD pattern 1: Generic OCNG TDD Pattern for all unused REs	709
A.6	FR2 RF tests with testability issues.....	709
A.6.1	FR2 RF tests with testability issues not related to Measurement Uncertainty (MU).....	709
Annex B (normative): Propagation conditions.....		711
B.0	No interference.....	711
Annex C (normative): Downlink Physical Channels.....		712
C.0	Downlink signal levels	712
C.1	General	713
C.2	Setup.....	713
C.3	Connection	714
C.3.0	Measurement of Transmitter Characteristics.....	714
C.3.1	Measurement of Receiver Characteristics	715
Annex D (normative): Characteristics of the interfering signal		716
D.1	General	716
D.2	Interference signals.....	716
Annex E (normative): Global In-Channel TX-Test		717
E.1	General	717
E.2	Signals and results	717
E.2.1	Basic principle.....	717
E.2.2	Output signal of the TX under test	717
E.2.3	Reference signal	717
E.2.4	Measurement results.....	718
E.2.5	Measurement points	718
E.3	Signal processing.....	718
E.3.1	Pre FFT minimization process.....	718
E.3.2	Timing of the FFT window	719
E.3.3	Post FFT equalisation.....	720

E.4	Derivation of the results	721
E.4.1	EVM	721
E.4.2	Averaged EVM	721
E.4.3	In-band emissions measurement	722
E.4.4	EVM equalizer spectrum flatness	724
E.4.5	Frequency error and Carrier leakage	725
E.4.6	EVM of Demodulation reference symbols (EVM _{DMRS})	725
E.4.6.1	1 st average for EVM _{DMRS}	726
E.4.6.2	Final average for EVM _{DMRS}	726
E.5	EVM and inband emissions for PUCCH	726
E.5.1	Basic principle	726
E.5.2	Output signal of the TX under test	726
E.5.3	Reference signal	726
E.5.4	Measurement results	727
E.5.5	Measurement points	727
E.5.6	Pre FFT minimization process	727
E.5.7	Timing of the FFT window	727
E.5.8	Post FFT equalisation	727
E.5.9	Derivation of the results	728
E.5.9.1	EVM _{PUCCH}	728
E.5.9.2	Averaged EVM _{PUCCH}	728
E.5.9.3	In-band emissions measurement	729
E.5.10	Modified signal under test	730
E.6	EVM for PRACH	732
E.6.1	Basic principle	732
E.6.2	Output signal of the TX under test	732
E.6.3	Reference signal	732
E.6.4	Measurement results	732
E.6.5	Measurement points	733
E.6.6	Pre FFT minimization process	733
E.6.7	Timing of the FFT window	733
E.6.8	Post FFT equalisation	734
E.6.9	Derivation of the results	734
E.6.9.1	EVM _{PRACH}	734
E.6.9.2	Averaged EVM _{PRACH}	735
E.6.10	Modified signal under test	735
E.6.11	Phase offset measurement for DMRS bundling	735
E.6.11.1	Measurement point	735
E.6.11.2	Symbols used	735
E.6.11.3	Modified test signal	735
E.6.11.4	Phase offset measurement	735
E.6.12	Void	736
E.7	EVM for dual transmit polarizations	736
E.7.1	General	736
E.7.2	MIMO Equalization (UL MIMO transmission)	736
E.7.3	Maximum Ratio combining (Tx diversity transmission)	737
E.7.4	Layer processing	737
Annex F (normative):	Measurement uncertainties and Test Tolerances	739
F.1	Acceptable uncertainty of Test System (normative)	739
F.1.0	General	739
F.1.1	Measurement of test environments	739
F.1.2	Measurement of transmitter	739
F.1.3	Measurement of receiver	761
F.2	Interpretation of measurement results (normative)	764
F.3	Test Tolerance and Derivation of Test Requirements (informative)	765
F.3.1	Measurement of test environments	765
F.3.2	Measurement of transmitter	765
F.3.3	Measurement of receiver	783

F.4	Uplink power window	786
F.4.1	Introduction	786
F.4.2	Setting the power window above a requirement.....	786
F.4.3	Setting the power window below a requirement	786
F.4.4	Setting the power window centred on a target value	786
F.8	FFS	787
F.9	FFS	787
F.10	FFS	787
Annex G (normative): Uplink Physical Channels		788
G.0	Uplink Signal Levels	788
G.1	General	788
G.2	Set-up	788
G.3	Connection	788
G.3.0	Measurement of Transmitter Characteristics.....	788
G.3.1	Measurement of Receiver Characteristics	788
Annex H (normative): Statistical Testing.....		789
H.1	General	789
H.2	Statistical testing of receiver characteristics.....	789
H.2.1	General	789
H.2.2	Mapping throughput to error ratio.....	789
H.2.3	Design of the test.....	790
H.2.4	Numerical definition of the pass fail limits	790
H.2.5	Pass fail decision rules	791
H.2.6	Theory to derive the pass fail limits (Informative).....	791
H.2.6.1	Numerical definition of the pass-fail limits	791
H.2.6.2	Simulation to derive the pass-fail limits for testing 95% throughput.....	792
Annex I: Void		794
Annex J (normative): Test applicability per permitted test method		795
Annex K (normative): EIRP, TRP, and EIS measurement procedures.....		796
K.1	Direct far field (DFF)	796
K.1.1	TX beam peak direction search	796
K.1.2	RX beam peak direction search.....	798
K.1.3	Peak EIRP measurement procedure	800
K.1.4	Peak EIS measurement procedure	801
K.1.5	EIRP spherical coverage	801
K.1.5.0	Tx Spherical Coverage Method	801
K.1.5.1	Tx Fast Spherical Coverage Method.....	802
K.1.5.1.1	Introduction	802
K.1.5.1.2	Description	802
K.1.5.1.3	Measurement uncertainties.....	802
K.1.6	EIS spherical coverage	802
K.1.6.0	Rx Spherical Coverage Method	802
K.1.6.1	Rx Fast Spherical Coverage Method	803
K.1.6.1.1	Introduction.....	803
K.1.6.1.2	Description	803
K.1.6.1.3	Measurement uncertainties.....	803
K.1.7	TRP measurement procedure	803
K.1.8	Blocking measurement procedure	804
K.1.9	Beam Correspondence tolerance procedure	804
K.1.11	RSRP(B) based RX beam peak search	805
K.1.11.1	Test procedure	805

K.1.12	Enhanced test method for EIRP measurements	806
K.1.12.1	Applicability of TPMI side condition method	807
K.1.12.2	TPMI side condition method Measurement uncertainties impact	807
K.2	Direct far field (DFF) simplification	807
K.2.1	TX beam peak direction search	807
K.2.2	RX beam peak direction search	807
K.2.3	Peak EIRP measurement procedure	807
K.2.4	Peak EIS measurement procedure	807
K.2.5	EIRP spherical coverage	807
K.2.6	EIS spherical coverage	808
K.2.7	TRP measurement procedure	808
K.2.8	Blocking measurement procedure	808
K.3	Indirect far field (IFF)	808
K.3.1	TX beam peak direction search	808
K.3.2	RX beam peak direction search	808
K.3.3	Peak EIRP measurement procedure	808
K.3.4	Peak EIS measurement procedure	808
K.3.5	EIRP spherical coverage	808
K.3.6	EIS spherical coverage	808
K.3.7	TRP measurement procedure	808
K.3.8	Blocking measurement procedure	808
K.4	Near field to far field transform (NFTF)	809
K.4.1	TX beam peak direction search	809
K.4.2	RX beam peak direction search	809
K.4.3	Peak EIRP measurement procedure	809
K.4.4	Peak EIS measurement procedure	809
K.4.5	EIRP spherical coverage	809
K.4.6	EIS spherical coverage	809
K.4.7	TRP measurement procedure	809
K.4.8	Blocking measurement procedure	810
Annex L (normative):	Void	811
Annex M:(normative) Measurement grids.....		812
M.1	Grid Types.....	812
M.2	Beam Peak Search Grid.....	814
M.2.1	UE Power classes	814
M.2.1.1	Power class 1 devices	814
M.2.1.2	Power class 2 devices	815
M.2.1.3	Power class 3 devices	815
M.2.1.4	Power class 4 devices	817
M.2.1.5	Power class 5 devices	817
M.2.1.6	Power class 6 devices	817
M.2.2	Coarse and fine measurement grids.....	817
M.3	Spherical Coverage Grid	821
M.3.1	EIRP spherical coverage	821
M.3.1.1	UE Power classes.....	821
M.3.1.1.1	Power class 1 devices.....	821
M.3.1.1.2	Power class 2 devices.....	822
M.3.1.1.3	Power class 3 devices.....	822
M.3.1.1.4	Power class 4 devices.....	823
M.3.1.1.5	Power class 5 devices.....	823
M.3.1.1.6	Power class 6 devices.....	823
clause M.3.2 EIS spherical coverage	823
M.3.2.1	UE Power classes.....	823
M.3.2.1.1	Power class 1 devices.....	823
M.3.2.1.2	Power class 2 devices.....	824