

ETSI TS 138 521-2 V19.2.0 (2026-04)



TECHNICAL SPECIFICATION

**5G;
NR;
User Equipment (UE) conformance specification;
Radio transmission and reception;
Part 2: Range 2 standalone
(3GPP TS 38.521-2 version 19.2.0 Release 19)**



Reference

RTS/TSGR-0538521-2vj20

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed, this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our [Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2026.

All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by the ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found at [3GPP to ETSI numbering cross-referencing](#).

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	17
1 Scope	18
2 References	18
3 Definitions, symbols and abbreviations	19
3.1 Definitions	19
3.2 Symbols.....	21
3.3 Abbreviations	23
4 General	24
4.1 Relationship between minimum requirements and test requirements	24
4.2 Applicability of minimum requirements	25
4.3 Specification suffix information.....	25
4.4 Test point analysis.....	26
4.5 Applicability and test coverage rules.....	26
5 Operating bands and channel arrangement.....	26
5.1 General	26
5.2 Operating bands.....	27
5.2A Operating bands for CA	27
5.2A.2 Void	27
5.2A.3 Inter-band CA	27
5.2D Operating bands for UL MIMO	27
5.2K Operating bands for simultaneous reception or transmission in multiple directions	28
5.3 UE Channel bandwidth	28
5.3.1 General.....	28
5.3.2 Maximum transmission bandwidth configuration	29
5.3.3 Minimum guardband and transmission bandwidth configuration.....	29
5.3.4 RB alignment	31
5.3.5 Channel bandwidth per operating band	31
5.3A UE Channel bandwidth for CA	31
5.3A.1 General.....	31
5.3A.2 Minimum guardband and transmission bandwidth configuration for CA	31
5.3A.3 RB alignment with different numerologies for CA.....	33
5.3A.4 UE channel bandwidth per operating band for CA.....	33
5.3D Channel bandwidth for UL MIMO.....	35
5.4 Channel arrangement.....	35
5.4.1 Channel spacing.....	35
5.4.1.1 Channel spacing for adjacent NR carriers	35
5.4.2 Channel raster	35
5.4.2.1 NR-ARFCN and channel raster.....	35
5.4.2.2 Channel raster to resource element mapping.....	36
5.4.2.3 Channel raster entries for each operating band	36
5.4.3 Synchronization raster	37
5.4.3.1 Synchronization raster and numbering.....	37
5.4.3.2 Synchronization raster to synchronization block resource element mapping.....	37
5.4.3.3 Synchronization raster entries for each operating band.....	37
5.4A Channel arrangement for CA.....	38
5.4A.1 Channel spacing for CA.....	38
5.5 Configurations	39
5.5A Configurations for CA.....	39
5.5A.1 Configurations for intra-band contiguous CA.....	39
5.5A.2 Configurations for intra-band non-contiguous CA	40

5.5A.3	Configurations for inter-band CA	44
5.5D	Configurations for UL MIMO	44
6	Transmitter characteristics	45
6.1	General	45
6.2	Transmit power	47
6.2.1	UE maximum output power	47
6.2.1.0	General	47
6.2.1.1	UE maximum output power - EIRP and TRP	48
6.2.1.1_1	UE maximum output power - EIRP and TRP (Rel16 and forward)	60
6.2.1.2	UE maximum output power - Spherical coverage	62
6.2.1.2_1	UE maximum output power - Spherical coverage (Rel16 and forward)	68
6.2.2	UE maximum output power reduction	69
6.2.2.0	General	69
6.2.2.3.1	UE maximum output power reduction for power class 1	70
6.2.2.3.2	UE maximum output power reduction for power class 2	71
6.2.2.3.3	UE maximum output power reduction for power class 3	72
6.2.2.3.4	UE maximum output power reduction for power class 4	73
6.2.2.3.5	UE maximum output power reduction for power class 5	73
6.2.2.3.6	UE maximum output power reduction for power class 6	73
6.2.2.3.7	UE maximum output power reduction for power class 7	73
6.2.2_1	UE maximum output power reduction enhancements	89
6.2.2_1.0	General	89
6.2.3	UE maximum output power with additional requirements	96
6.2.3.3.1	General	96
6.2.3.3.2	Void	97
6.2.3.3.3	A-MPR for NS_202	97
6.2.3.3.4	A-MPR for NS_203	98
6.2.3.3.5	[Reserved]	98
6.2.3.3.6	A-MPR for NS_205	98
6.2.4	Configured transmitted power	108
6.2.4_1	Configured transmitted power with Power Boost	109
6.2.5	UE maximum output power – EIRP with UL Gaps	111
6.2A	Transmit power for CA	115
6.2A.1	UE maximum output power for CA	115
6.2A.1.0	Minimum conformance requirements	115
6.2A.1.1	UE maximum output power - EIRP and TRP for CA	115
6.2A.1.1.1	UE maximum output power - EIRP and TRP for CA (2UL CA)	115
6.2A.1.1.2	UE maximum output power - EIRP and TRP for CA (3UL CA)	120
6.2A.1.1.3	UE maximum output power - EIRP and TRP for CA (4UL CA)	122
6.2A.1.1.4	UE maximum output power - EIRP and TRP for CA (5UL CA)	124
6.2A.1.1.5	UE maximum output power - EIRP and TRP for CA (6UL CA)	125
6.2A.1.1.6	UE maximum output power - EIRP and TRP for CA (7UL CA)	125
6.2A.1.1.7	UE maximum output power - EIRP and TRP for CA (8UL CA)	125
6.2A.1.2	UE maximum output power - Spherical coverage	126
6.2A.1.2.1	UE maximum output power - Spherical coverage for CA (2UL CA)	126
6.2A.1.2.2	UE maximum output power - Spherical coverage for CA (3UL CA)	130
6.2A.1.2.3	UE maximum output power - Spherical coverage for CA (4UL CA)	133
6.2A.1.2.4	UE maximum output power - Spherical coverage for CA (5UL CA)	135
6.2A.1.2.5	UE maximum output power - Spherical coverage for CA (6UL CA)	135
6.2A.1.2.6	UE maximum output power - Spherical coverage for CA (7UL CA)	136
6.2A.1.2.7	UE maximum output power - Spherical coverage for CA (8UL CA)	136
6.2A.2	UE maximum output power reduction for CA	136
6.2A.2.0	Minimum conformance requirements	136
6.2A.2.0.1	General	136
6.2A.2.0.2	Maximum output power reduction for power class 1	136
6.2A.2.0.3	Maximum output power reduction for power class 2	139
6.2A.2.0.4	Maximum output power reduction for power class 3	140
6.2A.2.0.5	Maximum output power reduction for power class 4	142
6.2A.2.0.6	Maximum output power reduction for power class 5	142
6.2A.2.0.7	Maximum output power reduction for power class 6	142
6.2A.2.1	UE maximum output power reduction for CA (2UL CA)	142

6.2A.2.2	UE maximum output power reduction for CA (3UL CA).....	165
6.2A.2.3	UE maximum output power reduction for CA (4UL CA).....	171
6.2A.2.4	UE maximum output power reduction for CA (5UL CA).....	178
6.2A.2.5	UE maximum output power reduction for CA (6UL CA).....	178
6.2A.2.6	UE maximum output power reduction for CA (7UL CA).....	178
6.2A.2.7	UE maximum output power reduction for CA (8UL CA).....	178
6.2A.3	UE maximum output power with additional requirements for CA.....	178
6.2A.3.0	Minimum conformance requirements	178
6.2A.3.0.1	General	178
6.2A.3.0.2	Void.....	179
6.2A.3.0.3	A-MPR for CA_NS_202	179
6.2A.3.0.4	A-MPR for CA_NS_203	179
6.2A.3.0.5	[Reserved]	180
6.2A.3.0.6	A-MPR for CA_NS_205	180
6.2A.3.1	UE maximum output power with additional requirements for CA (2UL CA).....	181
6.2A.3.2	UE maximum output power with additional requirements for CA (3UL CA).....	188
6.2A.3.3	UE maximum output power with additional requirements for CA (4UL CA).....	195
6.2A.3.4	UE maximum output power with additional requirements for CA (5UL CA).....	202
6.2A.3.5	UE maximum output power with additional requirements for CA (6UL CA).....	202
6.2A.3.6	UE maximum output power with additional requirements for CA (7UL CA).....	203
6.2A.3.7	UE maximum output power with additional requirements for CA (8UL CA).....	203
6.2A.4	Configured transmitted power for CA	203
6.2A.4.0	Minimum conformance requirements	203
6.2A.4.1	Configured transmitted power for CA (2UL CA)	204
6.2A.4.2	Configured transmitted power for CA (3UL CA)	204
6.2A.4.3	Configured transmitted power for CA (4UL CA)	204
6.2A.4.4	Configured transmitted power for CA (5UL CA)	204
6.2A.4.5	Configured transmitted power for CA (6UL CA)	204
6.2A.4.6	Configured transmitted power for CA (7UL CA)	204
6.2A.4.7	Configured transmitted power for CA (8UL CA)	205
6.2A.5	UE maximum output power - EIRP and TRP for CA (2UL CA) with UL Gaps.....	205
6.2D	Transmit power for UL MIMO	207
6.2D.1	UE maximum output power for UL MIMO.....	207
6.2D.1.0	General	207
6.2D.1.1	UE maximum output power - EIRP and TRP for UL MIMO	208
6.2D.1.2	UE maximum output power - Spherical coverage for UL MIMO	217
6.2D.2	UE maximum output power reduction for UL MIMO.....	220
6.2D.3	UE maximum output power with additional requirements for UL MIMO	233
6.2D.4	Configured transmitted power for UL MIMO	245
6.2K	Transmitter power for simultaneous transmission to multiple directions.....	245
6.2K.1	UE maximum output power for simultaneous transmission to multiple directions	245
6.2K.1.1	UE maximum output power - EIRP and TRP	246
6.2K.1.2	UE spherical coverage for simultaneous transmission to multiple directions	248
6.2K.2	UE maximum output power reduction for simultaneous transmission to multiple directions	248
6.2K.3	UE maximum output power with additional requirements for simultaneous transmission to multiple directions	249
6.2K.4	Configured transmitted power for simultaneous transmission to multiple directions.....	249
6.3	Output power dynamics.....	250
6.3.1	Minimum output power	250
6.3.2	Transmit OFF power.....	255
6.3.3	Transmit ON/OFF time mask	257
6.3.3.1	General	257
6.3.3.2	General ON/OFF time mask	257
6.3.3.3	Transmit power time mask for slot and short or long subslot boundaries.....	260
6.3.3.4	PRACH time mask.....	261
6.3.3.5	Void.....	265
6.3.3.6	SRS time mask	265
6.3.3.7	PUSCH-PUCCH and PUSCH-SRS time masks	269
6.3.3.8	Transmit power time mask for consecutive slot or long subslot transmission and short subslot transmission boundaries	270
6.3.3.9	Transmit power time mask for consecutive short subslot transmissions boundaries	270
6.3.4	Power control.....	270

6.3.4.1	General	270
6.3.4.2	Absolute power tolerance	270
6.3.4.3	Relative power tolerance	275
6.3.4.4	Aggregate power tolerance	284
6.3A	Output power dynamics for CA	288
6.3A.1	Minimum output power for CA	288
6.3A.1.0	Minimum conformance requirements	288
6.3A.1.1	Minimum output power for CA (2UL CA)	289
6.3A.1.2	Minimum output power for CA (3UL CA)	292
6.3A.1.3	Minimum output power for CA (4UL CA)	294
6.3A.1.4	Minimum output power for CA (5UL CA)	297
6.3A.1.5	Minimum output power for CA (6UL CA)	299
6.3A.1.6	Minimum output power for CA (7UL CA)	301
6.3A.1.7	Minimum output power for CA (8UL CA)	304
6.3A.2	Transmit OFF power for CA	306
6.3A.2.0	Minimum conformance requirements	306
6.3A.2.1	Void	307
6.3A.2.2	Void	307
6.3A.2.3	Void	307
6.3A.3	Transmit ON/OFF time mask for CA	307
6.3A.3.0	Minimum conformance requirements	307
6.3A.3.1	General ON/OFF time mask for CA	307
6.3A.3.1.1	General ON/OFF time mask for CA (2UL CA)	307
6.3A.3.1.2	General ON/OFF time mask for CA (3UL CA)	310
6.3A.3.1.3	General ON/OFF time mask for CA (4UL CA)	311
6.3A.3.1.4	General ON/OFF time mask for CA (5UL CA)	313
6.3A.3.1.5	General ON/OFF time mask for CA (6UL CA)	313
6.3A.3.1.6	General ON/OFF time mask for CA (7UL CA)	313
6.3A.3.1.7	General ON/OFF time mask for CA (8UL CA)	313
6.3A.4	Power control for CA	313
6.3A.4.1	General	313
6.3A.4.2	Absolute power tolerance for CA	313
6.3A.4.2.0	Minimum conformance requirements	313
6.3A.4.2.1	Absolute power tolerance for CA (2UL CA)	314
6.3A.4.2.2	Absolute power tolerance for CA (3UL CA)	316
6.3A.4.2.3	Absolute power tolerance for CA (4UL CA)	317
6.3A.4.2.4	Absolute power tolerance for CA (5UL CA)	319
6.3A.4.2.5	Absolute power tolerance for CA (6UL CA)	321
6.3A.4.2.6	Absolute power tolerance for CA (7UL CA)	323
6.3A.4.2.7	Absolute power tolerance for CA (8UL CA)	325
6.3A.4.3	Relative power tolerance for CA	327
6.3A.4.3.0	Minimum conformance requirements	327
6.3A.4.3.1	Relative power tolerance for CA (2UL CA)	328
6.3A.4.3.2	Relative power tolerance for CA (3UL CA)	328
6.3A.4.3.3	Relative power tolerance for CA (4UL CA)	328
6.3A.4.3.4	Relative power tolerance for CA (5UL CA)	328
6.3A.4.3.5	Relative power tolerance for CA (6UL CA)	328
6.3A.4.3.6	Relative power tolerance for CA (7UL CA)	328
6.3A.4.3.7	Relative power tolerance for CA (8UL CA)	328
6.3A.4.4	Aggregate power tolerance for CA	328
6.3A.4.4.0	Minimum conformance requirements	328
6.3A.4.4.1	Aggregate power tolerance for CA (2UL CA)	328
6.3A.4.4.2	Aggregate power tolerance for CA (3UL CA)	331
6.3A.4.4.3	Aggregate power tolerance for CA (4UL CA)	333
6.3A.4.4.4	Aggregate power tolerance for CA (5UL CA)	334
6.3A.4.4.5	Aggregate power tolerance for CA (6UL CA)	336
6.3A.4.4.6	Aggregate power tolerance for CA (7UL CA)	337
6.3A.4.4.7	Aggregate power tolerance for CA (8UL CA)	339
6.3D	Output power dynamics for UL MIMO	341
6.3D.0	General	341
6.3D.1	Minimum output power for UL MIMO	341
6.3D.2	Transmit OFF power for UL MIMO	344

6.3D.3	Transmit ON/OFF time mask for UL MIMO	346
6.3D.3.1	General ON/OFF time mask for UL MIMO	346
6.3D.3.2	Void.....	349
6.3D.3.3	Void.....	349
6.3D.3.4	Void.....	349
6.4	Transmit signal quality	349
6.4.1	Frequency error.....	349
6.4.2	Transmit modulation quality.....	351
6.4.2.1	Error vector magnitude	351
6.4.2.1_1	Error vector magnitude with Power Boost.....	358
6.4.2.2	Carrier leakage	360
6.4.2.3	In-band emissions	365
6.4.2.4	EVM equalizer spectrum flatness	379
6.4.2.5	EVM spectral flatness for pi/2 BPSK modulation	382
6.4.2.6	Phase continuity requirements for DMRS bundling	385
6.4A	Transmit signal quality for CA.....	390
6.4A.1	Frequency error for CA.....	390
6.4A.1.0	Minimum conformance requirements.....	390
6.4A.1.1	Frequency error for CA (2UL CA).....	390
6.4A.1.2	Frequency error for CA (3UL CA).....	392
6.4A.1.3	Frequency error for CA (4UL CA).....	393
6.4A.1.4	Frequency error for CA (5UL CA).....	394
6.4A.1.5	Frequency error for CA (6UL CA).....	396
6.4A.1.6	Frequency error for CA (7UL CA).....	398
6.4A.1.7	Frequency error for CA (8UL CA).....	399
6.4A.2	Transmit modulation quality for CA.....	402
6.4A.2.0	General	402
6.4A.2.1	Error vector magnitude for CA	402
6.4A.2.1.0	Minimum conformance requirements.....	402
6.4A.2.1.1	Error vector magnitude for CA (2UL CA)	402
6.4A.2.1.2	Error vector magnitude for CA (3UL CA)	405
6.4A.2.1.3	Error vector magnitude for CA (4UL CA)	408
6.4A.2.1.4	Error Vector magnitude for CA (5UL CA)	410
6.4A.2.1.5	Error Vector magnitude for CA (6UL CA)	413
6.4A.2.1.6	Error vector magnitude for CA (7UL CA)	416
6.4A.2.1.7	Error vector magnitude for CA (8UL CA)	419
6.4A.2.2	Carrier leakage for CA.....	422
6.4A.2.2.0	Minimum conformance requirements.....	422
6.4A.2.2.0.7	Carrier leakage for power class 6	423
6.4A.2.2.1	Carrier leakage for CA (2UL CA).....	424
6.4A.2.2.2	Carrier leakage for CA (3UL CA).....	426
6.4A.2.2.3	Carrier leakage for CA (4UL CA).....	428
6.4A.2.2.4	Carrier leakage for CA (5UL CA).....	429
6.4A.2.2.5	Carrier leakage for CA (6UL CA).....	431
6.4A.2.2.6	Carrier leakage for CA (7UL CA).....	432
6.4A.2.2.7	Carrier leakage for CA (8UL CA).....	433
6.4A.2.3	In-band emissions for CA	435
6.4A.2.3.0	Minimum conformance requirements.....	435
6.4A.2.3.1	In-band emissions for CA (2UL CA)	439
6.4A.2.3.2	In-band emissions for CA (3UL CA)	445
6.4A.2.3.3	In-band emissions for CA (4UL CA)	449
6.4A.2.3.4	In-band emissions for CA (5UL CA)	453
6.4A.2.3.5	In-band emissions for CA (6UL CA)	457
6.4A.2.3.6	In-band emissions for CA (7UL CA)	462
6.4A.2.3.7	In-band emissions for CA (8UL CA)	466
6.4A.2.4	EVM equalizer spectrum flatness for CA	470
6.4A.2.4.0	Minimum conformance requirements.....	470
6.4A.2.4.1	EVM equalizer spectrum flatness for CA (2UL CA)	470
6.4A.2.4.2	EVM equalizer spectrum flatness for CA (3UL CA)	473
6.4A.2.4.3	EVM equalizer spectrum flatness for CA (4UL CA)	475
6.4A.2.4.4	EVM equalizer spectrum flatness for CA (5UL CA)	477
6.4A.2.4.5	EVM equalizer spectrum flatness for CA (6UL CA)	479

6.4A.2.4.6	EVM equalizer spectrum flatness for CA (7UL CA)	481
6.4A.2.4.7	EVM equalizer spectrum flatness for CA (8UL CA)	483
6.4A.2.5	Void	485
6.4D	Transmit signal quality for UL MIMO	485
6.4D.0	General	485
6.4D.1	Frequency error for UL MIMO	485
6.4D.2	Transmit signal quality for UL MIMO	487
6.4D.2.1	Error vector magnitude for UL MIMO	487
6.4D.2.2	Carrier leakage for UL MIMO	490
6.4D.2.3	In-band emissions for UL MIMO	494
6.4D.2.4	EVM equalizer spectrum flatness for UL MIMO	504
6.4D.3	Time alignment error for UL MIMO	510
6.5	Output RF spectrum emissions	513
6.5.1	Occupied bandwidth	513
6.5.2	Out of band emission	516
6.5.2.1	Spectrum Emission Mask	516
6.5.2.1_1	Spectrum Emission Mask with Power Boost	519
6.5.2.2	Void	520
6.5.2.3	Adjacent channel leakage ratio	520
6.5.3	Spurious emissions	525
6.5.3.1	Transmitter Spurious emissions	525
6.5.3.1_1	Transmitter Spurious emissions with Power Boost	530
6.5.3.2	Spurious emission band UE co-existence	531
6.5.3.2_1	Spurious emission band UE co-existence with Power Boost	535
6.5.3.3	Additional spurious emissions	537
6.5.3.3_1	Additional spurious emissions with Power Boost	543
6.5A	Output RF spectrum emissions for CA	544
6.5A.1	Occupied bandwidth for CA	544
6.5A.1.0	Minimum conformance requirements	544
6.5A.1.1	Occupied bandwidth for CA (2UL CA)	544
6.5A.1.2	Occupied bandwidth for CA (3UL CA)	547
6.5A.1.3	Occupied bandwidth for CA (4UL CA)	548
6.5A.1.4	Occupied bandwidth for CA (5UL CA)	549
6.5A.1.5	Occupied bandwidth for CA (6UL CA)	550
6.5A.1.6	Occupied bandwidth for CA (7UL CA)	551
6.5A.1.7	Occupied bandwidth for CA (8UL CA)	552
6.5A.2	Out of band emission for CA	553
6.5A.2.1	Spectrum Emission Mask for CA	553
6.5A.2.1.0	Minimum conformance requirements	553
6.5A.2.1.1	Spectrum Emission Mask for CA (2UL CA)	554
6.5A.2.1.2	Spectrum Emission Mask for CA (3UL CA)	558
6.5A.2.1.3	Spectrum Emission Mask for CA (4UL CA)	559
6.5A.2.1.4	Spectrum Emission Mask for CA (5UL CA)	560
6.5A.2.1.5	Spectrum Emission Mask for CA (6UL CA)	561
6.5A.2.1.6	Spectrum Emission Mask for CA (7UL CA)	562
6.5A.2.1.7	Spectrum Emission Mask for CA (8UL CA)	563
6.5A.2.2	Adjacent channel leakage ratio for CA	564
6.5A.2.2.0	Minimum conformance requirements	564
6.5A.2.2.1	Adjacent channel leakage ratio for CA (2UL CA)	565
6.5A.2.2.2	Adjacent channel leakage ratio for CA (3UL CA)	569
6.5A.2.2.3	Adjacent channel leakage ratio for CA (4UL CA)	570
6.5A.2.2.4	Adjacent channel leakage ratio for CA (5UL CA)	571
6.5A.2.2.5	Adjacent channel leakage ratio for CA (6UL CA)	572
6.5A.2.2.6	Adjacent channel leakage ratio for CA (7UL CA)	573
6.5A.2.2.7	Adjacent channel leakage ratio for CA (8UL CA)	574
6.5A.3	Spurious emissions for CA	575
6.5A.3.1	General spurious emissions for CA	575
6.5A.3.1.0	Minimum conformance requirements	575
6.5A.3.1.1	General spurious emissions for CA (2UL CA)	575
6.5A.3.1.2	General spurious emissions for CA (3UL CA)	580
6.5A.3.1.3	General spurious emissions for CA (4UL CA)	580
6.5A.3.1.4	General spurious emissions for CA (5UL CA)	581

6.5A.3.1.5	General spurious emissions for CA (6UL CA).....	581
6.5A.3.1.6	General spurious emissions for CA (7UL CA).....	582
6.5A.3.1.7	General spurious emissions for CA (8UL CA).....	582
6.5A.3.2	Spurious emission band UE co-existence for UL CA.....	583
6.5A.3.2.0	Minimum conformance requirements.....	583
6.5A.3.2.1	Spurious emission band UE co-existence for CA (2UL CA).....	584
6.5A.3.2.2	Spurious emission band UE co-existence for CA (3UL CA).....	588
6.5A.3.2.3	Spurious emission band UE co-existence for CA (4UL CA).....	589
6.5A.3.2.4	Spurious emission band UE co-existence for CA (5UL CA).....	589
6.5A.3.2.5	Spurious emission band UE co-existence for CA (6UL CA).....	590
6.5A.3.2.6	Spurious emission band UE co-existence for CA (7UL CA).....	591
6.5A.3.2.7	Spurious emission band UE co-existence for CA (8UL CA).....	591
6.5A.3.3	Additional spurious emissions for CA.....	592
6.5A.3.3.0	Minimum conformance requirements.....	592
6.5A.3.3.1	Additional spurious emissions for CA (2UL CA).....	593
6.5A.3.3.2	Additional spurious emissions for CA (3UL CA).....	599
6.5A.3.3.3	Additional spurious emissions for CA (4UL CA).....	600
6.5A.3.3.4	Additional spurious emissions for CA (5UL CA).....	600
6.5A.3.3.5	Additional spurious emissions for CA (6UL CA).....	601
6.5A.3.3.6	Additional spurious emissions for CA (7UL CA).....	601
6.5A.3.3.7	Additional spurious emissions for CA (8UL CA).....	602
6.5D	Output RF spectrum emissions for UL MIMO.....	603
6.5D.1	Occupied bandwidth for UL MIMO.....	603
6.5D.2	Out of band emission for UL MIMO.....	605
6.5D.2.1	Spectrum Emission Mask for UL MIMO.....	605
6.5D.2.2	Adjacent channel leakage ratio for UL MIMO.....	606
6.5D.3	Spurious emissions for UL MIMO.....	609
6.5D.3.1	Transmitter Spurious emissions for UL MIMO.....	609
6.5D.3.2	Spurious emission band UE co-existence for UL MIMO.....	610
6.5D.3.3	Additional spurious emissions for UL MIMO.....	610
6.6	Beam correspondence.....	611
6.6.0	General.....	611
6.6.1	Beam correspondence - EIRP.....	612
6.6.2	Enhanced Beam correspondence – EIRP.....	622
6.6.3	Beam Correspondence in RRC_INACTIVE and initial access.....	629
6.6A	Beam correspondence for CA.....	630
7	Receiver characteristics.....	630
7.1	General.....	630
7.2	Diversity characteristics.....	631
7.2M	Diversity characteristics for LP-WUR/WUS.....	631
7.3	Reference sensitivity.....	631
7.3.1	General.....	631
7.3.2	Reference sensitivity power level.....	631
7.3.4	EIS spherical coverage.....	640
7.3A	Reference sensitivity for CA.....	647
7.3A.1	General.....	647
7.3A.2	Reference sensitivity power level for CA.....	647
7.3A.2.0	Minimum Conformance Requirements.....	647
7.3A.2.0.1	Intra-band contiguous CA.....	647
7.3A.2.0.2	Intra-band non-contiguous CA.....	647
7.3A.2.0.3	Inter-band CA.....	648
7.3A.2.1	Reference sensitivity power level for CA (2DL CA).....	648
7.3A.2.2	Reference sensitivity power level for CA (3DL CA).....	653
7.3A.2.3	Reference sensitivity power level for CA (4DL CA).....	654
7.3A.2.4	Reference sensitivity power level for CA (5DL CA).....	654
7.3A.2.5	Reference sensitivity power level for CA (6DL CA).....	655
7.3A.2.6	Reference sensitivity power level for CA (7DL CA).....	655
7.3A.2.7	Reference sensitivity power level for CA (8DL CA).....	656
7.3A.3	EIS spherical coverage for DL CA.....	657
7.3A.3.0	Minimum Conformance Requirements.....	657
7.3A.3.0.1	Void.....	657

7.3A.3.0.2	Void.....	657
7.3A.3.0.3	EIS spherical coverage for inter-band CA.....	657
7.3A.3.1	EIS Spherical Coverage for Inter-band CA (2DL CA).....	657
7.3A.3.2	EIS Spherical Coverage for Inter-band CA (3DL CA).....	661
7.3A.3.3	EIS Spherical Coverage for Inter-band CA (4DL CA).....	661
7.3D	Reference sensitivity for UL MIMO.....	662
7.3K	Spherical coverage requirement for simultaneous reception from multiple directions.....	662
7.3K.1	Spherical coverage with two Angle of Arrivals (AoAs) with simultaneous reception from multiple directions.....	662
7.3K.1.0	General.....	662
7.3K.1.1	UE spherical coverage for simultaneous reception from multiple directions (2 AoAs).....	663
7.3M	Reference sensitivity for LP-WUR/WUS.....	666
7.3M.1	General.....	666
7.3M.2	Reference sensitivity power level for LP-WUS/WUR.....	667
7.3M.2.1	Test purpose.....	667
7.3M.2.2	Test applicability.....	667
7.3M.3	Void.....	667
7.3M.4	LP-WUR/WUS [sensitivity] spherical coverage.....	667
7.3M.4.1	Test purpose.....	668
7.3M.4.2	Test applicability.....	668
7.4	Maximum input level.....	668
7.4A	Maximum input level for CA.....	671
7.4A.0	Minimum Conformance Requirements.....	671
7.4A.0.1	Maximum input level for Intra-band contiguous CA.....	671
7.4A.0.2	Maximum input level for Intra-band non-contiguous CA.....	671
7.4A.0.3	Maximum input level for inter-band CA.....	671
7.4A.1	Maximum input level for CA (2DL CA).....	672
7.4A.2	Maximum input level for CA (3DL CA).....	675
7.4A.3	Maximum input level for CA (4DL CA).....	676
7.4A.4	Maximum input level for CA (5DL CA).....	676
7.4A.5	Maximum input level for CA (6DL CA).....	677
7.4A.6	Maximum input level for CA (7DL CA).....	677
7.4A.7	Maximum input level for CA (8DL CA).....	678
7.4D	Maximum input level for UL MIMO.....	678
7.5	Adjacent channel selectivity.....	678
7.5A	Adjacent channel selectivity for CA.....	684
7.5A.0	Minimum Conformance Requirements.....	684
7.5A.0.1	Adjacent channel selectivity for Intra-band contiguous CA.....	684
7.5A.0.2	Adjacent channel selectivity for Intra-band non-contiguous CA.....	686
7.5A.0.3	Adjacent channel selectivity for Inter-band CA.....	686
7.5A.1	Adjacent channel selectivity for CA (2DL CA).....	686
7.5A.2	Adjacent channel selectivity for CA (3DL CA).....	686
7.5A.3	Adjacent channel selectivity for CA (4DL CA).....	686
7.5A.4	Adjacent channel selectivity for CA (5DL CA).....	686
7.5A.5	Adjacent channel selectivity for CA (6DL CA).....	686
7.5A.6	Adjacent channel selectivity for CA (7DL CA).....	686
7.5A.7	Adjacent channel selectivity for CA (8DL CA).....	686
7.5D	Adjacent channel selectivity for UL MIMO.....	687
7.5M	Adjacent channel and subcarrier selectivity for LP-WUS/WUR.....	687
7.5M.1	General.....	687
7.5M.2	Adjacent channel selectivity for LP-WUS/WUR.....	687
7.5M.2.1	Test purpose.....	687
7.5M.2.2	Test applicability.....	687
7.5M.3	Adjacent subcarrier selectivity for LP-WUS/WUR.....	688
7.5M.3.1	Test purpose.....	688
7.5M.3.2	Test applicability.....	688
7.6	Blocking characteristics.....	689
7.6.1	General.....	689
7.6.2	In-band blocking.....	689
7.6.3	Void.....	695
7.6A	Blocking characteristics for CA.....	695
7.6A.1	General.....	695

7.6A.2	In-band blocking for CA.....	695
7.6A.2.0	Minimum Conformance Requirements.....	695
7.6A.2.0.1	In-band blocking for Intra-band contiguous CA.....	695
7.6A.2.0.2	In-band blocking for Intra-band non-contiguous CA.....	696
7.6A.2.0.3	In-band blocking for Inter-band CA.....	696
7.6A.2.1	In-band blocking for CA (2DL CA).....	696
7.6A.2.2	Void.....	699
7.6A.2.3	Void.....	699
7.6A.2.4	Void.....	699
7.6A.2.5	Void.....	699
7.6A.2.6	Void.....	699
7.6A.2.7	Void.....	699
7.6D	Blocking characteristics for UL MIMO.....	699
7.7	Void.....	699
7.8	Void.....	699
7.9	Spurious emissions.....	699
7.10	Void.....	702
Annex A (normative): Measurement channels.....		703
A.1	General.....	703
A.2	UL reference measurement channels.....	703
A.2.1	General.....	703
A.2.2	Void.....	703
A.2.3	Reference measurement channels for TDD.....	704
A.2.3.1	DFT-s-OFDM Pi/2-BPSK.....	705
A.2.3.2	DFT-s-OFDM QPSK.....	705
A.2.3.3	DFT-s-OFDM 16QAM.....	706
A.2.3.4	DFT-s-OFDM 64QAM.....	707
A.2.3.5	CP-OFDM QPSK.....	708
A.2.3.6	CP-OFDM 16QAM.....	708
A.2.3.7	CP-OFDM 64QAM.....	709
A.3	DL reference measurement channels.....	711
A.3.1	General.....	711
A.3.2	Void.....	713
A.3.3	DL reference measurement channels for TDD.....	713
A.3.3.1	General.....	713
A.3.3.2	FRC for receiver requirements for QPSK.....	713
A.3.3.3	FRC for receiver requirements for 16QAM.....	716
A.3.3.4	FRC for receiver requirements for 64QAM.....	716
A.3.3.5	FRC for receiver requirements for 256QAM.....	717
A.4	Void.....	719
A.5	OFDMA Channel Noise Generator (OCNG).....	719
A.5.1	OCNG Patterns for FDD.....	719
A.5.2	OCNG Patterns for TDD.....	719
A.5.2.1	OCNG TDD pattern 1: Generic OCNG TDD Pattern for all unused REs.....	719
A.6	FR2 RF tests with testability issues.....	719
A.6.1	FR2 RF tests with testability issues not related to Measurement Uncertainty (MU).....	720
Annex B (normative): Propagation conditions.....		721
B.0	No interference.....	721
Annex C (normative): Downlink Physical Channels.....		722
C.0	Downlink signal levels.....	722
C.1	General.....	723
C.2	Setup.....	723

C.3	Connection	724
C.3.0	Measurement of Transmitter Characteristics	724
C.3.1	Measurement of Receiver Characteristics	725
Annex D (normative):	Characteristics of the interfering signal	726
D.1	General	726
D.2	Interference signals.....	726
Annex E (normative):	Global In-Channel TX-Test	727
E.1	General	727
E.2	Signals and results	727
E.2.1	Basic principle.....	727
E.2.2	Output signal of the TX under test	727
E.2.3	Reference signal	727
E.2.4	Measurement results.....	728
E.2.5	Measurement points	728
E.3	Signal processing.....	728
E.3.1	Pre FFT minimization process.....	728
E.3.2	Timing of the FFT window	729
E.3.3	Post FFT equalisation.....	730
E.4	Derivation of the results	731
E.4.1	EVM.....	731
E.4.2	Averaged EVM	731
E.4.3	In-band emissions measurement.....	732
E.4.4	EVM equalizer spectrum flatness.....	734
E.4.5	Frequency error and Carrier leakage	735
E.4.6	EVM of Demodulation reference symbols (EVM _{DMRS})	735
E.4.6.1	1 st average for EVM _{DMRS}	736
E.4.6.2	Final average for EVM _{DMRS}	736
E.5	EVM and inband emissions for PUCCH.....	736
E.5.1	Basic principle.....	736
E.5.2	Output signal of the TX under test	736
E.5.3	Reference signal	736
E.5.4	Measurement results.....	737
E.5.5	Measurement points	737
E.5.6	Pre FFT minimization process.....	737
E.5.7	Timing of the FFT window	737
E.5.8	Post FFT equalisation.....	737
E.5.9	Derivation of the results	738
E.5.9.1	EVM _{PUCCH}	738
E.5.9.2	Averaged EVM _{PUCCH}	738
E.5.9.3	In-band emissions measurement	739
E.5.10	Modified signal under test.....	740
E.6	EVM for PRACH	742
E.6.1	Basic principle.....	742
E.6.2	Output signal of the TX under test	742
E.6.3	Reference signal	742
E.6.4	Measurement results.....	742
E.6.5	Measurement points	743
E.6.6	Pre FFT minimization process.....	743
E.6.7	Timing of the FFT window	743
E.6.8	Post FFT equalisation.....	744
E.6.9	Derivation of the results	744
E.6.9.1	EVM _{PRACH}	744
E.6.9.2	Averaged EVM _{PRACH}	745
E.6.10	Modified signal under test.....	745
E.6.11	Phase offset measurement for DMRS bundling	745

E.6.11.1	Measurement point	745
E.6.11.2	Symbols used	745
E.6.11.3	Modified test signal	745
E.6.11.4	Phase offset measurement.....	745
E.6.12	Void.....	746
E.7	EVM for dual transmit polarizations	746
E.7.1	General.....	746
E.7.2	MIMO Equalization (UL MIMO transmission).....	746
E.7.3	Maximum Ratio combining (Tx diversity transmission)	747
E.7.4	Layer processing.....	747

Annex F (normative): Measurement uncertainties and Test Tolerances749

F.1	Acceptable uncertainty of Test System (normative)	749
F.1.0	General	749
F.1.1	Measurement of test environments.....	749
F.1.2	Measurement of transmitter.....	749
F.1.3	Measurement of receiver	771
F.2	Interpretation of measurement results (normative)	774
F.3	Test Tolerance and Derivation of Test Requirements (informative).....	775
F.3.1	Measurement of test environments.....	775
F.3.2	Measurement of transmitter.....	775
F.3.3	Measurement of receiver	793
F.4	Uplink power window	796
F.4.1	Introduction	796
F.4.2	Setting the power window above a requirement.....	796
F.4.3	Setting the power window below a requirement	796
F.4.4	Setting the power window centred on a target value	796
F.8	FFS	797
F.9	FFS	797
F.10	FFS	797

Annex G (normative): Uplink Physical Channels798

G.0	Uplink Signal Levels	798
G.1	General	798
G.2	Set-up	798
G.3	Connection	798
G.3.0	Measurement of Transmitter Characteristics.....	798
G.3.1	Measurement of Receiver Characteristics	798

Annex H (normative): Statistical Testing.....799

H.1	General	799
H.2	Statistical testing of receiver characteristics.....	799
H.2.1	General	799
H.2.2	Mapping throughput to error ratio.....	799
H.2.3	Design of the test.....	800
H.2.4	Numerical definition of the pass fail limits	800
H.2.5	Pass fail decision rules	801
H.2.6	Theory to derive the pass fail limits (Informative).....	801
H.2.6.1	Numerical definition of the pass-fail limits	801
H.2.6.2	Simulation to derive the pass-fail limits for testing 95% throughput.....	802

Annex I: Void 804

Annex J (normative): Test applicability per permitted test method805

Annex K (normative):	EIRP, TRP, and EIS measurement procedures	806
K.1	Direct far field (DFF)	806
K.1.1	TX beam peak direction search	806
K.1.2	RX beam peak direction search	808
K.1.3	Peak EIRP measurement procedure	810
K.1.4	Peak EIS measurement procedure	811
K.1.5	EIRP spherical coverage	811
K.1.5.0	Tx Spherical Coverage Method	811
K.1.5.1	Tx Fast Spherical Coverage Method	812
K.1.5.1.1	Introduction	812
K.1.5.1.2	Description	812
K.1.5.1.3	Measurement uncertainties	812
K.1.6	EIS spherical coverage	812
K.1.6.0	Rx Spherical Coverage Method	812
K.1.6.1	Rx Fast Spherical Coverage Method	813
K.1.6.1.1	Introduction	813
K.1.6.1.2	Description	813
K.1.6.1.3	Measurement uncertainties	813
K.1.7	TRP measurement procedure	813
K.1.8	Blocking measurement procedure	814
K.1.9	Beam Correspondence tolerance procedure	814
K.1.11	RSRP(B) based RX beam peak search	815
K.1.11.1	Test procedure	815
K.1.12	Enhanced test method for EIRP measurements	816
K.1.12.1	Applicability of TPMI side condition method	817
K.1.12.2	TPMI side condition method Measurement uncertainties impact	817
K.2	Direct far field (DFF) simplification	817
K.2.1	TX beam peak direction search	817
K.2.2	RX beam peak direction search	817
K.2.3	Peak EIRP measurement procedure	817
K.2.4	Peak EIS measurement procedure	817
K.2.5	EIRP spherical coverage	817
K.2.6	EIS spherical coverage	818
K.2.7	TRP measurement procedure	818
K.2.8	Blocking measurement procedure	818
K.3	Indirect far field (IFF)	818
K.3.1	TX beam peak direction search	818
K.3.2	RX beam peak direction search	818
K.3.3	Peak EIRP measurement procedure	818
K.3.4	Peak EIS measurement procedure	818
K.3.5	EIRP spherical coverage	818
K.3.6	EIS spherical coverage	818
K.3.7	TRP measurement procedure	818
K.3.8	Blocking measurement procedure	818
K.4	Near field to far field transform (NFTF)	819
K.4.1	TX beam peak direction search	819
K.4.2	RX beam peak direction search	819
K.4.3	Peak EIRP measurement procedure	819
K.4.4	Peak EIS measurement procedure	819
K.4.5	EIRP spherical coverage	819
K.4.6	EIS spherical coverage	819
K.4.7	TRP measurement procedure	819
K.4.8	Blocking measurement procedure	820
Annex L (normative):	Void	821
Annex M:(normative) Measurement grids		822
M.1	Grid Types	822