



TECHNICAL SPECIFICATION

**5G;  
NR;  
User Equipment (UE) conformance specification;  
Radio transmission and reception;  
Part 4: Performance  
(3GPP TS 38.521-4 version 18.9.0 Release 18)**



---

**Reference**

RTS/TSGR-0538521-4v190

---

**Keywords**

5G

**ETSI**

---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° w061004871

---

**Important notice**

The present document can be downloaded from the  
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed, this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our [Coordinated Vulnerability Disclosure \(CVD\)](#) program.

---

**Notice of disclaimer & limitation of liability**

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2026.  
All rights reserved.

---

## Intellectual Property Rights

### Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

### Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

---

## Legal Notice

This Technical Specification (TS) has been produced by the ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found at [3GPP to ETSI numbering cross-referencing](#).

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

# Contents

Intellectual Property Rights .....	2
Legal Notice .....	2
Modal verbs terminology.....	2
Foreword.....	22
1 Scope .....	23
2 References .....	23
3 Definition of terms, symbols and abbreviations.....	24
3.1 Terms.....	24
3.2 Symbols.....	25
3.3 Abbreviations .....	25
4 General .....	27
4.1 Relationship between minimum requirements and test requirements .....	27
4.2 Applicability of minimum requirements .....	27
4.3 Specification suffix information.....	28
4.4 Conducted requirements.....	28
4.4.0 Introduction.....	28
4.4.1 Reference point.....	28
4.4.2 SNR definition.....	28
4.4.3 Noc.....	29
4.4.3.1 Introduction.....	29
4.4.3.2 Noc for NR operating bands in FR1.....	29
4.4.3.2.1 Derivation of Noc values for NR operating bands in FR1.....	29
4.4.4 Es.....	29
4.4.4.1 Introduction.....	29
4.4.4.2 Es for NR operating bands in FR1 .....	30
4.4.4.2.1 Derivation of Es values for NR operating bands in FR1 .....	30
4.4.5 SINR definition.....	30
4.5 Radiated requirements.....	31
4.5.0 Introduction.....	31
4.5.1 Reference point.....	31
4.5.2 SNR definition .....	31
4.5.3 Noc.....	32
4.5.3.1 Introduction.....	32
4.5.3.2 Noc for NR operating bands in FR2.....	32
4.5.3.3 Derivation of Noc values for NR operating bands in FR2 .....	32
4.5.4 Angle of arrival.....	33
4.5.5 Es.....	33
4.6 Test coverage across 5G NR connectivity options .....	33
5 Demodulation performance requirements (Conducted requirements) .....	34
5.1 General .....	34
5.1.1 Applicability of requirements .....	34
5.1.1.1 General.....	34
5.1.1.2 Applicability of requirements for different number of RX antenna ports .....	34
5.1.1.3 Applicability of requirements for optional UE features .....	35
5.1.1.4 Applicability of requirements for mandatory UE features with capability signalling.....	39
5.1.1.5 Applicability of CA requirements .....	41
5.1.1.5.1 Definition of CA capability .....	41
5.1.1.5.2 Applicability and test rules for different CA configurations and bandwidth combination sets .....	41
5.1.1.5.3 Applicability rule and antenna connection for CA tests with 4 RX.....	42
5.1.1.5.4 Applicability of different requirements for HST.....	42
5.1.1.5.5 Applicability and test rules for different CA configurations and bandwidth combination sets for 8Rx UE .....	44
5.1.1.5.6 Applicability rule and antenna connection for CA tests with 8 RX.....	46

5.1.1.5.7	Applicability rule for optional UE features for 8Rx .....	46
5.1.1.6	Applicability and test rules for PDSCH performance requirements with power imbalance for intra-band contiguous CA .....	46
5.1.1.7	Applicability of different requirements for HST.....	46
5.1.1.8	Applicability of different requirements with Multi-TRxP .....	47
5.1.1.9	Applicability of requirements for PDSCH on bands with shared spectrum access.....	48
5.1.1.10	Applicability of requirements for PDSCH with inter cell interference .....	48
5.1.1.11	Applicability of requirements for RedCap .....	48
5.1.1.12	Applicability of requirements for ATG.....	48
5.1.1.14	Applicability of requirements for eRedCap .....	50
5.2	PDSCH demodulation requirements .....	50
5.2.1	1RX requirements .....	53
5.2.1.1	FDD.....	53
5.2.1.1.1	1Rx FDD FR1 PDSCH performance for RedCap .....	53
5.2.1.1.2	1Rx FDD FR1 PDSCH performance for eRedCap .....	56
5.2.1.2	TDD .....	60
5.2.1.2.1	1Rx TDD FR1 PDSCH performance for RedCap .....	60
5.2.1.2.2	1Rx TDD FR1 PDSCH performance for eRedCap .....	63
5.2.2	2RX requirements .....	67
5.2.2.1	FDD.....	67
5.2.2.1.1	2Rx FDD FR1 PDSCH mapping Type A performance .....	67
5.2.2.1.1_1	2Rx FDD FR1 PDSCH mapping Type A performance - 2x2 MIMO with baseline receiver for both SA and NSA.....	68
5.2.2.1.1_2	2Rx FDD FR1 PDSCH mapping Type A performance - 2x2 MIMO with enhanced receiver type 1 for both SA and NSA .....	71
5.2.2.1.1_3	2Rx FDD FR1 PDSCH mapping Type A performance – 2x2 MIMO with baseline receiver for DL1024QAM for both SA and NSA.....	72
5.2.2.1.1_4	2Rx FDD FR1 PDSCH mapping Type A performance – 2x2 MIMO with enhanced DMRS for both SA and NSA.....	74
5.2.2.1.2	2Rx FDD FR1 PDSCH mapping Type A and CSI-RS overlapped with PDSCH performance .....	75
5.2.2.1.2_1	2Rx FDD FR1 PDSCH mapping Type A and CSI-RS overlapped with PDSCH performance - 2x2 MIMO with baseline receiver for both SA and NSA .....	76
5.2.2.1.3	2Rx FDD FR1 PDSCH mapping Type B performance .....	79
5.2.2.1.3_1	2Rx FDD FR1 PDSCH mapping Type B performance - 2x2 MIMO with baseline receiver for both SA and NSA.....	79
5.2.2.1.4	2Rx FDD FR1 PDSCH Mapping Type A and LTE-NR coexistence performance .....	82
5.2.2.1.4_1	2Rx FDD FR1 PDSCH Mapping Type A and LTE-NR coexistence performance - 4x2 MIMO with baseline receiver for both SA and NSA.....	83
5.2.2.1.5	2Rx FDD FR1 PDSCH 0.001% BLER performance .....	87
5.2.2.1.5_1	2Rx FDD FR1 PDSCH 0.001% BLER performance - 1x2 MIMO with baseline receiver for both SA and NSA.....	88
5.2.2.1.6	2Rx FDD FR1 PDSCH repetitions over multiple slots performance .....	90
5.2.2.1.6_1	2Rx FDD FR1 PDSCH repetitions over multiple slots performance - 2x2 MIMO with baseline receiver for both SA and NSA .....	91
5.2.2.1.7	2Rx FDD FR1 PDSCH Mapping Type B and UE processing capability 2 performance .....	92
5.2.2.1.7_1	2Rx FDD FR1 PDSCH Mapping Type B and UE processing capability 2 performance - 2x2 MIMO with baseline receiver for both SA and NSA.....	93
5.2.2.1.8	2Rx FDD FR1 PDSCH pre-emption performance .....	95
5.2.2.1.8_1	2Rx FDD FR1 PDSCH pre-emption performance - 2x2 MIMO with baseline receiver for both SA and NSA .....	96
5.2.2.1.9	2Rx FDD FR1 HST-SFN performance .....	99
5.2.2.1.9_1	2Rx FDD FR1 HST-SFN performance - 2x2 MIMO with baseline receiver for both SA and NSA.....	100
5.2.2.1.10	2Rx FDD FR1 HST DPS performance.....	102
5.2.2.1.10_1	2Rx FDD FR1 HST-DPS performance - 2x2 MIMO with baseline receiver for both SA and NSA.....	104
5.2.2.1.11	2Rx FDD FR1 PDSCH Single-DCI based SDM scheme performance.....	110
5.2.2.1.11_1	2Rx FDD FR1 PDSCH Single-DCI based SDM scheme performance - 2x2 MIMO for both SA and NSA .....	111
5.2.2.1.12	2Rx FDD FR1 PDSCH Multi-DCI based transmission scheme performance.....	115
5.2.2.1.12_1	2Rx FDD FR1 PDSCH Multiple-DCI based transmission scheme performance - 2x2 MIMO for both SA and NSA.....	116

5.2.2.1.13	2Rx FDD FR1 PDSCH Single-DCI based FDM scheme A performance .....	120
5.2.2.1.13_1	2Rx FDD FR1 PDSCH Single-DCI based FDM scheme A performance - 2x2 MIMO for both SA and NSA .....	122
5.2.2.1.14	2Rx FDD FR1 PDSCH Single-DCI based Inter-slot TDM scheme performance .....	125
5.2.2.1.14_1	2Rx FDD FR1 PDSCH Single-DCI based Inter-slot TDM scheme performance - 2x2 MIMO for both SA and NSA.....	127
5.2.2.1.15	2Rx FDD FR1 PDSCH with inter-cell interference .....	130
5.2.2.1.15_1	2Rx FDD FR1 PDSCH with inter-cell interference performance - 2x2 MIMO for both SA and NSA.....	132
5.2.2.1.16	2Rx FDD FR1 for PDSCH with intra-cell inter user interference.....	134
5.2.2.1.16_1	2Rx FDD FR1 for PDSCH with intra cell inter user interference performance for baseline MMSE-IRC receiver – 2x2 MIMO for both NSA and SA .....	136
5.2.2.1.16_2	2Rx FDD FR1 for PDSCH with intra cell inter user interference performance for Enhanced Receiver Type 2 – 2x2 MIMO for both NSA and SA.....	137
5.2.2.1.17	2Rx FDD FR1 PDSCH performance for RedCap .....	140
5.2.2.1.18	2Rx FDD FR1 for PDSCH CRS interference mitigation under NR-LTE coexistence scenario ...	143
5.2.2.1.18_1	2Rx FDD FR1 for PDSCH CRS interference mitigation under NR-LTE coexistence scenario – 2x2 MIMO for both NSA and SA .....	145
5.2.2.1.19	2Rx FDD FR1 for PDSCH with inter cell CRS interference.....	148
5.2.2.1.19_1	2Rx FDD FR1 for PDSCH with inter cell CRS interference scenario – 4x2 MIMO for both NSA and SA .....	150
5.2.2.1.20	2Rx FDD FR1 PDSCH HST-SFN Scheme A performance - 2x2 MIMO for both SA and NSA.....	153
5.2.2.1.21	2Rx FDD FR1 PDSCH HST-SFN Scheme B performance - 2x2 MIMO for both SA and NSA.....	160
5.2.2.1.23	2Rx FDD FR1 PDSCH performance for eRedCap .....	164
5.2.2.2	TDD .....	169
5.2.2.2.1	2Rx TDD FR1 PDSCH mapping Type A performance.....	169
5.2.2.2.1_1	2Rx TDD FR1 PDSCH mapping Type A performance - 2x2 MIMO with baseline receiver for both SA and NSA .....	171
5.2.2.2.1_2	2Rx TDD FR1 PDSCH mapping Type A performance - 2x2 MIMO with enhanced receiver type 1 for both SA and NSA .....	176
5.2.2.2.1_3	2Rx TDD FR1 PDSCH mapping Type A performance - 2x2 MIMO with baseline receiver for DL1024QAM for both SA and NSA .....	177
5.2.2.2.1_4	2Rx TDD FR1 PDSCH mapping Type A performance - 2x2 MIMO with enhanced DMRS for both SA and NSA.....	179
5.2.2.2.2	2Rx TDD FR1 PDSCH mapping Type A and CSI-RS overlapped with PDSCH performance ....	180
5.2.2.2.2_1	2Rx TDD FR1 PDSCH mapping Type A and CSI-RS overlapped with PDSCH performance - 2x2 MIMO with baseline receiver for both SA and NSA .....	180
5.2.2.2.3	2Rx TDD FR1 PDSCH mapping Type B performance.....	184
5.2.2.2.3_1	2Rx TDD FR1 PDSCH mapping Type B performance - 2x2 MIMO with baseline receiver for both SA and NSA.....	185
5.2.2.2.4	2Rx TDD FR1 PDSCH mapping Type A and LTE-NR coexistence performance .....	187
5.2.2.2.4_1	2Rx TDD FR1 PDSCH Mapping Type A and LTE-NR coexistence performance - 4x2 MIMO with baseline receiver for both SA and NSA.....	188
5.2.2.2.5	2Rx TDD FR1 PDSCH 0.001% BLER performance .....	193
5.2.2.2.5_1	2Rx TDD FR1 PDSCH 0.001% BLER performance - 1x2 MIMO with baseline receiver for both SA and NSA.....	194
5.2.2.2.6	2Rx TDD FR1 PDSCH repetitions over multiple slots performance .....	195
5.2.2.2.6_1	2Rx TDD FR1 PDSCH repetitions over multiple slots performance - 2x2 MIMO with baseline receiver for both SA and NSA .....	196
5.2.2.2.7	2Rx TDD FR1 PDSCH Mapping Type B and UE processing capability 2 performance.....	198
5.2.2.2.7_1	2Rx TDD FR1 PDSCH Mapping Type B and UE processing capability 2 performance - 2x2 MIMO with baseline receiver for both SA and NSA.....	199
5.2.2.2.8	2Rx TDD FR1 PDSCH pre-emption performance .....	201
5.2.2.2.8_1	2Rx TDD FR1 PDSCH pre-emption performance - 2x2 MIMO with baseline receiver for both SA and NSA .....	202
5.2.2.2.9	2Rx TDD FR1 HST-SFN performance .....	203
5.2.2.2.9_1	2Rx TDD FR1 HST-SFN performance - 2x2 MIMO with baseline receiver for both SA and NSA.....	204
5.2.2.2.10	2Rx TDD FR1 HST DPS performance .....	207

5.2.2.2.10_1	2Rx TDD FR1 HST-DPS performance - 2x2 MIMO with baseline receiver for both SA and NSA.....	209
5.2.2.2.11	2Rx TDD FR1 PDSCH Single-DCI based SDM scheme performance.....	214
5.2.2.2.11_1	2Rx TDD FR1 PDSCH Single-DCI based SDM scheme performance - 2x2 MIMO for both SA and NSA .....	216
5.2.2.2.12	2Rx TDD FR1 PDSCH Multi-DCI based transmission scheme performance .....	219
5.2.2.2.12_1	2Rx TDD FR1 PDSCH Multiple-DCI based transmission scheme performance - 2x2 MIMO for both SA and NSA.....	221
5.2.2.2.13	2Rx TDD FR1 PDSCH Single-DCI based FDM scheme A performance.....	222
5.2.2.2.13_1	2Rx TDD FR1 PDSCH Single-DCI based FDM scheme A performance - 2x2 MIMO for both SA and NSA .....	223
5.2.2.2.14	2Rx TDD FR1 PDSCH Single-DCI based Inter-slot TDM scheme performance.....	224
5.2.2.2.14_1	2Rx TDD FR1 PDSCH Single-DCI based Inter-slot TDM scheme performance - 2x2 MIMO for both SA and NSA.....	226
5.2.2.2.15	2Rx TDD FR1 PDSCH mapping type A performance on band with shared spectrum access .....	227
5.2.2.2.15_1	2Rx TDD FR1 PDSCH mapping type A performance on band with shared spectrum access – 2x2 MIMO for both NSA and SA.....	228
5.2.2.2.16	2Rx TDD FR1 for PDSCH with inter-cell interference performance.....	231
5.2.2.2.16_1	2Rx TDD FR1 for PDSCH with inter-cell interference performance – 2x2 MIMO for both NSA and SA.....	232
5.2.2.2.17	2Rx TDD FR1 for PDSCH with intra-cell inter user interference.....	235
5.2.2.2.17_1	2Rx TDD FR1 for PDSCH with baseline MMSE-IRC receiver – 2x2 MIMO for both NSA and SA.....	237
5.2.2.2.17_2	2Rx TDD FR1 for PDSCH with Enhanced Receiver Type 2 – 2x2 MIMO for both NSA and SA .....	238
5.2.2.2.18	2Rx TDD FR1 PDSCH performance for RedCap .....	240
5.2.2.2.19	2Rx TDD FR1 for PDSCH CRS interference mitigation under NR-LTE coexistence scenario ...	244
5.2.2.2.19_1	2Rx TDD FR1 for PDSCH CRS interference mitigation under NR-LTE coexistence scenario – 4x2 MIMO for both NSA and SA .....	245
5.2.2.2.20	2Rx TDD FR1 for PDSCH with inter cell CRS interference .....	248
5.2.2.2.20_1	2Rx TDD FR1 for PDSCH with inter cell CRS interference scenario – 4x2 MIMO for both NSA and SA .....	250
5.2.2.2.21	2Rx TDD FR1 PDSCH HST-SFN Scheme A performance - 2x2 MIMO for both SA and NSA.....	253
5.2.2.2.22	2Rx TDD FR1 PDSCH HST-SFN Scheme B performance - 2x2 MIMO for both SA and NSA.....	261
5.2.3	4RX requirements .....	264
5.2.3.1	FDD.....	264
5.2.3.1.1	4Rx FDD FR1 PDSCH mapping Type A performance.....	264
5.2.3.1.1_1	4Rx FDD FR1 PDSCH mapping Type A performance - 2x4 MIMO with baseline receiver for both SA and NSA.....	267
5.2.3.1.1_2	4Rx FDD FR1 PDSCH mapping Type A performance - 4x4 MIMO with baseline receiver for both SA and NSA.....	270
5.2.3.1.1_3	FFS.....	271
5.2.3.1.1_4	4Rx FDD FR1 PDSCH mapping Type A performance - 4x4 MIMO with enhanced receiver type 1 for both SA and NSA .....	271
5.2.3.1.1_5	4Rx FDD FR1 PDSCH mapping Type A performance - 2x4 MIMO with baseline receiver for DL1024QAM for both SA and NSA.....	271
5.2.3.1.1_6	4Rx FDD FR1 PDSCH mapping Type A performance - 4x4 MIMO with enhanced DMRS for both SA and NSA.....	273
5.2.3.1.2	4Rx FDD FR1 PDSCH mapping Type A and CSI-RS overlapped with PDSCH performance ....	275
5.2.3.1.2_1	4Rx FDD FR1 PDSCH mapping Type A and CSI-RS overlapped with PDSCH performance - 4x4 MIMO with baseline receiver for both SA and NSA .....	276
5.2.3.1.3	4Rx FDD FR1 PDSCH mapping Type B performance .....	278
5.2.3.1.3_1	4Rx FDD FR1 PDSCH mapping Type B performance - 2x4 MIMO with baseline receiver for both SA and NSA.....	279
5.2.3.1.4	4Rx FDD FR1 PDSCH Mapping Type A and LTE-NR coexistence performance.....	281
5.2.3.1.4_1	4Rx FDD FR1 PDSCH Mapping Type A and LTE-NR coexistence performance - 4x4 MIMO with baseline receiver for both SA and NSA.....	282
5.2.3.1.5	4Rx FDD FR1 PDSCH 0.001% BLER performance .....	283
5.2.3.1.5_1	4Rx FDD FR1 PDSCH 0.001% BLER performance - 1x4 MIMO with baseline receiver for both SA and NSA.....	284

5.2.3.1.6	4Rx FDD FR1 PDSCH repetitions over multiple slots performance .....	286
5.2.3.1.6_1	4Rx FDD FR1 PDSCH repetitions over multiple slots performance - 2x4 MIMO with baseline receiver for both SA and NSA .....	287
5.2.3.1.7	4Rx FDD FR1 PDSCH Mapping Type B and UE processing capability 2 performance .....	288
5.2.3.1.7_1	4Rx FDD FR1 PDSCH Mapping Type B and UE processing capability 2 performance - 2x4 MIMO with baseline receiver for both SA and NSA .....	289
5.2.3.1.8	4Rx FDD FR1 PDSCH pre-emption performance .....	291
5.2.3.1.8_1	4Rx FDD FR1 PDSCH pre-emption performance - 2x4 MIMO with baseline receiver for both SA and NSA .....	292
5.2.3.1.9	4Rx FDD FR1 HST-SFN performance .....	294
5.2.3.1.9_1	4Rx FDD FR1 HST-SFN performance - 2x4 MIMO with baseline receiver for both SA and NSA .....	295
5.2.3.1.10	4Rx FDD FR1 HST DPS performance .....	297
5.2.3.1.10_1	4Rx FDD FR1 HST-DPS performance - 2x4 MIMO with baseline receiver for both SA and NSA .....	299
5.2.3.1.11	4Rx FDD FR1 PDSCH Single-DCI based SDM scheme performance .....	305
5.2.3.1.11_1	4Rx FDD FR1 PDSCH Single-DCI based SDM scheme performance - 2x4 MIMO for both SA and NSA .....	306
5.2.3.1.12	4Rx FDD FR1 PDSCH Multi-DCI based transmission scheme performance .....	310
5.2.3.1.12_1	4Rx FDD FR1 PDSCH Multiple-DCI based transmission scheme performance - 2x4 MIMO for both SA and NSA .....	312
5.2.3.1.13	4Rx FDD FR1 PDSCH Single-DCI based FDM scheme A performance .....	316
5.2.3.1.13_1	4Rx FDD FR1 PDSCH Single-DCI based FDM scheme A performance - 2x4 MIMO for both SA and NSA .....	317
5.2.3.1.14	4Rx FDD FR1 PDSCH Single-DCI based Inter-slot TDM scheme performance .....	321
5.2.3.1.14_1	4Rx FDD FR1 PDSCH Single-DCI based Inter-slot TDM scheme performance - 2x4 MIMO for both SA and NSA .....	322
5.2.3.1.15	4Rx FDD FR1 PDSCH with inter-cell interference .....	326
5.2.3.1.15_1	4Rx FDD FR1 PDSCH with inter-cell interference performance - 2x4 MIMO for both SA and NSA .....	327
5.2.3.1.16	4Rx FDD FR1 for PDSCH with intra-cell inter-user interference .....	330
5.2.3.1.16_1	4Rx FDD FR1 for PDSCH with intra cell inter user interference performance for baseline MMSE-IRC receiver – 2x4 MIMO for both NSA and SA .....	332
5.2.3.1.16_2	4Rx FDD FR1 for PDSCH with intra cell inter user interference performance for baseline MMSE-IRC receiver – 4x4 MIMO for both NSA and SA .....	333
5.2.3.1.16_3	4Rx FDD FR1 for PDSCH with intra cell inter user interference performance for Enhanced Receiver Type 2 – 2x4 MIMO for both NSA and SA .....	335
5.2.3.1.16_4	4Rx FDD FR1 for PDSCH with intra cell inter user interference performance for Enhanced Receiver Type 2 – 4x4 MIMO for both NSA and SA .....	337
5.2.3.1.17	4Rx FDD FR1 for PDSCH CRS interference mitigation under NR-LTE coexistence scenario .....	339
5.2.3.1.17_1	4Rx FDD FR1 for PDSCH CRS interference mitigation under NR-LTE coexistence scenario – 2x4 MIMO for both NSA and SA .....	341
5.2.3.1.18	4Rx FDD FR1 for PDSCH with inter cell CRS interference .....	343
5.2.3.1.18_1	4Rx FDD FR1 for PDSCH with inter cell CRS interference scenario – 4x4 MIMO for both NSA and SA .....	345
5.2.3.1.19	4Rx FDD FR1 PDSCH HST-SFN Scheme A performance - 2x4 MIMO for both SA and NSA .....	348
5.2.3.1.20	4Rx FDD FR1 PDSCH HST-SFN Scheme B performance - 2x4 MIMO for both SA and NSA .....	356
5.2.3.2	TDD .....	359
5.2.3.2.1	4Rx TDD FR1 PDSCH mapping Type A performance .....	359
5.2.3.2.1_1	4Rx TDD FR1 PDSCH mapping Type A performance - 2x4 MIMO with baseline receiver for both SA and NSA .....	362
5.2.3.2.1_2	4Rx TDD FR1 PDSCH mapping Type A performance - 4x4 MIMO with baseline receiver for both SA and NSA .....	368
5.2.3.2.1_3	4Rx TDD FR1 PDSCH mapping Type A performance - 2x4 MIMO with enhanced receiver type 1 for both SA and NSA .....	369
5.2.3.2.1_4	4Rx TDD FR1 PDSCH mapping Type A performance - 4x4 MIMO with enhanced receiver type 1 for both SA and NSA .....	369
5.2.3.2.1_5	4Rx TDD FR1 PDSCH mapping Type A performance - 2x4 MIMO with baseline receiver for DL1024QAM for both SA and NSA .....	370

5.2.3.2.1_6	4Rx TDD FR1 PDSCH mapping Type A performance - 4x4 MIMO with enhanced DMRS for both SA and NSA.....	371
5.2.3.2.2	4Rx TDD FR1 PDSCH mapping Type A and CSI-RS overlapped with PDSCH performance ....	373
5.2.3.2.2_1	4Rx TDD FR1 PDSCH mapping Type A and CSI-RS overlapped with PDSCH performance - 2x4 MIMO with baseline receiver for both SA and NSA .....	374
5.2.3.2.3	4Rx TDD FR1 PDSCH mapping Type B performance.....	376
5.2.3.2.3_1	4Rx TDD FR1 PDSCH mapping Type B performance - 2x4 MIMO with baseline receiver for both SA and NSA.....	377
5.2.3.2.4	4Rx TDD FR1 PDSCH mapping Type A performance.....	379
5.2.3.2.4_1	4Rx TDD FR1 PDSCH Mapping Type A and LTE-NR coexistence performance - 4x4 MIMO with baseline receiver for both SA and NSA.....	380
5.2.3.2.5	4Rx TDD FR1 PDSCH 0.001% BLER performance .....	381
5.2.3.2.5_1	4Rx TDD FR1 PDSCH 0.001% BLER performance - 1x4 MIMO with baseline receiver for both SA and NSA.....	382
5.2.3.2.6	4Rx TDD FR1 PDSCH repetitions over multiple slots performance .....	384
5.2.3.2.6_1	4Rx TDD FR1 PDSCH repetitions over multiple slots performance - 2x4 MIMO with baseline receiver for both SA and NSA .....	385
5.2.3.2.7	4Rx TDD FR1 PDSCH Mapping Type B and UE processing capability 2 performance.....	386
5.2.3.2.7_1	4Rx TDD FR1 PDSCH Mapping Type B and UE processing capability 2 performance - 2x4 MIMO with baseline receiver for both SA and NSA.....	387
5.2.3.2.8	4Rx TDD FR1 PDSCH pre-emption performance .....	389
5.2.3.2.8_1	4Rx TDD FR1 PDSCH pre-emption performance - 2x4 MIMO with baseline receiver for both SA and NSA .....	390
5.2.3.2.9	4Rx TDD FR1 HST-SFN performance .....	392
5.2.3.2.9_1	4Rx TDD FR1 HST-SFN performance - 2x4 MIMO with baseline receiver for both SA and NSA.....	393
5.2.3.2.10	4Rx TDD FR1 HST DPS performance .....	395
5.2.3.2.10_1	4Rx TDD FR1 HST DPS performance - 2x4 MIMO with baseline receiver for both SA and NSA.....	397
5.2.3.2.11	4Rx TDD FR1 PDSCH Single-DCI based SDM scheme performance.....	402
5.2.3.2.11_1	4Rx TDD FR1 PDSCH Single-DCI based SDM scheme performance - 2x4 MIMO for both SA and NSA .....	404
5.2.3.2.12	4Rx TDD FR1 PDSCH Multi-DCI based transmission scheme performance .....	407
5.2.3.2.12_1	4Rx TDD FR1 PDSCH Multiple-DCI based transmission scheme performance - 2x4 MIMO for both SA and NSA.....	409
5.2.3.2.13	4Rx TDD FR1 PDSCH Single-DCI based FDM scheme A performance.....	410
5.2.3.2.13_1	4Rx TDD FR1 PDSCH Single-DCI based FDM scheme A performance - 2x4 MIMO for both SA and NSA .....	412
5.2.3.2.14	4Rx TDD FR1 PDSCH Single-DCI based Inter-slot TDM scheme performance .....	412
5.2.3.2.14_1	4Rx TDD FR1 PDSCH Single-DCI based Inter-slot TDM scheme performance - 2x4 MIMO for both SA and NSA.....	414
5.2.3.2.15	4Rx TDD FR1 PDSCH mapping type A performance on band with shared spectrum access .....	415
5.2.3.2.15_1	4Rx TDD FR1 PDSCH mapping type A performance on band with shared spectrum access – 2x4 MIMO for both NSA and SA.....	416
5.2.3.2.16	4Rx TDD FR1 for PDSCH with inter-cell interference performance.....	417
5.2.3.2.16_1	4Rx TDD FR1 for PDSCH with inter-cell interference performance – 2x4 MIMO for both NSA and SA.....	419
5.2.3.2.17	4Rx TDD FR1 for PDSCH with intra-cell inter-user interference .....	421
5.2.3.2.17_1	2Rx TDD FR1 for PDSCH with baseline MMSE-IRC receiver – 2x2 MIMO for both NSA and SA.....	424
5.2.3.2.17_2	4Rx TDD FR1 for PDSCH with baseline MMSE-IRC receiver – 4x4 MIMO for both NSA and SA.....	425
5.2.3.2.17_3	4Rx TDD FR1 for PDSCH with intra cell inter user interference performance for Enhanced Receiver Type 2 – 2x4 MIMO for both NSA and SA.....	427
5.2.3.2.17_4	4Rx TDD FR1 for PDSCH with intra cell inter user interference performance for Enhanced Receiver Type 2 – 4x4 MIMO for both NSA and SA.....	429
5.2.3.2.18	4Rx TDD FR1 for PDSCH CRS interference mitigation under NR-LTE coexistence scenario ...	431
5.2.3.2.18_1	4Rx TDD FR1 for PDSCH CRS interference mitigation under NR-LTE coexistence scenario – 4x4 MIMO for both NSA and SA .....	433
5.2.3.2.19	4Rx TDD FR1 for PDSCH with inter cell CRS interference .....	435
5.2.3.2.19_1	4Rx TDD FR1 for PDSCH with inter cell CRS interference scenario – 4x4 MIMO for both NSA and SA .....	437

5.2.3.2.20	4Rx TDD FR1 PDSCH HST-SFN Scheme A performance - 2x4 MIMO for both SA and NSA .....	441
5.2.3.2.21	4Rx TDD FR1 PDSCH HST-SFN Scheme B performance - 2x4 MIMO for both SA and NSA .....	448
5.2.4	8RX requirements .....	452
5.2.4.1	FDD .....	452
5.2.4.1.1	8Rx FDD FR1 PDSCH mapping Type A performance .....	452
5.2.4.1.1_1	8Rx FDD FR1 PDSCH mapping Type A performance - 2x8 MIMO with baseline 8Rx receiver for both SA and NSA .....	453
5.2.4.2	TDD .....	455
5.2.4.2.1	8Rx TDD FR1 PDSCH mapping Type A performance .....	455
5.2.4.2.1_1	FFS .....	457
5.2.4.2.1_2	FFS .....	457
5.2.4.2.1_3	8Rx TDD FR1 PDSCH mapping Type A performance – 2x8 MIMO with simplified receiver for both SA and NSA .....	457
5.2.4.2.1_4	8Rx TDD FR1 PDSCH mapping Type A performance – 4x8 MIMO with simplified receiver for both SA and NSA .....	458
5.2A	PDSCH demodulation requirements for CA .....	459
5.2A.1	1RX requirements (Void) .....	460
5.2A.2	2RX requirements .....	460
5.2A.2.1	Requirements for 2RX normal PDSCH .....	460
5.2A.2.1.0	Minimum conformance requirements for 2RX normal PDSCH .....	460
5.2A.2.1.1	2Rx Normal PDSCH Demodulation Performance for CA (2DL CA) for both SA and NSA .....	462
5.2A.2.1.2	2Rx Normal PDSCH Demodulation Performance for CA (3DL CA) for both SA and NSA .....	465
5.2A.2.1.3	2Rx Normal PDSCH Demodulation Performance for CA (4DL CA) for both SA and NSA .....	466
5.2A.2.2	Requirements for 2RX PDSCH carrier aggregation with power imbalance .....	466
5.2A.2.2.0	Minimum conformance requirements for 2RX PDSCH CA with power imbalance .....	466
5.2A.2.2.1	2Rx PDSCH Demodulation Performance for CA with power imbalance (2DL CA) .....	468
5.2A.2.2.2	Void .....	469
5.2A.2.2.3	Void .....	469
5.2A.2.3	2Rx TDD FR1 PDSCH mapping type A performance of SCell on band with shared spectrum access .....	469
5.2A.2.4	Requirements for 2RX HST-SFN CA PDSCH .....	472
5.2A.2.4.0	Minimum conformance requirements for 2RX HST-SFN CA PDSCH .....	472
5.2A.2.4.1	2Rx PDSCH Demodulation Performance for HST-SFN CA .....	474
5.2A.2.5	Requirements for 2RX HST-DPS CA PDSCH .....	477
5.2A.2.5.0	Minimum conformance requirements for 2RX HST-DPS CA PDSCH .....	477
5.2A.2.5.1	2RX PDSCH Demodulation Performance for HST-DPS CA .....	482
5.2A.3	4RX requirements .....	489
5.2A.3.1	Requirements for 4RX normal PDSCH .....	489
5.2A.3.1.0	Minimum conformance requirements for 4RX normal PDSCH .....	489
5.2A.3.1.1	4Rx Normal PDSCH Demodulation Performance for CA (2DL CA) .....	490
5.2A.3.1.2	4Rx Normal PDSCH Demodulation Performance for CA (3DL CA) .....	493
5.2A.3.1.3	4Rx Normal PDSCH Demodulation Performance for CA (4DL CA) .....	494
5.2A.3.2	Requirements for 4RX PDSCH carrier aggregation with power imbalance .....	494
5.2A.3.2.0	Minimum requirements for carrier aggregation with power imbalance .....	494
5.2A.3.2.1	4Rx PDSCH Demodulation Performance for CA with power imbalance (2DL CA) .....	496
5.2A.3.3	4Rx TDD FR1 PDSCH mapping type A performance of SCell on band with shared spectrum access .....	497
5.2A.3.4	Requirements for 4RX HST-SFN CA PDSCH .....	499
5.2A.3.4.0	Minimum conformance requirements for 4RX HST-SFN CA PDSCH .....	499
5.2A.3.4.1	4RX PDSCH Demodulation Performance for HST-SFN CA .....	502
5.2A.3.5	Requirements for 4RX HST-DPS CA PDSCH .....	505
5.2A.3.5.0	Minimum conformance requirements for 4RX HST-DPS CA PDSCH .....	505
5.2A.3.5.1	4RX PDSCH Demodulation Performance for HST-DPS CA .....	510
5.2A.3A	2Rx-4RX requirements .....	517
5.2A.3A.1	Requirements for 2Rx-4RX normal PDSCH .....	517
5.2A.3A.1.0	Minimum conformance requirements for 2Rx-4RX normal PDSCH .....	517
5.2A.3A.1.1	2Rx-4Rx Normal PDSCH Demodulation Performance for CA (2DL CA) .....	517
5.2A.3A.1.2	2Rx-4Rx Normal PDSCH Demodulation Performance for CA (3DL CA) .....	521
5.2A.3A.1.3	2Rx-4Rx Normal PDSCH Demodulation Performance for CA (4DL CA) .....	521
5.3	PDCCH demodulation requirements .....	522

5.3.1	1RX requirements .....	523
5.3.1.1	FDD.....	523
5.3.1.1.1	1Rx FDD FR1 PDCCH performance for RedCap.....	523
5.3.1.2	TDD .....	526
5.3.1.2.1	1Rx TDD FR1 PDCCH performance for RedCap.....	526
5.3.2	2RX requirements .....	528
5.3.2.1	FDD.....	528
5.3.2.1.1	2Rx FDD FR1 PDCCH 1 Tx antenna performance for both SA and NSA .....	529
5.3.2.1.2	2Rx FDD FR1 PDCCH 2 Tx antenna performance for both SA and NSA .....	532
5.3.2.1.3	2Rx FDD FR1 PDCCH 1 Tx antenna performance for power saving.....	535
5.3.2.1.4	2Rx FDD FR1 PDCCH performance for RedCap.....	540
5.3.2.1.5	2RX FDD Minimum requirements for PDCCH with intra-slot repetition .....	543
5.3.2.1.7	2RX FDD FR1 PDCCH antenna performance for 3 MHz channel bandwidth .....	546
5.3.2.2	TDD .....	549
5.3.2.2.1	2Rx TDD FR1 PDCCH 1 Tx antenna performance for both SA and NSA .....	549
5.3.2.2.2	2Rx TDD FR1 PDCCH 2 Tx antenna performance for both SA and NSA.....	552
5.3.2.2.3	2Rx TDD FR1 PDCCH 1 Tx antenna performance for power saving .....	555
5.3.2.2.4	2Rx TDD FR1 PDCCH performance for RedCap.....	560
5.3.2.2.5	2RX TDD Minimum requirements for PDCCH with intra-slot repetition .....	562
5.3.3	4RX requirements .....	566
5.3.3.1	FDD.....	566
5.3.3.1.1	4Rx FDD FR1 PDCCH 1 Tx antenna performance for both SA and NSA .....	566
5.3.3.1.2	4Rx FDD FR1 PDCCH 2 Tx antenna performance for both SA and NSA .....	569
5.3.3.1.3	4Rx FDD FR1 PDCCH 1 Tx antenna performance for power saving.....	572
5.3.3.1.4	4RX FDD Minimum requirements for PDCCH with intra-slot repetition .....	578
5.3.3.1.5	581	
5.3.3.1.6	4RX FDD FR1 PDCCH antenna performance for 3 MHz channel bandwidth .....	581
5.3.3.2	TDD .....	584
5.3.3.2.1	4Rx TDD FR1 PDCCH 1 Tx antenna performance for both SA and NSA .....	584
5.3.3.2.2	4Rx TDD FR1 PDCCH 2 Tx antenna performance for both SA and NSA .....	587
5.3.3.2.3	4Rx TDD FR1 PDCCH 1 Tx antenna performance for power saving .....	590
5.3.3.2.4	4RX TDD Minimum requirements for PDCCH with intra-slot repetition .....	595
5.4	PBCH demodulation requirements .....	598
5.5	Sustained downlink data rate provided by lower layers .....	599
5.5.1	FR1 Sustained downlink data rate performance for single carrier.....	599
5.5.1_1	FR1 Sustained downlink data rate performance for single carrier for 8Rx.....	606
5.5.2	FR1 Sustained downlink data rate performance for single carrier with DL1024QAM .....	610
5.5.3	FR1 Sustained downlink data rate performance for RedCap.....	611
5.5.A.1	FR1 Sustained downlink data rate performance for carrier aggregation.....	613
5.5.A.1.1	FR1 SDR performance for CA (2DL CA).....	613
5.5.A.1.2	FR1 SDR performance for CA (3DL CA) .....	620
5.5.A.1.2.1	Test Purpose .....	620
5.5.A.1.2.2	Test applicability .....	620
5.5.A.1.2.3	Minimum conformance requirements.....	620
5.5.A.1.2.4	Test description .....	620
5.5.A.1.2.5	Test requirement .....	621
5.5.A.1.3	FR1 SDR performance for CA (4DL CA) .....	621
5.5.A.1.3.1	Test Purpose .....	621
5.5.A.1.3.2	Test applicability .....	621
5.5.A.1.3.3	Minimum conformance requirements.....	621
5.5.A.1.3.4	Test description .....	621
5.5.A.1.3.5	Test requirement .....	621
5.5.A.1.4	FR1 SDR performance for CA (5DL CA) .....	621
5.5.A.1.4.1	Test Purpose .....	621
5.5.A.1.4.2	Test applicability .....	621
5.5.A.1.4.3	Minimum conformance requirements.....	621
5.5.A.1.4.4	Test description .....	622
5.5.A.1.4.5	Test requirement .....	622
5.6	PDSCH absolute physical layer throughput requirements .....	622
5.6.1	1RX requirements .....	622
5.6.2	2RX requirements .....	622
5.6.2.1	FDD.....	622

5.6.2.1.1	2Rx FDD FR1 PDSCH absolute physical layer throughput performance with link adaptation ....	622
5.6.2.1.1_1	2Rx FDD FR1 PDSCH performance with link adaptation - 2x2 MIMO for both SA and NSA .....	624
5.6.2.2	TDD .....	626
5.6.2.2.1	2Rx TDD FR1 PDSCH absolute physical layer throughput performance with link adaptation ....	626
5.6.2.2.1_1	2Rx TDD FR1 PDSCH performance with link adaptation - 2x2 MIMO for both SA and NSA .....	627
5.6.3	4Rx requirements .....	629
5.6.3.1	FDD .....	629
5.6.3.1.1	4Rx FDD FR1 PDSCH absolute physical layer throughput performance with link adaptation ....	629
5.6.3.1.1_1	4Rx FDD FR1 PDSCH performance with link adaptation - 2x4 MIMO for both SA and NSA .....	630
5.6.3.2	TDD .....	632
5.6.3.2.1	4Rx TDD FR1 PDSCH absolute physical layer throughput performance with link adaptation ....	632
5.6.3.2.1_1	4Rx TDD FR1 PDSCH performance with link adaptation - 2x4 MIMO for both SA and NSA .....	633
6	CSI reporting requirements (Conducted requirements) .....	635
6.1	General .....	635
6.1.1	Applicability of requirements .....	635
6.1.1.1	General .....	635
6.1.1.2	Applicability of requirements for different number of RX antenna ports .....	635
6.1.1.3	Applicability of requirements for optional UE features .....	636
6.1.1.4	Applicability of requirements for mandatory UE features with capability signalling .....	637
6.1.1.5	Applicability of Channel Quality Indicator (CQI) reporting requirements for CA .....	637
6.1.1.5.1	Applicability and test rules for different duplex modes and SCS combinations .....	637
6.1.1.5.2	Applicability and test rules for different CA configurations and bandwidth combination sets .....	638
6.1.1.5.3	Test coverage for different number of component carriers .....	638
6.1.1.5.4	Applicability rule and antenna connection for CA tests with 4 RX .....	638
6.1.1.6	Applicability of requirements for RedCap .....	638
6.1.1.7	Applicability of requirements for eRedCap .....	639
6.1.2	Common test parameters .....	639
6.2	Reporting of Channel Quality Indicator (CQI) .....	642
6.2.1	1RX requirements .....	642
6.2.1.1	FDD .....	642
6.2.1.1.1	CQI reporting definition under AWGN conditions .....	642
6.2.1.1.1.1	1Rx FDD FR1 periodic CQI reporting under AWGN conditions for RedCap .....	642
6.2.1.1.1.2	1Rx FDD FR1 periodic CQI reporting under AWGN conditions for eRedCap .....	645
6.2.1.1.2	CQI reporting under fading conditions .....	649
6.2.1.1.2.1	1Rx FDD FR1 periodic wideband CQI reporting under fading conditions for RedCap .....	649
6.2.1.1.2.2	1Rx FDD FR1 periodic wideband CQI reporting under fading conditions for eRedCap .....	654
6.2.1.2	TDD .....	659
6.2.1.2.1	CQI reporting definition under AWGN conditions .....	659
6.2.1.2.1.1	1Rx TDD FR1 periodic CQI reporting under AWGN conditions for RedCap .....	659
6.2.1.2.1.2	1Rx TDD FR1 periodic CQI reporting under AWGN conditions for eRedCap .....	662
6.2.1.2.2	CQI reporting definition under fading conditions .....	665
6.2.1.2.2.1	1Rx TDD FR1 periodic wideband CQI reporting under fading conditions for RedCap .....	665
6.2.1.2.2.2	1Rx TDD FR1 periodic wideband CQI reporting under fading conditions for eRedCap .....	671
6.2.2	2RX requirements .....	676
6.2.2.1	FDD .....	676
6.2.2.1.1	CQI reporting definition under AWGN conditions .....	676
6.2.2.1.1.1	2Rx FDD FR1 periodic CQI reporting under AWGN conditions for both SA and NSA .....	676
6.2.2.1.1.2	2Rx FDD FR1 periodic CQI reporting with Table 3 under AWGN conditions for both SA and NSA .....	680
6.2.2.1.1.3	2Rx FDD FR1 periodic CQI reporting with Table 4 under AWGN conditions for both SA and NSA .....	684
6.2.2.1.1.4	2Rx FDD FR1 periodic CQI reporting under AWGN conditions for RedCap .....	687
6.2.2.1.1.5	2Rx FDD FR1 periodic CQI reporting under AWGN conditions for eRedCap .....	689
6.2.2.1.2	CQI reporting under fading conditions .....	692
6.2.2.1.2.1	2Rx FDD FR1 periodic wideband CQI reporting under fading conditions for both SA and NSA .....	693

6.2.2.1.2.2	2Rx FDD FR1 aperiodic subband CQI reporting under fading conditions for both SA and NSA .....	698
6.2.2.1.2.3	2Rx FDD FR1 Wideband CQI reporting with inter-cell interference for both SA and NSA...	702
6.2.2.1.2.4	2Rx FDD FR1 periodic wideband CQI reporting under fading conditions for RedCap .....	706
6.2.2.1.2.5	2Rx FDD FR1 periodic wideband CQI reporting under fading conditions for eRedCap .....	709
6.2.2.2	TDD .....	713
6.2.2.2.1	CQI Reporting definition under AWGN conditions .....	713
6.2.2.2.1.1	2Rx TDD FR1 periodic CQI reporting under AWGN conditions for both SA and NSA .....	713
6.2.2.2.1.2	2Rx TDD FR1 periodic CQI reporting with Table 3 under AWGN conditions for both SA and NSA.....	716
6.2.2.2.1.3	2Rx TDD FR1 CQI reporting for PCell on band with shared spectrum access under AWGN conditions for both SA and NSA .....	720
6.2.2.2.1.4	2Rx TDD FR1 periodic CQI reporting with Table 4 under AWGN conditions for both SA and NSA.....	723
6.2.2.2.1.5	2Rx TDD FR1 periodic CQI reporting under AWGN conditions for RedCap .....	727
6.2.2.2.1.6	2Rx TDD FR1 periodic CQI reporting under AWGN conditions for eRedCap .....	730
6.2.2.2.2	CQI reporting under fading conditions.....	733
6.2.2.2.2.1	2Rx TDD FR1 periodic wideband CQI reporting under fading conditions for both SA and NSA .....	733
6.2.2.2.2.2	2Rx TDD FR1 aperiodic subband CQI reporting under fading conditions for both SA and NSA .....	735
6.2.2.2.2.3	2Rx TDD FR1 Wideband CQI reporting with inter-cell interference for both SA and NSA ..	739
6.2.2.2.2.4	2Rx TDD FR1 periodic wideband CQI reporting under fading conditions for RedCap.....	742
6.2.3	4RX requirements .....	746
6.2.3.1	FDD.....	746
6.2.3.1.1	CQI reporting definition under AWGN conditions .....	746
6.2.3.1.1.1	4Rx FDD FR1 periodic CQI reporting under AWGN conditions for both SA and NSA .....	747
6.2.3.1.1.2	4Rx FDD FR1 periodic CQI reporting with Table 3 under AWGN conditions for both SA and NSA.....	750
6.2.3.1.1.3	4Rx FDD FR1 periodic CQI reporting with Table 4 under AWGN conditions for both SA and NSA.....	753
6.2.3.1.2	CQI reporting definition under fading conditions .....	756
6.2.3.1.2.1	4Rx FDD FR1 periodic wideband CQI reporting under fading conditions for both SA and NSA .....	756
6.2.3.1.2.2	4Rx FDD FR1 aperiodic subband CQI reporting under fading conditions for both SA and NSA .....	759
6.2.3.1.2.3	4Rx FDD FR1 Wideband CQI reporting with inter-cell interference for both SA and NSA...	761
6.2.3.2	TDD .....	764
6.2.3.2.1	CQI reporting definition under AWGN conditions .....	764
6.2.3.2.1.1	4Rx TDD FR1 periodic CQI reporting under AWGN conditions for both SA and NSA .....	764
6.2.3.2.1.2	4Rx TDD FR1 periodic CQI reporting with Table 3 under AWGN conditions for both SA and NSA.....	767
6.2.3.2.1.3	4Rx TDD FR1 CQI reporting for PCell on band with shared spectrum access under AWGN conditions for both SA and NSA .....	770
6.2.3.2.1.4	4Rx TDD FR1 periodic CQI reporting with Table 4 under AWGN conditions for both SA and NSA.....	774
6.2.3.2.2	CQI reporting under fading conditions.....	777
6.2.3.2.2.1	4Rx TDD FR1 periodic wideband CQI reporting under fading conditions for both SA and NSA .....	777
6.2.3.2.2.2	4Rx TDD FR1 aperiodic subband CQI reporting under fading conditions for both SA and NSA .....	780
6.2.3.2.2.3	4Rx TDD FR1 Wideband CQI reporting with inter-cell interference for both SA and NSA ..	783
6.2.4	8RX requirements .....	786
6.2.4.1	FFS .....	786
6.2.4.2	TDD .....	786
6.2.4.2.1	CQI reporting definition under AWGN conditions .....	786
6.2.4.2.1.1	8Rx TDD FR1 periodic CQI reporting under AWGN conditions for both SA and NSA .....	786
6.2A	Reporting of Channel Quality Indicator (CQI) for CA.....	789
6.2A.1	General.....	789
6.2A.2	1RX requirements .....	789
6.2A.3	2RX and 4RX requirements.....	789
6.2A.3.1	CQI reporting definition under AWGN conditions.....	789

6.2A.3.1.0	Minimum requirement for periodic CQI reporting.....	789
6.2A.3.1.1	CQI reporting accuracy under AWGN conditions for CA (2DL CA).....	792
6.2A.3.1.1_1	2Rx FR1 CQI reporting under AWGN for Scell on band with shared spectrum access for CA (2DLCA).....	796
6.2A.3.1.2	CQI reporting accuracy under AWGN conditions for CA (3DL CA).....	802
6.2A.3.1.3	CQI reporting accuracy under AWGN conditions for CA (4DL CA).....	803
6.2A.3.1.4	CQI reporting accuracy under AWGN conditions for CA (5DL CA).....	804
6.2A.4	4RX requirements.....	805
6.2A.4.1	CQI reporting definition under AWGN conditions.....	805
6.2A.4.1.1	4Rx FR1 CQI reporting under AWGN for Scell on band with shared spectrum access for CA (2DLCA).....	805
6.3	Reporting of Precoding Matrix Indicator (PMI).....	811
6.3.0	General.....	811
6.3.1	1RX requirements.....	812
6.3.1.1	FDD.....	812
6.3.1.1.1	1Rx FDD Single PMI with 4TX TypeI-SinglePanel Codebook for RedCap.....	812
6.3.1.1.2	1Rx FDD Single PMI with 4TX TypeI-SinglePanel Codebook for eRedCap.....	816
6.3.1.2	TDD.....	821
6.3.1.2.1	1Rx TDD Single PMI with 4TX TypeI-SinglePanel Codebook for RedCap.....	821
6.3.1.2.2	1Rx TDD Single PMI with 4TX TypeI-SinglePanel Codebook for eRedCap.....	825
6.3.2	2RX requirements.....	829
6.3.2.1	FDD.....	829
6.3.2.1.1	2Rx FDD FR1 Single PMI with 4TX TypeI-SinglePanel codebook for both SA and NSA.....	829
6.3.2.1.1_1	2Rx FDD FR1 Single PMI with 4Tx TypeI-SinglePanel codebook for RedCap.....	834
6.3.2.1.2	2Rx FDD FR1 Single PMI with 8TX TypeI-SinglePanel codebook for both SA and NSA.....	835
6.3.2.1.3	2Rx FDD FR1 Multiple PMI with 16Tx Type I – SinglePanel Codebook for both SA and NSA.....	839
6.3.2.1.4	2Rx FDD FR1 Single PMI with 32Tx Type1 - SinglePanel codebook for both SA and NSA.....	843
6.3.2.1.5	2Rx FDD FR1 Multiple PMI with 16Tx TypeII codebook for both SA and NSA.....	847
6.3.2.1.6	2Rx FDD FR1 Multiple PMI with 16Tx Enhanced TypeII codebook for both SA and NSA.....	850
6.3.2.1.7	2Rx FDD FR1 Single PMI with 8TX TypeI-SinglePanel codebook for Single-DCI based transmission scheme for both SA and NSA.....	854
6.3.2.1.8	2Rx FDD FR1 Multiple PMI with 16TX Enhanced Type II codebook for predicted PMI for both SA and NSA.....	865
6.3.2.1.9	2Rx FDD FR1 Multiple PMI with 8 ports Enhanced Type II Codebook for CJT for both SA and NSA.....	870
6.3.2.1.10	2Rx FDD FR1 Single PMI with 4TX TypeI-SinglePanel codebook for eRedCap.....	878
6.3.2.2	TDD.....	882
6.3.2.2.1	2Rx TDD FR1 Single PMI with 4TX TypeI-SinglePanel codebook for both SA and NSA.....	882
6.3.2.2.2	2Rx TDD FR1 Single PMI with 8TX TypeI-SinglePanel codebook for both SA and NSA.....	887
6.3.2.2.3	2Rx TDD FR1 Multiple PMI with 16Tx Type1 - SinglePanel codebook for both SA and NSA.....	892
6.3.2.2.4	2Rx TDD FR1 Single PMI with 32Tx Type1 - SinglePanel codebook for both SA and NSA.....	895
6.3.2.2.5	2Rx TDD FR1 Multiple PMI with 16Tx TypeII codebook for both SA and NSA.....	899
6.3.2.2.6	2Rx TDD FR1 Multiple PMI with 16Tx Enhanced TypeII codebook for both SA and NSA.....	903
6.3.2.2.7	2Rx TDD Single PMI with 4TX TypeI-SinglePanel Codebook for RedCap.....	907
6.3.2.2.8	2Rx TDD FR1 Single PMI with 8TX TypeI-SinglePanel Codebook for Single-DCI based transmission scheme for both SA and NSA.....	911
6.3.2.2.9	2Rx TDD FR1 Multiple PMI with 16TX Enhanced Type II codebook for predicted PMI.....	922
6.3.2.2.10	2Rx TDD Single PMI with 4TX TypeI-SinglePanel Codebook for eRedCap.....	927
6.3.3	4RX requirements.....	931
6.3.3.1	FDD.....	931
6.3.3.1.1	4Rx FDD FR1 Single PMI with 4TX TypeI-SinglePanel codebook for both SA and NSA.....	931
6.3.3.1.2	4Rx FDD FR1 Single PMI with 8TX TypeI-SinglePanel codebook for both SA and NSA.....	936
6.3.3.1.3	4Rx FDD FR1 Multiple PMI with 16Tx Type I – SinglePanel Codebook for both SA and NSA.....	941
6.3.3.1.4	4Rx FDD FR1 Single PMI with 32Tx Type1 - SinglePanel codebook for both SA and NSA.....	944
6.3.3.1.5	4Rx FDD FR1 Multiple PMI with 16Tx TypeII codebook for both SA and NSA.....	948
6.3.3.1.6	4Rx FDD FR1 Multiple PMI with 16Tx Enhanced TypeII codebook for both SA and NSA.....	952
6.3.3.1.7	4Rx FDD FR1 Single PMI with 8 ports TypeI-SinglePanel Codebook for Single-DCI based transmission scheme.....	956
6.3.3.1.8	960	

6.3.3.1.9	4Rx FDD FR1 Multiple PMI with 8 ports Enhanced Type II Codebook for CJT for both SA and NSA .....	960
6.3.3.2	TDD .....	964
6.3.3.2.1	4Rx TDD FR1 Single PMI with 4TX TypeI-SinglePanel codebook for both SA and NSA .....	964
6.3.3.2.2	4Rx TDD FR1 Single PMI with 8TX TypeI-SinglePanel codebook for both SA and NSA .....	968
6.3.3.2.3	4Rx TDD FR1 Multiple PMI with 16Tx Type1 - SinglePanel codebook for both SA and NSA .....	973
6.3.3.2.4	4Rx TDD FR1 Single PMI with 32Tx Type1 - SinglePanel codebook for both SA and NSA .....	977
6.3.3.2.5	4Rx TDD FR1 Multiple PMI with 16Tx TypeII codebook for both SA and NSA .....	980
6.3.3.2.6	4Rx TDD FR1 Multiple PMI with 16Tx Enhanced TypeII codebook for both SA and NSA .....	985
6.3.3.2.7	4Rx TDD FR1 Single PMI with 8 ports TypeI-SinglePanel Codebook for Single-DCI based transmission scheme .....	988
6.4	Reporting of Rank Indicator (RI) .....	993
6.4.1	1RX requirements (Void) .....	993
6.4.2	2RX requirements .....	993
6.4.2.1	FDD .....	993
6.4.2.1_1	2Rx FDD FR1 RI reporting for both SA and NSA .....	993
6.4.2.1.1	2Rx FDD FR1 RI reporting for RedCap .....	997
6.4.2.2	TDD .....	1001
6.4.2.2_1	2Rx TDD FR1 RI reporting for both SA and NSA .....	1001
6.4.2.2.1	2Rx TDD FR1 RI reporting for RedCap .....	1006
6.4.3	4RX requirements .....	1010
6.4.3.1	FDD .....	1010
6.4.3.1_1	4Rx FDD FR1 RI reporting for both SA and NSA .....	1010
6.4.3.2	TDD .....	1014
6.4.3.2_1	4Rx TDD FR1 RI reporting for both SA and NSA .....	1014
7	Demodulation performance requirements (Radiated requirements) .....	1019
7.1	General .....	1019
7.1.1	Applicability of requirements .....	1019
7.1.1.1	General .....	1019
7.1.1.2	Applicability of requirements for different number of RX antenna ports .....	1019
7.1.1.3	Applicability of requirements for optional UE features .....	1019
7.1.1.4	Applicability of requirements for mandatory UE features with capability signaling .....	1020
7.1.1.5	Applicability of CA requirements .....	1020
7.1.1.5.1	Definition of CA capability .....	1020
7.1.1.5.2	Applicability and test rules for different CA configurations and bandwidth combination sets ...	1021
7.1.1.6	FFS .....	1021
7.1.1.7	Applicability of requirements for RedCap .....	1021
7.1.1_1	Applicability of test requirements due to maximum achievable SNR .....	1022
7.2	PDSCH demodulation requirements .....	1024
7.2.1	1RX requirements (Void) .....	1027
7.2.2	2RX requirements .....	1027
7.2.2.1	FDD (Void) .....	1027
7.2.2.2	TDD .....	1027
7.2.2.2.1	2Rx TDD FR2 PDSCH mapping Type A performance .....	1027
7.2.2.2.1_1	2Rx TDD FR2 PDSCH mapping Type A performance - 2x2 MIMO with baseline receiver for SA and NSA .....	1029
7.2.2.2.1_2	2Rx TDD FR2 PDSCH mapping Type A performance - 2x2 MIMO with enhanced type 1 receiver for SA and NSA .....	1033
7.2.2.2.1_3	2Rx TDD FR2 PDSCH mapping Type A performance - 2x2 MIMO with 256QAM for SA and NSA (Rel-16 and forward) .....	1034
7.2.2.2.2	2Rx TDD FR2 PDSCH repetitions over multiple slots .....	1035
7.2.2.2.2_1	2Rx TDD FR2 PDSCH repetitions over multiple slots - 2x2 MIMO with baseline receiver for SA and NSA .....	1036
7.2.2.2.3	2Rx TDD FR2 PDSCH Mapping Type B .....	1038
7.2.2.2.3_1	2Rx TDD FR2 PDSCH mapping Type B performance - 2x2 MIMO with baseline receiver for SA and NSA .....	1039
7.2.2.2.4	2Rx TDD FR2 PDSCH for HST-DPS .....	1041
7.2.2.2.4_1	2Rx TDD FR2 PDSCH for HST-DPS - 2x2 MIMO with baseline receiver for SA and NSA .....	1048
7.2.2.2.5	TDD FR2 PDSCH using Multi-DCI non-overlapping based transmission scheme performance .....	1053