



**5G;
NR;
User Equipment (UE) conformance specification;
Radio transmission and reception;
Part 4: Performance
(3GPP TS 38.521-4 version 19.0.0 Release 19)**



Reference

RTS/TSGR-0538521-4vj00

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed,
this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our
[Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2026.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by the ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found at [3GPP to ETSI numbering cross-referencing](#).

Modal verbs terminology

In the present document **"shall"**, **"shall not"**, **"should"**, **"should not"**, **"may"**, **"need not"**, **"will"**, **"will not"**, **"can"** and **"cannot"** are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and **"must not"** are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	23
1 Scope	24
2 References	24
3 Definition of terms, symbols and abbreviations.....	25
3.1 Terms.....	25
3.2 Symbols.....	26
3.3 Abbreviations	26
4 General	28
4.1 Relationship between minimum requirements and test requirements	28
4.2 Applicability of minimum requirements	28
4.3 Specification suffix information.....	29
4.4 Conducted requirements.....	29
4.4.0 Introduction.....	29
4.4.1 Reference point.....	29
4.4.2 SNR definition.....	29
4.4.3 Noc.....	30
4.4.3.1 Introduction.....	30
4.4.3.2 Noc for NR operating bands in FR1.....	30
4.4.3.2.1 Derivation of Noc values for NR operating bands in FR1.....	30
4.4.4 Es	30
4.4.4.1 Introduction.....	30
4.4.4.2 Es for NR operating bands in FR1	31
4.4.4.2.1 Derivation of Es values for NR operating bands in FR1	31
4.4.5 SINR definition.....	31
4.5 Radiated requirements.....	32
4.5.0 Introduction.....	32
4.5.1 Reference point.....	32
4.5.2 SNR definition	32
4.5.3 Noc.....	33
4.5.3.1 Introduction.....	33
4.5.3.2 Noc for NR operating bands in FR2.....	33
4.5.3.3 Derivation of Noc values for NR operating bands in FR2	33
4.5.4 Angle of arrival.....	34
4.5.5 Es	34
4.6 Test coverage across 5G NR connectivity options	34
5 Demodulation performance requirements (Conducted requirements)	35
5.1 General	35
5.1.1 Applicability of requirements	35
5.1.1.1 General	35
5.1.1.2 Applicability of requirements for different number of RX antenna ports	35
5.1.1.3 Applicability of requirements for optional UE features	36
5.1.1.4 Applicability of requirements for mandatory UE features with capability signalling.....	40
5.1.1.5 Applicability of CA requirements	42
5.1.1.5.1 Definition of CA capability	42
5.1.1.5.2 Applicability and test rules for different CA configurations and bandwidth combination sets	42
5.1.1.5.3 Applicability rule and antenna connection for CA tests with 4 RX.....	43
5.1.1.5.4 Applicability of different requirements for HST	44
5.1.1.5.5 Applicability and test rules for different CA configurations and bandwidth combination sets for 8Rx UE	45
5.1.1.5.6 Applicability rule and antenna connection for CA tests with 8 RX.....	47

5.1.1.5.7	Applicability rule for optional UE features for 8Rx	47
5.1.1.6	Applicability and test rules for PDSCH performance requirements with power imbalance for intra-band contiguous CA	47
5.1.1.7	Applicability of different requirements for HST.....	48
5.1.1.8	Applicability of different requirements with Multi-TRxP	48
5.1.1.9	Applicability of requirements for PDSCH on bands with shared spectrum access.....	49
5.1.1.10	Applicability of requirements for PDSCH with inter cell interference	49
5.1.1.11	Applicability of requirements for RedCap	49
5.1.1.12	Applicability of requirements for ATG.....	50
5.1.1.14	Applicability of requirements for eRedCap	51
5.2	PDSCH demodulation requirements	52
5.2.1	1RX requirements	54
5.2.1.1	FDD.....	54
5.2.1.1.1	1Rx FDD FR1 PDSCH performance for RedCap	54
5.2.1.1.2	1Rx FDD FR1 PDSCH performance for eRedCap	57
5.2.1.2	TDD	61
5.2.1.2.1	1Rx TDD FR1 PDSCH performance for RedCap	61
5.2.1.2.2	1Rx TDD FR1 PDSCH performance for eRedCap	64
5.2.2	2RX requirements	68
5.2.2.1	FDD.....	68
5.2.2.1.1	2Rx FDD FR1 PDSCH mapping Type A performance	68
5.2.2.1.1_1	2Rx FDD FR1 PDSCH mapping Type A performance - 2x2 MIMO with baseline receiver for both SA and NSA.....	70
5.2.2.1.1_2	2Rx FDD FR1 PDSCH mapping Type A performance - 2x2 MIMO with enhanced receiver type 1 for both SA and NSA	73
5.2.2.1.1_3	2Rx FDD FR1 PDSCH mapping Type A performance – 2x2 MIMO with baseline receiver for DL1024QAM for both SA and NSA	74
5.2.2.1.1_4	2Rx FDD FR1 PDSCH mapping Type A performance – 2x2 MIMO with enhanced DMRS for both SA and NSA.....	75
5.2.2.1.2	2Rx FDD FR1 PDSCH mapping Type A and CSI-RS overlapped with PDSCH performance	77
5.2.2.1.2_1	2Rx FDD FR1 PDSCH mapping Type A and CSI-RS overlapped with PDSCH performance - 2x2 MIMO with baseline receiver for both SA and NSA	78
5.2.2.1.3	2Rx FDD FR1 PDSCH mapping Type B performance	80
5.2.2.1.3_1	2Rx FDD FR1 PDSCH mapping Type B performance - 2x2 MIMO with baseline receiver for both SA and NSA.....	81
5.2.2.1.4	2Rx FDD FR1 PDSCH Mapping Type A and LTE-NR coexistence performance	83
5.2.2.1.4_1	2Rx FDD FR1 PDSCH Mapping Type A and LTE-NR coexistence performance - 4x2 MIMO with baseline receiver for both SA and NSA.....	84
5.2.2.1.5	2Rx FDD FR1 PDSCH 0.001% BLER performance	88
5.2.2.1.5_1	2Rx FDD FR1 PDSCH 0.001% BLER performance - 1x2 MIMO with baseline receiver for both SA and NSA.....	89
5.2.2.1.6	2Rx FDD FR1 PDSCH repetitions over multiple slots performance	91
5.2.2.1.6_1	2Rx FDD FR1 PDSCH repetitions over multiple slots performance - 2x2 MIMO with baseline receiver for both SA and NSA	92
5.2.2.1.7	2Rx FDD FR1 PDSCH Mapping Type B and UE processing capability 2 performance	93
5.2.2.1.7_1	2Rx FDD FR1 PDSCH Mapping Type B and UE processing capability 2 performance - 2x2 MIMO with baseline receiver for both SA and NSA	94
5.2.2.1.8	2Rx FDD FR1 PDSCH pre-emption performance	96
5.2.2.1.8_1	2Rx FDD FR1 PDSCH pre-emption performance - 2x2 MIMO with baseline receiver for both SA and NSA	98
5.2.2.1.9	2Rx FDD FR1 HST-SFN performance	100
5.2.2.1.9_1	2Rx FDD FR1 HST-SFN performance - 2x2 MIMO with baseline receiver for both SA and NSA.....	101
5.2.2.1.10	2Rx FDD FR1 HST DPS performance.....	103
5.2.2.1.10_1	2Rx FDD FR1 HST-DPS performance - 2x2 MIMO with baseline receiver for both SA and NSA.....	105
5.2.2.1.11	2Rx FDD FR1 PDSCH Single-DCI based SDM scheme performance.....	111
5.2.2.1.11_1	2Rx FDD FR1 PDSCH Single-DCI based SDM scheme performance - 2x2 MIMO for both SA and NSA	113
5.2.2.1.12	2Rx FDD FR1 PDSCH Multi-DCI based transmission scheme performance.....	116
5.2.2.1.12_1	2Rx FDD FR1 PDSCH Multiple-DCI based transmission scheme performance - 2x2 MIMO for both SA and NSA.....	118

5.2.2.1.13	2Rx FDD FR1 PDSCH Single-DCI based FDM scheme A performance	121
5.2.2.1.13_1	2Rx FDD FR1 PDSCH Single-DCI based FDM scheme A performance - 2x2 MIMO for both SA and NSA	123
5.2.2.1.14	2Rx FDD FR1 PDSCH Single-DCI based Inter-slot TDM scheme performance	126
5.2.2.1.14_1	2Rx FDD FR1 PDSCH Single-DCI based Inter-slot TDM scheme performance - 2x2 MIMO for both SA and NSA	128
5.2.2.1.15	2Rx FDD FR1 PDSCH with inter-cell interference	131
5.2.2.1.15_1	2Rx FDD FR1 PDSCH with inter-cell interference performance - 2x2 MIMO for both SA and NSA	133
5.2.2.1.16	2Rx FDD FR1 for PDSCH with intra-cell inter user interference	135
5.2.2.1.16_1	2Rx FDD FR1 for PDSCH with intra cell inter user interference performance for baseline MMSE-IRC receiver – 2x2 MIMO for both NSA and SA	137
5.2.2.1.16_2	2Rx FDD FR1 for PDSCH with intra cell inter user interference performance for Enhanced Receiver Type 2 – 2x2 MIMO for both NSA and SA	139
5.2.2.1.17	2Rx FDD FR1 PDSCH performance for RedCap	141
5.2.2.1.18	2Rx FDD FR1 for PDSCH CRS interference mitigation under NR-LTE coexistence scenario ...	145
5.2.2.1.18_1	2Rx FDD FR1 for PDSCH CRS interference mitigation under NR-LTE coexistence scenario – 2x2 MIMO for both NSA and SA	146
5.2.2.1.19	2Rx FDD FR1 for PDSCH with inter cell CRS interference	149
5.2.2.1.19_1	2Rx FDD FR1 for PDSCH with inter cell CRS interference scenario – 4x2 MIMO for both NSA and SA	151
5.2.2.1.20	2Rx FDD FR1 PDSCH HST-SFN Scheme A performance - 2x2 MIMO for both SA and NSA	154
5.2.2.1.21	2Rx FDD FR1 PDSCH HST-SFN Scheme B performance - 2x2 MIMO for both SA and NSA	162
5.2.2.1.22	2Rx FDD FR1 PDSCH ATG performance	165
5.2.2.1.23	2Rx FDD FR1 PDSCH performance for eRedCap	168
5.2.2.2	TDD	173
5.2.2.2.1	2Rx TDD FR1 PDSCH mapping Type A performance	173
5.2.2.2.1_1	2Rx TDD FR1 PDSCH mapping Type A performance - 2x2 MIMO with baseline receiver for both SA and NSA	175
5.2.2.2.1_2	2Rx TDD FR1 PDSCH mapping Type A performance - 2x2 MIMO with enhanced receiver type 1 for both SA and NSA	180
5.2.2.2.1_3	2Rx TDD FR1 PDSCH mapping Type A performance - 2x2 MIMO with baseline receiver for DL1024QAM for both SA and NSA	181
5.2.2.2.1_4	2Rx TDD FR1 PDSCH mapping Type A performance - 2x2 MIMO with enhanced DMRS for both SA and NSA	183
5.2.2.2.2	2Rx TDD FR1 PDSCH mapping Type A and CSI-RS overlapped with PDSCH performance	184
5.2.2.2.2_1	2Rx TDD FR1 PDSCH mapping Type A and CSI-RS overlapped with PDSCH performance - 2x2 MIMO with baseline receiver for both SA and NSA	184
5.2.2.2.3	2Rx TDD FR1 PDSCH mapping Type B performance	188
5.2.2.2.3_1	2Rx TDD FR1 PDSCH mapping Type B performance - 2x2 MIMO with baseline receiver for both SA and NSA	189
5.2.2.2.4	2Rx TDD FR1 PDSCH mapping Type A and LTE-NR coexistence performance	191
5.2.2.2.4_1	2Rx TDD FR1 PDSCH Mapping Type A and LTE-NR coexistence performance - 4x2 MIMO with baseline receiver for both SA and NSA	192
5.2.2.2.5	2Rx TDD FR1 PDSCH 0.001% BLER performance	197
5.2.2.2.5_1	2Rx TDD FR1 PDSCH 0.001% BLER performance - 1x2 MIMO with baseline receiver for both SA and NSA	198
5.2.2.2.6	2Rx TDD FR1 PDSCH repetitions over multiple slots performance	199
5.2.2.2.6_1	2Rx TDD FR1 PDSCH repetitions over multiple slots performance - 2x2 MIMO with baseline receiver for both SA and NSA	200
5.2.2.2.7	2Rx TDD FR1 PDSCH Mapping Type B and UE processing capability 2 performance	202
5.2.2.2.7_1	2Rx TDD FR1 PDSCH Mapping Type B and UE processing capability 2 performance - 2x2 MIMO with baseline receiver for both SA and NSA	203
5.2.2.2.8	2Rx TDD FR1 PDSCH pre-emption performance	205
5.2.2.2.8_1	2Rx TDD FR1 PDSCH pre-emption performance - 2x2 MIMO with baseline receiver for both SA and NSA	206
5.2.2.2.9	2Rx TDD FR1 HST-SFN performance	207
5.2.2.2.9_1	2Rx TDD FR1 HST-SFN performance - 2x2 MIMO with baseline receiver for both SA and NSA	208
5.2.2.2.10	2Rx TDD FR1 HST DPS performance	211

5.2.2.2.10_1	2Rx TDD FR1 HST-DPS performance - 2x2 MIMO with baseline receiver for both SA and NSA.....	213
5.2.2.2.11	2Rx TDD FR1 PDSCH Single-DCI based SDM scheme performance.....	218
5.2.2.2.11_1	2Rx TDD FR1 PDSCH Single-DCI based SDM scheme performance - 2x2 MIMO for both SA and NSA	220
5.2.2.2.12	2Rx TDD FR1 PDSCH Multi-DCI based transmission scheme performance	223
5.2.2.2.12_1	2Rx TDD FR1 PDSCH Multiple-DCI based transmission scheme performance - 2x2 MIMO for both SA and NSA.....	225
5.2.2.2.13	2Rx TDD FR1 PDSCH Single-DCI based FDM scheme A performance.....	226
5.2.2.2.13_1	2Rx TDD FR1 PDSCH Single-DCI based FDM scheme A performance - 2x2 MIMO for both SA and NSA	227
5.2.2.2.14	2Rx TDD FR1 PDSCH Single-DCI based Inter-slot TDM scheme performance.....	228
5.2.2.2.14_1	2Rx TDD FR1 PDSCH Single-DCI based Inter-slot TDM scheme performance - 2x2 MIMO for both SA and NSA.....	230
5.2.2.2.15	2Rx TDD FR1 PDSCH mapping type A performance on band with shared spectrum access	231
5.2.2.2.15_1	2Rx TDD FR1 PDSCH mapping type A performance on band with shared spectrum access – 2x2 MIMO for both NSA and SA.....	232
5.2.2.2.16	2Rx TDD FR1 for PDSCH with inter-cell interference performance.....	235
5.2.2.2.16_1	2Rx TDD FR1 for PDSCH with inter-cell interference performance – 2x2 MIMO for both NSA and SA.....	236
5.2.2.2.17	2Rx TDD FR1 for PDSCH with intra-cell inter user interference.....	239
5.2.2.2.17_1	2Rx TDD FR1 for PDSCH with baseline MMSE-IRC receiver – 2x2 MIMO for both NSA and SA.....	241
5.2.2.2.17_2	2Rx TDD FR1 for PDSCH with Enhanced Receiver Type 2 – 2x2 MIMO for both NSA and SA	242
5.2.2.2.18	2Rx TDD FR1 PDSCH performance for RedCap	244
5.2.2.2.19	2Rx TDD FR1 for PDSCH CRS interference mitigation under NR-LTE coexistence scenario ...	248
5.2.2.2.19_1	2Rx TDD FR1 for PDSCH CRS interference mitigation under NR-LTE coexistence scenario – 4x2 MIMO for both NSA and SA	249
5.2.2.2.20	2Rx TDD FR1 for PDSCH with inter cell CRS interference	252
5.2.2.2.20_1	2Rx TDD FR1 for PDSCH with inter cell CRS interference scenario – 4x2 MIMO for both NSA and SA	254
5.2.2.2.21	2Rx TDD FR1 PDSCH HST-SFN Scheme A performance - 2x2 MIMO for both SA and NSA.....	257
5.2.2.2.22	2Rx TDD FR1 PDSCH HST-SFN Scheme B performance - 2x2 MIMO for both SA and NSA.....	265
5.2.2.2.23	2Rx TDD FR1 PDSCH ATG performance	268
5.2.2.2.24	2Rx TDD FR1 PDSCH performance for eRedCap	271
5.2.3	4RX requirements.....	276
5.2.3.1	FDD.....	276
5.2.3.1.1	4Rx FDD FR1 PDSCH mapping Type A performance.....	276
5.2.3.1.1_1	4Rx FDD FR1 PDSCH mapping Type A performance - 2x4 MIMO with baseline receiver for both SA and NSA.....	278
5.2.3.1.1_2	4Rx FDD FR1 PDSCH mapping Type A performance - 4x4 MIMO with baseline receiver for both SA and NSA.....	281
5.2.3.1.1_3	FFS.....	282
5.2.3.1.1_4	4Rx FDD FR1 PDSCH mapping Type A performance - 4x4 MIMO with enhanced receiver type 1 for both SA and NSA	282
5.2.3.1.1_5	4Rx FDD FR1 PDSCH mapping Type A performance - 2x4 MIMO with baseline receiver for DL1024QAM for both SA and NSA.....	283
5.2.3.1.1_6	4Rx FDD FR1 PDSCH mapping Type A performance - 4x4 MIMO with enhanced DMRS for both SA and NSA.....	285
5.2.3.1.2	4Rx FDD FR1 PDSCH mapping Type A and CSI-RS overlapped with PDSCH performance	286
5.2.3.1.2_1	4Rx FDD FR1 PDSCH mapping Type A and CSI-RS overlapped with PDSCH performance - 4x4 MIMO with baseline receiver for both SA and NSA	287
5.2.3.1.3	4Rx FDD FR1 PDSCH mapping Type B performance	290
5.2.3.1.3_1	4Rx FDD FR1 PDSCH mapping Type B performance - 2x4 MIMO with baseline receiver for both SA and NSA.....	291
5.2.3.1.4	4Rx FDD FR1 PDSCH Mapping Type A and LTE-NR coexistence performance	293
5.2.3.1.4_1	4Rx FDD FR1 PDSCH Mapping Type A and LTE-NR coexistence performance - 4x4 MIMO with baseline receiver for both SA and NSA.....	294
5.2.3.1.5	4Rx FDD FR1 PDSCH 0.001% BLER performance	295

5.2.3.1.5_1	4Rx FDD FR1 PDSCH 0.001% BLER performance - 1x4 MIMO with baseline receiver for both SA and NSA	296
5.2.3.1.6	4Rx FDD FR1 PDSCH repetitions over multiple slots performance	298
5.2.3.1.6_1	4Rx FDD FR1 PDSCH repetitions over multiple slots performance - 2x4 MIMO with baseline receiver for both SA and NSA	298
5.2.3.1.7	4Rx FDD FR1 PDSCH Mapping Type B and UE processing capability 2 performance	300
5.2.3.1.7_1	4Rx FDD FR1 PDSCH Mapping Type B and UE processing capability 2 performance - 2x4 MIMO with baseline receiver for both SA and NSA	301
5.2.3.1.8	4Rx FDD FR1 PDSCH pre-emption performance	303
5.2.3.1.8_1	4Rx FDD FR1 PDSCH pre-emption performance - 2x4 MIMO with baseline receiver for both SA and NSA	304
5.2.3.1.9	4Rx FDD FR1 HST-SFN performance	306
5.2.3.1.9_1	4Rx FDD FR1 HST-SFN performance - 2x4 MIMO with baseline receiver for both SA and NSA	307
5.2.3.1.10	4Rx FDD FR1 HST DPS performance	309
5.2.3.1.10_1	4Rx FDD FR1 HST-DPS performance - 2x4 MIMO with baseline receiver for both SA and NSA	311
5.2.3.1.11	4Rx FDD FR1 PDSCH Single-DCI based SDM scheme performance	317
5.2.3.1.11_1	4Rx FDD FR1 PDSCH Single-DCI based SDM scheme performance - 2x4 MIMO for both SA and NSA	318
5.2.3.1.12	4Rx FDD FR1 PDSCH Multi-DCI based transmission scheme performance	322
5.2.3.1.12_1	4Rx FDD FR1 PDSCH Multiple-DCI based transmission scheme performance - 2x4 MIMO for both SA and NSA	324
5.2.3.1.13	4Rx FDD FR1 PDSCH Single-DCI based FDM scheme A performance	327
5.2.3.1.13_1	4Rx FDD FR1 PDSCH Single-DCI based FDM scheme A performance - 2x4 MIMO for both SA and NSA	329
5.2.3.1.14	4Rx FDD FR1 PDSCH Single-DCI based Inter-slot TDM scheme performance	332
5.2.3.1.14_1	4Rx FDD FR1 PDSCH Single-DCI based Inter-slot TDM scheme performance - 2x4 MIMO for both SA and NSA	334
5.2.3.1.15	4Rx FDD FR1 PDSCH with inter-cell interference	337
5.2.3.1.15_1	4Rx FDD FR1 PDSCH with inter-cell interference performance - 2x4 MIMO for both SA and NSA	339
5.2.3.1.16	4Rx FDD FR1 for PDSCH with intra-cell inter-user interference	341
5.2.3.1.16_1	4Rx FDD FR1 for PDSCH with intra cell inter user interference performance for baseline MMSE-IRC receiver – 2x4 MIMO for both NSA and SA	344
5.2.3.1.16_2	4Rx FDD FR1 for PDSCH with intra cell inter user interference performance for baseline MMSE-IRC receiver – 4x4 MIMO for both NSA and SA	345
5.2.3.1.16_3	4Rx FDD FR1 for PDSCH with intra cell inter user interference performance for Enhanced Receiver Type 2 – 2x4 MIMO for both NSA and SA	347
5.2.3.1.16_4	4Rx FDD FR1 for PDSCH with intra cell inter user interference performance for Enhanced Receiver Type 2 – 4x4 MIMO for both NSA and SA	349
5.2.3.1.17	4Rx FDD FR1 for PDSCH CRS interference mitigation under NR-LTE coexistence scenario ...	351
5.2.3.1.17_1	4Rx FDD FR1 for PDSCH CRS interference mitigation under NR-LTE coexistence scenario – 2x4 MIMO for both NSA and SA	352
5.2.3.1.18	4Rx FDD FR1 for PDSCH with inter cell CRS interference	355
5.2.3.1.18_1	4Rx FDD FR1 for PDSCH with inter cell CRS interference scenario – 4x4 MIMO for both NSA and SA	357
5.2.3.1.19	4Rx FDD FR1 PDSCH HST-SFN Scheme A performance - 2x4 MIMO for both SA and NSA	360
5.2.3.1.20	4Rx FDD FR1 PDSCH HST-SFN Scheme B performance - 2x4 MIMO for both SA and NSA	367
5.2.3.1.21	4Rx FDD FR1 PDSCH ATG performance	371
5.2.3.2	TDD	374
5.2.3.2.1	4Rx TDD FR1 PDSCH mapping Type A performance	374
5.2.3.2.1_1	4Rx TDD FR1 PDSCH mapping Type A performance - 2x4 MIMO with baseline receiver for both SA and NSA	377
5.2.3.2.1_2	4Rx TDD FR1 PDSCH mapping Type A performance - 4x4 MIMO with baseline receiver for both SA and NSA	382
5.2.3.2.1_3	4Rx TDD FR1 PDSCH mapping Type A performance - 2x4 MIMO with enhanced receiver type 1 for both SA and NSA	383
5.2.3.2.1_4	4Rx TDD FR1 PDSCH mapping Type A performance - 4x4 MIMO with enhanced receiver type 1 for both SA and NSA	383

5.2.3.2.1_5	4Rx TDD FR1 PDSCH mapping Type A performance - 2x4 MIMO with baseline receiver for DL1024QAM for both SA and NSA	384
5.2.3.2.1_6	4Rx TDD FR1 PDSCH mapping Type A performance - 4x4 MIMO with enhanced DMRS for both SA and NSA.....	386
5.2.3.2.2	4Rx TDD FR1 PDSCH mapping Type A and CSI-RS overlapped with PDSCH performance	387
5.2.3.2.2_1	4Rx TDD FR1 PDSCH mapping Type A and CSI-RS overlapped with PDSCH performance - 2x4 MIMO with baseline receiver for both SA and NSA	388
5.2.3.2.3	4Rx TDD FR1 PDSCH mapping Type B performance.....	391
5.2.3.2.3_1	4Rx TDD FR1 PDSCH mapping Type B performance - 2x4 MIMO with baseline receiver for both SA and NSA.....	391
5.2.3.2.4	4Rx TDD FR1 PDSCH mapping Type A performance.....	393
5.2.3.2.4_1	4Rx TDD FR1 PDSCH Mapping Type A and LTE-NR coexistence performance - 4x4 MIMO with baseline receiver for both SA and NSA.....	395
5.2.3.2.5	4Rx TDD FR1 PDSCH 0.001% BLER performance	396
5.2.3.2.5_1	4Rx TDD FR1 PDSCH 0.001% BLER performance - 1x4 MIMO with baseline receiver for both SA and NSA.....	397
5.2.3.2.6	4Rx TDD FR1 PDSCH repetitions over multiple slots performance	398
5.2.3.2.6_1	4Rx TDD FR1 PDSCH repetitions over multiple slots performance - 2x4 MIMO with baseline receiver for both SA and NSA	399
5.2.3.2.7	4Rx TDD FR1 PDSCH Mapping Type B and UE processing capability 2 performance.....	401
5.2.3.2.7_1	4Rx TDD FR1 PDSCH Mapping Type B and UE processing capability 2 performance - 2x4 MIMO with baseline receiver for both SA and NSA.....	402
5.2.3.2.8	4Rx TDD FR1 PDSCH pre-emption performance	404
5.2.3.2.8_1	4Rx TDD FR1 PDSCH pre-emption performance - 2x4 MIMO with baseline receiver for both SA and NSA	405
5.2.3.2.9	4Rx TDD FR1 HST-SFN performance	406
5.2.3.2.9_1	4Rx TDD FR1 HST-SFN performance - 2x4 MIMO with baseline receiver for both SA and NSA.....	407
5.2.3.2.10	4Rx TDD FR1 HST DPS performance	410
5.2.3.2.10_1	4Rx TDD FR1 HST DPS performance - 2x4 MIMO with baseline receiver for both SA and NSA.....	412
5.2.3.2.11	4Rx TDD FR1 PDSCH Single-DCI based SDM scheme performance.....	417
5.2.3.2.11_1	4Rx TDD FR1 PDSCH Single-DCI based SDM scheme performance - 2x4 MIMO for both SA and NSA	419
5.2.3.2.12	4Rx TDD FR1 PDSCH Multi-DCI based transmission scheme performance	422
5.2.3.2.12_1	4Rx TDD FR1 PDSCH Multiple-DCI based transmission scheme performance - 2x4 MIMO for both SA and NSA.....	424
5.2.3.2.13	4Rx TDD FR1 PDSCH Single-DCI based FDM scheme A performance.....	425
5.2.3.2.13_1	4Rx TDD FR1 PDSCH Single-DCI based FDM scheme A performance - 2x4 MIMO for both SA and NSA	426
5.2.3.2.14	4Rx TDD FR1 PDSCH Single-DCI based Inter-slot TDM scheme performance	427
5.2.3.2.14_1	4Rx TDD FR1 PDSCH Single-DCI based Inter-slot TDM scheme performance - 2x4 MIMO for both SA and NSA.....	429
5.2.3.2.15	4Rx TDD FR1 PDSCH mapping type A performance on band with shared spectrum access	430
5.2.3.2.15_1	4Rx TDD FR1 PDSCH mapping type A performance on band with shared spectrum access – 2x4 MIMO for both NSA and SA.....	431
5.2.3.2.16	4Rx TDD FR1 for PDSCH with inter-cell interference performance.....	432
5.2.3.2.16_1	4Rx TDD FR1 for PDSCH with inter-cell interference performance – 2x4 MIMO for both NSA and SA.....	434
5.2.3.2.17	4Rx TDD FR1 for PDSCH with intra-cell inter-user interference	436
5.2.3.2.17_1	2Rx TDD FR1 for PDSCH with baseline MMSE-IRC receiver – 2x2 MIMO for both NSA and SA.....	439
5.2.3.2.17_2	4Rx TDD FR1 for PDSCH with baseline MMSE-IRC receiver – 4x4 MIMO for both NSA and SA.....	440
5.2.3.2.17_3	4Rx TDD FR1 for PDSCH with intra cell inter user interference performance for Enhanced Receiver Type 2 – 2x4 MIMO for both NSA and SA.....	442
5.2.3.2.17_4	4Rx TDD FR1 for PDSCH with intra cell inter user interference performance for Enhanced Receiver Type 2 – 4x4 MIMO for both NSA and SA.....	444
5.2.3.2.18	4Rx TDD FR1 for PDSCH CRS interference mitigation under NR-LTE coexistence scenario ...	446
5.2.3.2.18_1	4Rx TDD FR1 for PDSCH CRS interference mitigation under NR-LTE coexistence scenario – 4x4 MIMO for both NSA and SA	448
5.2.3.2.19	4Rx TDD FR1 for PDSCH with inter cell CRS interference	450

5.2.3.2.19_1	4Rx TDD FR1 for PDSCH with inter cell CRS interference scenario – 4x4 MIMO for both NSA and SA	452
5.2.3.2.20	4Rx TDD FR1 PDSCH HST-SFN Scheme A performance - 2x4 MIMO for both SA and NSA	456
5.2.3.2.21	4Rx TDD FR1 PDSCH HST-SFN Scheme B performance - 2x4 MIMO for both SA and NSA	463
5.2.3.2.22	4Rx TDD FR1 PDSCH ATG performance	467
5.2.4	8RX requirements	470
5.2.4.1	FDD	470
5.2.4.1.1	8Rx FDD FR1 PDSCH mapping Type A performance	470
5.2.4.1.1_1	8Rx FDD FR1 PDSCH mapping Type A performance - 2x8 MIMO with baseline 8Rx receiver for both SA and NSA	472
5.2.4.1.1_2	8Rx TDD FR1 PDSCH mapping Type A performance - 4x8 MIMO with baseline receiver for both SA and NSA	473
5.2.4.1.1_3	474	
5.2.4.1.1_4	474	
5.2.4.1.1_5	8Rx FDD FR1 PDSCH mapping Type A performance - 8x8 MIMO with baseline receiver for both SA and NSA	474
5.2.4.1.3	8Rx FDD FR1 for PDSCH with intra-cell inter-user interference	475
5.2.4.1.3_1	8Rx FDD FR1 for PDSCH with intra-cell inter-user interference – 4x8 MIMO with baseline 8Rx receiver for both SA and NSA	477
5.2.4.2	TDD	479
5.2.4.2.1	8Rx TDD FR1 PDSCH mapping Type A performance	479
5.2.4.2.1_1	8Rx TDD FR1 PDSCH mapping Type A performance - 2x8 MIMO with baseline receiver for both SA and NSA	480
5.2.4.2.1_2	8Rx TDD FR1 PDSCH mapping Type A performance - 4x8 MIMO with baseline receiver for both SA and NSA	482
5.2.4.2.1_3	8Rx TDD FR1 PDSCH mapping Type A performance – 2x8 MIMO with simplified receiver for both SA and NSA	483
5.2.4.2.1_4	8Rx TDD FR1 PDSCH mapping Type A performance – 4x8 MIMO with simplified receiver for both SA and NSA	485
5.2.4.2.1_5	8Rx TDD FR1 PDSCH mapping Type A performance - 8x8 MIMO with baseline receiver for both SA and NSA	486
5.2A	PDSCH demodulation requirements for CA	487
5.2A.1	1RX requirements (Void)	489
5.2A.2	2RX requirements	489
5.2A.2.1	Requirements for 2RX normal PDSCH	489
5.2A.2.1.0	Minimum conformance requirements for 2RX normal PDSCH	489
5.2A.2.1.1	2Rx Normal PDSCH Demodulation Performance for CA (2DL CA) for both SA and NSA	490
5.2A.2.1.2	2Rx Normal PDSCH Demodulation Performance for CA (3DL CA) for both SA and NSA	493
5.2A.2.1.3	2Rx Normal PDSCH Demodulation Performance for CA (4DL CA) for both SA and NSA	494
5.2A.2.1.4	2Rx Normal PDSCH Demodulation Performance for CA (5DL CA) for both SA and NSA	495
5.2A.2.1.5	2Rx Normal PDSCH Demodulation Performance for CA (6DL CA) for both SA and NSA	495
5.2A.2.2	Requirements for 2RX PDSCH carrier aggregation with power imbalance	496
5.2A.2.2.0	Minimum conformance requirements for 2RX PDSCH CA with power imbalance	496
5.2A.2.2.1	2Rx PDSCH Demodulation Performance for CA with power imbalance (2DL CA)	497
5.2A.2.2.2	Void	499
5.2A.2.2.3	Void	499
5.2A.2.3	2Rx TDD FR1 PDSCH mapping type A performance of SCell on band with shared spectrum access	499
5.2A.2.4	Requirements for 2RX HST-SFN CA PDSCH	501
5.2A.2.4.0	Minimum conformance requirements for 2RX HST-SFN CA PDSCH	501
5.2A.2.4.1	2Rx PDSCH Demodulation Performance for HST-SFN CA	503
5.2A.2.5	Requirements for 2RX HST-DPS CA PDSCH	507
5.2A.2.5.0	Minimum conformance requirements for 2RX HST-DPS CA PDSCH	507
5.2A.2.5.1	2RX PDSCH Demodulation Performance for HST-DPS CA	512
5.2A.3	4RX requirements	518
5.2A.3.1	Requirements for 4RX normal PDSCH	518
5.2A.3.1.0	Minimum conformance requirements for 4RX normal PDSCH	518
5.2A.3.1.1	4Rx Normal PDSCH Demodulation Performance for CA (2DL CA) for both SA and NSA	520
5.2A.3.1.2	4Rx Normal PDSCH Demodulation Performance for CA (3DL CA) for both SA and NSA	523
5.2A.3.1.3	4Rx Normal PDSCH Demodulation Performance for CA (4DL CA) for both SA and NSA	523

5.2A.3.1.4	4Rx Normal PDSCH Demodulation Performance for CA (5DL CA) for both SA and NSA	524
5.2A.3.1.5	4Rx Normal PDSCH Demodulation Performance for CA (6DL CA) for both SA and NSA	525
5.2A.3.2	Requirements for 4RX PDSCH carrier aggregation with power imbalance	525
5.2A.3.2.0	Minimum requirements for carrier aggregation with power imbalance	525
5.2A.3.2.1	4Rx PDSCH Demodulation Performance for CA with power imbalance (2DL CA).....	527
5.2A.3.3	4Rx TDD FR1 PDSCH mapping type A performance of SCell on band with shared spectrum access.....	528
5.2A.3.4	Requirements for 4RX HST-SFN CA PDSCH.....	530
5.2A.3.4.0	Minimum conformance requirements for 4RX HST-SFN CA PDSCH	530
5.2A.3.4.1	4RX PDSCH Demodulation Performance for HST-SFN CA	533
5.2A.3.5	Requirements for 4RX HST-DPS CA PDSCH.....	536
5.2A.3.5.0	Minimum conformance requirements for 4RX HST-DPS CA PDSCH	536
5.2A.3.5.1	4RX PDSCH Demodulation Performance for HST-DPS CA	541
5.2A.3A	2Rx-4RX requirements	548
5.2A.3A.1	Requirements for 2Rx-4RX normal PDSCH	548
5.2A.3A.1.0	Minimum conformance requirements for 2Rx-4RX normal PDSCH.....	548
5.2A.3A.1.1	2Rx-4Rx Normal PDSCH Demodulation Performance for CA (2DL CA) for both SA and NSA	548
5.2A.3A.1.2	2Rx-4Rx Normal PDSCH Demodulation Performance for CA (3DL CA) for both SA and NSA	552
5.2A.3A.1.3	2Rx-4Rx Normal PDSCH Demodulation Performance for CA (4DL CA) for both SA and NSA	552
5.2A.3A.1.4	2Rx-4Rx Normal PDSCH Demodulation Performance for CA (5DL CA) for both SA and NSA	553
5.2A.3A.1.5	2Rx-4Rx Normal PDSCH Demodulation Performance for CA (6DL CA) for both SA and NSA	553
5.3	PDCCH demodulation requirements	554
5.3.1	1RX requirements	555
5.3.1.1	FDD.....	555
5.3.1.1.1	1Rx FDD FR1 PDCCH performance for RedCap	556
5.3.1.2	TDD	558
5.3.1.2.1	1Rx TDD FR1 PDCCH performance for RedCap.....	558
5.3.2	2RX requirements	560
5.3.2.1	FDD.....	560
5.3.2.1.1	2Rx FDD FR1 PDCCH 1 Tx antenna performance for both SA and NSA	561
5.3.2.1.2	2Rx FDD FR1 PDCCH 2 Tx antenna performance for both SA and NSA	564
5.3.2.1.3	2Rx FDD FR1 PDCCH 1 Tx antenna performance for power saving.....	567
5.3.2.1.4	2Rx FDD FR1 PDCCH performance for RedCap	572
5.3.2.1.5	2RX FDD Minimum requirements for PDCCH with intra-slot repetition	574
5.3.2.1.7	2RX FDD FR1 PDCCH antenna performance for 3 MHz channel bandwidth	578
5.3.2.2	TDD	580
5.3.2.2.1	2Rx TDD FR1 PDCCH 1 Tx antenna performance for both SA and NSA	581
5.3.2.2.2	2Rx TDD FR1 PDCCH 2 Tx antenna performance for both SA and NSA	584
5.3.2.2.3	2Rx TDD FR1 PDCCH 1 Tx antenna performance for power saving	586
5.3.2.2.4	2Rx TDD FR1 PDCCH performance for RedCap.....	592
5.3.2.2.5	2RX TDD Minimum requirements for PDCCH with intra-slot repetition	594
5.3.3	4RX requirements	597
5.3.3.1	FDD.....	597
5.3.3.1.1	4Rx FDD FR1 PDCCH 1 Tx antenna performance for both SA and NSA	598
5.3.3.1.2	4Rx FDD FR1 PDCCH 2 Tx antenna performance for both SA and NSA	601
5.3.3.1.3	4Rx FDD FR1 PDCCH 1 Tx antenna performance for power saving.....	604
5.3.3.1.4	4RX FDD Minimum requirements for PDCCH with intra-slot repetition	609
5.3.3.1.5	613	
5.3.3.1.6	4RX FDD FR1 PDCCH antenna performance for 3 MHz channel bandwidth	613
5.3.3.2	TDD	616
5.3.3.2.1	4Rx TDD FR1 PDCCH 1 Tx antenna performance for both SA and NSA	616
5.3.3.2.2	4Rx TDD FR1 PDCCH 2 Tx antenna performance for both SA and NSA	619
5.3.3.2.3	4Rx TDD FR1 PDCCH 1 Tx antenna performance for power saving	622
5.3.3.2.4	4RX TDD Minimum requirements for PDCCH with intra-slot repetition	627
5.4	PBCH demodulation requirements	630
5.5	Sustained downlink data rate provided by lower layers	630
5.5.1	FR1 Sustained downlink data rate performance for single carrier.....	630

5.5.1_1	FR1 Sustained downlink data rate performance for single carrier for 8Rx.....	638
5.5.2	FR1 Sustained downlink data rate performance for single carrier with DL1024QAM	642
5.5.3	FR1 Sustained downlink data rate performance for RedCap	644
5.5.4	FR1 Sustained downlink data rate performance for eRedCap	645
Same as in Clause 5.5.1.5.5.5A.1	FR1 Sustained downlink data rate performance for carrier aggregation	646
5.5A.1.1	FR1 SDR performance for CA (2DL CA).....	646
5.5A.1.2	FR1 SDR performance for CA (3DL CA)	654
5.5A.1.2.1	Test Purpose	654
5.5A.1.2.2	Test applicability	654
5.5A.1.2.3	Minimum conformance requirements.....	654
5.5A.1.2.4	Test description	654
5.5A.1.2.5	Test requirement.....	654
5.5A.1.3	FR1 SDR performance for CA (4DL CA)	654
5.5A.1.3.1	Test Purpose	654
5.5A.1.3.2	Test applicability	654
5.5A.1.3.3	Minimum conformance requirements.....	654
5.5A.1.3.4	Test description	655
5.5A.1.3.5	Test requirement	655
5.5A.1.4	FR1 SDR performance for CA (5DL CA)	655
5.5A.1.4.1	Test Purpose	655
5.5A.1.4.2	Test applicability	655
5.5A.1.4.3	Minimum conformance requirements.....	655
5.5A.1.4.4	Test description	655
5.5A.1.4.5	Test requirement.....	655
5.6	PDSCH absolute physical layer throughput requirements	655
5.6.1	1RX requirements	655
5.6.2	2RX requirements	656
5.6.2.1	FDD.....	656
5.6.2.1.1	2Rx FDD FR1 PDSCH absolute physical layer throughput performance with link adaptation	656
5.6.2.1.1_1	2Rx FDD FR1 PDSCH performance with link adaptation - 2x2 MIMO for both SA and NSA	657
5.6.2.2	TDD	659
5.6.2.2.1	2Rx TDD FR1 PDSCH absolute physical layer throughput performance with link adaptation	659
5.6.2.2.1_1	2Rx TDD FR1 PDSCH performance with link adaptation - 2x2 MIMO for both SA and NSA	661
5.6.3	4Rx requirements.....	662
5.6.3.1	FDD.....	662
5.6.3.1.1	4Rx FDD FR1 PDSCH absolute physical layer throughput performance with link adaptation	662
5.6.3.1.1_1	4Rx FDD FR1 PDSCH performance with link adaptation - 2x4 MIMO for both SA and NSA	664
5.6.3.2	TDD	665
5.6.3.2.1	4Rx TDD FR1 PDSCH absolute physical layer throughput performance with link adaptation	665
5.6.3.2.1_1	4Rx TDD FR1 PDSCH performance with link adaptation - 2x4 MIMO for both SA and NSA	667
6	CSI reporting requirements (Conducted requirements)	669
6.1	General	669
6.1.1	Applicability of requirements	669
6.1.1.1	General	669
6.1.1.2	Applicability of requirements for different number of RX antenna ports	669
6.1.1.3	Applicability of requirements for optional UE features	670
6.1.1.4	Applicability of requirements for mandatory UE features with capability signalling.....	671
6.1.1.5	Applicability of Channel Quality Indicator (CQI) reporting requirements for CA	671
6.1.1.5.1	Applicability and test rules for different duplex modes and SCS combinations	671
6.1.1.5.2	Applicability and test rules for different CA configurations and bandwidth combination sets	672
6.1.1.5.3	Test coverage for different number of component carriers.....	672
6.1.1.5.4	Applicability rule and antenna connection for CA tests with 4 RX.....	672
6.1.1.6	Applicability of requirements for RedCap	672
6.1.1.7	Applicability of requirements for eRedCap	673
6.1.2	Common test parameters	673
6.2	Reporting of Channel Quality Indicator (CQI).....	676

6.2.1	1RX requirements	676
6.2.1.1	FDD.....	676
6.2.1.1.1	CQI reporting definition under AWGN conditions	676
6.2.1.1.1.1	1Rx FDD FR1 periodic CQI reporting under AWGN conditions for RedCap	676
6.2.1.1.1.2	1Rx FDD FR1 periodic CQI reporting under AWGN conditions for eRedCap	679
6.2.1.1.2	CQI reporting under fading conditions.....	683
6.2.1.1.2.1	1Rx FDD FR1 periodic wideband CQI reporting under fading conditions for RedCap	683
6.2.1.1.2.2	1Rx FDD FR1 periodic wideband CQI reporting under fading conditions for eRedCap	688
6.2.1.2	TDD	692
6.2.1.2.1	CQI reporting definition under AWGN conditions	692
6.2.1.2.1.1	1Rx TDD FR1 periodic CQI reporting under AWGN conditions for RedCap	692
6.2.1.2.1.2	1Rx TDD FR1 periodic CQI reporting under AWGN conditions for eRedCap	696
6.2.1.2.2	CQI reporting definition under fading conditions	699
6.2.1.2.2.1	1Rx TDD FR1 periodic wideband CQI reporting under fading conditions for RedCap.....	699
6.2.1.2.2.2	1Rx TDD FR1 periodic wideband CQI reporting under fading conditions for eRedCap	704
6.2.2	2RX requirements	710
6.2.2.1	FDD.....	710
6.2.2.1.1	CQI reporting definition under AWGN conditions	710
6.2.2.1.1.1	2Rx FDD FR1 periodic CQI reporting under AWGN conditions for both SA and NSA	710
6.2.2.1.1.2	2Rx FDD FR1 periodic CQI reporting with Table 3 under AWGN conditions for both SA and NSA.....	713
6.2.2.1.1.3	2Rx FDD FR1 periodic CQI reporting with Table 4 under AWGN conditions for both SA and NSA.....	717
6.2.2.1.1.4	2Rx FDD FR1 periodic CQI reporting under AWGN conditions for RedCap	720
6.2.2.1.1.5	2Rx FDD FR1 periodic CQI reporting under AWGN conditions for eRedCap	723
6.2.2.1.2	CQI reporting under fading conditions.....	726
6.2.2.1.2.1	2Rx FDD FR1 periodic wideband CQI reporting under fading conditions for both SA and NSA	726
6.2.2.1.2.2	2Rx FDD FR1 aperiodic subband CQI reporting under fading conditions for both SA and NSA	731
6.2.2.1.2.3	2Rx FDD FR1 Wideband CQI reporting with inter-cell interference for both SA and NSA...736	
6.2.2.1.2.4	2Rx FDD FR1 periodic wideband CQI reporting under fading conditions for RedCap	739
6.2.2.1.2.5	2Rx FDD FR1 periodic wideband CQI reporting under fading conditions for eRedCap	742
6.2.2.2	TDD	746
6.2.2.2.1	CQI Reporting definition under AWGN conditions.....	746
6.2.2.2.1.1	2Rx TDD FR1 periodic CQI reporting under AWGN conditions for both SA and NSA	746
6.2.2.2.1.2	2Rx TDD FR1 periodic CQI reporting with Table 3 under AWGN conditions for both SA and NSA.....	749
6.2.2.2.1.3	2Rx TDD FR1 CQI reporting for PCell on band with shared spectrum access under AWGN conditions for both SA and NSA	753
6.2.2.2.1.4	2Rx TDD FR1 periodic CQI reporting with Table 4 under AWGN conditions for both SA and NSA.....	757
6.2.2.2.1.5	2Rx TDD FR1 periodic CQI reporting under AWGN conditions for RedCap	760
6.2.2.2.1.6	2Rx TDD FR1 periodic CQI reporting under AWGN conditions for eRedCap	764
6.2.2.2.2	CQI reporting under fading conditions.....	766
6.2.2.2.2.1	2Rx TDD FR1 periodic wideband CQI reporting under fading conditions for both SA and NSA	766
6.2.2.2.2.2	2Rx TDD FR1 aperiodic subband CQI reporting under fading conditions for both SA and NSA	769
6.2.2.2.2.3	2Rx TDD FR1 Wideband CQI reporting with inter-cell interference for both SA and NSA ..773	
6.2.2.2.2.4	2Rx TDD FR1 periodic wideband CQI reporting under fading conditions for RedCap	776
6.2.3	4RX requirements	780
6.2.3.1	FDD.....	780
6.2.3.1.1	CQI reporting definition under AWGN conditions	780
6.2.3.1.1.1	4Rx FDD FR1 periodic CQI reporting under AWGN conditions for both SA and NSA	781
6.2.3.1.1.2	4Rx FDD FR1 periodic CQI reporting with Table 3 under AWGN conditions for both SA and NSA.....	784
6.2.3.1.1.3	4Rx FDD FR1 periodic CQI reporting with Table 4 under AWGN conditions for both SA and NSA.....	787
6.2.3.1.2	CQI reporting definition under fading conditions	790
6.2.3.1.2.1	4Rx FDD FR1 periodic wideband CQI reporting under fading conditions for both SA and NSA	790

6.2.3.1.2.2	4Rx FDD FR1 aperiodic subband CQI reporting under fading conditions for both SA and NSA	792
6.2.3.1.2.3	4Rx FDD FR1 Wideband CQI reporting with inter-cell interference for both SA and NSA...	795
6.2.3.2	TDD	798
6.2.3.2.1	CQI reporting definition under AWGN conditions	798
6.2.3.2.1.1	4Rx TDD FR1 periodic CQI reporting under AWGN conditions for both SA and NSA	798
6.2.3.2.1.2	4Rx TDD FR1 periodic CQI reporting with Table 3 under AWGN conditions for both SA and NSA.....	801
6.2.3.2.1.3	4Rx TDD FR1 CQI reporting for PCell on band with shared spectrum access under AWGN conditions for both SA and NSA	804
6.2.3.2.1.4	4Rx TDD FR1 periodic CQI reporting with Table 4 under AWGN conditions for both SA and NSA.....	808
6.2.3.2.2	CQI reporting under fading conditions.....	811
6.2.3.2.2.1	4Rx TDD FR1 periodic wideband CQI reporting under fading conditions for both SA and NSA	811
6.2.3.2.2.2	4Rx TDD FR1 aperiodic subband CQI reporting under fading conditions for both SA and NSA	814
6.2.3.2.2.3	4Rx TDD FR1 Wideband CQI reporting with inter-cell interference for both SA and NSA ..	816
6.2.4	8RX requirements	819
6.2.4.1	FFS	819
6.2.4.2	TDD	819
6.2.4.2.1	CQI reporting definition under AWGN conditions	819
6.2.4.2.1.1	8Rx TDD FR1 periodic CQI reporting under AWGN conditions for both SA and NSA	820
6.2A	Reporting of Channel Quality Indicator (CQI) for CA.....	823
6.2A.1	General.....	823
6.2A.2	1RX requirements	823
6.2A.3	2RX and 4RX requirements.....	823
6.2A.3.1	CQI reporting definition under AWGN conditions.....	823
6.2A.3.1.0	Minimum requirement for periodic CQI reporting.....	823
6.2A.3.1.1	CQI reporting accuracy under AWGN conditions for CA (2DL CA).....	826
6.2A.3.1.1_1	2Rx FR1 CQI reporting under AWGN for Scell on band with shared spectrum access for CA (2DLCA)	830
6.2A.3.1.2	CQI reporting accuracy under AWGN conditions for CA (3DL CA).....	836
6.2A.3.1.3	CQI reporting accuracy under AWGN conditions for CA (4DL CA).....	837
6.2A.3.1.4	CQI reporting accuracy under AWGN conditions for CA (5DL CA).....	838
6.2A.3.1.5	CQI reporting accuracy under AWGN conditions for CA (6DL CA).....	839
6.2A.4	4RX requirements	840
6.2A.4.1	CQI reporting definition under AWGN conditions.....	840
6.2A.4.1.1	4Rx FR1 CQI reporting under AWGN for Scell on band with shared spectrum access for CA (2DLCA)	840
6.3	Reporting of Precoding Matrix Indicator (PMI).....	847
6.3.0	General.....	847
6.3.1	1RX requirements	847
6.3.1.1	FDD.....	847
6.3.1.1.1	1Rx FDD Single PMI with 4TX TypeI-SinglePanel Codebook for RedCap	847
6.3.1.1.2	1Rx FDD Single PMI with 4TX TypeI-SinglePanel Codebook for eRedCap.....	852
6.3.1.2	TDD	856
6.3.1.2.1	1Rx TDD Single PMI with 4TX TypeI-SinglePanel Codebook for RedCap	856
6.3.1.2.2	1Rx TDD Single PMI with 4TX TypeI-SinglePanel Codebook for eRedCap	860
6.3.2	2RX requirements	865
6.3.2.1	FDD.....	865
6.3.2.1.1	2Rx FDD FR1 Single PMI with 4TX TypeI-SinglePanel codebook for both SA and NSA	865
6.3.2.1.1_1	2Rx FDD FR1 Single PMI with 4Tx TypeI-SinglePanel codebook for RedCap	869
6.3.2.1.2	2Rx FDD FR1 Single PMI with 8TX TypeI-SinglePanel codebook for both SA and NSA	870
6.3.2.1.3	2Rx FDD FR1 Multiple PMI with 16Tx Type I – SinglePanel Codebook for both SA and NSA	875
6.3.2.1.4	2Rx FDD FR1 Single PMI with 32Tx Type1 - SinglePanel codebook for both SA and NSA.....	878
6.3.2.1.5	2Rx FDD FR1 Multiple PMI with 16Tx TypeII codebook for both SA and NSA.....	882
6.3.2.1.6	2Rx FDD FR1 Multiple PMI with 16Tx Enhanced TypeII codebook for both SA and NSA	886
6.3.2.1.7	2Rx FDD FR1 Single PMI with 8TX TypeI-SinglePanel codebook for Single-DCI based transmission scheme for both SA and NSA.....	890

6.3.2.1.8	2Rx FDD FR1 Multiple PMI with 16Tx Enhanced Type II codebook for predicted PMI for both SA and NSA	901
6.3.2.1.9	2Rx FDD FR1 Multiple PMI with 8 ports Enhanced Type II Codebook for CJT for both SA and NSA	906
6.3.2.1.10	2Rx FDD FR1 Single PMI with 4Tx TypeI-SinglePanel codebook for eRedCap.....	913
6.3.2.2	TDD	918
6.3.2.2.1	2Rx TDD FR1 Single PMI with 4Tx TypeI-SinglePanel codebook for both SA and NSA	918
6.3.2.2.2	2Rx TDD FR1 Single PMI with 8Tx TypeI-SinglePanel codebook for both SA and NSA	923
6.3.2.2.3	2Rx TDD FR1 Multiple PMI with 16Tx Type1 - SinglePanel codebook for both SA and NSA ..	927
6.3.2.2.4	2Rx TDD FR1 Single PMI with 32Tx Type1 - SinglePanel codebook for both SA and NSA	931
6.3.2.2.5	2Rx TDD FR1 Multiple PMI with 16Tx TypeII codebook for both SA and NSA.....	935
6.3.2.2.6	2Rx TDD FR1 Multiple PMI with 16Tx Enhanced TypeII codebook for both SA and NSA	938
6.3.2.2.7	2Rx TDD Single PMI with 4Tx TypeI-SinglePanel Codebook for RedCap	942
6.3.2.2.8	2Rx TDD FR1 Single PMI with 8Tx TypeI-SinglePanel Codebook for Single-DCI based transmission scheme for both SA and NSA.....	947
6.3.2.2.9	2Rx TDD FR1 Multiple PMI with 16Tx Enhanced Type II codebook for predicted PMI.....	958
6.3.2.2.10	2Rx TDD Single PMI with 4Tx TypeI-SinglePanel Codebook for eRedCap	962
6.3.3	4RX requirements	967
6.3.3.1	FDD.....	967
6.3.3.1.1	4Rx FDD FR1 Single PMI with 4Tx TypeI-SinglePanel codebook for both SA and NSA	967
6.3.3.1.2	4Rx FDD FR1 Single PMI with 8Tx TypeI-SinglePanel codebook for both SA and NSA	972
6.3.3.1.3	4Rx FDD FR1 Multiple PMI with 16Tx Type I – SinglePanel Codebook for both SA and NSA	976
6.3.3.1.4	4Rx FDD FR1 Single PMI with 32Tx Type1 - SinglePanel codebook for both SA and NSA.....	980
6.3.3.1.5	4Rx FDD FR1 Multiple PMI with 16Tx TypeII codebook for both SA and NSA.....	984
6.3.3.1.6	4Rx FDD FR1 Multiple PMI with 16Tx Enhanced TypeII codebook for both SA and NSA	988
6.3.3.1.7	4Rx FDD FR1 Single PMI with 8 ports TypeI-SinglePanel Codebook for Single-DCI based transmission scheme	992
6.3.3.1.9	4Rx FDD FR1 Multiple PMI with 8 ports Enhanced Type II Codebook for CJT for both SA and NSA	1000
6.3.3.2	TDD	1004
6.3.3.2.1	4Rx TDD FR1 Single PMI with 4Tx TypeI-SinglePanel codebook for both SA and NSA	1004
6.3.3.2.2	4Rx TDD FR1 Single PMI with 8Tx TypeI-SinglePanel codebook for both SA and NSA	1009
6.3.3.2.3	4Rx TDD FR1 Multiple PMI with 16Tx Type1 - SinglePanel codebook for both SA and NSA ..	1013
6.3.3.2.4	4Rx TDD FR1 Single PMI with 32Tx Type1 - SinglePanel codebook for both SA and NSA ..	1017
6.3.3.2.5	4Rx TDD FR1 Multiple PMI with 16Tx TypeII codebook for both SA and NSA.....	1021
6.3.3.2.6	4Rx TDD FR1 Multiple PMI with 16Tx Enhanced TypeII codebook for both SA and NSA	1025
6.3.3.2.7	4Rx TDD FR1 Single PMI with 8 ports TypeI-SinglePanel Codebook for Single-DCI based transmission scheme	1029
6.4	Reporting of Rank Indicator (RI)	1033
6.4.1	1RX requirements (Void)	1033
6.4.2	2RX requirements	1033
6.4.2.1	FDD.....	1033
6.4.2.1_1	2Rx FDD FR1 RI reporting for both SA and NSA.....	1033
6.4.2.1.1	2Rx FDD FR1 RI reporting for RedCap.....	1037
6.4.2.2	TDD	1041
6.4.2.2_1	2Rx TDD FR1 RI reporting for both SA and NSA	1041
6.4.2.2.1	2Rx TDD FR1 RI reporting for RedCap	1046
6.4.3	4RX requirements	1050
6.4.3.1	FDD.....	1050
6.4.3.1_1	4Rx FDD FR1 RI reporting for both SA and NSA.....	1050
6.4.3.2	TDD	1054
6.4.3.2_1	4Rx TDD FR1 RI reporting for both SA and NSA	1054
7	Demodulation performance requirements (Radiated requirements)	1059
7.1	General	1059
7.1.1	Applicability of requirements	1059
7.1.1.1	General	1059
7.1.1.2	Applicability of requirements for different number of RX antenna ports	1059
7.1.1.3	Applicability of requirements for optional UE features	1059
7.1.1.4	Applicability of requirements for mandatory UE features with capability signaling	1060
7.1.1.5	Applicability of CA requirements	1060