

ETSI TS 145 005 V7.26.0 (2014-01)



**Digital cellular telecommunications system (Phase 2+);
Radio transmission and reception
(3GPP TS 45.005 version 7.26.0 Release 7)**

Document Preview

[ETSI TS 145 005 V7.26.0 \(2014-01\)](https://standards.iteh.ai/catalog/standards/etsi/16f54684-fc8d-4248-800f-cc09c1139843/etsi-ts-145-005-v7-26-0-2014-01)

<https://standards.iteh.ai/catalog/standards/etsi/16f54684-fc8d-4248-800f-cc09c1139843/etsi-ts-145-005-v7-26-0-2014-01>



ReferenceRTS/TSGG-0145005v7q0

KeywordsGSM

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

(<https://standards.iteh.ai>)
Document Preview

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2014.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

iTeh Standards (<https://standards.iteh.ai>) Document Preview

[ETSI TS 145 005 V7.26.0 \(2014-01\)](https://standards.iteh.ai/catalog/standards/etsi/16f54684-fc8d-4248-800f-cc09c1139843/etsi-ts-145-005-v7-26-0-2014-01)

<https://standards.iteh.ai/catalog/standards/etsi/16f54684-fc8d-4248-800f-cc09c1139843/etsi-ts-145-005-v7-26-0-2014-01>

Contents

Intellectual Property Rights	2
Foreword.....	2
Foreword.....	7
1 Scope	8
1.1 References	8
1.2 Abbreviations	10
2 Frequency bands and channel arrangement.....	10
3 Reference configuration	13
4 Transmitter characteristics	13
4.1 Output power.....	13
4.1.1 Mobile Station	13
4.1.2 Base station.....	18
4.1.2.1 Additional requirements for PCS 1 900 and MXM 1900 Base stations.....	19
4.1.2.2 Additional requirements for GSM 850 and MXM 850 Base stations	19
4.1.2.3 Additional requirements for GSM 700 Base stations.....	19
4.2 Output RF spectrum	19
4.2.1 Spectrum due to the modulation and wide band noise.....	19
4.2.2 Spectrum due to switching transients	25
4.3 Spurious emissions	26
4.3.1 Principle of the specification	27
4.3.2 Base Transceiver Station	27
4.3.2.1 General requirements	27
4.3.2.2 Additional requirements for co-existence with GSM systems on other frequency bands	28
4.3.2.3 Additional requirements for co-existence with 3 G	29
4.3.3 Mobile Station	29
4.3.3.1 Mobile Station GSM 400, T-GSM 810, GSM 900 and DCS 1 800	29
4.3.3.2 Mobile Station GSM 700, GSM 850 and PCS 1 900.....	30
4.4 Radio frequency tolerance.....	31
4.5 Output level dynamic operation	31
4.5.1 Base Transceiver Station	31
4.5.2 Mobile Station	31
4.6 Modulation accuracy	32
4.6.1 GMSK modulation.....	32
4.6.2 QPSK, 8-PSK, 16-QAM and 32-QAM modulations	32
4.6.2.1 RMS EVM	33
4.6.2.2 Origin Offset Suppression.....	33
4.6.2.3 Peak EVM.....	34
4.6.2.4 95:th percentile.....	34
4.7 Intermodulation attenuation.....	34
4.7.1 Base transceiver station	34
4.7.2 Intra BTS intermodulation attenuation	34
4.7.2.1 GSM 400, GSM 900, DCS 1800.....	34
4.7.2.2 MXM 850 and MXM 1900.....	34
4.7.2.3 GSM 700, GSM 850 and PCS 1900.....	35
4.7.3 Void	35
4.7.4 Mobile PBX (GSM 900 only).....	35
5 Receiver characteristics	35
5.1 Blocking characteristics	36
5.2 AM suppression characteristics	40
5.3 Intermodulation characteristics	40
5.4 Spurious emissions	41
6 Transmitter/receiver performance	41

6.1	Nominal Error Rates (NER)	42
6.1.1	GMSK modulation	42
6.1.2	QPSK/8-PSK modulation	42
6.1.3	16-QAM/32-QAM modulation	43
6.2	Reference sensitivity level	44
6.3	Reference interference level	49
6.4	Erroneous frame indication performance	52
6.5	Random access and paging performance at high input levels	53
6.6	Frequency hopping performance under interference conditions	53
6.7	Incremental Redundancy Performance for EGPRS and EGPRS2 MS	54
Annex A (informative): Spectrum characteristics (spectrum due to the modulation)		117
Annex B (normative): Transmitted power level versus time		125
Annex C (normative): Propagation conditions		130
C.1	Simple wideband propagation model	130
C.2	Doppler spectrum types	130
C.3	Propagation models	131
C.3.1	Typical case for rural area (RAx): (6 tap setting)	131
C.3.2	Typical case for hilly terrain (HTx): (12 tap setting)	131
C.3.3	Typical case for urban area (TUx): (12 tap setting)	132
C.3.4	Profile for equalization test (EQx): (6 tap setting)	132
C.3.5	Typical case for very small cells (Tlx): (2 tap setting)	132
Annex D (normative): Environmental conditions		133
D.1	General	133
D.2	Environmental requirements for the MSs	133
D.2.1	Temperature (GSM 400, GSM 900 and DCS 1 800)	133
D.2.1.1	Environmental Conditions (PCS 1 900, GSM 850 and GSM 700)	133
D.2.2	Voltage	133
D.2.3	Vibration (GSM 400, GSM 900 and DCS 1 800)	134
D.2.3.1	Vibration (PCS 1 900, GSM 850 and GSM 700)	134
D.3	Environmental requirements for the BSS equipment	134
D.3.1	Environmental requirements for the BSS equipment	135
Annex E (normative): Repeater characteristics		136
E.1	Introduction	136
E.2	Spurious emissions	136
E.3	Intermodulation products	137
E.4	Out of band gain	137
E.5	Frequency error and modulation accuracy	137
E.5.1	Frequency error	137
E.5.2	Modulation accuracy at GMSK modulation	137
E.5.3	Modulation accuracy at 8-PSK, 16-QAM, 32-QAM and QPSK modulation	138
Annex F (normative): Antenna Feeder Loss Compensator Characteristics (GSM 400, GSM 900 and DCS 1800)		139
F.1	Introduction	139
F.2	Transmitting path	139
F.2.1	Maximum output power	139
F.2.2	Gain	140
F.2.3	Burst transmission characteristics	140
F.2.4	Phase error	140
F.2.5	Frequency error	141
F.2.6	Group delay	141
F.2.7	Spurious emissions	141

F.2.8	VSWR	142
F.2.9	Stability	142
F.3	Receiving path.....	142
F.3.1	Gain	142
F.3.2	Noise figure	142
F.3.3	Group delay	142
F.3.4	Intermodulation performance	142
F.3.5	VSWR	142
F.3.6	Stability	142
F.4	Guidelines (informative)	142
Annex G (normative): Calculation of Error Vector Magnitude		144
Annex H (normative): Requirements on Location Measurement Unit		146
H.1	TOA LMU Requirements.....	146
H.1.1	Void.....	146
H.1.2	LMU characteristics	146
H.1.2.1	Blocking characteristics	146
H.1.2.2	AM suppression characteristics	146
H.1.2.3	Intermodulation characteristics	147
H.1.2.4	Spurious emissions	147
H.1.3	Time-of-Arrival Measurement Performance	147
H.1.3.1	Sensitivity Performance	147
H.1.3.2	Interference Performance	148
H.1.3.3	Multipath Performance	149
H.1.4	Radio Interface Timing Measurement Performance.....	149
H.2	E-OTD LMU Requirements	149
H.2.1	LMU Characteristics	149
H.2.1.1	Blocking characteristics	150
H.2.1.2	AM suppression characteristics	150
H.2.1.3	Intermodulation characteristics	150
H.2.2	Sensitivity and Interference Performance.....	150
H.2.2.1	Sensitivity Performance	150
H.2.2.2	Interference Performance	151
H.2.2.3	Multipath Performance	151
Annex I (normative): E-OTD Mobile Station Requirements.....		153
I.1	Introduction	153
I.2	Sensitivity and Interference Performance	153
I.2.1	Sensitivity Performance	153
I.2.2	Interference Performance	154
I.2.3	Multipath Performance.....	154
Annex J (informative): Guidance on the Usage of Dynamic ARFCN Mapping		155
J.1	Introduction	155
J.2	Dynamic allocation of GSM 400, GSM 800, GSM 900, DCS 1800 and PCS 1900 ARFCNs.....	155
J.3	Controlling changes in dynamic mapping.....	155
Annex K (normative): Reference TFCs for FLO		157
Annex L (normative): Reference Test Scenarios for DARP		159
Annex M (normative): Minimum Performance Requirements for Assisted Global Positioning System (A-GPS)		161
M.1	General	161
M.1.1	Abbreviations	161
M.1.2	Measurement parameters.....	161
M.1.2.1	MS based A-GPS measurement parameters	161
M.1.2.2	MS assisted A-GPS measurement parameters	161

M.1.3	Response time	161
M.1.4	Time assistance	161
M.1.4.1	Use of fine time assistance.....	162
M.1.4.2	2D position error.....	162
M.2	A-GPS minimum performance requirements	162
M.2.1	Sensitivity.....	162
M.2.1.1	Coarse time assistance	162
M.2.1.1.1	Minimum Requirements (Coarse time assistance).....	163
M.2.1.2	Fine time assistance	163
M.2.1.2.1	Minimum Requirements (Fine time assistance)	163
M.2.2	Nominal Accuracy.....	163
M.2.2.1	Minimum requirements (nominal accuracy).....	164
M.2.3	Dynamic Range	164
M.2.3.1	Minimum requirements (dynamic range)	164
M.2.4	Multi-Path scenario	164
M.2.4.1	Minimum Requirements (multi-path scenario).....	165
M.2.5	Moving scenario and periodic location	165
M.2.5.1	Minimum Requirements (moving scenario and periodic location).....	166
M.3	Test conditions	166
M.3.1	General	166
M.3.1.1	Parameter values.....	166
M.3.1.2	Time assistance.....	167
M.3.1.3	GPS Reference Time	167
M.3.1.4	Reference and MS locations	167
M.3.1.5	Satellite constellation and assistance data.....	167
M.3.1.6	Atmospheric delays.....	167
M.3.1.7	GSM Frequency and frequency error.....	168
M.3.1.8	Information elements	168
M.3.1.9	GPS signals.....	168
M.3.1.10	RESET MS POSITIONING STORED INFORMATION Message	168
M.4	Propagation Conditions	168
M.4.1	Static propagation conditions	168
M.4.2	Multi-path Case G1	168
M.5	Measurement sequence chart.....	169
M.5.1	General	169
M.5.2	MS Based A-GPS Measurement Sequence Chart	169
M.5.3	MS Assisted A-GPS Measurement Sequence Chart	170
M.6	Assistance data required for testing.....	171
M.6.1	Introduction	171
M.6.2	Information elements required for MS-based.....	171
M.6.3	Information elements available for MS-assisted	172
M.7	Converting MS-assisted measurement reports into position estimates	174
M.7.1	Introduction	174
M.7.2	MS measurement reports.....	174
M.7.3	Weighted Least Squares (WLS) position solution.....	175
Annex N (normative): Reference Test Scenarios for DARP Phase II (MSRD).....		177
N.1	Interferer configurations.....	177
N.2	Correlation and antenna gain imbalance.....	178
N.3	Testing MSRD terminal conformance to legacy requirements.....	179
Annex O (informative): Change history		181
History		189