



Edition 7.0 2025-07

# INTERNATIONAL STANDARD

INTERNATIONAL SPECIAL COMMITTEE ON RADIO INTERFERENCE

Vehicles, boats and devices with internal combustion engines or traction batteries – Radio disturbance characteristics – Limits and methods of measurement for the protection of off-board receivers

## **Document Preview**

CISPR 12:2025

https://standards.iteh.ai/catalog/standards/iec/516d70bd-b7c0-4cd0-9379-351db00f9f1b/cispr-12-2025



# THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2025 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat Tel.: +41 22 919 02 11

3, rue de Varembé info@iec.ch CH-1211 Geneva 20 www.iec.ch

Switzerland

#### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

#### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

#### IEC publications search -

#### webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

**IEC Just Published - webstore.iec.ch/justpublished**Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

## IEC Customer Service Centre - webstore.iec.ch/csc If you wish to give us your feedback on this publication or

need further assistance, please contact the Customer Service Centre: sales@iec.ch.

#### IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

#### Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

Preview

#### CISPR 12:2025

https://standards.iteh.ai/catalog/standards/iec/516d70bd-b7c0-4cd0-9379-351db00f9f1b/cispr-12-2026

## CONTENTS

FC	FOREWORD6				
IN	INTRODUCTION8				
1	Scop	e	9		
2	Norm	native references	.10		
3	Term	is, definitions and abbreviated terms	.11		
	3.1	Terms and definitions			
	3.2	Abbreviated terms			
4		s of radiated disturbance			
•	4.1	General			
	4.2	Group definitions			
	4.3	Determination of conformance of the vehicle, boat and device with the limits			
	4.4	Peak and quasi-peak detector limits			
	4.5	Average detector limit			
5		ods of measurement			
	5.1	Measuring instruments			
	5.1.1	· · · · · · · · · · · · · · · · · · ·			
	5.1.2	3			
	5.2	Measurement instrumentation uncertainty			
	5.3	Measuring site requirements	.24		
	5.3.1				
	5.3.2		.24		
	5.3.3				
	5.4	Test setup for measurement	.27		
	5.4.1	·			
	5.4.2				
	5.5	Test object conditions	.42		
	5.5.1				
	5.5.2	Vehicles and boats	.42		
	5.5.3	Devices	.44		
	5.6	Data collection	.44		
6	Meth	ods of checking for compliance with CISPR requirements	.45		
	6.1	General			
	6.2	Application of limit curves	.45		
	6.2.1	Measurements under dry conditions	.45		
	6.2.2	Measurements under wet conditions	.45		
		(normative) Procedure to determine an alternative emission limit for			
me	easuren	nents	.46		
Ar	inex B (	(informative) Measurement of the insertion loss of ignition noise suppressors	.47		
	B.1	Overview	.47		
	B.1.1	General	.47		
	B.1.2	CISPR box method (50/75 $\Omega$ laboratory method)	.47		
	B.1.3	· ·			
	B.2	Comparison of test methods	.47		
	B.2.1				
	B.2.2	Pield comparison method	.47		

B.3	CISPR box method (50/75 $\Omega$ laboratory method of measurement of insertion loss of ignition noise suppressors)	48
B.3.	1 General conditions and limitations of measurement	48
B.3.	2 Test procedure	48
B.3.	3 Test box construction	48
B.3.	4 Results	48
	(informative) Methods of measurement to determine the attenuation	50
	ristics of ignition noise suppressors for high voltage ignition systems	
C.1	General	
C.2	Recommended requirements for ignition noise suppressors	
C.3	Test set-up	
C.4	Test procedure	
C.5	Measuring spark-plugs without suppression elements	
C.6	Test setup examples	
C.6.		
C.6.	3 3 1 1 3 3 11	
C.6.		58
C.6.	suppressors	
C.6.	3	
Annex D	(informative) Applicability of CISPR 12	61
D.1	Flow chart	61
D.2	Example products that are in the scope of CISPR 121	63
D.2.	1 General	63
D.2.		63
D.2.	Boats and boat ICE(s) and EM(s)	63
D.2.		
D.3	Grouping <u>CISPR 12:2025</u>	64 -12-2025
Annex E artificial r	(normative) Direct current charging artificial networks (DC-charging-AN), mains networks (AMN) and asymmetric artificial networks (AAN)	67
E.1	General	67
E.2	Direct current charging artificial networks (DC-charging-AN)	67
E.3	Artificial mains networks (AMN)	69
E.4	Asymmetric artificial network (AAN)	69
E.4.	1 General	69
E.4.:	2 Signal and control port with symmetric lines	69
E.4.	Signal and control port with PLC (technology) on control pilot line	70
E.4.	4 Signal and control port with control pilot line	71
Annex F	(informative) Measurement instrumentation uncertainty	73
F.1	General	73
F.2	Uncertainty sources	73
F.3	Measurand	75
F.4	Input quantities to be considered	75
Annex G (informative) Uncertainty budgets for radiated disturbance measurement electric field strength		78
G.1	General	
G.2	Typical CISPR 12 uncertainty budgets	
G.3	Receiver's frequency step	
Annex H	(informative) Justification for the limits for an electric vehicle	

H.1 G	eneral	83
H.2 B	ackground	83
H.3 C	onsideration on the effect of radio receivers	83
H.4 C	alculation of limits	84
H.4.1	General	84
H.4.2	Electric vehicles in a driven mode	84
H.4.3	Electric vehicles in a charging mode	85
H.5 C	onclusion	
Annex I (info	ormative) Items under consideration	88
	eneral	
	requency range	
I.2.1	General considerations	
1.2.2	Testing between 1 GHz to 6 GHz	
	orrelation between OTS, ALSE and OATS measurements	
	alibration of antennas	
	harging mode for boats	
	ecessity for the use of artificial networks in the test setups	
	lectric vehicle limits	
1.7.1	Charging	
1.7.1	Driven mode	
	ynamic test modes	00
Dibilography	(https://standards.iteh.ai)	90
	Method of determination of conformance	
Figure 2 – 0	Quasi-peak limits at 10 m antenna distance	20
	Peak limits at 10 m antenna distance	
	Average limits at 10 m antenna distance	
	Measuring site (OTS) for vehicles, boats and devices	
•	Neasuring site (OTS) for boats	
_	Antenna height to measure emissions – Elevation view (vertical polarization	
-		28
Figure 8 – A	Antenna distance to measure emissions – Plan view (horizontal polarization	
shown)		29
Figure 9 – A	Antenna position for $N = 1$ (one antenna position to be used) – Horizontal	
polarization	shown	31
	Example antenna positions for $N = 2$ (multiple antenna positions to be	
used) – Hor	izontal polarization shown	31
	Example of test setup for vehicle with vehicle inlet located on vehicle side ode 1 or 2, AC powered, without communication)	34
	Example of test setup for vehicle with vehicle inlet located front or rear of arging mode 1 or 2, AC powered, without communication)	35
	Example of test setup for vehicle with vehicle inlet located on vehicle side ode 3 or mode 4, AC/DC powered, with communication)	38
Figure 14 –	Example of test setup for vehicle with vehicle inlet located front or rear of arging mode 3 or mode 4, AC/DC powered, with communication)	
•	Example of test setup for vehicle in charging mode through wireless power	
	Example of test setap for verifice in charging mode through wheless power	41
Figure A.1 -	- Calculation of the resulting gain reduction $X_{\sf dB}$	46

Figure B.1 – Test circuit	49
Figure B.2 – General arrangement of the test box	49
Figure B.3 – Details of the test box lid	50
Figure B.4 – Details of the test box	50
Figure B.5 – Straight spark-plug ignition noise suppressor (screened or unscreened)	50
Figure B.6 – Right-angle spark-plug ignition noise suppressor (screened or	=0
unscreened)	
Figure B.7 – Noise suppression spark-plug	
Figure B.8 – Resistive distributor brush	
Figure B.9 – Noise suppressor in distributor cap	
Figure B.10 – Noise suppression distributor rotor	
Figure B.11 – Noise suppression ignition cable (resistive or reactive)	
Figure C.2 – Test set-up, side view	
Figure C.3 – Pressure chamber with ventilation	
Figure C.4 – Top view of the set-up of a right-angle ignition noise suppressor for	50
distributors	57
Figure C.5 – Location of high voltage ignition components	58
Figure C.6 – Top view of the test set-up for distributor rotors	59
Figure C.7 – Side view of the test set-up for ready-to-use resistive ignition cables	60
Figure D.1 – Flowchart for the applicability of CISPR 12	62
Figure E.1 – Example of 5 μH / 50 Ω DC-charging-AN schematic	67
Figure E.2 – Characteristics of the DC-charging-AN impedance	68
Figure E.3 – Example of an AAN for signal and control port with symmetric lines (e.g.	
CAN) <u>CISPR 12:2025</u>	
Figure E.4 – Example of AAN circuit for signal and control port with PLC (technology) on control pilot	12-20 71
Figure E.5 – Example of AAN circuit for pilot line	
Figure F.1 – Typical sources of measurement instrumentation uncertainty	
Figure G.1 – Example of measurement for frequency step uncertainty evaluation for	
120 kHz bandwidth	82
Figure H.1 – Histogram – Peak to quasi-peak delta, EV driving mode	85
Figure H.2 – Histogram – Peak to quasi-peak delta, vehicle in AC or DC charging mode	86
Figure H.3 – Degradation to 12 dB SINAD (LO-VHF) from Mode 3 charging vs. CW noise	87
110136	01
Table 1 – Detection limits	18
Table 2 – Quasi-peak limits at 10 m antenna distance	
Table 3 – Peak limits at 10 m antenna distance	
Table 4 – Spectrum analyser parameters	
Table 5 – Scanning receiver parameters	
Table 6 – ICE operating speeds	43
Table C.1 – Limits	52

Table D.1 – Examples of products in the scope of CISPR 12 with their assignment to the groups	.65
Table E.1 – Magnitude of the DC-charging-AN impedance $Z_{PB}$	
Table F.1 – Input quantities to be considered for radiated disturbance measurements	.75
Table G.1 – Typical uncertainty budget – 3 m/10 m distance – Biconical antenna	.78
Table G.2 – Typical uncertainty budget – 3 m/10 m distance – Log-periodic antenna	.80

## iTeh Standards (https://standards.iteh.ai) Document Preview

CISPR 12:2025

https://standards.iteh.ai/catalog/standards/iec/516d70bd-b7c0-4cd0-9379-351db00f9f1b/cispr-12-2025