



INTERNATIONAL STANDARD

**Environmental testing -
Part 2-2: Tests - Test B: Dry heat**

Sample Document

get full document from standards.iteh.ai



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2025 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search -

webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD	3
INTRODUCTION	5
1 Scope	6
2 Normative references	6
3 Terms and definitions	6
4 Symbols	7
5 Application of tests for non-heat-dissipating specimens versus tests for heat-dissipating specimens	7
5.1 General	7
5.2 Ascertaining high or low air velocity in the test chamber	8
5.3 Temperature monitoring	9
5.4 Packaging	10
5.5 Background	10
6 Test descriptions	10
6.1 General	10
6.2 Severities	11
6.2.1 General	11
6.2.2 High conditioning temperature T_B	11
6.2.3 Exposure time t_1	11
6.3 Test Bb: Dry heat for non-heat-dissipating specimens	11
6.4 Test Bd: Dry heat for heat-dissipating specimens that are energized after initial temperature stabilization	13
6.5 Test Be: Dry heat for heat-dissipating specimens that are energized throughout the test	14
7 Testing procedure	15
7.1 General	15
7.2 Thermal radiation	15
7.3 Specimen with artificial cooling or heating	15
7.4 Mounting	15
7.5 Initial measurements	16
7.6 Preconditioning	16
7.7 Conditioning	16
7.8 Intermediate measurements	16
7.9 Final temperature ramp	16
7.10 Recovery	16
7.11 Final measurements	17
8 Information to be given in the relevant specification	17
9 Information to be given in the test report	18
Annex A (informative) Relationship of suffixes between Test A: Cold and Test B: Dry heat	19
Annex B (normative) Nomogram for the correction of the conditioning temperature	20
B.1 General	20
B.2 Determination of the corrected high conditioning temperature T_B'	20
B.2.1 General	20
B.2.2 Application of the graphical solution method	20
B.2.3 Application of the numerical solution method	22

B.2.4	Conditioning with the corrected conditioning temperature $T_{B'}$	23
B.2.5	Further adjustment of the corrected high conditioning temperature $T_{B'}$	24
B.3	Example of application of the nomogram.....	25
B.3.1	Example of test setup and specimen.....	25
B.3.2	Graphical solution method	25
B.3.3	Numerical solution method	27
Annex C (informative)	Advantages and disadvantages of available test procedures for heat-dissipating specimens.....	28
Bibliography	29
Figure 1	– Examples of temperature profiles of energized heat-dissipating specimens in test chambers with a) high air velocity and b) low air velocity.....	9
Figure 2	– Block diagram of the test procedures and applicable selection criteria of Test B: Dry heat.....	10
Figure 3	– Test Bb: Dry heat for non-heat-dissipating and non-operating specimens.....	12
Figure 4	– Test Bb: Dry heat for non-heat-dissipating, operating specimens	12
Figure 5	– Test Bd: Dry heat for heat-dissipating specimens that are energized after initial temperature stabilization	13
Figure 6	– Test Be: Dry heat for heat-dissipating specimens that are required to be energized throughout the test	14
Figure B.1	– Nomogram to determine the corrected conditioning temperature $T_{B'}$	21
Figure B.2	– a) Test Bd and b) Test Be with the corrected conditioning temperature $T_{B'}$	23
Figure B.3	– a) Test Bd and b) Test Be with the corrected conditioning temperature $T_{B'}$ and a second temperature adjustment	24
Figure B.4	– a) Test Bd and b) Test Be with a preliminary temperature below the corrected conditioning temperature $T_{B'}$ and a second temperature adjustment	25
Figure B.5	– Nomogram with example of application of the procedure.....	26
Table 1	– Preferred values for the high conditioning temperature $T_{B'}$	11
Table 2	– Preferred values for the exposure time t_1	11
Table A.1	– Relationship of suffixes between Test A: Cold, and Test B: Dry heat.....	19

INTERNATIONAL ELECTROTECHNICAL COMMISSION

Environmental testing - Part 2-2: Tests - Test B: Dry heat

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 60068-2-2 has been prepared by IEC technical committee 104: Environmental conditions, classification and methods of test. It is an International Standard.

This sixth edition cancels and replaces the fifth edition published in 2007. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) revision of the introduction and scope;
- b) inclusion of new figures and symbols for clarification purposes;
- c) clarification of the test procedure for ascertaining high or low air velocity in the test chamber;
- d) clarification of the requirements for measuring points around, on or in specimens;
- e) reintroduction of the nomogram procedure for the correction of the conditioning temperature when testing with high air velocity (Test Bd and Test Be);

- f) revision of the temperature tolerances of the test;
- g) revision of standardized requirements for the relevant specification and test report;
- h) inclusion of the advantages and disadvantages of the testing procedures.

The text of this International Standard is based on the following documents:

Draft	Report on voting
104/1108/FDIS	104/1128/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all the parts of the IEC 60068 series, under the general title *Environmental testing*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

INTRODUCTION

The working ranges and performance of equipment and machinery can be significantly affected or limited by ambient temperatures. The degree of this influence can depend on temperature distributions of the environment as well as temperatures on components of the device itself. In order to determine the existing degree of influence and to ensure that the device is suitably designed for its ambient conditions, tests are carried out with cold (IEC 60068-2-1) or dry heat, or both. During the test detailed in this document, it will be taken into account whether the tested device itself emits heat or not.

Reducing the air flow within the test chamber can be required to reduce the air velocity at heat-dissipating specimens. This can be achieved by using air baffles or adjusting the air flow of the test chamber. If the reduction of air velocity is not practical or possible due to the required test conditions, this document provides an alternative test procedure without the need for adjustable air flow as well as guidance on selecting the applicable test procedure.

Sample Document

get full document from standards.iteh.ai

1 Scope

This part of IEC 60068 specifies dry heat temperature tests that are applicable to non-heat-dissipating and heat-dissipating specimens, to determine the ability of components, equipment or other articles to be used, transported or stored at high temperature.

This document is applicable to energized as well as non-energized specimens that normally achieve temperature stability during the test. The specimens can be subject to test in packed condition (to simulate transportation and storage) or in unpacked condition (to simulate use).

This document does not specify tests to determine the impact of temperature changes on specimens.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60068-1, *Environmental testing - Part 1: General and guidance*

IEC 60068-5-2, *Environmental testing - Part 5-2: Guide to drafting of test methods - Terms and definitions*

IEC 60721 (all parts), *Classification of environmental conditions*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60068-1, IEC 60068-5-2 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at <https://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

3.1

low air velocity

velocity of conditioning airflow within a working space which is sufficient to maintain conditions but low enough so that the temperature at the relevant point or relevant points on the test specimen is not reduced by more than 5 K by the influence of the circulation of the air

Note 1 to entry: The relevant points to be considered are determined by the relevant test specification.

3.2

high air velocity

velocity of conditioning airflow within a working space, which, in order to maintain conditions, also reduces the temperature at the relevant point or relevant points on the test specimen by more than 5 K by the influence of the circulation of the air

4 Symbols

T_B	high conditioning temperature [°C]
$T_{B'}$	corrected high conditioning temperature (nomogram procedure) [°C]
T_{STD}	temperature of standard atmospheric conditions for measurement and tests (15 °C to 35 °C) [°C]
T_{Ca}	measured ambient temperature in the vicinity of the specimen, either in the test chamber or the laboratory air, without forced convection (see 5.2) [°C]
T_{Cb}	measured test chamber temperature with forced convection (see 5.2) [°C]
T_S	temperature of the energized specimen at the specified conditioning temperature [°C]
T_{Sa}	temperature of the energized specimen at the temperature of standard atmospheric conditions without forced convection (see 5.2) [°C]
T_{Sb}	temperature of the energized specimen at the temperature of standard atmospheric conditions with forced convection (see 5.2) [°C]
ΔT_S	temperature difference between the energized specimen and the air [K]
$\Delta T_{Sa/b}$	temperature difference between the energized specimen without forced convection (T_{Sa}) and with forced convection (T_{Sb}) at the temperature of standard atmospheric conditions [K]
dT_R	temperature change rate [K/min]
t_s	stabilization time of specimen temperature before exposure to the high conditioning temperature [min or h]
t_{s0}	stabilization time of specimen temperature after energizing [min or h]
t_1	exposure time of the specimen to the high conditioning temperature [h]

5 Application of tests for non-heat-dissipating specimens versus tests for heat-dissipating specimens

5.1 General

This test is subdivided as follows:

- Test Bb: Dry heat for non-heat-dissipating specimens;
- Test Bd: Dry heat for heat-dissipating specimens that are energized after initial temperature stabilization;
- Test Be: Dry heat for heat-dissipating specimens that are energized throughout the test.

A specimen, while energized, is considered to be heat-dissipating only if the hottest point on its surface or any other relevant point, measured in free air conditions (i.e. low air velocity circulation), is more than 5 K above the ambient temperature of the surrounding atmosphere after temperature stability has been reached (see IEC 60068-1).

NOTE 1 In some cases, for example for test specimens with air-permeable housings, the relevant measuring points can be located inside the external housing.

Tests of heat-dissipating and non-heat-dissipating specimens generally differ in the air velocity applied. Non-heat-dissipating specimens are typically tested at high air velocity to reduce the time required to reach temperature stability. Heat-dissipating specimens are generally tested at low air velocity to allow for the formation of local hotspots similar to those that would appear in installed applications. Annex A gives an overview of the relevant test conditions and shows the relationship of suffixes between Test A: Cold and Test B: Dry heat.